

FCC - TEST REPORT

Report Number	:	68.760.12.076.0)1	Date of Issue:	25 July 2012
Model	<u>:</u>	KT700VCI			
Product Type	<u>:</u>	Vehicle Diagnos	sis		
Applicant	<u>:</u>	Bosch Automoti	ve Diagno	stics Equipmen	t (Shenzhen) Limited
Address	:	5/F,A, Gardon C	City Cyber	Port, Nanhai Ro	oad No.1079,
		Nanshan Distric	t, Shenzhe	en518067 P.R.	China
Production Facility	:	Bosch Automoti	ve Diagno	stics Equipmen	t (Shenzhen) Limited
Address	<u>:</u>	5/F,A, Gardon C	City Cyber	Port, Nanhai Ro	oad No.1079,
		Nanshan Distric	t, Shenzhe	en518067 P.R.	China
Test Result	:	■ Positive	□ Negati	ve	
Total pages including Appendices		34			
прропаюсь		UT .			

Jiangsu TÜV Product Service Ltd. - Shenzhen Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

Jiangsu TÜV Product Service Ltd. - Shenzhen Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. Jiangsu TÜV Product Service Ltd. – Shenzhen Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from Jiangsu TÜV Product Service Ltd. – Shenzhen Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval



1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks	7
7	Technical Requirements	8 8 25
8	System Measurement Uncertainty	34



2 Details about the Test Laboratory

Details about the Test Laboratory

Test site1:

Jiangsu TÜV Product Service Ltd. - Shenzhen Branch Company name:

6th Floor, H Hall,

Century Craftwork Culture Square,

No. 4001, Fuqiang Road, Futian District 518048,

Shenzhen, P.R.C.

Telephone: 86 755 8828 6998 Fax: 86 755 8828 5299

Test site2:

Shenzhen Academy of Metrology & Quality Inspection Company name:

> Longzhu road, Nan Shan,

Shenzhen 518055, Guangdong, China

Telephone: 86 755 2694 1723 Fax: 86 755 2694 1545



3 Description of the Equipment Under Test

Description of the Equipment Under Test

Product: Vehicle Diagnosis

Model no.: KT700VCI

Brand Name: BOSCH

Options and accessories: NIL

Rating: 7-32VDC

Charged by external adapter FJ-SW1402800T: Adaptor Input: 100-240VAC, 50/60Hz, 1.5A Max

Adaptor Output: 14VDC, 2800mA

or charged by Lead-acid battery power sources used on vehicles

Description of the EUT: NIL

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	T61	-
Engine	IMSEOER	ME797	-



4 Summary of Test Standards

	Test Standards
FCC Part 15 Subpart B,	Unintentional Radiators
10-1-2011 Edition	



5 Summary of Test Results

Emission Tests					
FCC Part 15 Subpart B					
Test Condition	Pages	Tes	st Result		Test Site
		Pass	Fail	N/A	
Radiated Emission	8				Site 2
30MHz to 6000MHz					
Conducted Emission on AC 150kHz to 30MHz	25				Site 2



6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: WSO-KT700VCI complies with Section 15.107, 15.109 of the FCC Part 15, Subpart B Rules.

All the configurations of the product were tested and only the worst test results are listed in the report.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed
- ☐ Not Performed

The Equipment Under Test

- - Fulfills the general approval requirements.
- ☐ **Does not** fulfill the general approval requirements.

Sample Received Date: 18 July 2012

Testing Start Date: 20 July 2012

Testing End Date: 27 July 2012

- Jiangsu TÜV Product Service Ltd. - Shenzhen Branch -

Reviewed by:

Prepared by:

Tested by:

Ken Li **EMC Project Manager**

Cookies Bu **EMC Project Engineer**

Eric Gao **EMC Test Engineer**

Eno Gas



7 Emission Test Results


7.1 Radiated Emission Test 30MHz - 6000MHz

EUT: KT700VCI

Op Cond: Data transmitting via USB port

Vertical and horizontal, 30MHz-1GHz Test Spec:

Comment: AC 120V/60Hz





Radiated Emission Test 30MHz - 6000MHz

29 May 2011 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Data transmitting via USB port Operating mode

Test Specification Horizontal and Vertical, 30MHz-1GHz

Model No KT700VCI

 Frequency MHz	Horizontal dBµV/m	Limit dBµV/m	Margin dB
55.27	33.7	40.0	6.4
173.847	39.6	43.5	3.9


Frequency MHz	Vertical dBµV/m	Limit dBµV/m	Margin dB
43.607	36.4	40.0	3.6
53.326	33.2	40.0	6.8
173.847	36.5	43.5	7.0
191.342	36.3	43.5	7.2



EUT: KT700VCI

Op Cond: Data transmitting via USB port Test Spec: Vertical and horizontal, above 1GHz

Comment: AC 120V/60Hz





Radiated Emission Test 30MHz - 6000MHz

Date of test 29 May 2011

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode Data transmitting via USB port

Test Specification Horizontal and Vertical, above 1GHz

Model No KT700VCI

 Frequency	Horizontal	Limit	Margin
MHz	dBμV/m	dBµV/m	dB
1	1	/	

Frequency Vertical Limit Margin dBµV/m dBµV/m dB MHz




EUT: KT700VCI

Data transmitting via USB port Op Cond:

Test Spec: Vertical and horizontal, 30MHz-1GHz

Comment: **DC 12V**





Test Result Passed

Not Passed

Radiated Emission Test 30MHz - 6000MHz

Date of test 1 June 2011

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Data transmitting via USB port Operating mode

Test Specification Horizontal and Vertical, 30MHz-1GHz

Model No KT700VCI

	Frequency MHz	Horizontal dBμV/m	Limit dBµV/m	Margin dB
_	174.987	36.1	43.5	7.4
	200.015	31.6	43.5	11.9


Frequency MHz	Vertical dBµV/m	Limit dBµV/m	Margin dB
45.11	32.5	40.0	7.5
175.014	35.7	43.5	7.8
200.012	31.2	43.5	12.3



EUT: KT700VCI

Op Cond: Data transmitting via USB port Test Spec: Vertical and horizontal, above 1GHz

Comment: DC12V





Radiated Emission Test 30MHz - 6000MHz

Date of test 29 May 2011

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode Data transmitting via USB port

Test Specification Horizontal and Vertical, above 1GHz

Model No KT700VCI

Frequency	Horizontal	Limit	Margin
MHz	dBµV/m	dBµV/m	dB
 1	1	1	

Frequency Vertical Limit Margin dBµV/m dBµV/m dB MHz




EUT: KT700VCI

Op Cond: Data transmitting via RJ45 port

Test Spec: Vertical and horizontal

Comment: AC 120V/60Hz





Test Result Passed

Not Passed

Radiated Emission Test 30MHz - 6000MHz

29 May 2011 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Data transmitting via RJ45 port Operating mode

Test Specification Horizontal and Vertical, 30MHz-1GHz

Model No KT700VCI

Frequency MHz	Horizontal dBµV/m	Limit dBµV/m	Margin dB
44.813	34.8	40.0	5.2
175.011	36.4	43.5	7.1


 Frequency MHz	Vertical dBµV/m	Limit dBµV/m	Margin dB
175.014	37.8	43.5	5.7
94.148	33.8	43.5	9.7
224.388	36.1	46.0	9.9
249.659	37.8	46.0	8.2



EUT: KT700VCI

Op Cond: Data transmitting via RJ45 port Test Spec: Vertical and horizontal, above 1GHz

Comment: AC120/60Hz





Radiated Emission Test 30MHz - 6000MHz

Date of test 29 May 2011

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode Data transmitting via RJ45 port

Test Specification Horizontal and Vertical, above 1GHz

Model No KT700VCI

 Frequency	Horizontal	Limit	Margin
MHz	dBµV/m	dBµV/m	dB
1	/	/	

Frequency Vertical Limit Margin dBµV/m dBµV/m dB MHz




EUT: KT700VCI

Op Cond: Data transmitting via RJ45 port

Test Spec: Vertical and horizontal

Comment: DC12V





Radiated Emission Test 30MHz - 6000MHz

29 May 2011 Date of test

Test requirement FCC Part 15 Subpart B

FCC Part 15 Subpart B Test method

Data transmitting via RJ45 port Operating mode

Test Specification Horizontal and Vertical

Model No KT700VCI

Frequency	Horizontal	Limit	Margin
MHz	dBµV/m	dBµV/m	dB
175.014	37.7	43.5	


-	Frequency MHz	Vertical dBµV/m	Limit dBµV/m	Margin dB
	175.01	36.4	43.5	7.1
	225.01	36.2	43.5	7.3
	250.01	45.9	46.0	0.1



EUT: KT700VCI

Op Cond: Data transmitting via RJ45 port Test Spec: Vertical and horizontal, above 1GHz

Comment: DC12V





Radiated Emission Test 30MHz - 6000MHz

Date of test 29 May 2011

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode Data transmitting via RJ45 port

Test Specification Horizontal and Vertical, above 1GHz

Model No KT700VCI

 Frequency	Horizontal	Limit	Margin
MHz	dBµV/m	dBµV/m	dB
1	/	/	

Frequency Vertical Limit Margin dBµV/m dBµV/m dB MHz



Test Equipment List

Radiated Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESI26	838786/013	2013-01-20
Bilog Antenna	Chase	CBL6112B	2591	2013-01-20
Horn Antenna	Rohde & Schwarz	HF906	100014	2013-01-20
3m Semi-anechoic chamber	Albatross Project	9X6X6		2012-10-09




7.2 Conducted Emission Test 150kHz - 30MHz

EUT: KT700VCI

USB

Op Cond: Test Spec: Power line, Live Comment: AC 120V/60Hz





Conducted Emission Test 150kHz - 30MHz

Date of test 29 May 2011

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode **USB**

Tested on Power Line, Live

Model No KT700VCI

> **QP Limit Frequency QP Test result** Margin MHz $dB\mu V$ dΒμV dB

Frequency AV Test result AV Limit Margin MHz dBµV dΒμV dB




Conducted Emission Test 150kHz - 30MHz

EUT: KT700VCI

USB

Op Cond: Test Spec: Power line, Neutral AC 120V/60Hz Comment:





Conducted Emission Test 150kHz - 30MHz

Date of test 29 May 2011

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode **USB**

Tested on Power Line, Neutral

Model No KT700VCI

> **QP Limit Frequency QP Test result** Margin MHz $dB\mu V$ dΒμV dB

Frequency AV Test result AV Limit Margin MHz dBµV dΒμV dB




Conducted Emission Test 150kHz - 30MHz

EUT: KT700VCI

Op Cond: Test Spec: RJ45 data transmitting

Power line, Live AC 120V/60Hz Comment:





Test Result

Passed

Not Passed

Conducted Emission Test 150kHz - 30MHz

Date of test 29 May 2011

Test requirement: FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode RJ45 data transmitting

Tested on Power Line, Live

Model No KT700VCI

Frequency	QP Test result	QP Limit	Margin
MHz	dBμV	dBμV	dB
- /	1	1	1


Frequency **AV Test result AV Limit** Margin MHz dBµV dB_µV dB



Conducted Emission Test 150kHz - 30MHz

EUT: KT700VCI

Op Cond: RJ45 data transmitting Test Spec: Power line, Neutral AC 120V/60Hz Comment:





Conducted Emission Test 150kHz - 30MHz

Date of test 29 May 2011

Test requirement FCC Part 15 Subpart B

Test method FCC Part 15 Subpart B

Operating mode RJ45 data transmitting

Tested on Power Line, Neutral

Model No KT700VCI

> **QP Limit Frequency QP Test result** Margin MHz $dB\mu V$ dΒμV dB

Frequency AV Test result AV Limit Margin MHz dBµV dB_µV dB



Test Equipment List

Conducted Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESCS30	100003	2013-01-20
AMN	Rohde & Schwarz	ESH3-Z5	100229	2013-01-20
AMN	Rohde & Schwarz	ENV216	100042	2013-01-20



8 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty

	Items	Extended Uncertainty
RE	Field strength (dBμV/m)	U=4.60dB (30MHz-25GHz)
CE	Disturbance Voltage (dBμV)	U=3.50dB(150KHz-30MHz)