


# FCC Test Report


APPLICANT : Brightstar Corporation  
EQUIPMENT : Mobile phone  
BRAND NAME : AVVIO, PULSARE, WUPA  
MODEL NAME : AVVIO 794, AVVIO 794S, PULSARE  
794, PULSARE 794S, WUPA 794,  
WUPA 794S  
FCC ID : WVBA794X  
STANDARD : FCC 47 CFR FCC Part 15 Subpart B  
CLASSIFICATION : Certification

The product was received on Sep. 18, 2014 and testing was completed on Oct. 13, 2014. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2003 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



---

Reviewed by: Louis Wu / Manager

---

Approved by: Jones Tsai / Manager

**SPORTON INTERNATIONAL (SHENZHEN) INC.**

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District,  
Shenzhen, Guangdong, P.R.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY .....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1. GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1. Applicant.....	5
1.2. Manufacturer .....	5
1.3. Product Feature of Equipment Under Test .....	5
1.4. Product Specification subjective to this standard.....	6
1.5. Modification of EUT .....	6
1.6. Test Location.....	7
1.7. Applicable Standards .....	7
<b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1. Test Mode .....	8
2.2. Connection Diagram of Test System .....	10
2.3. Support Unit used in test configuration and system.....	11
2.4. EUT Operation Test Setup .....	12
<b>3. TEST RESULT .....</b>	<b>13</b>
3.1. Test of AC Conducted Emission Measurement .....	13
3.2. Test of Radiated Emission Measurement .....	20
<b>4. LIST OF MEASURING EQUIPMENT .....</b>	<b>24</b>
<b>5. UNCERTAINTY OF EVALUATION .....</b>	<b>25</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC491805	Rev. 01	Initial issue of report	Oct. 24, 2014



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 1.74 dB at 0.50 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 2.01 dB at 35.820 MHz for Quasi-Peak

# 1. General Description

## 1.1. Applicant

**Brightstar Corporation**

9725 NW 117th Ave., Miami, Florida, FL 33178, United States

## 1.2. Manufacturer

**KCMobile Co.,Ltd.**

#1305-1, Kolon Digital Tower Villant II , 31, Digital-ro 30-gil, Guro-Gu, Seoul, KOREA ( 152-727)

## 1.3. Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Mobile phone
<b>Brand Name</b>	Avvio, PULSARE, WUPA
<b>Model Name</b>	Avvio 794, Avvio 794S, Pulsare 794, Pulsare 794S, WUPA 794, WUPA 794S
<b>FCC ID</b>	WVBA794X
<b>EUT supports Radios application</b>	GSM/GPRS/EGPRS/WCDMA/HSPA WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
<b>HW Version</b>	V1.01
<b>SW Version</b>	M7207.PULSARE.KC794.W.V01.01.20140821
<b>EUT Stage</b>	Production Unit

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are six types of EUT for this project. The differences between them are summary below:

Sample List	Model name	Brand name	SIM Slots
Sample 1	Avvio 794	Avvio	1
Sample 2	Avvio 794S	Avvio	2
Sample 3	PULSARE 794	PULSARE	1
Sample 4	PULSARE 794S	PULSARE	2
Sample 5	WUPA 794	WUPA	1
Sample 6	WUPA 794S	WUPA	2

These models are identical on hardware except the SIM slots. The different model with different brand is for market purpose.

## 1.4. Product Specification subjective to this standard

Product Specification subjective to this standard	
<b>Tx Frequency</b>	GSM850 : 824.2 MHz ~ 848.8 MHz GSM1900 : 1850.2 MHz ~ 1909.8MHz WCDMA Band V : 826.4 MHz ~ 846.6 MHz WCDMA Band II : 1852.4 MHz ~ 1907.6 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
<b>Rx Frequency</b>	GSM850 : 869.2 MHz ~ 893.8 MHz GSM1900 : 1930.2 MHz ~ 1989.8 MHz WCDMA Band V : 871.4 MHz ~ 891.6 MHz WCDMA Band II : 1932.4 MHz ~ 1987.6 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
<b>Antenna Type</b>	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM ) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK

## 1.5. Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6. Test Location

<b>Test Site</b>	SPORTON INTERNATIONAL (SHENZHEN) INC.	
<b>Test Site Location</b>	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	CO01-SZ	831040

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.	
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Registration No.</b>
	03CH01-KS	149928

## 1.7. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B
- ♦ ANSI C63.4-2003

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition		
		EMI AC	EMI RE<1G	EMI RE≥1G
1.	Charging Mode (EUT with adapter)	☒	☒	Note 1
2.	Data application transferred mode (EUT connected with notebook)	☒	☒	☒

**Abbreviations:**

- EMI AC: AC conducted emissions
- EMI RE ≥ 1G: EUT radiated emissions ≥ 1GHz
- EMI RE < 1G: EUT radiated emissions < 1GHz


**Note 1:** Testing for this mode is not required or not the worst case.

**Remark:** For signal above 1GHz, the worst case was test item 2.




Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera for SIM 1<Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 for SIM 2<Fig.1> Mode 3: WCDMA Band V + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + GPS Rx for SIM 1<Fig.2>
Radiated Emissions < 1GHz	1/2	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + USB Cable (Charging from Adapter) + Earphone + Camera for SIM 1<Fig.1> Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 for SIM 2<Fig.1> Mode 3: WCDMA Band V + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + GPS Rx for SIM 1<Fig.2>
Radiated Emissions ≥ 1GHz	2	Mode 1: WCDMA Band V + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + GPS Rx for SIM 1<Fig.2>
<b>Remark:</b> <ol style="list-style-type: none"> <li>The worst case of AC is mode 2, and the USB Link mode of AC is mode 3, the test data of these modes are reported.</li> <li>The worst case of RE &lt; 1G is mode 3; only the test data of this mode was reported.</li> <li>Link with Notebook means data application transferred mode between EUT and Notebook.</li> </ol>		

## 2.2. Connection Diagram of Test System



<Fig.1>



## 2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMW 500	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Nokia	BH-108	PYAHS-107W	N/A	N/A
4.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
5.	GPS Station	T&E	GS-50	N/A	N/A	Unshielded, 1.8 m
6.	WLAN AP	ASUSTek	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 2.7m
7.	Bluetooth Earphone	Lenovo	LBH301	N/A	N/A	N/A
8.	Bluetooth Earphone	Hawk	B690	03HKB690	N/A	N/A
9.	Notebook	Lenovo	G480	FCC DoC	N/A	AC I/P: Unshielded, 1.2m DC O/P: Shielded, 1.8 m
10.	iPod	Apple	A1199	FCC DoC	Shielded, 1.2 m	N/A
11.	WLAN AP	D-Link	DIR-815	KA2DIR815A1	N/A	Unshielded, 1.8 m
12.	iPod nano 8GB	Apple	MC690 ZP/A	FCC DoC	Shielded, 1.2 m	N/A

## **2.4. EUT Operation Test Setup**

The EUT was in GSM or WCDMA idle mode during the testing. The EUT was synchronized to the BCCH, and was in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Laptop and EUT via USB cable.
2. Execute "GPS Test" to make the EUT receive continuous signals from GPS station.
3. Execute "Video Media Player" to play MPEG4 files.
4. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.1.4 Test Setup





## 3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 for SIM 2		




Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_L\_20140304 LINE  
Project : (FC)491802  
Mode : Mode 2

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.19	37.23	-17.01	54.24	26.70	0.22	10.31	Average
2	0.19	50.63	-13.61	64.24	40.10	0.22	10.31	QP
3	0.43	27.45	-19.75	47.20	17.00	0.29	10.16	Average
4	0.43	37.75	-19.45	57.20	27.30	0.29	10.16	QP
5	0.49	32.86	-13.37	46.23	22.40	0.30	10.16	Average
6	0.49	44.66	-11.57	56.23	34.20	0.30	10.16	QP
7	0.52	35.64	-10.36	46.00	25.19	0.29	10.16	Average
8 *	0.52	46.94	-9.06	56.00	36.49	0.29	10.16	QP
9	0.59	31.59	-14.41	46.00	21.20	0.24	10.15	Average
10	0.59	44.39	-11.61	56.00	34.00	0.24	10.15	QP
11	0.75	28.44	-17.56	46.00	18.10	0.19	10.15	Average
12	0.75	39.94	-16.06	56.00	29.60	0.19	10.15	QP
13	0.91	27.29	-18.71	46.00	16.90	0.24	10.15	Average
14	0.91	39.19	-16.81	56.00	28.80	0.24	10.15	QP
15	1.10	28.91	-17.09	46.00	18.50	0.25	10.16	Average
16	1.10	40.61	-15.39	56.00	30.20	0.25	10.16	QP
17	1.17	26.71	-19.29	46.00	16.30	0.25	10.16	Average
18	1.17	40.81	-15.19	56.00	30.40	0.25	10.16	QP
19	1.32	25.21	-20.79	46.00	14.80	0.24	10.17	Average
20	1.32	37.11	-18.89	56.00	26.70	0.24	10.17	QP
21	1.87	27.01	-18.99	46.00	16.61	0.22	10.18	Average
22	1.87	38.71	-17.29	56.00	28.31	0.22	10.18	QP
23	2.22	31.44	-14.56	46.00	21.01	0.24	10.19	Average
24	2.22	42.64	-13.36	56.00	32.21	0.24	10.19	QP
25	2.50	29.87	-16.13	46.00	19.40	0.27	10.20	Average
26	2.50	41.97	-14.03	56.00	31.50	0.27	10.20	QP
27	3.06	25.92	-20.08	46.00	15.40	0.31	10.21	Average
28	3.06	37.42	-18.58	56.00	26.90	0.31	10.21	QP
29	3.51	28.96	-17.04	46.00	18.40	0.34	10.22	Average
30	3.51	40.56	-15.44	56.00	30.00	0.34	10.22	QP
31	4.75	28.95	-17.05	46.00	18.30	0.41	10.24	Average
32	4.75	40.75	-15.25	56.00	30.10	0.41	10.24	QP



Test Mode :	Mode 2	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 for SIM 2		




Site : CO01-SZ  
Condition: FCC 15B\_QP LISN\_N\_20140304 NEUTRAL  
Project : (FC)491802  
Mode : Mode 2

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.18	40.64	-13.82	54.46	30.00	0.32	10.32	Average
2	0.18	50.24	-14.22	64.46	39.60	0.32	10.32	QP
3	0.25	38.29	-13.62	51.91	27.70	0.34	10.25	Average
4	0.25	47.69	-14.22	61.91	37.10	0.34	10.25	QP
5	0.39	37.36	-10.63	47.99	26.80	0.39	10.17	Average
6	0.39	45.96	-12.03	57.99	35.40	0.39	10.17	QP
7	0.43	38.56	-8.68	47.24	28.00	0.40	10.16	Average
8	0.43	47.86	-9.38	57.24	37.30	0.40	10.16	QP
9 *	0.50	44.26	-1.74	46.00	33.69	0.41	10.16	Average
10	0.50	53.56	-2.44	56.00	42.99	0.41	10.16	QP
11	0.57	35.50	-10.50	46.00	25.00	0.35	10.15	Average
12	0.57	46.70	-9.30	56.00	36.20	0.35	10.15	QP
13	0.63	35.15	-10.85	46.00	24.70	0.30	10.15	Average
14	0.63	44.95	-11.05	56.00	34.50	0.30	10.15	QP
15	0.68	36.62	-9.38	46.00	26.20	0.27	10.15	Average
16	0.68	46.52	-9.48	56.00	36.10	0.27	10.15	QP
17	0.77	37.12	-8.88	46.00	26.70	0.27	10.15	Average
18	0.77	45.92	-10.08	56.00	35.50	0.27	10.15	QP
19	0.87	34.05	-11.95	46.00	23.60	0.30	10.15	Average
20	0.87	43.55	-12.45	56.00	33.10	0.30	10.15	QP
21	1.00	35.08	-10.92	46.00	24.60	0.33	10.15	Average
22	1.00	46.48	-9.52	56.00	36.00	0.33	10.15	QP






Test Mode :	Mode 2	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM1900 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Charging from Adapter) + MPEG4 for SIM 2		



Site : C001-SZ  
Condition: FCC 15B\_QP LISN\_N\_20140304 NEUTRAL  
Project : (FC)491802  
Mode : Mode 2

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
23	1.09	36.39	-9.61	46.00	25.89	0.34	10.16	Average
24	1.09	45.79	-10.21	56.00	35.29	0.34	10.16	QP
25	1.25	34.31	-11.69	46.00	23.81	0.34	10.16	Average
26	1.25	45.11	-10.89	56.00	34.61	0.34	10.16	QP
27	1.38	31.92	-14.08	46.00	21.40	0.35	10.17	Average
28	1.38	41.12	-14.88	56.00	30.60	0.35	10.17	QP
29	1.59	30.03	-15.97	46.00	19.49	0.36	10.18	Average
30	1.59	40.83	-15.17	56.00	30.29	0.36	10.18	QP
31	1.96	35.56	-10.44	46.00	25.00	0.37	10.19	Average
32	1.96	45.26	-10.74	56.00	34.70	0.37	10.19	QP
33	2.20	39.38	-6.62	46.00	28.81	0.38	10.19	Average
34	2.20	48.38	-7.62	56.00	37.81	0.38	10.19	QP
35	2.40	38.39	-7.61	46.00	27.80	0.39	10.20	Average
36	2.40	48.49	-7.51	56.00	37.90	0.39	10.20	QP
37	2.90	35.73	-10.27	46.00	25.10	0.42	10.21	Average
38	2.90	44.93	-11.07	56.00	34.30	0.42	10.21	QP
39	3.51	35.86	-10.14	46.00	25.20	0.44	10.22	Average
40	3.51	44.96	-11.04	56.00	34.30	0.44	10.22	QP
41	3.84	33.18	-12.82	46.00	22.49	0.46	10.23	Average
42	3.84	42.78	-13.22	56.00	32.09	0.46	10.23	QP
43	4.65	35.42	-10.58	46.00	24.70	0.48	10.24	Average
44	4.65	44.92	-11.08	56.00	34.20	0.48	10.24	QP

<b>Test Mode :</b>	Mode 3	<b>Temperature :</b>	21~22℃
<b>Test Engineer :</b>	Jack Tian	<b>Relative Humidity :</b>	41~42%
<b>Test Voltage :</b>	120Vac / 60Hz	<b>Phase :</b>	Line
<b>Function Type :</b>	WCDMA Band V + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + GPS Rx for SIM 1		




Site : C001-SZ  
 Condition: FCC 15B\_QP LISN\_L\_20140304 LINE  
 Project : (FC)491802  
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	30.57	-25.12	55.69	20.00	0.22	10.35	Average
2	0.16	42.47	-23.22	65.69	31.90	0.22	10.35	QP
3	0.19	23.32	-30.66	53.98	12.80	0.22	10.30	Average
4	0.19	39.32	-24.66	63.98	28.80	0.22	10.30	QP
5	0.21	22.91	-30.19	53.10	12.40	0.23	10.28	Average
6	0.21	35.01	-28.09	63.10	24.50	0.23	10.28	QP
7	0.25	30.86	-20.87	51.73	20.38	0.24	10.24	Average
8	0.25	45.28	-16.45	61.73	34.80	0.24	10.24	QP
9	0.31	23.26	-26.84	50.10	12.80	0.26	10.20	Average
10	0.31	42.26	-17.84	60.10	31.80	0.26	10.20	QP
11	0.55	31.92	-14.08	46.00	21.50	0.27	10.15	Average
12 *	0.55	43.92	-12.08	56.00	33.50	0.27	10.15	QP



Test Mode :	Mode 2 3	Temperature :	21~22℃
Test Engineer :	Jack Tian	Relative Humidity :	41~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band V + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + GPS Rx for SIM 1		



Site : C001-SZ  
Condition: FCC 15B\_QP LISN\_N\_20140304 NEUTRAL  
Project : (FC)491802  
Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.16	20.77	-34.61	55.38	10.10	0.33	10.34	Average
2 *	0.16	44.47	-20.91	65.38	33.80	0.33	10.34	QP
3	0.19	24.83	-29.32	54.15	14.20	0.32	10.31	Average
4	0.19	39.43	-24.72	64.15	28.80	0.32	10.31	QP
5	0.21	22.11	-31.25	53.36	11.50	0.32	10.29	Average
6	0.21	39.21	-24.15	63.36	28.60	0.32	10.29	QP
7	0.24	20.19	-31.85	52.04	9.60	0.34	10.25	Average
8	0.24	38.89	-23.15	62.04	28.30	0.34	10.25	QP
9	0.32	25.56	-24.06	49.62	15.00	0.37	10.19	Average
10	0.32	32.06	-27.56	59.62	21.50	0.37	10.19	QP
11	1.12	23.49	-22.51	46.00	12.99	0.34	10.16	Average
12	1.12	28.49	-27.51	56.00	17.99	0.34	10.16	QP

## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

### 3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





## 3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 3	Temperature :	22~23°C
Test Engineer :	Levi Quan	Relative Humidity :	40~41%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	WCDMA Band V + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + GPS Rx for SIM 1		
Remark :	#7is system simulator signal which can be ignored.		




Site : 03CH01-KS  
Condition : FCC CLASS-B 3m LF\_ANT\_23182 HORIZONTAL  
Project : (FC) 491805  
Mode : mode 3

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	cm	deg	
			dB	dBuV/m	dBuV	dB/m	dB	dB		
1	54.25	33.79	-6.21	40.00	60.20	6.49	0.68	33.58	---	Peak
2	124.09	35.22	-8.28	43.50	56.03	11.76	1.03	33.60	---	Peak
3	244.37	39.74	-6.26	46.00	60.00	11.75	1.44	33.45	100	215 QP
4	719.67	41.35	-4.65	46.00	52.24	19.52	2.43	32.84	---	Peak
5	749.74	40.40	-5.60	46.00	50.82	19.90	2.46	32.78	---	Peak
6	849.65	37.29	-8.71	46.00	46.89	20.51	2.63	32.74	---	Peak
7	881.66	38.09			47.46	20.47	2.68	32.52	---	Peak
8	1222.00	39.82	-34.18	74.00	41.63	29.14	2.59	33.54	---	Peak
9	1594.00	41.20	-32.80	74.00	40.43	30.94	2.93	33.10	---	Peak
10	1728.00	45.02	-28.98	74.00	43.52	31.54	3.06	33.10	---	Peak
11	3076.00	47.78	-26.22	74.00	43.53	33.76	4.10	33.61	---	Peak
12	3460.00	48.17	-25.83	74.00	43.12	34.28	4.46	33.69	---	Peak
13	4584.00	47.55	-26.45	74.00	41.17	35.12	5.06	33.80	---	Peak



Test Mode :	Mode 3	Temperature :	22~23°C
Test Engineer :	Levi Quan	Relative Humidity :	40~41%
Test Distance :	3m	Polarization :	Vertical
Function Type :	WCDMA Band V + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Data Link with Notebook) + GPS Rx for SIM 1		
Remark :	#7is system simulator signal which can be ignored.		



Site : 03CH01-KS  
 Condition : FCC CLASS-B 3m LF\_ANT\_23182 VERTICAL  
 Project : (FC) 491805  
 Mode : mode 3

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	I/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	cm	deg	
			dB	dBuV/m	dBuV	dB/m	dB	dB		
1 !	35.82	37.99	-2.01	40.00	56.41	14.65	0.55	33.62	200	154 QP
2	66.86	33.78	-6.22	40.00	61.36	5.25	0.76	33.59	---	Peak
3	239.52	39.47	-6.53	46.00	59.98	11.51	1.44	33.46	---	Peak
4	720.64	39.89	-6.11	46.00	50.77	19.53	2.43	32.84	---	Peak
5 !	749.74	42.28	-3.72	46.00	52.70	19.90	2.46	32.78	---	Peak
6 !	849.65	41.06	-4.94	46.00	50.66	20.51	2.63	32.74	---	Peak
7 !	881.66	45.30			54.67	20.47	2.68	32.52	---	Peak
8	1200.00	39.58	-34.42	74.00	41.50	29.08	2.57	33.57	---	Peak
9	1392.00	44.17	-29.83	74.00	44.82	29.81	2.77	33.23	---	Peak
10	1996.00	47.48	-26.52	74.00	44.88	32.40	3.30	33.10	---	Peak
11	3190.00	49.72	-24.28	74.00	45.27	33.88	4.21	33.64	---	Peak
12	3982.00	49.97	-24.03	74.00	43.93	34.99	4.65	33.60	---	Peak
13	4790.00	48.25	-25.75	74.00	41.66	35.17	5.22	33.80	---	Peak



## 4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 05, 2013	Oct. 13, 2014	Nov. 04, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Oct. 13, 2014	May 03, 2015	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 08, 2014	Oct. 13, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 08, 2014	Oct. 13, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	Oct. 13, 2014	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Dec. 10, 2013	Oct. 13, 2014	Dec. 09, 2014	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 13, 2014	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Oct. 13, 2014	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Oct. 13, 2014	NCR	Radiation (03CH01-KS)
ESCIO TEST Receiver	R&S	ESCI	100724	9kHz~3GHz	Feb. 21, 2014	Sep. 25 2014	Feb. 20, 2015	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Mar. 04, 2014	Sep. 25 2014	Mar. 03, 2015	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Mar. 04, 2014	Sep. 25 2014	Mar. 03, 2015	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Dec. 17, 2013	Sep. 25 2014	Dec. 16, 2014	Conduction (CO01-SZ)



## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.3
--	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_c(y)$ )	2.5
--	-----