

FCC RF Test Report

APPLICANT : Brightstar Corporation
EQUIPMENT : Mobile phone
BRAND NAME : Avvio, PULSARE, WUPA
MODEL NAME : Avvio 777, Avvio 777S, Pulsare 777,
Pulsare 777S, WUPA 777, WUPA 777S
FCC ID : WVBA777X
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Sep. 19, 2014 and testing was completed on Oct. 02, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	7
1.6 Testing Site.....	7
1.7 Applied Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency Channel	8
2.2 Pre-Scanned RF Power.....	9
2.3 Test Mode.....	10
2.4 Connection Diagram of Test System.....	11
2.5 Support Unit used in test configuration and system	12
2.6 EUT Operation Test Setup	11
2.7 Measurement Results Explanation Example.....	12
3 TEST RESULT.....	13
3.1 6dB and 99% Bandwidth Measurement	13
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement	19
3.4 Conducted Band Edges and Spurious Emission Measurement	22
3.5 Radiated Band Edges and Spurious Emission Measurement	35
3.6 AC Conducted Emission Measurement.....	57
3.7 Antenna Requirements.....	63
4 LIST OF MEASURING EQUIPMENT	64
5 UNCERTAINTY OF EVALUATION	65
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR491904C	Rev. 01	Initial issue of report	Oct. 23, 2014

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 3.52 dB at 4924.000 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.05 dB at 0.570 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Brightstar Corporation

9725 NW 117th Ave., Miami, Florida, FL 33178, United States

1.2 Manufacturer

KCMobile Co.,Ltd.

#1305-1, Kolon Digital Tower Villant II, 31, Digital-ro 30-gil, Guro-Gu, Seoul, KOREA (152-727)

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile phone
Brand Name	Avvio, PULSARE, WUPA
Model Name	Avvio 777, Avvio 777S, Pulsare 777, Pulsare 777S, WUPA 777, WUPA 777S
FCC ID	WVBA777X
EUT supports Radios application	GSM/GPRS/EGPRS(Downlink only)/WCDMA/HSPA WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	V1.01
SW Version	M7202.Viano.KC777.WD4+4.V1.02.20140826
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are six types of EUT for this project. The differences between them are summary below:

Sample List	Model name	Brand name	SIM Slots
Sample 1	Avvio 777	Avvio	1
Sample 2	Avvio 777S	Avvio	2
Sample 3	PULSARE 777	PULSARE	1
Sample 4	PULSARE 777S	PULSARE	2
Sample 5	WUPA 777	WUPA	1
Sample 6	WUPA 777S	WUPA	2

These models are identical on hardware except the SIM slots. The different model with different brand is for market purpose.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 16.97 dBm (0.0498 W) 802.11g : 18.61 dBm (0.0726 W) 802.11n HT20 : 18.69 dBm (0.0740 W) 802.11n HT40 : 18.56 dBm (0.0718 W)
Antenna Type	802.11b/g/n : PIFA Antenna with gain 0.8 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC Registration No.
	TH01-SZ	831040

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH01-KS	CO01-KS 149928

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ANSI C63.4-2003

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	16.40	CH 11	16.95	16.92	16.91
CH 06	2437 MHz	16.62				
CH 11	2462 MHz	16.97				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
		6Mbps								
CH 01	2412 MHz	18.31	CH 11	18.58	18.57	18.55	18.52	18.50	18.47	18.46
CH 06	2437 MHz	18.46								
CH 11	2462 MHz	18.61								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 01	2412 MHz	18.38	CH 11	18.67	18.61	18.57	18.53	18.51	18.50	18.49
CH 06	2437 MHz	18.46								
CH 11	2462 MHz	18.69								

2.4GHz 802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 03	2422 MHz	18.17	CH 06	18.28	18.25	18.24	18.19	18.17	18.15	18.14
CH 06	2437 MHz	18.56								
CH 09	2452 MHz	18.37								


2.3 Test Mode

Final results of test modes, data rates and test channels are shown as following table.


Test Cases				
Conducted TCs	Test Items	Mode	Data Rate	Test Channel
	6dB BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone			
Remark: For Radiated Test Cases, the tests were performance with adapter, earphone and USB cable.				

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Lenovo	LBH505	N/A	N/A	N/A
4.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m

2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 7.5 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 7.5 + 10 = 17.5 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup



**3.1.5 Test Result of 6dB Bandwidth**

Test Band :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Fly Liang	Relative Humidity :	50~53%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	10.04	0.5	Pass
11b	1Mbps	1	6	2437	10.04	0.5	Pass
11b	1Mbps	1	11	2462	10.04	0.5	Pass
11g	6Mbps	1	1	2412	15.48	0.5	Pass
11g	6Mbps	1	6	2437	15.80	0.5	Pass
11g	6Mbps	1	11	2462	15.78	0.5	Pass
HT20	MCS0	1	1	2412	16.92	0.5	Pass
HT20	MCS0	1	6	2437	16.88	0.5	Pass
HT20	MCS0	1	11	2462	16.92	0.5	Pass
HT40	MCS0	1	3	2422	35.36	0.5	Pass
HT40	MCS0	1	6	2437	35.20	0.5	Pass
HT40	MCS0	1	9	2452	35.20	0.5	Pass



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



**3.2.5 Test Result of Peak Output Power**

Test Mode :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Fly Liang	Relative Humidity :	50~53%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	RF Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	16.40	30	0.80	Pass
11b	1Mbps	1	6	2437	16.62	30	0.80	Pass
11b	1Mbps	1	11	2462	16.97	30	0.80	Pass
11g	6Mbps	1	1	2412	18.31	30	0.80	Pass
11g	6Mbps	1	6	2437	18.46	30	0.80	Pass
11g	6Mbps	1	11	2462	18.61	30	0.80	Pass
HT20	MCS0	1	1	2412	18.38	30	0.80	Pass
HT20	MCS0	1	6	2437	18.46	30	0.80	Pass
HT20	MCS0	1	11	2462	18.69	30	0.80	Pass
HT40	MCS0	1	3	2422	18.17	30	0.80	Pass
HT40	MCS0	1	6	2437	18.56	30	0.80	Pass
HT40	MCS0	1	9	2452	18.37	30	0.80	Pass

Note: Measured power (dBm) has offset with cable loss.

3.2.6 Test Result of Average output Power (Reporting Only)

Test Mode :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Fly Liang	Relative Humidity :	50~53%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Duty Factor (dB)	Average Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	0.08	14.04	30	0.80	Pass
11b	1Mbps	1	6	2437	0.08	14.31	30	0.80	Pass
11b	1Mbps	1	11	2462	0.08	14.81	30	0.80	Pass
11g	6Mbps	1	1	2412	0.52	10.25	30	0.80	Pass
11g	6Mbps	1	6	2437	0.52	10.73	30	0.80	Pass
11g	6Mbps	1	11	2462	0.52	11.34	30	0.80	Pass
HT20	MCS0	1	1	2412	0.54	10.26	30	0.80	Pass
HT20	MCS0	1	6	2437	0.54	10.78	30	0.80	Pass
HT20	MCS0	1	11	2462	0.54	11.32	30	0.80	Pass
HT40	MCS0	1	3	2422	1.02	8.37	30	0.80	Pass
HT40	MCS0	1	6	2437	1.02	10.63	30	0.80	Pass
HT40	MCS0	1	9	2452	1.02	8.81	30	0.80	Pass

Note: Measured power (dBm) has offset with cable loss and duty factor.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Test Mode :	2.4GHz	Temperature :	24~26℃
Test Engineer :	Fly Liang	Relative Humidity :	50~53%

Mod.	Data Rate	N _{TX}	Channel	Freq. (MHz)	Peak Power Density (dBm/3kHz)	Max. Limits (dBm/3kHz)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	-8.92	8	0.80	Pass
11b	1Mbps	1	6	2437	-9.68	8	0.80	Pass
11b	1Mbps	1	11	2462	-9.33	8	0.80	Pass
11g	6Mbps	1	1	2412	-13.12	8	0.80	Pass
11g	6Mbps	1	6	2437	-14.90	8	0.80	Pass
11g	6Mbps	1	11	2462	-12.51	8	0.80	Pass
HT20	MCS0	1	1	2412	-14.25	8	0.80	Pass
HT20	MCS0	1	6	2437	-15.07	8	0.80	Pass
HT20	MCS0	1	11	2462	-14.41	8	0.80	Pass
HT40	MCS0	1	3	2422	-19.82	8	0.80	Pass
HT40	MCS0	1	6	2437	-18.00	8	0.80	Pass
HT40	MCS0	1	9	2452	-20.44	8	0.80	Pass

Note: Measured power density (dBm) has offset with cable loss.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~26℃
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Fly Liang


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 25.SEP.2014 10:13:20

Low Channel Plot




Date: 25.SEP.2014 10:13:34

Spurious Emission 30MHz~3GHz



Date: 25.SEP.2014 10:13:53

Spurious Emission 2GHz~25GHz




Date: 25.SEP.2014 10:14:12



Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Fly Liang


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 25.SEP.2014 10:17:19

Spurious Emission 30MHz~3GHz



Date: 25.SEP.2014 10:17:39


Spurious Emission 2GHz~25GHz




Date: 25.SEP.2014 10:17:58




Test Mode :	802.11b	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Fly Liang

WLAN 802.11b Channel 11**100kHz PSD reference Level**


Date: 25.SEP.2014 10:22:06

High Channel Plot

Date: 25.SEP.2014 10:22:20

Spurious Emission 30MHz~3GHz

Date: 25.SEP.2014 10:22:39

Spurious Emission 2GHz~25GHz


Date: 25.SEP.2014 10:22:58



Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Fly Liang


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 25.SEP.2014 10:43:57

Low Channel Plot




Date: 25.SEP.2014 10:44:11

Spurious Emission 30MHz~3GHz



Date: 25.SEP.2014 10:44:30

Spurious Emission 2GHz~25GHz




Date: 25.SEP.2014 10:44:48

Test Mode :	802.11g	Temperature :	24~26℃
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Fly Liang


WLAN 802.11g Channel 06

100kHz PSD reference Level




Date: 25.SEP.2014 12:54:42

Spurious Emission 30MHz~3GHz



Date: 25.SEP.2014 12:55:02


Spurious Emission 2GHz~25GHz




Date: 25.SEP.2014 12:55:21




Test Mode :	802.11g	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Fly Liang

WLAN 802.11g Channel 11**100kHz PSD reference Level**


Date: 25.SEP.2014 10:53:17

High Channel Plot

Date: 25.SEP.2014 10:53:31

Spurious Emission 30MHz~3GHz

Date: 25.SEP.2014 10:53:50

Spurious Emission 2GHz~25GHz


Date: 25.SEP.2014 10:54:09



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	01	Test Engineer :	Fly Liang


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 25.SEP.2014 11:00:48

Low Channel Plot




Date: 25.SEP.2014 11:01:02

Spurious Emission 30MHz~3GHz



Date: 25.SEP.2014 11:01:21


Spurious Emission 2GHz~25GHz




Date: 25.SEP.2014 11:01:40




Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Fly Liang

WLAN 802.11n HT20 Channel 06**100kHz PSD reference Level**

Date: 25.SEP.2014 11:05:42

Spurious Emission 30MHz~3GHz

Date: 25.SEP.2014 11:06:02

Spurious Emission 2GHz~25GHz


Date: 25.SEP.2014 11:06:20



Test Mode :	802.11n HT20	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	11	Test Engineer :	Fly Liang


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 25.SEP.2014 12:13:25

High Channel Plot




Date: 25.SEP.2014 12:13:39

Spurious Emission 30MHz~3GHz



Date: 25.SEP.2014 12:16:31


Spurious Emission 2GHz~25GHz




Date: 25.SEP.2014 12:16:49




Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Low	Relative Humidity :	50~53%
Test Channel :	03	Test Engineer :	Fly Liang

WLAN 802.11n HT40 Channel 03**100kHz PSD reference Level**


Date: 25.SEP.2014 11:20:01

Low Channel Plot

Date: 25.SEP.2014 11:20:15

Spurious Emission 30MHz~3GHz


Date: 25.SEP.2014 11:27:32

Spurious Emission 2GHz~25GHz


Date: 25.SEP.2014 11:25:49




Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	50~53%
Test Channel :	06	Test Engineer :	Fly Liang

WLAN 802.11n HT40 Channel 06**100kHz PSD reference Level**

Date: 25.SEP.2014 11:31:23

Spurious Emission 30MHz~3GHz

Date: 25.SEP.2014 11:34:38

Spurious Emission 2GHz~25GHz


Date: 25.SEP.2014 11:33:14



Test Mode :	802.11n HT40	Temperature :	24~26°C
Test Band :	2.4GHz High	Relative Humidity :	50~53%
Test Channel :	09	Test Engineer :	Fly Liang


WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level




Date: 25.SEP.2014 11:40:27

High Channel Plot




Date: 25.SEP.2014 11:40:40

Spurious Emission 30MHz~3GHz



Date: 25.SEP.2014 11:41:00

Spurious Emission 2GHz~25GHz



Date: 25.SEP.2014 11:41:18

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	98.22	-	-	10Hz
802.11g	88.62	1.39	0.72	1kHz
2.4GHz 802.11n HT20	88.28	1.30	0.77	1kHz
2.4GHz 802.11n HT40	79.13	0.65	1.53	3kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Test Mode :	802.11b	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	40~41%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2354.37	59.81	-14.19	74	56.68	32.81	3.57	33.25	200	61	Peak
2357.7	38.34	-15.66	54	35.21	32.81	3.57	33.25	200	61	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2370.39	58.94	-15.06	74	55.79	32.83	3.58	33.26	200	93	Peak
2386.77	38.54	-15.46	54	35.35	32.86	3.59	33.26	200	93	Average

Test Mode :	802.11b	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	40~41%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2499.97	51.31	-22.69	74	47.9	33.05	3.66	33.3	105	20	Peak
2488.6	38.99	-15.01	54	35.58	33.05	3.66	33.3	105	20	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2487.25	46.7	-27.3	74	43.33	33.01	3.65	33.29	200	159	Peak
2488.15	34.77	-19.23	54	31.36	33.05	3.66	33.3	200	259	Average



Test Mode :	802.11g	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	40~41%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.65	57.57	-16.43	74	54.38	32.86	3.59	33.26	102	106	Peak
2389.65	38.99	-15.01	54	35.8	32.86	3.59	33.26	102	106	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.74	59.14	-14.86	74	55.95	32.86	3.59	33.26	100	134	Peak
2389.56	39.22	-14.78	54	36.03	32.86	3.59	33.26	100	134	Average

Test Mode :	802.11g	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	40~41%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.62	66.08	-7.92	74	62.71	33.01	3.65	33.29	200	44	Peak
2483.5	44.61	-9.39	54	41.24	33.01	3.65	33.29	200	44	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.01	61.63	-12.37	74	58.26	33.01	3.65	33.29	100	108	Peak
2483.62	39.99	-14.01	54	36.62	33.01	3.65	33.29	100	108	Average



Test Mode :	802.11n HT20	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	40~41%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.02	63.32	-10.68	74	60.13	32.86	3.59	33.26	100	308	Peak
2389.83	41.6	-12.4	54	38.41	32.86	3.59	33.26	100	306	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.66	61.83	-12.17	74	58.64	32.86	3.59	33.26	100	139	Peak
2389.83	41.7	-12.3	54	38.51	32.86	3.59	33.26	100	136	Average

Test Mode :	802.11n HT20	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	40~41%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.91	66.03	-7.97	74	62.66	33.01	3.65	33.29	100	17	Peak
2483.5	44.2	-9.8	54	40.83	33.01	3.65	33.29	100	17	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.01	62.41	-11.59	74	59.04	33.01	3.65	33.29	100	124	Peak
2483.5	39.02	-14.98	54	35.65	33.01	3.65	33.29	100	124	Average



Test Mode :	802.11n HT40	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	40~41%
Test Channel :	03	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.21	67.1	-6.9	74	63.91	32.86	3.59	33.26	176	339	Peak
2389.83	44.68	-9.32	54	41.49	32.86	3.59	33.26	176	339	Average
2491.12	47.04	-26.96	74	43.63	33.05	3.66	33.3	200	147	Peak
2491.24	33.6	-20.4	54	30.19	33.05	3.66	33.3	200	147	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.91	46.52	-27.48	74	43.15	33.01	3.65	33.29	100	214	Peak
2498.47	33.26	-20.74	54	29.85	33.05	3.66	33.3	100	214	Average
2388.48	65.15	-8.85	74	61.96	32.86	3.59	33.26	200	0	Peak
2388.48	43.3	-10.7	54	40.11	32.86	3.59	33.26	200	0	Average



Test Mode :	802.11n HT40	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	40~41%
Test Channel :	09	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2377.41	59.08	-14.92	74	55.93	32.83	3.58	33.26	100	359	Peak
2385.78	38.33	-15.67	54	35.14	32.86	3.59	33.26	100	359	Average
2485.21	61.89	-12.11	74	58.52	33.01	3.65	33.29	200	342	Peak
2488.75	36.17	-17.83	54	32.76	33.05	3.66	33.3	200	342	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2377.41	56.8	-17.2	74	53.65	32.83	3.58	33.26	200	57	Peak
2384.16	38.25	-15.75	54	35.1	32.83	3.58	33.26	200	57	Average
2483.68	61.78	-12.22	74	58.41	33.01	3.65	33.29	100	57	Peak
2484.37	36.25	-17.75	54	32.88	33.01	3.65	33.29	100	57	Average

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Note: Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	101.49	-	-	98.26	32.89	3.61	33.27	200	50	Peak
2412	95.43	-	-	92.2	32.89	3.61	33.27	200	50	Average
4824	50.7	-23.3	74	44.08	35.17	5.25	33.8	100	214	Peak

Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	97.79	-	-	94.56	32.89	3.61	33.27	200	258	Peak
2412	91.77	-	-	88.54	32.89	3.61	33.27	200	258	Average
4824	50.63	-23.37	74	44.01	35.17	5.25	33.8	100	214	Peak



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	98.32	-	-	95.02	32.95	3.63	33.28	200	40	Peak
2437	92.15	-	-	88.85	32.95	3.63	33.28	200	40	Average
4874	55.27	-18.73	74	48.61	35.18	5.28	33.8	100	324	Peak
4874	48.43	-5.57	54	41.77	35.18	5.28	33.8	100	324	Average
7312	50.95	-23.05	74	42.27	36.2	6.61	34.13	100	265	Peak

Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	95.51	-	-	92.21	32.95	3.63	33.28	100	42	Peak
2437	89.37	-	-	86.07	32.95	3.63	33.28	100	42	Average
4874	53.61	-20.39	74	46.95	35.18	5.28	33.8	100	7	Peak
4874	49.63	-4.37	54	42.97	35.18	5.28	33.8	100	7	Average
7312	53.57	-20.43	74	44.89	36.2	6.61	34.13	100	340	Peak
7312	33.49	-20.51	54	24.81	36.2	6.61	34.13	100	340	Average



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
79.47	27.5	-12.5	40	53.81	6.47	0.82	33.6	100	51	Peak
113.42	25.63	-17.87	43.5	46.45	11.8	0.99	33.61			Peak
196.84	25.41	-18.09	43.5	48.82	8.86	1.29	33.56			Peak
427.7	25.08	-20.92	46	40.25	16.18	1.9	33.25			Peak
673.11	27.48	-18.52	46	38.96	19.08	2.36	32.92			Peak
815.7	30.39	-15.61	46	40.43	20.02	2.59	32.65			Peak
2462	97.89	-	-	94.56	32.98	3.64	33.29	200	22	Peak
2462	91.92	-	-	88.59	32.98	3.64	33.29	200	22	Average
4924	55.36	-18.64	74	48.66	35.19	5.31	33.8	100	339	Peak
4924	50.48	-3.52	54	43.78	35.19	5.31	33.8	100	339	Average
7386	54.57	-19.43	74	45.79	36.24	6.7	34.16	100	291	Peak
7386	43.99	-10.01	54	35.21	36.24	6.7	34.16	100	291	Average



Test Mode :	802.11b	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.85	30.46	-9.54	40	48.43	15.1	0.54	33.61	100	61	Peak
159.98	30.65	-12.85	43.5	53.47	9.6	1.16	33.58			Peak
541.19	25.07	-20.93	46	37.66	18.33	2.11	33.03			Peak
601.33	27.41	-18.59	46	39.51	18.6	2.25	32.95			Peak
727.43	26.44	-19.56	46	37.16	19.65	2.45	32.82			Peak
838.98	25.76	-20.24	46	35.45	20.4	2.63	32.72			Peak
2462	95.5	-	-	92.17	32.98	3.64	33.29	189	89	Peak
2462	90.12	-	-	86.79	32.98	3.64	33.29	189	89	Average
4924	53.72	-20.28	74	47.02	35.19	5.31	33.8	100	11	Peak
4924	50.2	-3.8	54	43.5	35.19	5.31	33.8	100	11	Average
7386	55.66	-18.34	74	46.88	36.24	6.7	34.16	100	349	Peak
7386	49.38	-4.62	54	40.6	36.24	6.7	34.16	100	349	Average

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	95.73	-	-	92.5	32.89	3.61	33.27	115	47	Peak
2412	85.2	-	-	81.97	32.89	3.61	33.27	115	47	Average
4824	48.63	-25.37	74	42.01	35.17	5.25	33.8	100	214	Peak

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	94.09	-	-	90.86	32.89	3.61	33.27	100	121	Peak
2412	82.43	-	-	79.2	32.89	3.61	33.27	100	121	Average
4824	49.56	-24.44	74	42.94	35.17	5.25	33.8	100	24	Peak

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	98.62	-	-	95.32	32.95	3.63	33.28	111	73	Peak
2437	88.64	-	-	85.34	32.95	3.63	33.28	111	73	Average
4874	47.24	-26.76	74	40.58	35.18	5.28	33.8	200	154	Peak
7312	50.1	-23.9	74	41.42	36.2	6.61	34.13	100	216	Peak

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	93.87	-	-	90.57	32.95	3.63	33.28	100	109	Peak
2437	81.47	-	-	78.17	32.95	3.63	33.28	100	109	Average
4874	48.7	-25.3	74	42.04	35.18	5.28	33.8	100	214	Peak
7312	50.32	-23.68	74	41.64	36.2	6.61	34.13	100	214	Peak

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	101.95	-	-	98.62	32.98	3.64	33.29	111	62	Peak
2462	91.17	-	-	87.84	32.98	3.64	33.29	111	62	Average
4924	50.02	-23.98	74	43.32	35.19	5.31	33.8	200	142	Peak
7386	50.68	-23.32	74	41.9	36.24	6.7	34.16	200	164	Peak

Test Mode :	802.11g	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	97.71	-	-	94.38	32.98	3.64	33.29	200	119	Peak
2462	86.92	-	-	83.59	32.98	3.64	33.29	200	119	Average
4924	50.97	-23.03	74	44.27	35.19	5.31	33.8	100	258	Peak
7386	50.14	-23.86	74	41.36	36.24	6.7	34.16	100	235	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	97.17	-	-	93.94	32.89	3.61	33.27	133	68	Peak
2412	87.37	-	-	84.14	32.89	3.61	33.27	133	68	Average
4824	47.75	-26.25	74	41.13	35.17	5.25	33.8	100	214	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	01	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2412	94.39	-	-	91.16	32.89	3.61	33.27	100	61	Peak
2412	82.71	-	-	79.48	32.89	3.61	33.27	100	61	Average
4824	50.54	-23.46	74	43.92	35.17	5.25	33.8	100	320	Peak



Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	97.24	-	-	93.94	32.95	3.63	33.28	100	16	Peak
2437	84.59	-	-	81.29	32.95	3.63	33.28	100	16	Average
4874	48.68	-25.32	74	42.02	35.18	5.28	33.8	100	45	Peak
7312	49.64	-24.36	74	40.96	36.2	6.61	34.13	100	32	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	94.25	-	-	90.95	32.95	3.63	33.28	100	87	Peak
2437	83.44	-	-	80.14	32.95	3.63	33.28	100	87	Average
4874	47.16	-26.84	74	40.5	35.18	5.28	33.8	100	47	Peak
7312	49.69	-24.31	74	41.01	36.2	6.61	34.13	200	100	Peak

Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	96.16	-	-	92.83	32.98	3.64	33.29	151	23	Peak
2462	85.18	-	-	81.85	32.98	3.64	33.29	151	23	Average
4924	49.59	-24.41	74	42.89	35.19	5.31	33.8	100	149	Peak
7386	51.69	-22.31	74	42.91	36.24	6.7	34.16	100	292	Peak
7386	38.63	-15.37	54	29.85	36.24	6.7	34.16	100	292	Average

Test Mode :	2.4GHz 802.11n HT20	Temperature :	22~23°C
Test Channel :	11	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2462	93.77	-	-	90.44	32.98	3.64	33.29	200	124	Peak
2462	83.01	-	-	79.68	32.98	3.64	33.29	200	124	Average
4924	50.08	-23.92	74	43.38	35.19	5.31	33.8	100	214	Peak
7386	50.31	-23.69	74	41.53	36.24	6.7	34.16	100	215	Peak

Test Mode :	2.4GHz 802.11n HT40	Temperature :	22~23°C
Test Channel :	03	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2422 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2422	91.54	-	-	88.28	32.92	3.62	33.28	100	6	Peak
2422	81.31	-	-	78.05	32.92	3.62	33.28	100	6	Average
4844	47.7	-26.3	74	41.06	35.18	5.26	33.8	100	201	Peak
7266	49.2	-24.8	74	40.56	36.19	6.56	34.11	200	164	Peak

Test Mode :	2.4GHz 802.11n HT40	Temperature :	22~23°C
Test Channel :	03	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2422 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2422	90.62	-	-	87.36	32.92	3.62	33.28	166	0	Peak
2422	80.09	-	-	76.83	32.92	3.62	33.28	166	0	Average
4844	46.63	-27.37	74	39.99	35.18	5.26	33.8	100	164	Peak
7266	50.15	-23.85	74	41.51	36.19	6.56	34.11	200	178	Peak

Test Mode :	2.4GHz 802.11n HT40	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	94.82	-	-	91.52	32.95	3.63	33.28	175	0	Peak
2437	84.08	-	-	80.78	32.95	3.63	33.28	175	0	Average
4874	48.85	-25.15	74	42.19	35.18	5.28	33.8	200	165	Peak
7312	49.53	-24.47	74	40.85	36.2	6.61	34.13	200	98	Peak

Test Mode :	2.4GHz 802.11n HT40	Temperature :	22~23°C
Test Channel :	06	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2437	92.97	-	-	89.67	32.95	3.63	33.28	200	24	Peak
2437	82.46	-	-	79.16	32.95	3.63	33.28	200	24	Average
4874	47.51	-26.49	74	40.85	35.18	5.28	33.8	100	24	Peak
7312	49.62	-24.38	74	40.94	36.2	6.61	34.13	100	215	Peak

Test Mode :	2.4GHz 802.11n HT40	Temperature :	22~23°C
Test Channel :	09	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Horizontal
Remark :	1. 2452 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2452	90.51	-	-	87.21	32.95	3.63	33.28	100	2	Peak
2452	82.39	-	-	79.09	32.95	3.63	33.28	100	2	Average
4904	47.04	-26.96	74	40.35	35.19	5.3	33.8	200	56	Peak
7356	49.34	-24.66	74	40.61	36.22	6.66	34.15	200	215	Peak

Test Mode :	2.4GHz 802.11n HT40	Temperature :	22~23°C
Test Channel :	09	Relative Humidity :	40~41%
Test Engineer :	Star Wei	Polarization :	Vertical
Remark :	1. 2452 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2452	89.69	-	-	86.39	32.95	3.63	33.28	103	63	Peak
2452	78.73	-	-	75.43	32.95	3.63	33.28	103	63	Average
4904	46.91	-27.09	74	40.22	35.19	5.3	33.8	200	134	Peak
7356	48.59	-25.41	74	39.86	36.22	6.66	34.15	200	312	Peak

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.


3.6.4 Test Setup





3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	55~58%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		




Site : CO01-KS
Condition : FCC PART 15C LISN-L20140306 LINE

mode		: Mode 1						
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz		dB			dB	dB	
1	0.45	49.62	-7.23	56.85	39.10	0.25	10.27	QP
2	0.45	39.62	-7.23	46.85	29.10	0.25	10.27	Average
3	0.48	46.59	-9.77	56.36	36.10	0.22	10.27	QP
4	0.48	37.29	-9.07	46.36	26.80	0.22	10.27	Average
5	0.57	48.35	-7.65	56.00	37.90	0.20	10.25	QP
6	0.57	39.95	-6.05	46.00	29.50	0.20	10.25	Average
7	0.80	46.66	-9.34	56.00	36.29	0.17	10.20	QP
8	0.80	37.46	-8.54	46.00	27.09	0.17	10.20	Average
9	0.89	43.91	-12.09	56.00	33.59	0.13	10.19	QP
10	0.89	34.61	-11.39	46.00	24.29	0.13	10.19	Average
11	0.95	43.79	-12.21	56.00	33.50	0.11	10.18	QP
12	0.95	35.59	-10.41	46.00	25.30	0.11	10.18	Average
13	1.05	43.18	-12.82	56.00	32.90	0.10	10.18	QP
14	1.05	32.88	-13.12	46.00	22.60	0.10	10.18	Average
15	1.17	45.88	-10.12	56.00	35.60	0.10	10.18	QP
16	1.17	36.38	-9.62	46.00	26.10	0.10	10.18	Average
17	1.25	43.58	-12.42	56.00	33.30	0.10	10.18	QP
18	1.25	34.08	-11.92	46.00	23.80	0.10	10.18	Average
19	1.36	43.08	-12.92	56.00	32.80	0.10	10.18	QP
20	1.36	33.48	-12.52	46.00	23.20	0.10	10.18	Average
21	1.46	41.19	-14.81	56.00	30.90	0.10	10.19	QP
22	1.46	32.19	-13.81	46.00	21.90	0.10	10.19	Average
23	1.80	42.19	-13.81	56.00	31.90	0.10	10.19	QP
24	1.80	34.39	-11.61	46.00	24.10	0.10	10.19	Average
25	2.05	46.59	-9.41	56.00	36.30	0.10	10.19	QP



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	55~58%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		




Site : CO01-KS
Condition : FCC PART 15C LISN-L20140306 LINE

mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz		dB			dB	dB	
26	2.05	38.59	-7.41	46.00	28.30	0.10	10.19	Average
27	2.19	48.60	-7.40	56.00	38.30	0.11	10.19	QP
28	2.19	39.40	-6.60	46.00	29.10	0.11	10.19	Average
29	2.40	46.91	-9.09	56.00	36.60	0.11	10.20	QP
30	2.40	36.61	-9.39	46.00	26.30	0.11	10.20	Average
31	3.17	40.98	-15.02	56.00	30.60	0.15	10.23	QP
32	3.17	33.78	-12.22	46.00	23.40	0.15	10.23	Average
33	3.36	42.69	-13.31	56.00	32.30	0.16	10.23	QP
34	3.36	34.69	-11.31	46.00	24.30	0.16	10.23	Average
35	3.60	43.21	-12.79	56.00	32.81	0.17	10.23	QP
36	3.60	34.51	-11.49	46.00	24.11	0.17	10.23	Average
37	3.92	40.32	-15.68	56.00	29.90	0.18	10.24	QP
38	3.92	32.02	-13.98	46.00	21.60	0.18	10.24	Average



Test Mode :	Mode 1	Temperature :	22~24°C
Test Engineer :	Eligah Wang	Relative Humidity :	55~58%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		




Site : CO01-KS
Condition : FCC PART 15C LISN-N20140306 NEUTRAL

mode	: Mode 1							
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz		dB			dB	dB	
1	0.45	42.42	-14.47	56.89	31.81	0.34	10.27	QP
2	0.45	34.92	-11.97	46.89	24.31	0.34	10.27	Average
3	0.59	44.79	-11.21	56.00	34.30	0.25	10.24	QP
4	0.59	36.79	-9.21	46.00	26.30	0.25	10.24	Average
5	0.63	43.66	-12.34	56.00	33.20	0.23	10.23	QP
6	0.63	35.06	-10.94	46.00	24.60	0.23	10.23	Average
7	0.72	43.30	-12.70	56.00	32.90	0.19	10.21	QP
8	0.72	34.30	-11.70	46.00	23.90	0.19	10.21	Average
9	0.92	43.20	-12.80	56.00	32.89	0.12	10.19	QP
10	0.92	33.40	-12.60	46.00	23.09	0.12	10.19	Average
11	0.98	46.59	-9.41	56.00	36.31	0.10	10.18	QP
12	0.98	38.19	-7.81	46.00	27.91	0.10	10.18	Average
13	1.09	44.58	-11.42	56.00	34.30	0.10	10.18	QP
14	1.09	34.88	-11.12	46.00	24.60	0.10	10.18	Average
15	1.34	43.18	-12.82	56.00	32.90	0.10	10.18	QP
16	1.34	34.38	-11.62	46.00	24.10	0.10	10.18	Average
17	1.47	43.19	-12.81	56.00	32.90	0.10	10.19	QP
18	1.47	33.19	-12.81	46.00	22.90	0.10	10.19	Average
19	1.63	38.09	-17.91	56.00	27.80	0.10	10.19	QP
20	1.63	29.19	-16.81	46.00	18.90	0.10	10.19	Average
21	1.93	41.89	-14.11	56.00	31.60	0.10	10.19	QP
22	1.93	33.49	-12.51	46.00	23.20	0.10	10.19	Average
23	2.11	44.80	-11.20	56.00	34.51	0.10	10.19	QP
24	2.11	36.20	-9.80	46.00	25.91	0.10	10.19	Average
25	2.35	46.81	-9.19	56.00	36.50	0.11	10.20	QP



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	55~58%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone		



Site : CO01-KS
Condition : FCC PART 15C LISN-N20140306 NEUTRAL

mode		: Mode 1						
	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz		dB			dB	dB	
26	2.35	37.61	-8.39	46.00	27.30	0.11	10.20	Average
27	2.53	41.92	-14.08	56.00	31.60	0.12	10.20	QP
28	2.53	32.62	-13.38	46.00	22.30	0.12	10.20	Average
29	3.33	39.99	-16.01	56.00	29.60	0.16	10.23	QP
30	3.33	32.49	-13.51	46.00	22.10	0.16	10.23	Average
31	3.64	41.31	-14.69	56.00	30.90	0.17	10.24	QP
32	3.64	33.01	-12.99	46.00	22.60	0.17	10.24	Average
33	4.65	41.75	-14.25	56.00	31.30	0.20	10.25	QP
34	4.65	32.75	-13.25	46.00	22.30	0.20	10.25	Average

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 03, 2014	Sep. 25, 2014	Mar. 02, 2015	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	13dBm ~-20dBm	Mar. 03, 2014	Sep. 25, 2014	Mar. 02, 2015	Conducted (TH01-SZ)
Power Sensor	Dare	RPR3006W	TH01SZ00 019	0.3GHz~6GHz	Mar. 14, 2014	Sep. 25, 2014	Mar. 13, 2015	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 05, 2013	Oct. 02, 2014	Nov. 04, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Oct. 02, 2014	May 03, 2015	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Sep. 08, 2014	Oct. 02, 2014	Sep. 07, 2015	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 08, 2014	Oct. 02, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 08, 2014	Oct. 02, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 18, 2013	Oct. 02, 2014	Nov. 17, 2014	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Mar. 10, 2014	Oct. 02, 2014	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	Oct. 02, 2014	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A023 71	1GHz~26.5GHz	Dec. 10, 2013	Oct. 02, 2014	Dec. 09, 2014	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F1040900 04	N/A	NCR	Oct. 02, 2014	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Oct. 02, 2014	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Oct. 02, 2014	NCR	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2014	Sep. 30, 2014	May 03, 2015	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Dec. 10, 2013	Sep. 30, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Dec. 10, 2013	Sep. 30, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Nov. 12, 2013	Sep. 30, 2014	Nov. 11, 2014	Conduction (CO01-KS)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.3
--	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.5
--	-----