

FCC RF Test Report


APPLICANT : Brightstar Corporation
EQUIPMENT : Smartphone
BRAND NAME : mint
MODEL NAME : Mint 135
FCC ID : WVB135M
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Sep. 09, 2015 and testing was completed on Sep. 25, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-C-2004 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	6
1.1 Applicant.....	6
1.2 Manufacturer	6
1.3 Product Feature of Equipment Under Test	6
1.4 Product Specification subjective to this standard.....	7
1.5 Modification of EUT	7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	8
1.7 Testing Location	8
1.8 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode.....	10
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	11
3 CONDUCTED TEST RESULT.....	12
3.1 Measuring Instruments.....	12
3.2 Test Setup	12
3.3 Test Result of Conducted Test.....	12
3.4 Conducted Output Power	13
3.5 Peak-to-Average Ratio	13
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	14
3.7 Conducted Band Edge	15
3.8 Conducted Spurious Emission	16
3.9 Frequency Stability	17
4 RADIATED TEST ITEMS	18
4.1 Measuring Instruments.....	18
4.2 Test Setup	18
4.3 Test Result of Radiated Test.....	18
4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	19
4.5 Field Strength of Spurious Radiation Measurement	21
5 LIST OF MEASURING EQUIPMENT	22
6 UNCERTAINTY OF EVALUATION	23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG590902	Rev. 01	Initial issue of report	Oct. 14, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235		Within Authorized Band		



Report Section	FCC Rule	Description	Limit	Result	Remark
4.4	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
4.5	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 5.77 dB at 3760.000 MHz



1 General Description

1.1 Applicant

Brightstar Corporation

9725 NW 117th Ave.,Miami,Florida, FL 33178, United States

1.2 Manufacturer

KCMobile Co.,Ltd

#1305-1, Kolon Digital Tower Villant II , 31, Digital-ro 30-gil, Guro-Gu, Seoul, KOREA (152-727)

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Brand Name	mint
Model Name	Mint 135
FCC ID	WVB135M
EUT supports Radios application	GSM/GPRS/WCDMA/HSPA/HSPA+(Downlink only)/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0+EDR/Bluetooth v4.0 LE
IMEI Code	Conducted: 353041070004384 /353041070004392 Radiation: 353041070004368 /353041070004376 ERP&EIRP: 353041070004368 /353041070004376
HW Version	Y721_MB_V1
SW Version	Mint.135S.OC.W25.V01
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, sample 1 is dual SIM card, sample 2 is single SIM card. The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we choose dual SIM card mobile to perform all test.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx Frequency	GSM/GPRS: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM/GPRS: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM/GPRS: 850: 32.08 dBm 1900: 29.30 dBm WCDMA: Band V: 22.60 dBm Band II: 21.35 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+ : 16QAM(Downlink only)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.7639	0.0239	249KGXW
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0832	0.0299	4M16F9W
Part 24	GSM1900 GSM	GMSK	0.8868	0.0287	247KGXW
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.2122	0.0347	4M17F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH01-SZ	831040



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link	■ GSM Link
GSM 1900	■ GSM Link	■ GSM Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\
 &= 4.5 + 10 = 14.5 \text{ (dB)}
 \end{aligned}$$


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the two sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 4.2.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of the EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, peak detector, trace maximum hold.
5. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band)

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-C-2004 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-C. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

4.5 Field Strength of Spurious Radiation Measurement

4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-C-2004 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Sep. 11, 2015~ Sep. 25, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Aug. 07, 2015	Sep. 11, 2015~ Sep. 25, 2015	Aug. 06, 2016	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2015	Sep. 11, 2015	May 25, 2016	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSV40	101041	10kHz~40GHz;Ma x 30dBm	Oct. 15, 2014	Sep. 11, 2015	Oct. 14, 2015	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Nov. 07, 2014	Sep. 11, 2015	Nov. 06, 2015	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Oct. 15, 2014	Sep. 11, 2015	Oct. 14, 2015	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug.19, 2015	Sep. 11, 2015	Aug. 18, 2016	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz~3000MHz / 30 dB	Jan. 28, 2015	Sep. 11, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 05, 2015	Sep. 11, 2015	May 04, 2016	Radiation (03CH01-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 28, 2015	Sep. 11, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	61601000198 5	N/A	NCR	Sep. 11, 2015	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Sep. 11, 2015	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Sep. 11, 2015	NCR	Radiation (03CH01-SZ)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.9dB
---	-------

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.04	31.95	32.08	29.17	29.19	29.30
GPRS class 8	32.03	31.94	32.06	29.16	29.17	29.27
GPRS class 10	29.84	29.75	29.85	27.14	27.15	27.20
GPRS class 11	26.38	26.32	26.39	23.98	24.00	24.15
GPRS class 12	26.02	25.98	26.04	23.71	23.73	23.88







Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
AMR 12.2K	22.58	22.38	22.47	21.31	21.32	21.18
RMC 12.2K	22.60	22.40	22.50	21.34	21.35	21.20
HSDPA Subtest-1	20.73	20.28	20.57	19.94	18.83	18.81
HSDPA Subtest-2	20.70	20.34	20.64	19.89	18.86	18.83
HSDPA Subtest-3	20.25	19.91	20.21	19.49	18.43	18.39
HSDPA Subtest-4	20.20	19.88	20.18	19.46	18.42	18.38
HSUPA Subtest-1	20.60	20.26	20.62	20.26	19.79	19.72
HSUPA Subtest-2	19.21	18.81	19.18	19.26	18.37	18.30
HSUPA Subtest-3	20.07	19.77	20.08	20.07	19.25	19.18
HSUPA Subtest-4	19.66	19.31	19.64	19.62	18.80	18.72
HSUPA Subtest-5	19.50	19.30	19.60	19.80	18.80	18.70

Note: maximum burst average power for GSM, and maximum average power for WCDMA with SIM 1.

**Peak-to-Average Ratio**

Mode	GSM850	GSM1900	Limit: 13dB
Mod.	GSM	GSM	Result
Lowest CH	0.24	0.24	PASS
Middle CH	0.24	0.28	
Highest CH	0.24	0.24	


Mode	WCDMA Band V	WCDMA Band II	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.32	2.64	PASS
Middle CH	3.40	3.12	
Highest CH	3.32	3.08	

GSM850 (GSM)	GSM1900 (GSM)
Lowest Channel	Lowest Channel
 <p>Ref 34.5 dBm *Att 30 dB AQT 3.125 ms Offset 14.5 dB Center 824.2 MHz 2 dB/ Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 32.07 dBm Peak 32.35 dBm Crest 0.28 dB</p> <p>10 % 0.20 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.28 dB</p> <p>Date: 11.SEP.2015 16:17:15</p>	 <p>Ref 35 dBm *Att 30 dB AQT 3.125 ms Offset 15 dB Center 1.8502 GHz 2 dB/ Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 28.75 dBm Peak 28.98 dBm Crest 0.23 dB</p> <p>10 % 0.16 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.24 dB</p> <p>Date: 24.SEP.2015 23:00:55</p>
Middle Channel	Middle Channel
 <p>Ref 34.5 dBm *Att 30 dB AQT 3.125 ms Offset 14.5 dB Center 836.4 MHz 2 dB/ Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 32.06 dBm Peak 32.35 dBm Crest 0.29 dB</p> <p>10 % 0.16 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.24 dB</p> <p>Date: 11.SEP.2015 16:18:40</p>	 <p>Ref 35 dBm *Att 30 dB AQT 3.125 ms Offset 15 dB Center 1.88 GHz 2 dB/ Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 28.72 dBm Peak 28.98 dBm Crest 0.26 dB</p> <p>10 % 0.20 dB 1 % 0.24 dB .1 % 0.28 dB .01 % 0.28 dB</p> <p>Date: 24.SEP.2015 23:01:12</p>
Highest Channel	Highest Channel
 <p>Ref 34.5 dBm *Att 30 dB AQT 3.125 ms Offset 14.5 dB Center 848.8 MHz 2 dB/ Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 32.14 dBm Peak 32.35 dBm Crest 0.22 dB</p> <p>10 % 0.16 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.24 dB</p> <p>Date: 11.SEP.2015 16:19:42</p>	 <p>Ref 35 dBm *Att 30 dB AQT 3.125 ms Offset 15 dB Center 1.9098 GHz 2 dB/ Mean Pwr + 20 dB</p> <p>Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 28.76 dBm Peak 29.05 dBm Crest 0.29 dB</p> <p>10 % 0.16 dB 1 % 0.24 dB .1 % 0.24 dB .01 % 0.24 dB</p> <p>Date: 24.SEP.2015 23:01:24</p>



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 25.SEP.2015 00:51:51


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 25.SEP.2015 00:25:51

Middle Channel




Date: 25.SEP.2015 00:52:03

Middle Channel




Date: 25.SEP.2015 00:26:24

Highest Channel



Date: 25.SEP.2015 00:52:16

Highest Channel



Date: 25.SEP.2015 00:27:21

**26dB Bandwidth**


Mode	GSM850	GSM1900
Mod.	GSM	GSM
Lowest CH	0.315	0.309
Middle CH	0.309	0.306
Highest CH	0.317	0.312

Mode	WCDMA Band V	WCDMA Band II
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.66	4.71
Middle CH	4.68	4.67
Highest CH	4.66	4.68



GSM850 (GSM)


Lowest Channel



Date: 24.SEP.2015 22:28:20


GSM1900 (GSM)

Lowest Channel




Date: 24.SEP.2015 22:54:34

Middle Channel




Date: 24.SEP.2015 22:28:48

Middle Channel




Date: 24.SEP.2015 22:55:02

Highest Channel



Date: 24.SEP.2015 22:29:16

Highest Channel




Date: 24.SEP.2015 22:55:30



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 25.SEP.2015 00:47:29


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 25.SEP.2015 00:17:41

Middle Channel




Date: 25.SEP.2015 00:47:56

Middle Channel




Date: 25.SEP.2015 00:18:09

Highest Channel



Date: 25.SEP.2015 00:48:24

Highest Channel



Date: 25.SEP.2015 00:18:36


**Occupied Bandwidth**

Mode	GSM850	GSM1900
Mod.	GSM	GSM
Lowest CH	0.243	0.244
Middle CH	0.249	0.244
Highest CH	0.246	0.247

Mode	WCDMA Band V	WCDMA Band II
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.14	4.17
Middle CH	4.16	4.17
Highest CH	4.16	4.17

GSM850 (GSM)


Lowest Channel



Date: 24.SEP.2015 22:29:53


GSM1900 (GSM)

Lowest Channel




Date: 24.SEP.2015 22:56:18

Middle Channel




Date: 24.SEP.2015 22:30:21

Middle Channel




Date: 24.SEP.2015 22:56:46

Highest Channel



Date: 24.SEP.2015 22:30:49

Highest Channel




Date: 24.SEP.2015 22:57:13



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 25.SEP.2015 00:49:43


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 25.SEP.2015 00:19:22

Middle Channel




Date: 25.SEP.2015 00:50:11

Middle Channel




Date: 25.SEP.2015 00:19:50

Highest Channel



Date: 25.SEP.2015 00:50:39

Highest Channel




Date: 25.SEP.2015 00:20:18



Conducted Band Edge


GSM850 (GSM)

Lowest Band Edge



Date: 24.SEP.2015 22:32:21

Highest Band Edge




Date: 24.SEP.2015 22:33:48




GSM1900 (GSM)

Lowest Band Edge

Highest Band Edge



Date: 24.SEP.2015 22:58:59




Date: 24.SEP.2015 23:00:25




WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Date: 25.SEP.2015 00:56:17

Highest Band Edge




Date: 25.SEP.2015 01:00:14




WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge



Date: 25.SEP.2015 00:36:31

Highest Band Edge




Date: 25.SEP.2015 00:41:40



Conducted Spurious Emission

GSM850 (GSM)

Lowest Channel




Start	Stop	RBW	Freq	PwrAbs	ΔLimit
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]
30.000 M	820.000 M	1.00 M	772.595000 M	-44.26	-31.25
855.000 M	1.000 G	1.00 M	967.411258 M	-44.32	-31.32
1.000 G	3.000 G	1.00 M	1.648500 G	-38.58	-25.58
3.000 G	7.000 G	1.00 M	3.655000 G	-37.50	-24.50
7.000 G	9.000 G	1.00 M	8.231000 G	-36.92	-23.92

Date: 24.SEP.2015 22:43:30

GSM1900 (GSM)


Lowest Channel



Start	Stop	RBW	Freq	PwrAbs	ΔLimit
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]
30.000 M	1.000 G	1.00 M	819.822500 M	-43.66	-30.66
1.000 G	1.845 G	1.00 M	1.053657 G	-43.04	-30.04
1.915 G	3.000 G	1.00 M	2.985352 G	-40.87	-27.87
3.000 G	7.000 G	1.00 M	3.038000 G	-37.05	-24.05
7.000 G	13.600 G	1.00 M	12.343525 G	-35.68	-22.68
13.600 G	19.100 G	1.00 M	13.628187 G	-24.07	-11.07

Date: 24.SEP.2015 22:50:17


Middle Channel



Start	Stop	RBW	Freq	PwrAbs	ΔLimit
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]
30.000 M	820.000 M	1.00 M	612.427500 M	-44.56	-31.56
855.000 M	1.000 G	1.00 M	856.687503 M	-44.48	-31.48
1.000 G	3.000 G	1.00 M	2.988000 G	-42.91	-29.91
3.000 G	7.000 G	1.00 M	3.020000 G	-37.38	-24.38
7.000 G	9.000 G	1.00 M	8.364500 G	-33.94	-20.94

Date: 24.SEP.2015 22:44:00


Middle Channel



Start	Stop	RBW	Freq	PwrAbs	ΔLimit
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]
30.000 M	1.000 G	1.00 M	912.457500 M	-42.84	-29.84
1.000 G	1.845 G	1.00 M	1.280751 G	-43.58	-30.58
1.915 G	3.000 G	1.00 M	2.979385 G	-41.83	-28.83
3.000 G	7.000 G	1.00 M	3.037000 G	-37.43	-24.43
7.000 G	13.600 G	1.00 M	13.387850 G	-35.75	-22.75
13.600 G	19.100 G	1.00 M	13.686625 G	-24.24	-11.24

Date: 24.SEP.2015 22:50:47


Highest Channel



Start	Stop	RBW	Freq	PwrAbs	ΔLimit
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]
30.000 M	820.000 M	1.00 M	807.360500 M	-44.86	-31.86
855.000 M	1.000 G	1.00 M	864.171251 M	-44.43	-31.43
1.000 G	3.000 G	1.00 M	2.988500 G	-41.31	-28.31
3.000 G	7.000 G	1.00 M	5.942000 G	-37.28	-24.28
7.000 G	9.000 G	1.00 M	8.519000 G	-35.87	-22.87

Date: 24.SEP.2015 22:44:29

Highest Channel




Start	Stop	RBW	Freq	PwrAbs	ΔLimit
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]
30.000 M	1.000 G	1.00 M	584.597500 M	-43.68	-30.68
1.000 G	1.845 G	1.00 M	1.209983 G	-43.62	-30.62
1.915 G	3.000 G	1.00 M	2.999644 G	-41.51	-28.51
3.000 G	7.000 G	1.00 M	3.036000 G	-36.73	-23.73
7.000 G	13.600 G	1.00 M	13.336000 G	-35.40	-22.40
13.600 G	19.100 G	1.00 M	13.642625 G	-23.66	-10.66

Date: 24.SEP.2015 22:51:17



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 25.SEP.2015 00:45:44


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 25.SEP.2015 00:42:37

Middle Channel




Date: 25.SEP.2015 00:46:14

Middle Channel




Date: 25.SEP.2015 00:43:06

Highest Channel



Date: 25.SEP.2015 00:46:43

Highest Channel



Date: 25.SEP.2015 00:43:36

**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GSM)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0191	PASS
40	Normal Voltage	0.0120	
30	Normal Voltage	0.0072	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0036	
0	Normal Voltage	0.0084	
-10	Normal Voltage	0.0132	
-20	Normal Voltage	0.0179	
-30	Normal Voltage	0.0239	
20	Maximum Voltage	0.0012	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0024	

Test Conditions	Middle Channel	GSM1900 (GSM)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0179	PASS
40	Normal Voltage	0.0132	
30	Normal Voltage	0.0048	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0048	
0	Normal Voltage	0.0096	
-10	Normal Voltage	0.0155	
-20	Normal Voltage	0.0227	
-30	Normal Voltage	0.0287	
20	Maximum Voltage	0.0024	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0048	

Note:

1. Normal Voltage = 3.8V. ; Battery End Point (BEP) = 3.5 V. ; Maximum Voltage =4.2 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0036	PASS
40	Normal Voltage	0.0024	
30	Normal Voltage	0.0012	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0012	
0	Normal Voltage	0.0263	
-10	Normal Voltage	0.0275	
-20	Normal Voltage	0.0287	
-30	Normal Voltage	0.0299	
20	Maximum Voltage	0.0012	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0012	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0048	PASS
40	Normal Voltage	0.0036	
30	Normal Voltage	0.0012	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0012	
0	Normal Voltage	0.0299	
-10	Normal Voltage	0.0311	
-20	Normal Voltage	0.0335	
-30	Normal Voltage	0.0347	
20	Maximum Voltage	0.0012	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0024	

Note:

1. Normal Voltage = 3.8V. ; Battery End Point (BEP) = 3.5 V. ; Maximum Voltage =4.2 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Appendix B. Test Results of Radiated Test

ERP/EIRP

Channel	Mode	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	GSM850 GSM	27.62	0.5783	11.16	0.0131
Middle		28.23	0.6650	12.02	0.0159
Highest		28.83	0.7639	12.10	0.0162
Lowest	WCDMA Band V RMC 12.2Kbps	16.29	0.0426	-0.77	0.0008
Middle		19.20	0.0832	2.41	0.0017
Highest		19.14	0.0821	1.74	0.0015
Limit	ERP < 7W	Result		PASS	

Channel	Mode	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900 GSM	28.56	0.7173	28.94	0.7828
Middle		29.10	0.8131	29.23	0.8381
Highest		29.48	0.8868	29.33	0.8565
Lowest	WCDMA Band II RMC 12.2Kbps	22.85	0.1927	23.27	0.2122
Middle		18.02	0.0634	18.14	0.0651
Highest		18.71	0.0744	18.98	0.0790
Limit	EIRP < 2W	Result		PASS	

**Radiated Spurious Emission**

GSM850 (GSM)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-39.91	-13	-26.91	-56.49	-46.59	0.57	9.40	H
	2510	-49.44	-13	-36.44	-70.36	-57.14	0.75	10.60	H
	3346	-46.34	-13	-33.34	-71.48	-55.92	0.87	12.60	H
	1672	-32.55	-13	-19.55	-49.98	-39.23	0.57	9.40	V
	2510	-46.49	-13	-33.49	-69.98	-54.19	0.75	10.60	V
	3346	-42.73	-13	-29.73	-71.71	-52.31	0.87	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GSM)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-36.70	-13	-23.70	-68.41	-48.43	0.87	12.60	H
	5640	-42.54	-13	-29.54	-72.86	-54.57	1.07	13.10	H
	7520	-43.82	-13	-30.82	-75.48	-53.25	1.87	11.30	H
	3760	-42.36	-13	-29.36	-70.81	-54.09	0.87	12.6	V
	5640	-42.03	-13	-29.03	-73.16	-54.06	1.07	13.1	V
	7520	-43.70	-13	-30.70	-75.59	-53.13	1.87	11.3	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-44.66	-13	-31.66	-60.85	-51.34	0.57	9.40	H
	2510	-43.30	-13	-30.30	-65.45	-51.00	0.75	10.60	H
	3346	-46.77	-13	-33.77	-71.73	-56.35	0.87	12.60	H
	1672	-39.23	-13	-26.23	-56.51	-45.91	0.57	9.40	V
	2510	-35.48	-13	-22.48	-62.31	-43.18	0.75	10.60	V
	3346	-41.06	-13	-28.06	-70.98	-50.64	0.87	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band II(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-18.77	-13	-5.77	-55.52	-30.50	0.87	12.60	H
	5640	-41.88	-13	-28.88	-72.20	-53.91	1.07	13.10	H
	7520	-40.76	-13	-27.76	-72.42	-50.19	1.87	11.30	H
	3760	-26.65	-13	-13.65	-60.17	-38.38	0.87	12.6	V
	5640	-41.65	-13	-28.65	-72.78	-53.68	1.07	13.1	V
	7520	-41.19	-13	-28.19	-73.08	-50.62	1.87	11.3	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.