

FCC RF Test Report


APPLICANT : Brightstar Corporation
EQUIPMENT : Mobile Phone
BRAND NAME : Avvio
MODEL NAME : Avvio 775S/Avvio 775
FCC ID : WVBA775X
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Aug. 16, 2013 and testing was completed on Sep. 04, 2013. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	6
1.7 Testing Site	7
1.8 Applied Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration and system.....	11
2.4 Measurement Results Explanation Example	12
3 TEST RESULT.....	13
3.1 Conducted Output Power Measurement.....	13
3.2 Peak-to-Average Ratio	15
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	23
3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	29
3.5 Band Edge Measurement.....	49
3.6 Conducted Spurious Emission Measurement.....	62
3.7 Field Strength of Spurious Radiation Measurement	78
3.8 Frequency Stability Measurement.....	92
4 LIST OF MEASURING EQUIPMENT	97
5 UNCERTAINTY OF EVALUATION	98
APPENDIX A. SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG381601	Rev. 01	Initial issue of report	Sep. 17, 2013

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	Conducted Spurious Emission	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	Under limit 20.08 dB at 7520.000 MHz
3.8	§2.1055 §22.355 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

Brightstar Corporation

9725 NW 117th Ave., Miami, Florida, FL 33178, United States

1.2 Manufacturer

Konka Telecommunications Techenology co., LTD.

Overseas Chinese Town, Nanshan District, Shenzhen, China

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Avvio
Model Name	Avvio 775S/Avvio 775
FCC ID	WVBA775X
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+(Downlink Only)/WLAN 2.4GHz 802.11bgn/Bluetooth v3.0 + EDR/Bluetooth v4.0
HW Version	1.1
SW Version	KAAI120_SAPBO_Es_En_0.00.809
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two different types of EUT. They are single SIM card mobile (Model Name: Avvio 775) and dual SIM card mobile (Model Name: Avvio 775S). The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM (Model Name: Avvio 775S) was the worst, so we choose dual SIM card mobile to perform all test.
3. For dual SIM card mobile, SIM1 supports GSM and WCDMA functions, and SIM2 only supports GSM function.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GSM850 : 32.70 dBm GSM1900 : 29.58 dBm WCDMA Band V : 22.39 dBm WCDMA Band II : 22.78 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (Downlink Only)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.7362	0.02 ppm	244KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.1932	0.03 ppm	250KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0735	0.02 ppm	4M16F9W
Part 24	GSM1900 GSM	GMSK	1.9011	0.02 ppm	248KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.9036	0.02 ppm	250KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.3864	0.01 ppm	4M18F9W

1.7 Testing Site

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.		
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C. TEL: +86-755- 3320-2398		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-SZ	OTA01-SZ	831040

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	03CH01-KS		149928

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900 and WCDMA Band II.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

Note: The maximum power levels are GSM mode for GMSK link, EDGE multi-slot class 8 mode for 8PSK link, RMC 12.2Kbps mode for WCDMA band V, and RMC 12.2Kbps mode for WCDMA band II, only these modes were used for all tests.

The conducted power tables are as follows:

For SIM1 Card


Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1 Tx slot)	32.64	32.70	32.69	29.48	29.53	29.58
GPRS (GMSK, 1 Tx slot) – CS1	32.63	32.69	32.68	29.47	29.52	29.57
GPRS (GMSK, 2 Tx slots) – CS1	31.68	31.72	31.71	28.61	28.67	28.68
GPRS (GMSK, 3 Tx slots) – CS1	29.87	29.91	29.94	26.98	27.00	27.02
GPRS (GMSK, 4 Tx slots) – CS1	29.14	29.19	29.18	26.23	26.27	26.39
EDGE (GMSK, 1 Tx slot) – MCS1	32.61	32.65	32.62	29.40	29.43	29.56
EDGE (GMSK, 2 Tx slots) – MCS1	31.65	31.73	31.67	28.57	28.60	28.62
EDGE (GMSK, 3 Tx slots) – MCS1	29.89	29.88	29.93	26.91	26.95	26.98
EDGE (GMSK, 4 Tx slots) – MCS1	29.13	29.12	29.18	26.15	26.19	26.30
EDGE (8PSK, 1 Tx slot) – MCS5	26.56	26.45	26.41	25.63	25.79	25.86
EDGE (8PSK, 2 Tx slots) – MCS5	25.25	25.16	25.15	24.36	24.49	24.62
EDGE (8PSK, 3 Tx slots) – MCS5	22.94	22.80	22.80	22.16	22.31	22.50
EDGE (8PSK, 4 Tx slots) – MCS5	21.72	21.75	21.70	20.94	21.09	21.22

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880.0	1907.6
AMR	22.28	22.35	22.22	22.76	22.65	22.63
RMC 12.2K	22.31	22.39	22.28	22.78	22.72	22.64
HSDPA Subtest-1	21.30	21.37	21.33	21.79	21.72	21.62
HSDPA Subtest-2	21.32	21.39	21.35	21.83	21.74	21.64
HSDPA Subtest-3	20.92	20.96	20.92	21.34	21.28	21.20
HSDPA Subtest-4	20.91	20.99	20.89	21.33	21.27	21.18
HSUPA Subtest-1	19.62	19.68	19.65	19.62	19.69	19.98
HSUPA Subtest-2	18.68	18.75	18.72	18.68	18.77	19.04
HSUPA Subtest-3	19.69	19.74	19.70	19.62	19.71	20.01
HSUPA Subtest-4	19.18	19.23	19.17	18.63	18.72	19.00
HSUPA Subtest-5	19.59	19.58	19.60	19.60	19.67	19.96

For SIM2 Card

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM (GMSK, 1 Tx slot)	32.63	32.69	32.68	29.45	29.52	29.56
GPRS (GMSK, 1 Tx slot) – CS1	32.62	32.67	32.65	29.43	29.49	29.54
GPRS (GMSK, 2 Tx slots) – CS1	31.67	31.71	31.69	28.57	28.64	28.67
GPRS (GMSK, 3 Tx slots) – CS1	29.85	29.89	29.92	26.95	26.98	27.01
GPRS (GMSK, 4 Tx slots) – CS1	29.12	29.18	29.17	26.21	26.25	26.37
EDGE (GMSK, 1 Tx slot) – MCS1	32.60	32.64	32.61	29.38	29.41	29.54
EDGE (GMSK, 2 Tx slots) – MCS1	31.64	31.71	31.65	28.55	28.58	28.56
EDGE (GMSK, 3 Tx slots) – MCS1	29.88	29.86	29.90	26.89	26.91	26.96
EDGE (GMSK, 4 Tx slots) – MCS1	29.12	29.11	29.17	26.14	26.17	26.28
EDGE (8PSK, 1 Tx slot) – MCS5	26.55	26.43	26.40	25.61	25.75	25.84
EDGE (8PSK, 2 Tx slots) – MCS5	25.23	25.15	25.12	24.34	24.47	24.60
EDGE (8PSK, 3 Tx slots) – MCS5	22.93	22.78	22.79	22.12	22.28	22.48
EDGE (8PSK, 4 Tx slots) – MCS5	21.71	21.74	21.68	20.92	21.05	21.21

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Agilent	E5515C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 7 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 7 + 10 = 17(\text{dB})\end{aligned}$$

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band									
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)			WCDMA Band V (RMC 12.2Kbps)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8	826.4	836.4	846.6
Conducted Power (dBm)	32.64	32.70	32.69	26.56	26.45	26.41	22.31	22.39	22.28
Conducted Power (Watts)	1.84	1.86	1.86	0.45	0.44	0.44	0.17	0.17	0.17

PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Conducted Power (dBm)	29.48	29.53	29.58	25.63	25.79	25.86	22.78	22.72	22.64
Conducted Power (Watts)	0.89	0.90	0.91	0.37	0.38	0.39	0.19	0.19	0.18

Note: Maximum burst average power for GSM, and maximum average power for WCDMA.

3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
2. For GSM/EGPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
3. For UMTS operating modes:
 - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
 - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup




3.2.5 Test Result of Peak-to-Average Ratio


PCS Band									
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)			WCDMA Band II (RMC 12.2Kbps)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8	1852.4	1880	1907.6
Peak-to-Average Ratio (dB)	0.28	0.29	0.29	2.96	3.01	2.95	2.72	2.84	2.72

3.2.6 Test Result (Plots) of Peak-to-Average Ratio

Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
---------------	-----------------	--------------------	------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 31.AUG.2013 11:47:38

Peak-to-Average Ratio on Channel 661 (1880.0 MHz)


Date: 31.AUG.2013 11:46:50



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)




Date: 31.AUG.2013 11:48:10




Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
--------	----------	-------------	--------------------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 31.AUG.2013 11:53:29


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 31.AUG.2013 11:51:51




Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 31.AUG.2013 11:53:01


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------

Peak-to-Average Ratio on Channel 9262 (1852.4 MHz)



Date: 2.SEP.2013 00:36:07


Peak-to-Average Ratio on Channel 9400 (1880.0 MHz)



Date: 2.SEP.2013 00:34:48



Peak-to-Average Ratio on Channel 9538 (1907.6 MHz)



Date: 2.SEP.2013 00:34:20

3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
UMTS operating modes: Set RBW= 100 kHz, VBW= 300 kHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
 P_s (dBm) : Input power to substitution antenna.
 G_s (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
 AF (dB/m) : Receive antenna factor
 R_t : The highest received signal in spectrum analyzer for EUT.
 R_s : The highest received signal in spectrum analyzer for substitution antenna.

3.3.4 Test Setup



3.3.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-20.48	-48.12	0.00	-1.08	26.56	0.4529
836.40	-19.60	-48.28	0.00	-0.93	27.75	0.5957
848.80	-18.92	-48.35	0.00	-0.76	28.67	0.7362
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-31.49	-47.97	0.00	-1.08	15.40	0.0347
836.40	-30.40	-48.01	0.00	-0.93	16.68	0.0466
848.80	-29.55	-48.05	0.00	-0.76	17.74	0.0594

GSM850 (EDGE class 8) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-25.60	-48.12	0.00	-1.08	21.44	0.1393
836.40	-24.86	-48.28	0.00	-0.93	22.49	0.1774
848.80	-24.73	-48.35	0.00	-0.76	22.86	0.1932
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-37.50	-47.97	0.00	-1.08	9.39	0.0087
836.40	-37.12	-48.01	0.00	-0.93	9.96	0.0099
848.80	-36.37	-48.05	0.00	-0.76	10.92	0.0124

WCDMA Band V (RMC 12.2Kbps) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-29.26	-48.12	0.00	-1.08	17.78	0.0600
836.40	-28.93	-48.28	0.00	-0.93	18.42	0.0695
846.60	-28.93	-48.35	0.00	-0.76	18.66	0.0735
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
826.40	-40.14	-47.97	0.00	-1.08	6.75	0.0047
836.40	-39.61	-48.01	0.00	-0.93	7.47	0.0056
846.60	-39.64	-48.05	0.00	-0.76	7.65	0.0058

3.3.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-21.20	-51.88	0.00	1.96	32.64	1.8365
1880.00	-22.52	-52.99	0.00	2.00	32.47	1.7660
1909.80	-23.99	-54.28	0.00	1.98	32.27	1.6866
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-21.30	-52.13	0.00	1.96	32.79	1.9011
1880.00	-22.42	-53.17	0.00	2.00	32.75	1.8836
1909.80	-23.64	-54.13	0.00	1.98	32.47	1.7660

GSM1900 (EDGE class 8) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-24.98	-51.88	0.00	1.96	28.86	0.7691
1880.00	-25.56	-52.99	0.00	2.00	29.43	0.8770
1909.80	-27.14	-54.28	0.00	1.98	29.12	0.8166
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-25.20	-52.13	0.00	1.96	28.89	0.7745
1880.00	-25.61	-53.17	0.00	2.00	29.56	0.9036
1909.80	-27.17	-54.13	0.00	1.98	28.94	0.7834

WCDMA Band II (RMC 12.2Kbps) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-28.34	-51.88	0.00	1.96	25.50	0.3548
1880.00	-29.38	-52.99	0.00	2.00	25.61	0.3639
1907.60	-30.39	-54.28	0.00	1.98	25.87	0.3864
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1852.40	-28.45	-52.13	0.00	1.96	25.64	0.3664
1880.00	-29.39	-53.17	0.00	2.00	25.78	0.3784
1907.60	-30.36	-54.13	0.00	1.98	25.75	0.3758

3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



3.4.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Cellular Band						
Modes	GSM850 (GSM)			GSM850 (EDGE class 8)		
Channel	128 (Low)	189 (Mid)	251 (High)	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8	824.2	836.4	848.8
99% OBW (kHz)	244.00	244.00	242.00	244.00	250.00	244.00
26dB BW (kHz)	316.00	312.00	312.00	308.00	304.00	300.00

PCS Band						
Modes	GSM1900 (GSM)			GSM1900 (EDGE class 8)		
Channel	512 (Low)	661 (Mid)	810 (High)	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
99% OBW (kHz)	248.00	246.00	244.00	248.00	250.00	250.00
26dB BW (kHz)	302.00	314.00	312.00	314.00	310.00	318.00


Cellular Band			
Modes	WCDMA Band V (RMC 12.2Kbps)		
Channel	4132 (Low)	4182 (Mid)	4233 (High)
Frequency (MHz)	826.4	836.4	846.6
99% OBW (MHz)	4.140	4.160	4.160
26dB BW (MHz)	4.700	4.680	4.700

PCS Band			
Modes	WCDMA Band II (RMC 12.2Kbps)		
Channel	9262 (Low)	9400 (Mid)	9538 (High)
Frequency (MHz)	1852.4	1880	1907.6
99% OBW (MHz)	4.180	4.160	4.180
26dB BW (MHz)	4.720	4.720	4.740

3.4.6 Test Result (Plots) of 99% Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 850	Test Mode :	GSM Link (GMSK)
---------------	---------	--------------------	-----------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 1.SEP.2013 15:55:33


26dB Bandwidth Plot on Channel 128 (824.2 MHz)



Date: 1.SEP.2013 16:03:43


99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)


Date: 1.SEP.2013 15:53:31

26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 1.SEP.2013 16:02:35

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)



Date: 1.SEP.2013 15:56:50

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 1.SEP.2013 15:58:33




Band :	GSM 850	Test Mode :	EDGE class 8 Link (8PSK)
--------	---------	-------------	--------------------------

99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 1.SEP.2013 17:47:22

26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 1.SEP.2013 17:38:25

99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 1.SEP.2013 17:49:51

26dB Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 1.SEP.2013 17:36:17

99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 1.SEP.2013 17:52:34

26dB Bandwidth Plot on Channel 251 (848.8 MHz)




Date: 1.SEP.2013 17:35:10

Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
---------------	-----------------	--------------------	------------------------


99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)


Date: 1.SEP.2013 16:38:15

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 1.SEP.2013 16:31:26

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 1.SEP.2013 16:36:43


26dB Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 1.SEP.2013 16:29:57


99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 1.SEP.2013 16:35:16


26dB Bandwidth Plot on Channel 810 (1909.8 MHz)


Date: 1.SEP.2013 16:32:41

Band :	GSM 1900	Test Mode :	EDGE class 8 Link (8PSK)
---------------	-----------------	--------------------	---------------------------------


99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)


Date: 1.SEP.2013 17:04:24

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 1.SEP.2013 16:53:25

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 1.SEP.2013 17:00:25

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 1.SEP.2013 16:51:00

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 1.SEP.2013 16:58:31

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)




Date: 1.SEP.2013 16:55:57

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	--------------	--------------------	--------------------------

99% Occupied Bandwidth Plot on Channel 4132 (826.4 MHz)



Date: 2.SEP.2013 00:55:00

26dB Bandwidth Plot on Channel 4132 (826.4 MHz)


Date: 2.SEP.2013 00:42:18




99% Occupied Bandwidth Plot on Channel 4182 (836.4 MHz)




Date: 2.SEP.2013 00:52:44


26dB Bandwidth Plot on Channel 4182 (836.4 MHz)



Date: 2.SEP.2013 00:45:37


99% Occupied Bandwidth Plot on Channel 4233 (846.6 MHz)


Date: 2.SEP.2013 00:50:29


26dB Bandwidth Plot on Channel 4233 (846.6 MHz)


Date: 2.SEP.2013 00:44:01

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
---------------	---------------	--------------------	--------------------------


99% Occupied Bandwidth Plot on Channel 9262 (1852.4 MHz)


Date: 2.SEP.2013 01:07:55

26dB Bandwidth Plot on Channel 9262 (1852.4 MHz)



Date: 2.SEP.2013 01:19:15

99% Occupied Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 2.SEP.2013 01:10:32

26dB Bandwidth Plot on Channel 9400 (1880.0 MHz)




Date: 2.SEP.2013 01:17:17

99% Occupied Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 2.SEP.2013 01:12:49

26dB Bandwidth Plot on Channel 9538 (1907.6 MHz)



Date: 2.SEP.2013 01:15:51

3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
4. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
5. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$


3.5.4 Test Setup



3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-17.43dBm	Measurement Value :	-17.66dBm


Lower Band Edge Plot on Channel 128 (824.2 MHz)



Date: 1.SEP.2013 16:05:40

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
 2. Band Edge= Measurement Value + Correction Factor(dB)
- For example, $-17.66\text{dBm} + 0.23\text{dB} = -17.43\text{dBm}$


Band :	GSM850	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-16.90dBm	Measurement Value :	-17.13dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 1.SEP.2013 16:07:15

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.11dB	Maximum 26dB Bandwidth :	0.308MHz
Band Edge :	-20.33dBm	Measurement Value :	-20.44dBm

Lower Band Edge Plot on Channel 128 (824.2 MHz)


Date: 1.SEP.2013 17:31:57

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM850	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.11dB	Maximum 26dB Bandwidth :	0.308MHz
Band Edge :	-23.63dBm	Measurement Value :	-23.74dBm

Higher Band Edge Plot on Channel 251 (848.8 MHz)


Date: 1.SEP.2013 17:33:21

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-18.84dBm	Measurement Value :	-19.04dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 1.SEP.2013 16:39:22

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.20dB	Maximum 26dB Bandwidth :	0.314MHz
Band Edge :	-19.58dBm	Measurement Value :	-19.78dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 1.SEP.2013 16:42:24

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-24.02dBm	Measurement Value :	-24.27dBm

Lower Band Edge Plot on Channel 512 (1850.2 MHz)


Date: 1.SEP.2013 17:07:16

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	GSM1900	Test Mode :	EDGE class 8 Link (8PSK)
Correction Factor :	0.25dB	Maximum 26dB Bandwidth :	0.318MHz
Band Edge :	-26.35dBm	Measurement Value :	-26.60dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)


Date: 1.SEP.2013 17:09:22

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.700MHz
Band Edge :	-28.51dBm	Measurement Value :	-25.23dBm


Lower Band Edge Plot on Channel 4132 (826.4 MHz)


Date: 2.SEP.2013 00:57:06

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band V	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.28dB	Maximum 26dB Bandwidth :	4.700MHz
Band Edge :	-29.20dBm	Measurement Value :	-25.92dBm


Higher Band Edge Plot on Channel 4233 (846.6 MHz)



Date: 2.SEP.2013 00:59:23

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.24dB	Maximum 26dB Bandwidth :	4.740MHz
Band Edge :	-25.80dBm	Measurement Value :	-22.56dBm

Lower Band Edge Plot on Channel 9262 (1852.4 MHz)


Date: 2.SEP.2013 02:14:55

1. Correction Factor(dB)= $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

Band :	WCDMA Band II	Test Mode :	RMC 12.2Kbps Link (QPSK)
Correction Factor :	-3.24dB	Maximum 26dB Bandwidth :	4.740MHz
Band Edge :	-26.17dBm	Measurement Value :	-22.93dBm

Higher Band Edge Plot on Channel 9538 (1907.6 MHz)


Date: 2.SEP.2013 02:13:56

1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
2. Band Edge= Measurement Value + Correction Factor(dB)

3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}$$


3.6.4 Test Setup



3.6.5 Test Result (Plots) of Conducted Spurious Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link (GMSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 1.SEP.2013 16:17:14


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 1.SEP.2013 16:10:52

Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 1.SEP.2013 16:13:13


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 1.SEP.2013 16:14:37




Band :	GSM850	Channel :	CH189
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 1.SEP.2013 17:29:58


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 1.SEP.2013 17:26:56


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 1.SEP.2013 17:28:02


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 1.SEP.2013 17:28:48


Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link (GMSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 1.SEP.2013 16:19:00

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 1.SEP.2013 16:20:56

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 1.SEP.2013 16:22:52

Conducted Emission Plot between 7GHz ~ 13.6GHz


Date: 1.SEP.2013 16:26:05




Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 1.SEP.2013 16:26:37


Band :	GSM1900	Channel :	CH661
Test Mode :	EDGE class 8 Link (8PSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 1.SEP.2013 17:11:36

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 1.SEP.2013 17:13:02


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 1.SEP.2013 17:17:16

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 1.SEP.2013 17:18:19

Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz




Date: 1.SEP.2013 17:20:15




Band :	WCDMA Band V	Channel :	CH4182
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	836.4 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz




Date: 2.SEP.2013 02:05:17


Conducted Spurious Emission Plot between 1GHz ~ 3GHz



Date: 2.SEP.2013 01:44:47


Conducted Spurious Emission Plot between 3GHz ~ 7GHz


Date: 2.SEP.2013 01:47:39


Conducted Spurious Emission Plot between 7GHz ~ 9GHz


Date: 2.SEP.2013 01:49:10


Band :	WCDMA Band II	Channel :	CH9400
Test Mode :	RMC 12.2Kbps Link (QPSK)	Frequency :	1880.0 MHz

Conducted Spurious Emission Plot between 30MHz ~ 1GHz



Date: 2.SEP.2013 01:24:36

Conducted Spurious Emission Plot between 1GHz ~ 3GHz


Date: 2.SEP.2013 01:28:42

Conducted Spurious Emission Plot between 3GHz ~ 7GHz



Date: 2.SEP.2013 01:31:32

Conducted Spurious Emission Plot between 7GHz ~ 13.6GHz


Date: 2.SEP.2013 01:33:38



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 2.SEP.2013 01:38:10

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$
12. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
13. $\text{ERP (dBm)} = \text{EIRP} - 2.15$

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz



3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link (GMSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
EUT : (FG) 381601

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-33.49	-13	-20.49	-37.04	-34.81	3.41	6.88	H	Pass
2510	-45.93	-13	-32.93	-57.30	-48.79	3.86	8.87	H	Pass
3344	-51.38	-13	-38.38	-64.27	-54.71	4.72	10.20	H	Pass
4182	-45.55	-13	-32.55	-59.80	-47.96	5.04	9.60	H	Pass




Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link (GMSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
EUT : (FG) 381601

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-35.27	-13	-22.27	-41.57	-36.59	3.41	6.88	V	Pass
2508	-51.62	-13	-38.62	-63.96	-54.48	3.86	8.87	V	Pass
3344	-49.59	-13	-36.59	-63.94	-52.92	4.72	10.20	V	Pass
4182	-50.00	-13	-37.00	-64.45	-52.41	5.04	9.60	V	Pass


Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 381601

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-53.50	-13	-40.50	-56.84	-54.82	3.41	6.88	H	Pass
2508	-55.32	-13	-42.32	-65.85	-58.18	3.86	8.87	H	Pass
3344	-50.70	-13	-37.70	-63.59	-54.03	4.72	10.20	H	Pass

Band :	GSM850	Temperature :	23~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 381601

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-56.81	-13	-43.81	-62.46	-58.13	3.41	6.88	V	Pass
2508	-52.97	-13	-39.97	-64.92	-55.83	3.86	8.87	V	Pass
3344	-49.90	-13	-36.90	-64.30	-53.23	4.72	10.20	V	Pass




Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link (GMSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
EUT : (FG) 381601

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-41.00	-13	-28.00	-56.74	-45.34	5.13	9.47	H	Pass
5640	-43.06	-13	-30.06	-61.92	-45.73	6.3	8.97	H	Pass
7520	-33.08	-13	-20.08	-52.46	-32.05	7.38	6.35	H	Pass


Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link (GMSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 381601

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-40.27	-13	-27.27	-56.43	-44.61	5.13	9.47	V	Pass
5640	-43.90	-13	-30.90	-61.82	-46.57	6.3	8.97	V	Pass
7520	-35.79	-13	-22.79	-54.22	-34.76	7.38	6.35	V	Pass

Band :	GSM1900	Temperature :	23~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 381601

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-43.70	-13	-30.70	-59.29	-48.04	5.13	9.47	H	Pass
5640	-43.65	-13	-30.65	-62.53	-46.32	6.3	8.97	H	Pass
7520	-33.81	-13	-20.81	-53.22	-32.78	7.38	6.35	H	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	EDGE class 8 Link (8PSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS
Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
EUT : (FG) 381601

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-39.78	-13	-26.78	-55.93	-44.12	5.13	9.47	V	Pass
5640	-46.45	-13	-33.45	-64.11	-49.12	6.3	8.97	V	Pass
7520	-38.13	-13	-25.13	-56.63	-37.10	7.38	6.35	V	Pass




Band :	WCDMA Band V	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
EUT : (FG) 381601

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1670	-56.76	-13	-43.76	-59.93	-58.08	3.41	6.88	H	Pass
2508	-55.15	-13	-42.15	-65.68	-58.01	3.86	8.87	H	Pass
3344	-51.68	-13	-38.68	-64.57	-55.01	4.72	10.20	H	Pass


Band :	WCDMA Band V	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 381601

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-57.21	-13	-44.21	-62.81	-58.53	3.41	6.88	V	Pass
2509	-53.12	-13	-40.12	-65.08	-55.98	3.86	8.87	V	Pass
3344	-49.53	-13	-36.53	-63.87	-52.86	4.72	10.20	V	Pass


Band :	WCDMA Band II	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 HORIZONTAL
 EUT : (FG) 381601

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3762	-43.74	-13	-30.74	-59.33	-48.08	5.13	9.47	H	Pass
5640	-46.78	-13	-33.78	-65.29	-49.45	6.3	8.97	H	Pass
7520	-45.99	-13	-32.99	-64.55	-44.96	7.38	6.35	H	Pass

Band :	WCDMA Band II	Temperature :	23~24°C
Test Mode :	RMC 12.2Kbps Link (QPSK)	Relative Humidity :	43~44%
Test Engineer :	Stone Gu	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS
 Condition : FCC PART22 24 HF_EIRP_FACTOR130726 VERTICAL
 EUT : (FG) 381601

Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3758	-44.37	-13	-31.37	-60.3	-48.71	5.13	9.47	V	Pass
5640	-48.62	-13	-35.62	-65.97	-51.29	6.3	8.97	V	Pass
7520	-47.76	-13	-34.76	-65.09	-46.73	7.38	6.35	V	Pass

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.8.2 Measuring Instruments

See list of measuring instruments of this test report.


3.8.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.8.5 Test Setup



3.8.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	GSM		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	9	+0.01	-15	-0.02	PASS
-20	11	+0.01	-13	-0.02	
-10	13	+0.02	12	+0.01	
0	10	+0.01	18	+0.02	
10	8	+0.01	20	+0.02	
20	13	+0.02	23	+0.03	
30	7	+0.01	24	+0.03	
40	14	+0.02	-22	-0.03	
50	16	+0.02	-26	-0.03	
60	18	+0.02	28	+0.03	

Note: The manufacturer declared that the EUT could work properly at temperature 60°C.

Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	GSM		EDGE class 8		Result
	Freq. Dev. (Hz)	Deviation (ppm)	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-13	-0.01	-29	-0.02	PASS
-20	-12	-0.01	24	+0.01	
-10	16	+0.01	26	+0.01	
0	-22	-0.01	-30	-0.02	
10	24	+0.01	-33	-0.02	
20	23	+0.01	27	+0.01	
30	26	+0.01	-34	-0.02	
40	30	+0.02	25	+0.01	
50	34	+0.02	-27	-0.01	
60	33	+0.02	31	+0.02	

Note: The manufacturer declared that the EUT could work properly at temperature 60°C.

Band :	WCDMA Band V	Channel :	4182
Limit (ppm) :	2.5	Frequency :	836.4 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	9	+0.01	PASS
-20	6	+0.01	
-10	8	+0.01	
0	-7	-0.01	
10	-10	-0.01	
20	9	+0.01	
30	11	+0.01	
40	13	+0.02	
50	-10	-0.01	
60	14	+0.02	

Note: The manufacturer declared that the EUT could work properly at temperature 60°C.

Band :	WCDMA Band II	Channel :	9400
Limit (ppm) :	2.5	Frequency :	1880.0 MHz

Temperature (°C)	RMC 12.2Kbps		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	21	+0.01	PASS
-20	-18	-0.01	
-10	16	+0.01	
0	-23	-0.01	
10	26	+0.01	
20	20	+0.01	
30	22	+0.01	
40	-24	-0.01	
50	-26	-0.01	
60	24	+0.01	

Note: The manufacturer declared that the EUT could work properly at temperature 60°C.

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	3.8	10	+0.01	2.5	PASS
		BEP	8	+0.01		
		4.2	11	+0.01		
	EDGE class 8	3.8	20	+0.02		
		BEP	18	+0.02		
		4.2	-22	-0.03		
GSM 1900 CH661	GSM	3.8	26	+0.01		
		BEP	24	+0.01		
		4.2	-23	-0.01		
	EDGE class 8	3.8	30	+0.02		
		BEP	-29	-0.02		
		4.2	28	+0.01		
WCDMA Band V CH4182	RMC 12.2Kbps	3.8	9	+0.01		
		BEP	-8	-0.01		
		4.2	7	+0.01		
WCDMA Band II CH9400	RMC 12.2Kbps	3.8	24	+0.01		
		BEP	20	+0.01		
		4.2	-23	-0.01		

Note:

1. Normal Voltage = 3.8V.
2. Battery End Point (BEP) = 3.5 V.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 28, 2013	Aug. 31, 2013 ~ Sep. 02, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	N/A	Mar. 28, 2013	Aug. 31, 2013 ~ Sep. 02, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA2411B	1207253	N/A	Mar. 28, 2013	Aug. 31, 2013 ~ Sep. 02, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Thermal Chamber	Hongzhan	LP-150U	HD20120425	N/A	Mar. 28, 2013	Aug. 31, 2013 ~ Sep. 02, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 08, 2012	Sep. 04, 2013	Nov. 07, 2013	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	100400	9kHz~30GHz	May 23, 2013	Sep. 04, 2013	May 22, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 07, 2012	Sep. 04, 2013	Dec. 06, 2013	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2013	Sep. 04, 2013	Jan. 05, 2014	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz	May 23, 2013	Sep. 04, 2013	May 22, 2014	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 29, 2012	Sep. 04, 2013	Dec. 28, 2013	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	9170249	15GHz~40GHz	Nov. 23, 2012	Sep. 04, 2013	Nov. 22, 2013	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0 ~ 360 degree	NA	Sep. 04, 2013	NA	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m - 4 m	NA	Sep. 04, 2013	NA	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Aug. 21, 2013	Aug. 31, 2013 ~ Sep. 02, 2013	Aug. 20, 2014	ERP/EIRP (OTA01-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000 MHz	N/A	Aug. 31, 2013 ~ Sep. 02, 2013	N/A	ERP/EIRP (OTA01-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	N/A	Aug. 31, 2013 ~ Sep. 02, 2013	N/A	ERP/EIRP (OTA01-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	N/A	Aug. 31, 2013 ~ Sep. 02, 2013	N/A	ERP/EIRP (OTA01-SZ)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54
---	------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72
---	------