

# FCC RF Test Report

**APPLICANT** : Brightstar Corporation  
**EQUIPMENT** : 3G mobile phone  
**BRAND NAME** : Avvio, PULSARE, WUPA  
**MODEL NAME** : Avvio 750S, Avvio 750, PULSARE 750S,  
PULSARE 750, WUPA 750S, WUPA 750  
**FCC ID** : WVBA750X  
**STANDARD** : FCC Part 15 Subpart C §15.247  
**CLASSIFICATION** : (DTS) Digital Transmission System


The product was received on Sep. 12, 2014 and testing was completed on Sep. 26, 2014. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



---

Reviewed by: Joseph Lin / Supervisor



---

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification subjective to this standard .....	6
1.5 Modification of EUT .....	7
1.6 Testing Location .....	7
1.7 Applicable Standards.....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1 Carrier Frequency Channel .....	8
2.2 Pre-Scanned RF Power.....	9
2.3 Test Mode.....	10
2.4 Connection Diagram of Test System.....	11
2.5 Support Unit used in test configuration and system .....	12
2.6 EUT Operation Test Setup .....	12
2.7 Measurement Results Explanation Example.....	12
<b>3 TEST RESULT.....</b>	<b>13</b>
3.1 6dB Bandwidth Measurement .....	13
3.2 Output Power Measurement.....	16
3.3 Power Spectral Density Measurement .....	19
3.4 Conducted Band Edges and Spurious Emission Measurement .....	22
3.5 Radiated Band Edges and Spurious Emission Measurement .....	35
3.6 AC Conducted Emission Measurement.....	57
3.7 Antenna Requirements.....	61
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>62</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>63</b>
<b>APPENDIX A. SETUP PHOTOGRAPHS</b>	



## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR491201C	Rev. 01	Initial issue of report	Sep. 28, 2014

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.28 dB at 2483.620 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 6.85 dB at 0.320 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

# 1 General Description

## 1.1 Applicant

**Brightstar Corporation**

9725 NW 117th Ave., Miami, Florida, FL 33178, United States

## 1.2 Manufacturer

**Konka Telecommunications Techenology co., LTD.**

Overseas Chinese Town, Nanshan District, Shenzhen, China

## 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	3G mobile phone
<b>Brand Name</b>	Avvio, PULSARE, WUPA
<b>Model Name</b>	Avvio 750S, Avvio 750, PULSARE 750S, PULSARE 750, WUPA 750S, WUPA 750
<b>FCC ID</b>	WVBA750X
<b>EUT supports Radios application</b>	GSM/GPRS/EGPRS (Downlink Only)/ WCDMA/HSPA/HSPA+ (Downlink Only)/ WLAN 2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
<b>HW Version</b>	I119 TMBRf
<b>SW Version</b>	KAAI119_En_0.01.818
<b>EUT Stage</b>	Production Unit

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are six types of EUT for this project. The differences between them are summary below:

Sample List	Model name	Brand name	SIM Slots
Sample 1	Avvio 750	Avvio	1
Sample 2	Avvio 750S	Avvio	2
Sample 3	PULSARE 750	PULSARE	1
Sample 4	PULSARE 750S	PULSARE	2
Sample 5	WUPA 750	WUPA	1
Sample 6	WUPA 750S	WUPA	2

These models are identical on hardware except the SIM slots. The different model with different brand is for market purpose.

## 1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
<b>Tx/Rx Channel Frequency Range</b>	2412 MHz ~ 2462 MHz
<b>Maximum (Peak) Output Power to Antenna</b>	802.11b : 20.91 dBm (0.1233 W) 802.11g : 23.40 dBm (0.2188 W) 802.11n HT20 : 22.91 dBm (0.1954 W) 802.11n HT40 : 22.96 dBm (0.1977 W)
<b>Antenna Type / Gain</b>	PIFA Antenna with gain -1.15 dBi
<b>Type of Modulation</b>	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)



## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.		
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		
	TH01-KS	03CH01-KS	CO01-KS
	<b>FCC Registration No.</b>		
	149928		

**Note:** The test site complies with ANSI C63.4 2003 requirement.

## 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ANSI C63.4-2003

### **Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-



## 2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	20.16	CH 11	20.67	20.73	20.89
CH 06	2437 MHz	19.84				
CH 11	2462 MHz	20.91				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
		6Mbps								
CH 01	2412 MHz	22.98	CH 06	23.04	23.12	23.11	23.32	23.38	23.24	23.26
CH 06	2437 MHz	23.40								
CH 11	2462 MHz	23.09								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 01	2412 MHz	22.70	CH 11	22.35	22.33	22.42	22.16	22.09	22.22	22.15
CH 06	2437 MHz	22.81								
CH 11	2462 MHz	22.91								


2.4GHz 802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 03	2422 MHz	22.66	CH 09	21.49	21.07	21.10	21.22	21.48	21.24	21.55
CH 06	2437 MHz	22.94								
CH 09	2452 MHz	22.96								

## 2.3 Test Mode


Test Cases				
Conducted TCs	Test Items	Mode	Data Rate	Test Channel
	6dB BW Power Spectral Density	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Output Power	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
	Conducted Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Conducted Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
Radiated TCs	Radiated Band Edge	802.11b	1 Mbps	1/11
		802.11g	6 Mbps	1/11
		802.11n HT20	MCS0	1/11
		802.11n HT40	MCS0	3/9
	Radiated Spurious Emission	802.11b	1 Mbps	1/6/11
		802.11g	6 Mbps	1/6/11
		802.11n HT20	MCS0	1/6/11
		802.11n HT40	MCS0	3/6/9
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone + Battery			
Remark: For radiated TCs, the tests were performed with adapter, battery, earphone and USB cable.				

## 2.4 Connection Diagram of Test System

### <WLAN Tx Mode>



### <AC Conducted Emission Mode>



## 2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH505	N/A	N/A	N/A

## 2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

## 2.7 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 6 dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 6 \text{ (dB)}\end{aligned}$$

### 3 Test Result

#### 3.1 6dB Bandwidth Measurement

##### 3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


##### 3.1.4 Test Setup



**3.1.5 Test Result of 6dB Occupied Bandwidth**

<b>Test Band :</b>	2.4GHz	<b>Temperature :</b>	24~25°C
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Mod.	Data Rate	N <sub>TX</sub>	Channel	Freq. (MHz)	6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	9.98	0.50	Pass
11b	1Mbps	1	6	2437	10.04	0.50	Pass
11b	1Mbps	1	11	2462	10.02	0.50	Pass
11g	6Mbps	1	1	2412	15.10	0.50	Pass
11g	6Mbps	1	6	2437	15.46	0.50	Pass
11g	6Mbps	1	11	2462	15.14	0.50	Pass
HT20	MCS0	1	1	2412	17.60	0.50	Pass
HT20	MCS0	1	6	2437	17.60	0.50	Pass
HT20	MCS0	1	11	2462	17.60	0.50	Pass
HT40	MCS0	1	3	2422	35.92	0.50	Pass
HT40	MCS0	1	6	2437	35.84	0.50	Pass
HT40	MCS0	1	9	2452	36.04	0.50	Pass



**Note:** The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.2 Output Power Measurement

### 3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.

### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

### 3.2.4 Test Setup





**3.2.5 Test Result of Peak Output Power**

<b>Test Mode :</b>	2.4GHz	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Mod.	Data Rate	N <sub>TX</sub>	Channel	Freq. (MHz)	RF Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	20.16	30.00	-1.15	Pass
11b	1Mbps	1	6	2437	19.84	30.00	-1.15	Pass
11b	1Mbps	1	11	2462	20.91	30.00	-1.15	Pass
11g	6Mbps	1	1	2412	22.98	30.00	-1.15	Pass
11g	6Mbps	1	6	2437	23.40	30.00	-1.15	Pass
11g	6Mbps	1	11	2462	23.09	30.00	-1.15	Pass
HT20	MCS0	1	1	2412	22.70	30.00	-1.15	Pass
HT20	MCS0	1	6	2437	22.81	30.00	-1.15	Pass
HT20	MCS0	1	11	2462	22.91	30.00	-1.15	Pass
HT40	MCS0	1	3	2422	22.66	30.00	-1.15	Pass
HT40	MCS0	1	6	2437	22.94	30.00	-1.15	Pass
HT40	MCS0	1	9	2452	22.96	30.00	-1.15	Pass

**Note:** Measured power (dBm) has offset with cable loss.

**3.2.6 Test Result of Average output Power (Reporting Only)**

<b>Test Mode :</b>	2.4GHz	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Mod.	Data Rate	N <sub>TX</sub>	Channel	Freq. (MHz)	Duty Factor (dB)	Average Output Power (dBm)	Power Limit (dBm)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	0.08	17.53	30.00	-1.15	Pass
11b	1Mbps	1	6	2437	0.08	16.97	30.00	-1.15	Pass
11b	1Mbps	1	11	2462	0.08	18.06	30.00	-1.15	Pass
11g	6Mbps	1	1	2412	0.50	13.42	30.00	-1.15	Pass
11g	6Mbps	1	6	2437	0.50	13.85	30.00	-1.15	Pass
11g	6Mbps	1	11	2462	0.50	13.52	30.00	-1.15	Pass
HT20	MCS0	1	1	2412	0.56	11.98	30.00	-1.15	Pass
HT20	MCS0	1	6	2437	0.56	12.02	30.00	-1.15	Pass
HT20	MCS0	1	11	2462	0.56	12.24	30.00	-1.15	Pass
HT40	MCS0	1	3	2422	1.02	10.82	30.00	-1.15	Pass
HT40	MCS0	1	6	2437	1.02	11.00	30.00	-1.15	Pass
HT40	MCS0	1	9	2452	1.02	11.27	30.00	-1.15	Pass

**Note:** Measured power (dBm) has offset with cable loss and duty factor.

### 3.3 Power Spectral Density Measurement

#### 3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup




### 3.3.5 Test Result of Power Spectral Density

<b>Test Mode :</b>	2.4GHz	<b>Temperature :</b>	24~25℃
<b>Test Engineer :</b>	Issac Song	<b>Relative Humidity :</b>	49~51%

Mod.	Data Rate	N <sub>TX</sub>	Channel	Freq. (MHz)	Peak Power Density (dBm/3kHz)	Max. Limits (dBm/3kHz)	DG (dBi)	Pass/Fail
11b	1Mbps	1	1	2412	-6.78	8.00	-1.15	Pass
11b	1Mbps	1	6	2437	-3.66	8.00	-1.15	Pass
11b	1Mbps	1	11	2462	-5.93	8.00	-1.15	Pass
11g	6Mbps	1	1	2412	-11.49	8.00	-1.15	Pass
11g	6Mbps	1	6	2437	-9.73	8.00	-1.15	Pass
11g	6Mbps	1	11	2462	-13.93	8.00	-1.15	Pass
HT20	MCS0	1	1	2412	-15.19	8.00	-1.15	Pass
HT20	MCS0	1	6	2437	-14.20	8.00	-1.15	Pass
HT20	MCS0	1	11	2462	-14.59	8.00	-1.15	Pass
HT40	MCS0	1	3	2422	-19.27	8.00	-1.15	Pass
HT40	MCS0	1	6	2437	-19.42	8.00	-1.15	Pass
HT40	MCS0	1	9	2452	-18.76	8.00	-1.15	Pass

**Note:** Measured power density (dBm) has offset with cable loss.



### **3.4 Conducted Band Edges and Spurious Emission Measurement**

#### **3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement**

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


#### **3.4.2 Measuring Instruments**

The measuring equipment is listed in the section 4 of this test report.

#### **3.4.3 Test Procedures**

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

#### **3.4.4 Test Setup**






## 3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


## WLAN 802.11b Channel 01

## 100kHz PSD reference Level




Date: 26.SEP.2014 00:28:46

## Low Channel Plot




Date: 26.SEP.2014 00:29:09

## Spurious Emission 30MHz~3GHz



Date: 26.SEP.2014 00:42:31


## Spurious Emission 2GHz~25GHz




Date: 26.SEP.2014 00:42:49




Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song

**WLAN 802.11b Channel 06****100kHz PSD reference Level**

Date: 26.SEP.2014 00:35:44

**Spurious Emission 30MHz~3GHz**

Date: 26.SEP.2014 00:38:48


**Spurious Emission 2GHz~25GHz**

Date: 26.SEP.2014 00:39:06







Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song

**WLAN 802.11b Channel 11****100kHz PSD reference Level**


Date: 26.SEP.2014 00:46:28

**High Channel Plot**

Date: 26.SEP.2014 00:46:46

**Spurious Emission 30MHz~3GHz**


Date: 26.SEP.2014 00:47:15

**Spurious Emission 2GHz~25GHz**


Date: 26.SEP.2014 00:47:34




Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song

**WLAN 802.11g Channel 01****100kHz PSD reference Level**


Date: 26.SEP.2014 00:51:49

**Low Channel Plot**

Date: 26.SEP.2014 00:52:16

**Spurious Emission 30MHz~3GHz**

Date: 26.SEP.2014 00:52:39


**Spurious Emission 2GHz~25GHz**

Date: 26.SEP.2014 00:52:57

<b>Test Mode :</b>	802.11g	<b>Temperature :</b>	24~25℃
<b>Test Band :</b>	2.4GHz Mid	<b>Relative Humidity :</b>	49~51%
<b>Test Channel :</b>	06	<b>Test Engineer :</b>	Issac Song


## WLAN 802.11g Channel 06

### 100kHz PSD reference Level




Date: 26.SEP.2014 00:56:18

## Spurious Emission 30MHz~3GHz



Date: 26.SEP.2014 00:57:07


## Spurious Emission 2GHz~25GHz




Date: 26.SEP.2014 00:57:26




Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song

**WLAN 802.11g Channel 11****100kHz PSD reference Level**


Date: 26.SEP.2014 01:00:34

**High Channel Plot**

Date: 26.SEP.2014 01:00:54

**Spurious Emission 30MHz~3GHz**


Date: 26.SEP.2014 01:01:25

**Spurious Emission 2GHz~25GHz**


Date: 26.SEP.2014 01:01:44




Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song

**WLAN 802.11n HT20 Channel 01****100kHz PSD reference Level**


Date: 26.SEP.2014 01:09:15

**Low Channel Plot**

Date: 26.SEP.2014 01:09:32

**Spurious Emission 30MHz~3GHz**


Date: 26.SEP.2014 01:10:21

**Spurious Emission 2GHz~25GHz**


Date: 26.SEP.2014 01:10:40




Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song

**WLAN 802.11n HT20 Channel 06****100kHz PSD reference Level**

Date: 26.SEP.2014 01:14:44

**Spurious Emission 30MHz~3GHz**

Date: 26.SEP.2014 01:15:07

**Spurious Emission 2GHz~25GHz**


Date: 26.SEP.2014 01:15:26



Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song


## WLAN 802.11n HT20 Channel 11

## 100kHz PSD reference Level




Date: 26.SEP.2014 01:19:31

## High Channel Plot




Date: 26.SEP.2014 01:19:59

## Spurious Emission 30MHz~3GHz



Date: 26.SEP.2014 01:20:33

## Spurious Emission 2GHz~25GHz




Date: 26.SEP.2014 01:20:52



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	03	Test Engineer :	Issac Song


## WLAN 802.11n HT40 Channel 03

## 100kHz PSD reference Level




Date: 26.SEP.2014 01:29:05

## Low Channel Plot




Date: 26.SEP.2014 01:29:32

## Spurious Emission 30MHz~3GHz



Date: 26.SEP.2014 01:35:20

## Spurious Emission 2GHz~25GHz




Date: 26.SEP.2014 01:31:14







Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song

**WLAN 802.11n HT40 Channel 06****100kHz PSD reference Level**

Date: 26.SEP.2014 02:05:01

**Spurious Emission 30MHz~3GHz**

Date: 26.SEP.2014 02:08:16

**Spurious Emission 2GHz~25GHz**


Date: 26.SEP.2014 02:06:43



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	09	Test Engineer :	Issac Song


## WLAN 802.11n HT40 Channel 09

## 100kHz PSD reference Level




Date: 26.SEP.2014 02:13:27

## High Channel Plot




Date: 26.SEP.2014 02:13:59

## Spurious Emission 30MHz~3GHz



Date: 26.SEP.2014 02:17:48

## Spurious Emission 2GHz~25GHz



Date: 26.SEP.2014 02:15:55

### 3.5 Radiated Band Edges and Spurious Emission Measurement

#### 3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f \geq 1$  GHz for peak measurement.


For average measurement:

  - VBW = 10 Hz, when duty cycle is no less than 98 percent.
  - VBW  $\geq 1/T$ , when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	98.13	-	-	10Hz
802.11g	89.17	1.400	0.714	1kHz
2.4GHz 802.11n HT20	88.96	1.306	0.766	1kHz
2.4GHz 802.11n HT40	79.13	0.652	1.534	3kHz

### 3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



### 3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

### 3.5.6 Test Result of Radiated Spurious at Band Edges

<b>Test Mode :</b>	802.11b	<b>Temperature :</b>	22~23°C
<b>Test Band :</b>	Low	<b>Relative Humidity :</b>	42~43%
<b>Test Channel :</b>	01	<b>Test Engineer :</b>	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.56	58.88	-15.12	74	55.69	32.86	3.59	33.26	192	0	Peak
2387.22	45.12	-8.88	54	41.93	32.86	3.59	33.26	192	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2387.94	55.51	-18.49	74	52.32	32.86	3.59	33.26	100	34	Peak
2387.13	40.12	-13.88	54	36.93	32.86	3.59	33.26	100	34	Average

<b>Test Mode :</b>	802.11b	<b>Temperature :</b>	22~23°C
<b>Test Band :</b>	High	<b>Relative Humidity :</b>	42~43%
<b>Test Channel :</b>	11	<b>Test Engineer :</b>	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2495.98	59.5	-14.5	74	56.09	33.05	3.66	33.3	184	0	Peak
2486.11	43.91	-10.09	54	40.54	33.01	3.65	33.29	184	0	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2485.33	53.34	-20.66	74	49.97	33.01	3.65	33.29	100	46	Peak
2483.5	38.47	-15.53	54	35.1	33.01	3.65	33.29	100	46	Average



Test Mode :	802.11g	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2388.75	66.47	-7.53	74	63.28	32.86	3.59	33.26	100	61	Peak
2389.92	46.81	-7.19	54	43.62	32.86	3.59	33.26	100	61	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2387.94	63.67	-10.33	74	60.48	32.86	3.59	33.26	100	131	Peak
2389.74	42.36	-11.64	54	39.17	32.86	3.59	33.26	100	131	Average

Test Mode :	802.11g	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.5	69.47	-4.53	74	66.1	33.01	3.65	33.29	100	247	Peak
2483.56	46.04	-7.96	54	42.67	33.01	3.65	33.29	100	247	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2483.62	69.72	-4.28	74	66.35	33.01	3.65	33.29	100	90	Peak
2483.59	43.45	-10.55	54	40.08	33.01	3.65	33.29	100	90	Average





Test Mode :	802.11n HT20	Temperature :	22~23°C
Test Band :	Low	Relative Humidity :	42~43%
Test Channel :	01	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.74	67.48	-6.52	74	64.29	32.86	3.59	33.26	100	358	Peak
2389.83	46.22	-7.78	54	43.03	32.86	3.59	33.26	100	356	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.65	60.4	-13.6	74	57.21	32.86	3.59	33.26	100	61	Peak
2389.92	42.11	-11.89	54	38.92	32.86	3.59	33.26	100	61	Average

Test Mode :	802.11n HT20	Temperature :	22~23°C
Test Band :	High	Relative Humidity :	42~43%
Test Channel :	11	Test Engineer :	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2484.22	68.33	-5.67	74	64.96	33.01	3.65	33.29	100	174	Peak
2483.65	45.3	-8.7	54	41.93	33.01	3.65	33.29	100	174	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2486.71	62.42	-11.58	74	59.05	33.01	3.65	33.29	124	264	Peak
2484.07	41.74	-12.26	54	38.37	33.01	3.65	33.29	124	264	Average



<b>Test Mode :</b>	802.11n HT40	<b>Temperature :</b>	22~23°C
<b>Test Band :</b>	Low	<b>Relative Humidity :</b>	42~43%
<b>Test Channel :</b>	03	<b>Test Engineer :</b>	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.02	61.35	-12.65	74	58.16	32.86	3.59	33.26	100	121	Peak
2388.84	45	-9	54	41.81	32.86	3.59	33.26	100	121	Average
2483.98	57.34	-16.66	74	53.97	33.01	3.65	33.29	100	12	Peak
2483.74	39.58	-14.42	54	36.21	33.01	3.65	33.29	100	12	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2388.03	56.2	-17.8	74	53.01	32.86	3.59	33.26	100	21	Peak
2388.48	43.07	-10.93	54	39.88	32.86	3.59	33.26	100	21	Average
2484.67	53.98	-20.02	74	50.61	33.01	3.65	33.29	100	49	Peak
2483.8	36.5	-17.5	54	33.13	33.01	3.65	33.29	100	49	Average



<b>Test Mode :</b>	802.11n HT40	<b>Temperature :</b>	22~23°C
<b>Test Band :</b>	High	<b>Relative Humidity :</b>	42~43%
<b>Test Channel :</b>	09	<b>Test Engineer :</b>	Star Wei

ANTENNA POLARITY : HORIZONTAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2389.11	57.97	-16.03	74	54.78	32.86	3.59	33.26	100	0	Peak
2388.84	40.22	-13.78	54	37.03	32.86	3.59	33.26	100	0	Average
2490.13	68.86	-5.14	74	65.45	33.05	3.66	33.3	100	350	Peak
2483.5	44.76	-9.24	54	41.39	33.01	3.65	33.29	100	350	Average

ANTENNA POLARITY : VERTICAL										
Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2384.7	56.67	-17.33	74	53.52	32.83	3.58	33.26	200	79	Peak
2389.92	38.87	-15.13	54	35.68	32.86	3.59	33.26	200	79	Average
2490.4	63.69	-10.31	74	60.28	33.05	3.66	33.3	100	239	Peak
2490.46	40.82	-13.18	54	37.41	33.05	3.66	33.3	100	239	Average

### 3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)

**Note:** Pre-scanned all test modes and only choose the worst case mode recorded in the test report for radiated spurious emission below 1GHz.

<b>Test Mode :</b>	802.11b	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2412	111.28	-	-	108.05	32.89	3.61	33.27	159	2	Peak
2412	105.1	-	-	101.87	32.89	3.61	33.27	159	2	Average
4824	45.69	-28.31	74	39.07	35.17	5.25	33.8	100	154	Peak

<b>Test Mode :</b>	802.11b	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2412	106.19	-	-	102.96	32.89	3.61	33.27	197	308	Peak
2412	100.21	-	-	96.98	32.89	3.61	33.27	197	308	Average
4824	46.73	-27.27	74	40.11	35.17	5.25	33.8	100	32	Peak

<b>Test Mode :</b>	802.11b	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2437	110.75	-	-	107.45	32.95	3.63	33.28	159	18	Peak
2437	104.36	-	-	101.06	32.95	3.63	33.28	159	18	Average
4874	46.15	-27.85	74	39.49	35.18	5.28	33.8	100	154	Peak
7312	47.62	-26.38	74	38.94	36.2	6.61	34.13	166	59	Peak

<b>Test Mode :</b>	802.11b	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2437	107.36	-	-	104.06	32.95	3.63	33.28	100	32	Peak
2437	101.15	-	-	97.85	32.95	3.63	33.28	100	32	Average
4874	45.62	-28.38	74	38.96	35.18	5.28	33.8	184	21	Peak
7312	47.98	-26.02	74	39.3	36.2	6.61	34.13	100	25	Peak

<b>Test Mode :</b>	802.11b	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2462	111.64	-	-	108.31	32.98	3.64	33.29	184	176	Peak
2462	105.36	-	-	102.03	32.98	3.64	33.29	184	176	Average
4924	45.32	-28.68	74	38.62	35.19	5.31	33.8	100	263	Peak
7386	48.68	-25.32	74	39.9	36.24	6.7	34.16	100	255	Peak

<b>Test Mode :</b>	802.11b	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2462	106.08	-	-	102.75	32.98	3.64	33.29	100	30	Peak
2462	99.6	-	-	96.27	32.98	3.64	33.29	100	30	Average
4924	45.1	-28.9	74	38.4	35.19	5.31	33.8	100	78	Peak
7386	48.34	-25.66	74	39.56	36.24	6.7	34.16	122	125	Peak



<b>Test Mode :</b>	802.11g	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2412	106.79	-	-	103.56	32.89	3.61	33.27	100	57	Peak
2412	96.37	-	-	93.14	32.89	3.61	33.27	100	57	Average
4824	44.95	-29.05	74	38.33	35.17	5.25	33.8	100	152	Peak

<b>Test Mode :</b>	802.11g	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2412	104.43	-	-	101.2	32.89	3.61	33.27	100	30	Peak
2412	93.29	-	-	90.06	32.89	3.61	33.27	100	30	Average
4824	44.61	-29.39	74	37.99	35.17	5.25	33.8	100	261	Peak

<b>Test Mode :</b>	802.11g	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2437	107.31	-	-	104.01	32.95	3.63	33.28	100	57	Peak
2437	96.57	-	-	93.27	32.95	3.63	33.28	100	57	Average
4874	44.18	-29.82	74	37.52	35.18	5.28	33.8	100	184	Peak
7312	48.26	-25.74	74	39.58	36.2	6.61	34.13	166	320	Peak

<b>Test Mode :</b>	802.11g	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2437	105.46	-	-	102.16	32.95	3.63	33.28	100	35	Peak
2437	94.68	-	-	91.38	32.95	3.63	33.28	100	35	Average
4874	44.64	-29.36	74	37.98	35.18	5.28	33.8	100	85	Peak
7312	48.15	-25.85	74	39.47	36.2	6.61	34.13	174	85	Peak





<b>Test Mode :</b>	802.11g	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
157.07	27.26	-16.24	43.5	49.99	9.71	1.14	33.58	100	148	Peak
250.19	22.09	-23.91	46	42.08	12	1.45	33.44	-	-	Peak
326.82	18.83	-27.17	46	36.71	13.84	1.65	33.37	-	-	Peak
478.14	17.72	-28.28	46	32.05	16.83	2	33.16	-	-	Peak
584.84	18.77	-27.23	46	30.97	18.57	2.2	32.97	-	-	Peak
699.3	17.24	-28.76	46	28.44	19.29	2.39	32.88	-	-	Peak
2462	108.03	-	-	104.7	32.98	3.64	33.29	100	20	Peak
2462	97.45	-	-	94.12	32.98	3.64	33.29	100	20	Average
4924	44.56	-29.44	74	37.86	35.19	5.31	33.8	100	114	Peak
7386	47.64	-26.36	74	38.86	36.24	6.7	34.16	184	56	Peak



<b>Test Mode :</b>	802.11g	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
34.85	26.99	-13.01	40	44.96	15.1	0.54	33.61	166	20	Peak
159.98	19.31	-24.19	43.5	42.13	9.6	1.16	33.58	-	-	Peak
246.31	15.49	-30.51	46	35.65	11.84	1.45	33.45	-	-	Peak
450.01	21.8	-24.2	46	36.76	16.3	1.95	33.21	-	-	Peak
567.38	22.3	-23.7	46	34.59	18.53	2.18	33	-	-	Peak
800.18	20.99	-25.01	46	31.2	19.85	2.56	32.62	-	-	Peak
2462	104.93	-	-	101.6	32.98	3.64	33.29	100	45	Peak
2462	94.51	-	-	91.18	32.98	3.64	33.29	100	45	Average
4924	44.99	-29.01	74	38.29	35.19	5.31	33.8	195	220	Peak
7386	48.67	-25.33	74	39.89	36.24	6.7	34.16	144	120	Peak



<b>Test Mode :</b>	2.4GHz 802.11n HT20	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2412	104.7	-	-	101.47	32.89	3.61	33.27	100	0	Peak
2412	93.52	-	-	90.29	32.89	3.61	33.27	100	0	Average
4824	45.22	-28.78	74	38.6	35.17	5.25	33.8	148	59	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT20	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	01	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2412 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2412	101.61	-	-	98.38	32.89	3.61	33.27	100	44	Peak
2412	90.66	-	-	87.43	32.89	3.61	33.27	100	44	Average
4824	44.56	-29.44	74	37.94	35.17	5.25	33.8	133	26	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT20	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2437	104.53	-	-	101.23	32.95	3.63	33.28	100	16	Peak
2437	93.38	-	-	90.08	32.95	3.63	33.28	100	16	Average
4874	44.05	-29.95	74	37.39	35.18	5.28	33.8	100	26	Peak
7312	47.5	-26.5	74	38.82	36.2	6.61	34.13	166	29	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT20	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2437	103.58	-	-	100.28	32.95	3.63	33.28	100	39	Peak
2437	92.09	-	-	88.79	32.95	3.63	33.28	100	39	Average
4874	44.97	-29.03	74	38.31	35.18	5.28	33.8	120	118	Peak
7312	47.97	-26.03	74	39.29	36.2	6.61	34.13	184	47	Peak



<b>Test Mode :</b>	2.4GHz 802.11n HT20	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2462	105.49	-	-	102.16	32.98	3.64	33.29	100	356	Peak
2462	94.3	-	-	90.97	32.98	3.64	33.29	100	356	Average
4924	44.28	-29.72	74	37.58	35.19	5.31	33.8	100	184	Peak
7386	48.01	-25.99	74	39.23	36.24	6.7	34.16	199	52	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT20	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	11	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2462 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2462	101.13	-	-	97.8	32.98	3.64	33.29	100	43	Peak
2462	89.86	-	-	86.53	32.98	3.64	33.29	100	43	Average
4924	45.08	-28.92	74	38.38	35.19	5.31	33.8	100	85	Peak
7386	48.19	-25.81	74	39.41	36.24	6.7	34.16	100	196	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT40	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	03	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2422 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2422	101.86	-	-	98.6	32.92	3.62	33.28	100	353	Peak
2422	91.68	-	-	88.42	32.92	3.62	33.28	100	353	Average
4844	44.43	-29.57	74	37.79	35.18	5.26	33.8	100	0	Peak
7266	47.26	-26.74	74	38.62	36.19	6.56	34.11	100	62	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT40	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	03	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2422 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2422	96.56	-	-	93.3	32.92	3.62	33.28	100	44	Peak
2422	85.67	-	-	82.41	32.92	3.62	33.28	100	44	Average
4844	44.56	-29.44	74	37.92	35.18	5.26	33.8	100	85	Peak
7266	48.1	-25.9	74	39.46	36.19	6.56	34.11	103	215	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT40	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2437	101.81	-	-	98.51	32.95	3.63	33.28	100	353	Peak
2437	90.65	-	-	87.35	32.95	3.63	33.28	100	353	Average
4874	44.32	-29.68	74	37.66	35.18	5.28	33.8	102	115	Peak
7312	48.5	-25.5	74	39.82	36.2	6.61	34.13	100	111	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT40	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	06	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2437 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2437	99.31	-	-	96.01	32.95	3.63	33.28	100	46	Peak
2437	88.27	-	-	84.97	32.95	3.63	33.28	100	46	Average
4844	44.56	-29.44	74	37.92	35.18	5.26	33.8	100	59	Peak
7312	47.08	-26.92	74	38.4	36.2	6.61	34.13	133	263	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT40	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	09	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	1. 2452 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2452	101.97	-	-	98.67	32.95	3.63	33.28	100	0	Peak
2452	91.11	-	-	87.81	32.95	3.63	33.28	100	0	Average
4904	44.3	-29.7	74	37.61	35.19	5.3	33.8	100	148	Peak
7356	47.69	-26.31	74	38.96	36.22	6.66	34.15	133	296	Peak

<b>Test Mode :</b>	2.4GHz 802.11n HT40	<b>Temperature :</b>	22~23°C
<b>Test Channel :</b>	09	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Star Wei	<b>Polarization :</b>	Vertical
<b>Remark :</b>	1. 2452 MHz is fundamental signal which can be ignored. 2. Average measurement was not performed if peak level went lower than the average limit.		

Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level (dBμV)	Antenna Factor ( dB )	Cable Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Remark
2452	96.41	-	-	93.11	32.95	3.63	33.28	100	48	Peak
2452	86.04	-	-	82.74	32.95	3.63	33.28	100	48	Average
4904	44.75	-29.25	74	38.06	35.19	5.3	33.8	114	85	Peak
7356	47.95	-26.05	74	39.22	36.22	6.66	34.15	100	203	Peak



### 3.6 AC Conducted Emission Measurement

#### 3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


### 3.6.4 Test Setup





## 3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	55~58%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone + Battery		




Site : CO01-KS  
Condition : FCC PART 15C LISN-L20140306 LINE

mode	: Mode 1							
	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz		Limit	Line	Level	Factor	Loss	
			dB			dB	dB	
1	0.32	48.31	-11.35	59.66	37.40	0.56	10.35	QP
2	0.32	42.81	-6.85	49.66	31.90	0.56	10.35	Average
3	0.40	34.90	-23.00	57.90	24.30	0.32	10.28	QP
4	0.40	27.90	-20.00	47.90	17.30	0.32	10.28	Average
5	0.44	39.74	-17.41	57.15	29.20	0.27	10.27	QP
6	0.44	34.44	-12.71	47.15	23.90	0.27	10.27	Average
7	0.60	39.74	-16.26	56.00	29.30	0.20	10.24	QP
8	0.60	33.54	-12.46	46.00	23.10	0.20	10.24	Average
9	0.66	38.72	-17.28	56.00	28.30	0.20	10.22	QP
10	0.66	31.02	-14.98	46.00	20.60	0.20	10.22	Average
11	0.87	37.12	-18.88	56.00	26.80	0.13	10.19	QP
12	0.87	29.42	-16.58	46.00	19.10	0.13	10.19	Average



Test Mode :	Mode 1	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	55~58%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + USB Cable (Charging from Adapter) + Earphone + Battery		



Site : CO01-KS  
Condition : FCC PART 15C LISN-N20140306 NEUTRAL

mode		: Mode 1									
	Freq	Level	Over	Limit	Read	LISN	Cable				
	MHz		Limit	Line	Level	Factor	Loss	Remark			
			dB			dB	dB				
1	0.32	45.28	-14.43	59.71	34.30	0.62	10.36	QP			
2	0.32	38.18	-11.53	49.71	27.20	0.62	10.36	Average			
3	0.34	45.79	-13.52	59.31	34.90	0.55	10.34	QP			
4	0.34	38.19	-11.12	49.31	27.30	0.55	10.34	Average			
5	0.44	38.23	-18.84	57.07	27.61	0.35	10.27	QP			
6	0.44	33.93	-13.14	47.07	23.31	0.35	10.27	Average			
7	0.60	35.78	-20.22	56.00	25.30	0.24	10.24	QP			
8	0.60	30.78	-15.22	46.00	20.30	0.24	10.24	Average			
9	1.25	37.88	-18.12	56.00	27.60	0.10	10.18	QP			
10	1.25	29.68	-16.32	46.00	19.40	0.10	10.18	Average			
11	1.52	38.89	-17.11	56.00	28.60	0.10	10.19	QP			
12	1.52	30.89	-15.11	46.00	20.60	0.10	10.19	Average			



## **3.7 Antenna Requirements**

### **3.7.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **3.7.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.7.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 28, 2013	Sep. 26, 2014	Dec. 27, 2014	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	30MHz~40GHz	Feb. 27, 2014	Sep. 26, 2014	Feb. 26, 2015	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Feb. 27, 2014	Sep. 26, 2014	Feb. 26, 2015	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 05, 2013	Sep. 23, 2014	Nov. 04, 2014	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Sep. 23, 2014	May 03, 2015	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 09, 2013	Sep. 23, 2014	Oct. 08, 2014	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Jan. 08, 2014	Sep. 23, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 08, 2014	Sep. 23, 2014	Jan. 07, 2015	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 18, 2013	Sep. 23, 2014	Nov. 17, 2014	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 10, 2014	Sep. 23, 2014	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161073	1MHz~1GHz	May 04, 2014	Sep. 23, 2014	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Dec. 10, 2013	Sep. 23, 2014	Dec. 09, 2014	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Sep. 23, 2014	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Sep. 23, 2014	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Sep. 23, 2014	NCR	Radiation (03CH01-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 04, 2014	Sep. 18, 2014	May 03, 2015	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Dec. 10, 2013	Sep. 18, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Dec. 10, 2013	Sep. 18, 2014	Dec. 09, 2014	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Nov. 12, 2013	Sep. 18, 2014	Nov. 11, 2014	Conduction (CO01-KS)

## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.5
---	-----