

# FCC RF Test Report

APPLICANT : Brightstar Coporation  
EQUIPMENT : GSM device  
BRAND NAME : AVVIO  
MODEL NAME/  
MARKETING NAME/ : GT860  
TYPE NAME  
FCC ID : WVBAGT860  
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)  
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Oct. 09, 2012 and completely tested on Oct. 11, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:



---

Jones Tsai / Manager



**SPORTON INTERNATIONAL (KUNSHAN) INC.**  
**No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.**

## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Feature of Equipment Under Test.....	5
1.4 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	6
1.5 Testing Site .....	6
1.6 Applied Standards .....	6
1.7 Ancillary Equipment List.....	7
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>8</b>
2.1 Test Mode.....	8
2.2 Connection Diagram of Test System .....	9
<b>3 TEST RESULT.....</b>	<b>10</b>
3.1 Conducted Output Power Measurement.....	10
3.2 Peak-to-Average Ratio .....	12
3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	16
3.4 Occupied Bandwidth and 26dB Bandwidth Measurement.....	19
3.5 Band Edge Measurement.....	27
3.6 Conducted Spurious Emission Measurement.....	32
3.7 Field Strength of Spurious Radiation Measurement .....	38
3.8 Frequency Stability Measurement.....	45
<b>4 LIST OF MEASURING EQUIPMENT .....</b>	<b>49</b>
<b>5 UNCERTAINTY OF EVALUATION .....</b>	<b>50</b>
<b>APPENDIX A. PHOTOGRAPHS OF EUT</b>	
<b>APPENDIX B. SETUP PHOTOGRAPHS</b>	

## REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG2O0901	Rev. 01	Initial issue of report	Oct. 16, 2012

## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	N/A	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.3	§24.232©	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.6	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Spurious Emission	< 43+10log <sub>10</sub> (P[Watts])	PASS	-
3.7	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log <sub>10</sub> (P[Watts])	PASS	Under limit 30.78 dB at 1674.000 MHz
3.8	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

# 1 General Description

## 1.1 Applicant

**Brightstar Coporation**

9725 NW 117th Ave., Miami, Florida, United States

## 1.2 Manufacturer

**KCMobile Co., Ltd.**

#502, Ace techno tower 8th,191-7 Guro-dong, Guro-Gu, Seoul, South Korea

## 1.3 Feature of Equipment Under Test

Product Feature	
Equipment	GSM device
Brand Name	AVVIO
Model Name/Marketing Name /Type Name	GT860
FCC ID	WVBAGT860
EUT supports Radios application	GSM
HW Version	AL RL100_MB_V20
SW Version	GT860_107_MUL_52A
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Product Specification subjective to this standard	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz
Maximum Output Power to Antenna	GSM850 : 33.26 dBm GSM1900 : 29.66 dBm
Antenna Type	Dipole Antenna
Type of Modulation	GSM / GPRS: GMSK

## 1.4 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (% , Hz, ppm)	Emission Designator
Part 22	GSM850 GSM (GPRS 8)	GMSK	1.0965	0.03 ppm	250KGXW
Part 24	GSM1900 GSM (GPRS 8)	GMSK	0.8260	0.04 ppm	246KGXW

## 1.5 Testing Site

<b>Test Site</b>	SPORTON INTERNATIONAL (KUNSHAN) INC.		
<b>Test Site Location</b>	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>		<b>FCC/IC Registration No.</b>
	TH01-KS	03CH01-KS	149928/4086E-1

## 1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v01
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 1.7 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 19000 MHz for GSM1900.

Test Modes		
Band	Radiated TCs	Conducted TCs
<b>GSM 850</b>	■ GSM (GPRS 8) Link	■ GSM (GPRS 8) Link
<b>GSM 1900</b>	■ GSM (GPRS 8) Link	■ GSM (GPRS 8) Link


**Note:** The maximum power level is GSM mode for GMSK link, only this mode was used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
<b>GSM</b>	32.77	33.05	33.25	29.32	29.47	29.65
<b>GPRS 8</b>	32.78	33.06	<b>33.26</b>	29.32	29.48	<b>29.66</b>
<b>GPRS 10</b>	31.13	31.39	31.70	28.00	27.91	27.94
<b>GPRS 11</b>	29.15	29.41	29.70	26.35	26.16	26.15
<b>GPRS 12</b>	28.00	28.30	28.66	25.20	25.00	24.90



## 2.2 Connection Diagram of Test System



### 3 Test Result

#### 3.1 Conducted Output Power Measurement

##### 3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


##### 3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

##### 3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

##### 3.1.4 Test Setup



**3.1.5 Test Result of Conducted Output Power**

Cellular Band			
Modes	GSM850 (GSM (GPRS 8))		
Channel	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	32.78	33.06	33.26
Conducted Power (Watts)	1.90	2.02	2.12

PCS Band			
Modes	GSM1900 (GSM (GPRS 8))		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	29.32	29.48	29.66
Conducted Power (Watts)	0.86	0.89	0.92

**Note:** maximum burst average power for GSM.

## 3.2 Peak-to-Average Ratio

### 3.2.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


### 3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.2.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. For GSM/EGPRS operating modes:
  - a. Set the RBW = 1MHz, VBW = 1MHz, Peak detector in spectrum analyzer.
  - b. Set EUT in maximum power output, and triggered the burst signal.
  - c. Measured respectively the Peak level and Mean level, and the deviation was recorded as Peak to Average Ratio.
3. For UMTS operating modes:
  - a. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
  - b. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.

### 3.2.4 Test Setup




### 3.2.5 Test Result of Peak-to-Average Ratio


PCS Band			
Modes	GSM1900 (GSM (GPRS 8))		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
Peak-to-Average Ratio (dB)	0.13	0.13	0.15

### 3.2.6 Test Result (Plots) of Peak-to-Average Ratio

<b>Band :</b>	<b>GSM 1900</b>	<b>Test Mode :</b>	<b>GSM (GPRS 8) Link</b>
---------------	-----------------	--------------------	--------------------------

**Peak-to-Average Ratio on Channel 512 (1850.2 MHz)**



Date: 11.OCT.2012 03:00:06

**Peak-to-Average Ratio on Channel 661 (1880.0 MHz)**


Date: 11.OCT.2012 02:59:23



Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Date: 11.OCT.2012 02:58:31

### 3.3 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

#### 3.3.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

#### 3.3.2 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.3.3 Test Procedures

1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
2. The EUT was set at 3 meter from the receiving antenna, which was mounted on the antenna tower.
3. GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;  
UMTS operating modes: Set RBW= 100 KHz, VBW= 300 KHz, RMS detector over frame, and use channel power option with bandwidth=5MHz, per section 4.0 of KDB 971168 D01.
4. The table was rotated 360 degrees to determine the position of the highest radiated power.
5. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
6. Taking the record of maximum ERP/EIRP.
7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
8. The conducted power at the terminal of the dipole antenna is measured.
9. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
10.  $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$   
 $P_s$  (dBm) : Input power to substitution antenna.  
 $G_s$  (dBi or dBd) : Substitution antenna Gain.  
 $E_t = R_t + AF$   
 $E_s = R_s + AF$   
 $AF$  (dB/m) : Receive antenna factor  
 $R_t$  : The highest received signal in spectrum analyzer for EUT.  
 $R_s$  : The highest received signal in spectrum analyzer for substitution antenna.



### 3.3.4 Test Setup



### 3.3.5 Test Result of ERP

<b>GSM850 (GSM (GPRS 8)) Radiated Power ERP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-17.17	-48.12	0.00	-1.08	29.87	0.9705
836.40	-17.53	-48.28	0.00	-0.93	29.82	0.9594
848.80	-17.19	-48.35	0.00	-0.76	30.40	1.0965
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-25.29	-47.97	0.00	-1.08	21.60	0.1445
836.40	-26.79	-48.01	0.00	-0.93	20.29	0.1069
848.80	-27.56	-48.05	0.00	-0.76	19.73	0.0940

### 3.3.6 Test Result of EIRP

<b>GSM1900 (GSM (GPRS 8)) Radiated Power EIRP</b>						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.98	-51.88	0.00	1.96	26.86	0.4853
1880.00	-26.99	-52.99	0.00	2.00	28.00	0.6310
1909.80	-27.09	-54.28	0.00	1.98	29.17	0.8260
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-26.93	-52.13	0.00	1.96	27.16	0.5200
1880.00	-27.61	-53.17	0.00	2.00	27.56	0.5702
1909.80	-27.92	-54.13	0.00	1.98	28.19	0.6592

### 3.4 Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.4.1 Description of Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


#### 3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% occupied bandwidth and 26 dB bandwidth of the middle channel for the highest RF powers were measured.

#### 3.4.4 Test Setup



**3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth**


Cellular Band			
Modes	GSM850 (GSM (GPRS 8))		
Channel	128 (Low)	189 (Mid)	251 (High)
Frequency (MHz)	824.2	836.4	848.8
99% OBW (KHz)	250.00	244.00	246.00
26dB BW (KHz)	312.00	314.00	316.00

PCS Band			
Modes	GSM1900 (GSM (GPRS 8))		
Channel	512 (Low)	661 (Mid)	810 (High)
Frequency (MHz)	1850.2	1880	1909.8
99% OBW (KHz)	244.00	244.00	246.00
26dB BW (KHz)	312.00	314.00	312.00

### 3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


<b>Band :</b>	GSM 850	<b>Test Mode :</b>	GSM (GPRS 8) Link
---------------	---------	--------------------	-------------------

#### 99% Occupied Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 11.OCT.2012 03:38:55

#### 26dB Bandwidth Plot on Channel 128 (824.2 MHz)




Date: 11.OCT.2012 03:29:23

### 99% Occupied Bandwidth Plot on Channel 189 (836.4 MHz)




Date: 11.OCT.2012 03:37:24


### 26dB Bandwidth Plot on Channel 189 (836.4 MHz)



Date: 11.OCT.2012 03:28:03

**99% Occupied Bandwidth Plot on Channel 251 (848.8 MHz)**


Date: 11.OCT.2012 03:35:11


**26dB Bandwidth Plot on Channel 251 (848.8 MHz)**


Date: 11.OCT.2012 03:31:56




Band :	GSM 1900	Test Mode :	GSM (GPRS 8) Link
--------	----------	-------------	-------------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 11.OCT.2012 02:53:23

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 11.OCT.2012 02:49:02




**99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)**


Date: 11.OCT.2012 02:52:05

**26dB Bandwidth Plot on Channel 661 (1880.0 MHz)**



Date: 11.OCT.2012 02:48:04

### 99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 11.OCT.2012 02:51:11

### 26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 11.OCT.2012 02:49:54

### 3.5 Band Edge Measurement

#### 3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.


#### 3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

#### 3.5.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.


#### 3.5.4 Test Setup



### 3.5.5 Test Result (Plots) of Conducted Band Edge

Band :	GSM850	Test Mode :	GSM (GPRS 8) Link
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-14.66dBm	Measurement Value :	-14.89dBm


**Lower Band Edge Plot on Channel 128 (824.2 MHz)**



Date: 11.OCT.2012 03:42:35

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
  2. Band Edge= Measurement Value + Correction Factor(dB)
- For example,  $-14.89\text{dBm} + 0.23\text{dB} = -14.66\text{dBm}$


<b>Band :</b>	GSM850	<b>Test Mode :</b>	GSM (GPRS 8) Link
<b>Correction Factor :</b>	0.23dB	<b>Maximum 26dB Bandwidth :</b>	0.316MHz
<b>Band Edge :</b>	-16.34dBm	<b>Measurement Value :</b>	-15.57dBm

**Higher Band Edge Plot on Channel 251 (848.8 MHz)**


Date: 11.OCT.2012 03:43:51

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)


<b>Band :</b>	GSM1900	<b>Test Mode :</b>	GSM (GPRS 8) Link
<b>Correction Factor :</b>	0.20dB	<b>Maximum 26dB Bandwidth :</b>	0.314MHz
<b>Band Edge :</b>	-16.74dBm	<b>Measurement Value :</b>	-17.94dBm

**Lower Band Edge Plot on Channel 512 (1850.2 MHz)**


Date: 11.OCT.2012 02:55:13

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

<b>Band :</b>	GSM1900	<b>Test Mode :</b>	GSM (GPRS 8) Link
<b>Correction Factor :</b>	0.20dB	<b>Maximum 26dB Bandwidth :</b>	0.314MHz
<b>Band Edge :</b>	-19.74dBm	<b>Measurement Value :</b>	-19.94dBm

**Higher Band Edge Plot on Channel 810 (1909.8 MHz)**


Date: 11.OCT.2012 02:56:27

1. Correction Factor(dB)=  $10\log(1\% \text{ Emission BW/RBW})$
2. Band Edge= Measurement Value + Correction Factor(dB)

## 3.6 Conducted Spurious Emission Measurement

### 3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.


### 3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

### 3.6.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

### 3.6.4 Test Setup






### 3.6.5 Test Result (Plots) of Conducted Spurious Emission


<b>Band :</b>	GSM850	<b>Channel :</b>	CH189
<b>Test Mode :</b>	GSM (GPRS 8) Link	<b>Frequency :</b>	836.4 MHz

**Conducted Spurious Emission Plot between 30MHz ~ 1GHz**




Date: 11.OCT.2012 03:47:13


**Conducted Spurious Emission Plot between 1GHz ~ 3GHz**



Date: 11.OCT.2012 04:01:31


**Conducted Spurious Emission Plot between 3GHz ~ 7GHz**


Date: 11.OCT.2012 04:03:22


**Conducted Spurious Emission Plot between 7GHz ~ 9GHz**


Date: 11.OCT.2012 04:04:45


<b>Band :</b>	GSM1900	<b>Channel :</b>	CH661
<b>Test Mode :</b>	GSM (GPRS 8) Link	<b>Frequency :</b>	1880.0 MHz

**Conducted Spurious Emission Plot between 30MHz ~ 1GHz**



Date: 11.OCT.2012 00:57:15

**Conducted Spurious Emission Plot between 1GHz ~ 3GHz**


Date: 11.OCT.2012 01:00:36

**Conducted Spurious Emission Plot between 3GHz ~ 7GHz**



Date: 11.OCT.2012 03:16:38

**Conducted Emission Plot between 7GHz ~ 13.6GHz**


Date: 11.OCT.2012 03:20:49



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 11.OCT.2012 03:21:57

### **3.7 Field Strength of Spurious Radiation Measurement**

#### **3.7.1 Description of Field Strength of Spurious Radiated Measurement**

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

#### **3.7.2 Measuring Instruments**


See list of measuring instruments of this test report.

#### **3.7.3 Test Procedures**


1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11.  $ERP \text{ (dBm)} = EIRP - 2.15$

### 3.7.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




### 3.7.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



**3.7.6 Test Result of Field Strength of Spurious Radiated**

<b>Band :</b>	GSM850	<b>Temperature :</b>	22~24°C
<b>Test Mode :</b>	GSM (GPRS 8) Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
Condition : FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL  
Project : (FG) 2O0901

Plan : E2

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading ( dBm )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain ( dBi )	Polarization ( H/V )	Result
1674	-46.21	-13	-33.21	-45.56	-46.86	0.57	3.37	H	Pass
2510	-51.71	-13	-38.71	-53.96	-53.94	0.78	5.16	H	Pass
3344	-60.81	-13	-47.81	-62.75	-64.45	0.87	6.66	H	Pass

<b>Band :</b>	GSM850	<b>Temperature :</b>	22~24°C
<b>Test Mode :</b>	GSM (GPRS 8) Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Site : 03CH01-KS  
Condition : FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL  
Project : (FG) 2O0901

Plan : E2

Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1674	-43.78	-13	-30.78	-47.84	-44.43	0.57	3.37	V	Pass
2510	-48.26	-13	-35.26	-52.07	-50.49	0.78	5.16	V	Pass
3344	-60.49	-13	-47.49	-62.47	-64.13	0.87	6.66	V	Pass


<b>Band :</b>	GSM1900	<b>Temperature :</b>	22~24°C
<b>Test Mode :</b>	GSM (GPRS 8) Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Horizontal
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS  
Condition : FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL  
Project : (FG) 2O0901  
Plan : E2

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-64.97	-13	-51.97	-65.94	-71.35	0.78	7.16	H	Pass
5640	-62.57	-13	-49.57	-66.75	-71.11	1.04	9.58	H	Pass
7520	-62.50	-13	-49.50	-67.63	-72.61	1.35	11.46	H	Pass

<b>Band :</b>	GSM1900	<b>Temperature :</b>	22~24°C
<b>Test Mode :</b>	GSM (GPRS 8) Link	<b>Relative Humidity :</b>	42~43%
<b>Test Engineer :</b>	Steven Hao	<b>Polarization :</b>	Vertical
<b>Remark :</b>	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Site : 03CH01-KS  
Condition : FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL  
Project : (FG) 2O0901  
Plan : E2

Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-63.64	-13	-50.64	-65.01	-70.02	0.78	7.16	V	Pass
5640	-62.40	-13	-49.40	-65.62	-70.94	1.04	9.58	V	Pass
7520	-62.21	-13	-49.21	-66.7	-72.32	1.35	11.46	V	Pass

### **3.8 Frequency Stability Measurement**

#### **3.8.1 Description of Frequency Stability Measurement**

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

#### **3.8.2 Measuring Instruments**

See list of measuring instruments of this test report.


#### **3.8.3 Test Procedures for Temperature Variation**

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT cannot be turned on at  $-30^{\circ}\text{C}$ , the testing lowest temperature will be raised in  $10^{\circ}\text{C}$  step until the EUT can be turned on.

#### **3.8.4 Test Procedures for Voltage Variation**

1. The EUT was placed in a temperature chamber at  $25\pm 5^{\circ}\text{C}$  and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

### 3.8.5 Test Setup



**3.8.6 Test Result of Temperature Variation**

<b>Band :</b>	GSM 850	<b>Channel :</b>	189
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	836.4 MHz

Temperature (°C)	GSM (GPRS 8)		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	-29	-0.03	PASS
-20	22	0.03	
-10	21	0.02	
0	-22	-0.03	
10	-16	-0.02	
20	18	0.02	
30	-16	-0.02	
40	-19	-0.02	
50	-13	-0.02	

<b>Band :</b>	GSM 1900	<b>Channel :</b>	661
<b>Limit (ppm) :</b>	2.5	<b>Frequency :</b>	1880.0 MHz

Temperature (°C)	GSM (GPRS 8)		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	81	0.04	PASS
-20	-46	-0.02	
-10	-43	-0.02	
0	35	0.02	
10	49	0.03	
20	55	0.03	
30	30	0.02	
40	34	0.02	
50	44	0.02	

**3.8.7 Test Result of Voltage Variation**

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM (GPRS 8)	3.7	-20	-0.02	2.5	PASS
		BEP	-15	-0.02		
		4.2	13	0.02		
GSM 1900 CH661	GSM (GPRS 8)	3.7	43	0.02		
		BEP	31	0.02		
		4.2	25	0.01		

**Note:**

1. Normal Voltage = 3.7V.
2. Battery End Point (BEP) = 3.6 V.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Oct. 11, 2012	Dec. 29, 2012	Conducted (TH01-KS)
System Simulator	R&S	CMU200	837587/066	2G Full-Band	Dec. 30, 2011	Oct. 11, 2012	Dec. 29, 2012	Conducted (TH01-KS)
DC Power Supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 22, 2012	Oct. 11, 2012	Aug. 21, 2013	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	N/A	Dec. 30, 2011	Oct. 11, 2012	Dec. 29, 2012	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Oct. 10, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Oct. 10, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Oct. 10, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Double Ridge Horn	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Oct. 10, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060007	30MHz~2GHz	Dec. 30, 2011	Oct. 10, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 30, 2011	Oct. 10, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
SHE-EHF Horn	Schwarzbeck	BBHA9170	BBHA170249	15GHz~40GHz	Oct. 10, 2012	Oct. 10, 2012	Oct. 09, 2013	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/001	9KHz ~ 30MHz	Jul. 03, 2012	Oct. 10, 2012	Jul. 02, 2014	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	116456	Full-Band	Sep. 19, 2012	Oct. 10, 2012	Sep. 18, 2013	Radiation (03CH01-KS)

## 5 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.54
--	------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.72
---	------



## **Appendix A. Photographs of EUT**

Please refer to Sporton report number EP2O0901 as below.