

Model. TWX-241XRSXX

Antenna Specifications

· Description	1)Thean	tennai	isas	wivelan	d 1	$/4\lambda$	du	alband	anten	na	
_	T . 1	0 10		T C T F D	•	00			0 = 4	_	_


 $It's useful for the ISMB and of 2.4 \hbox{\sim} 2.5 GHz \& 5.15 \hbox{\sim} 5.85 GHz.$

• ElectricalProperties

1)FrequencyRange	2.4~5.XGHz
2)Impedance	50ohmnominal
3)V.S.W.R.	≦2.0
4)Gain	2.4GHz 2dBi
	5.0GHz 1.5dBi
5)Polarization	Vertical
6)AdmittedPower	1W
7)ElectricalWavelength	1/4 λ Dipole


• Mechanical Properties

1)Connector	ReverseSMAPlug
2)AntennaCover	Polyurethane
AntennaBase	Polycarbonate
3)RotatingTest	1.2Kg · cm, After 2000
	cycleswiththerateof
	30cycles/minute(max.).
	Itshallbepossibleto
	remainit'sposition.
4)Adhesive Strength	5.0kgf(at30minutes)




E-PlaneFieldPatterns

Frequency:2.45GHz



H-PlaneFieldPatterns


Frequency:2.45GHz



TestReport Pattern Test


E-PlaneFieldPatterns

Frequency:5.25GHz



H-PlaneFieldPatterns


Frequency:5.25GHz



Pattern Test

E-PlaneFieldPatterns

Frequency:5.75GHz



H-PlaneFieldPatterns

Frequency:5.75GHz

