FCC HAC (T-Coil) Test Report

Report No.	:	**SA171025C36A-1**
Applicant	:	**Sonim Technologies, Inc.**
Address	:	**1825 S. Grant St., Suite 200., San Mateo, CA, 94402**
Product	:	**Mobile Phone**
FCC ID	:	**WYPPG4032**
Brand	:	**Sonim**
Model No.	:	**XP8800**
Type Number	:	**PG4032/PG4033/PG4034/PG4035/PG4012/PG4041/PG4022**
Standards	:	**FCC 47 CFR Part 20.19**
		ANSI C63.19-2011
Sample Received Date	:	**Oct. 25, 2017**
Date of Testing	:	**Oct. 27, 2017 ~ Dec. 02, 2017**
Summary T-Rating	:	**T4**
Lab Address	:	**No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.**
Test Location	:	**No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City 33383, Taiwan (R.O.C)**

CERTIFICATION: The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's HAC characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :

Rona Chen / Specialist

Approved By :

Gordon Lin / Assistant Manager

FCC Accredited No.: TW0003

Table of Contents

Report Issue History Record

Report No.	Reason for Change	Date Issued
SA171025C36-1	Initial release	Dec. 06, 2017
SA171025C36A-1	Base the original report "SA171025C36-1" to disable CDMA function.	Jan. 02, 2018

<u>Summary of Maximum T-Rating</u>

Mode / Band	Test Item	Criterion	Test Results	T-Rating
GSM850	**Field Intensity**	**≥ -18 dB**	**-14.77**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**31.69**	
GSM1900	**Field Intensity**	**≥ -18 dB**	**-14.71**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**35.44**	
WCDMA Band II	**Field Intensity**	**≥ -18 dB**	**-13.50**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**40.52**	
WCDMA Band IV	**Field Intensity**	**≥ -18 dB**	**-13.76**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**40.54**	
WCDMA Band V	**Field Intensity**	**≥ -18 dB**	**-13.54**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**40.52**	
LTE 2	**Field Intensity**	**≥ -18 dB**	**-16.26**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**35.90**	
LTE 4	**Field Intensity**	**≥ -18 dB**	**-15.05**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**37.12**	
LTE 5	**Field Intensity**	**≥ -18 dB**	**-15.09**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**38.23**	
LTE 7	**Field Intensity**	**≥ -18 dB**	**-15.03**	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	**T3 : ≥ 20 dB**	**36.99**	

LTE 12	**Field Intensity**	≥ -18 dB	-14.40	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	38.91	
LTE 13	**Field Intensity**	≥ -18 dB	-14.39	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	38.54	
LTE 14	**Field Intensity**	≥ -18 dB	-14.81	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	38.24	
LTE 25	**Field Intensity**	≥ -18 dB	-14.86	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	38.60	
LTE 26	**Field Intensity**	≥ -18 dB	-14.87	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	38.36	
LTE 30	**Field Intensity**	≥ -18 dB	-14.75	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	37.86	
LTE 38	**Field Intensity**	≥ -18 dB	-16.90	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	32.01	
LTE 40	**Field Intensity**	≥ -18 dB	-14.27	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	38.44	
LTE 41	**Field Intensity**	≥ -18 dB	-15.95	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	35.99	
LTE 66	**Field Intensity**	≥ -18 dB	-14.70	**T4**
	Frequency Response	**Pass**	**Pass**	
	Signal Quality	T3 : ≥ 20 dB	37.24	
Summary				**T4**

Note:

1. The HAC T-Coil limit **(T-Rating Category T3)** is specified in FCC 47 CFR part 20.19 and ANSI C63.19.

2. The device T-Coil rating is determined by the minimum rating.

1. Description of Equipment Under Test

EUT Type	Mobile Phone
FCC ID	WYPPG4032
Brand Name	Sonim
Model Name	XP8800
Tx Frequency Bands (Unit: MHz)	GSM850 : 824.2 ~ 848.8 GSM1900 : 1850.2 ~ 1909.8 WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band IV : 1712.4 ~ 1752.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 2 : 1850.7 ~ 1909.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M) LTE Band 4 : 1710.7 ~ 1754.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M) LTE Band 5 : 824.7 ~ 848.3 (BW: 1.4M, 3M, 5M, 10M) LTE Band 7 : 2502.5 ~ 2567.5 (BW: 5M, 10M, 15M, 20M) LTE Band 12 : 699.7 ~ 715.3 (BW: 1.4M, 3M, 5M, 10M) LTE Band 13 : 779.5 ~ 784.5 (BW: 5M, 10M) LTE Band 14 : 790.5 ~ 795.5 (BW: 5M, 10M) LTE Band 25 : 1850.7 ~ 1914.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M) LTE Band 26 : 814.7 ~ 848.3 (BW: 1.4M, 3M, 5M, 10M, 15M) LTE Band 30 : 2307.5 ~ 2312.5 (BW: 5M, 10M) LTE Band 38 : 2572.5 ~ 2617.5 (BW: 5M, 10M, 15M, 20M) LTE Band 40 : 2305 ~ 2315 (BW: 5M, 10M) LTE Band 41 : 2498.5 ~ 2687.5 (BW: 5M, 10M, 15M, 20M) LTE Band 66 : 1710.7 ~ 1779.3 (BW: 1.4M, 3M, 5M, 10M, 15M, 20M) WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5700, 5745 ~ 5825 Bluetooth : 2402 ~ 2480 NFC : 13.56
Uplink Modulations	GSM & GPRS : GMSK EDGE : 8PSK WCDMA : QPSK LTE : QPSK, 16QAM, 64QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, π/4-DQPSK, 8-DPSK NFC : ASK
Antenna Type	Fixed Internal Antenna
EUT Stage	Production Unit

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

List of Accessory:

	Brand Name	Sonim
Battery	Model Name	BAT-01900-01S
	Power Rating	3.85 Vdc, 4900 mAh
	Type	Li-ion

Air Interface and Operational Mode							
Air Interface	Bands	Type Transport	HAC Tested	Simultaneous But Not Tested	Voice Over Digital Transport OTT Capability	WiFi Low Power	Additional GSM Power Reduction
GSM	850	VO	YES	WLAN or BT	N/A	N/A	N/A
	1900	VO	YES	WLAN or BT	N/A		
	GPRS/EDGE	DT	N/A	WLAN or BT	YES		
WCDMA	II	VO	YES	WLAN or BT	N/A	N/A	N/A
	IV	VO	YES	WLAN or BT	N/A		
	V						
	HSPA	DT	N/A	WLAN or BT	YES		
LTE	2	VD[1]	YES	WLAN or BT	YES	N/A	N/A
	4						
	5						
	7						
	12						
	13						
	14						
	25						
	26						
	30						
	38						
	40						
	41						
	66						
WLAN	2.4G / 5G	VD	NO[2]	WWAN	YES	N/A	N/A
Bluetooth	2.4G	DT	N/A	WWAN	N/A	N/A	N/A

Type Transport	Note
VO = Voice only DT = Digital Data – Not Indented for CMRS Service VD = CMRS and Data transport	1. The 3GPP VoLTE CMRS service is defined by GSMA in PRD IR.92 for IP voice service and digital transport. 2. No associated T-Coil measurement has been made in accordance with the guidance issued by OET in KDB publication 285076 D02 T-Coil testing for CMRS IP.

2. HAC T-Coil Measurement System

3.1 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion form the optical into digital electric signal of the DAE and transfers data to the PC.

Fig-3.1 DASY System Setup

The principal cabling of the T-Coil setup is shown in below. All cables provided with the basic setup have a length of approximately 5 m.


**Fig-3.2a T-Coil Setup Cabling for 2G/3G**

Fig-3.2b T-Coil Setup Cabling for VoLTE

3.1.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ±0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)


Fig-3.3 DASY5

3.1.2 AM1D Probe

The AM1D probe is an active probe with a single sensor. It is fully RF-shielded and has a rounded tip 6 mm in diameter incorporating a pickup coil with its center offset 3 mm from the tip and the sides. The symmetric signal preamplifier in the probe is fed via the shielded symmetric output cable from the AMMI with a 48V "phantom" voltage supply. The 7-pin connector on the back in the axis of the probe does not carry any signals. It is mounted to the DAE for the correct orientation of the sensor. If the probe axis is tilted 54.7 degrees from the vertical, the sensor is approximately vertical when the signal connector is at the underside of the probe (cable hanging downwards).

Model	AM1DV3	
Sampling Rate	0.1 kHz to 20 kHz RF sensitivity < -100 dB	
Preamplifier	Symmetric, 40 dB	
Dynamic Range	-60 to 40 dB A/m	
Calibration	at 1kHz	
Dimensions	Tip diameter : 6 mm Length : 290 mm	

3.1.3 Audio Magnetic Calibration Coil (AMCC)

The AMCC is a Helmholtz Coil designed for calibration of the AM1D probe. The two horizontal coils generate a homogeneous magnetic field in the z direction. The DC input resistance is adjusted by a series resistor to approximately 50 Ohm, and a shunt resistor of 10 Ohm permits monitoring the current with a scale of 1:10.

Signal	Connector	Resistance	
Coil In	BNC	Typically 50 Ohm	
Coil Monitor	BNO	10 Ohm ±1% (100mV corresponding to 1 A/m)	
Dimensions	370 x 370 x 196 mm		

3.1.4 Audio Magnetic Measuring Instrument (AMMI)

The AMMI is a desktop 19-inch unit containing a sampling unit, a waveform generator for test and calibration signals, and a USB interface.

Sampling Rate	48 kHz / 24 bit	
Dynamic Range	100 dB (with AM1DV3 probe)	
Test Signal Generation	User selectable and predefined (via PC)	
Calibration	Auto-calibration / full system calibration using AMCC with monitor output	
Dimensions	482 x 65 x 270 mm	

3.1.5 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5µV (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

3.1.6 Phantoms

Model	Test Arch	
Construction	Enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot.	
Dimensions	Length : 370 mm Width : 370 mm Height : 370 mm	

3.1.7 Device Holder

Model	Mounting Device	
Construction	The Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to ANSI C63.19.	
Material	POM	

3.2 System Calibration

For correct and calibrated measurement of the voltages and ABM field, DASY will perform a calibration job as below. In phase 1, the audio output is switched off, and a 200 mV$_{pp}$ symmetric rectangular signal of 1 kHz is generated and internally connected directly to both channels of the sampling unit (Coil in, Probe in).

In phase 2, the audio output is off, and a 20 mV$_{pp}$ symmetric 100 Hz signal is internally connected. The signals during phases 1 and 2 are available at the output on the rear panel of the AMMI. However, the output must not be loaded, in order to avoid influencing the calibration. An RMS voltmeter would indicate 100 mV$_{RMS}$ during the first phase and 10 mV$_{RMS}$ during the second phase. After the first two phases, the two input channels are both calibrated for absolute measurements of voltages. The resulting factors are displayed above the multi-meter window.

After phases 1 and 2, the input channels are calibrated to measure exact voltages. This is required to use the inputs for measuring voltages with their peak and RMS value.

In phase 3, a multi-sine signal covering each third-octave band from 50 Hz to 10 kHz is generated and applied to both audio outputs. The probe should be positioned in the center of the AMCC and aligned in the z-direction, the field orientation of the AMCC. The "Coil In" channel is measuring the voltage over the AMCC internal shunt, which is proportional to the magnetic field in the AMCC. At the same time, the "Probe In" channel samples the amplified signal picked up by the probe coil and provides it to a numerical integrator. The ratio of the two voltages in each third-octave filter leads to the spectral representation over the frequency band of interest. The Coil signal is scaled in dBV, and the Probe signal is first integrated and normalized to show dB A/m. The ratio probe-to-coil at the frequency of 1 kHz is the sensitivity which will be used in the consecutive T-Coil jobs.


Fig-3.4 Frequency Response and Sensitivity of AM1D Probe

3.3 EUT Measurements Reference and Plane

The EUT is mounted in the device holder. The acoustic output of the EUT will coincide with the center point of the area formed by the dielectric wire and the middle bar of the arch's top frame. Then EUT will be moved vertically upwards until it touches the frame.

Figure 3.5 illustrates the three standard probe orientations. Position 1 is the perpendicular (axial) orientation of the probe coil. Orientation 2 is the transverse (radial) orientation. The space between the measurement positions is not fixed. It is recommended that a scan of the EUT be done for each probe coil orientation and that the maximum level recorded be used as the reading for that orientation of the probe coil.

(1)   The reference plane is the planar area that contains the highest point in the area of the phone that normally rests against the user's ear. It is parallel to the centerline of the receiver area of the phone and is defined by the points of the receiver-end of the EUT handset that, in normal handset use, rest against the ear.

(2)   The measurement plane is parallel to, and 10 mm in front of the reference plane.

(3)   The reference axis is normal to the reference plane and passes through the center of the receiver speaker section or it may be centered on a secondary inductive source.

(4)   The measurement points may be located where the perpendicular (axial) and transverse (radial) field intensity measurements are optimum with regard to the requirements. However, the measurement points should be near the acoustic output of the EUT and shall be located in the same half of the phone as the EUT receiver. In a EUT handset with a centered receiver and a circularly symmetrical magnetic field, the measurement axis and the reference axis would coincide.

(5)   The relative spacing of each measurement orientations is not fixed. The perpendicular (axial) and transverse (radial) orientations should be chosen to select the optimal position.

(6)   The measurement point for the axial position is located 10 mm from the reference plane on the measurement axis.


Fig-3.5 Axis and Planes

3.4 HAC T-Coil Measurement Procedure

According to ANSI C63.19-2011, the T-Coil test procedure for wireless communications device is as below.

1. Position the EUT in the test setup and connect the EUT RF connector to a base station simulator.
2. The drive level to the EUT is set such that the reference input level specified in Table 7.1 is input to the base station simulator in the 1 kHz, 1/3 octave band. This drive level shall be used for the T-Coil signal test (ABM1) at f = 1 kHz. Either a sine wave at 1025 Hz or a voice-like signal, band-limited to the 1 kHz 1/3 octave, as defined in 7.4.2, shall be used for the reference audio signal. If interference is found at 1025 Hz, an alternate nearby reference audio signal frequency may be used. The same drive level will be used for the ABM1 frequency response measurements at each 1/3 octave band center frequency. The EUT volume control may be set at any level up to maximum, provided that a signal at any frequency at maximum modulation would not result in clipping or signal overload.
3. Determine the magnetic measurement locations for the EUT, if not already specified by the manufacturer, as described in 7.4.4.1.1 and 7.4.4.2.
4. At each measurement location, measure and record the desired T-Coil magnetic signals (ABM1 at f_i) as described in 7.4.4.2 in each individual ISO 266-1975 R10 standard 1/3 octave band. The desired audio band input frequency (f_i) shall be centered in each 1/3 octave band maintaining the same drive level as determined in Step 2 and the reading taken for that band. Equivalent methods of determining the frequency response may also be employed, such as fast Fourier transform (FFT) analysis using noise excitation or input–output comparison using simulated speech. The full-band integrated or half-band integrated probe output, as described in D.9, may be used, as long as the appropriate calibration curve is applied to the measured result, so as to yield an accurate measurement of the field magnitude. (The resulting measurement shall be an accurate measurement in dB A/m.) All measurements of the desired signal shall be shown to be of the desired signal and not of an undesired signal. This may be shown by turning the desired signal on and off with the probe measuring the same location. If the scanning method is used, the scans shall show that all measurement points selected for the ABM1 measurement meet the ambient and test system noise criterion in 7.3.1.
5. At the measurement location for each orientation, measure and record the undesired broadband audio magnetic signal (ABM2) as described in 7.4.4.4 with no audio signal applied (or digital zero applied, if appropriate) using A-weighting, and the half-band integrator. Calculate the ratio of the desired to undesired signal strength (i.e., signal quality).
6. Determine the category that properly classifies the signal quality based on Table 8.5.

**Fig-3.6 T-Coil Measurement Test Setup**

Fig-3.7 T-Coil Signal Test Flowchart

3.5 Instrumentation for VoLTE and VoWiFi T-Coil Testing

According to KDB 285076 D02, T-Coil testing for VoLTE and VoWiFi requires test instrumentation that can (1) for the system to be able to establish an IP call from/to the handset under test, (2) through an IMS (IP Multimedia Subsystem) and SIP/IP server, (3) to an analog audio adapter containing the permissible set of codecs used by the device under test, and (4) inject the necessary C63.19 test tones at the average speech level for the measurement. The test setup for VoLTE is illustrated in Figure 3.8. The R&S CMW500 was used as system simulator for VoLTE and VoWiFi T-Coil testing. The DAU (Data Application Unit) in CMW500 integrates IMS and SIP/IP server that can establish VoLTE call and transport the test tones from AMMI (Audio Magnetic Measuring Instrument) to EUT (Equipment Under Test).


Fig-3.8 T-Coil Testing Setup for VoLTE

For the speech level, the interpretation on July 2012 for T-Coil audio levels for LTE processed by ASC-C63 states that LTE 3GPP TS26.131 section 5.22 and 3GPP TS26.132 section 7.2.2.2 define the required RLR levels, and based on these specifications to satisfy the requirement of subclause 7.4.2.1 an audio signal level of -16 dBm0 shall be used for normal speech input level. For VoWiFi, the average speech level of -20 dBm0 was used for testing. The speech levels with the settings at the AF connector of CMW500 have been calibrated, and it can be set manually to ensure that the full-scale speech level is -16 dBm0 or -20 dBm0 during T-Coil testing.

3. HAC Measurement Evaluation

4.1 Measurement Criteria

The HAC Standard ANSI C63.19-2011 represents performance requirements for acceptable interoperability of hearing aids with wireless communications devices. When these parameters are met, a hearing aid operates acceptably in close proximity to a wireless communications device.

4.1.1 Field Intensity

When measured as specified in this standard, the T-Coil signal shall be ≥ –18 dB (A/m) at 1 kHz, in a 1/3 octave band filter for all orientations.

4.1.2 Frequency Response

The frequency response of the axial component of the magnetic field, measured in 1/3 octave bands, shall follow the below response curve, over the frequency range 300 Hz to 3000 Hz. Figure 4.1 and Figure 4.2 provide the boundaries for the specified frequency. These response curves are for true field strength measurements of the T-Coil signal. Thus the 6 dB/octave probe response has been corrected from the raw readings.

**Fig-4.1 Boundaries for EUT with a field ≤ -15 dB (A/m) at 1 kHz**

Fig-4.2 Boundaries for EUT with a field > -15 dB (A/m) at 1 kHz

4.1.3 Signal Quality

The worst signal quality of the three T-Coil signal measurements shall be used to determine the T-Coil mode category per below table.

Category	Telephone Parameters WD Signal Quality (Signal to Noise Ratio, in dB)
Category T1	0 – 10
Category T2	10 – 20
Category T3	20 – 30
Category T4	> 30

4.2 EUT Configuration and Setting

For HAC T-Coil testing, the EUT was linked and controlled by base station emulator. Communication between the EUT and the emulator was established by coaxial connection. The EUT was set from the emulator to radiate maximum output power during HAC testing.

4.3 VoLTE Configuration for T-Coil Testing

The pre-scan for each LTE band supported by the EUT was performed to determine the worst-case LTE band. The configurations of RB and RB offset were pre-scanned on the worst-case LTE band to determine the worst-case radio configuration for coming audio codec testing. The pre-scan results please refer to below table.

LTE Band	Bandwidth (MHz)	Channel	ABM2 (dB A/m)	ABM1 (dB A/m)	SNR (dB)
2	20	18900	-53.21	-14.96	38.25
4	20	20175	-52.98	-15.03	37.95
5	**10**	20525	-52.71	-15.06	**37.65**
7	20	21100	-52.95	-14.97	37.98
12	10	23095	-53.33	-15.23	38.10
13	10	23230	-53.30	-15.25	38.05
14	10	23330	-53.09	-15.18	37.91
25	20	26365	-53.35	-15.53	37.82
26	15	26865	-53.07	-15.35	37.72
30	10	27710	-53.19	-14.75	38.44
38	20	38000	-52.95	-15.09	37.86
40	10	39150	-52.80	-14.95	37.85
41	20	40620	-53.31	-15.27	38.04
66	20	132322	-53.15	-14.65	38.50

LTE Band	Bandwidth (MHz)	Modulation	Channel	RB Size	RB Offset	ABM2 (dB A/m)	ABM1 (dB A/m)	SNR (dB)
5	10	QPSK	20525	1	0	-53.34	-15.18	38.16
5	10	QPSK	20525	1	24	-53.09	-15.26	37.83
5	10	QPSK	20525	1	49	-53.16	-15.06	38.10
5	10	QPSK	20525	25	0	-53.26	-15.26	38.00
5	10	QPSK	20525	25	12	-53.18	-15.16	38.02
5	10	QPSK	20525	25	25	-53.05	-15.27	37.78
5	10	QPSK	20525	50	0	-53.06	-15.27	37.79
5	10	16QAM	20525	1	0	-53.34	-15.18	38.16
5	**10**	**16QAM**	**20525**	**1**	**24**	**-50.10**	**-15.26**	**34.84**
5	10	16QAM	20525	1	49	-50.61	-15.18	35.43
5	10	16QAM	20525	25	0	-50.17	-15.18	34.99
5	10	16QAM	20525	25	12	-50.28	-15.33	34.95
5	10	16QAM	20525	25	25	-50.36	-15.28	35.08
5	10	16QAM	20525	50	0	-50.42	-15.42	35.00
5	10	64QAM	20525	1	0	-53.42	-15.36	38.06
5	10	64QAM	20525	1	24	-50.37	-15.25	35.12
5	10	64QAM	20525	1	49	-50.57	-15.11	35.46
5	10	64QAM	20525	25	0	-50.19	-15.13	35.06
5	10	64QAM	20525	25	12	-50.38	-15.27	35.11
5	10	64QAM	20525	25	25	-50.67	-15.40	35.27
5	10	64QAM	20525	50	0	-50.15	-15.14	35.01

The pre-scan for audio codec configurations was performed on the worst-case LTE band and RB configuration to determine the worst-case audio codec configuration which was used for VoLTE T-Coil testing. The pre-scan results please refer to below table.

AMR Type	Codec Bit-Rates (kbit/s)	ABM2 (dB A/m)	ABM1 (dB A/m)	SNR (dB)
Wide Band	**6.60**	**-50.10**	**-15.26**	**34.84**
Wide Band	23.85	-50.34	-14.92	35.42
Narrow Band	4.75	-50.29	-15.07	35.22
Narrow Band	12.20	-50.28	-14.71	35.57

4.4 HAC T-Coil Testing Results

Plot No.	Band	CH	Probe Orientation	Frequency Response	Coordinates (mm)	ABM2 (dB A/m)	ABM1 (dB A/m)	SNR (dB)	T-Rating
01	GSM850	189	Axial (Z)	Pass	10, -4, 3.7	-36.95	-5.26	**31.69**	**T4**
			Radial (Y)	-	0, -6.5, 3.7	-53.51	-14.77	38.74	T4
02	GSM1900	661	Axial (Z)	Pass	8.5, -3, 3.7	-40.44	-5.00	**35.44**	**T4**
			Radial (Y)	-	0, -7, 3.7	-53.87	-14.71	39.16	T4
03	WCDMA II	9400	Axial (Z)	Pass	6, -2.5, 3.7	-48.63	-4.67	43.96	T4
			Radial (Y)	-	5.5, 7.5, 3.7	-54.02	-13.50	**40.52**	**T4**
04	WCDMA IV	1413	Axial (Z)	Pass	6, -2.5, 3.7	-48.33	-4.65	43.68	T4
			Radial (Y)	-	3.5, -10, 3.7	-54.30	-13.76	**40.54**	**T4**
05	WCDMA V	4182	Axial (Z)	Pass	5.5, -2, 3.7	-48.50	-4.75	43.75	T4
			Radial (Y)	-	5.5, 7, 3.7	-54.06	-13.54	**40.52**	**T4**

Plot No.	LTE Band	BW (MHz)	Channel	Probe Orientation	Frequency Response	Coordinates (mm)	ABM2 (dB A/m)	ABM1 (dB A/m)	SNR (dB)	T-Rating
06	LTE 2	20M	18900	Axial (Z)	Pass	5, -0.5, 3.7	-46.81	-6.66	40.15	T4
				Radial (Y)	-	6, -14.5, 3.7	-52.16	-16.26	35.90	T4
	LTE 2	15M	18900	Axial (Z)	Pass	5.5, 0, 3.7	-45.55	-6.60	38.95	T4
				Radial (Y)	-	3.5, -10.5, 3.7	-53.14	-15.77	37.37	T4
	LTE 2	10M	18900	Axial (Z)	Pass	5, -0.5, 3.7	-45.32	-6.73	38.59	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.18	-15.74	37.44	T4
	LTE 2	5M	18900	Axial (Z)	Pass	5, -0.5, 3.7	-45.13	-6.64	38.49	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.16	-15.69	37.47	T4
	LTE 2	3M	18900	Axial (Z)	Pass	5.5, -0.5, 3.7	-45.76	-6.54	39.22	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.10	-15.62	37.48	T4
	LTE 2	1.4M	18900	Axial (Z)	Pass	5.5, -1.5, 3.7	-46.03	-6.56	39.47	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.26	-14.84	38.42	T4
	LTE 4	20M	20175	Axial (Z)	Pass	5, -1, 3.7	-45.30	-6.66	38.64	T4
				Radial (Y)	-	2.5, -10, 3.7	-53.25	-15.00	38.25	T4
	LTE 4	15M	20175	Axial (Z)	Pass	5, -1, 3.7	-45.76	-6.47	39.29	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.15	-14.82	38.33	T4
	LTE 4	10M	20175	Axial (Z)	Pass	5, -1, 3.7	-44.31	-6.65	37.66	T4
				Radial (Y)	-	4, -10.5, 3.7	-52.95	-14.93	38.02	T4
	LTE 4	5M	20175	Axial (Z)	Pass	5.5, -1, 3.7	-44.44	-6.57	37.87	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.05	-14.82	38.23	T4
07	LTE 4	3M	20175	Axial (Z)	Pass	2, 0.5, 3.7	-46.04	-8.92	37.12	T4
				Radial (Y)	-	5, -10, 3.7	-53.62	-15.05	38.57	T4
	LTE 4	1.4M	20175	Axial (Z)	Pass	5.5, -0.5, 3.7	-45.81	-6.52	39.29	T4
				Radial (Y)	-	5, -10.5, 3.7	-53.59	-15.00	38.59	T4
08	LTE 5	10M	20525	Axial (Z)	Pass	5, 0, 3.7	-44.86	-6.63	38.23	T4
				Radial (Y)	-	0, -6, 3.7	-53.60	-15.09	38.51	T4
	LTE 5	5M	20525	Axial (Z)	Pass	5.5, 0, 3.7	-44.55	-5.94	38.61	T4
				Radial (Y)	-	3.5, -8.5, 3.7	-53.12	-14.65	38.47	T4
	LTE 5	3M	20525	Axial (Z)	Pass	5.5, 0, 3.7	-45.58	-5.89	39.69	T4
				Radial (Y)	-	4.5, -9, 3.7	-53.14	-14.57	38.57	T4
	LTE 5	1.4M	20525	Axial (Z)	Pass	5.5, -1.5, 3.7	-45.15	-5.95	39.20	T4
				Radial (Y)	-	4.5, -10, 3.7	-53.00	-14.17	38.83	T4
	LTE 7	20M	21100	Axial (Z)	Pass	4.5, -0.5, 3.7	-45.66	-6.17	39.49	T4
				Radial (Y)	-	3, -10.5, 3.7	-52.96	-15.03	37.93	T4
	LTE 7	15M	21100	Axial (Z)	Pass	5, -0.5, 3.7	-45.81	-6.05	39.76	T4
				Radial (Y)	-	4.5, -11, 3.7	-53.02	-14.69	38.33	T4
	LTE 7	10M	21100	Axial (Z)	Pass	5, -0.5, 3.7	-45.64	-6.11	39.53	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.07	-14.67	38.40	T4
09	LTE 7	5M	21100	Axial (Z)	Pass	6, -0.5, 3.7	-42.91	-5.92	36.99	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.23	-14.70	38.53	T4
	LTE 12	10M	23095	Axial (Z)	Pass	5, -1, 3.7	-45.20	-5.97	39.23	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.00	-14.06	38.94	T4
10	LTE 12	5M	23095	Axial (Z)	Pass	5, -1, 3.7	-45.16	-6.00	39.16	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.04	-14.13	38.91	T4
	LTE 12	3M	23095	Axial (Z)	Pass	5, -1, 3.7	-46.40	-6.09	40.31	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.61	-14.19	39.42	T4
	LTE 12	1.4M	23095	Axial (Z)	Pass	5, -1.5, 3.7	-46.61	-6.30	40.31	T4
				Radial (Y)	-	5, -10.5, 3.7	-53.69	-14.40	39.29	T4

Plot No.	LTE Band	BW (MHz)	Channel	Probe Orientation	Frequency Response	Coordinates (mm)	ABM2 (dB A/m)	ABM1 (dB A/m)	SNR (dB)	T-Rating
11	LTE 13	10M	23230	Axial (Z)	Pass	5, -0.5, 3.7	-45.86	-5.97	39.89	T4
				Radial (Y)	-	4, -10.5, 3.7	-52.93	-14.39	**38.54**	**T4**
	LTE 13	5M	23230	Axial (Z)	Pass	5, -1, 3.7	-45.48	-6.00	39.48	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.13	-14.06	39.07	T4
	LTE 14	10M	23330	Axial (Z)	Pass	4.5, -0.5, 3.7	-45.60	-6.10	39.50	T4
				Radial (Y)	-	4, -10, 3.7	-53.19	-14.53	38.66	T4
12	LTE 14	5M	23330	Axial (Z)	Pass	4.5, -0.5, 3.7	-44.26	-5.92	38.34	T4
				Radial (Y)	-	0.5, -8, 3.7	-53.05	-14.81	**38.24**	**T4**
	LTE 25	20M	26365	Axial (Z)	Pass	5, -0.5, 3.7	-44.78	-5.93	38.85	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.26	-14.24	39.02	T4
13	LTE 25	15M	26365	Axial (Z)	Pass	5, -0.5, 3.7	-45.72	-6.00	39.72	T4
				Radial (Y)	-	5, -10.5, 3.7	-53.14	-14.54	**38.60**	**T4**
	LTE 25	10M	26365	Axial (Z)	Pass	5, -1, 3.7	-45.35	-5.91	39.44	T4
				Radial (Y)	-	4, -10, 3.7	-52.96	-14.21	38.75	T4
	LTE 25	5M	26365	Axial (Z)	Pass	4.5, -1, 3.7	-44.83	-6.20	38.63	T4
				Radial (Y)	-	5, -10.5, 3.7	-53.13	-14.39	38.74	T4
	LTE 25	3M	26365	Axial (Z)	Pass	5, -0.5, 3.7	-45.72	-5.81	39.91	T4
				Radial (Y)	-	4.5, -10, 3.7	-53.33	-14.22	39.11	T4
	LTE 25	1.4M	26365	Axial (Z)	Pass	5.5, -0.5, 3.7	-47.21	-6.28	40.93	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.59	-14.86	38.73	T4
14	LTE 26	15M	26865	Axial (Z)	Pass	5.5, -1, 3.7	-46.47	-6.40	40.07	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.23	-14.87	**38.36**	**T4**
	LTE 26	10M	26865	Axial (Z)	Pass	5.5, -0.5, 3.7	-46.28	-6.36	39.92	T4
				Radial (Y)	-	4, -10.5, 3.7	-53.30	-14.85	38.45	T4
	LTE 26	5M	26865	Axial (Z)	Pass	5, -0.5, 3.7	-45.78	-6.37	39.41	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.66	-14.70	38.96	T4
	LTE 26	3M	26865	Axial (Z)	Pass	5, -0.5, 3.7	-47.21	-6.33	40.88	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.48	-14.72	38.76	T4
	LTE 26	1.4M	26865	Axial (Z)	Pass	5.5, -1.5, 3.7	-47.32	-6.26	41.06	T4
				Radial (Y)	-	5, -10.5, 3.7	-53.74	-14.84	38.90	T4
15	LTE 30	10	27710	Axial (Z)	Pass	5.5, -1, 3.7	-44.67	-6.81	**37.86**	**T4**
				Radial (Y)	-	9, -13.5, 3.7	-53.60	-14.75	38.85	T4
	LTE 30	5	27710	Axial (Z)	Pass	6, -1.5, 3.7	-44.61	-6.57	38.04	T4
				Radial (Y)	-	9, -13.5, 3.7	-53.50	-14.71	38.79	T4
	LTE 38	20M	38000	Axial (Z)	Pass	5, -1, 3.7	-44.91	-5.49	39.42	T4
				Radial (Y)	-	3, -10.5, 3.7	-52.72	-14.34	38.38	T4
	LTE 38	15M	38000	Axial (Z)	Pass	5, -1, 3.7	-45.11	-5.71	39.40	T4
				Radial (Y)	-	3, -10.5, 3.7	-52.65	-14.28	38.37	T4
	LTE 38	10M	38000	Axial (Z)	Pass	5, -1.5, 3.7	-45.15	-5.58	39.57	T4
				Radial (Y)	-	2, -10, 3.7	-52.77	-14.37	38.40	T4
16	LTE 38	5M	38000	Axial (Z)	Pass	5, -1.5, 3.7	-42.10	-5.51	39.59	T4
				Radial (Y)	-	15.5, -15.5, 3.7	-48.91	-16.90	**32.01**	**T4**
17	LTE 40	10M	38750	Axial (Z)	Pass	5, -1, 3.7	-45.37	-5.45	39.92	T4
				Radial (Y)	-	3, -10.5, 3.7	-52.71	-14.27	**38.44**	**T4**
	LTE 40	5M	38750	Axial (Z)	Pass	5, -1.5, 3.7	-44.90	-5.57	39.33	T4
				Radial (Y)	-	2.5, -10, 3.7	-52.82	-14.26	38.56	T4

Plot No.	LTE Band	BW (MHz)	Channel	Probe Orientation	Frequency Response	Coordinates (mm)	ABM2 (dB A/m)	ABM1 (dB A/m)	SNR (dB)	T-Rating
	LTE 41	20M	40620	Axial (Z)	Pass	4, 0, 3.7	-44.40	-6.59	37.81	T4
				Radial (Y)	-	4.5, -10.5, 3.7	-53.30	-14.62	38.68	T4
	LTE 41	15M	40620	Axial (Z)	Pass	5.5, -0.5, 3.7	-45.50	-6.70	38.80	T4
				Radial (Y)	-	7, -14.5, 3.7	-52.22	-15.94	36.28	T4
	LTE 41	10M	40620	Axial (Z)	Pass	5.5, -1, 3.7	-45.06	-6.95	38.11	T4
				Radial (Y)	-	7.5, -15, 3.7	-52.01	-15.95	36.06	T4
18	LTE 41	5M	40620	Axial (Z)	Pass	5.5, -0.5, 3.7	-44.51	-6.75	37.76	T4
				Radial (Y)	-	7, -14.5, 3.7	-51.93	-15.94	**35.99**	**T4**
	LTE 66	20M	132322	Axial (Z)	Pass	6, -0.5, 3.7	-44.90	-6.62	38.28	T4
				Radial (Y)	-	9.5, -13, 3.7	-53.52	-14.64	38.88	T4
19	LTE 66	15M	132322	Axial (Z)	Pass	6, -0.5, 3.7	-43.85	-6.61	**37.24**	**T4**
				Radial (Y)	-	9, -12.5, 3.7	-53.27	-14.67	38.60	T4
	LTE 66	10M	132322	Axial (Z)	Pass	6, -0.5, 3.7	-44.29	-6.63	37.66	T4
				Radial (Y)	-	8, -11.5, 3.7	-53.32	-14.62	38.70	T4
	LTE 66	5M	132322	Axial (Z)	Pass	5.5, -0.5, 3.7	-44.03	-6.67	37.36	T4
				Radial (Y)	-	9, -11.5, 3.7	-53.43	-14.07	39.36	T4
	LTE 66	3M	132322	Axial (Z)	Pass	6, -0.5, 3.7	-44.75	-6.57	38.18	T4
				Radial (Y)	-	9.5, -13, 3.7	-53.54	-14.53	39.01	T4
	LTE 66	1.4M	132322	Axial (Z)	Pass	5.5, -0.5, 3.7	-45.12	-6.66	38.46	T4
				Radial (Y)	-	9.5, -13.5, 3.7	-53.61	-14.70	38.91	T4

Note: The low and high channels were verified on the worst-case configuration for each probe orientation.

Test Engineer：Eric Wu, and Raymond Wu

4. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
Audio Band Magnetic Probe	SPEAG	AM1DV3	3060	Jan. 23, 2017	1 Year
Data Acquisition Electronics	SPEAG	DAE3	579	Aug. 17, 2017	1 Year
Data Acquisition Electronics	SPEAG	DAE4	861	May 22, 2017	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1431	Mar. 20, 2017	1 Year
Universal Radio Communication Tester	R&S	CMW500	152443	Sep. 20, 2017	1 Year
Test Arch Phantom	SPEAG	Arch	N/A	N/A	N/A

5. <u>Measurement Uncertainty</u>

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (ABM1)	Ci (ABM2)	Standard Uncertainty (ABM1)	Standard Uncertainty (ABM2)
Probe Sensitivity							
Reference Level	3.0	Normal	1	1	1	± 3.0 %	± 3.0 %
AMCC Geometry	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
AMCC Current	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Probe Positioning During Calibration	0.1	Rectangular	√3	1	1	± 0.1 %	± 0.1 %
Noise Contribution	0.7	Rectangular	√3	0.0143	1	± 0.0 %	± 0.4 %
Frequency Slope	5.9	Rectangular	√3	0.1	1	± 0.3 %	± 3.5 %
Probe System							
Repeatability / Drift	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity / Dynamic Range	0.6	Rectangular	√3	1	1	± 0.4 %	± 0.4 %
Acoustic Noise	1.0	Rectangular	√3	0.1	1	± 0.1 %	± 0.6 %
Probe Angle	2.3	Rectangular	√3	1	1	± 1.4 %	± 1.4 %
Spectral Processing	0.9	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	0.6	Normal	1	1	5	± 0.6 %	± 3.0 %
Field Distribution	0.2	Rectangular	√3	1	1	± 0.1 %	± 0.1 %
Test Signal							
Ref. Signal Spectral Response	0.6	Rectangular	√3	0	1	± 0.0 %	± 0.4 %
Positioning							
Probe Positioning	1.9	Rectangular	√3	1	1	± 1.1 %	± 1.1 %
Phantom Thickness	0.9	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
EUT Positioning	1.9	Rectangular	√3	1	1	± 1.1 %	± 1.1 %
External Contributions							
RF Interference	0.0	Rectangular	√3	1	0.3	± 0.0 %	± 0.0 %
Test Signal Variation	2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %
Combined Standard Uncertainty						± 4.1 %	± 6.1 %
Coverage Factor for 95 %						K = 2	
Expanded Uncertainty						**± 8.1 %**	**± 12.3 %**

Uncertainty Budget for HAC T-Coil

6. Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Taiwan HwaYa EMC/RF/Safety Lab:
Add: No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan, R.O.C.
Tel: 886-3-318-3232
Fax: 886-3-327-0892

Taiwan LinKo EMC/RF Lab:
Add: No. 47-2, 14th Ling, Chia Pau Vil., Linkou Dist., New Taipei City 244, Taiwan, R.O.C.
Tel: 886-2-2605-2180
Fax: 886-2-2605-1924

Taiwan HsinChu EMC/RF/Telecom Lab:
Add: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 30078, Taiwan, R.O.C.
Tel: 886-3-666-8565
Fax: 886-3-666-8323

Email: service.adt@tw.bureauveritas.com
Web Site: www.adt.com.tw

The road map of all our labs can be found in our web site also.

---END---

Appendix A. Plots of HAC T-Coil Measurement

The plots for HAC measurement are shown as follows.

P01 T-Coil_GSM850_GSM_Ch189_Axial (Z)

DUT: 171025C36

Communication System: GSM; Frequency: 836.4 MHz;Duty Cycle: 1:8.3

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3

Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm

ABM1/ABM2 = 31.69 dB

ABM1 comp = -5.26 dBA/m

Location: 10, -4, 3.7 mm

P01 T-Coil_GSM850_GSM_Ch189_Radial (Y)

DUT: 171025C36

Communication System: GSM; Frequency: 836.4 MHz;Duty Cycle: 1:8.3
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.74 dB
ABM1 comp = -14.77 dBA/m
Location: 0, -6.5, 3.7 mm

P01 T-Coil_GSM850_GSM_Ch189_Freq Resp

DUT: 171025C36

Communication System: GSM; Frequency: 836.4 MHz;Duty Cycle: 1:8.3
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P02 T-Coil_GSM1900_GSM_Ch661_Axial (Z)

DUT: 171025C36

Communication System: GSM; Frequency: 1880 MHz;Duty Cycle: 1:8.3
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 35.44 dB
ABM1 comp = -5.00 dBA/m
Location: 8.5, -3, 3.7 mm

P02 T-Coil_GSM1900_GSM_Ch661_Radial (Y)

DUT: 171025C36

Communication System: GSM; Frequency: 1880 MHz;Duty Cycle: 1:8.3
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 39.16 dB
ABM1 comp = -14.71 dBA/m
Location: 0, -7, 3.7 mm

P02 T-Coil_GSM1900_GSM_Ch661_Freq Resp

DUT: 171025C36

Communication System: GSM; Frequency: 1880 MHz;Duty Cycle: 1:8.3
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

General Scans/z (Axial) wideband at best S/N/ABM Freq Resp(x,y,z,f)
Loc: 8.7, -3.2, 3.7 mm Diff: 1.74dB

P03 T-Coil_WCDMA II_Voice_Ch9400_Axial (Z)

DUT: 171025C36

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 43.96 dB
ABM1 comp = -4.67 dBA/m
Location: 6, -2.5, 3.7 mm

P03 T-Coil_WCDMA II_Voice_Ch9400_Radial (Y)

DUT: 171025C36

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 40.52 dB
ABM1 comp = -13.50 dBA/m
Location: 5.5, 7.5, 3.7 mm

P03 T-Coil_WCDMA II_Voice_Ch9400_Freq Resp

DUT: 171025C36

Communication System: WCDMA; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P04 T-Coil_WCDMA IV_Voice_Ch1413_Axial (Z)

DUT: 171025C36

Communication System: WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 43.68 dB
ABM1 comp = -4.65 dBA/m
Location: 6, -2.5, 3.7 mm

P04 T-Coil_WCDMA IV_Voice_Ch1413_Radial (Y)

DUT: 171025C36

Communication System: WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 40.54 dB
ABM1 comp = -13.76 dBA/m
Location: 3.5, -10, 3.7 mm

P04 T-Coil_WCDMA IV_Voice_Ch1413_Freq Resp

DUT: 171025C36

Communication System: WCDMA; Frequency: 1732.6 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid:
dx=10mm, dy=10mm

P05 T-Coil_WCDMA V_Voice_Ch4182_Axial (Z)

DUT: 171025C36

Communication System: WCDMA; Frequency: 836.4 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 43.75 dB
ABM1 comp = -4.75 dBA/m
Location: 5.5, -2, 3.7 mm

P05 T-Coil_WCDMA V_Voice_Ch4182_Radial (Y)

DUT: 171025C36

Communication System: WCDMA; Frequency: 836.4 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 40.52 dB
ABM1 comp = -13.54 dBA/m
Location: 5.5, 7, 3.7 mm

P05 T-Coil_WCDMA V_Voice_Ch4182_Freq Resp

DUT: 171025C36

Communication System: WCDMA; Frequency: 836.4 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P06 LTE 2_BW20M_Ch18900_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 40.15 dB
ABM1 comp = -6.66 dBA/m
Location: 5, -0.5, 3.7 mm

P06 LTE 2_BW20M_Ch18900_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 35.90 dB
ABM1 comp = -16.26 dBA/m
Location: 6, -14.5, 3.7 mm

P06 LTE 2_BW20M_Ch18900_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid:
dx=10mm, dy=10mm

P07 LTE 4_BW3M_Ch20175_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 37.12 dB
ABM1 comp = -8.92 dBA/m
Location: 2, 0.5, 3.7 mm

P07 LTE 4_BW3M_Ch20175_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.57 dB
ABM1 comp = -15.05 dBA/m
Location: 5, -10, 3.7 mm

P07 LTE 4_BW3M_Ch20175_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P08 LTE 5_BW10M_Ch20525_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.23 dB
ABM1 comp = -6.63 dBA/m
Location: 5, 0, 3.7 mm

P08 LTE 5_BW10M_Ch20525_Radiao (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1 kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.51 dB
ABM1 comp = -15.09 dBA/m
Location: 0, -6, 3.7 mm

P08 LTE 5_BW10M_Ch20525_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 836.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid:
dx=10mm, dy=10mm

P09 LTE 7_BW5M_Ch21100_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 36.99 dB
ABM1 comp = -5.92 dBA/m
Location: 6, -0.5, 3.7 mm

P09 LTE 7_BW5M_Ch21100_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1 kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.53 dB
ABM1 comp = -14.70 dBA/m
Location: 4, -10.5, 3.7 mm

P09 LTE 7_BW5M_Ch21100_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 2535 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid:
dx=10mm, dy=10mm

P10 LTE 12_BW5M_Ch23095_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 39.16 dB
ABM1 comp = -6.00 dBA/m
Location: 5, -1, 3.7 mm

P10 LTE 12_BW5M_Ch23095_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.91 dB
ABM1 comp = -14.13 dBA/m
Location: 4, -10.5, 3.7 mm

P10 LTE 12_BW5M_Ch23095_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid:
dx=10mm, dy=10mm

P11 LTE 13_BW10M_Ch23230_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 782 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 39.89 dB
ABM1 comp = -5.97 dBA/m
Location: 5, -0.5, 3.7 mm

P11 LTE 13_BW10M_Ch23230_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 782 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.54 dB
ABM1 comp = -14.39 dBA/m
Location: 4, -10.5, 3.7 mm

P11 LTE 13_BW10M_Ch23230_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 782 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)


T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P12 LTE 14_BW5M_Ch23330_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 793 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1 kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.34 dB
ABM1 comp = -5.92 dBA/m
Location: 4.5, -0.5, 3.7 mm

P12 LTE 14_BW5M_Ch23330_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 793 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.24 dB
ABM1 comp = -14.81 dBA/m
Location: 0.5, -8, 3.7 mm

P12 LTE 14_BW5M_Ch23330_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 793 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P13 LTE 25_BW15M_Ch26365_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 1882.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 39.72 dB
ABM1 comp = -6.00 dBA/m
Location: 5, -0.5, 3.7 mm

P13 LTE 25_BW15M_Ch26365_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 1882.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.60 dB
ABM1 comp = -14.54 dBA/m
Location: 5, -10.5, 3.7 mm

P13 LTE 25_BW15M_Ch26365_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 1882.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)


T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid:
dx=10mm, dy=10mm

P14 LTE 26_BW15M_Ch26865_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 831.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 40.07 dB
ABM1 comp = -6.40 dBA/m
Location: 5.5, -1, 3.7 mm

P14 LTE 26_BW15M_Ch26865_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 831.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.36 dB
ABM1 comp = -14.87 dBA/m
Location: 4.5, -10.5, 3.7 mm

P14 LTE 26_BW15M_Ch26865_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 831.5 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P15 LTE 30_BW10M_Ch27710_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 2310 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1 kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn861; Calibrated: 2017/05/22
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 37.86 dB
ABM1 comp = -6.81 dBA/m
Location: 5.5, -1, 3.7 mm

P15 LTE 30_BW10M_Ch27710_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 2310 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn861; Calibrated: 2017/05/22
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.85 dB
ABM1 comp = -14.75 dBA/m
Location: 9, -13.5, 3.7 mm

P15 LTE 30_BW10M_Ch27710_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 2310 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn861; Calibrated: 2017/05/22
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P16 LTE 38_BW5M_Ch38000_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 2595 MHz;Duty Cycle: 1:1.58
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 39.59 dB
ABM1 comp = -5.51 dBA/m
Location: 5, -1.5, 3.7 mm

P16 LTE 38_BW5M_Ch38000_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 2595 MHz;Duty Cycle: 1:1.58

Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3

Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 32.01 dB
ABM1 comp = -16.90 dBA/m
Location: 15.5, -15.5, 3.7 mm

P16 LTE 38_BW5M_Ch38000_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 2595 MHz;Duty Cycle: 1:1.58
Medium: Air Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1 kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P17 LTE 40_BW10M_Ch38750_Axial (Z)

DUT: 171025C36

Communication System: LTE TDD CF0; Frequency: 2310 MHz;Duty Cycle: 1:1.58
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 39.92 dB
ABM1 comp = -5.45 dBA/m
Location: 5, -1, 3.7 mm

P17 LTE 40_BW10M_Ch38750_Radial (Y)

DUT: 171025C36

Communication System: LTE TDD CF0; Frequency: 2310 MHz;Duty Cycle: 1:1.58
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.44 dB
ABM1 comp = -14.27 dBA/m
Location: 3, -10.5, 3.7 mm

P17 LTE 40_BW10M_Ch38750_Freq Resp

DUT: 171025C36

Communication System: LTE TDD CF0; Frequency: 2310 MHz;Duty Cycle: 1:1.58
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P18 LTE 41_BW5M_Ch40620_Axial (Z)

DUT: 171025C36

Communication System: LTE TDD CF0; Frequency: 2593 MHz;Duty Cycle: 1:1.58
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 37.76 dB
ABM1 comp = -6.75 dBA/m
Location: 5.5, -0.5, 3.7 mm

P18 LTE 41_BW5M_Ch40620_Radial (Y)

DUT: 171025C36

Communication System: LTE TDD CF0; Frequency: 2593 MHz;Duty Cycle: 1:1.58
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 35.99 dB
ABM1 comp = -15.94 dBA/m
Location: 7, -14.5, 3.7 mm

P18 LTE 41_BW5M_Ch40620_Freq Resp

DUT: 171025C36

Communication System: LTE TDD CF0; Frequency: 2593 MHz;Duty Cycle: 1:1.58
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn1431; Calibrated: 2017/03/20
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid: dx=10mm, dy=10mm

P19 LTE 66_BW15M_Ch132232_Axial (Z)

DUT: 171025C36

Communication System: LTE; Frequency: 1745 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn861; Calibrated: 2017/05/22
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 37.24 dB
ABM1 comp = -6.61 dBA/m
Location: 6, -0.5, 3.7 mm

P19 LTE 66_BW15M_Ch132232_Radial (Y)

DUT: 171025C36

Communication System: LTE; Frequency: 1745 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn861; Calibrated: 2017/05/22
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Interpolated grid:
dx=1.000 mm, dy=1.000 mm
ABM1/ABM2 = 38.60 dB
ABM1 comp = -14.67 dBA/m
Location: 9, -12.5, 3.7 mm

P19 LTE 66_BW15M_Ch132232_Freq Resp

DUT: 171025C36

Communication System: LTE; Frequency: 1745 MHz;Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ S/m, $\varepsilon_r = 1$; $\rho = 1$ kg/m^3
Ambient Temperature：23.8 ℃

DASY5 Configuration:
- Probe: AM1DV3 - 3060; ; Calibrated: 2017/01/23
- Sensor-Surface: 0mm (Fix Surface)
- Electronics: DAE4 Sn861; Calibrated: 2017/05/22
- Phantom: HAC Test Arch with AMCC; Type: SD HAC P01 BA;
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7373)

T-Coil scan (scan for ANSI C63.19 compliance)/General Scans: Measurement grid:
dx=10mm, dy=10mm

Appendix B.   Calibration Certificate for Probe

The SPEAG calibration certificates are shown as follows.

Calibration Laboratory of
Schmid & Partner
 Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

ilac-MRA

S **Schweizerischer Kalibrierdienst**
C **Service suisse d'étalonnage**
 Servizio svizzero di taratura
S **Swiss Calibration Service**

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client   **B.V.ADT (Auden)**

Certificate No: **AM1DV3-3060_Jan17**

CALIBRATION CERTIFICATE

Object	AM1DV3 - SN: 3060
Calibration procedure(s)	**QA CAL-24.v4** **Calibration procedure for AM1D magnetic field probes and TMFS in the audio range**
Calibration date:	**January 23, 2017**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0810278	09-Sep-16 (No. 19065)	Sep-17
Reference Probe AM1DV3	SN: 3000	18-Aug-16 (No. AM1D-3000_Aug16)	Aug-17
DAE4	SN: 781	02-Sep-16 (No. DAE4-781_Sep16)	Sep-17

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
AMCC	SN: 1050	01-Oct-13 (in house check Sep-15)	Oct-17
AMMI Audio Measuring Instrument	SN: 1062	26-Sep-12 (in house check Sep-15)	Oct-17

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: January 23, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

[References

[1]   ANSI-C63.19-2007
       American National Standard for Methods of Measurement of Compatibility between Wireless
       Communications Devices and Hearing Aids.
[2]   ANSI-C63.19-2011
       American National Standard, Methods of Measurement of Compatibility between Wireless
       Communications Devices and Hearing Aids.
[3]   DASY5 manual, Chapter: Hearing Aid Compatibility (HAC) T-Coil Extension

Description of the AM1D probe

The AM1D Audio Magnetic Field Probe is a fully shielded magnetic field probe for the frequency range from 100 Hz to 20 kHz. The pickup coil is compliant with the dimensional requirements of [1+2]. The probe includes a symmetric low noise amplifier for the signal available at the shielded 3 pin connector at the side. Power is supplied via the same connector (phantom power supply) and monitored via the LED near the connector. The 7 pin connector at the end of the probe does not carry any signals, but determines the angle of the sensor when mounted on the DAE. The probe supports mechanical detection of the surface.

The single sensor in the probe is arranged in a tilt angle allowing measurement of 3 orthogonal field components when rotating the probe by 120° around its axis. It is aligned with the perpendicular component of the field, if the probe axis is tilted nominally 35.3° above the measurement plane, using the connector rotation and sensor angle stated below.

The probe is fully RF shielded when operated with the matching signal cable (shielded) and allows measurement of audio magnetic fields in the close vicinity of RF emitting wireless devices according to [1+2] without additional shielding.

Handling of the item

The probe is manufactured from stainless steel. In order to maintain the performance and calibration of the probe, it must not be opened. The probe is designed for operation in air and shall not be exposed to humidity or liquids. For proper operation of the surface detection and emergency stop functions in a DASY system, the probe must be operated with the special probe cup provided (larger diameter).

Methods Applied and Interpretation of Parameters

- *Coordinate System:* The AM1D probe is mounted in the DASY system for operation with a HAC Test Arch phantom with AMCC Helmholtz calibration coil according to [3], with the tip pointing to "southwest" orientation.

- *Functional Test:* The functional test preceding calibration includes test of
  Noise level
  RF immunity (1kHz AM modulated signal). The shield of the probe cable must be well connected.
  Frequency response verification from 100 Hz to 10 kHz.

- *Connector Rotation:* The connector at the end of the probe does not carry any signals and is used for fixation to the DAE only. The probe is operated in the center of the AMCC Helmholtz coil using a 1 kHz magnetic field signal. Its angle is determined from the two minima at nominally +120° and −120° rotation, so the sensor in the tip of the probe is aligned to the vertical plane in z-direction, corresponding to the field maximum in the AMCC Helmholtz calibration coil.

- *Sensor Angle:* The sensor tilting in the vertical plane from the ideal vertical direction is determined from the two minima at nominally +120° and −120°. DASY system uses this angle to align the sensor for radial measurements to the x and y axis in the horizontal plane.

Sensitivity: With the probe sensor aligned to the z-field in the AMCC, the output of the probe is compared to the magnetic field in the AMCC at 1 kHz. The field in the AMCC Helmholtz coil is given by the geometry and the current through the coil, which is monitored on the precision shunt resistor of the coil.

AM1D probe identification and configuration data

Item	**AM1DV3** Audio Magnetic 1D Field Probe
Type No	SP AM1 001 BA
Serial No	**3060**

Overall length	296 mm
Tip diameter	6.0 mm (at the tip)
Sensor offset	3.0 mm (centre of sensor from tip)
Internal Amplifier	20 dB

Manufacturer / Origin	Schmid & Partner Engineering AG, Zürich, Switzerland
Manufacturing date	October 30, 2009
Last calibration date	January 26, 2016

Calibration data

Connector rotation angle	(in DASY system)	**50.6 °**	+/- 3.6 ° (k=2)
Sensor angle	(in DASY system)	**0.57 °**	+/- 0.5 ° (k=2)
Sensitivity at 1 kHz	(in DASY system)	**0.00732 V / (A/m)**	+/- 2.2 % (k=2)

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Appendix C. Photographs of EUT and Setup