

**A Radio Test Report**

**FOR**

**Timelox AB**

**ON**

**Endnode**

**DOCUMENT NO. TRA-011412-W-NA-1**

**HULL**

Unit E, South Orbital Trading Park, Hedon Road, Hull, HU9 1NJ, UK.  
**T** +44 (0)1482 801801 **F** +44 (0)1482 801806 **E** test@tracglobal.com  
[www.tracglobal.com](http://www.tracglobal.com)

**TRaC Wireless Test Report** : TRA-011412-W-NA-1

**Applicant** : Timelox AB

**Apparatus** : Endnode

**Specification(s)** : CFR47 Part 15.247 July 2010 & RSS-210, Issue 8

**FCCID** : WYV-EN110

**IC Certification Number** : 8231A-EN110

**Purpose of Test** : **Certification**

**Authorised by** :



: Radio Product Manager

**Issue Date** : 26<sup>th</sup> November 2012

**Authorised Copy Number** : *PDF*

**Contents**

Section 1:	Introduction	4
1.1	General	4
1.2	Tests Requested By	5
1.3	Manufacturer	5
1.4	Apparatus Assessed	5
1.5	Test Result Summary	6
1.6	Notes Relating To The Assessment	7
1.7	Deviations from Test Standards	7
Section 2:	Measurement Uncertainty	8
2.1	Application of Measurement Uncertainty	8
2.2	Measurement Uncertainty Values	9
Section 3:	Modifications	11
3.1	Modifications Performed During Assessment	11
Appendix A:	Formal Emission Test Results	12
A1	6 dB Bandwidth	13
A2	Transmitter Peak Output Power	14
A3	Transmitter Power Spectral Density	15
A4	RF Antenna Conducted Spurious Emissions	16
A5	Radiated Electric Field Emissions	18
A6	Antenna Gain	22
A7	Unintentional Radiated Electric Field Emissions	23
Appendix B:	Supporting Graphical Data	25
Appendix C:	Additional Test and Sample Details	56
Appendix D:	Additional Information	62
Appendix E:	Calculation of the duty cycle correction factor	63
Appendix F:	Photographs and Figures	64
Appendix G:	MPE Calculation	69

**Section 1:****Introduction****1.1 General**

This report contains an assessment of an apparatus against Electromagnetic Compatibility Standards based upon tests carried out on samples submitted to the Laboratory.

Test performed at: TRaC Global [ ]  
Unit E  
South Orbital Trading Park  
Hedon Road  
Hull, HU9 1NJ.  
United Kingdom.

Telephone: +44 (0) 1482 801801  
Fax: +44 (0) 1482 801806

TRaC Global [X]  
Unit 1  
Pendle Place  
Skelmersdale  
West Lancashire, WN8 9PN  
United Kingdom

Telephone: +44 (0) 1695 556666  
Fax: +44 (0) 1695 577077

Email: [test@tracglobal.com](mailto:test@tracglobal.com)  
Web site: <http://www.tracglobal.com>

Tests performed by: D Winstanley

Report author: D Winstanley

**This report must not be reproduced except in full without prior written permission from TRaC Global.**

## **1.2 Tests Requested By**

This testing in this report was requested by :

Timelox AB  
Lodjursgatan 1  
SE-261 44  
LANDSKRONA  
Sweden

## **1.3 Manufacturer**

As Above

## **1.4 Apparatus Assessed**

The following apparatus was assessed between 15<sup>th</sup> – 21<sup>st</sup> November 2012:

Endnode

The above product is a DSSS RF module operating in the 2.4 GHz ISM band. The device is to be used for door control at indoor commercial premises (e.g Hotels).

## 1.5 Test Result Summary

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

The statements relating to compliance with the standards below apply ONLY as qualified in the notes and deviations stated in sections 1.6 to 1.7 of this test report.

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

Test Type	Regulation		Measurement standard	Result
Radiated spurious emissions (Restricted bands)	RSS-210 Issue 8 December 2010 Annex 8, A8.5	Title 47 of the CFR: Part 15 Subpart C; 15.247	ANSI C63.10:2009	Pass
Conducted spurious emissions (Non-restricted bands)	RSS-210 Issue 8 December 2010 Annex 8.A4(4)	Title 47 of the CFR: Part 15 Subpart C; 15.247	ANSI C63.10:2009	Pass
AC Power conducted emissions	RSS-GEN Issue 3 December 2010 Annex 7, 7.2.4	Title 47 of the CFR: Part 15 Subpart C; 15.207	ANSI C63.10:2009	N/A
Occupied Bandwidth	RSS-210 Issue 8 December 2010 Annex 8.A8.2a	Title 47 of the CFR : Part 15 Subpart C; 15.247(a)(2)	ANSI C63.10:2009	Pass
Conducted Carrier Power	RSS-210 Issue 8 December 2010 Annex 8.A4(4).	Title 47 of the CFR : Part 15 Subpart C; 15.247(b)	ANSI C63.10:2009	Pass
Power Spectral Density	RSS-210 Issue 8 December 2010 Annex 8.A8.2b	Title 47 of the CFR : Part 15 Subpart C; 15.247(d)	ANSI C63.10:2009	Pass
Unintentional Radiated Spurious Emissions	RSS-GEN Issue 3 December 2010 7.2.2(c)	Title 47 of the CFR: Part 15 Subpart B; 15.109	ANSI C63.10:2009	Pass
RF Safety	RSS-102	Title 47 of the CFR : Part 15 Subpart C; 15.247(b)(5)	-	Pass

The Endnode will only be powered by batteries

Abbreviations used in the above table:

ANSI C 63.10:2009 is outside the scope of the laboratories UKAS accreditation.

Mod : Modification  
CFR : Code of Federal Regulations  
REFE : Radiated Electric Field Emissions

RSS : Radio Standards Specification  
ANSI : American National Standards Institution  
PLCE : Power Line Conducted Emissions

## **1.6 Notes Relating To The Assessment**

With regard to this assessment, the following points should be noted:

The results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only.

Particular operating modes, apparatus monitoring methods and performance criteria required by the standards tested to have been performed except where identified in Section 1.7 of this test report (Deviations from Test Standards).

For emissions testing, throughout this test report, "Pass" indicates that the results for the sample as tested were below the specified limit (refer also to Section 2, Measurement Uncertainty).

Where relevant, the apparatus was only assessed using the monitoring methods and susceptibility criteria defined in this report.

All testing with the exception of testing at the Open Area Test Site was performed under the following environmental conditions:

Temperature	: 17 to 23 °C
Humidity	: 45 to 75 %
Barometric Pressure	: 86 to 106 kPa

All dates used in this report are in the format dd/mm/yy.

This assessment has been performed in accordance with the requirements of ISO/IEC 17025.

## **1.7 Deviations from Test Standards**

There were no deviations from the standards tested to.

**Section 2:****Measurement Uncertainty****2.1 Application of Measurement Uncertainty**

The following table contains the measurement uncertainties for measurements

The following procedure is used when determining the result of a measurement :

- (i) If specification limits are not exceeded by the measured result, extended by the positive component of the expanded uncertainty interval at a confidence level of 95%, then a pass result is recorded.
- (ii) Where a specification limit is exceeded by the result even when the result is decreased by the negative component of the expanded uncertainty interval, a fail result is recorded.
- (iii) Where measured result is below a limit, but by a margin less than the positive measurement uncertainty component, it is not possible to record a pass based on a 95% confidence level. However, the result indicates that a pass result is more probable than a fail result.
- (iv) Where a measured result is above a limit, but by a margin less than the negative measurement uncertainty component, it is not possible to record a fail based on a 95% confidence level. However the result indicates that a fail is more probable than a pass.



## 2.2 Measurement Uncertainty Values

For the test data recorded in accordance with note (iii) of Section 2.1 the following measurement uncertainty was calculated :

### Radio Testing – General Uncertainty Schedule

*All statements of uncertainty are expanded standard uncertainty using a coverage factor of 1.96 to give a 95% confidence where no required test level exists.*

#### **[1] Adjacent Channel Power**

Uncertainty in test result = **1.86dB**

#### **[2] Carrier Power**

Uncertainty in test result (Power Meter) = **1.08dB**

Uncertainty in test result (Spectrum Analyser) = **2.48dB**

#### **[3] Effective Radiated Power**

Uncertainty in test result = **4.71dB**

#### **[4] Spurious Emissions**

Uncertainty in test result = **4.75dB**

#### **[5] Maximum frequency error**

Uncertainty in test result (Power Meter) = **0.113ppm**

Uncertainty in test result (Spectrum Analyser) = **0.265ppm**

#### **[6] Radiated Emissions, field strength OATS 14kHz-18GHz Electric Field**

Uncertainty in test result (14kHz – 30MHz) = **4.8dB**,

Uncertainty in test result (30MHz – 1GHz) = **4.6dB**,

Uncertainty in test result (1GHz – 18GHz) = **4.7dB**

#### **[7] Frequency deviation**

Uncertainty in test result = **3.2%**

#### **[8] Magnetic Field Emissions**

Uncertainty in test result = **2.3dB**

#### **[9] Conducted Spurious**

Uncertainty in test result – Up to 8.1GHz = **3.31dB**

Uncertainty in test result – 8.1GHz – 15.3GHz = **4.43dB**

Uncertainty in test result – 15.3GHz – 21GHz = **5.34dB**

Uncertainty in test result – Up to 26GHz = **3.14dB**

#### **[10] Channel Bandwidth**

Uncertainty in test result = **15.5%**

#### **[11] Amplitude and Time Measurement – Oscilloscope**

Uncertainty in overall test level = **2.1dB**,

Uncertainty in time measurement = **0.59%**,

Uncertainty in Amplitude measurement = **0.82%**

**[12] Power Line Conduction**

Uncertainty in test result = **3.4dB**

**[13] Spectrum Mask Measurements**

Uncertainty in test result = **2.59% (frequency)**

Uncertainty in test result = **1.32dB (amplitude)**

**[14] Adjacent Sub Band Selectivity**

Uncertainty in test result = **1.24dB**

**[15] Receiver Blocking – Listen Mode, Radiated**

Uncertainty in test result = **3.42dB**

**[16] Receiver Blocking – Talk Mode, Radiated**

Uncertainty in test result = **3.36dB**

**[17] Receiver Blocking – Talk Mode, Conducted**

Uncertainty in test result = **1.24dB**

**[18] Receiver Threshold**

Uncertainty in test result = **3.23dB**

**[19] Transmission Time Measurement**

Uncertainty in test result = **7.98%**

## **Section 3:**

## **Modifications**

### **3.1 Modifications Performed During Assessment**

No modifications were performed during the assessment

**Appendix A:****Formal Emission Test Results**

Abbreviations used in the tables in this appendix:

Spec	: Specification	ALSR	: Absorber Lined Screened Room
Mod	: Modification	OATS	: Open Area Test Site
EUT	: Equipment Under Test	ATS	: Alternative Test Site
SE	: Support Equipment	Ref	: Reference
L	: Live Power Line	Freq	: Frequency
N	: Neutral Power Line	MD	: Measurement Distance
E	: Earth Power Line	SD	: Spec Distance
Pk	: Peak Detector	Pol	: Polarisation
QP	: Quasi-Peak Detector	H	: Horizontal Polarisation
Av	: Average Detector	V	: Vertical Polarisation
CDN	: Coupling & decoupling network		

**A1 6 dB Bandwidth**

Title 47 of the CFR: Part 15 Subpart (c) 15.247(a)(2) requires the measurement of the bandwidth of the transmission between the -6 dB points on the transmitted spectrum.

RSS-210 Issue 8 December 2010 requires the measurement of the bandwidth of the transmission between the -6 dB points on the transmitted spectrum.

Test Details:	
Regulation	Part 15 Subpart (c) 15.247(a)(2), RSS-210 Annex 8.A8.2a
Measurement standard	ANSI C63.10, KDB Document: 558074
EUT sample number	S05
Modification state	0
SE in test environment	S01
SE isolated from EUT	None
Temperature	24°C
EUT set up	Refer to Appendix C

Channel Frequency (MHz)	$F_{\text{lower}}$	$F_{\text{Higher}}$	Measured 20 dB Bandwidth (kHz)	Limit	Result
2405	2404.221154	2405.833333	1612.179	>500kHz	Pass
2440	2439.213141	2440.799679	1586.538	>500kHz	Pass
2480	2479.221154	2480.793269	1572.115	>500kHz	Pass

Plots of the 6 dB bandwidth are contained in Appendix B of this test report.

**A2 Transmitter Peak Output Power**

Carrier power was verified with the EUT transmitting on its lowest, centre and highest carrier frequency in turn.

<b>Test Details:</b>	
Regulation	Title 47 of the CFR: Part15 Subpart (c) 15.247(b)(3)
Measurement standard	ANSI C63.10, KDB Document: 558074
EUT sample number	S05
Modification state	0
SE in test environment	S01
SE isolated from EUT	None
Temperature	24 <sup>0</sup> C
EUT set up	Refer to Appendix C

<b>Channel Frequency (MHz)</b>	<b>Conducted Peak Carrier Power (dBm)</b>	<b>Conducted Peak Carrier Power (mW)</b>	<b>Limit (W)</b>	<b>Result</b>
2405	1.04	1.27	1	Pass
2440	0.70	1.17	1	Pass
2480	0.09	1.02	1	Pass

**Notes:****Conducted Measurement**

Conducted measurements were performed with a temporary antenna connector provided by the client.

**A3 Transmitter Power Spectral Density**

Transmitter Power Spectral Density was verified with the EUT transmitting on its lowest, centre and highest carrier frequency in turn.

<b>Test Details:</b>	
Regulation	Part15 Subpart (c) 15.247(b)(3), RSS-210 Annex 8.A8.2b
Measurement standard	ANSI C63.10, KDB Document: 558074
EUT sample number	S05
Modification state	0
SE in test environment	S01
SE isolated from EUT	None
Temperature	24 <sup>0</sup> C
EUT set up	Refer to Appendix C

<b>Channel Frequency (MHz)</b>	<b>Conducted Peak Power Spectral Density</b>	<b>Limit (dBm)</b>	<b>Result</b>
2405	-2.62	+8	Pass
2440	-3.24	+8	Pass
2480	-3.62	+8	Pass

Notes:

Conducted Measurement

Conducted measurements were performed on the unique antenna connector.

Measurements performed as per KDB Document:

558074 D01 DTS Meas Guidance v02

Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

**A4 RF Antenna Conducted Spurious Emissions**

Measurement of conducted spurious emissions at the antenna port was performed using a peak detector with the RBW set to 100kHz and the VBW>RBW. Frequencies were scanned up through to the 10th harmonic with the EUT transmitting on its lowest, centre and highest carrier frequency in turn.

Regulation	Part 15 Subpart (c) Clause 15.247(d), RSS-210 Annex 8.A8.5
Measurement standard	ANSI C63.10, KDB Document: 558074
Frequency range	9 kHz to 25 GHz
EUT sample number	S05
Modification state	0
SE in test environment	S01
SE isolated from EUT	None
Temperature	24°C
EUT set up	Refer to Appendix C

The worst case conducted emission measurements at the antenna port are listed below:

Test Details: 2405 MHz					
Ref No.	Measured Freq (MHz)	Det.	Measured Peak Conducted power (RBW =100kHz) (dBuV)	Limit (dBuV)	Summary
1.	592.000	Pk	46.20	84.49	Pass
2.	4809.022	Pk	67.26	84.49	Pass
3.	9618.012	Pk	43.63	84.49	Pass

Test Details: 2440 MHz					
Ref No.	Measured Freq (MHz)	Det.	Measured Peak Conducted power (RBW =100kHz) (dBuV)	Limit (dBuV)	Summary
1.	608.00	Pk	50.71	84.21	Pass
2.	4879.01	Pk	67.89	84.21	Pass
3.	9758.00	Pk	40.89	84.21	Pass

Test Details: 2480MHz					
Ref No.	Measured Freq (MHz)	Det.	Measured Peak Conducted power (RBW =100kHz) (dBuV)	Limit (dBuV)	Summary
1.	624.00	Pk	45.27	84.01	Pass
2.	4958.99	Pk	66.59	84.01	Pass
3.	9197.98	Pk	34.45	84.01	Pass



**Notes:**

1. The conducted emission limit for emissions are based on a transmitted carrier level of 15.247(b) / Annex 8, A8.4(2). With the EUT transmitting on its lowest, centre and highest carrier frequencies in turn, emissions from the EUT are required to be 20 dB below the level of the highest fundamental as measured within a 100 kHz RBW in accordance with 15.247(d) and Annex 8, A8.5 using a peak detector.
2. The RBW = 100 kHz, Video bandwidth (VBW) > RBW and the radio spectrum was investigated up to the 10th harmonic in accordance 15.33 (a)(1) and RSS-GEN 4.9.
3. The measurements at 2400 MHz and 2483.5 MHz were made to ensure band edge compliance.
4. The carrier level was measured whilst varying the supply voltage between 85% and 105% of the nominal supply voltage as required by 15.31(e). No variation in carrier level was observed. All other emissions were at least 20dB below the test limit

The limit defined using the following formula in accordance with 15.247(d) and Annex 8, A8.5

$$\text{The limit in 100 kHz RBW} = (\text{Maximum Peak Conducted Carrier}) - 20\text{dB}$$

Where:

The maximum peak conducted power was measured using a peak power meter. Please refer to section A1 of this test report.

Channel Frequency (MHz)	Measured Peak Carrier (dBμV)	Emission Limit In a 100 kHz RBW (dBμV)
2405	104.49	84.49
2440	104.21	84.21
2480	104.01	84.01

**A5 Radiated Electric Field Emissions**

Preliminary scans were performed using a peak detector with the RBW = 100kHz. The maximum permitted field strength is listed in Section 15.209 and per RSS – 210 Annex 8, A8.5. The EUT was set to transmit on its lowest, centre and highest carrier frequency.

The following test site was used for final measurements as specified by the standard tested to:

3m open area test site : ☐

3m alternative test site : ☒

The effect of the EUT set-up on the measurements is summarised in note (c) below.

Test Details:	
Regulation	Part 15 Subpart (c) Clause 15.247(d), RSS – 210 Annex 8, A8.5
Measurement standard	ANSI C63.10, KDB Document: 558074
Frequency range	30MHz – 25GHz
EUT sample number	S05
Modification state	0
SE in test environment	S01
SE isolated from EUT	None
Temperature	24°C
EUT set up	Refer to Appendix C
Photographs (Appendix F)	1 & 2

The worst case radiated emission measurements for spurious emissions and harmonics that fall within the restricted bands are listed below:

Test Details: 2405 MHz									
Ref No.	FREQ. (MHz)	MEAS Rx (dBµV)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dBµV/m)	EXTRAP FACT (dB)	FIELD ST'GH (µV/m)	LIMIT (µV/m)
No Significant Emissions Within 20 dB of the limit									

Test Details: 2440 MHz									
Ref No.	FREQ. (MHz)	MEAS Rx (dBµV)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dBµV/m)	EXTRAP FACT (dB)	FIELD ST'GH (µV/m)	LIMIT (µV/m)
No Significant Emissions Within 20 dB of the limit									

Test Details: 2480 MHz									
Ref No.	FREQ. (MHz)	MEAS Rx (dBµV)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dBµV/m)	EXTRAP FACT (dB)	FIELD ST'GH (µV/m)	LIMIT (µV/m)
No Significant Emissions Within 20 dB of the limit									

**Radiated Electric Field Emissions – Bandedge Compliance**

Lower Bandedge Compliance	
Measurement	PK
Carrier power (100kHz RBW)	94.14 dBuV/m
Power At Bandedge dBuV/m	98.20 dBuV/m
Power At Bandedge dBc	-40.61 dBc
Limit (@ -20 dBc)	74.14 dBuV/m
Margin	-20.61 dB
Result	Compliant

Upper Bandedge Compliance		
Measurement	PK	AV
Carrier power (5MHz RBW)	96.52 dBuV/m	95.09 dBuV/m
dBuV (100kHz RBW)	98.20 dBuV	88.86 dBuV
delta in 100kHz	-37.55 dB	-41.25 dB
Power At Bandedge dBuV/m	58.97 dBuV/m	53.84 dBuV/m
Limit dBuV/m	74.00 dBuV/m	54.00 dBuV/m
Margin	-15.03 dB	0.16 dB
Result	Compliant	Compliant

Upper Bandedge Compliance measurement made using the delta marker method as detailed in ANSI C63.10 and KDB Document: 558074

Plots are contained in appendix B

**Notes:**

- 1 Any testing performed below 30 MHz was performed using a magnetic loop antenna in accordance with ANSI C63.10: section 4.5, Table 1
- 2 In accordance with 15.35(b), above 1 GHz, emissions measured using a peak detector shall not exceed a level 20 dB above the average limit.
- 3 Measurements at 2400 & 2483.5 MHz were made to ensure band edge compliance.
- 4 Testing was performed with the EUT orientated in three orthogonal planes and the maximum emissions level recorded. In addition, the EUT antenna was varied within its range of motion in order to maximise emissions.
- 5 For Frequencies below 1 GHz, RBW= 100 kHz, testing was performed with CISPR16 compliant test receiver with QP detector. Above 1 GHz tests were performed using a spectrum analyser using the following settings:
 

Peak	RBW=VBW= 1MHz
Average	RBW=VBW= 1MHz

These settings as per ANSI C63.10

The upper and lower frequency of the measurement range was decided according to 47 CFR Part 15 Clause 15.33(a) and 15.33(a)(1) and RSS-Gen 4.3.

Radiated emission limits (47 CFR Part 15: Clause 15.209) for emissions falling within the restricted bands defined in 15.205(a) and RSS-Gen 7.2.2:

Frequency of emission (MHz)	Field strength $\mu\text{V/m}$	Measurement Distance m	Field strength $\text{dB}\mu\text{V/m}$
0.009-0.490	$2400/F(\text{kHz})$	300	$67.6/F(\text{kHz})$
0.490-1.705	$24000/F(\text{kHz})$	30	$87.6/F(\text{kHz})$
1.705-30	30	30	29.5
30-88	100	3	40.0
88-216	150	3	43.5
216-960	200	3	46.0
Above 960	500	3	54.0

**Notes:**

- (a) Where results have been measured at one distance, and a signal level displayed at another, the results have been extrapolated using the following formula:

$$\text{Extrapolation (dB)} = 20 \log_{10} \left( \frac{\text{measurement distance}}{\text{specification distance}} \right)$$

The results displayed take into account applicable antenna factors and cable losses.

- (b) The levels may have been rounded for display purposes.
- (c) The following table summarises the effect of the EUT operating mode, internal configuration and arrangement of cables / samples on the measured emission levels :

	See (i)	See (ii)	See (iii)	See (iv)
Effect of EUT operating mode on emission levels	✓			
Effect of EUT internal configuration on emission levels	✓			
Effect of Position of EUT cables & samples on emission levels			✓	
(i) Parameter defined by standard and / or single possible, refer to Appendix D (ii) Parameter defined by client and / or single possible, refer to Appendix D (iii) Parameter had a negligible effect on emission levels, refer to Appendix D (iv) Worst case determined by initial measurement, refer to Appendix D				

**A6     Antenna Gain**

The maximum antenna gain for the antenna types to be used with the EUT, as declared by the client, is 3.5 dBi.

**A7 Unintentional Radiated Electric Field Emissions**

Preliminary scans were performed using a peak detector with the RBW = 100kHz. The maximum permitted field strength is listed in Section 15.109 and in RSS- GEN Section 7.2.3. The EUT was set to receive mode only on its lowest, centre and highest carrier frequency in turn.

The following test site was used for final measurements as specified by the standard tested to :

3m open area test site :

☐

3m alternative test site :

☒

Test Details:	
Regulation	Part 15 Subpart (b) Clause 15.109, RSS – GEN Section 7.2.3
Measurement standard	ANSI C63.10
Frequency range	30MHz to 25 GHz
EUT sample number	S05
Modification state	0
SE in test environment	S01
SE isolated from EUT	None
Temperature	24 <sup>0</sup> C
EUT set up	Refer to Appendix C
Photographs (Appendix F)	1 & 2

The worst case radiated emission measurements for spurious emissions:

Test Details: 2405 MHz									
Ref No.	FREQ. (MHz)	MEAS Rx (dBμV)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dBμV/m)	EXTRAP FACT (dB)	FIELD ST'GH (μV/m)	LIMIT (μV/m)
No Significant Emissions Within 20 dB of the limit									

Test Details: 2440 MHz									
Ref No.	FREQ. (MHz)	MEAS Rx (dBμV)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dBμV/m)	EXTRAP FACT (dB)	FIELD ST'GH (μV/m)	LIMIT (μV/m)
No Significant Emissions Within 20 dB of the limit									

Test Details: 2480 MHz									
Ref No.	FREQ. (MHz)	MEAS Rx (dBμV)	CABLE LOSS (dB)	ANT FACT. (dB/m)	PRE AMP (dB)	FIELD ST'GH (dBμV/m)	EXTRAP FACT (dB)	FIELD ST'GH (μV/m)	LIMIT (μV/m)
No Significant Emissions Within 20 dB of the limit									

Sample Plots for 2440 MHz operation can be found in Appendix B

**Notes:**

- 1 Any testing performed below 30 MHz was performed using a magnetic loop antenna in accordance with ANSI C63.10: section 4.5, Table 1 For emissions below 30MHz the cable losses are assumed to be negligible.
- 2 In accordance with 15.35(b), above 1 GHz, emissions measured using a peak detector shall not exceed a level 20 dB above the average limit.
- 3 Testing was performed with the EUT orientated in three orthogonal planes and the maximum emissions level recorded. In addition, the EUT antenna was varied within its range of motion in order to maximise emissions.
- 4 For Frequencies below 1 GHz, RBW = 120 kHz, testing was performed with CISPR16 compliant test receiver with QP detector. Above 1 GHz tests were performed using a spectrum analyser using the following settings:

Peak RBW= 1MHz, VBW ≥ RBW  
 Average RBW= 1MHz, VBW ≥ RBW

The upper and lower frequency of the measurement range was decided according to 47 CFR Part 15 Clause 15.33(a) and 15.33(a)(1) and RSS-Gen 4.3.

Radiated emission limits 47 CFR Part 15: Clause 15.209 and RSS – GEN Section 7.2.3 for all emissions:

Frequency of emission (MHz)	Field strength $\mu\text{V/m}$	Measurement Distance m	Field strength $\text{dB}\mu\text{V/m}$
30-88	100	3	40.0
88-216	150	3	43.5
216-960	200	3	46.0
Above 960	500	3	54.0

- (a) Where results have been measured at one distance, and a signal level displayed at another, the results have been extrapolated using the following formula:

$$\text{Extrapolation (dB)} = 20 \log_{10} \left( \frac{\text{measurement distance}}{\text{specification distance}} \right)$$

- (b) The levels may have been rounded for display purposes.
- (c) The following table summarises the effect of the EUT operating mode, internal configuration and arrangement of cables / samples on the measured emission levels :

	See (i)	See (ii)	See (iii)	See (iv)
Effect of EUT operating mode on emission levels	✓			
Effect of EUT internal configuration on emission levels	✓			
Effect of Position of EUT cables & samples on emission levels			✓	
(i) Parameter defined by standard and / or single possible, refer to Appendix D (ii) Parameter defined by client and / or single possible, refer to Appendix D (iii) Parameter had a negligible effect on emission levels, refer to Appendix D (iv) Worst case determined by initial measurement, refer to Appendix D				




**Appendix B:****Supporting Graphical Data**

This appendix contains graphical data obtained during testing.


Notes:

- (a) The radiated electric field emissions and conducted emissions graphical data in this appendix is preview data. For details of formal results, refer to Appendix A and Appendix B.
- (b) The time and date on the plots do not necessarily equate to the time of the test.
- (c) Where relevant, on power line conducted emission plots, the limit displayed is the average limit, which is stricter than the quasi peak limit.
- (d) Appendix C details the numbering system used to identify the sample and its modification state.
- (e) The plots presented in this appendix may not be a complete record of the measurements performed, but are a representative sample, relative to the final assessment.




Date: 15.NOV.2012 10:15:33

### 6dB Bandwidth 2405 MHz




Date: 15.NOV.2012 10:07:20

### 6dB Bandwidth 2440 MHz




Date: 15.NOV.2012 10:05:37

### 6dB Bandwidth 2480 MHz




Date: 15.NOV.2012 10:42:38

### Conducted Spurious emissions 9kHz to 150 MHz – 2405MHz




Date: 15.NOV.2012 10:42:57

### Conducted Spurious emissions 150kHz to 30 MHz – 2405MHz




Date: 15.NOV.2012 10:43:57

### Conducted Spurious emissions 30 MHz to 1 GHz – 2405MHz




Date: 15.NOV.2012 10:38:35

### Conducted Spurious emissions 1 GHz to 5 GHz – 2405MHz




Date: 15.NOV.2012 10:41:26

## Conducted Spurious emissions 5 GHz to 10 GHz – 2405MHz




Date: 15.NOV.2012 10:41:41

## Conducted Spurious emissions 10 GHz to 15GHz – 2405MHz




Date: 15.NOV.2012 10:41:59

## Conducted Spurious emissions 15 GHz to 20 GHz – 2405MHz




Date: 15.NOV.2012 10:42:17

## Conducted Spurious emissions 20 GHz to 25 GHz – 2405MHz




Date: 15.NOV.2012 10:54:43

### Conducted Spurious emissions 9kHz to 150 MHz – 2440MHz




Date: 15.NOV.2012 10:55:05

### Conducted Spurious emissions 150kHz to 30 MHz – 2440 MHz



Date: 15.NOV.2012 10:55:32


### Conducted Spurious emissions 30 MHz to 1 GHz – 2440 MHz



Date: 15.NOV.2012 10:47:20


### Conducted Spurious emissions 1 GHz to 5 GHz – 2440 MHz






Date: 15.NOV.2012 10:49:51

### Conducted Spurious emissions 5 GHz to 10 GHz – 2440 MHz




Date: 15.NOV.2012 10:53:39

### Conducted Spurious emissions 10 GHz to 15GHz – 2440 MHz




Date: 15.NOV.2012 10:53:59

### Conducted Spurious emissions 15 GHz to 20GHz – 2440 MHz




Date: 15.NOV.2012 10:54:25

### Conducted Spurious emissions 20 GHz to 25GHz – 2440 MHz




Date: 15.NOV.2012 11:06:03

### Conducted Spurious emissions 9kHz to 150 MHz – 2480MHz




Date: 15.NOV.2012 11:06:30

### Conducted Spurious emissions 150 kHz to 30 MHz – 2480MHz




Date: 15.NOV.2012 11:06:57

### Conducted Spurious emissions 30 MHz to 1 GHz – 2480MHz




Date: 15.NOV.2012 11:04:49

### Conducted Spurious emissions 1 GHz to 5 GHz – 2480MHz




Date: 15.NOV.2012 11:04:49

### Conducted Spurious emissions 5 GHz to 10 GHz– 2480MHz




Date: 15.NOV.2012 11:05:08

### Conducted Spurious emissions 10 GHz to 15 GHz– 2480MHz



Date: 15.NOV.2012 11:05:26


### Conducted Spurious emissions 15 GHz to 20 GHz– 2480MHz



Date: 15.NOV.2012 11:05:41


### Conducted Spurious emissions 20 GHz to 25 GHz– 2480MHz

## Conducted Bandedge Compliance




Date: 15.NOV.2012 10:37:02

## Lower Bandedge




Date: 15.NOV.2012 11:03:56

## Upper Bandedge




Date: 15.NOV.2012 10:22:12

### Conducted carrier power 2405MHz



Date: 15.NOV.2012 10:25:46


### Conducted carrier power 2440 MHz



Date: 15.NOV.2012 10:29:28


### Conducted carrier power 2480 MHz






Date: 15.NOV.2012 10:33:47

### Conducted power spectral density 2405MHz




Date: 15.NOV.2012 10:32:47

### Conducted power spectral density 2440 MHz




Date: 15.NOV.2012 10:31:20

### Conducted power spectral density 2480 MHz




Radiated Spurious emissions 30 MHz to 1 GHz – 2405MHz




Date: 20.NOV.2012 14:03:32

Radiated Spurious emissions 1 GHz to 5 GHz – 2405MHz




Date: 20.NOV.2012 14:03:18

## Radiated Spurious emissions 5 GHz to 8 GHz – 2405MHz




Date: 20.NOV.2012 14:02:52

## Radiated Spurious emissions 8 GHz to 13 GHz – 2405MHz




Date: 20.NOV.2012 14:02:32

### Radiated Spurious emissions 13 GHz to 18GHz – 2405MHz




Date: 20.NOV.2012 15:21:29

### Radiated Spurious emissions 18 GHz to 25 GHz – 2405MHz




### Radiated Spurious emissions 30 MHz to 1 GHz – 2440MHz




Date: 20.NOV.2012 13:52:50

### Radiated Spurious emissions 1 GHz to 5 GHz – 2440MHz




Date: 20.NOV.2012 13:52:20

## Radiated Spurious emissions 5 GHz to 8 GHz – 2440MHz




Date: 20.NOV.2012 13:51:57

## Radiated Spurious emissions 8 GHz to 13 GHz – 2440MHz




Date: 20.NOV.2012 13:51:39

### Radiated Spurious emissions 13 GHz to 18GHz – 2440MHz




Date: 20.NOV.2012 15:20:38

### Radiated Spurious emissions 18 GHz to 25 GHz – 2440MHz




### Radiated Spurious emissions 30 MHz to 1 GHz – 2480MHz



Date: 20.NOV.2012 13:53:17


### Radiated Spurious emissions 1 GHz to 5 GHz – 2480MHz






Date: 20.NOV.2012 13:53:59

### Radiated Spurious emissions 5 GHz to 8 GHz – 2480MHz




Date: 20.NOV.2012 13:54:19

### Radiated Spurious emissions 8 GHz to 13 GHz – 2480MHz



Date: 20.NOV.2012 13:58:42


### Radiated Spurious emissions 13 GHz to 18GHz – 2480MHz



Date: 20.NOV.2012 15:20:15


### Radiated Spurious emissions 18 GHz to 25 GHz – 2480MHz

## Radiated Bandedge Compliance




Date: 20.NOV.2012 14:08:44

## Lower Bandedge




Date: 20.NOV.2012 14:32:24

## Carrier power For Delta Marker Method




Date: 20.NOV.2012 14:21:50

### Upper Bandedge – Markers On Peak Trace




Date: 20.NOV.2012 14:22:38

### Upper Bandedge – Markers On Average Trace




### Unintentional Radiated Spurious emissions 30 MHz to 1 GHz




Date: 20.NOV.2012 14:56:01

### Unintentional Radiated Spurious emissions 1 GHz to 5 GHz




Date: 20.NOV.2012 15:07:43

### Unintentional Radiated Spurious emissions 5 GHz to 8 GHz




Date: 20.NOV.2012 14:55:07

### Unintentional Radiated Spurious emissions 8 GHz to 13 GHz



Date: 20.NOV.2012 14:54:41

### Unintentional Radiated Spurious emissions 13 GHz to 18GHz



Date: 20.NOV.2012 15:18:57

### Unintentional Radiated Spurious emissions 18 GHz to 25 GHz

**Appendix C:****Additional Test and Sample Details**

This appendix contains details of:

1. The samples submitted for testing.
2. Details of EUT operating mode(s)
3. Details of EUT configuration(s) (see below).
4. EUT arrangement (see below).

Throughout testing, the following numbering system is used to identify the sample and it's modification state:

**Sample No:** Sxx Mod w

where:

xx	= sample number	eg. S01
w	= modification number	eg. Mod 2

The following terminology is used throughout the test report:

**Support Equipment (SE)** is any additional equipment required to exercise the EUT in the applicable operating mode. Where relevant SE is divided into two categories:

SE in test environment: The SE is positioned in the test environment and is not isolated from the EUT (e.g. on the table top during REFE testing).

SE isolated from the EUT: The SE is isolated via filtering from the EUT. (e.g. equipment placed externally to the ALSR during REFE testing).

**EUT configuration** refers to the internal set-up of the EUT. It may include for example:

- Positioning of cards in a chassis.
- Setting of any internal switches.
- Circuit board jumper settings.
- Alternative internal power supplies.

Where no change in EUT configuration is **possible**, the configuration is described as "single possible configuration".

**EUT arrangement** refers to the termination of EUT ports / connection of support equipment, and where relevant, the relative positioning of samples (EUT and SE) in the test environment.

For further details of the test procedures and general test set ups used during testing please refer to the related document "EMC Test Methods - An Overview", which can be supplied by TRaC Global upon request.



**C1) Test samples**

The following samples of the apparatus were submitted by the client for testing :

Sample No.	Description	Identification
S01	USB – TTL Serial Cable	TTL-232-3V3
S02	Endnode Radiated Sample	
S05	Endnode with temporary Antenna Connector	

The following samples of apparatus were submitted by the client as host, support or drive equipment (auxiliary equipment):

Sample No.	Description	Identification

The following samples of apparatus were supplied by TRaC Global as support or drive equipment (auxiliary equipment):

Identification	Description
IT-0146	Test Laptop

**C2) EUT Operating Mode During Testing.**

During testing, the EUT was exercised as described in the following tables :

Test	Description of Operating Mode:
All Transmitter tests detailed in this report	EUT transmitting modulated carrier for all formal measurements, CW signal for spurious emissions scans only

Test	Description of Operating Mode:
Receiver conducted and radiated (ERP) spurious emissions	EUT active in receive but non-transmitting.

**C3) EUT Configuration Information.**

The EUT was submitted for testing in one single possible configuration.

**C4) List of EUT Ports**

The tables below describe the termination of EUT ports:

Sample : S05  
Tests : Conducted

Port	Description of Cable Attached	Cable length	Equipment Connected
J1	6 Way Serial – USB cable	2m	Laptop

Sample : S02  
Tests : Radiated Emissions

Port	Description of Cable Attached	Cable length	Equipment Connected
J1	6 Way Serial – USB cable	2m	Laptop

\* Only connected during setup.

**C5 Details of Equipment Used**

TRAC Ref	Type	Description	Manufacturer	CalDate	Interval.	Cal Due
UH281	FSU46	Spectrum Analyser	R&S	09/02/2012	12	09/02/2013
L138	3115	1-18GHz Horn	EMCO	08/11/2011	24	08/11/2013
L572	8449B	Pre Amp	Agilent	24/11/2010	24	24/11/2012
L317	ESVS10	Receiver	R&S	21/12/2011	12	21/12/2012
UH191	CBL611/A	Bilog	Chase	08/11/2010	24	08/11/2012
L300	20240-20	18GHz - 26GHz Horn	Flann	17/11/2011	24	17/11/2013
REF940	ATS	Ferrite Lined Chamber	Rainford EMC	26/06/2012	12	26/06/2013

**Appendix D:**

**Additional Information**

No additional information is included within this test report.

**Appendix E:****Calculation of the duty cycle correction factor**

Using a spectrum analyser in zero span mode, centred on the fundamental carrier frequency with a RBW of 1MHz and a video Bandwidth of 1MHz the sweep time was set accordingly to capture the pulse train. The transmit pulsewidths and period was measured. A plots of the pulse train is contained in Appendix B of this test report.

If the pulse train was less than 100 ms, including blanking intervals, the duty cycle was calculated by averaging the sum of the pulsewidths over one complete pulse train. However if the pulse train exceeds 100ms then the duty cycle was calculated by averaging the sum of the pulsewidths over the 100ms width with the highest average value. (The duty cycle is the value of the sum of the pulse widths in one period (or 100ms), divided by the length of the period (or 100ms). The duty cycle correction factor was then expressed in dB and the peak emissions adjusted accordingly to give an average value of the emission.

Correction factor dB =  $20 \times (\text{Log}_{10} \text{ Calculated Duty Cycle})$

Therefore the calculated duty cycle was determined:

The pulse train period was greater than >100ms and in as shown from the plots in contained in appendix B of this test report.

Duty cycle =  $\frac{\text{the sum of the highest average value pulsewidths over 100ms}}{100\text{ms}}$

e.g

$$= \frac{7.459\text{ms}}{100\text{ms}} = 0.07459$$

0.07459 or 7.459%

Correction factor (dB) =  $20 \times (\text{Log}_{10} 0.07459) = -22.54\text{dB}$

Duty cycle correction may not be applicable / required by the device covered in this report.

The correction factor above is for example of how the correction is calculated.

Any applicable duty cycle used will be recorded in the relevant results sections of this report.


## **Appendix F:**

## **Photographs and Figures**


The following photographs were taken of the test samples:

1. Radiated electric field emissions arrangement: Over view.
2. Radiated electric field emissions arrangement: close up.
3. Antenna port conducted test setup : Overview







Photograph 1



Photograph 2



Photograph 3



**Appendix G:****MPE Calculation**

OET Bulletin No. 65, Supplement C 01-01

**47 CFR §§1.1307 and 2.1091 & RSS - 102**

2.1091 Radio frequency radiation exposure evaluation: mobile devices.

For purposes of these requirements mobile devices are defined by the FCC as transmitters designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimetres is normally maintained between radiating structures and the body of the user or nearby persons. These devices are normally evaluated for exposure potential with relation to the MPE limits. As the 20cm separation specified under FCC rules may not be achievable under normal operation of the EUT, an RF exposure calculation is needed to show the minimum distance required to be less than 1mW/cm<sup>2</sup> power density limit, as required under FCC rules and 10W/m<sup>2</sup> power density limit, as required under IC rules.

$$1\text{mW/cm}^2 \quad \equiv \quad 10\text{W/m}^2$$

**Prediction of MPE limit at a given distance**

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{EIRP}{4 \pi R^2} \quad \text{re - arranged} \quad R = \sqrt{\frac{EIRP}{S 4 \pi}}$$

where:

S = power density

R = distance to the centre of radiation of the antenna

EIRP = EUT Maximum power

Note:

The EIRP measurement was performed by adding the declared antenna gain to the maximum conducted output power.

$$EIRP = 1.04 \text{ dBm} + 3.5 \text{ dBi}$$

$$EIRP = 4.54 \text{ dBm} \quad 2.844$$

Result

Prediction Frequency (MHz)	Maximum EIRP	Power density limit (S) (mW/cm <sup>2</sup> )	Distance (R) cm required to be less than 1mW/cm <sup>2</sup>
2405	2.844 mW	1	0.48



