



Prüfbericht-Nr.: <i>Test Report No.:</i>	10044135 001	Auftrags-Nr.: <i>Order No.:</i>	113154149	Seite 1 von 44 Page 1 of 44
Kunden-Referenz-Nr.: <i>Client Reference No.:</i>	N/A	Auftragsdatum: <i>Order date:</i>	March 8, 2013	
Auftraggeber: <i>Client:</i>	Schneider Electric (Australia) Pty. Ltd., 33-37 Port Wakefield Road, Gepps Cross, 5094, Australia			
Prüfgegenstand: <i>Test item:</i>	Wiser Home Controller MKII			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	WHC2_5918			
Auftrags-Inhalt: <i>Order content:</i>	NCC Test report (Bluetooth Portion of the Device) FCC Part 15C Test report			
Prüfgrundlage: <i>Test specification:</i>	NCC Low-power Radio-frequency Devices Technical Regulations LP0002(2011) FCC 47CFR Part 15: Subpart C Section 15.247			
Wareneingangsdatum: <i>Date of receipt:</i>	7/2/2013			
Prüfmuster-Nr.: <i>Test sample No.:</i>	TPE81936 TPE81935			
Prüfzeitraum: <i>Testing period:</i>	August 1, 2013 - October 22, 2013			
Ort der Prüfung: <i>Place of testing:</i>	EMC Laboratory Taipei			
Prüflaboratorium: <i>Testing laboratory:</i>	TUV Rheinland Taiwan Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
2013-10-30 Danny S. C. Sung/Project Manager		2013-10-30 Rene Charton/Senior Project Manager		
Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name / Stellung <i>Name / Position</i>
				
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i>		
* Legende: 1 = sehr gut 2 = gut 3 = befriedigend 4 = ausreichend 5 = mangelhaft P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet				
Legend: 1 = very good 2 = good 3 = satisfactory 4 = sufficient 5 = poor P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				

v04

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT

RESULT: *Passed*

5.1.2 PEAK OUTPUT POWER

RESULT: *Passed*

5.1.3 20dB BANDWIDTH

RESULT: *Passed*

**5.1.4 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN
100kHz BANDWIDTH**

RESULT: *Passed*

5.1.5 SPURIOUS EMISSION

RESULT: *Passed*

5.1.6 FREQUENCY SEPARATION

RESULT: *Passed*

5.1.7 NUMBER OF HOPPING FREQUENCY

RESULT: *Passed*

5.1.8 TIME OF OCCUPANCY

RESULT: *Passed*

5.2.1 MAINS CONDUCTED EMISSIONS

RESULT: *Passed*

Contents

1.	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS.....	5
2.	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	7
2.3	TRACEABILITY	8
2.4	CALIBRATION	8
2.5	MEASUREMENT UNCERTAINTY	8
3.	GENERAL PRODUCT INFORMATION.....	9
3.1	PRODUCT FUNCTION AND INTENDED USE	9
3.2	SYSTEM DETAILS AND RATINGS.....	9
3.3	INDEPENDENT OPERATION MODES.....	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS	11
3.5	SUBMITTED DOCUMENTS.....	11
4.	TEST SET-UP AND OPERATION MODES.....	12
4.1	PRINCIPLE OF CONFIGURATION SELECTION	12
4.2	TEST OPERATION AND TEST SOFTWARE.....	12
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	12
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	13
4.5	TEST SETUP DIAGRAM	13
5.	TEST RESULTS	15
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	15
5.1.1	<i>Antenna Requirement</i>	<i>15</i>
5.1.2	<i>Peak Output Power</i>	<i>16</i>
5.1.3	<i>20dB Bandwidth</i>	<i>20</i>
5.1.4	<i>Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth.....</i>	<i>24</i>
5.1.5	<i>Spurious Emission</i>	<i>31</i>
5.1.6	<i>Frequency Separation.....</i>	<i>32</i>
5.1.7	<i>Number of hopping frequency.....</i>	<i>34</i>
5.1.8	<i>Time of Occupancy</i>	<i>36</i>
5.2	MAINS EMISSIONS.....	39
5.2.1	<i>Mains Conducted Emissions.....</i>	<i>39</i>
6.	PHOTOGRAPHS OF THE TEST SET-UP.....	40

7.	LIST OF TABLES	44
8.	LIST OF PHOTOGRAPHS.....	44

1. General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix P: Photo Documentation external view
(File Name: 10044135APPENDIX P)

Appendix D: Test Result of Radiated Emissions
(File Name: 10044135APPENDIX D)

Test Specifications

The following standards were applied (in bold: product standards, otherwise: basic standards).

Table 1: Applied Standard and Test Levels

Radio
ANSI C63.4:2009, Public Notice DA 00-705
NCC Low-power Radio-frequency Devices Technical Regulations LP0002(2011)(100年6月28日)
FCC CFR47 Part 15: Subpart C Section 15.247

2. Test Sites

2.1 Test Facilities

TUV Rheinland Taiwan Ltd.

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)
FCC Registration No.: 365730

TAF Accredited NCC Test Lab. No.:0759

TAF Accreditation effective period: 2013-Jul-1st to 2016-Jun-30th



Testing Laboratory
0759

2.2 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Calibrated until	Used for test items
EMI Test Receiver	R&S	ESCI 7	1166.5950K07-100797-Pt	20-Dec-13	Spurious Emission and Frequency Band Edge
Bilog Antenna	TESEQ	CBL6111D	29802	29-Jun-14	Spurious Emission and Frequency Band Edge
Pre-Amplifier	HP	8447F	2805A03335	13-Dec-13	Spurious Emission and Frequency Band Edge
Spectrum Analyzer	R&S	FSV 40	100921	10-Jan-14	6dB Bandwidth Output Power Power Density Conducted Spurious Emissions Spurious Emission
Horn Antenna (1GHz~18GHz)	COM-POWER	AHA118	701251	2-Nov-13	Spurious Emission and Frequency Band Edge
Horn Antenna (18GHz~40GHz)	COM-POWER	AH840	101031	2-Sep-14	Spurious Emission and Frequency Band Edge
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	2-Sep-14	Spurious Emission and Frequency Band Edge
Preamplifier (18 GHz -40 GHz)	COMPOWER	PAM-840	461257	12-Nov-13	Spurious Emission and Frequency Band Edge
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	28-Sep-14	Spurious Emission and Frequency Band Edge
EMI Test Receiver	R&S	ESCI	101094	29-Aug-14	Mains Spurious Emission
LISN (1 phase)	R&S	ENV216	101243	5-Jun-14	Mains Spurious Emission
LISN	Rolf Heine	NNB-2/16Z	99080	30-Aug-14	Mains Spurious Emission

2.3 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements are $\pm 3\text{dB}$.

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-7}$
RF power, conducted	$\pm 1 \text{ dB}$
Adjacent channel power	$\pm 3 \text{ dB}$
Radiated emission of transmitter, valid up to 26 GHz	$\pm 6 \text{ dB}$
Radiated emission of receiver, valid up to 26 GHz	$\pm 6 \text{ dB}$
Temperature	$\pm 2 \text{ }^{\circ}\text{C}$
Humidity	$\pm 10 \%$

3. General Product Information

3.1 Product Function and Intended Use

The device is a Controller for home use with a BT and WiFi RF interface. This test report refers to the BT portion of the device.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment	Wiser Home Controller MKII
Type Designation	WHC2_5918
Brand Name	Schneider Electric
FCC ID	WZCWHC25918

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequency	2402 MHz ~ 2480 MHz
Channel Spacing	1 MHz
Channel number	79
Operation Voltage	220 V
Modulation	GFSK, $\pi/4$ QPSK, 8 DPSK
Antenna gain	1.97 dBi

Table 6: Frequency hopping information

Technical Specification	Description
Hopping Range	Hereby we declare that the maximum frequency of this device is: 2402-2480MHz. This is according the Bluetooth Core Specification V2.1+EDR for devices which will be operated in the USA. This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04).
Hopping Sequence	Example of a 79 hopping sequence in data mode: 33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73,07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56,69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43,15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47,
Receiver input bandwidth	<p>The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master.</p> <p>Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.</p> <p>Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case.</p> <p>That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.</p>

3.3 Independent Operation Modes

The basic operation modes are:

- A. Transmitting
 - 1. Low channel
 - 2. Middle channel
 - 3. High channel
- B. Receiving
- C. Standby
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------|
| - Bill of Material | - Circuit Diagram |
| - PCB Layout | - Instruction Manual |
| - Photo Document | - Rating Label |
| - Technical Description | |

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 4. All testing were performed according to the procedures in ANSI C63.10: 2009 and DA 00-705 of March 30, 2000.

The samples were used as follows:

Conducted: **TPE81935**

Radiation: **TPE81936**

Full test was applied on all test modes, but only worst case was shown.

4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Kind of Equipment	Manufacturer	Model Name	S/N
Laptop	MSI	MSI4532 (CX420MX)	CX420 MX-233TWK 1008000096

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test




Diagram of Measurement Equipment Configuration for Mains Conduction Measurement





Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:**Passed**

Test standard	:	LP0002(2011): 3.10.1, (3) FCC Part 15.247(b)(4), Part 15.203
Limit	:	the use of antennas with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 1.97 dBi. The antenna is a printed PCB trace with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Refer to EUT photo for details.

5.1.2 Peak Output Power

RESULT:
Passed

Test standard : LP0002(2011): 3.10.1, (2) ,
 FCC Part 15.247(b)(1)
 Basic standard : LP0002(2011) Appendix III
 DA 00-705 of March 30, 2000
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A

 Ambient temperature : 22-26 °C
 Relative humidity : 50-65 %
 Atmospheric pressure : 100-103 kPa

Table 7: Test result of Peak Output Power, GFSK modulation

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(W)	(W)
Low Channel	2402	8.2	0.00661	0.125
Middle Channel	2441	7.95	0.00624	0.125
High Channel	2480	8.03	0.00635	0.125


Table 8: Test result of Peak Output Power, 8DPSK modulation

Channel	Channel Frequency	Peak Output Power		Limit
	(MHz)	(dBm)	(W)	(W)
Low Channel	2402	8.39	0.00690	0.125
Middle Channel	2441	8.2	0.00661	0.125
High Channel	2480	8.24	0.00667	0.125


Pmax: 6.9 mW

Test Plot of Peak Output Power, GFSK modulation


Low Channel



Middle Channel




High Channel




Date: 16.AUG.2013 11:29:22

Test Plot of Peak Output Power, 8DPSK modulation


Low Channel



Date: 16.AUG.2013 11:30:44

Middle Channel


Date: 16.AUG.2013 11:30:08

High Channel


Date: 16.AUG.2013 11:29:52

5.1.3 20dB Bandwidth

RESULT:
Passed

Test standard : LP0002(2011): 3.10.1, (6.1.1) ,
 FCC Part 15.247(a)(1)
 Basic standard : LP0002(2011) Appendix III
 DA 00-705 of March 30, 2000
 Kind of test site : Shielded room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A

 Ambient temperature : 22-26°C
 Relative humidity : 50-65%
 Atmospheric pressure : 100-103kPa

Table 9: Test result of 20dB Bandwidth, GFSK modulation

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2402	933.4	1.5	Pass
Mid Channel	2441	955.1	1.5	Pass
High Channel	2480	955.1	1.5	Pass

Note: Limit is for Channel Separation of 1 MHz and a power limit of 125 mW.


Table 10: Test result of 20dB Bandwidth, 8DPSK modulation

Channel	Channel Frequency (MHz)	20dB Bandwidth (kHz)	Limit (MHz)	Result
Low Channel	2402	1332.9	1.5	Pass
Mid Channel	2441	1332.9	1.5	Pass
High Channel	2480	1293.8	1.5	Pass

Note: Limit is for Channel Separation of 1 MHz and a power limit of 125 mW.


Test Plot of 20dB Bandwidth, GFSK modulation

Low Channel




Date: 16.AUG.2013 11:35:14


Middle Channel




Date: 16.AUG.2013 11:36:00

High Channel



Date: 16.AUG.2013 11:36:34

Test Plot of 20dB Bandwidth, 8DPSK modulation
Low Channel


Date: 16.AUG.2013 11:36:11

Middle Channel


Date: 16.AUG.2013 11:37:38

High Channel


Date: 16.AUG.2013 11:37:06

**5.1.4 Conducted spurious emissions and Frequency Band Edge
measured in 100kHz Bandwidth****RESULT:****Passed**

Test standard	:	LP0002(2011): 3.10.1, (5), FCC part 15.247(d)
Basic standard	:	LP0002(2011) Appendix III DA 00-705 of March 30, 2000
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

Test setup


Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	22-26°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.


Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

Test Plot of 100kHz Conducted Emissions, GFSK modulation


Low Channel



Middle Channel




High Channel



Date: 16.AUG.2013 11:45:13



Test Plot of 100kHz Conducted Emissions, 8DPSK modulation

Low Channel




Date: 16.AUG.2013 11:46:19

Middle Channel


High Channel



Test Plot of 100kHz Bandwidth of Frequency Band Edge, GFSK modulation

Low Channel




Date: 16.AUG.2013 11:47:30


High Channel




Date: 16.AUG.2013 11:47:53

Hopping On



Date: 16.AUG.2013 11:48:20

Test Plot of 100kHz Bandwidth of Frequency Band Edge, 8DPSK modulation
Low Channel


Date: 16.AUG.2013 11:49:28

High Channel


Date: 16.AUG.2013 11:49:08

Hopping On


Date: 16.AUG.2013 11:48:45

5.1.5 Spurious Emission

RESULT:
Passed

Test standard	:	LP0002(2011): 3.10.1, (5), FCC part 15.247(d), FCC 15.205, FCC 15.209
Basic standard	:	LP0002(2011) Appendix III ANSI C63.10: 2009
Limits	:	Radiated emissions which fall in the restricted bands, as defined in LP0002(2011): 2.7 , must comply with the radiated emission limits specified in LP0002(2011): 2.8 Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a), must comply with the radiated emission limits specified in FCC 15.209(a). Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2011): 2.8 Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in FCC 15.209(a) and FCC 15.249(a).
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A, B

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic. For details refer to Appendix 2. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The X Axis orientation is the worst-case and recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

5.1.6 Frequency Separation

RESULT:
Passed

Test standard : LP0002(2011): 3.10.1, (6.1.1)
 FCC part 15.247(a)(1)
 Basic standard : LP0002(2011) Appendix III
 DA 00-705 of March 30, 2000
 Limit : $\geq 25\text{kHz}$ or $2/3$ of 20dB bandwidth, whichever is greater

Test setup


Test Channel : Low/ Middle/ High
 Operation Mode : A
 Ambient temperature : 24°C
 Relative humidity : 53%

Table 11: Test result of Frequency Separation


Channel	Channel Frequency (MHz)	Measured Channel Separation (MHz)	Limit (kHz)	Result
Record Channel	2441	1	$\geq 25\text{kHz}$ or $2/3$ of 20dB bandwidth	Pass
Record Channel adj 1	2440			
Record Channel adj 2	2442			

Test Plot of Frequency Separation

GFSK



Date: 16.AUG.2013 11:41:11



Date: 16.AUG.2013 11:41:55

5.1.7 Number of hopping frequency**RESULT:****Passed**

Test standard : LP0002(2011): 3.10.1, (6.1.2)
FCC part 15.247(a)(1)(iii)
Basic standard : LP0002(2011) Appendix III
DA 00-705 of March 30, 2000
Limits : ≥ 15 non-overlapping channels
Kind of test site : Shield room

Test setup



Test Channel : Low/ Middle/ High
Operation Mode : A

Ambient temperature : 22-26°C
Relative humidity : 50-65%
Atmospheric pressure : 100-103 kPa

Table 12: Test result of Number of hopping frequency

Frequency Range	Measured Quantity of Hopping Channel	Limit	Result
<u>2400</u> to <u>2483.5</u> MHz	79	≥ 15	Pass

Test Plot of Number of hopping frequencies



5.1.8 Time of Occupancy

RESULT:
Passed

Test standard : LP0002(2011): 3.10.1, (6.1.2)
 FCC part 15.247(a)(1)(iii)
 Basic standard : LP0002(2011) Appendix III
 DA 00-705 of March 30, 2000
 Limits : 0.4s
 Kind of test site : Shield room

Test setup

Test Channel : Low/ Middle/ High
 Operation Mode : A
 Ambient temperature : 22-26°C
 Relative humidity : 50-65%
 Atmospheric pressure : 100-103 kPa

Table 13: Test result of Time of Occupancy


Data Mode	Captured Burst (s)	Dwell time (s)	On+Off time (s)	Limit (s)	Result
DH5	0.0030	0.3166	0.003754	0.4	Pass
3DH5	0.0030	0.3188	0.003783	0.4	Pass

Note:


Dwell time = Pulse width x (Hopping rate / Number of channels) x Period

Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds.

Test Plot of Time of Occupancy, GFSK modulation




Date: 16.AUG.2013 11:32:20




Date: 16.AUG.2013 11:32:35

Test Plot of Time of Occupancy, 8DPSK modulation



Date: 16.AUG.2013 11:33:41



Date: 16.AUG.2013 11:33:54

5.2 Mains Emissions

5.2.1 Mains Conducted Emissions

RESULT:**Passed**

Test standard	:	LP0002: 2.3 FCC Part 15.207 FCC Part 15.107
Limits	:	Mains Conducted emissions as defined in above test standards must comply with the mains conducted emission limits specified
Kind of test site	:	Shielded Room

Test setup

Test Channel	:	Middle
Operation mode	:	A


Remark: For details refer to Appendix D.

6. Photographs of the Test Set-Up

Photograph 1: Set-up for Spurious Emissions (Front View)



Photograph 2: Set-up for Spurious Emissions (Back View 1)



Photograph 3: Set-up for Spurious Emissions (Back View 2)



Photograph 4: Set-up for Conducted testing



Photograph 5: Set-up for for Mains Conducted testing Back



Photograph 6: Set-up for for Mains Conducted testing Front



7. List of Tables

Table 1: Applied Standard and Test Levels	5
Table 2: List of Test and Measurement Equipment	7
Table 3: Emission Measurement Uncertainty.....	8
Table 4: Basic Information of EUT	9
Table 5: Technical Specification of EUT	9
Table 5: Frequency hopping information.....	10
Table 6: Test result of Peak Output Power, GFSK modulation.....	16
Table 7: Test result of Peak Output Power, 8DPSK modulation.....	16
Table 8: Test result of 20dB Bandwidth, GFSK modulation.....	20
Table 9: Test result of 20dB Bandwidth, 8DPSK modulation.....	20
Table 12: Test result of Frequency Separation	32
Table 13: Test result of Number of hopping frequency	34
Table 14: Test result of Time of Occupancy.....	36

8. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View).....	40
Photograph 2: Set-up for Spurious Emissions (Back View 1)	41
Photograph 3: Set-up for Spurious Emissions (Back View 2)	42
Photograph 4: Set-up for Conducted testing	42
Photograph 5: Set-up for for Mains Conducted testing Back	43
Photograph 6: Set-up for for Mains Conducted testing Front.....	43