

TUV SUD BABT FCB Octagon House, Segensworth Road, Fareham, Hampshire, PO15 5RL

Date: December 04, 2014

RF exposure analysis for the equipment BE70 (FCC ID: X26BE70)

1. Introduction

The device BE70 (FCC ID: X26BE70) is a wireless hearing instrument used to amplify sound from the surrounding to the end user and also receive audio signals through wireless connection to accessories. It contains a multi-mode 2.4GHz radio which operates, time & frequency divided, in either BlueTooth Low Energy mode (BTLE) or a proprietary "Proximity" mode and is intended for use within 20 cm of humans.

2. SAR limits

According to § 2.1093 (d) (2) the limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and peak spatial-average SAR limit is 1.6 W/kg, averaged over any 1 gram of tissue over the whole body.

3. Compliance criteria:

Individual transmitters are deeded to comply with § 2.1093 requirements if the output power of the transmitter meets the conditions specified in section 4.3.1 (Standalone SAR test exclusion) considerations of the document "KDB 447498 D01 General RF Exposure Guidance v05r02".

4. Compliance calculations:

Mode	Sub-mode	Frequency	Average field strength (dBµV/m)	Average output power (mW)	Evalutation distance per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 (mm)	SAR Test Exclusion Thresholds per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 - 1) (mW)	SAR Test Exclusion Thresholds per KDB 447498 D01 General RF Exposure Guidance v05r02 - 4.3.1 - 1)
BLE	BLE	2402	78,95	0,081	5	10	COMPLIANT
		2440	79,4	0,016	5	10	COMPLIANT
		2480	78,24	0,012	5	10	COMPLIANT
Proximity	Proximity	2404	72,05	0,003	5	10	COMPLIANT
		2440	73,15	0,004	5	10	COMPLIANT
		2478	72,45	0,003	5	10	COMPLIANT

Sincerely,

By: Lars Hagander

Title: Vice president, Corporate Quality

Company: GN Hearing A/S, Lautrupbjerg 7, 2750 Ballerup, Denmark

Telephone / Fax: +45 45 75 21 00 / +45 45 75 44 29

e-mail: lhagander@gnresound.dk