Jongo T6 RF Exposure:-

The Jongo T6 is intended as a mobile device. A warning statement is included in the user manual advising users to maintain a minimum distance of 20cm.

Evaluation is therefore for exposure potential against the MPE limits given in Appendix A of OET Bulletin 65, Supplement C: 1500-100,000MHz; 1mW/cm²

Compliance requirements are based upon General population / Uncontrolled exposure.

Equation (3) of OET Bulletin 65:

$$S = \frac{FG}{4\pi \epsilon R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g. mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna (appropriate units, e.g. cm)

Substituting known values for the Jongo T6:

WiFi RF worst case Peak conducted power, P = 26.9mW (+13.8dBm).

WiFi antenna gain (measured), G = +4.7 dB.

n.b. although the specified gain for the chip antenna is 0dBi, this is the best gain (Low channel gain) measured in practice.

Distance, R = 20cm (for mobile use).

$$S = 0.0141$$
 < 1mW/cm²

The Jongo T6 will be internally fitted with a pre-approved FCC Bluetooth USB dongle, which would therefore be co-located. Maximum power of all Bluetooth devices is 100mW eirp. The maximum MPE is therefore as follows.

Equation (3) of OET Bulletin 65:

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g. mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna (appropriate units, e.g. cm)

Bluetooth worst case average power, P = 100mW

Bluetooth antenna gain (maximum with above power is unity), G = 1.

Distance, R = 20cm (for mobile use).

$$S = 0.002$$
 < 1mW/cm²

For co-location we can compare both items to the limit and sum the percentage of limit to check 100% not exceeded:

$$0.02/1 + 0.0141/1 = 3.41\%$$
 limit < 100%