Certification Exhibit

FCC ID: X32-CDSSG000

FCC Rule Part: 47 CFR Part 2.1093

TÜV SÜD Project Number: 72143908

Manufacturer: iKeyless, LLC
Model: CDSSL-G000

RF Exposure

Model(s): CDSSL-G000   **FCC ID: X32-CDSSG000**

<u>**General Information:**</u>
Applicant: iKeyless, LLC
Environment: General Population/Uncontrolled Exposure
Exposure Conditions: Portable

<u>**Technical Information:**</u>
Minimum Test Separation Distance: 5 mm
Highest Operating Frequency: 433.92 MHz
Antenna Type: PCB Loop Antenna
Antenna Gain: -11 dBi
Maximum Transmitter Conducted Power: 2.27 dBm, 1.69 mW
Maximum Transmitter EIRP: -8.73 dBm, 0.13396767 mW

<u>**Justification for SAR Test Exclusion:**</u>

<u>Standalone SAR Test Exclusion:</u>
Per KDB 447498 D01 General RF Exposure Guidance v05r02, the standalone 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

= (1.69 / 5)*($\sqrt{0.43}$) = 0.2
0.2 < 3.0

Standalone SAR test exclusion is applied.

Project: 72143908   **TÜV SÜD America Inc.**   **Page 2**