


Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmitter (802.11n MCS8 14.4Mbps 20M-BW)-ANT 1+2 (2412MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2412.00	17850	>500	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmitter (802.11n MCS8 14.4Mbps 20M-BW)-ANT 1+2 (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
6	2437.00	17850	>500	Pass


Figure Channel 6:



Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmitter (802.11n MCS8 14.4Mbps 20M-BW)-ANT 1+2 (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
11	2462.00	17900	>500	Pass


Figure Channel 11:



Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 5: Transmitter (802.11n MCS0 15Mbps 40M-BW)-ANT 1 (2422MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2422.00	35600	>500	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 5: Transmitter (802.11n MCS0 15Mbps 40M-BW)-ANT 1 (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
4	2437.00	36200	>500	Pass


Figure Channel 4:



Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 5: Transmitter (802.11n MCS0 15Mbps 40M-BW)-ANT 1 (2452MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
7	2452.00	36200	>500	Pass


Figure Channel 7:



Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 6: Transmitter (802.11n MCS8 30Mbps 40M-BW)-ANT 1+2 (2422MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
1	2422.00	33700	>500	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 6: Transmitter (802.11n MCS8 30Mbps 40M-BW)-ANT 1+2 (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
4	2437.00	35900	>500	Pass


Figure Channel 4:



Product : ThereGate
 Test Item : Occupied Bandwidth Data
 Test Site : No.3 OATS
 Test Mode : Mode 6: Transmitter (802.11n MCS8 30Mbps 40M-BW)-ANT 1+2 (2452MHz)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
7	2452.00	36100	>500	Pass

Figure Channel 7:



8. Power Density

8.1. Test Equipment


The following test equipments are used during the radiated emission tests:

	Equipment	Manufacturer	Model No./Serial No.	Last Cal.
X	Spectrum Analyzer	Agilent	N9010A / MY48030495	Apr, 2009
X	8-WAY Power	JFW	50PD-647 / 526770 0916	Apr., 2009

Note:

1. All equipments are calibrated with traceable calibrations. Each calibration is traceable to the national or international standards.
2. The test instruments marked with "X" are used to measure the final test results.
3. The power combiner is used for measure 11n mode.

8.2. Test Setup



8.3. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

8.4. Test Procedure

The EUT was setup according to ANSI C63.4, 2003; tested according to DTS test procedure of Mar. 2005 KDB558074 for compliance to FCC 47CFR 15.247 requirements.
Set RBW= 3 kHz, VBW=10KHz, Sweep time=(SPAN/3KHz), detector=Peak detector

8.5. Uncertainty


± 1.27 dB

8.6. Test Result of Power Density

Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (802.11b 1Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412.00	-10.773	< 8dBm	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3OATS
 Test Mode : Mode 1: Transmitter (802.11b 1Mbps) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6	2437.000	-2.717	< 8dBm	Pass


Figure Channel 6:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 1: Transmitter (802.11b 1Mbps) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11	2462.00	-6.104	< 8dBm	Pass


Figure Channel 11:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmitter (802.11g 6Mbps) (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412.00	-12.490	< 8dBm	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3OATS
 Test Mode : Mode 2: Transmitter (802.11g 6Mbps) (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6	2437.000	-2.268	< 8dBm	Pass


Figure Channel 6:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 2: Transmitter (802.11g 6Mbps) (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11	2462.00	-3.164	< 8dBm	Pass


Figure Channel 11:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmitter (802.11n MCS0 7.2Mbps 20M-BW)-ANT 1 (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412.00	-7.582	< 8dBm	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3OATS
 Test Mode : Mode 3: Transmitter (802.11n MCS0 7.2Mbps 20M-BW)-ANT 1 (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6	2437.000	-5.273	< 8dBm	Pass


Figure Channel 6:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 3: Transmitter (802.11n MCS0 7.2Mbps 20M-BW)-ANT 1 (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11	2462.00	-4.985	< 8dBm	Pass


Figure Channel 11:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmitter (802.11n MCS8 14.4Mbps 20M-BW)-ANT 1+2 (2412MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2412.00	-4.222	< 8dBm	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3OATS
 Test Mode : Mode 4: Transmitter (802.11n MCS8 14.4Mbps 20M-BW)-ANT 1+2 (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
6	2437.000	-3.329	< 8dBm	Pass


Figure Channel 6:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 4: Transmitter (802.11n MCS8 14.4Mbps 20M-BW)-ANT 1+2 (2462MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
11	2462.00	-12.271	< 8dBm	Pass


Figure Channel 11:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 5: Transmitter (802.11n MCS0 15Mbps 40M-BW)-ANT 1 (2422MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2422.00	-11.854	< 8dBm	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3OATS
 Test Mode : Mode 5: Transmitter (802.11n MCS0 15Mbps 40M-BW)-ANT 1 (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
4	2437.000	0.477	< 8dBm	Pass


Figure Channel 4:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 5: Transmitter (802.11n MCS0 15Mbps 40M-BW)-ANT 1 (2452MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
7	2452.00	-9.985	< 8dBm	Pass


Figure Channel 7:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 6: Transmitter (802.11n MCS8 30Mbps 40M-BW)-ANT 1+2 (2422MHz)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
1	2422.00	-8.258	< 8dBm	Pass


Figure Channel 1:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3OATS
 Test Mode : Mode 6: Transmitter (802.11n MCS8 30Mbps 40M-BW)-ANT 1+2 (2437MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
4	2437.000	-10.133	< 8dBm	Pass


Figure Channel 4:



Product : ThereGate
 Test Item : Power Density Data
 Test Site : No.3 OATS
 Test Mode : Mode 6: Transmitter (802.11n MCS8 30Mbps 40M-BW)-ANT 1+2 (2452MHz)

Channel No.	Frequency (MHz)	Measurement Level (dBm)	Required Limit (dBm)	Result
7	2452.00	-5.910	< 8dBm	Pass

Figure Channel 7:



9. EMI Reduction Method During Compliance Testing

No modification was made during testing.

Attachment 1: EUT Test Photographs

Attachment 2: EUT Detailed Photographs