



# FCC PART 15.407 TEST REPORT

For

# ZIONCOM ELECTRONICS (SHENZHEN) LTD.

Building A1-A2, Lantian Science and Technology Park, Xinyu Road, Xinqiao Henggang Block, Shajing Street, Baoan District, Shenzhen, China

**FCC ID: X7DIP04347** 

Report Type: Product Name:

Original Report AC1200 Wireless Dual Band Router

**Report Number:** RDG180129005-00B

**Report Date:** 2018-02-13

Jerry Zhang

**Reviewed By:** EMC Manager

Bay Area Compliance Laboratories Corp. (Dongguan)

Jerry Zhang

**Test Laboratory:** No.69 Pulongcun, Puxinhu Industry Area,

Tangxia, Dongguan, Guangdong, China

Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

**Note:** This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA\* or any agency of the Federal Government. \* This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "\*".

# **TABLE OF CONTENTS**

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
MEASUREMENT UNCERTAINTY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT EXERCISE SOFTWARE	
EQUIPMENT MODIFICATIONS LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	10
SUPPORT CABLE LIST AND DETAILS	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
FCC §15.407 (f) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	12
APPLICABLE STANDARD	
FCC §15.203 – ANTENNA REQUIREMENT	14
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER SETUP	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST PROCEDURE	
Test Data	
FCC §15.209, §15.205 & §15.407(b) –UNWANTED EMISSION	
APPLICABLE STANDARD	
EUT SETUP	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS TEST DATA	
FCC §15.407(b)-OUT- OF-BAND EMISSIONS	
APPLICABLE STANDARD	
TEST PROCEDURE	
TEST FROCEDURE  TEST EQUIPMENT LIST AND DETAILS.	38
TEST DATA	
FCC §15.407(a)(e) –EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH	54
APPLICABLE STANDARD	54
TEST EQUIPMENT LIST AND DETAILS.	54
TEST PROCEDURE	54

Report No.: RDG180129005-00B

# **GENERAL INFORMATION**

### **Product Description for Equipment under Test (EUT)**

	<b>EUT Name:</b>	AC1200 Wireless Dual Band Router	
EUT Model:		A810R	
M	fultiple Models:	IP04347	
	FCC ID:	X7DIP04347	
Rated	Input Voltage:	DC 9V from Adapter	
Model Name:		DCP005C09080U	
Adapter 1 Information	Input:	AC 100-240V~50/60Hz 0.2A	
inioi mation	Output:	DC 9V 0.8A	
	Model Name:	DCP017C090800U	
Adapter 2 Information	Input:	AC 100-240V~50/60Hz 0.2A	
inioi mation	Output:	DC 9V 0.8A	
<b>External Dimension:</b>		Length (159.36mm)*Width (109.07mm)*High (36.16mm)	
Serial Number:		180129005	
EUT	Received Date:	2018.01.31	

Report No.: RDG180129005-00B

Note: The series product, models A810R, IP04347 are electrically identical, we selected A810R for fully test, the difference between them please refer to the declaration letter.

## **Objective**

This type approval report is prepared on behalf of **ZIONCOM ELECTRONICS** (**SHENZHEN**) **LTD**.in accordance with Part 2-Subpart J, Part 15-Subparts A, and E of the Federal Communications Commission's rules.

The tests were performed in order to determine compliance with FCC Rules Part 15, Subpart E, section 15.203, 15.205, 15.207, 15.209 and 15.407 rules.

# Related Submittal(s)/Grant(s)

FCC Part 15C DTS submissions with FCC ID: X7DIP04347.

## **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices. And KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

FCC Part 15.407 Page 4 of 97

# **Measurement Uncertainty**

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical 1G~6GHz: 4.45 dB, 6G~40GHz: 5.23 dB
Unwanted Emissions, conducted	±1.5 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.12 dB (150 kHz to 30 MHz)

Report No.: RDG180129005-00B

# **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industry Area, Tangxia, Dongguan, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 897218,the FCC Designation No. : CN1220.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062D.

FCC Part 15.407 Page 5 of 97

# SYSTEM TEST CONFIGURATION

### **Description of Test Configuration**

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

Report No.: RDG180129005-00B

The device has 3 external antennas for 2.4GHz and 2 external antennas for 5GHz. For 5G Band, the system supports 802.11a/n ht20/n ht40/ac vht20/ac vht40/ac vht80, the vh20/vht40 were reduced since the identical parameters with 802.11n ht20 and ht40.

For 5150~5250 MHz band, 7 channels are provided to testing:

Channel	Channel Frequency (MHz)		Frequency (MHz)
36	5180	44	5220
38	5190	46	5230
40	5200	48	5240
42	5210	/	/

802.11a, 802.11n ht20 were tested with Channel 36, 40 and 48,

802.11n ht40 were tested with Channel 38 and 46.

802.11ac80 mode was tested with channel 42

For 5725~5850MHz band, 8 channels are provided to testing:

Channel Frequency (MHz)		Channel	Frequency (MHz)
149	5745	157	5785
151	5755	159	5795
153	5765	161	5805
155	5775	165	5825

802.11a, 802.11n ht20 were tested with Channel 149, 157 and 165,

802.11n ht40 were tested with Channel 151 and 159.

802.11ac80 mode was tested with channel 155.

The device supports SISO and MIMO at 802.11n ht20/n ht40/AC80 mode, per pre-test, MIMO mode was the worst and reported.

#### **EUT Exercise Software**

The software "MP-Tool-v3.3" was used for testing, which was provided by manufacturer. The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations. The maximum power was configured as below table, that provided by the manufacturer:

FCC Part 15.407 Page 6 of 97

Band	Mode	( nannai	Frequency	Data rate	Power level	
			(MHz)		ANT 1	ANT 2
		Low	5180	6 Mbps	43	43
	802.11a	Middle	5200	6 Mbps	43	43
		High	5240	6 Mbps	42	42
		Low	5180	MCS8	37	37
5150-	802.11n ht20	Middle	5200	MCS8	37	37
5250MHz		High	5240	MCS8	36	36
802.11n ht40 802.11ac80	Low	5190	MCS8	36	36	
	802.111111140	High	5230	MCS8	34	34
	802.11ac80	Middle	5210	MCS8	32	32
		Low	5745	6 Mbps	42	41
	802.11a	Middle	5785	6 Mbps	38	37
		High	5825	6 Mbps	36	34
		Low	5745	MCS8	35	35
5725-	802.11n ht20	Middle	5785	MCS8	33	33
5850MHz		High	5825	MCS8	30	30
	802.11n ht40	Low	5755	MCS8	34	34
	604.11H Ht40	High	5795	MCS8	32	32
	802.11ac80	Middle	5775	MCS8	30	30


The duty cycle as below:

Mode	Ton (ms)	T <sub>on+off</sub> (ms)	Duty Cycle (%)
802.11a	100	100	100
802.11n ht20	100	100	100
802.11n ht40	100	100	100
802.11ac80	100	100	100

FCC Part 15.407 Page 7 of 97


#### 802.11a mode

Report No.: RDG180129005-00B



Date: 6.FEB.2018 09:56:31

#### 802.11n ht20 mode




Date: 6.FEB.2018 09:56:00

FCC Part 15.407 Page 8 of 97


#### 802.11n ht40 mode

Report No.: RDG180129005-00B



Date: 6.FEB.2018 09:57:06

#### 802.11ac80 mode



Date: 6.FEB.2018 09:57:55

FCC Part 15.407 Page 9 of 97

# **Equipment Modifications**

No modification was made to the EUT.

# **Local Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017

Report No.: RDG180129005-00B

# **Support Cable List and Details**

Cable Description	<b>Shielding Type</b>	Ferrite Core	Length (m)	From Port	То
RJ45 Cable	yes	No	10	RJ45 Port of Laptop	EUT
RJ45 Cable*2	yes	No	0.8	EUT	Load
Adapter Cable	No	No	1.1	Adapter	EUT

# **Block Diagram of Test Setup**



FCC Part 15.407 Page 10 of 97

# SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.407 (f) & §1.1310 & §2.1091	Maximum Permissable Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.407(b)(6)& §15.207(a)	Conducted Emissions	Compliance
§15.205& §15.209 &§15.407(b)	Undesirable Emission& Restricted Bands	Compliance
§15.407(b)	Out Of Band Emissions	Compliance
§15.407(a) (e)	Emission Bandwidth	Compliance
§15.407(a)	Conducted Transmitter Output Power	Compliance
§15.407 (a)	Power Spectral Density	Compliance

Report No.: RDG180129005-00B

FCC Part 15.407 Page 11 of 97

# FCC §15.407 (f) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

## **Applicable Standard**

According to subpart 15.407(f)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Report No.: RDG180129005-00B

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)		
0.3-1.34	614	1.63	*(100)	30		
1.34–30	824/f	2.19/f	*(180/f²)	30		
30–300	27.5	0.073	0.2	30		
300–1500	/	/	f/1500	30		
1500-100,000	/	/	1.0	30		

f = frequency in MHz; \* = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

#### **Calculation formula:**

Prediction of power density at the distance of the applicable MPE limit

 $S = PG/4\pi R^2$  = power density (in appropriate units, e.g. mW/cm<sup>2</sup>);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

FCC Part 15.407 Page 12 of 97

Frequency Band	Antenna Gain		Output Power including Turn-Up tolerance		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
	(dBi)	(numeric)	(dBm)	(mW)	,	,	
2.4GHz	5	3.16	24	251.19	20.00	0.16	1.0
5GHz	5	3.16	14	25.12	20.00	0.02	1.0

The 2.4GHz and 5GHz band can transmit simultaneously:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}}$$

$$=S_{2.4}/S_{limit-2.4} + S_5/S_{limit-5}$$

$$=0.18$$

**Result:** The device meet FCC MPE at 20 cm distance

FCC Part 15.407 Page 13 of 97

# FCC §15.203 – ANTENNA REQUIREMENT

### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Report No.: RDG180129005-00B

And according to FCC 47 CFR section 15.407 (a)(1),if transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### **Antenna Connector Construction**

The EUT have 2 external antennas for 5G Band, which permanently attached to the unit, ANT 1 and ANT 2 for TX and RX, all the antenna gains are 5dBi. Please refer to the EUT photo.

Result: Compliance.


FCC Part 15.407 Page 14 of 97

# FCC §15.407 (b) (6) §15.207 (a) – CONDUCTED EMISSIONS

### **Applicable Standard**

FCC §15.207(a), §15.407(b) (6).

#### **EUT Setup**



Report No.: RDG180129005-00B

Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to the main lisn with a 120 V/60 Hz AC power source.

# **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

FCC Part 15.407 Page 15 of 97

# **Corrected Amplitude & Margin Calculation**

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$
$$C_f = A_C + VDF$$

Herein,

 $V_{\text{C}}(\text{cord. Reading})$ : corrected voltage amplitude

V<sub>R</sub>: reading voltage amplitude A<sub>c</sub>: attenuation caused by cable loss VDF: voltage division factor of AMN C<sub>f</sub>: Correction Factor

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Report No.: RDG180129005-00B

Margin = Limit – Corrected Amplitude

# **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2017-12-11	2018-12-11
N/A	Coaxial Cable	C-NJNJ-50	C-0200-01	2017-09-05	2018-09-05
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A
R&S	Two-line V-network	ENV 216	101614	2017-12-08	2018-12-08
R&S	L.I.S.N	ESH2-Z5	892107/021	2017-09-25	2018-09-25

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Procedure**

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

FCC Part 15.407 Page 16 of 97

# **Test Data**

# **Environmental Conditions**


Temperature:	22.3°C
Relative Humidity:	28 %
ATM Pressure:	102kPa

The testing was performed by Jim Zhang on 2018-02-13.

Test Mode: Transmitting

# For Adapter 1:

# AC120 V, 60 Hz, Line:




Report No.: RDG180129005-00B

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.372042	37.4	9.000	L1	10.0	21.1	58.5	Compliance
0.511698	32.6	9.000	L1	9.9	23.4	56.0	Compliance
0.624492	33.1	9.000	L1	9.8	22.9	56.0	Compliance
0.780588	35.3	9.000	L1	9.8	20.7	56.0	Compliance
1.162648	32.0	9.000	L1	9.8	24.0	56.0	Compliance
1.548915	30.9	9.000	L1	9.7	25.1	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.372042	26.6	9.000	L1	10.0	21.9	48.5	Compliance
0.511698	23.3	9.000	L1	9.9	22.7	46.0	Compliance
0.649874	21.1	9.000	L1	9.8	24.9	46.0	Compliance
0.768247	18.6	9.000	L1	9.8	27.4	46.0	Compliance
1.181325	17.1	9.000	L1	9.8	28.9	46.0	Compliance
1.374420	21.4	9.000	L1	9.7	24.6	46.0	Compliance

FCC Part 15.407 Page 17 of 97

# AC120 V, 60 Hz, Neutral:



Report No.: RDG180129005-00B


requency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.372042	32.0	9.000	N	10.0	26.5	58.5	Compliance
0.644717	28.8	9.000	N	9.8	27.2	56.0	Compliance
0.780588	28.7	9.000	N	9.8	27.3	56.0	Compliance
1.153421	25.5	9.000	N	9.8	30.5	56.0	Compliance
1.249088	23.7	9.000	N	9.8	32.3	56.0	Compliance
26.847135	34.3	9.000	N	10.1	25.7	60.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.167702	25.9	9.000	N	10.9	29.2	55.1	Compliance
0.375019	19.5	9.000	N	10.0	28.9	48.4	Compliance
0.515791	17.5	9.000	N	9.9	28.5	46.0	Compliance
1.239175	14.8	9.000	N	9.8	31.2	46.0	Compliance
1.374420	16.6	9.000	N	9.7	29.4	46.0	Compliance
28.614240	25.5	9.000	N	10.2	24.5	50.0	Compliance

FCC Part 15.407 Page 18 of 97

# For Adapter 2:

# AC120 V, 60 Hz, Line:




Report No.: RDG180129005-00B

Frequency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.419276	29.5	9.000	L1	10.0	28.0	57.5	Compliance
0.515791	38.8	9.000	L1	9.9	17.2	56.0	Compliance
0.676289	25.5	9.000	L1	9.8	30.5	56.0	Compliance
1.023481	24.8	9.000	L1	9.8	31.2	56.0	Compliance
1.374420	29.1	9.000	L1	9.7	26.9	56.0	Compliance
1.816511	23.4	9.000	L1	9.7	32.6	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.429420	19.8	9.000	L1	9.9	27.5	47.3	Compliance
0.515791	29.6	9.000	L1	9.9	16.4	46.0	Compliance
0.915445	19.8	9.000	L1	9.8	26.2	46.0	Compliance
1.374420	22.3	9.000	L1	9.7	23.7	46.0	Compliance
2.749070	17.7	9.000	L1	9.8	28.3	46.0	Compliance
20.152030	20.9	9.000	L1	10.1	29.1	50.0	Compliance

FCC Part 15.407 Page 19 of 97

# AC120 V, 60 Hz, Neutral:



Report No.: RDG180129005-00B

requency (MHz)	QuasiPeak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.426011	26.0	9.000	N	9.9	31.3	57.3	Compliance
0.515791	33.4	9.000	N	9.9	22.6	56.0	Compliance
0.893821	22.5	9.000	N	9.8	33.5	56.0	Compliance
1.374420	25.8	9.000	N	9.7	30.2	56.0	Compliance
2.362847	21.0	9.000	N	9.8	35.0	56.0	Compliance
30.000000	38.0	9.000	N	10.2	22.0	60.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.429420	18.0	9.000	N	9.9	29.3	47.3	Compliance
0.515791	25.4	9.000	N	9.9	20.6	46.0	Compliance
0.922769	16.8	9.000	N	9.8	29.2	46.0	Compliance
1.374420	17.7	9.000	N	9.7	28.3	46.0	Compliance
17.459396	18.9	9.000	N	10.0	31.1	50.0	Compliance
30.000000	28.9	120.000	N	10.2	21.1	50.0	Compliance

FCC Part 15.407 Page 20 of 97

# FCC §15.209, §15.205 & §15.407(b) – UNWANTED EMISSION

#### **Applicable Standard**

FCC §15.407; §15.209; §15.205;

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:


Report No.: RDG180129005-00B

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
  - (4) For transmitters operating in the 5.725-5.85 GHz band:
- (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.
  - (7) The provisions of §15.205 apply to intentional radiators operating under this section.

FCC Part 15.407 Page 21 of 97


# **EUT Setup**

#### **Below 1 GHz:**



Report No.: RDG180129005-00B

#### **Above 1 GHz:**



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.407 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

FCC Part 15.407 Page 22 of 97

#### **EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 40 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Report No.: RDG180129005-00B

30-1000MHz:

Measurement	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz-40GHz:

Measurement	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Avo	>98%	1MHz	10 Hz
Ave.	<98%	1MHz	1/T

#### **Test Procedure**

During the radiated emission test, the adapter was connected to the first AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1GHz, peak and Average detection modes for frequencies above 1GHz.

According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01, emission shall be computed as:  $E [dB\mu V/m] = EIRP[dBm] + 95.2$ , for d = 3 meters.

According to C63.10, the above 1G test result shall be extrapolated to the specified distance using an extrapolation factor of 20dB/decade from 3m to 1.5m

Distance extrapolation factor =20 log (specific distance [3m]/test distance [1.5m]) dB= 6.02 dB

All emissions under the average limit and under the noise floor have not recorded in the report.

# **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain Extrapolation result = Corrected Amplitude- Distance extrapolation factor

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Extrapolation result -Limit

FCC Part 15.407 Page 23 of 97

# **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB3	A060611-1	2017-11-10	2020-11-10
R&S	EMI Test Receiver	ESCI	100224	2017-12-11	2018-12-11
HP	Amplifier	8447D	2727A05902	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0400-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-0075-01	2017-09-05	2018-09-05
N/A	Coaxial Cable	C-NJNJ-50	C-1000-01	2017-09-05	2018-09-05
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
ETS-Lindgren	Horn Antenna	3115	000 527 35	2016-01-05	2019-01-04
Agilent	Spectrum Analyzer	E4440A	SG43360054	2018-01-04	2019-01-04
N/A	Coaxial Cable	C-SJSJ-50	C-0800-01	2017-09-05	2018-09-05
MITEQ	Amplifier	AFS42-00101800- 25-S-42	2001271	2017-09-05	2018-09-05
Ducommun Technolagies	Horn Antenna	ARH-4223-02	1007726-01 1304	2016-11-18	2019-11-18
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2017-06-27	2018-06-27
N/A	Coaxial Cable	C-2.4J2.4J-50	C-0700-02	2017-06-27	2018-06-27
Ducommun Technolagies	Horn Antenna	ARH-2823-02	1007726-01 1302	2016-11-18	2019-11-18
R&S	Spectrum Analyzer	FSP 38	100478	2017-12-08	2018-12-08
Chengdu OuLi	Bandrejector Filter	5725-5850	005	2017-09-05	2018-09-05
Chengdu OuLi	Bandrejector Filter	5150-5350	006	2017-09-05	2018-09-05

Report No.: RDG180129005-00B

# **Test Data**

#### **Environmental Conditions**

Temperature:	16.4 °C
Relative Humidity:	37 %
ATM Pressure:	102.1 kPa

<sup>\*</sup> The testing was performed by Steven Zuo on 2018-02-06.


Test Mode: Transmitting(Adapter 1 was the worst)

FCC Part 15.407 Page 24 of 97

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

# 1) **Below 1GHz**(802.11n ht20 5785 MHz was the worst):

#### Horizontal




Report No.: RDG180129005-00B

Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
32.9100	27.80	QP	-1.10	26.70	40.00	13.30
125.0600	33.13	QP	-4.83	28.30	43.50	15.20
147.3700	34.59	QP	-6.49	28.10	43.50	15.40
246.3100	50.52	QP	-6.32	44.20	46.00	1.80
282.2000	43.16	QP	-3.66	39.50	46.00	6.50
563.5000	31.72	QP	0.18	31.90	46.00	14.10

FCC Part 15.407 Page 25 of 97

# Vertical



Report No.: RDG180129005-00B

Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
42.6100	42.95	QP	-8.05	34.90	40.00	5.10
164.8300	40.43	QP	-6.93	33.50	43.50	10.00
244.3700	45.70	QP	-6.30	39.40	46.00	6.60
340.4000	36.32	QP	-3.52	32.80	46.00	13.20
480.0800	31.71	QP	-1.01	30.70	46.00	15.30
640.1300	29.74	QP	1.86	31.60	46.00	14.40

FCC Part 15.407 Page 26 of 97

2) 1GHz-40GHz:5150-5250MHz802.11a(ANT 1 was the worst)

_	Rece	eiver	Rx A	ntenna	Cable	Amplifier	Corrected	Extrapolation		
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	result (dBμV/m)	Limit (dBµV/m)	Margin (dB)
				Lo	ow Chani	nel: 5180 MH	[z			
5180.00	64.29	PK	Н	33.59	3.58	0.00	101.46	95.44	N/A	N/A
5180.00	54.57	AV	Н	33.59	3.58	0.00	91.74	85.72	N/A	N/A
5180.00	74.28	PK	V	33.59	3.58	0.00	111.45	105.43	N/A	N/A
5180.00	64.95	AV	V	33.59	3.58	0.00	102.12	96.1	N/A	N/A
5150.00	27.89	PK	V	33.54	3.56	0.00	64.99	58.97	74.00	15.03
5150.00	14.79	AV	V	33.54	3.56	0.00	51.89	45.87	54.00	8.13
10360.00	49.26	PK	V	38.17	6.29	36.85	56.87	50.85	74.00	23.15
10360.00	37.58	AV	V	38.17	6.29	36.85	45.19	39.17	54.00	14.83
15540.00	45.48	PK	V	38.06	8.85	39.04	53.35	47.33	74.00	26.67
15540.00	33.26	AV	V	38.06	8.85	39.04	41.13	35.11	54.00	18.89
9829.00	57.36	PK	V	38.03	5.96	36.72	64.63	58.61	74.00	15.39
9829.00	45.29	AV	V	38.03	5.96	36.72	52.56	46.54	54.00	7.46
				Mic	ddle Chai	nnel: 5200 M	Hz			
5200.00	64.75	PK	Н	33.62	3.60	0.00	101.97	95.95	N/A	N/A
5200.00	54.66	AV	Н	33.62	3.60	0.00	91.88	85.86	N/A	N/A
5200.00	74.58	PK	V	33.62	3.60	0.00	111.80	105.78	N/A	N/A
5200.00	64.73	AV	V	33.62	3.60	0.00	101.95	95.93	N/A	N/A
10400.00	48.46	PK	V	38.18	6.32	36.86	56.10	50.08	74.00	23.92
10400.00	35.94	AV	V	38.18	6.32	36.86	43.58	37.56	54.00	16.44
15600.00	45.65	PK	V	38.00	8.83	39.09	53.39	47.37	74.00	26.63
15600.00	33.38	AV	V	38.00	8.83	39.09	41.12	35.1	54.00	18.90
				Hi	igh Chani	nel: 5240 MF	Iz			
5240.00	64.62	PK	Н	33.68	3.52	0.00	101.82	95.8	N/A	N/A
5240.00	54.78	AV	Н	33.68	3.52	0.00	91.98	85.96	N/A	N/A
5240.00	74.34	PK	V	33.68	3.52	0.00	111.54	105.52	N/A	N/A
5240.00	64.57	AV	V	33.68	3.52	0.00	101.77	95.75	N/A	N/A
5350.00	25.45	PK	V	33.86	3.52	0.00	62.83	56.81	74.00	17.19
5350.00	13.48	AV	V	33.86	3.52	0.00	50.86	44.84	54.00	9.16
10480.00	47.95	PK	V	38.20	6.37	36.88	55.64	49.62	74.00	24.38
10480.00	36.03	AV	V	38.20	6.37	36.88	43.72	37.7	54.00	16.30
15720.00	45.79	PK	V	37.88	8.79	39.18	53.28	47.26	74.00	26.74
15720.00	33.54	AV	V	37.88	8.79	39.18	41.03	35.01	54.00	18.99

FCC Part 15.407 Page 27 of 97

**802.11n ht20(2Tx was the worst)** 

0021		21x was tn		/								
Frequency	Reco	eiver	Rx A	ntenna	Cable	Amplifier	Corrected	Extrapolation	Limit	Mangin		
(MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	result (dBμV/m)	(dBµV/m)	Margin (dB)		
	Low Channel: 5180 MHz											
5180.00	63.46	PK	Н	33.59	3.58	0.00	100.63	94.61	N/A	N/A		
5180.00	53.59	AV	Н	33.59	3.58	0.00	90.76	84.74	N/A	N/A		
5180.00	75.84	PK	V	33.59	3.58	0.00	113.01	106.99	N/A	N/A		
5180.00	65.63	AV	V	33.59	3.58	0.00	102.80	96.78	N/A	N/A		
5150.00	27.52	PK	V	33.54	3.56	0.00	64.62	58.6	74.00	15.40		
5150.00	14.45	AV	V	33.54	3.56	0.00	51.55	45.53	54.00	8.47		
10360.00	47.85	PK	V	38.17	6.29	36.85	55.46	49.44	74.00	24.56		
10360.00	36.06	AV	V	38.17	6.29	36.85	43.67	37.65	54.00	16.35		
15540.00	45.76	PK	V	38.06	8.85	39.04	53.63	47.61	74.00	26.39		
15540.00	33.27	AV	V	38.06	8.85	39.04	41.14	35.12	54.00	18.88		
				Mic	ddle Chai	nnel: 5200 M	Hz					
5200.00	63.18	PK	Н	33.62	3.60	0.00	100.40	94.38	N/A	N/A		
5200.00	53.44	AV	Н	33.62	3.60	0.00	90.66	84.64	N/A	N/A		
5200.00	75.21	PK	V	33.62	3.60	0.00	112.43	106.41	N/A	N/A		
5200.00	65.49	AV	V	33.62	3.60	0.00	102.71	96.69	N/A	N/A		
10400.00	48.05	PK	V	38.18	6.32	36.86	55.69	49.67	74.00	24.33		
10400.00	36.09	AV	V	38.18	6.32	36.86	43.73	37.71	54.00	16.29		
15600.00	45.82	PK	V	38.00	8.83	39.09	53.56	47.54	74.00	26.46		
15600.00	33.25	AV	V	38.00	8.83	39.09	40.99	34.97	54.00	19.03		
				Hi	gh Chan	nel: 5240 MF						
5240.00	63.59	PK	Н	33.68	3.52	0.00	100.79	94.77	N/A	N/A		
5240.00	54.16	AV	Н	33.68	3.52	0.00	91.36	85.34	N/A	N/A		
5240.00	75.43	PK	V	33.68	3.52	0.00	112.63	106.61	N/A	N/A		
5240.00	65.37	AV	V	33.68	3.52	0.00	102.57	96.55	N/A	N/A		
5350.00	25.68	PK	V	33.86	3.52	0.00	63.06	57.04	74.00	16.96		
5350.00	13.72	AV	V	33.86	3.52	0.00	51.10	45.08	54.00	8.92		
10480.00	47.81	PK	V	38.20	6.37	36.88	55.50	49.48	74.00	24.52		
10480.00	36.17	AV	V	38.20	6.37	36.88	43.86	37.84	54.00	16.16		
15720.00	45.86	PK	V	37.88	8.79	39.18	53.35	47.33	74.00	26.67		
15720.00	33.31	AV	V	37.88	8.79	39.18	40.80	34.78	54.00	19.22		

FCC Part 15.407 Page 28 of 97

802.11n ht40(2Tx was the worst)

Т	Rece	eiver	Rx A	ntenna	Cable	Amplifier	Corrected	Extrapolation	T,	3.4
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
				Lo	ow Chani	nel: 5190 MH	Z			
5190.00	59.78	PK	Н	33.60	3.59	0.00	96.97	90.95	N/A	N/A
5190.00	50.23	AV	Н	33.60	3.59	0.00	87.42	81.4	N/A	N/A
5190.00	73.35	PK	V	33.60	3.59	0.00	110.54	104.52	N/A	N/A
5190.00	63.64	AV	V	33.60	3.59	0.00	100.83	94.81	N/A	N/A
5150.00	33.76	PK	V	33.54	3.56	0.00	70.86	64.84	74.00	9.16
5150.00	18.15	AV	V	33.54	3.56	0.00	55.25	49.23	54.00	4.77
10380.00	47.97	PK	V	38.18	6.31	36.85	55.61	49.59	74.00	24.41
10380.00	36.11	AV	V	38.18	6.31	36.85	43.75	37.73	54.00	16.27
15570.00	45.74	PK	V	38.03	8.84	39.06	53.55	47.53	74.00	26.47
15570.00	33.13	AV	V	38.03	8.84	39.06	40.94	34.92	54.00	19.08
				Hi	gh Chan	nel: 5230 MF	Iz			
5230.00	59.68	PK	Н	33.67	3.54	0.00	96.89	90.87	N/A	N/A
5230.00	50.13	AV	Н	33.67	3.54	0.00	87.34	81.32	N/A	N/A
5230.00	71.65	PK	V	33.67	3.54	0.00	108.86	102.84	N/A	N/A
5230.00	61.84	AV	V	33.67	3.54	0.00	99.05	93.03	N/A	N/A
5350.00	25.78	PK	V	33.86	3.52	0.00	63.16	57.14	74.00	16.86
5350.00	13.64	AV	V	33.86	3.52	0.00	51.02	45	54.00	9.00
10460.00	47.94	PK	V	38.19	6.36	36.87	55.62	49.6	74.00	24.40
10460.00	36.01	AV	V	38.19	6.36	36.87	43.69	37.67	54.00	16.33
15690.00	45.89	PK	V	37.91	8.80	39.15	53.45	47.43	74.00	26.57
15690.00	33.13	AV	V	37.91	8.80	39.15	40.69	34.67	54.00	19.33

# **802.11** ac**80**(2Tx was the worst)

1		A Was the								
E	Reco	eiver	Rx A	ntenna	Cable	Amplifier	Corrected	Extrapolation	T ::4	M
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	result (dBμV/m)	Limit (dBµV/m)	Margin (dB)
				Mie	ddle Chai	nnel: 5210 M	Hz			
5210.00	56.82	PK	Н	33.64	3.58	0.00	94.04	88.02	N/A	N/A
5210.00	46.93	AV	Н	33.64	3.58	0.00	84.15	78.13	N/A	N/A
5210.00	68.75	PK	V	33.64	3.58	0.00	105.97	99.95	N/A	N/A
5210.00	58.37	AV	V	33.64	3.58	0.00	95.59	89.57	N/A	N/A
5150.00	31.58	PK	V	33.54	3.56	0.00	68.68	62.66	74.00	11.34
5150.00	17.65	AV	V	33.54	3.56	0.00	54.75	48.73	54.00	5.27
5350.00	28.17	PK	V	33.86	3.52	0.00	65.55	59.53	74.00	14.47
5350.00	14.63	AV	V	33.86	3.52	0.00	52.01	45.99	54.00	8.01
10420.00	48.19	PK	V	38.18	6.33	36.86	55.84	49.82	74.00	24.18
10420.00	35.96	AV	V	38.18	6.33	36.86	43.61	37.59	54.00	16.41
15630.00	45.95	PK	V	37.97	8.82	39.11	53.63	47.61	74.00	26.39
15630.00	33.11	AV	V	37.97	8.82	39.11	40.79	34.77	54.00	19.23

FCC Part 15.407 Page 29 of 97

5725-5850MHz: 802.11a(ANT 1 was the worst)

002.	IIa(AIVI	I was the v	voist)			Γ	Γ	F	Г	
E	Reco	eiver	Rx A	ntenna	Cable	Amplifier	Corrected	Extrapolation	T ::4	M
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	result (dBμV/m)	Limit (dBμV/m)	Margin (dB)
				Lo	ow Chanı	nel: 5745 MH	Íz			
5745.00	65.37	PK	Н	34.20	3.69	0.00	103.26	97.24	N/A	N/A
5745.00	55.49	AV	Н	34.20	3.69	0.00	93.38	87.36	N/A	N/A
5745.00	78.16	PK	V	34.20	3.69	0.00	116.05	110.03	N/A	N/A
5745.00	68.52	AV	V	34.20	3.69	0.00	106.41	100.39	N/A	N/A
5725.00	39.84	PK	V	34.19	3.69	0.00	77.72	71.7	122.20	50.50
5720.00	32.56	PK	V	34.19	3.69	0.00	70.44	64.42	110.80	46.38
5700.00	27.48	PK	V	34.18	3.68	0.00	65.34	59.32	105.20	45.88
5650.00	26.15	PK	V	34.16	3.63	0.00	63.94	57.92	68.20	10.28
11490.00	48.63	PK	V	38.99	6.59	37.35	56.86	50.84	74.00	23.16
11490.00	36.55	AV	V	38.99	6.59	37.35	44.78	38.76	54.00	15.24
17235.00	46.38	PK	V	41.56	8.78	38.61	58.11	52.09	74.00	21.91
17235.00	34.54	AV	V	41.56	8.78	38.61	46.27	40.25	54.00	13.75
9840.00	57.49	PK	V	38.04	5.96	36.72	64.77	58.75	74.00	15.25
9840.00	44.27	AV	V	38.04	5.96	36.72	51.55	45.53	54.00	8.47
				Mic	ddle Chai	nnel: 5785 M	Hz			
5785.00	63.48	PK	Н	34.21	3.71	0.00	101.40	95.38	N/A	N/A
5785.00	53.52	AV	Н	34.21	3.71	0.00	91.44	85.42	N/A	N/A
5785.00	76.68	PK	V	34.21	3.71	0.00	114.60	108.58	N/A	N/A
5785.00	66.43	AV	V	34.21	3.71	0.00	104.35	98.33	N/A	N/A
11570.00	47.86	PK	V	39.00	6.61	37.44	56.03	50.01	74.00	23.99
11570.00	34.92	AV	V	39.00	6.61	37.44	43.09	37.07	54.00	16.93
17355.00	46.44	PK	V	42.26	8.81	38.52	58.99	52.97	74.00	21.03
17355.00	34.58	AV	V	42.26	8.81	38.52	47.13	41.11	54.00	12.89
		T	•			nel: 5825 MF			T	
5825.00	62.36	PK	Н	34.23	3.73	0.00	100.32	94.3	N/A	N/A
5825.00	52.49	AV	Н	34.23	3.73	0.00	90.45	84.43	N/A	N/A
5825.00	75.18	PK	V	34.23	3.73	0.00	113.14	107.12	N/A	N/A
5825.00	65.23	AV	V	34.23	3.73	0.00	103.19	97.17	N/A	N/A
5850.00	28.67	PK	V	34.24	3.75	0.00	66.66	60.64	122.20	61.56
5855.00	28.12	PK	V	34.24	3.75	0.00	66.11	60.09	110.80	50.71
5875.00	27.56	PK	V	34.25	3.77	0.00	65.58	59.56	105.20	45.64
5925.00	25.84	PK	V	34.27	3.80	0.00	63.91	57.89	68.20	10.31
11650.00	47.56	PK	V	39.00	6.64	37.53	55.67	49.65	74.00	24.35
11650.00	35.48	AV	V	39.00	6.64	37.53	43.59	37.57	54.00	16.43
17475.00	46.23	PK	V	42.96	8.84	38.44	59.59	53.57	74.00	20.43
17475.00	34.76	AV	V	42.96	8.84	38.44	48.12	42.1	54.00	11.90

FCC Part 15.407 Page 30 of 97

**802.11n ht20(2Tx was the worst)** 

002.		21x was tn								
Emagneman	Rec	eiver	Rx A	ntenna	Cable	Amplifier	Corrected	Extrapolation	Limit	Margin
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	result (dBμV/m)	(dBµV/m)	(dB)
				Lo	ow Chani	nel: 5745 MH	ĺz .			
5745.00	65.98	PK	Н	34.20	3.69	0.00	103.87	97.85	N/A	N/A
5745.00	55.77	AV	Н	34.20	3.69	0.00	93.66	87.64	N/A	N/A
5745.00	79.64	PK	V	34.20	3.69	0.00	117.53	111.51	N/A	N/A
5745.00	69.48	AV	V	34.20	3.69	0.00	107.37	101.35	N/A	N/A
5725.00	38.46	PK	V	34.19	3.69	0.00	76.34	70.32	122.20	51.88
5720.00	31.33	PK	V	34.19	3.69	0.00	69.21	63.19	110.80	47.61
5700.00	28.46	PK	V	34.18	3.68	0.00	66.32	60.3	105.20	44.90
5650.00	25.78	PK	V	34.16	3.63	0.00	63.57	57.55	68.20	10.65
11490.00	47.61	PK	V	38.99	6.59	37.35	55.84	49.82	74.00	24.18
11490.00	35.49	AV	V	38.99	6.59	37.35	43.72	37.7	54.00	16.30
17235.00	46.33	PK	V	41.56	8.78	38.61	58.06	52.04	74.00	21.96
17235.00	34.68	AV	V	41.56	8.78	38.61	46.41	40.39	54.00	13.61
				Mic	ddle Chai	nnel: 5785 M				
5785.00	64.36	PK	Н	34.21	3.71	0.00	102.28	96.26	N/A	N/A
5785.00	54.52	AV	Н	34.21	3.71	0.00	92.44	86.42	N/A	N/A
5785.00	78.79	PK	V	34.21	3.71	0.00	116.71	110.69	N/A	N/A
5785.00	68.93	AV	V	34.21	3.71	0.00	106.85	100.83	N/A	N/A
11570.00	47.41	PK	V	39.00	6.61	37.44	55.58	49.56	74.00	24.44
11570.00	35.54	AV	V	39.00	6.61	37.44	43.71	37.69	54.00	16.31
17355.00	46.32	PK	V	42.26	8.81	38.52	58.87	52.85	74.00	21.15
17355.00	34.73	AV	V	42.26	8.81	38.52	47.28	41.26	54.00	12.74
						nel: 5825 MF				
5825.00	63.27	PK	Н	34.23	3.73	0.00	101.23	95.21	N/A	N/A
5825.00	53.36	AV	Н	34.23	3.73	0.00	91.32	85.3	N/A	N/A
5825.00	77.69	PK	V	34.23	3.73	0.00	115.65	109.63	N/A	N/A
5825.00	67.57	AV	V	34.23	3.73	0.00	105.53	99.51	N/A	N/A
5850.00	28.26	PK	V	34.24	3.75	0.00	66.25	60.23	122.20	61.97
5855.00	27.49	PK	V	34.24	3.75	0.00	65.48	59.46	110.80	51.34
5875.00	27.15	PK	V	34.25	3.77	0.00	65.17	59.15	105.20	46.05
5925.00	25.34	PK	V	34.27	3.80	0.00	63.41	57.39	68.20	10.81
11650.00	47.82	PK	V	39.00	6.64	37.53	55.93	49.91	74.00	24.09
11650.00	35.65	AV	V	39.00	6.64	37.53	43.76	37.74	54.00	16.26
17475.00	46.24	PK	V	42.96	8.84	38.44	59.60	53.58	74.00	20.42
17475.00	34.43	AV	V	42.96	8.84	38.44	47.79	41.77	54.00	12.23

FCC Part 15.407 Page 31 of 97

802.11n ht40(2Tx was the worst)

	D			,								
Frequency	Rec	eiver	RX A	ntenna	Cable	Amplifier	Corrected	Extrapolation	Limit	Margin		
(MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	result (dBμV/m)	(dBµV/m)	(dB)		
Low Channel: 5755 MHz												
5755.00												
5755.00	53.29	AV	Н	34.20	3.70	0.00	91.19	85.17	N/A	N/A		
5755.00	76.84	PK	V	34.20	3.70	0.00	114.74	108.72	N/A	N/A		
5755.00	66.72	AV	V	34.20	3.70	0.00	104.62	98.6	N/A	N/A		
5725.00	42.38	PK	V	34.19	3.69	0.00	80.26	74.24	122.20	47.96		
5720.00	39.67	PK	V	34.19	3.69	0.00	77.55	71.53	110.80	39.27		
5700.00	27.85	PK	V	34.18	3.68	0.00	65.71	59.69	105.20	45.51		
5650.00	25.69	PK	V	34.16	3.63	0.00	63.48	57.46	68.20	10.74		
11510.00	47.56	PK	V	39.00	6.59	37.37	55.78	49.76	74.00	24.24		
11510.00	35.84	AV	V	39.00	6.59	37.37	44.06	38.04	54.00	15.96		
17265.00	46.45	PK	V	41.74	8.79	38.58	58.40	52.38	74.00	21.62		
17265.00	34.42	AV	V	41.74	8.79	38.58	46.37	40.35	54.00	13.65		
				Hi	igh Chan	nel: 5795 MF	łz					
5795.00	62.12	PK	Н	34.22	3.71	0.00	100.05	94.03	N/A	N/A		
5795.00	52.37	AV	Н	34.22	3.71	0.00	90.30	84.28	N/A	N/A		
5795.00	75.63	PK	V	34.22	3.71	0.00	113.56	107.54	N/A	N/A		
5795.00	65.48	AV	V	34.22	3.71	0.00	103.41	97.39	N/A	N/A		
5850.00	27.69	PK	V	34.24	3.75	0.00	65.68	59.66	122.20	62.54		
5855.00	27.43	PK	V	34.24	3.75	0.00	65.42	59.4	110.80	51.40		
5875.00	26.54	PK	V	34.25	3.77	0.00	64.56	58.54	105.20	46.66		
5925.00	25.82	PK	V	34.27	3.80	0.00	63.89	57.87	68.20	10.33		
11590.00	47.63	PK	V	39.00	6.62	37.46	55.79	49.77	74.00	24.23		
11590.00	35.26	AV	V	39.00	6.62	37.46	43.42	37.4	54.00	16.60		
17385.00	46.54	PK	V	42.43	8.82	38.50	59.29	53.27	74.00	20.73		
17385.00	34.42	AV	V	42.43	8.82	38.50	47.17	41.15	54.00	12.85		


FCC Part 15.407 Page 32 of 97

**802.11** ac**80**(2Tx was the worst)


602.11 acou(21x was the worst)										
Frequency (MHz)	Receiver		Rx Antenna		Cable	Amplifier	Corrected	Extrapolation	T ::4	Mangin
	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	result (dBμV/m)	Limit (dBµV/m)	Margin (dB)
Middle Channel: 5775 MHz										
5775.00	59.23	PK	Н	34.21	3.70	0.00	97.14	91.12	N/A	N/A
5775.00	49.46	AV	Н	34.21	3.70	0.00	87.37	81.35	N/A	N/A
5775.00	71.85	PK	V	34.21	3.70	0.00	109.76	103.74	N/A	N/A
5775.00	61.69	AV	V	34.21	3.70	0.00	99.60	93.58	N/A	N/A
5725.00	26.28	PK	V	34.19	3.69	0.00	64.16	58.14	122.20	64.06
5720.00	29.67	PK	V	34.19	3.69	0.00	67.55	61.53	110.80	49.27
5700.00	33.82	PK	V	34.18	3.68	0.00	71.68	65.66	105.20	39.54
5650.00	35.39	PK	V	34.16	3.63	0.00	73.18	67.16	68.20	1.04
5850.00	34.26	PK	V	34.24	3.75	0.00	72.25	66.23	122.20	55.97
5855.00	31.48	PK	V	34.24	3.75	0.00	69.47	63.45	110.80	47.35
5875.00	30.55	PK	V	34.25	3.77	0.00	68.57	62.55	105.20	42.65
5925.00	26.17	PK	V	34.27	3.80	0.00	64.24	58.22	68.20	9.98
11550.00	47.36	PK	V	39.00	6.61	37.42	55.55	49.53	74.00	24.47
11550.00	35.44	AV	V	39.00	6.61	37.42	43.63	37.61	54.00	16.39
17325.00	46.25	PK	V	42.09	8.80	38.54	58.60	52.58	74.00	21.42
17325.00	34.43	AV	V	42.09	8.80	38.54	46.78	40.76	54.00	13.24


FCC Part 15.407 Page 33 of 97

# Test Plots(For worst mode 802.11a mode, ANT 1 5825MHz) Horizontal:




Report No.: RDG180129005-00B







FCC Part 15.407 Page 34 of 97





#### Vertical:





FCC Part 15.407 Page 35 of 97





FCC Part 15.407 Page 36 of 97

## FCC §15.407(b)-OUT- OF-BAND EMISSIONS

#### **Applicable Standard**

FCC §15.407

(b) Undesirable emission limits. Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

Report No.: RDG180129005-00B

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
  - (4) For transmitters operating in the 5.725-5.85 GHz band:
- (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.

#### **Test Procedure**

According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

FCC Part 15.407 Page 37 of 97

# **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-01-04	2019-01-04
N/A	Coaxial Cable	C-SJ00-0010	C0010/04	Each Time	/

Report No.: RDG180129005-00B

#### **Test Data**

#### **Environmental Conditions**

Temperature:	21.3°C	
Relative Humidity:	36 %	
ATM Pressure:	102kPa	

The testing was performed by Nami Quan on 2018-02-02.

Test Result: Pass.

Please refer to the following plots.


FCC Part 15.407 Page 38 of 97

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

**5150-5250MHz**(the atenna gain was offset in the display, all emission under limit more than 3dBc for 802.11n and ac modes, so 2TX mode also compliance the requirement)


ANT 1:

802.11a Low Channel



Date: 2.FEB.2018 11:43:45

## 802.11a High Channel




Date: 2.FEB.2018 11:44:45

FCC Part 15.407 Page 39 of 97


#### 802.11n ht20 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:47:01

## 802.11n ht20 High Channel




Date: 2.FEB.2018 11:47:41

FCC Part 15.407 Page 40 of 97


# 802.11n ht40 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:51:36

## 802.11n ht40 High Channel




Date: 2.FEB.2018 11:52:40

FCC Part 15.407 Page 41 of 97

## 802.11n ac80 Middle Channel

Report No.: RDG180129005-00B




Date: 2.FEB.2018 11:54:59

FCC Part 15.407 Page 42 of 97

## ANT 2:


#### 802.11a Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 13:04:22

## 802.11a High Channel




Date: 2.FEB.2018 13:04:59

FCC Part 15.407 Page 43 of 97


#### 802.11n ht20 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 13:06:36

## 802.11n ht20 High Channel




Date: 2.FEB.2018 13:07:13

FCC Part 15.407 Page 44 of 97


# 802.11n ht40 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 13:11:47

## 802.11n ht40 High Channel




Date: 2.FEB.2018 13:12:25

FCC Part 15.407 Page 45 of 97

## 802.11n ac80 Middle Channel

Report No.: RDG180129005-00B




Date: 2.FEB.2018 13:17:17

FCC Part 15.407 Page 46 of 97


**5725-5850MHz**(the atenna gain was offset in the display, all emission under limit more than 3dBc, so 2TX mode also compliance the requirement)
ANT 1:

### 802.11a Low Channel



Date: 2.FEB.2018 11:45:23

## 802.11a High Channel




Date: 2.FEB.2018 11:46:10

FCC Part 15.407 Page 47 of 97


#### 802.11n ht20 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:48:43

## 802.11n ht20 High Channel




Date: 2.FEB.2018 11:50:27

FCC Part 15.407 Page 48 of 97


# 802.11n ht40 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:53:27

## 802.11n ht40 High Channel




Date: 2.FEB.2018 11:54:17

FCC Part 15.407 Page 49 of 97

#### 802.11n ac80 Middle Channel


Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:55:35

#### ANT 2:

## 802.11a Low Channel




Date: 2.FEB.2018 13:08:13

FCC Part 15.407 Page 50 of 97


### 802.11a High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 13:08:52

#### 802.11n ht20 Low Channel




Date: 2.FEB.2018 13:10:39

FCC Part 15.407 Page 51 of 97


## 802.11n ht20 High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 13:09:50

#### 802.11n ht40 Low Channel




Date: 2.FEB.2018 13:13:06

FCC Part 15.407 Page 52 of 97


## 802.11n ht40 High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 13:13:57

#### 802.11n ac80 Middle Channel



Date: 2.FEB.2018 13:15:27

FCC Part 15.407 Page 53 of 97

# FCC §15.407(a)(e) –EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH

#### **Applicable Standard**

15.407(a) (e)

## **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-01-04	2019-01-04
N/A	Coaxial Cable	C-SJ00-0010	C0010/04	Each Time	/

Report No.: RDG180129005-00B

#### **Test Procedure**

According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	21.3°C	
Relative Humidity:	36%	
ATM Pressure:	102kPa	

The testing was performed by Nami Quan on 2018-02-02.

Test Result: Pass.

Please refer to the following tables and plots.

FCC Part 15.407 Page 54 of 97

<sup>\*</sup> **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

*Test mode: Transmitting(Test performed at ANT 1)* 

#### 5150-5250MHz:

Mode	Channel	Frequency (MHz)	26 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
	Low	5180	20.52	17.2
802.11 a	Middle	5200	20.6	17.2
	High	5240	20.6	17.2
802.11n ht20	Low	5180	21.24	18.16
	Middle	5200	21.32	18.16
	High	5240	21.24	18.16
802.11n ht40	Low	5190	42.48	37.6
	High	5230	42.65	37.6
802.11ac80	Middle	5210	81.12	76.48

Report No.: RDG180129005-00B

Note: the 99% Occupied Bandwidth have not fall into the band 5250-5350 MHz, please refer to the test plots of 99% Occupied Bandwidth.

## 5725-5850MHz:

Mode	Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
802.11 a	Low	5745	16.35	17.28
	Middle	5785	16.35	17.36
	High	5825	16.35	17.36
802.11n ht20	Low	5745	17.64	18.08
	Middle	5785	17.64	18.08
	High	5825	17.47	18.08
802.11n ht40	Low	5755	36.39	37.6
	High	5795	36.39	37.6
802.11ac80	Middle	5775	75.03	76.8


Note: For 5725-5850MHz band, the 99% Occupied Bandwidth have not fall into the band 5470-5725MHz.

FCC Part 15.407 Page 55 of 97

## 5150-5250MHz: 26dB Emission Bandwidth:


#### 802.11a Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:25:01

# 802.11a Middle Channel




Date: 2.FEB.2018 10:26:15

FCC Part 15.407 Page 56 of 97


## 802.11a High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:27:10

#### 802.11n ht20 Low Channel




Date: 2.FEB.2018 10:28:30

FCC Part 15.407 Page 57 of 97


## 802.11n ht20 Middle Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:29:35

## 802.11n ht20 High Channel




Date: 2.FEB.2018 10:30:51

FCC Part 15.407 Page 58 of 97


# 802.11n ht40 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:32:02

## 802.11n ht40 High Channel




Date: 2.FEB.2018 10:34:19

FCC Part 15.407 Page 59 of 97

## 802.11ac80 Middle Channel


Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:37:05

## 99% Occupied Bandwidth

#### 802.11a Low Channel



Date: 2.FEB.2018 10:25:12

FCC Part 15.407 Page 60 of 97


#### **802.11a** Middle Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:26:26

## 802.11a High Channel




Date: 2.FEB.2018 10:27:23

FCC Part 15.407 Page 61 of 97


# 802.11n ht20 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:28:47

#### 802.11n ht20 Middle Channel




Date: 2.FEB.2018 10:29:51

FCC Part 15.407 Page 62 of 97


## 802.11n ht20 High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:31:07

#### 802.11n ht40 Low Channel




Date: 2.FEB.2018 10:32:18

FCC Part 15.407 Page 63 of 97


## 802.11n ht40 High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:34:35

#### 802.11ac80 Middle Channel




Date: 2.FEB.2018 10:37:21

FCC Part 15.407 Page 64 of 97

# **5725-5850MHz: 6dB Bandwidth:**


#### 802.11a Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:49:51

# 802.11a Middle Channel




Date: 2.FEB.2018 10:51:07

FCC Part 15.407 Page 65 of 97


## 802.11a High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:52:17

#### 802.11ht20 Low Channel




Date: 2.FEB.2018 10:41:30

FCC Part 15.407 Page 66 of 97


# 802.11ht20 Middle Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:43:13

## 802.11ht20 High Channel




Date: 2.FEB.2018 10:44:35

FCC Part 15.407 Page 67 of 97


# 802.11ht40 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:46:36

## 802.11ht40 High Channel




Date: 2.FEB.2018 10:48:11

FCC Part 15.407 Page 68 of 97

#### 802.11ac80 Middle Channel


Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:39:24

## 99% Occupied Bandwidth:

#### 802.11a Low Channel




Date: 2.FEB.2018 10:50:01

FCC Part 15.407 Page 69 of 97


#### 802.11a Middle Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 14:14:32

## 802.11a High Channel




Date: 2.FEB.2018 14:16:11

FCC Part 15.407 Page 70 of 97


#### 802.11ht20 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:41:43

#### 802.11ht20 Middle Channel




Date: 2.FEB.2018 10:43:29

FCC Part 15.407 Page 71 of 97


## 802.11ht20 High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:44:52

#### 802.11ht40 Low Channel




Date: 2.FEB.2018 10:46:53

FCC Part 15.407 Page 72 of 97


# 802.11ht40 High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:48:24

## 802.11ac80 Middle Channel



Date: 2.FEB.2018 10:39:38

FCC Part 15.407 Page 73 of 97

# FCC §15.407(a) -MAXIMUM CONDUCTED OUTPUT POWER

#### **Applicable Standard**

- (a) Power limits:
- (1) For the band 5.15-5.25 GHz.
- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

Report No.: RDG180129005-00B

- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

FCC Part 15.407 Page 74 of 97

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Report No.: RDG180129005-00B

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

## **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	USB Wideband Power Sensor	U2022XA	MY5417006	2017-12-11	2018-12-11
Agilent	USB Wideband Power Sensor	U2022XA	MY5417014	2017-12-11	2018-12-11
Agilent	USB Wideband Power Sensor	U2022XA	MY5417009	2017-12-11	2018-12-11
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Procedure**

According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	21.3°C
Relative Humidity:	36%
ATM Pressure:	102kPa

The testing was performed by Nami Quan on 2018-02-02.

FCC Part 15.407 Page 75 of 97

Test Mode: Transmitting

UNII Band	Mode	Frequency (MHz)	Conducted Average Output Power (dBm)			Limit (dBm)	Result
		,	ANT 1	ANT 2	Total		
		5180	12.97	12.96	/	30	PASS
	802.11 a	5200	13.18	13.24	/	30	PASS
		5240	13.28	13.27	/	30	PASS
5150 5250		5180	9.42	9.14	12.29	30	PASS
5150-5250 MHz	802.11ht20	5200	9.59	9.15	12.39	30	PASS
IVIIIZ		5240	9.11	9.48	12.31	30	PASS
	802.11ht40	5190	9.27	9.09	12.19	30	PASS
		5230	8.83	8.95	11.9	30	PASS
	802.11 ac80	5210	7.31	7.18	10.26	30	PASS
	802.11 a	5745	12.97	13.11	/	30	PASS
		5785	12.65	12.69	/	30	PASS
		5825	12.65	12.71	/	30	PASS
5725-5850 MHz	802.11ht20	5745	8.52	9	11.78	30	PASS
		5785	8.7	9.33	12.04	30	PASS
		5825	8.26	9.14	11.73	30	PASS
	802.11ht40	5755	8.64	9.04	11.85	30	PASS
		5795	8.67	8.9	11.8	30	PASS
	802.11 ac80	5775	7.17	7.38	10.29	30	PASS

Report No.: RDG180129005-00B

Note: The maximum antenna gain is 5.0dBi in 5GHz band. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power measurements on IEEE 802.11 devices:

Array Gain = 0 dB (i.e., no array gain) for 
$$NANT \le 4$$
;

So:

Directional gain =  $G_{ANT}$  + Array Gain = 5.0dBi < 6dBi

FCC Part 15.407 Page 76 of 97

# FCC §15.407(a) - POWER SPECTRAL DENSITY

## **Applicable Standard**

- (a) Power limits:
- (1) For the band 5.15-5.25 GHz.
- (i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

Report No.: RDG180129005-00B

- (ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.
- (iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- (2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm 10 log B, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output

FCC Part 15.407 Page 77 of 97

power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Report No.: RDG180129005-00B

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

#### **Test Procedure**

According to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

## **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU 26	200256	2018-01-04	2019-01-04
N/A	Coaxial Cable	C-SJ00-0010	C0010/01	Each time	N/A

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

## **Environmental Conditions**

Temperature:	21.3~22.3°C		
Relative Humidity:	36 %		
ATM Pressure:	101.3~102kPa		

The testing was performed by Nami Quan from 2018-02-02 to 2018-02-12.

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plot.

FCC Part 15.407 Page 78 of 97

#### 5150-5250MHz

Mode	Frequency (MHz)	Power Spectral Density (dBm/MHz)					
		ANT 1	ANT 2	Total	Limits		
	5180	2.72	3.12	/	17		
802.11 a	5200	3.05	3.47	/	17		
	5240	2.78	3.31	/	17		
802.11 ht20	5180	-0.29	-0.24	2.75	17		
	5200	-0.38	-0.24	2.7	17		
	5240	-0.57	-0.33	2.56	17		
802.11	5190	-3.91	-3.4	-0.64	17		
ht40	5230	-4.45	-3.82	-1.11	17		
802.11 ac80	5210	-7.51	-7.28	-4.38	17		

Report No.: RDG180129005-00B

#### 5725-5850MHz

Mode	Frequency (MHz)	Reading (dBm/300kHz)		Power Spectral Density (dBm/500kHz)			
		ANT 1	ANT 2	ANT 1	ANT 2	Total	Limit
	5745	-0.93	-1.12	1.29	1.1	/	30
802.11 a	5785	-0.81	-1.07	1.41	1.15	/	30
	5825	-1.27	-1.50	0.95	0.72	/	30
802.11 ht20	5745	-4.75	-5.03	-2.53	-2.81	0.34	30
	5785	-5.14	-4.65	-2.92	-2.43	0.34	30
	5825	-5.56	-4.89	-3.34	-2.67	0.02	30
802.11	5755	-7.80	-6.99	-5.58	-4.77	-2.15	30
ht40	5795	-7.72	-6.51	-5.5	-4.29	-1.84	30
802.11 ac80	5775	-10.87	-9.53	-8.65	-7.31	-4.92	30

Note 1:The maximum antenna gain is 5.0dBi in 5GHz band. The device employed Cyclic Delay Diversity (CDD) for 802.11 MIMO transmitting, per KDB 662911 D01 Multiple Transmitter Output v02r01, for power spectral density (PSD) measurements on the devices:

Array Gain = 
$$10 \log(N_{ANT}/N_{SS}) dB$$
.

So:

Directional gain =  $G_{ANT}$  + Array Gain = 5.0dBi+10\*log(2/2)=5.0dBi

Note 2: For 5.8 GHz band, If measurement bandwidth of Maximum PSD is specified in 500 kHz, add  $10 \log(500 \text{kHz/RBW})$  to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.

FCC Part 15.407 Page 79 of 97

## 5150-5250MHz ANT 1:


## 802.11a Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:38:15

## 802.11a Middle Channel




Date: 2.FEB.2018 11:20:45

FCC Part 15.407 Page 80 of 97


# 802.11a High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:21:15

## 802.11n ht20 Low Channel




Date: 2.FEB.2018 11:23:59

FCC Part 15.407 Page 81 of 97


# 802.11n ht20 Middle Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:24:51

# 802.11n ht20 High Channel




Date: 2.FEB.2018 11:25:18

FCC Part 15.407 Page 82 of 97


# 802.11n ht40 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:31:23

# 802.11n ht40 High Channel




Date: 2.FEB.2018 11:35:22

FCC Part 15.407 Page 83 of 97

## 802.11ac80 Middle Channel


Report No.: RDG180129005-00B



Date: 12.FEB.2018 11:14:10

#### **ANT 2:**

## 802.11a Low Channel




Date: 2.FEB.2018 10:57:25

FCC Part 15.407 Page 84 of 97


#### 802.11a Middle Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 10:58:14

# 802.11a High Channel




Date: 2.FEB.2018 10:59:35

FCC Part 15.407 Page 85 of 97


## 802.11n ht20 Low Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:02:51

## 802.11n ht20 Middle Channel




Date: 2.FEB.2018 11:05:09

FCC Part 15.407 Page 86 of 97


# 802.11n ht20 High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:05:57

## 802.11n ht40 Low Channel




Date: 2.FEB.2018 11:06:47

FCC Part 15.407 Page 87 of 97


# 802.11n ht40 High Channel

Report No.: RDG180129005-00B



Date: 2.FEB.2018 11:07:36

## 802.11ac80 Middle Channel




Date: 12.FEB.2018 11:13:48

FCC Part 15.407 Page 88 of 97

## 5725-5850MHz ANT 1:


## 802.11a Low Channel

Report No.: RDG180129005-00B



Date: 12.FEB.2018 11:03:24

## 802.11a Middle Channel




Date: 12.FEB.2018 11:03:58

FCC Part 15.407 Page 89 of 97


## 802.11a High Channel

Report No.: RDG180129005-00B



Date: 12.FEB.2018 11:04:55

## 802.11n ht20 Low Channel




Date: 12.FEB.2018 10:58:25

FCC Part 15.407 Page 90 of 97


# 802.11n ht20 Middle Channel

Report No.: RDG180129005-00B



Date: 12.FEB.2018 10:58:56

# 802.11n ht20 High Channel




Date: 12.FEB.2018 11:00:27

FCC Part 15.407 Page 91 of 97


# 802.11n ht40 Low Channel

Report No.: RDG180129005-00B



Date: 12.FEB.2018 11:01:13

# 802.11n ht40 High Channel




Date: 12.FEB.2018 11:01:41

FCC Part 15.407 Page 92 of 97

## 802.11ac80 Middle Channel


Report No.: RDG180129005-00B



Date: 12.FEB.2018 11:12:52

#### **ANT 2:**

## 802.11a Low Channel




Date: 12.FEB.2018 11:06:26

FCC Part 15.407 Page 93 of 97


#### 802.11a Middle Channel

Report No.: RDG180129005-00B



Date: 12.FEB.2018 11:09:22

# 802.11a High Channel




Date: 12.FEB.2018 11:08:34

FCC Part 15.407 Page 94 of 97


#### 802.11n ht20 Low Channel

Report No.: RDG180129005-00B



Date: 12.FEB.2018 10:46:15

## 802.11n ht20 Middle Channel




Date: 12.FEB.2018 10:46:48

FCC Part 15.407 Page 95 of 97


# 802.11 n ht20 High Channel

Report No.: RDG180129005-00B



Date: 12.FEB.2018 10:47:20

## 802.11n ht40 Low Channel




Date: 12.FEB.2018 11:10:35

FCC Part 15.407 Page 96 of 97


# 802.11n ht40 High Channel

Report No.: RDG180129005-00B



Date: 12.FEB.2018 11:11:09

## 802.11ac80 Middle Channel



Date: 12.FEB.2018 11:11:46

\*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 15.407 Page 97 of 97