

FCC Test Report

FCC ID : X8Y600
Equipment : Swiftpoint G4 Computer Mouse
Brand Name : SWIFTPOINT
Model Name : 600 ; 601 ; 602 ; 603
Applicant : Swiftpoint Limited
77 Montreal St. Christchurch 8023 New Zealand
Manufacturer : Swiftpoint Limited
77 Montreal St. Christchurch 8023 New Zealand
Standard : 47 CFR FCC Part 15.247

The product was received on Jul. 26, 2018, and testing was started from Aug. 10, 2018 and completed on Aug. 10, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

HISTORY OF THIS TEST REPORT	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Information.....	5
1.2 Testing Applied Standards	7
1.3 Testing Location Information	7
1.4 Measurement Uncertainty	7
2 TEST CONFIGURATION OF EUT.....	8
2.1 Test Condition	8
2.2 Test Channel Mode	8
2.3 The Worst Case Measurement Configuration.....	9
2.4 Accessories and Support Equipment	10
2.5 Test Setup Diagram	11
3 TRANSMITTER TEST RESULT	12
3.1 AC Power-line Conducted Emissions	12
3.2 DTS Bandwidth.....	13
3.3 Maximum Conducted Output Power	14
3.4 Power Spectral Density	16
3.5 Emissions in Non-restricted Frequency Bands	17
3.6 Emissions in Restricted Frequency Bands.....	18
4 TEST EQUIPMENT AND CALIBRATION DATA.....	21
APPENDIX A. TEST RESULTS OF AC POWER-LINE CONDUCTED EMISSIONS	
APPENDIX B. TEST RESULTS OF DTS BANDWIDTH	
APPENDIX C. TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER	
APPENDIX D. TEST RESULTS OF POWER SPECTRAL DENSITY	
APPENDIX E. TEST RESULTS OF EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	
APPENDIX F. TEST RESULTS OF EMISSIONS IN RESTRICTED FREQUENCY BANDS	
APPENDIX G. TEST PHOTOS	
PHOTOGRAPHS OF EUT V01	



History of this test report

TEL : 886-3-3273456
FAX : 886-3-3270973
Report Template No.: HE1-C10 Ver3.1
FCC ID: X8Y600

Summary of Test Result

Report Clause	Ref. Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	FCC 15.203
3.1	15.207	AC Power-line Conducted Emissions	PASS	FCC 15.207
3.2	15.247(a)	DTS Bandwidth	PASS	≥500kHz
3.3	15.247(b)	Maximum Conducted Output Power	PASS	Power [dBm]:30
3.4	15.247(e)	Power Spectral Density	PASS	PSD [dBm/3kHz]:8
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	Non-Restricted Bands: >30 dBc
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	Restricted Bands: FCC 15.209

Reviewed by: Sam Tsai

Report Producer: Debby Hung

1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4-2.4835GHz	BT-LE(1Mbps)	1.0	1TX

Frequency Range (MHz)	Channel No.	Frequency	Channel No.	Frequency	Channel No.	Frequency	Channel No.	Frequency
2.4-2.4835GHz	0	2402	11	2424	22	2446	33	2468
	1	2404	12	2426	23	2448	34	2470
	2	2406	13	2428	24	2450	35	2472
	3	2408	14	2430	25	2452	36	2474
	4	2410	15	2432	26	2454	37	2476
	5	2412	16	2434	27	2456	38	2478
	6	2414	17	2436	28	2458	39	2480
	7	2416	18	2438	29	2460	-	-
	8	2418	19	2440	30	2462	-	-
	9	2420	20	2442	31	2464	-	-
	10	2422	21	2444	32	2466	-	-

Note:

- ♦ Bluetooth LE uses a GFSK (1Mbps) modulation for DSSS.
- ♦ BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	Port	Brand	Model Name	Antenna Type	Connector
1	1	SWIFTPPOINT	Antenna for Swiftpoint G4 Computer Mouse	PCB Antenna	fixed on board

Ant.	Gain (dBi)	
	SRD 2.4G	BTLE
1	-0.16	-0.16

For SRD 2.4GHz function:

For SRD 2.4G mode (1TX/1RX)

Ant. 1 (port 1) could transmit/receive simultaneously.

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Ant. 1 (port 1) could transmit/receive simultaneously.

1.1.3 Table for Multiple Listing

The brand/model names in the following table are all refer to the identical product.

Brand Name	Model Name	BUTTON	Description
SWIFTPPOINT	600	3	All the models are electrically identical, the difference model for difference brand and button served as marketing strategy.
SWIFTPPOINT	601	2	
SWIFTPPOINT	602	2	
SWIFTPPOINT	603	2	

1.1.4 EUT Information

Operational Condition			
EUT Power Type	From Battery / Host system		
EUT Function	<input type="checkbox"/> Point-to-multipoint	<input checked="" type="checkbox"/> Point-to-point	
Type of EUT			
<input checked="" type="checkbox"/>	Stand-alone		
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device)		
	Combined Equipment - Brand Name / Model No.:		...
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems)		
	Host System - Brand Name / Model No.:		...
<input type="checkbox"/>	Other:		

1.1.5 Mode Test Duty Cycle

Mode	DC	DCF(dB)	T(s)	VBW(Hz) $\geq 1/T$
BT-LE(1Mbps)	0.228	6.421	142.5u	10k

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013
- ♦ KDB 558074 D01 v05

1.3 Testing Location Information

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)		
		TEL : 886-3-327-3456	FAX : 886-3-327-0973	
Test site Designation No. TW1190 with FCC.				
<input type="checkbox"/>	JHUBEI	ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)		
		TEL : 886-3-656-9065	FAX : 886-3-656-9085	
Test site Designation No. TW0006 with FCC.				

Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH06-HY	Barry	23.3°C / 63%	10/Aug/2018
Radiated	03CH03-HY	Jeff	22.2°C / 51.8%	10/Aug/2018
AC Conduction	CO04-HY	Jerry	24.5°C / 55.5%	11/Sep/2018

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.6 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	3.0 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	3.9 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	3.5 dB	Confidence levels of 95%
Conducted Emission	1.3 dB	Confidence levels of 95%
Temperature	0.7 °C	Confidence levels of 95%
Humidity	4 %	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Condition

RF Conducted	Abbreviation	Remark
TnomVnom	Tnom	20°C
-	Vnom	3.3V

2.2 Test Channel Mode




Test Software Version	nRFgo Studio v1.21.2.10
-----------------------	-------------------------

Mode	PowerSetting
BT-LE(1Mbps)	-
2402MHz	default
2440MHz	default
2480MHz	default

2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral
Operating Mode	CTX
1	USB mode

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests			
Tests Item	Emissions in Restricted Frequency Bands		
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.		
Operating Mode < 1GHz	CTX		
1	Battery mode		
Operating Mode > 1GHz	CTX		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT		V	

2.4 Accessories and Support Equipment

Accessories				
Battery	Power Rating	3.7Vdc, 120 mAh	Type	Li-ion Polymer Battery, <u>Y</u>


Reminder: Regarding to more detail and other information, please refer to user manual.

Support Equipment – RF Conducted				
No.	Equipment	Brand Name	Model Name	FCC ID
1	Notebook	DELL	E5410	R33002 / DOC
2	Adapter for NB	DELL	HA65NM130	R35737 / DOC
3	DC Power Supply	GW	GPS-3030DD	-
4	fixture	-	-	-

Note.Support equipment No.4 was provided by customer.

Support Equipment – AC Conduction				
No.	Equipment	Brand Name	Model Name	FCC ID
1	NB	HP	5220m	-
2	AC adapter for NB	DELL	AD-90195D	-

2.5 Test Setup Diagram



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as ANSI C63.10-2013, clause 6.2 foray power-line conducted emissions.

3.1.4 Test Setup



3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit	
Systems using digital modulation techniques:	
▪	6 dB bandwidth \geq 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
▪ For the emission bandwidth shall be measured using one of the options below:	
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.2 (11.9.2.2 of ANSI C63.10) DTS bandwidth measurement.
<input type="checkbox"/>	Refer as RSS-Gen, clause 6.7 for occupied bandwidth testing.
<input type="checkbox"/>	Refer as ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit	
	<ul style="list-style-type: none"> If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)
	<ul style="list-style-type: none"> Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm
	<ul style="list-style-type: none"> Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> Smart antenna system (SAS):
	<ul style="list-style-type: none"> - Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm
	<ul style="list-style-type: none"> - Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dBm
e.i.r.p. Power Limit:	
	<ul style="list-style-type: none"> 2400-2483.5 MHz Band
	<ul style="list-style-type: none"> Point-to-multipoint systems (P2M): $P_{eirp} \leq 36$ dBm (4 W)
	<ul style="list-style-type: none"> Point-to-point systems (P2P): $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX}])$ dBm
	<ul style="list-style-type: none"> Smart antenna system (SAS)
	<ul style="list-style-type: none"> - Single beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<ul style="list-style-type: none"> - Overlap beam: $P_{eirp} \leq \text{MAX}(36, P_{Out} + G_{TX})$ dBm
	<ul style="list-style-type: none"> - Aggregate power on all beams: $P_{eirp} \leq \text{MAX}(36, [P_{Out} + G_{TX} + 8])$ dBm
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.	


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
<ul style="list-style-type: none"> Maximum Peak Conducted Output Power 	
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.1 (11.9.1.1 of ANSI C63.10) RBW ≥ EBW method.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.2 (11.9.1.2 of ANSI C63.10) integrated band power method.
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.1.3 (11.9.1.3 of ANSI C63.10) peak power meter.
<ul style="list-style-type: none"> Maximum Average Conducted Output Power 	
<input type="checkbox"/>	Refer as KDB 558074, clause 8.3.2.2 (11.9.2.2 of ANSI C63.10) using a spectrum analyzer.
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.3.2.3 (11.9.2.3 of ANSI C63.10) using a power meter.
<ul style="list-style-type: none"> For conducted measurement. 	
<ul style="list-style-type: none"> If the EUT supports multiple transmit chains using options given below: Refer as KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them. 	
<ul style="list-style-type: none"> If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$ 	

3.3.4 Test Setup



3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C

3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit	
▪	Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
▪	Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/>	Refer as KDB 558074, clause 8.4 (11.10 of ANSI C63.10) Method PKPSD.
▪	For conducted measurement.
▪	If The EUT supports multiple transmit chains using options given below:
▪	Measure and sum the spectra across the outputs. Refer as KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30
<p>Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.</p> <p>Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.</p>	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
<ul style="list-style-type: none"> Refer as KDB 558074, clause 8.5 (11.11 of ANSI C63.10) for non-restricted frequency bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.


3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
	<ul style="list-style-type: none"> The average emission levels shall be measured in [duty cycle \geq 98 or duty factor].
	<ul style="list-style-type: none"> Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
	<ul style="list-style-type: none"> For the transmitter unwanted emissions shall be measured using following options below:
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 8.6 (11.12 of ANSI C63.10) for restricted frequency bands.
	<ul style="list-style-type: none"> For the transmitter band-edge emissions shall be measured using following options below:
	<ul style="list-style-type: none"> Refer as KDB 558074 clause 8.7.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 8.7.2 (6.10.6 of ANSI C63.10) for marker-delta method for band-edge measurements.
	<ul style="list-style-type: none"> Refer as KDB 558074, clause 8.7.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).

3.6.4 Test Setup





3.6.5 Test Result of Emissions in Restricted Frequency Bands (Below 30MHz)

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.6.6 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F

4 Test Equipment and Calibration Data

Instrument for Conducted Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSV 40	101013	9kHz~40GHz	29/Dec/2017	28/Dec/2018
Signal Generator	R&S	SMR 40	100116	10MHz ~ 40GHz	23/Jul/2018	22/Jul/2019
Pulse Power Sensor	Anritsu	MA2411B	1027452	300MHz ~ 40GHz	27/Feb/2018	26/Feb/2019
Power Meter	Anritsu	ML2495A	1124009	300MHz ~ 40GHz	27/Feb/2018	26/Feb/2019
CABLE 0.2m	HUBER	MY37960/4	RF Cable - 17	1 to 18GHz	17/Jan/2018	16/Jan/2019
CABLE 0.2m	HUBER	MY37960/4	RF Cable - 17	30 to 1000MHz	17/Jan/2018	16/Jan/2019
CABLE 0.5m	HUBER	MY37963/4	RF Cable - 22	1 to 18GHz	17/Jan/2018	16/Jan/2019

Instrument for Radiated Test


Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz ~ 1GHz 3m	31/Oct/2017	30/Oct/2018
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	1GHz ~ 18GHz 3m	01/Nov/2017	31/Oct/2018
Amplifier	HP	8447D	2944A08033	10kHz ~ 1.3GHz	23/Apr/2018	19/Apr/2019
Microwave System Preamplifier	KEYSIGHT	83017A	MY53270196	1GHz ~ 26.5GHz	31/Aug/2017	30/Aug/2018
Signal Analyzer	R&S	FSP40	100305	10Hz ~ 40GHz	04/Jan/2018	03/Jan/2019
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	29/Jan/2018	28/Jan/2019
RF Cable-high	SUHNER	SUCOFLEX 106	CB222	1GHz ~ 40GHz	29/Jan/2018	28/Jan/2019
Bilog Antenna	SCHAFFNER	CBL 6112B	2723	30MHz ~ 1GHz	09/Sep/2017	08/Sep/2018
Receiver	R&S	ESCS 30	100354	9kHz ~ 2.75GHz	08/Dec/2017	07/Dec/2018
Broadband Horn Antenna	SCHWARZBEC K	BBHA 9170	BBHA 9170154	18GHz ~ 40GHz	06/Feb/ 2018	05/Feb/2019
Double Ridged Guide Horn Antenna	SCHWARZBEC K	BBHA 9120 D	BBHA 9120 D 1531	1GHz ~ 18GHz	18/Apr/ 2018	17/Apr/2019
Loop Antenna	TESEQ	HLA 6120	31244	9kHz ~ 30MHz	28/Mar/2018	27/Mar/2019

Instrument for Conduction Test

Instrument	Manufacturer	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
EMC Receiver	R&S	ESR	102051	9KHz ~ 3.6GHz	03/May/2018	02/May/2019
LISN	R&S	ENV216	101295	9kHz ~ 30MHz	17/Nov/2017	16/Nov/2018
RF Cable-CON	HUBER+SUHNER	RG213/U	0761183202000 1	9kHz ~ 30MHz	06/Oct/2017	05/Oct/2018
AC POWER	APC	AFC-11005G	F310050055	47Hz~63Hz 5~300V	NCR	NCR
Impuls Begrenzer Puls e Limiter	SCHWARZBEC K	VTSD 9561-F	9561-F041	9 kHz ~ 30 MHz	12/Oct/2017	11/Oct/2018

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Neutral
Operating Function	USB mode		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	17.41	-38.59	56.00	7.74	9.63	0.04	Average
2	0.15	19.42	-46.58	66.00	9.75	9.63	0.04	QP
3	0.29	19.65	-30.81	50.46	9.99	9.61	0.05	Average
4	0.29	21.39	-39.07	60.46	11.73	9.61	0.05	QP
5	1.89	16.59	-29.41	46.00	6.96	9.63	0.00	Average
6	1.89	19.19	-36.81	56.00	9.56	9.63	0.00	QP
7 MAX	2.20	18.37	-27.63	46.00	8.73	9.63	0.01	Average
8	2.20	24.53	-31.47	56.00	14.89	9.63	0.01	QP
9	3.60	18.06	-27.94	46.00	8.35	9.64	0.07	Average
10	3.60	21.02	-34.98	56.00	11.31	9.64	0.07	QP
11	19.33	15.25	-34.75	50.00	5.36	9.71	0.18	Average
12	19.33	17.45	-42.55	60.00	7.56	9.71	0.18	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

AC Power-line Conducted Emissions Result

Operating Mode	1	Power Phase	Line
Operating Function	USB mode		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.15	16.78	-39.04	55.82	7.12	9.62	0.04	Average
2	0.15	18.30	-47.52	65.82	8.64	9.62	0.04	QP
3	0.29	21.44	-29.02	50.46	11.78	9.61	0.05	Average
4	0.29	22.73	-37.73	60.46	13.07	9.61	0.05	QP
5	1.70	14.90	-31.10	46.00	5.28	9.62	0.00	Average
6	1.70	19.69	-36.31	56.00	10.07	9.62	0.00	QP
7	2.16	18.19	-27.81	46.00	8.56	9.62	0.01	Average
8	2.16	24.61	-31.39	56.00	14.98	9.62	0.01	QP
9 MAX	3.76	19.83	-26.17	46.00	10.12	9.63	0.08	Average
10	3.76	22.78	-33.22	56.00	13.07	9.63	0.08	QP
11	25.59	18.07	-31.93	50.00	8.48	9.55	0.04	Average
12	25.59	21.84	-38.16	60.00	12.25	9.55	0.04	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	617.5k	1.093M	1M09F1D	600k	920.79k

Max-N dB = Maximum 6dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;

Min-N dB = Minimum 6dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	617.5k	1.068M
2440MHz	Pass	500k	600k	920.79k
2480MHz	Pass	500k	613.75k	1.093M


Port X-N dB = Port X 6dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

BT-LE(1Mbps)
EBW
2402MHz


10/08/2018


BT-LE(1Mbps)
EBW
2440MHz

10/08/2018


BT-LE(1Mbps)
EBW
2480MHz

10/08/2018



Summary

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	-13.15	0.00005

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	-0.16	-14.59	30.00
2440MHz	Pass	-0.16	-13.15	30.00
2480MHz	Pass	-0.16	-14.14	30.00

Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	-21.81

RBW=3kHz.

Result

Mode	Result	Gain (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	-0.16	-25.79	8.00
2440MHz	Pass	-0.16	-21.81	8.00
2480MHz	Pass	-0.16	-22.68	8.00


RBW=3kHz.

BT-LE(1Mbps)

PSD

2402MHz

10/08/2018




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-25.79	-25.79	-25.79

BT-LE(1Mbps)

PSD

2440MHz

10/08/2018




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-21.81	-21.81	-21.81

BT-LE(1Mbps)

PSD

2480MHz

10/08/2018



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-22.68	-22.68	-22.68

Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.440247G	-7.92	-37.92	2.394448G	-63.43	2.399756G	-46.75	2.485348G	-63.67	16.255931G	-55.03	1

Result


Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.440247G	-7.92	-37.92	2.394448G	-63.43	2.399756G	-46.75	2.485348G	-63.67	16.255931G	-55.03	1
2440MHz	Pass	2.440247G	-7.92	-37.92	620.816M	-64.45	2.399352G	-64.31	2.485036G	-64.07	15.186492G	-54.11	1
2480MHz	Pass	2.440247G	-7.92	-37.92	427.824M	-63.91	2.399096G	-63.77	2.4836G	-53.29	2.496757G	-49.78	1

BT-LE(1Mbps)

2402MHz

CSE NdB

10/08/2018




BT-LE(1Mbps)

2440MHz

CSE NdB

10/08/2018




BT-LE(1Mbps)

2480MHz

CSE NdB

10/08/2018



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	PK	730.34M	31.67	46.00	-14.33	1.16	3	Horizontal	360	1.00	-


Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2440MHz	Pass	PK	39.7M	24.77	40.00	-15.23	-7.82	3	Vertical	0	1.00	-
2440MHz	Pass	PK	105.66M	20.38	43.50	-23.12	-8.72	3	Vertical	0	1.00	-
2440MHz	Pass	PK	282.2M	21.17	46.00	-24.83	-6.01	3	Vertical	0	1.00	-
2440MHz	Pass	PK	355.92M	24.15	46.00	-21.85	-4.43	3	Vertical	0	1.00	-
2440MHz	Pass	PK	483.96M	26.77	46.00	-19.23	-1.73	3	Vertical	0	1.00	-
2440MHz	Pass	PK	606.18M	28.76	46.00	-17.24	-0.38	3	Vertical	0	1.00	-
2440MHz	Pass	PK	30M	25.18	40.00	-14.82	-2.38	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	109.54M	19.65	43.50	-23.85	-8.32	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	258.92M	20.62	46.00	-25.38	-5.65	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	404.42M	24.31	46.00	-21.69	-3.19	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	546.04M	27.69	46.00	-18.31	-0.30	3	Horizontal	360	1.00	-
2440MHz	Pass	PK	730.34M	31.67	46.00	-14.33	1.16	3	Horizontal	360	1.00	-

BT-LE(1Mbps)

2440MHz_Battery

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	39.7M	24.77	40.00	-15.23	-7.82	3	Vertical	0	1.00	-
PK	105.66M	20.38	43.50	-23.12	-8.72	3	Vertical	0	1.00	-
PK	282.2M	21.17	46.00	-24.83	-6.01	3	Vertical	0	1.00	-
PK	355.92M	24.15	46.00	-21.85	-4.43	3	Vertical	0	1.00	-
PK	483.96M	26.77	46.00	-19.23	-1.73	3	Vertical	0	1.00	-
PK	606.18M	28.76	46.00	-17.24	-0.38	3	Vertical	0	1.00	-

BT-LE(1Mbps)

2440MHz_Battery

10/08/2018



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
PK	30M	25.18	40.00	-14.82	-2.38	3	Horizontal	360	1.00	-
PK	109.54M	19.65	43.50	-23.85	-8.32	3	Horizontal	360	1.00	-
PK	258.92M	20.62	46.00	-25.38	-5.65	3	Horizontal	360	1.00	-
PK	404.42M	24.31	46.00	-21.69	-3.19	3	Horizontal	360	1.00	-
PK	546.04M	27.69	46.00	-18.31	-0.30	3	Horizontal	360	1.00	-
PK	730.34M	31.67	46.00	-14.33	1.16	3	Horizontal	360	1.00	-

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	AV	2.496G	45.92	54.00	-8.08	30.74	3	Vertical	0	1.52	-


Result

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	AV	2.3872G	44.13	54.00	-9.87	30.37	3	Vertical	97	2.93	-
2402MHz	Pass	AV	2.402G	84.29	Inf	-Inf	30.41	3	Vertical	97	2.93	-
2402MHz	Pass	PK	2.387G	55.53	74.00	-18.47	30.37	3	Vertical	97	2.93	-
2402MHz	Pass	PK	2.402G	88.13	Inf	-Inf	30.41	3	Vertical	97	2.93	-
2402MHz	Pass	AV	2.3852G	44.08	54.00	-9.92	30.36	3	Horizontal	36	1.17	-
2402MHz	Pass	AV	2.402G	87.61	Inf	-Inf	30.41	3	Horizontal	36	1.17	-
2402MHz	Pass	PK	2.3736G	57.87	74.00	-16.13	30.33	3	Horizontal	36	1.17	-
2402MHz	Pass	PK	2.402G	91.59	Inf	-Inf	30.41	3	Horizontal	36	1.17	-
2402MHz	Pass	AV	4.80392G	37.69	54.00	-16.31	5.79	3	Vertical	191	1.02	-
2402MHz	Pass	PK	4.80352G	57.48	74.00	-16.52	5.78	3	Vertical	191	1.02	-
2402MHz	Pass	AV	4.80394G	37.48	54.00	-16.52	5.79	3	Horizontal	87	2.22	-
2402MHz	Pass	PK	4.8035G	56.88	74.00	-17.12	5.78	3	Horizontal	87	2.22	-
2440MHz	Pass	AV	2.382G	43.86	54.00	-10.14	30.35	3	Vertical	86	2.53	-
2440MHz	Pass	AV	2.44G	85.80	Inf	-Inf	30.55	3	Vertical	86	2.53	-
2440MHz	Pass	AV	2.496G	44.84	54.00	-9.16	30.74	3	Vertical	86	2.53	-
2440MHz	Pass	PK	2.389998G	55.24	74.00	-18.76	30.38	3	Vertical	86	2.53	-
2440MHz	Pass	PK	2.44G	89.65	Inf	-Inf	30.55	3	Vertical	86	2.53	-
2440MHz	Pass	PK	2.496G	59.50	74.00	-14.50	30.74	3	Vertical	86	2.53	-
2440MHz	Pass	AV	2.3884G	43.98	54.00	-10.02	30.37	3	Horizontal	36	1.35	-
2440MHz	Pass	AV	2.44G	87.22	Inf	-Inf	30.55	3	Horizontal	36	1.35	-
2440MHz	Pass	AV	2.496G	44.69	54.00	-9.31	30.74	3	Horizontal	36	1.35	-
2440MHz	Pass	PK	2.376G	55.27	74.00	-18.73	30.33	3	Horizontal	36	1.35	-
2440MHz	Pass	PK	2.4396G	91.06	Inf	-Inf	30.55	3	Horizontal	36	1.35	-
2440MHz	Pass	PK	2.496G	58.65	74.00	-15.35	30.74	3	Horizontal	36	1.35	-
2440MHz	Pass	AV	4.88002G	36.35	54.00	-17.65	5.95	3	Vertical	192	1.01	-
2440MHz	Pass	PK	4.87956G	53.16	74.00	-20.84	5.95	3	Vertical	192	1.01	-
2440MHz	Pass	AV	4.88004G	35.28	54.00	-18.72	5.95	3	Horizontal	331	2.39	-
2440MHz	Pass	PK	4.87958G	51.23	74.00	-22.77	5.95	3	Horizontal	331	2.39	-
2480MHz	Pass	AV	2.48G	87.09	Inf	-Inf	30.68	3	Vertical	0	1.52	-
2480MHz	Pass	AV	2.496G	45.92	54.00	-8.08	30.74	3	Vertical	0	1.52	-
2480MHz	Pass	PK	2.4802G	90.81	Inf	-Inf	30.68	3	Vertical	0	1.52	-
2480MHz	Pass	PK	2.4958G	60.97	74.00	-13.03	30.74	3	Vertical	0	1.52	-
2480MHz	Pass	AV	2.48G	87.33	Inf	-Inf	30.68	3	Horizontal	33	1.08	-
2480MHz	Pass	AV	2.4962G	45.30	54.00	-8.70	30.74	3	Horizontal	33	1.08	-
2480MHz	Pass	PK	2.4798G	91.02	Inf	-Inf	30.68	3	Horizontal	33	1.08	-
2480MHz	Pass	PK	2.496G	59.64	74.00	-14.36	30.74	3	Horizontal	33	1.08	-
2480MHz	Pass	AV	4.95994G	34.11	54.00	-19.89	6.11	3	Vertical	328	2.30	-
2480MHz	Pass	PK	4.96024G	49.05	74.00	-24.95	6.11	3	Vertical	328	2.30	-
2480MHz	Pass	AV	4.96006G	33.73	54.00	-20.27	6.11	3	Horizontal	340	2.49	-
2480MHz	Pass	PK	4.96012G	48.51	74.00	-25.49	6.11	3	Horizontal	340	2.49	-

BT-LE(1Mbps)

2402MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.3872G	44.13	54.00	-9.87	30.37	3	Vertical	97	2.93	-
AV	2.402G	84.29	Inf	-Inf	30.41	3	Vertical	97	2.93	-
PK	2.387G	55.53	74.00	-18.47	30.37	3	Vertical	97	2.93	-
PK	2.402G	88.13	Inf	-Inf	30.41	3	Vertical	97	2.93	-

BT-LE(1Mbps)

2402MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.3852G	44.08	54.00	-9.92	30.36	3	Horizontal	36	1.17	-
AV	2.402G	87.61	Inf	-Inf	30.41	3	Horizontal	36	1.17	-
PK	2.3736G	57.87	74.00	-16.13	30.33	3	Horizontal	36	1.17	-
PK	2.402G	91.59	Inf	-Inf	30.41	3	Horizontal	36	1.17	-

BT-LE(1Mbps)

2402MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.80392G	37.69	54.00	-16.31	5.79	3	Vertical	191	1.02	-
PK	4.80352G	57.48	74.00	-16.52	5.78	3	Vertical	191	1.02	-

BT-LE(1Mbps)

2402MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.80394G	37.48	54.00	-16.52	5.79	3	Horizontal	87	2.22	-
PK	4.8035G	56.88	74.00	-17.12	5.78	3	Horizontal	87	2.22	-

BT-LE(1Mbps)

2440MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.382G	43.86	54.00	-10.14	30.35	3	Vertical	86	2.53	-
AV	2.44G	85.80	Inf	-Inf	30.55	3	Vertical	86	2.53	-
AV	2.496G	44.84	54.00	-9.16	30.74	3	Vertical	86	2.53	-
PK	2.389998G	55.24	74.00	-18.76	30.38	3	Vertical	86	2.53	-
PK	2.44G	89.65	Inf	-Inf	30.55	3	Vertical	86	2.53	-
PK	2.496G	59.50	74.00	-14.50	30.74	3	Vertical	86	2.53	-

BT-LE(1Mbps)

2440MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.3884G	43.98	54.00	-10.02	30.37	3	Horizontal	36	1.35	-
AV	2.44G	87.22	Inf	-Inf	30.55	3	Horizontal	36	1.35	-
AV	2.496G	44.69	54.00	-9.31	30.74	3	Horizontal	36	1.35	-
PK	2.376G	55.27	74.00	-18.73	30.33	3	Horizontal	36	1.35	-
PK	2.4396G	91.06	Inf	-Inf	30.55	3	Horizontal	36	1.35	-
PK	2.496G	58.65	74.00	-15.35	30.74	3	Horizontal	36	1.35	-

BT-LE(1Mbps)

2440MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.88002G	36.35	54.00	-17.65	5.95	3	Vertical	192	1.01	-
PK	4.87956G	53.16	74.00	-20.84	5.95	3	Vertical	192	1.01	-

BT-LE(1Mbps)

2440MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.88004G	35.28	54.00	-18.72	5.95	3	Horizontal	331	2.39	-
PK	4.87958G	51.23	74.00	-22.77	5.95	3	Horizontal	331	2.39	-

BT-LE(1Mbps)

2480MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.48G	87.09	Inf	-Inf	30.68	3	Vertical	0	1.52	-
AV	2.496G	45.92	54.00	-8.08	30.74	3	Vertical	0	1.52	-
PK	2.4802G	90.81	Inf	-Inf	30.68	3	Vertical	0	1.52	-
PK	2.4958G	60.97	74.00	-13.03	30.74	3	Vertical	0	1.52	-

BT-LE(1Mbps)

2480MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	2.48G	87.33	Inf	-Inf	30.68	3	Horizontal	33	1.08	-
AV	2.4962G	45.30	54.00	-8.70	30.74	3	Horizontal	33	1.08	-
PK	2.4798G	91.02	Inf	-Inf	30.68	3	Horizontal	33	1.08	-
PK	2.496G	59.64	74.00	-14.36	30.74	3	Horizontal	33	1.08	-

BT-LE(1Mbps)

2480MHz_TX

10/08/2018




Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.95994G	34.11	54.00	-19.89	6.11	3	Vertical	328	2.30	-
PK	4.96024G	49.05	74.00	-24.95	6.11	3	Vertical	328	2.30	-

BT-LE(1Mbps)

2480MHz_TX

10/08/2018



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
AV	4.96006G	33.73	54.00	-20.27	6.11	3	Horizontal	340	2.49	-
PK	4.96012G	48.51	74.00	-25.49	6.11	3	Horizontal	340	2.49	-