

APPLICATION CERTIFICATION FCC Part 15C

On Behalf of
Success Compu China Ltd.

Wireless mouse

Model No.: BL-M1018, BL-M1016, BL-M1028, BL-M1031, BL-M1041,
BL-M1058, BL-M1059, BL-M1061, BL-M1078, BL-M1088, BL-M1089,
BL-M1091, BL-M1092, BL-M1093, BL-M1094, BL-M1095, BL-M1096,
BL-M1098, BL-M1099, BL-M1106, BL-M1108, BL-M1116, BL-M1118,
BL-M1128, BL-M1131, BL-M1158, BL-M1161, BL-M1167, BL-M1168,
BL-M1178, BL-M1188, BL-M1199, BL-M1216, BL-M1218, BL-M1228,
BL-M1258, BL-M1259, BL-M1261, BL-M1291, BL-M1298, BL-M1558,
BL-M1825, BL-M1826, BL-M1828, BL-M1829

FCC ID: X95-BL-M1018

Prepared for : Success Compu China Ltd.
Address : 1st Building, Shuidou Laowei Village, Yousong,
Longhua Town, Bao'an district, Shenzhen City,
Guangdong Province, China
Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Chan Yuan New Material Port, Keyuan
Rd. Science & Industry Park, Nan Shan, Shenzhen,
Guangdong P.R. China

Tel: (0755) 26503290

Fax: (0755) 26503396

Report Number : ATE20152291
Date of Test : Oct 27, 2015-Nov 30, 2015
Date of Report : Nov 30, 2015

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT)	4
1.2. Special Accessory and Auxiliary Equipment	4
1.3. Description of Test Facility	5
1.4. Measurement Uncertainty	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
3. OPERATION OF EUT DURING TESTING	7
3.1. Operating Mode	7
3.2. Configuration and peripherals	7
4. TEST PROCEDURES AND RESULTS	8
5. 20DB BANDWIDTH MEASUREMENT	9
5.1. Block Diagram of Test Setup	9
5.2. The Requirement For Section 15.215(c)	9
5.3. Operating Condition of EUT	9
5.4. Test Procedure	9
5.5. Test Result	10
6. BAND EDGE COMPLIANCE TEST	12
6.1. Block Diagram of Test Setup	12
6.2. The Requirement For Section 15.249	12
6.3. EUT Configuration on Measurement	12
6.4. Operating Condition of EUT	12
6.5. Test Procedure	12
6.6. Test Result	13
7. RADIATED SPURIOUS EMISSION TEST	19
7.1. Block Diagram of Test Setup	19
7.2. The Limit For Section 15.249	20
7.3. Restricted bands of operation	21
7.4. Configuration of EUT on Measurement	21
7.5. Operating Condition of EUT	21
7.6. Test Procedure	22
7.7. The Field Strength of Radiation Emission Measurement Results	23
8. ANTENNA REQUIREMENT	35
8.1. The Requirement	35
8.2. Antenna Construction	35

Test Report Certification

Applicant& address : Success Compu China Ltd.
1st Building, Shuidou Laowei Village, Yousong,
Longhua Town, Bao'an district, Shenzhen City, Guangdong
Province, China

Manufacturer& address : Success Compu China Ltd.
1st Building, Shuidou Laowei Village, Yousong,
Longhua Town, Bao'an district, Shenzhen City, Guangdong
Province, China

Product : Wireless mouse

Model No. : BL-M1018

Trade name : N.A

Measurement Procedure Used:

FCC Rules and Regulations Part 15 Subpart C Section 15.249 ANSI C63.10: 2013

The EUT was tested according to FCC 47CFR 15.249 for compliance to FCC 47CFR 15.249 requirements

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.249 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.

Date of Test :

Oct 27, 2015-Nov 30, 2015

Date of Report :

Nov 30, 2015

Prepared by :



(Tim.zhang, Engineer)

Approved & Authorized Signer :



(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

The submitted sample is a wireless mouse.

The sample is powered by DC 3V (Powered by battery).

		wireless mouse
Model	:	BL-M1018, BL-M1016, BL-M1028, BL-M1031, BL-M1041, BL-M1058, BL-M1059, BL-M1061, BL-M1078, BL-M1088, BL-M1089, BL-M1091, BL-M1092, BL-M1093, BL-M1094, BL-M1095, BL-M1096, BL-M1098, BL-M1099, BL-M1106, BL-M1108, BL-M1116, BL-M1118, BL-M1128, BL-M1131, BL-M1158, BL-M1161, BL-M1167, BL-M1168, BL-M1178, BL-M1188, BL-M1199, BL-M1216, BL-M1218, BL-M1228, BL-M1258, BL-M1259, BL-M1261, BL-M1291, BL-M1298, BL-M1558, BL-M1825, BL-M1826, BL-M1828, BL-M1829
Frequency Range	:	2.405-2.470GHz
Channel frequency	:	2405MHz, 2413MHz, 2422MHz, 2430MHz, 2440MHz, 2450MHz, 2460MHz, 2470MHz,
Number of Channels	:	8
Modulation Type	:	MSK
Type of Antenna	:	PCB Antenna
Max antenna gain	:	-1 dBi
Power Supply	:	DC 3V(Powered by battery)

1.2. Special Accessory and Auxiliary Equipment

N/A

1.3. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee
for Laboratories
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO. LTD
Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

1.4. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 11, 2015	Jan. 10, 2016
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 11, 2015	Jan. 10, 2016
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 11, 2015	Jan. 10, 2016
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 11, 2015	Jan. 10, 2016
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2015	Jan. 14, 2016
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2015	Jan. 14, 2016
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2015	Jan. 14, 2016
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	Jan. 15, 2015	Jan. 14, 2016
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 11, 2015	Jan. 10, 2016
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 11, 2015	Jan. 10, 2016
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 11, 2015	Jan. 10, 2016
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 11, 2015	Jan. 10, 2016

3. OPERATION OF EUT DURING TESTING

3.1.Operating Mode


The mode is used: **Transmitting mode**

Low Channel: 2405MHz

Middle Channel: 2430MHz

High Channel: 2470MHz

3.2.Configuration and peripherals



4. TEST PROCEDURES AND RESULTS

FCC Rules	Description of Test	Result
Section 15.215(c)	20dB Bandwidth	Compliant
Section 15.249(d)	Band Edge Compliance Test	Compliant
Section 15.205(a), Section 15.209(a), Section 15.249, Section 15.35	Radiated Spurious Emission Test	Compliant
Section 15.207	AC Power Line Conducted Emission Test	N/A (note: The EUT is powered by battery, so this test does not apply)
Section 15.203	Antenna Requirement	Compliant

5. 20DB BANDWIDTH MEASUREMENT

5.1. Block Diagram of Test Setup



5.2. The Requirement For Section 15.215(c)

The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system RF bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The hopset shall be such that the near-term distribution of frequencies appears random, with sequential hops randomly distributed in both direction and magnitude of change in the hopset while the long-term distribution appears evenly distributed.

5.3. Operating Condition of EUT

5.3.1. Setup the EUT and simulator as shown as Section 5.1.

5.3.2. Turn on the power of all equipment.

5.3.3. Let the EUT work in TX modes measure it. The transmit frequency are 2405-2470MHz. We select 2405MHz, 2430MHz, and 2470MHz TX frequency to transmit.

5.4. Test Procedure

5.4.1. Place the EUT on the table and set it in transmitting mode.

5.4.2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

5.4.3. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz, Detector function=peak, Trace=max hold, Sweep=auto.


5.4.4. Set the measured low, middle and high frequency and test 20dB bandwidth with spectrum analyzer.

5.5. Test Result

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2405	0.436
Mid	2430	0.450
High	2470	0.450


The spectrum analyzer plots are attached as below.

Low channel




Date: 3.NOV.2015 09:39:17

Middle channel



Date: 3.NOV.2015 09:55:24


High channel



Date: 3.NOV.2015 10:06:02

6. BAND EDGE COMPLIANCE TEST

6.1. Block Diagram of Test Setup



6.2. The Requirement For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

6.3. EUT Configuration on Measurement

The equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.4. Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX modes measure it. The transmit frequency are 2405-2470 MHz. We select 2405MHz, 2470MHz TX frequency to transmit.

6.5. Test Procedure

Conducted Band Edge:

6.5.1. The transmitter output was connected to the spectrum analyzer via a low loss cable.

6.5.2. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz.

Radiate Band Edge:

6.5.3.The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.

6.5.4.The turntable was rotated for 360 degrees to determine the position of maximum emission level.

6.5.5.EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.

6.5.6.Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:


6.5.7.RBW=1MHz, VBW=1MHz

6.5.8.The band edges was measured and recorded.


6.6.Test Result

Pass

Channel	Frequency	Delta peak to band emission	Limit(dBc)
1	2373.76MHz	36.91	20
8	2502.86MHz	46.57	20



Date: 7.NOV.2015 09:36:16



Date: 7.NOV.2015 09:40:58

Radiated Band Edge Result



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #866

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2405MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Horizontal

Power Source: DC 3V


Date: 15/10/31/

Time: 16/03/16

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	41.75	-7.81	33.94	74.00	-40.06	peak			
2	2310.000	32.69	-7.81	24.88	54.00	-29.12	AVG			
3	2372.800	58.54	-7.64	50.90	74.00	-23.10	peak			
4	2372.800	49.78	-7.64	42.14	54.00	-11.86	AVG			
5	2390.000	43.52	-7.53	35.99	74.00	-38.01	peak			
6	2390.000	35.69	-7.53	28.16	54.00	-25.84	AVG			
7	2400.000	44.13	-7.46	36.67	74.00	-37.33	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #867
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 23 C / 48 %
EUT: wireless mouse
Mode: TX 2405MHz
Model: BL-M1018
Manufacturer: Success Compu China Ltd.

Polarization: Vertical
Power Source: DC 3V
Date: 15/10/31/
Time: 16/04/35
Engineer Signature:
Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2310.000	41.79	-7.81	33.98	74.00	-40.02	peak			
2	2310.000	33.10	-7.81	25.29	54.00	-28.71	AVG			
3	2390.000	42.28	-7.53	34.75	74.00	-39.25	peak			
4	2390.000	34.97	-7.53	27.44	54.00	-26.56	AVG			
5	2400.000	42.19	-7.46	34.73	74.00	-39.27	peak			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #869

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2470MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Horizontal

Power Source: DC 3V


Date: 15/10/31/

Time: 16/07/16

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	42.95	-7.37	35.58	74.00	-38.42	peak			
2	2483.500	33.00	-7.37	25.63	54.00	-28.37	AVG			
3	2500.000	42.49	-7.40	35.09	74.00	-38.91	peak			
4	2500.000	32.97	-7.40	25.57	54.00	-28.43	AVG			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #868

Standard: FCC PK

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2470MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Vertical

Power Source: DC 3V


Date: 15/10/31/

Time: 16/06/29

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2483.500	42.10	-7.37	34.73	74.00	-39.27	peak			
2	2483.500	33.47	-7.37	26.10	54.00	-27.90	AVG			
3	2500.000	42.38	-7.40	34.98	74.00	-39.02	peak			
4	2500.000	31.97	-7.40	24.57	54.00	-29.43	AVG			


Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss (if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
3. Display the measurement of peak values.

7. RADIATED SPURIOUS EMISSION TEST

7.1. Block Diagram of Test Setup

7.1.1. Block diagram of connection between the EUT and peripherals




Setup: Transmitting mode

7.1.2. Semi-Anechoic Chamber Test Setup Diagram


Below 1GHz

ANTENNA ELEVATION VARIES FROM 1 TO 4 METERS



Above 1GHz

ANTENNA ELEVATION VARIES FROM 1 TO 4 METERS



7.2.The Limit For Section 15.249

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph A8.4(4), the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

7.3.Restricted bands of operation

7.3.1.FCC Part 15.205 Restricted bands of operation

(a) Except as shown in paragraph (d) of this section, Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510

²Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emission appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000MHz, Compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

7.4.Configuration of EUT on Measurement

The equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.5.Operating Condition of EUT

7.5.1.Setup the EUT and simulator as shown as Section 7.1.

7.5.2.Turn on the power of all equipment.

7.5.3.Let the EUT work in TX modes measure it. The transmit frequency are

2405-2470 MHz. We select 2405MHz, 2430MHz, and 2470MHz TX frequency to transmit.

7.6. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground(Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground(Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

7.7.The Field Strength of Radiation Emission Measurement Results

PASS.

Note: 1. Emissions attenuated more than 20 dB below the permissible value are not reported.

2. *: Denotes restricted band of operation.

3. The EUT is tested radiation emission at Low, Middle, High channel in three axes. The worst emissions are reported in all channels.

4. The radiation emissions from 18-25GHz are not reported, because the test values lower than the limits of 20dB.



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 2# Chamber

Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: STAR2015 #858

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2405MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Horizontal

Power Source: DC 3V


Date: 15/10/31/

Time: 15/48/30

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	679.9600	25.11	-2.02	23.09	46.00	-22.91	QP			

Job No.: STAR2015 #859

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2405MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Vertical

Power Source: DC 3V


Date: 15/10/31/

Time: 15/49/02

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	863.0562	24.11	0.96	25.07	46.00	-20.93	QP			

Job No.: STAR2015 #857

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2430MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Horizontal

Power Source: DC 3V


Date: 15/10/31/

Time: 15/47/35

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	804.6028	24.01	0.11	24.12	46.00	-21.88	QP			

Job No.: STAR2015 #856

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2430MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Vertical

Power Source: DC 3V


Date: 15/10/31/

Time: 15/46/24

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	31.2893	27.66	-9.31	18.35	40.00	-21.65	QP			

Job No.: STAR2015 #854

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2470MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Horizontal

Power Source: DC 3V


Date: 15/10/31/

Time: 15/44/45

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	734.4913	25.10	-1.29	23.81	46.00	-22.19	QP			

Job No.: STAR2015 #855

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 23 C / 48 %

EUT: wireless mouse

Mode: TX 2470MHz

Model: BL-M1018

Manufacturer: Success Compu China Ltd.

Polarization: Vertical

Power Source: DC 3V


Date: 15/10/31/

Time: 15/45/45

Engineer Signature:

Distance: 3m

Note: Report NO.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	701.7609	24.87	-1.72	23.15	46.00	-22.85	QP			



ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Report No.: ATE20152291

Page 29 of 35

Site: 1# Chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396

Job No.: star2015 #2147
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Wireless mouse
Mode: TX 2405MHz
Model: BL-M1018
Manufacturer: Success

Polarization: Horizontal
Power Source: DC 3V
Date: 2015/11/20
Time: 15:48:45
Engineer Signature: star
Distance: 3m

Note: Report No.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2405.000	96.18	-8.00	88.18	114.00	25.82	peak			
2	2405.000	92.90	-8.00	84.90	94.00	9.10	AVG			
3	4810.000	57.41	-2.48	54.93	74.00	19.07	peak			
4	4810.000	54.70	-2.48	52.22	54.00	1.78	AVG			

Job No.: star2015 #2146

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Wireless mouse

Mode: TX 2405MHz

Model: BL-M1018

Manufacturer: Success

Polarization: Vertical

Power Source: DC 3V


Date: 2015/11/20

Time: 15:47:46

Engineer Signature: star

Distance: 3m

Note: Report No.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2405.000	94.48	-8.00	86.48	114.00	27.52	peak			
2	2405.000	91.29	-8.00	83.29	94.00	10.71	AVG			
3	4810.000	56.64	-2.48	54.16	74.00	19.84	peak			
4	4810.000	53.60	-2.48	51.12	54.00	2.88	AVG			

Job No.: star2015 #2144

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Wireless mouse

Mode: TX 2430MHz

Model: BL-M1018

Manufacturer: Success

Polarization: Horizontal

Power Source: DC 3V


Date: 2015/11/20

Time: 15:45:21

Engineer Signature: star

Distance: 3m

Note: Report No.:ATE20152291




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2430.000	93.68	-7.96	85.72	114.00	28.28	peak			
2	2430.000	90.10	-7.96	82.14	94.00	11.86	AVG			
3	4860.000	57.28	-2.30	54.98	74.00	19.02	peak			
4	4860.000	54.60	-2.30	52.30	54.00	1.70	AVG			

Job No.: star2015 #2145
Standard: FCC Class B 3M Radiated
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: Wireless mouse
Mode: TX 2430MHz
Model: BL-M1018
Manufacturer: Success

Polarization: Vertical
Power Source: DC 3V
Date: 2015/11/20
Time: 15:46:31
Engineer Signature: star
Distance: 3m

Note: Report No.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2430.000	91.72	-7.96	83.76	114.00	30.24	peak			
2	2430.000	89.10	-7.96	81.14	94.00	12.86	AVG			
3	4860.000	55.99	-2.30	53.69	74.00	20.31	peak			
4	4860.000	52.69	-2.30	50.39	54.00	3.61	AVG			

Job No.: star2015 #2143

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Wireless mouse

Mode: TX 2470MHz

Model: BL-M1018

Manufacturer: Success

Polarization: Horizontal

Power Source: DC 3V


Date: 2015/11/20

Time: 15:42:01

Engineer Signature: star

Distance: 3m

Note: Report No.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2470.000	94.95	-7.86	87.09	114.00	26.91	peak			
2	2470.000	91.78	-7.86	83.92	94.00	10.08	AVG			
3	4940.000	56.79	-2.02	54.77	74.00	19.23	peak			
4	4940.000	54.00	-2.02	51.98	54.00	2.02	AVG			

Job No.: star2015 #2142

Standard: FCC Class B 3M Radiated

Test item: Radiation Test

Temp.(C)/Hum.(%) 25 C / 55 %

EUT: Wireless mouse

Mode: TX 2470MHz

Model: BL-M1018

Manufacturer: Success

Polarization: Vertical

Power Source: DC 3V


Date: 2015/11/20

Time: 15:39:21

Engineer Signature: star

Distance: 3m

Note: Report No.:ATE20152291



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	2470.000	93.38	-7.86	85.52	114.00	28.48	peak			
2	2470.000	90.26	-7.86	82.40	94.00	11.60	AVG			
3	4940.000	55.53	-2.02	53.51	74.00	20.49	peak			
4	4940.000	52.67	-2.02	50.65	54.00	3.35	AVG			


8. ANTENNA REQUIREMENT

8.1.The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2.Antenna Construction

Device is equipped with unique antenna, which isn't displaced by other antenna. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna