

Bâtiment le Ponant Avenue de la PEROUSE 29280 PLOUZANÉ France

Tél.: 02.98.05.13.34 Fax.: 02.98.05.53.87 sar@antennessa.com

CALIBRATION REPORT

VALIDATION DIPOLE

1900 MHz

DATE: 21/09/2007

REFERENCE: SN 01/06 DIP G 35

OBJECT: COMOSAR IEEE REF DIPOLE

MANUFACTURER: ANTENNESSA

SERIAL NUMBER: SN 01/06 DIP G 35

CUSTOMER: CCS

DATE OF CALIBRATION: 19/09/2007

WARRANTY:

This Calibration certificate may not be reproduced other than in full. Calibration certificates without signature and seal are not valid. This documentation contains property information which is protected by copyright. All right are reserved. No part of this document may be photocopied, reproduced without the prior written agreement of ANTENNESSA. ANTENNESSA shall not be liable for errors contained herein or for incidental or consequential in connection with the furnishing, performance or use of this material. Warranty doesn't apply to Normal wear, Normal tear, Improper use, Improper maintain, Improper installation.

Date

2 5 OCT. 2007

SEAL

ANTENNESSA
Bâtiment PONANT
Ave La Pérouse
Zone du Technopôle Brest Iroïse
29280 PLOUZANE
Tél. (33) 02-98 05 13 34 - Fax (33) 02-98 05 53 87

COMOSAR PROJECT MANAGER



Bâtiment le Ponant Avenue de la PEROUSE 29280 PLOUZANÉ France


Tél.: 02.98.05.13.34 Fax.: 02.98.05.53.87 sar@antennessa.com

CALIBRATION REPORT

VALIDATION DIPOLE

1900 MHz

PRODUCT DESCRIPTION




CALIBRATION TEST EQUIPMENT

TYPE	IDENTIFICATION
Vector Network Analyzer	HP8753D

MEASUREMENT PROCEDURE

We placed the dipole as define in IEEE1528-2005 SAR standard:





Bâtiment le Ponant Avenue de la PEROUSE 29280 PLOUZANÉ France

Tél.: 02.98.05.13.34 Fax.: 02.98.05.53.87 sar@antennessa.com

CALIBRATION REPORT

VALIDATION DIPOLE

1900 MHz

RETURN LOSS MEASUREMENT RESULTS




Figure 1: Return Loss in Head Liquid




Figure 2 : Return Loss in Body Liquid

VSWR at 1900 MHz in HL: 1.051:1 VSWR at 1900 MHz in BL: 1.157:1



Bâtiment le Ponant Avenue de la PEROUSE 29280 PLOUZANÉ France Tél.: 02.98.05.13.34

Fax.: 02.98.05.53.87 sar@antennessa.com

CALIBRATION REPORT

VALIDATION DIPOLE

1900 MHz

SAR MEASUREMENT EQUIPEMENT

PC	Dell (Pentium IV 2.4GHz, SN:X10-23533)	
Voltmeter	Keithley (2000, SN:1000572)	
Synthetizer	Rohde&Schwarz (SML_03, SN:101868)	
Amplifier	Nuclétudes (ALB216, SN:10800)	
Power Meter	Rohde&Schwarz (NRVD, SN:101066)	
Probe	Antennessa (SN:EP37)	
Phantom	Antennessa (SN: SN_20_07_SAM42)	
	Antennessa (Last Calibration: 17 09 07)	
Liquid	Head Liquid Values: eps' : 39,93 sigma : 1,377	
	Boby Liquid Values: eps' : 51,34 sigma : 1,574	
Sotfware	OpenSAR V3	

SAR MEASUREMENT RESULT

	10g	1g
SAR measured Liquid : HL Input power : 1W	20.358 W/Kg - 0,69%	38,248 W/Kg - 3,66%
SAR measured Liquid : BL Input power : 1W	20.110 W/Kg - 1,90%	37,746 W/Kg - 4,92%