High Frequency Ceramic Solutions

868MHz AntennaDetail Specification: 06/06/07 Page 1 of 3

General Specifications


Part Number	0868AT43A0020
Frequency Range	858 - 878 Mhz
Peak Gain	-1.0 dBi typ. (XZ-total)
Average Gain	-4.0 dBi typ. (XZ-total)
Return Loss	9.5 dB min.

Input Power	3W max.
Impedance	50 Ω
Operating Temperature	-40 to +85°C
Reel Quanity	1,000
MSL	2


No.	Function	Terminal Configuration
1	Feeding Point	
2	NC	2 1

Mechanical Dimensions

	In	mm
L	0.276 ± 0.008	7.00 ± 0.20
W	0.079 ± 0.008	2.00 ± 0.20
Т	0.031 +.004/008	0.80 +0.1/-0.2
а	0.020 ± 0.012	0.50 ± 0.30



Mounting Considerations



Johanson Technology, Inc. reserves the right to make design changes without notice. All sales are subject to Johanson Technology, Inc. terms and conditions.



High Frequency Ceramic Solutions

 868MHz Antenna
 P/N 0868AT43A0020

 Detail Specification: 06/06/07
 Page 2 of 3

Mounting Considerations Test Board 9.5mm 40mm 50Ω Feed Line 20mm Antenna Ground No Ground **Return Loss (with matching)** 0 -5 freq=858.0MHz dB(S(1,1))=-14.504 dB(S(1,1)) -10 m2 freq=878.0MHz mrn2 dB(S(1,1))=-14.301 -15 m3 freq=868.0MHz dB(S(1,1))=-23.116 -20 ŋβ -25 0.7 0.6 0.8 0.9 1.0 1.1 1.2 0.5 1.3 freq, GHz


Johanson Technology, Inc. reserves the right to make design changes without notice. All sales are subject to Johanson Technology, Inc. terms and conditions.



High Frequency Ceramic Solutions

868MHz Antenna P/N 0868AT43A0020

Detail Specification: 06/06/07 Page 3 or 3



Johanson Technology, Inc. reserves the right to make design changes without notice. All sales are subject to Johanson Technology, Inc. terms and conditions.

