# Sunny World (HK) Limited

Rm 302~306, Hewlett Ctr, 54 Hoi Yuen Rd, Kwun Tong, Kowloon, HK Tel (852) 2345 2772 Fax (852) 2357 4860



## **User Manual**

Dear Customer, Thank you for buying Sunny World (HK) Limited Energy Saving Lamp. Please read carefully the product instruction before using!

The model of EF-15W/FD, use only on 120 volt, 60Hz circuit. The wattage marked on the lamp. And the operating Frequency is More than 50KHz and less than 80KHz

### **Features**

Energy Saves up to 80% compared to common incandescent Lamps

Long lamp life, average 9 years

High Lumens efficiency;

Rapid on/off with silent operation;

Reduces Carbon Dioxide Electromagnetic Volume

Consumes natural resources

Generate less heat in the building

#### **Note & Attention**

Always turn-off power before re-lamping;

Avoid installing lamp by gripping the glass tube;

Do not use with electronic timers

Reliable operating temperature -18 ~50

Not suitable for damp surroundings or sealed occasions

Risk of electric shock-use in dry locations

For best result use in proper voltage range as mentioned on lamp base

Applications:

Home, Office, Hotel, Shop, Restaurant...and so on lighting

#### Warnning:

The users manual or instruction manual for an intentional or unintentional radiator shall caution

the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

#### **FCC Information**

- 1. This device complies with Part 18 of the FCC Rules.
- 2 . Information on the following matters shall be provided to the user in the Instruction manual:
- (a) The interference potential of the device or system;
- (b) Maintenance of the system;
- (c) Simple measures that can be taken by the user to correct interference;
- (d) Manufacturers of RF lighting devices must provide an advisory statement, either on the product packaging or with other user documentation, similar to the following: This product

may cause interference to radio equipment and should not be installed near maritime safety communications equipment or other critical navigation or communication equipment operating is in between 50KHz and 80KHz. Variations of this language are permitted provided all the points of the statement are addressed and may be presented in any legible font or text style.