



NVLAP LAB CODE 200707-0



FCC PART 22 H/24 E
MEASUREMENT AND TEST REPORT

For

Xiamen Youthnet Co., Ltd.

7/F, No. 56, Guanri Road, Software Park II,

Xiamen, China 361009

FCC ID: XCM-5AJ07

Report Type: Original Report	Product Type: GSM Remote Camera
Test Engineer: Cookies Bu <i>Cookies Bu</i>	
Report Number: RXM09052151	
Report Date: 2009-07-10	
Merry Zhao <i>Merry Zhao</i>	
Reviewed By: EMC Engineer	
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, NIST, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "*" (Rev.2)

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
EUT PHOTO	4
OBJECTIVE	5
RELATED SUBMITTAL(S)/GRANT(S).....	5
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	6
CONFIGURATION OF TEST SETUP	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
§1.1307 & §2.1091 - RF EXPOSURE.....	9
APPLICABLE STANDARD	9
TEST DATA	9
§2.1047 - MODULATION CHARACTERISTIC	11
§ 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	12
APPLICABLE STANDARD	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA	13
§2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH	22
APPLICABLE STANDARDS.....	22
TEST PROCEDURE	22
TEST EQUIPMENT LIST AND DETAILS.....	22
TEST DATA	23
§2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS	26
APPLICABLE STANDARDS.....	26
TEST PROCEDURE	26
TEST EQUIPMENT LIST AND DETAILS.....	26
TEST DATA	26
§2.1053, §22.917& §24.238 - SPURIOUS RADIATED EMISSIONS	33
APPLICABLE STANDARDS.....	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	34
§22.917(A) & §24.238(A) - BAND EDGES.....	36
APPLICABLE STANDARDS.....	36
TEST PROCEDURE	36

TEST EQUIPMENT LIST AND DETAILS.....36

TEST DATA36

§2.1055, §22.355 & §24.235 - FREQUENCY STABILITY42

APPLICABLE STANDARD42

TEST PROCEDURE42

TEST EQUIPMENT LIST AND DETAILS.....43

TEST DATA43

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The *Xiamen Youthnet Co., Ltd.*'s product, model number: *V900 (FCC ID: XCM-5AJ07)* or the "EUT" as referred to in this report is a *GSM Remote Camera*, which measures approximately: 13.0 cm L x 8.5 cm W x 3.5 cm H, rated input voltage: DC 3.7V battery.

Frequency Range:

Cellular Band: 824-849 MHz (TX), 869-894 MHz (RX)

PCS Band: 1850-1910 MHz (TX), 1930-1990 MHz (RX)

Modulation Mode: GMSK

Transmitter Output Power:

Cellular Band: 33±2 dBm

PCS Band: 30±2 dBm

** All measurement and test data in this report was gathered from production sample serial number: 0905007(Assigned by BACL, ShenZhen). The EUT was received on 2009-05-21.*

EUT Photo



Please see additional photos in Exhibit B&C

Objective

This type approval report is prepared on behalf of *Xiamen Youthnet Co., Ltd.* in accordance with Part 2, Subpart J, Part 22 Subpart H, and Part 24 Subpart E of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, band edge and radiated margin.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services
Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-C, ANSI C63.4-2003.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on November 21, 2007. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



NVLAP LAB CODE 200707-0

The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-C.

The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modifications were made to the EUT.


Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
Youthnet	REMOTE CONTROL	V900	N/A	XCM-5AJ0701

Configuration of Test Setup



Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1091	RF Exposure (MPE)	Compliant
§2.1046, § 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 2.1047	Modulation Characteristics	N/A
§ 2.1049, § 22.905 § 22.917, § 24.238	99% & -26 dB Occupied Bandwidth	Compliant
§ 2.1051, § 22.917 (a), § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§ 2.1053 § 22.917 (a), § 24.238 (a)	Field Strength of Spurious Radiation	Compliant
§ 22.917 (a), § 24.238 (a)	Out of band emission, Band Edge	Compliant
§ 2.1055 § 22.355, § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliant

§1.1307 & §2.1091 - RF EXPOSURE

Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Test Data

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to antenna

G = Antenna Gain

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Cellular Band (Part 22H)

Maximum peak output power at antenna input terminal (dBm): 31.82
Maximum peak output power at antenna input terminal (mW): 1520.547
Prediction distance (cm): 20
Prediction frequency (MHz): 848.8
Antenna Gain, typical (dBi): 1.58
Maximum Antenna Gain (numeric): 1.4388

The worst case is power density at predication frequency at 20 cm (mW/cm²): 0.435
MPE limit for general population exposure at prediction frequency (mW/cm²): 0.565

PCS Band (Part 24E)

Maximum peak output power at antenna input terminal (dBm): 29.81
Maximum peak output power at antenna input terminal (mW): 957.194
Prediction distance (cm): 20
Prediction frequency (MHz): 1850.2
Antenna Gain, typical (dBi): 2.5
Maximum Antenna Gain (numeric): 1.7783

The worst case is power density at predication frequency at 20 cm (mW/cm²): 0.3388
MPE limit for general population exposure at prediction frequency (mW/cm²): 1.0

Conclusion:

For GSM850, the highest power density level at 20 cm is 0.435 mW/cm², which is below the uncontrolled exposure limit of 0.565 mW/cm² at 848.8 MHz.

For PCS1900, the highest power density level at 20 cm is 0.3388 mW/cm², which is below the uncontrolled exposure limit of 1.0 mW/cm² at 1850.2 MHz.

The 20 cm safety distance has been addressed in the user manual.

§2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

§ 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), in no case may the peak output power of a base station transmitter exceed 2 watt EIRP.

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-C section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2008-09-25	2009-09-25
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2009-03-11	2010-03-11
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2008-08-28	2009-08-27
HP	Preamplifier	8449B	3008A00277	2008-09-12	2009-09-11
HP	Signal Generator	HP8657A	2849U00982	2008-10-16	2009-10-15
HP	Amplifier	HP8447D	2944A09795	2008-08-02	2009-08-02
HP	Synthesized Sweeper	8341B	2624A00116	2008-11-07	2009-11-06
COM POWER	Dipole Antenna	AD-100	041000	2008-09-25	2009-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2009-05-17	2010-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2009-05-09	2010-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Cookies Bu on 2009-06-25 to 2009-07-07.

Conducted Power

Cellular Band (Part 22H)

Mode	Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
GSM	Low	824.2	31.67	38.45
	Middle	836.6	31.73	38.45
	High	848.8	31.71	38.45
GRPS	Low	824.2	31.74	38.45
	Middle	836.6	31.79	38.45
	High	848.8	31.82	38.45

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Output Power (dBm)	Limit (dBm)
GSM	Low	1850.2	29.26	33
	Middle	1880.0	28.77	33
	High	1909.8	28.42	33
GRPS	Low	1850.2	29.81	33
	Middle	1880.0	29.45	33
	High	1909.8	29.09	33

Radiated Power (ERP and EIRP)**Cellular Band (Part 22H)**

GSM:

Indicated		Table Angle Degree	Test Antenna		Substituted					Absolute Level (dBm)	Part 22H
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Ant. Gain (dBi)	Cable Loss (dB)		Limit (dBm)
Low Channel											
824.2	118.37	250	1.0	H	824.2	28.98	H	0	0.9	28.08	38.45
824.2	119.40	359	1.52	V	824.2	30.43	V	0	0.9	29.53	38.45
Middle Channel											
836.6	118.6	185	1.53	H	836.6	29.12	H	0	0.9	28.22	38.45
836.6	119.68	197	1.42	V	836.6	30.72	V	0	0.9	29.82	38.45
High Channel											
848.8	118.42	160	1.0	H	848.8	29.03	H	0	0.9	28.13	38.45
848.8	119.53	167	1.10	V	848.8	30.51	V	0	0.9	29.61	38.45

GPRS:

Indicated		Table Angle Degree	Test Antenna		Substituted					Absolute Level (dBm)	Part 22H
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Ant. Gain (dBi)	Cable Loss (dB)		Limit (dBm)
Low Channel											
824.2	118.39	56	1.1	H	824.2	28.98	H	0	0.9	28.08	38.45
824.2	119.48	177	1.0	V	824.2	30.46	V	0	0.9	29.56	38.45
Middle Channel											
836.6	118.66	37	1.51	H	836.6	29.19	H	0	0.9	28.29	38.45
836.6	119.69	360	1.45	V	836.6	30.73	V	0	0.9	29.83	38.45
High Channel											
848.8	118.43	229	1.31	H	848.8	29.02	H	0	0.9	28.12	38.45
848.8	119.75	186	1.30	V	848.8	30.78	V	0	0.9	29.88	38.45

PCS Band (Part 24E)

GSM:

Indicated		Table Angle Degree	Test Antenna		Substituted					Absolute Level (dBm)	Part 24E
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Ant. Gain (dBi)	Cable Loss (dB)		Limit (dBm)
Low Channel											
1850.2	117.40	30	1.00	H	1850.2	16.22	H	6.2	1.02	21.40	33
1850.2	124.60	239	1.89	V	1850.2	24.75	V	6.2	1.02	29.93	33
Middle Channel											
1880.2	115.44	84	1.54	H	1880.2	14.26	H	6.2	1.03	19.43	33
1880.2	123.79	274	1.58	V	1880.2	23.82	V	6.2	1.03	28.99	33
High Channel											
1909.8	115.72	317	1.62	H	1909.8	14.59	H	6.2	1.03	19.76	33
1909.8	122.54	274	1.00	V	1909.8	22.59	V	6.2	1.03	27.76	33


GPRS:

Indicated		Table Angle Degree	Test Antenna		Substituted					Absolute Level (dBm)	Part 24E
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	S.G. Level (dBm)	Ant. Polar (H/V)	Ant. Gain (dBi)	Cable Loss (dB)		Limit (dBm)
Low Channel											
1850.2	116.28	329	1.0	H	1850.2	15.14	H	6.2	1.02	20.32	33
1850.2	124.89	281	1.0	V	1850.2	25.02	V	6.2	1.02	30.20	33
Middle Channel											
1880.2	117.29	154	1.1	H	1880.2	16.15	H	6.2	1.03	21.32	33
1880.2	124.55	282	1.0	V	1880.2	24.51	V	6.2	1.03	29.68	33
High Channel											
1909.8	116.02	327	1.9	H	1909.8	14.89	H	6.2	1.03	20.06	33
1909.8	124.15	281	1.0	V	1909.8	24.12	V	6.2	1.03	29.29	33


Plots of Conducted Output Power

Cellular Band (Part 22H)


Low Channel (GSM)




Middle Channel (GSM)




High Channel (GSM)




Low Channel (GPRS)



Middle Channel (GPRS)




High Channel (GPRS)




PCS Band (Part 24E)


Low Channel (GSM)




Middle Channel (GSM)




High Channel (GSM)




Low Channel (GPRS)



Middle Channel (GPRS)



High Channel (GPRS)




§2.1049, §22.917, §22.905 & §24.238 - OCCUPIED BANDWIDTH**Applicable Standards**

CFR 47 §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 30 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2008-11-07	2009-10-16
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2009-05-09	2010-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56%
ATM Pressure:	100.0kPa

The testing was performed by Cookies Bu on 2009-06-27.

Cellular Band (Part 22H)

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Occupied Bandwidth (kHz)
190	836.6	252	336


PCS Band (Part 24E)

Channel	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Occupied Bandwidth (kHz)
661	1880.0	252	334

Please refer to the following plots.


Cellular Band (Part 22H)

99% Occupied Bandwidth



Date: 27.JUN.2009 11:25:17


26 dB Occupied Bandwidth



Date: 27.JUN.2009 11:23:21


PCS Band (Part 24E)

99% Occupied Bandwidth



Date: 27.JUN.2009 11:47:08

26 dB Occupied Bandwidth



Date: 27.JUN.2009 11:46:34

§2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standards

CFR 47 §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 100 kHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2008-08-28	2009-08-27
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2009-05-09	2010-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions


Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Cookies Bu on 2009-06-27.

Please refer to the following plots.


Cellular Band (Part 22H)

30 – 1000 MHz - Middle Channel (GSM)




Date: 27.JUN.2009 16:31:36

1 – 4 GHz - Middle Channel (GSM)




Date: 27.JUN.2009 14:00:18

4 – 10 GHz - Middle Channel (GSM)



PCS Band (Part24E)

30 – 1000 MHz - Middle Channel (GSM)



Offset 4.0 dB

Ref 34.8 dBm * Att 50 dB

* RBW 1 MHz * VBW 3 MHz * SWT 5 ms

Marker 1 [T1] -30.50 dBm 1.436000000 GHz


1 PK MAXH

D1 -13 dBm


1

Start 1 GHz 100 MHz / Stop 2 GHz


2 – 20 GHz - Middle Channel (GSM)




Date: 27.JUN.2009 11:08:16

Cellular Band (Part22H)**30 – 1000 MHz - Middle Channel (GPRS)**

Date: 27.JUN.2009 16:36:00


1 – 4GHz - Middle Channel (GPRS)

4 – 10 GHz - Middle Channel (GPRS)




PCS Band (Part24E)

30 – 1000 MHz - Middle Channel (GPRS)




1 – 2 GHz - Middle Channel (GPRS)



Date: 27.JUN.2009 16:43:20

2 – 20 GHz - Middle Channel (GPRS)



Date: 27.JUN.2009 11:17:44

§2.1053, §22.917& §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standards

CFR 47 § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = 43 + 10 Log₁₀ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2008-09-25	2009-09-25
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2009-03-11	2010-03-11
Rohde & Schwarz	Spectrum Analyzer	FSEM30	849720/019	2008-08-28	2009-08-27
HP	Preamplifier	8449B	3008A00277	2008-09-12	2009-09-11
HP	Signal Generator	HP8657A	2849U00982	2008-10-16	2009-10-15
HP	Amplifier	HP8447D	2944A09795	2008-08-02	2009-08-02
HP	Synthesized Sweeper	8341B	2624A00116	2008-11-07	2009-11-06
COM POWER	Dipole Antenna	AD-100	041000	2008-09-25	2009-09-25
A.H. System	Horn Antenna	SAS-200/571	135	2009-05-17	2010-05-17
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2009-05-09	2010-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Cookies Bu on 2009-06-27.

Test mode: Transmitting

Below 1 GHz:**Cellular Band (Part 22H)**

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	FCC Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel											
110.83	36.80	235	1.0	V	110.83	-61.32	0	0.62	-61.94	-13	48.94
139.46	36.52	159	1.5	V	139.46	-61.31	0	0.65	-61.96	-13	48.96
635.72	30.33	70	1.5	H	635.72	-66.31	0	1.33	-67.64	-13	54.64
110.82	30.00	126	1.2	H	110.82	-67.12	0	0.62	-67.74	-13	54.74

PCS Band (Part 24E)

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	FCC Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel											
990.30	43.62	70	1.3	H	990.30	-53.62	0	1.77	-55.39	-13	42.39
146.40	35.09	260	1.5	V	146.40	-61.46	0	0.66	-62.12	-13	49.12
990.30	35.64	210	1.0	V	990.30	-62.53	0	1.77	-64.30	-13	51.30
332.64	31.26	150	1.5	H	332.64	-65.31	0	0.96	-66.27	-13	53.27

Above 1 GHz:**Cellular Band (Part 22H)**

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	FCC Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel											
4881.7	46.08	150	1.4	H	4881.7	-48.36	8.3	2.21	-42.27	-13	29.27
2509.8	45.32	210	1.6	V	2509.8	-48.85	7.3	1.19	-42.74	-13	29.74
2767.5	46.37	130	1.6	V	2767.5	-53.21	7.3	1.22	-47.13	-13	34.13
1673.2	47.61	220	1.3	H	1673.2	-52.53	6.2	0.94	-47.27	-13	34.27
2509.8	47.14	130	1.5	H	2509.8	-54.66	7.3	1.19	-48.55	-13	35.55
1673.2	52.79	100	1.9	V	1673.2	-54.63	6.2	0.94	-49.37	-13	36.37

PCS Band (Part 24E)

Indicated		Table Angle Degree	Test Antenna		Substituted				Absolute Level (dBm)	FCC Limit (dBm)	Margin (dB)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Frequency (MHz)	Level (dBm)	Ant. Gain (dBi)	Cable Loss (dB)			
Middle Channel											
1949.8	54.83	122	1.0	V	7520	-42.51	6.3	0.95	-37.16	-13	24.16
3188.4	47.10	231	1.5	H	7520	-50.51	6.9	1.36	-44.97	-13	31.97
5640	46.35	110	1.5	V	5640	-55.67	8.3	1.76	-49.13	-13	36.13
5640	45.61	98	1.6	H	5640	-56.56	8.3	1.76	-50.02	-13	37.02
3760	46.54	256	1.9	H	3760	-56.82	6.9	1.47	-51.39	-13	38.39
3760	46.33	132	1.1	V	3760	-59.35	6.9	1.47	-53.92	-13	40.92

§22.917(a) & §24.238(a) - BAND EDGES

Applicable Standards


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency, RBW set to 10 kHz.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100224	2008-11-07	2009-11-06
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2009-05-09	2010-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Cookies Bu on 2009-06-26 to 2009-07-07.

Please refer to the following tables and plots.


Cellular Band (Part 22H)

Mode	Frequency (MHz)	Emission (dBm)	Limit (dBm)
GSM	824	-16.95	-13
	849	-13.65	-13
GPRS	824	-14.40	-13
	849	-14.74	-13

PCS Band (Part 24E)


Mode	Frequency (MHz)	Emission (dBm)	Limit (dBm)
GSM	1850	-14.52	-13
	1910	-15.05	-13
GPRS	1850	-13.80	-13
	1910	-16.16	-13

Cellular Band, Lowest Channel (GSM)




Date: 7.JUL.2009 13:35:17

Cellular Band, Highest Channel (GSM)




Date: 26.JUN.2009 19:48:09

Cellular Band, Lowest Channel (GPRS)




Date: 26.JUN.2009 19:01:33

Cellular Band, Highest Channel (GPRS)




Date: 26.JUN.2009 19:09:19

PCS Band, Lowest Channel (GSM)




Date: 26.JUN.2009 19:50:46

PCS Band, Highest Channel (GSM)




Date: 26.JUN.2009 19:51:57

PCS Band, Lowest Channel (GPRS)



Date: 26.JUN.2009 19:24:04

PCS Band, Highest Channel (GPRS)



Date: 27.JUN.2009 12:22:35

§2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

CFR47 § 2.1055 (a), § 2.1055 (d), §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: An external variable DC power supply was connected to the battery terminals of the equipment under test. The voltage was set to 115% of the nominal value and was then decreased until the transmitter light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
WUHUAN	Temperature & Humidity Chamber	HTP205	20021115	2009-05-09	2010-05-09
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	109038	2009-05-09	2010-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to the NIST.

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Cookies Bu on 2009-07-07.

Cellular Band (Part 22H)

Middle Channel, fo = 836.6 MHz				
Test Environment		Frequency Error		Limit (ppm)
Temperature (°C)	Power Supplied (Vdc)	(Hz)	(ppm)	
-30	3.70	-22	-0.02630	2.5
-20	3.70	-23	-0.02749	2.5
-10	3.70	-23	-0.02749	2.5
0	3.70	-31	-0.03705	2.5
10	3.70	-26	-0.03108	2.5
20	3.70	-29	-0.03466	2.5
30	3.70	-32	-0.03825	2.5
40	3.70	-49	-0.05857	2.5
50	3.70	-48	-0.05738	2.5
25	3.50	-30	-0.03586	2.5

PCS Band (Part 24E)

Middle Channel, fo = 1880.0 MHz				
Test Environment		Frequency Error		Limit (ppm)
Temperature (°C)	Power Supplied (Vdc)	(Hz)	(ppm)	
-30	3.70	-24	-0.01277	2.5
-20	3.70	-26	-0.01383	2.5
-10	3.70	-19	-0.01011	2.5
0	3.70	-16	-0.00851	2.5
10	3.70	-29	-0.01543	2.5
20	3.70	-23	-0.01223	2.5
30	3.70	-31	-0.01649	2.5
40	3.70	-45	-0.02394	2.5
50	3.70	-48	-0.02553	2.5
25	3.50	-32	-0.01702	2.5

***** END OF REPORT *****