L		Part, Type	Designator	Footprint	Qty	Manufacturer
0						
2	Media Chair Transmitter Main BOARD					
3	Main BOARD SMT					
PCB	Main BOARD OWN					
4	Main Board PCB	VC1.0 FR-4 100*140mm			1	
DIODES	DIODE SCHOTTKY	MBR0560-TP	D16	SOD-123	1	Micro Commercial
4	Switch Diode	BAT54S, SOT23	D7, D8, D9, D10, D11, D12, D13, D14	SOT-23	8	PHILIPS
4	Surface Mount Rectifier	M2A	D15	SMA	1	HY
4	Switch Diode	1SS352	D1, D2, D3, D4, D5, D6	SOD-323	6	TOSHIBA
Transis	stors					
		ADMOSONO COTOS Terr	M4 MO	COT22/ECD/4 2V4 2	0	ANDEC
4	P-CH MOSFET	APM2301CAC, SOT23, Tape	M1, M2	SOT23/ECB/1.3X1.3	2	ANPEC
4	Transistor	MMBT3904	Q5	SOT23	1	Vishay/ONSEMI
IC						
4	Buffer	NC7NZ34K8X	U1	US8	1	FAIRCHILD
4	Buffer	NC7SZ125M5X	U2	SOT23-5	1	FAIRCHILD
4	MCU	PIC18F26K20-I/SS	U4	SSOP-28	1	MICROCHIP
4	Audio decoder Digital Audio Receiver	NJU26501FS1 CS8416-CZZ	U6 U7	QFP-52	1	NJRC
4	ADC	WM8775SEDS/V	U8	TSSOP28 SSOP-28	1	Cirrus Logic WOLFSON
4	LIP-SYNC Delay	TPA5051RSAR	U13, U14	QFN-16	2	TI
4	Asynchronous Sample Rate	AK4121VF	U15, U16, U17	TSSOP-24	3	AKM
	Converter		· · ·			
4	Regulator DC-DC	AMS1117-3.3 TPS54331D	U19 U20	SOT-223 SO-8	1	AMS TI
4	Regulator	AMS1117-5.0	U20 U21	SOT-223	1	AMS
4	Linear Regulator	AMS1117-1.8	U22	SOT-223	1	AMS
CRYST	AI S					
CRYSI	ALS	24.576MHz				
4	Crystal	49SMD,24.576MHz,FL=30PPM,CL=25pF,	XT1	XTLSMD	1	
	·	300uW,Tape				
4	Crystal	12.288MHZ,3.3V,5mmx7mm	XT2	5mmx7mm	1	
CONNE	CTOR					
4	Connector SMD	0.5s-1-26PB	CN3	SOP	1	
4	FFC Connector	1.0-9-11-PB	CN1	SOP	1	
CAPAC	NTOD					
			EC11, EC12, EC13, EC14, EC15,			
3	ALU Electrolytic CAP	CD110,10uF,16V,±20%,F2.5	EC16, EC23, EC24	EC/D5/P2.5/1.7X1.7X1	8	
3	ALU Electrolytic CAP	CD110,100uF,16V,±20%,F2.5	EC20, EC22, EC25	EC/D6.3/P2.5/2X2X1	3	
3	ALU Electrolytic CAP	CD263,470uF,16V,±20%,F5.0	EC21	RB.2/.3A	1	
3	ALU Electrolytic CAP	CD263X,330uF,25V,±20%,F5.0	EC18, EC19	RB.2/.3A	2	
3	ALU Electrolytic CAP	CD263,3300UF/16V,±20%,16*25mm	EC17	RB.3/.7	1	
0	7120 Electrolytic of th	GB200,000001710V,±2070,10 2011111	2017	113.07.7		
CONNE	CTOR					
	2RCA	RCA2-W-R 2 heads,AV2-8.4-13PB1	RCA1		1	
3						
3	4POL RCA	AV4-8.4-13,	RCA2, RCA3		2	SHARP
3	Optical Receiver DC POWER JACK	GP1FAV30RK0F DC-005	OPT1, OPT2 DC1		1	SHARP
3	Connector	2.54 5PIN	J1	SIP	1	
3	Wireless Module	DWAM80_EA CF3	Module1		1	STS
2	Plastic Spacer	Nylon66,H=10.5	wireless module(2)		2	
2	Plastic NUT Machine Screw	Nylon66,M3 MB3×6	wireless module(2) wireless module(2)		2	
	2011110 03104		5.000 modelo(E)			
2	FPP BOARD					
3 PCB	FPP BOARD SMT					
4	FPP PCB	VC1.0 FR-4 30*130mm			1	
Transis			04.00.00.	007.00		\r.i. 10115=
4	Transistor Digital transistor	MMBT3904 DTC114	Q1, Q2, Q3, Q4 Q7	SOT-23 SOT-23	1	Vishay/ONSEMI ROHM
4	Digital transistor Digital transistor	DTA114	Q6	SOT-23	1	ROHM
	-					
CONNE	FFC Connector	1.0-9-11-PB	CN2	SOP	1	
DIODES		1.0-9-11-FD	CINZ	SUF		
3	LED BLUE	φ3, Blue, BL-BB51V1V	LED1, LED2, LED3, LED4	LED-3MM	4	
3	LED RED/BLUE	BL-BUBB5271V Ф3 Bule&Red	LED5		1	
IC	ID Dessite	T00D24022	ID4		4	7/10/14/2
3	IR Receiver	TSOP34838	IR1		1	VISHAY
.1	SUBWOOFER					
3	AMP BOARD AMP BOARD					
4	PCB	FR-4, 1.6mm, 80×145mm			1	
ICS	ODANE	NUMEROOM OS S	11000	22.2		
4	OPAMP	NJM5532M SO-8	U202	SO-8	1	
5	MCU	ATMEGA16L-8AU,2.7-5.5V,TQFP-44	U102	TQFP-44	1	ATMEL
4	Digital Audio AMP	TAS5342LADDVR	U200, U201	HTSSOP44	2	TI

VP3.9 for Pilot Run 2009-06-26

	1					2009-06
4	8-channel digital audio PWM	TAS5508BPAG	U100	TQFP-64	1	TI
4	processor Rst	TPS3801K33DCKR	U103	SOT-323(SC70)	1	TI
4	Regulator	LM1117MPX-3.3 / AMS1117-3.3	U104	SOT-223	1	NS/AMS
Transis						
4	Transistor	MMBT3906/MMBT3906LT1	Q102, Q200, Q201		3	Vishay/ONSEMI
4	Transistor	MMBT3904/MMBT3904LT1/FMMT3904TA SOT-23	Q100, Q101, Q103, Q104, Q106, Q107		6	Vishay/ONSEMI
4	MOSFET	APM2301CAC, SOT23, Tape	M100	SOT23/ECB/1.3X1.3	1	ANPEC
DIODE	S					
4	Switch Diode	IN4148	D100	SOD80C	1	
4	ESD DIODE	1SMA33CAT	D200, D201, D202, D203, D204, D205,	SMA	8	ST
		1 111	D206, D207			-
CONNE	L ECTORS					
3	SMD Socket	0.5S-1-26PB	J100		1	
CAPAC	CITORS					
3	Alu Electrolytic Capacitor	CD263, 10uF, 50V, ±20%, Pitch=2.5mm	C200, C201, C202, C290	RB2.5/5.0	4	
			,,			
3	Alu Electrolytic Capacitor	CD263, 10uF, 50V, ±20%, Pitch=2.5mm	C203	RB2.5/5.0	1	
3	Alu Electrolytic Capacitor	CD263X,100uF,16V,±20%,5×11,F2.5	C140	RB2.5/6.3	1	
			C238, C239, C240, C241, C242, C243,			
3	Alu Electrolytic Capacitor	SD/RD-series, 470uF, 50V, ±20%, F5.0	C244, C245, C246, C247, C248, C249		12	
			.,, 52.10, 52.11, 52.40, 52.40			
3	Metallized Polyester Film Capacitor	CL23B,470nF,63V,Pitch=5mm,5%	C294, C295, C296, C297	MMK5.0	4	
	Metallized Polyester Film					
3	Capacitor	CL23B,1uF,63V,Pitch=5mm,5%	C274, C275, C276, C277	MMK5.0	4	
DIODE						
3	LED	φ3,Blue&Red, BL-BUBB4274 A	Q105		1	
	CTORS	0.54.0450	10100			
3	2.54 Connector Connector Socket	2.54 2*5Pin VH-2AW, 3.96 2Pin	JP100 J202		1	CNT
3	Connector Socket Connector Socket	3P 3.96	J202 J200		1	CNI
3	Connector Socket	PH 2.0A-7A	J101		1	
3	Connector Socket	PH 2.0A-5A	J102		1	
3	Connector Socket	VH 3.96A-10A	J201		1	
INDCT						
3	Ferrite Bead INDUCTANCE	7075P-100M	L204 L205, L206, L207, L208	FB10	1	
3	INDUCTANCE	10uH, GCP1014-100M	L205, L206, L207, L208		4	
3	INDUCTANCE	7075P-220M	L200, L201, L202, L203		4	
3	INDUCTANCE	22uH, GCP1014-220M	L200, L201, L202, L203		4	
3	Wireless Module	DWAM80_IA CF3	Module2		1	STS
_						
2	PCB	VD1 2 ED 4 1 6mm 110×25mm			1	
3	Slide Switch	VP1.2 FR-4, 1.6mm 110×35mm TS-13-A1-2-CQ-S20	S1, S2		2	
3	Connector Socket	5569-10A, 4.2mm 2*5pin	J2		1	
3	Connector Socket	PH 2.0A-5A	J3		1	
3	Connector Socket	3.96A-10A	J1		1	
2		CMT				
3 PCB		SMT				
4	SMPS PCB	VC1.0 FR-4, 1.6mm			1	
DIODE						
4	Switch Diode	LL4148	D902, D910	LL34	2	107
4	Schottky Rectifier Diode	MURS120T3G 5.6V, 0.5W	D904 D906	SMD LL34	1	HY
4	Zener Diode Rectifier Diode	5.6V, 0.5W M7A	D906 D901	SMD	1	HY
4	Schottky Rectifier Diode	MBRS3100T3G, 3A 100V	D911	SMD	1	ONSEMI
IC						
4	Photo Coupler Voltage Norm	PC817X2NIP TL431BCDBZTG4	U904, U905, U906	SMD	2	SHARP
4	voltage inorm	IL43 IDCDDZ IG4	U901,U902	SOT23	2	TI
CAPAC	ITORS					
3	Interfernece Suppression Cap	MKP62, 330nF, 275VAC, X2, ±10%	CX901	Pitch=15mm,18mm*10	1	
	за саррисовии оар	12, 13, 2.07.0, 72, 110/0	5,100.	mm	•	
3	Interfernece Suppression Cap	MKP62, 220nF, 275VAC, X2, ±10%	CX903, CX902	Pitch=15mm,18mm*10 mm	2	
				111111		
3	Hign Voltage Cermatic Capacitor	1nF, 400V(X1), 250V(Y1), ±20%	CY901, CY902, CY903	Pitch=10mm	3	
<u>L</u>	3 3	CT81-400VAC-08b-2E4-102M-YA				<u> </u>
3	Hign Voltage Cermatic Capacitor	2.2nF, 400V(X1), 250V(Y1), ±20%	CY904	Pitch=10mm	1	
	g vollage dermane dapacitor	CT81-400VAC-12b-2E4-222M-YA	31004			
	Metallized Polyester Film					
3		CL23B,10nF,400V,±10%,Pitch=5mm	C921, C903	Pitch=5mm	2	
	Canacitor			Pitch=10mm,30mm*45		
	Capacitor	000 E 400' CD 00E 0-			1	
3	Capacitor Alu Electrolytic Capacitor	390uF,400V,CD295,25*45, ±20%	C920	mm		
3	Alu Electrolytic Capacitor			Pitch=5mm,		
		390uF,400V,CD295,25*45, ±20% CD263(X), 10uF,50V, ±20%	C920 C904, C918, C922	Pitch=5mm, 5mm*11.5mm	3	
3	Alu Electrolytic Capacitor			Pitch=5mm, 5mm*11.5mm Pitch=2.5mm		
3	Alu Electrolytic Capacitor Alu Electrolytic Capacitor Alu Electrolytic Capacitor	CD263(X), 10uF,50V, ±20% CD263(X), 47uF, 16V, ±20%	C904, C918, C922 C915	Pitch=5mm, 5mm*11.5mm Pitch=2.5mm 5mm*11.5mm	3	
3	Alu Electrolytic Capacitor Alu Electrolytic Capacitor	CD263(X), 10uF,50V, ±20%	C904, C918, C922	Pitch=5mm, 5mm*11.5mm Pitch=2.5mm	3	

HS40-MEDIA CHAIR_B17VP3.9

						2009-06
3	Alu Electrolytic Capacitor	CD11H, 10uF, 400V, ±20%	C901	Pitch=5mm 10mm*20mm	1	
3	Alu Electrolytic Capacitor	CD286, 2200uF, 35V, ±20%	C927, C928	Pitch=7.5mm 16mm*25mm	2	
3	Alu Electrolytic Capacitor	CD263X, 100uF, 35V, ±20%	C929	Pitch=2.5mm 6.3mm*11.5mm	1	
3	Alu Electrolytic Capacitor	CD263X, 470uF, 25V, ±20%	C924	Pitch=5mm 10mm*11.5mm	1	
3	Alu Electrolytic Capacitor	CD263X, 1000uF, 10V, ±20%	C912	Pitch=5mm 10mm*16mm	1	
RESIS1	TOP					
3	Metal Oxide film Resistor	1KΩ, 2W, ±5%	R932, R933	Pitch=5mm	2	
3	Metal Oxide film Resistor	68KΩ, 1W, ±5%	R906	Pitch=5mm	1	
3	Metal Oxide film Resistor	47KΩ, 2W, ±5%	R929	Pitch=5mm	1	
3	NTC	5D-11	TH901	Pitch=7.5mm	1	SEMITEC
3	TVS	TUR10D471	ZV901	Pitch=7.5mm	1	
DIODE						
3	Rectifier Bridge	KBU810,8A/1000V	D907		1	HY
3	Rectifier Diode	UF4006	D903, D909	Pitch=5mm,	2	Vishay
3	Rectifier Diode	UF4006	D903, D909	Pitch=5mm,	2	Fairchild
3		P6KE-200A	D908	Pitch=5mm	1	
3	Rectifier Diode	MUR1620	D912	TO-220AC	1	Onsemi
3	Schottky Rectifier Diode	IN5822	D905	Pitch=5mm	1	
IC						
3	Voltage Regulators	KA78R12	U908	TO-220-4L	1	Fairchild
3	Power controller IC	TOP249YN	U907	TO220-7C	1	Power integrations
3	Power controller IC	TNY274P	U903	DIP8	1	Power integrations
	i ewer controller to			50		. over integrations
INDUC						
3	INDUCTOR	3~5uH	L906, L904	Pitch=10mm	2	
3	INDUCTOR	18uH/5A	L905	Pitch=7.5mm	1	
3	INDUCTOR	10uH, 2.6A,744772100	L901		1	
3	INDUCTOR	8mH min, 2A, T25*15*12	L903		1	
3	INDUCTOR	4mH 2A	L902		1	
	FORMER	EEL 1010 1 0 :: IL : 100/	T004	FF4040(4:0)		
3	Transformer	EEL1916, 1.2mH ±10% ER-35, 150uH ±10%	T901 T902	EE1916(4+6) EER35(8+8)	1	
3	Transformer	ER-35, 1500H ±10%	1902	EER35(8+8)	1	
CONNE	CTOR					
3	Connecter	PH 2.0A-7A	J903		1	LONSID
3	Connecter	VH 3.96A-3A	J902		1	LONSID
MISC		TO 454 (050) ((MOTO 45)	F		4	
3	Fuse	T3.15A/250V(MST3.15)	Fuse901		1	
3	Transistor Washer Insulated Pad	TW-5 SQ9418, SPK-4	MUR1620 MUR162		1	BERGQUIST
3	insulated Pad	SQ9418, SPK-4	MUR 162		1	BERGQUIST
.1	Bass shaker	AST-2B-4			1	AURA
4	2.5" Canalian				4	
.1	2.5" Speaker	40 40W PMC			4	Muni n
2	2.5" Speaker	4Ω,10W RMS			4	Musicyang
						
				T T	 	1