





# TEST REPORT No. I19Z62348-WMD03

for

**Shenzhen Tinno Mobile Technology Corp.** 

**Smart Phone** 

Model Name: U304AC

FCC ID: XD6U304AA

with

Hardware Version: V1.0

Software Version: U304ACV02.09.11

Issued Date: 2020-01-17



#### Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S.Government.

#### **Test Laboratory:**

CTTL, Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: <a href="mailto:cttl\_terminals@caict.ac.cn">cttl\_terminals@caict.ac.cn</a>, website: www.caict.ac.cn





## **REPORT HISTORY**

Report Number	Revision	Description	Issue Date
I19Z62348-WMD03	Rev.0	1 <sup>st</sup> edition	2020-01-17

Note: the latest revision of the test report supersedes all previous version.





## **CONTENTS**

1. TEST LABORATORY	4
1.1. INTRODUCTION & ACCREDITATION	4
1.2. TESTING LOCATION	4
1.3. TESTING ENVIRONMENT	5
1.4. PROJECT DATA	5
1.5. SIGNATURE	
2. CLIENT INFORMATION	
2.1. APPLICANT INFORMATION	
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	7
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	7
4. REFERENCE DOCUMENTS	8
4.1. REFERENCE DOCUMENTS FOR TESTING	8
5. LABORATORY ENVIRONMENT	9
6. SUMMARY OF TEST RESULTS	10
6.1. SUMMARY OF TEST RESULTS	10
6.2. EXPLANATION OF RE-USE OF TEST DATA	
7. TEST EQUIPMENTS UTILIZED	
ANNEX A: MEASUREMENT RESULTS	
A.1 OUTPUT POWER	
A.2 EMISSION LIMIT	
A.4 OCCUPIED BANDWIDTH	
A.5 EMISSION BANDWIDTH	
A.6 BAND EDGE COMPLIANCE	
A.7 CONDUCTED SPURIOUS EMISSION	
A.8 PEAK-TO-AVERAGE POWER RATIO	189
ANNEY B. ACCREDITATION CERTIFICATE	100





## 1. Test Laboratory

#### 1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

#### 1.2. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,

P. R. China 100191

Location 2: CTTL(Shouxiang)

Address: No. 51 Shouxiang Science Building, Xueyuan Road,

Haidian District, Beijing, P. R. China 100191





## 1.3. Testing Environment

Normal Temperature:

15-35℃

Relative Humidity: 20-75%

1.4. Project data

Testing Start Date: 2019-04-10
Testing End Date: 2020-01-17

## 1.5. Signature



Dong Yuan (Prepared this test report)



Zhou Yu (Reviewed this test report)



Zhao Hui Lin
Deputy Director of the laboratory
(Approved this test report)





## 2. Client Information

## 2.1. Applicant Information

Company Name: Shenzhen Tinno Mobile Technology Corp.

Address /Post: 4/F, H-3 Building,OCT Eastern Industrial Park. NO.1 XiangShan East

Road, Nan Shan District, Shenzhen, P.R.China

Contact: Jingwen.Guo

Email: jingwen.guo@tinno.com

Telephone: 0755-86095550

Fax: NA

Address /Post:

## 2.2. Manufacturer Information

Company Name: Shenzhen Tinno Mobile Technology Corp.

4/F, H-3 Building,OCT Eastern Industrial Park. NO.1 XiangShan East

Road, Nan Shan District, Shenzhen, P.R.China

Contact: Jingwen.Guo

Email: jingwen.guo@tinno.com

Telephone: 0755-86095550

Fax: NA





## 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

Description Smart Phone
Model Name U304AC
FCC ID XD6U304AA
Antenna Embedded

Output power 25.17dBm maximum EIRP measured for LTE Band 4

Extreme vol. Limits 3.5VDC to 4.4VDC (nominal: 3.85VDC)

Extremetemp. Tolerance -10°C to +55°C

Note: Components list, please refer to documents of the manufacturer; it is also included in the original test record of CTTL.

## 3.2. Internal Identification of EUT used during the test

EUT ID*	IMEI	<b>HW Version</b>	SW Version	Date of receipt
UT07a	863465040002405	V1.0	U304ACV02.09.11	2020-01-03

<sup>\*</sup>EUT ID: is used to identify the test sample in the lab internally.

## 3.3. Internal Identification of AE used during the test

**AE ID\* Description** AE1 Battery

AE1

Model LT25H426271B

Manufacturer Shenzhen BYD Lithium Battery Company Limited

Capacitance 2500mAh(rated)

Nominal Voltage 3.85V

\*AE ID: is used to identify the test sample in the lab internally.





## 4. Reference Documents

## 4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	10-1-18
		Edition
FCC Part 22	PUBLIC MOBILE SERVICES	10-1-18
		Edition
FCC Part 27	MISCELLANEOUS WIRELESS COMMUNICATIONS	10-1-18
	SERVICES	Edition
FCC Part 90	PRIVATE LAND MOBILE RADIO SERVICES	10-1-18
		Edition
ANSI/TIA-603-E	Land Mobile FM or PM Communications Equipment	2016
	Measurement and Performance Standards	
ANSI C63.26	American National Standard for Compliance Testing of	2015
	Transmitters Used in Licensed Radio Services	
KDB 971168 D01	MEASUREMENT GUIDANCE FOR CERTIFICATION OF	v03r01
	LICENSED DIGITAL TRANSMITTERS	





## 5. LABORATORY ENVIRONMENT

Control room / conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. =20 %, Max. = 80 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω

**Fully-anechoic chamber 2** (8.6 meters × 6.1 meters × 3.85 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	>2 MΩ
Ground system resistance	<1 Ω
Site voltage standing-wave ratio	Between 0 and 6 dB, from 1GHz to 18GHz
(Svswr)	
Uniformity of field strength	Between 0 and 6 dB, from 80 to 4000 MHz

**Semi-anechoic chamber 2** / **Fully-anechoic chamber 3** (10 meters×6.7 meters×6.15 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 35 %, Max. = 60 %
Shielding effectiveness	> 100 dB
Electrical insulation	>2 MΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	<±3.5 dB, 3 m distance
Site voltage standing-wave ratio	Between 0 and 6 dB, from 1GHz to 18GHz
(Svswr)	
Uniformity of field strength	Between 0 and 6 dB, from 80 to 3000 MHz





## 6. SUMMARY OF TEST RESULTS

## 6.1. <u>Summary of test results</u>

## LTE Band 2

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	24.232	BR
2	Emission Limit	2.1051/24.238	BR
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	24.238	BR
6	Band Edge Compliance	24.238	BR
7	Conducted Spurious Emission	24.238	BR
8	Peak-to-Average Power Ratio	24.232	BR

#### LTE Band 4

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	BR
2	Emission Limit	2.1051/27.53	BR
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	27.53	BR
6	Band Edge Compliance	27.53	BR
7	Conducted Spurious Emission	27.53	BR
8	Peak-to-Average Power Ratio	27.50	BR

## LTE Band 5

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	22.913	BR
2	Emission Limit	2.1051/22.917	BR
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	22.917	BR
6	Band Edge Compliance	22.917	BR
7	Conducted Spurious Emission	22.917	BR





#### LTE Band 12

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	Р
2	Emission Limit	2.1051/27.53	Р
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	27.53	BR
6	Band Edge Compliance	27.53	BR
7	Conducted Spurious Emission	27.53	BR
8	Peak-to-Average Power Ratio	27.50	BR

## LTE Band 14

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	90.635	BR
2	Emission Limit	2.1051/90.691	BR
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	2.1049	BR
6	Band Edge Compliance	90.691	BR
7	Conducted Spurious Emission	90.691	BR

## LTE Band 30

Items	Test Name	Clause in FCC rules	Verdict
1	Output Power	27.50	BR
2	Emission Limit	2.1051/27.53	BR
3	Frequency Stability	2.1055	BR
4	Occupied Bandwidth	2.1049	BR
5	Emission Bandwidth	27.53	BR
6	Band Edge Compliance	27.53	BR
7	Conducted Spurious Emission	27.53	BR
8	Peak-to-Average Power Ratio	27.50	BR

## Terms used in Verdict column

Р	Pass, The EUT complies with the essential requirements in the standard.		
NP	Not Perform, The test was not performed by CTTL		
NA	Not Applicable,The test was not applicable		
BR	Re-use test data from basic model report.		
F	Fail, The EUT does not comply with the essential requirements in the		
	standard		





Explanation of worst-case configuration

The worst-case scenario for all measurements is based on the conducted output power measurement investigation results. Output power was measured on QPSK,16QAM and 64QAM modulations. It was found that QPSK was the worst case. All testing was performed using QPSK modulations to represent the worst case unless otherwise stated. The test results shown in the following sections represent the worst case emission.

#### 6.2. Explanation of re-use of test data

The Equipment Under Test (EUT) model U304AC (FCC ID: XD6U304AA) is a variant product of U304AA (FCC ID: XD6U304AA). According to the declaration of changes provided by the applicant and FCC KDB publication 484596 D01, spot check measurements were performed on this device. All the test results are derived from test report No. I19Z60566-WMD03. Please refer Annex A for detail spot check verification data and reference data. The spot check test results are consistent with basic model.

For detail differences between two models please refer the Declaration of Changes document.





## 7. Test Equipments Utilized

NO.	Description	TYPE	series number	MANUFACTURE	CAL DUE DATE	Calibration interval
1	EMI Antenna	VULB9163	9163-301	Schwarzbeck	2020-02-29	1 year
2	EMI Antenna	3117	00058889	ETS-Lindgren	2020-11-18	1 year
3	EMI Antenna	3117	00119024	ETS-Lindgren	2020-02-25	1 year
4	Universal Radio Communication Tester	CMW500	159082	R&S	2019-12-25	1 year
5	Spectrum Analyzer	FSU26	200030	R&S	2020-06-03	1 year
6	EMI Antenna	9117	167	Schwarzbeck	2020-05-27	1 year
7	Signal Generator	N5183A	MY49060052	Agilent	2020-06-24	1 year
8	Climate chamber	SH-242	93008556	ESPEC	2020-12-21	3 year
9	Test Receiver	E4440A	MY48250642	Agilent	2020-03-18	1 year
10	Radio Communication Analyzer	MT8821C	6201763159	Anritsu	2020-07-23	1 year
11	Universal Radio Communication Tester	CMW500	143008	R&S	2020-11-26	1 year
12	Power Amplifier	5S1G4	0341863	AR	/	





## **ANNEX A: MEASUREMENT RESULTS**

## **A.1 OUTPUT POWER**

#### A.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMW500) to ensure max power transmission and proper modulation. In all cases, output power is within the specified limits.

#### A.1.2 Conducted

#### A.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

These measurements were done at 3 frequencies (bottom, middle and top of operational frequency range) for each bandwidth.





#### A.1.2.2 Measurement result

LTE band 2	RB	F	Power(dBm)			
Bandwidth	size/offset	Frequency (MHz)	QPSK	16QAM	64QAM	
		1909.3	23.43	22.64	21.08	
	1 RB high	1880.0	23.38	22.62	21.09	
		1850.7	23.43	22.64	21.20	
		1909.3	23.48	22.66	21.06	
	1 RB low	1880.0	23.40	22.68	21.07	
4 45411-		1850.7	23.46	22.65	21.18	
1.4MHz		1909.3	23.63	22.64	21.13	
	50% RB mid	1880.0	23.58	22.70	21.09	
		1850.7	23.62	22.68	21.14	
		1909.3	22.60	21.53	20.02	
	100% RB	1880.0	22.55	21.55	19.99	
		1850.7	22.56	21.59	20.02	
		1908.5	23.58	22.66	21.19	
	1 RB high	1880.0	23.49	22.68	21.14	
		1851.5	23.51	22.69	21.53	
	1 RB low	1908.5	23.54	22.65	21.10	
		1880.0	23.49	22.68	21.12	
		1851.5	23.52	22.65	21.20	
3MHz	50% RB mid	1908.5	22.62	21.52	20.05	
		1880.0	22.57	21.54	19.99	
		1851.5	22.56	21.60	20.07	
		1908.5	22.58	21.46	20.02	
	100% RB	1880.0	22.51	21.49	19.95	
		1851.5	22.53	21.49	19.99	
		1907.5	23.52	22.62	21.10	
	1 RB high	1880.0	23.47	22.65	21.07	
		1852.5	23.49	22.68	21.15	
		1907.5	23.48	22.65	21.09	
	1 RB low	1880.0	23.49	22.82	21.10	
ENALI→		1852.5	23.50	22.63	21.15	
5MHz		1907.5	22.60	21.53	20.07	
	50% RB mid	1880.0	22.56	21.56	20.06	
		1852.5	22.56	21.57	20.10	
		1907.5	22.60	21.58	20.00	
	100% RB	1880.0	22.57	21.58	20.00	
		1852.5	22.58	21.57	20.04	





		1905.0	23.57	22.67	21.15
	1 RB high	1880.0	23.49	22.64	21.09
		1855.0	23.50	22.67	21.18
		1905.0	23.55	22.69	21.16
	1 RB low	1880.0	23.57	22.72	21.15
10MHz		1855.0	23.56	22.68	21.24
TOWNIZ		1905.0	22.60	21.53	20.01
	50% RB mid	1880.0	22.59	21.56	20.02
		1855.0	22.59	21.54	20.03
		1905.0	22.65	21.60	20.00
	100% RB	1880.0	22.65	21.52	20.02
		1855.0	22.58	21.59	20.01
		1902.5	23.56	22.67	21.12
	1 RB high	1880.0	23.51	22.59	21.09
		1857.5	23.45	22.65	21.08
	1 RB low	1902.5	23.52	22.67	21.14
		1880.0	23.52	22.70	21.12
15MHz		1857.5	23.56	22.65	21.18
TOWINZ	50% RB mid	1902.5	22.59	21.56	20.01
		1880.0	22.60	21.56	20.01
		1857.5	22.56	21.55	20.02
	100% RB	1902.5	22.63	21.55	19.98
		1880.0	22.63	21.54	20.00
		1857.5	22.57	21.58	19.98
		1900.0	23.44	22.56	20.98
	1 RB high	1880.0	23.40	22.47	20.99
		1860.0	23.36	22.57	20.95
		1900.0	23.41	22.53	20.99
	1 RB low	1880.0	23.43	22.63	20.98
CONALL	[	1860.0	23.46	22.55	21.03
20MHz		1900.0	22.65	21.58	20.00
	50% RB mid	1880.0	22.62	21.58	19.99
	1	1860.0	22.64	21.59	20.00
		1900.0	22.64	21.64	19.96
	100% RB	1880.0	22.68	21.54	20.00
	100 /0 110	1000.0	22.00		





Bandwidth	RB	Frequency (MHz)	Power(dBm)			
Danuwiuiii	size/offset	r requericy (ivii iz)	QPSK	16QAM	64QAM	
		1754.3	23.38	22.69	21.20	
	1 RB high	1732.5	23.36	22.49	20.98	
		1710.7	23.49	22.64	21.15	
		1754.3	23.16	22.05	21.15	
	1 RB low	1732.5	23.33	22.05	21.02	
4 4NALI-		1710.7	23.12	22.13	21.19	
1.4MHz		1754.3	23.08	22.13	21.21	
	50% RB mid	1732.5	22.99	22.07	21.08	
		1710.7	23.13	22.19	21.21	
		1754.3	22.06	21.10	20.07	
	100% RB	1732.5	21.97	21.01	19.95	
		1710.7	22.10	21.13	20.07	
		1753.5	22.97	22.12	21.01	
	1 RB high	1732.5	22.88	22.04	21.07	
		1711.5	23.02	22.16	21.19	
	1 RB low	1753.5	22.94	22.09	21.11	
		1732.5	22.87	22.02	21.07	
ONALL		1711.5	23.03	22.18	21.21	
3MHz	50% RB mid	1753.5	22.01	21.05	19.95	
		1732.5	21.90	20.95	19.97	
		1711.5	22.04	21.10	20.07	
	100% RB	1753.5	21.97	20.97	20.00	
		1732.5	21.91	20.88	20.02	
		1711.5	22.04	21.03	20.01	
		1752.5	22.93	22.09	21.00	
	1 RB high	1732.5	22.84	21.95	21.00	
		1712.5	22.99	22.13	21.15	
		1752.5	22.93	22.06	20.91	
	1 RB low	1732.5	22.88	22.02	21.09	
C 8 41 1		1712.5	23.02	22.13	21.17	
5MHz		1752.5	22.02	21.06	19.95	
	50% RB mid	1732.5	21.92	20.96	19.95	
		1712.5	22.05	21.09	20.70	
		1752.5	22.02	21.04	19.94	
	100% RB	1732.5	21.92	20.93	20.96	
		1712.5	22.07	21.08	20.02	
401411	4.55	1750	22.97	22.07	20.98	
10MHz	1 RB high	1732.5	22.88	21.99	21.00	





		1715	23.00	22.15	21.18
		1750	22.95	22.04	20.90
	1 RB low	1732.5	22.97	22.10	21.13
	1 TO IOW	1715	23.07	22.17	21.16
		1750	22.03	21.05	19.92
	50% RB mid	1732.5	21.98	21.00	19.93
		1715	22.08	21.09	20.03
		1750	21.99	20.98	19.87
	100% RB	1732.5	21.93	20.96	19.88
		1715	22.05	21.04	20.03
		1747.5	22.93	22.07	20.99
	1 RB high	1732.5	22.88	21.88	20.92
		1717.5	22.90	22.09	21.07
		1747.5	22.95	22.02	21.00
	1 RB low	1732.5	22.95	22.17	21.11
		1717.5	23.05	22.19	21.21
15MHz		1747.5	21.99	21.02	19.92
	50% RB mid	1732.5	21.94	20.98	19.97
		1717.5	22.04	21.07	20.05
	100% RB	1747.5	21.98	20.99	19.86
		1732.5	21.95	20.96	19.92
		1717.5	22.04	21.04	20.00
		1745	22.80	21.90	20.81
	1 RB high	1732.5	22.69	21.80	20.80
		1720	22.73	21.84	20.95
		1745	22.80	21.87	20.98
	1 RB low	1732.5	22.84	21.93	20.66
		1720	22.95	22.13	21.12
20MHz		1745	22.04	21.01	19.93
	50% RB mid	1732.5	21.98	20.98	19.95
	-	1720	22.07	21.05	20.04
		1745	21.98	21.00	19.91
	100% RB	1732.5	21.98	20.99	19.92
	1007010	1732.5	22.06	21.07	20.06
		1120	22.00	21.07	20.00





Pandwidth	RB	Fragues av (MILE)	Power(dBm)			
Bandwidth	size/offset	Frequency (MHz)	QPSK	16QAM	64QAM	
		848.3	24.12	23.32	22.46	
	1 RB high	836.5	24.12	23.32	22.47	
		824.7	24.05	23.27	22.39	
		848.3	24.08	23.26	22.45	
	1 RB low	836.5	24.12	23.26	22.50	
4.4841.1		824.7	24.15	23.30	22.46	
1.4MHz		848.3	24.23	23.31	22.49	
	50% RB mid	836.5	24.24	23.34	22.44	
		824.7	24.23	23.31	22.43	
		848.3	23.26	22.24	21.45	
	100% RB	836.5	23.28	22.23	21.42	
		824.7	23.29	22.22	21.36	
		847.5	24.02	23.39	22.47	
	1 RB high	836.5	24.20	23.41	22.48	
		825.5	24.22	23.39	22.43	
	1 RB low	847.5	24.19	23.33	22.45	
		836.5	24.21	23.33	22.43	
		825.5	24.21	23.37	22.43	
3MHz	50% RB mid	847.5	23.29	22.26	21.39	
		836.5	23.31	22.28	21.33	
		825.5	23.26	22.25	21.36	
	100% RB	847.5	23.27	22.22	21.42	
		836.5	23.29	22.22	21.47	
		825.5	23.26	22.19	21.31	
		846.5	24.17	23.26	22.38	
	1 RB high	836.5	24.18	23.34	22.47	
		826.5	24.20	23.36	22.42	
		846.5	24.13	23.30	22.50	
	1 RB low	836.5	24.18	23.31	22.41	
		826.5	24.19	23.34	22.42	
5MHz		846.5	23.29	22.26	21.37	
	50% RB mid	836.5	23.32	22.30	21.33	
		826.5	23.26	22.28	21.27	
		846.5	23.28	22.26	21.48	
	100% RB	836.5	23.33	22.30	21.39	
		826.5	23.27	22.25	21.29	
40.4.	4.55	844.0	24.16	23.33	22.44	
10MHz	1 RB high	836.5	24.21	23.45	22.49	





		829.0	24.22	23.38	22.47
		844.0	24.16	23.32	22.49
	1 RB low	836.5	24.19	23.40	22.42
		829.0	24.16	23.32	22.41
	50% RB mid	844.0	23.30	22.27	21.39
		836.5	23.29	22.27	21.35
		829.0	23.28	22.28	21.34
		844.0	23.36	22.31	21.46
	100% RB	836.5	23.37	22.32	21.44
		829.0	23.30	22.27	21.36





LTE band 12

LTE band 12	RB size/offset	Fragues 24 (MILE)	Power(dBm)			
Bandwidth		Frequency (MHz)	QPSK	16QAM	64QAM	
		715.3	23.55	22.63	21.46	
	1 RB high	707.5	23.63	22.64	21.45	
		699.7	23.68	22.69	21.60	
		715.3	23.54	22.60	21.60	
	1 RB low	707.5	23.56	22.57	21.58	
4 48411-		699.7	23.68	22.70	21.72	
1.4MHz		715.3	23.67	22.61	21.65	
	50% RB mid	707.5	23.68	22.67	21.64	
		699.7	23.79	22.73	21.59	
		715.3	22.69	21.53	20.46	
	100% RB	707.5	22.75	21.59	20.54	
		699.7	22.81	21.62	20.48	
		714.5	23.59	22.61	21.45	
	1 RB high	707.5	23.65	22.72	21.55	
		700.5	23.69	22.69	21.56	
	1 RB low	714.5	23.56	22.58	21.57	
		707.5	23.59	22.62	21.65	
0.41.1		700.5	23.65	22.70	21.65	
3MHz	50% RB mid	714.5	22.66	21.53	20.48	
		707.5	22.71	21.59	20.46	
		700.5	22.73	21.61	20.46	
	100% RB	714.5	22.64	21.47	20.47	
		707.5	22.71	21.52	20.50	
		700.5	22.70	21.52	20.48	
		713.5	23.54	22.58	21.51	
	1 RB high	707.5	23.60	22.66	21.47	
		701.5	23.60	22.69	21.59	
		713.5	23.50	22.60	21.63	
	1 RB low	707.5	23.54	22.64	21.58	
C. M. I.		701.5	23.59	22.68	21.62	
5MHz		713.5	22.65	21.55	20.47	
	50% RB mid	707.5	22.68	21.58	20.53	
		701.5	22.67	21.60	20.44	
		713.5	22.65	21.52	20.53	
	100% RB	707.5	22.68	21.56	20.47	
		701.5	22.70	21.57	20.47	
405411	4.55111	711.0	23.57	22.62	21.50	
10MHz	1 RB high	707.5	23.58	22.64	21.51	





	704.0	23.63	22.69	21.58
	711.0	23.46	22.55	21.63
1 RB low	707.5	23.48	22.57	21.64
	704.0	23.56	22.63	21.68
	711.0	22.65	21.54	20.50
50% RB mid	707.5	22.65	21.54	20.50
	704.0	22.67	21.55	20.49
	711.0	22.67	21.54	20.49
100% RB	707.5	22.68	21.56	20.53
	704.0	22.69	21.56	20.53





Bandwidth	RB	Frequency (MHz)	Power(dBm)			
Dandwidth	size/offset	Trequency (MIT)	QPSK	16QAM	64QAM	
		795.5	23.24	22.34	21.23	
	1 RB high	793.0	23.29	22.37	21.30	
		790.5	23.26	22.35	21.30	
		795.5	23.29	22.40	21.34	
	1 RB low	793.0	23.26	22.35	21.35	
5MHz		790.5	23.26	22.30	21.37	
SIVITZ	50% RB mid	795.5	22.33	21.31	20.37	
		793.0	22.33	21.33	20.38	
		790.5	22.35	21.33	20.40	
	100% RB	795.5	22.33	21.28	20.33	
		793.0	22.38	21.37	20.39	
		790.5	22.37	21.32	20.34	
	1 RB high	793.0	23.28	22.29	21.25	
10М⊔→	1 RB low	793.0	23.28	22.32	21.36	
10MHz	50% RB mid	793.0	22.37	21.32	20.37	
	100% RB	793.0	22.47	21.40	20.43	





D de di dale	RB			Power(dBm)	
Bandwidth	size/offset	Frequency (MHz)	QPSK	16QAM	64QAM
		2312.5	23.14	22.21	20.97
	1 RB high	2310.0	23.08	22.02	20.96
		2307.5	23.08	21.74	20.99
	1 RB low	2312.5	22.68	21.75	21.00
		2310.0	22.70	21.73	20.99
5MHz		2307.5	22.55	21.72	21.03
SIVIFIZ		2312.5	21.71	20.71	19.91
	50% RB mid	2310.0	21.69	20.68	19.92
		2307.5	21.67	20.64	19.89
		2312.5	21.73	20.68	19.88
	100% RB	2310.0	21.71	20.69	19.89
		2307.5	21.68	20.65	19.85
	1 RB high	2310.0	22.67	21.84	21.00
10MHz	1 RB low	2310.0	22.60	21.75	21.06
IUIVI⊓∠	50% RB mid	2310.0	21.74	20.69	19.91
_	100% RB	2310.0	21.70	20.66	19.91





#### A.1.3 Radiated

#### A.1.3.1 Description

This is the test for the maximum radiated power from the EUT.

Rule Part 22.913(a) specifies "Mobile stations are limited to 2.0 watts EIRP.".

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 27.50(d) specifies "Fixed, mobile, and portable (handheld) stations operating in the

Rule Part 27.50(d) specifies "Fixed, mobile, and portable (handheld) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP".

Rule Part 27.50(h)(2) specifies "Mobile stations are limited to 2.0 watts EIRP.".

Rule Part 27.50(c) specifies "Portable stations (hand-held de-vices) are limited to 3 watts ERP.".


Rule Part 27.50(a)(3) specifies "For mobile and portable stations transmitting in the 2305–2315 MHz band or the 2350–2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, except that for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth."

Rule Part 90.635(b) specifies "The maximum output power of the transmitter for mobile stations is 100 watts(50dBm)".

#### A.1.3.2 Method of Measurement

The measurements procedures in TIA-603E-2016 are used.


1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with rms detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.







In the chamber, a substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power ( $P_{\text{Mea}}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_r$ ). The power of signal source ( $P_{\text{Mea}}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- 4. An amplifier should be connected to the Signal Source output port. And the cable should be connected between the amplifier and the substitution antenna.
  - The cable loss (P<sub>cl</sub>), the substitution antenna Gain (G<sub>a</sub>) and the amplifier Gain (P<sub>Ag</sub>) should be recorded after test.

The measurement results are obtained as described below:

- Power (EIRP) =  $P_{Mea} P_{Ag} P_{cl} G_a$
- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15.





## A.1.3.3 Measurement result Spot Check Measurement Results: LTE Band 12 - ERP

**Limits:** ≤34.77dBm (3W)

## LTE Band 12\_1.4MHz\_QPSK

	_	_							
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
699.70	-22.89	1.90	44.66	0.77	2.15	18.49	34.77	16.28	Н
707.50	-22.70	1.91	44.94	0.62	2.15	18.80	34.77	15.97	V
715.30	-22.66	1.92	45.26	0.50	2.15	19.03	34.77	15.74	V

#### LTE Band 12\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
700.50	-22.86	1.90	44.68	0.76	2.15	18.53	34.77	16.24	V
707.50	-22.71	1.91	44.94	0.62	2.15	18.79	34.77	15.98	V
714.50	-22.67	1.92	45.26	0.50	2.15	19.02	34.77	15.75	V

## LTE Band 12\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
701.50	-22.91	1.90	44.81	0.74	2.15	18.59	34.77	16.18	V
707.50	-22.73	1.91	44.94	0.62	2.15	18.77	34.77	16.00	V
713.50	-22.60	1.92	45.22	0.50	2.15	19.05	34.77	15.72	V

## LTE Band 12\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
704.00	-22.80	1.91	44.93	0.70	2.15	18.77	34.77	16.00	V
707.50	-22.72	1.91	44.94	0.62	2.15	18.78	34.77	15.99	V
711.00	-22.65	1.92	45.19	0.53	2.15	19.00	34.77	15.77	V





## LTE Band 12\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
699.70	-23.69	1.90	44.66	0.77	2.15	17.69	34.77	17.08	Н
707.50	-23.50	1.91	44.94	0.62	2.15	18.00	34.77	16.77	V
715.30	-23.47	1.92	45.26	0.50	2.15	18.22	34.77	16.55	V

## LTE Band 12\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
700.50	-23.69	1.90	44.68	0.76	2.15	17.70	34.77	17.07	V
707.50	-23.53	1.91	44.94	0.62	2.15	17.97	34.77	16.80	V
714.50	-23.49	1.92	45.26	0.50	2.15	18.20	34.77	16.57	V

## LTE Band 12\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
701.50	-23.71	1.90	44.81	0.74	2.15	17.79	34.77	16.98	V
707.50	-23.55	1.91	44.94	0.62	2.15	17.95	34.77	16.82	V
713.50	-23.42	1.92	45.22	0.50	2.15	18.23	34.77	16.54	V

## LTE Band 12\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
704.00	-23.60	1.91	44.93	0.70	2.15	17.97	34.77	16.80	V
707.50	-23.54	1.91	44.94	0.62	2.15	17.96	34.77	16.81	V
711.00	-23.49	1.92	45.19	0.53	2.15	18.16	34.77	16.61	V





## LTE Band 12\_1.4MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
699.70	-24.80	1.90	44.66	0.77	2.15	16.58	34.77	18.19	Н
707.50	-24.54	1.91	44.94	0.62	2.15	16.96	34.77	17.81	V
715.30	-24.55	1.92	45.26	0.50	2.15	17.14	34.77	17.63	V

## LTE Band 12\_3MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
700.50	-24.77	1.90	44.68	0.76	2.15	16.62	34.77	18.15	V
707.50	-24.61	1.91	44.94	0.62	2.15	16.89	34.77	17.88	V
714.50	-24.56	1.92	45.26	0.50	2.15	17.13	34.77	17.64	V

## LTE Band 12\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
701.50	-24.79	1.90	44.81	0.74	2.15	16.71	34.77	18.06	V
707.50	-24.64	1.91	44.94	0.62	2.15	16.86	34.77	17.91	V
713.50	-24.49	1.92	45.22	0.50	2.15	17.16	34.77	17.61	V

## LTE Band 12\_10MHz\_64QAM

-										
	Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
	704.00	-24.67	1.91	44.93	0.70	2.15	16.90	34.77	17.87	V
	707.50	-24.61	1.91	44.94	0.62	2.15	16.89	34.77	17.88	V
	711.00	-24.57	1.92	45.19	0.53	2.15	17.08	34.77	17.69	V





#### Reference Measurement Results from basic model:

#### LTE Band 2- EIRP

**Limits:** ≤33dBm (2W)

#### LTE Band 2\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.70	-22.46	2.92	43.75	4.87	23.24	33.00	9.76	Н
1880.00	-22.79	2.85	43.75	4.82	22.93	33.00	10.07	Н
1909.30	-22.73	2.87	43.77	4.76	22.93	33.00	10.07	Н

## LTE Band 2\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1851.50	-22.67	2.87	43.75	4.87	23.08	33.00	9.92	Н
1880.00	-22.91	2.85	43.75	4.82	22.81	33.00	10.19	Н
1908.50	-22.63	2.89	43.78	4.76	23.02	33.00	9.98	Н

#### LTE Band 2\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.50	-22.73	2.87	43.75	4.87	23.02	33.00	9.98	Н
1880.00	-22.90	2.85	43.75	4.82	22.82	33.00	10.18	Н
1907.50	-22.86	2.84	43.77	4.77	22.84	33.00	10.16	Н

## LTE Band 2\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1855.00	-22.76	2.88	43.74	4.86	22.96	33.00	10.04	Н
1880.00	-22.86	2.85	43.75	4.82	22.86	33.00	10.14	Н
1905.00	-22.99	2.87	43.77	4.77	22.68	33.00	10.32	Н

## LTE Band 2\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1857.50	-22.88	2.87	43.75	4.86	22.86	33.00	10.14	Н
1880.00	-22.93	2.85	43.75	4.82	22.79	33.00	10.21	Н
1902.50	-23.41	2.86	43.77	4.78	22.28	33.00	10.72	Н

## LTE Band 2\_20 MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1860.00	-22.91	2.86	43.75	4.85	22.83	33.00	10.17	Н
1880.00	-22.76	2.85	43.75	4.82	22.96	33.00	10.04	Н
1900.00	-23.49	2.87	43.77	4.78	22.19	33.00	10.81	Н





## LTE Band 2\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.70	-23.38	2.92	43.75	4.87	22.32	33.00	10.68	Н
1880.00	-23.76	2.85	43.75	4.82	21.96	33.00	11.04	Н
1909.30	-23.53	2.87	43.77	4.76	22.13	33.00	10.87	Н

## LTE Band 2\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1851.50	-23.52	2.87	43.75	4.87	22.23	33.00	10.77	Н
1880.00	-23.81	2.85	43.75	4.82	21.91	33.00	11.09	Н
1908.50	-23.65	2.89	43.78	4.76	22.00	33.00	11.00	Н

## LTE Band 2\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.50	-23.53	2.87	43.75	4.87	22.22	33.00	10.78	Н
1880.00	-23.73	2.85	43.75	4.82	21.99	33.00	11.01	Н
1907.50	-23.85	2.84	43.77	4.77	21.85	33.00	11.15	Н

## LTE Band 2\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1855.00	-23.64	2.88	43.74	4.86	22.08	33.00	10.92	Н
1880.00	-23.74	2.85	43.75	4.82	21.98	33.00	11.02	Н
1905.00	-24.05	2.87	43.77	4.77	21.62	33.00	11.38	Н

## LTE Band 2\_15MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1857.50	-23.92	2.87	43.75	4.86	21.82	33.00	11.18	Н
1880.00	-23.74	2.85	43.75	4.82	21.98	33.00	11.02	Н
1902.50	-24.36	2.86	43.77	4.78	21.33	33.00	11.67	Н

## LTE Band 2\_20 MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1860.00	-23.82	2.86	43.75	4.85	21.92	33.00	11.08	Н
1880.00	-23.73	2.85	43.75	4.82	21.99	33.00	11.01	Н
1900.00	-24.55	2.87	43.77	4.78	21.13	33.00	11.87	Н





#### LTE Band 2\_1.4MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1850.70	-24.74	2.92	43.75	4.87	20.96	33.00	12.04	Н
1880.00	-25.13	2.85	43.75	4.82	20.59	33.00	12.41	Н
1909.30	-24.79	2.87	43.77	4.76	20.87	33.00	12.13	Н

## LTE Band 2\_3MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1851.50	-24.76	2.87	43.75	4.87	20.99	33.00	12.01	Н
1880.00	-25.02	2.85	43.75	4.82	20.70	33.00	12.30	Н
1908.50	-24.93	2.89	43.78	4.76	20.72	33.00	12.28	Н

## LTE Band 2\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1852.50	-24.83	2.87	43.75	4.87	20.92	33.00	12.08	Н
1880.00	-25.03	2.85	43.75	4.82	20.69	33.00	12.31	Н
1907.50	-25.11	2.84	43.77	4.77	20.59	33.00	12.41	Н

## LTE Band 2\_10MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1855.00	-24.91	2.88	43.74	4.86	20.81	33.00	12.19	Н
1880.00	-24.93	2.85	43.75	4.82	20.79	33.00	12.21	Н
1905.00	-25.39	2.87	43.77	4.77	20.28	33.00	12.72	Н

## LTE Band 2\_15MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1857.50	-25.05	2.87	43.75	4.86	20.69	33.00	12.31	Н
1880.00	-24.98	2.85	43.75	4.82	20.74	33.00	12.26	Н
1902.50	-25.78	2.86	43.77	4.78	19.91	33.00	13.09	Н

## LTE Band 2\_20 MHz\_64QAM

	Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
Ī	1860.00	-24.86	2.86	43.75	4.85	20.88	33.00	12.12	Н
Ī	1880.00	-24.89	2.85	43.75	4.82	20.83	33.00	12.17	Н
	1900.00	-25.92	2.87	43.77	4.78	19.76	33.00	13.24	Н





## LTE Band 4- EIRP

**Limits:** ≤30dBm (1W)

## LTE Band 4\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1710.70	-22.46	3.17	44.10	5.12	23.59	30.00	6.41	Н
1732.50	-21.87	3.33	44.14	5.08	24.02	30.00	5.98	Н
1754.30	-20.25	3.76	44.14	5.04	25.17	30.00	4.83	Н

## LTE Band 4\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1711.50	-22.36	3.40	44.10	5.12	23.46	30.00	6.54	Н
1732.50	-21.99	3.33	44.14	5.08	23.90	30.00	6.10	Н
1753.50	-20.37	3.80	44.13	5.04	25.00	30.00	5.00	Н

## LTE Band 4\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.50	-22.07	3.66	44.10	5.12	23.49	30.00	6.51	Н
1732.50	-22.03	3.33	44.14	5.08	23.86	30.00	6.14	Н
1752.50	-20.53	3.82	44.14	5.05	24.84	30.00	5.16	Н

## LTE Band 4\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1715.00	-22.03	3.56	44.10	5.11	23.62	30.00	6.38	Н
1732.50	-21.94	3.33	44.14	5.08	23.95	30.00	6.05	Н
1750.00	-21.47	3.00	44.15	5.05	24.73	30.00	5.27	Н

## LTE Band 4\_15MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1717.50	-22.37	3.47	44.11	5.11	23.38	30.00	6.62	Н
1732.50	-22.04	3.33	44.14	5.08	23.85	30.00	6.15	Н
1747.50	-21.47	3.34	44.15	5.05	24.39	30.00	5.61	Н

## LTE Band 4\_20MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1720.00	-22.41	3.37	44.11	5.10	23.43	30.00	6.57	Н
1732.50	-21.96	3.33	44.14	5.08	23.93	30.00	6.07	Н
1745.00	-21.07	3.68	44.16	5.06	24.47	30.00	5.53	Н





## LTE Band 4\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1710.70	-23.49	3.17	44.10	5.12	22.56	30.00	7.44	Н
1732.50	-22.79	3.33	44.14	5.08	23.10	30.00	6.90	Н
1754.30	-21.19	3.76	44.14	5.04	24.23	30.00	5.77	Н

## LTE Band 4\_3MHz\_16QAM

I	Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Aq</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
	. , ,	. ,	( /	. 9( /	- ( )	, ,	, ,	0 ( )	
	1711.50	-22.36	3.40	44.10	5.12	23.46	30.00	6.54	Н
	1732.50	-21.99	3.33	44.14	5.08	23.90	30.00	6.10	Н
	1753.50	-20.37	3.80	44.13	5.04	25.00	30.00	5.00	Н

## LTE Band 4\_5MHz\_16QAM

	Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
	1712.50	-22.94	3.66	44.10	5.12	22.62	30.00	7.38	Н
F	1732.50	-22.83	3.33	44.14	5.08	23.06	30.00	6.94	Н
F	1752.50	-21.48	3.82	44.14	5.05	23.89	30.00	6.11	Н

## LTE Band 4\_10MHz\_16QAM

	Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
Ī	1715.00	-22.96	3.56	44.10	5.11	22.69	30.00	7.31	Н
	1732.50	-22.82	3.33	44.14	5.08	23.07	30.00	6.93	Н
	1750.00	-22.48	3.00	44.15	5.05	23.72	30.00	6.28	Н

## LTE Band 4\_15MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1717.50	-23.35	3.47	44.11	5.11	22.40	30.00	7.60	Н
1732.50	-22.96	3.33	44.14	5.08	22.93	30.00	7.07	Н
1747.50	-22.36	3.34	44.15	5.05	23.50	30.00	6.50	Н

## LTE Band 4\_20MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1720.00	-23.36	3.37	44.11	5.10	22.48	30.00	7.52	Н
1732.50	-22.84	3.33	44.14	5.08	23.05	30.00	6.95	Н
1745.00	-22.11	3.68	44.16	5.06	23.43	30.00	6.57	Н





## LTE Band 4\_1.4MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1710.70	-25.23	3.17	44.10	5.12	20.82	30.00	9.18	Н
1732.50	-24.30	3.33	44.14	5.08	21.59	30.00	8.41	Н
1754.30	-22.63	3.76	44.14	5.04	22.79	30.00	7.21	Н

## LTE Band 4\_3MHz\_64QAM

Freque	ency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
17	11.50	-24.99	3.40	44.10	5.12	20.83	30.00	9.17	Н
173	32.50	-24.29	3.33	44.14	5.08	21.60	30.00	8.40	Н
17:	53.50	-22.64	3.80	44.13	5.04	22.73	30.00	7.27	Н

## LTE Band 4\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1712.50	-24.65	3.66	44.10	5.12	20.91	30.00	9.09	Н
1732.50	-24.27	3.33	44.14	5.08	21.62	30.00	8.38	Н
1752.50	-22.72	3.82	44.14	5.05	22.65	30.00	7.35	Н

## LTE Band 4\_10MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1715.00	-24.67	3.56	44.10	5.11	20.98	30.00	9.02	Н
1732.50	-24.27	3.33	44.14	5.08	21.62	30.00	8.38	Н
1750.00	-23.66	3.00	44.15	5.05	22.54	30.00	7.46	Н

## LTE Band 4\_15MHz\_64QAM

	_							
Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1717.50	-24.90	3.47	44.11	5.11	20.85	30.00	9.15	Н
1732.50	-24.35	3.33	44.14	5.08	21.54	30.00	8.46	Н
1747.50	-23.93	3.34	44.15	5.05	21.93	30.00	8.07	Н

## LTE Band 4\_20MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
1720.00	-24.93	3.37	44.11	5.10	20.91	30.00	9.09	Н
1732.50	-24.29	3.33	44.14	5.08	21.60	30.00	8.40	Н
1745.00	-23.29	3.68	44.16	5.06	22.25	30.00	7.75	Н





#### LTE Band 5- ERP

**Limits:** ≤38.45dBm (7W)

## LTE Band 5\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.70	-21.46	2.26	45.79	0.95	2.15	20.87	38.45	17.58	Н
836.50	-21.22	2.26	45.66	0.82	2.15	20.85	38.45	17.60	Н
848.30	-21.96	2.27	45.55	0.80	2.15	19.97	38.45	18.48	Н

## LTE Band 5\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-21.71	2.26	45.79	0.94	2.15	20.61	38.45	17.84	Н
836.50	-21.42	2.26	45.66	0.82	2.15	20.65	38.45	17.80	Н
847.50	-22.14	2.27	45.56	0.81	2.15	19.81	38.45	18.64	Н

## LTE Band 5\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.50	-21.66	2.25	45.77	0.93	2.15	20.64	38.45	17.81	Н
836.50	-21.44	2.26	45.66	0.82	2.15	20.63	38.45	17.82	Н
846.50	-22.08	2.26	45.56	0.82	2.15	19.89	38.45	18.56	Н

## LTE Band 5\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
829.00	-21.62	2.13	45.74	0.90	2.15	20.74	38.45	17.71	Н
836.50	-21.38	2.26	45.66	0.82	2.15	20.69	38.45	17.76	Н
844.00	-22.01	2.26	45.59	0.82	2.15	19.99	38.45	18.46	Н





#### LTE Band 5\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.70	-22.43	2.26	45.79	0.95	2.15	19.90	38.45	18.55	Н
836.50	-22.14	2.26	45.66	0.82	2.15	19.93	38.45	18.52	Н
848.30	-23.02	2.27	45.55	0.80	2.15	18.91	38.45	19.54	Н

# LTE Band 5\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-22.63	2.26	45.79	0.94	2.15	19.69	38.45	18.76	Н
836.50	-22.39	2.26	45.66	0.82	2.15	19.68	38.45	18.77	Н
847.50	-23.04	2.27	45.56	0.81	2.15	18.91	38.45	19.54	Н

# LTE Band 5\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.50	-22.49	2.25	45.77	0.93	2.15	19.81	38.45	18.64	Н
836.50	-22.20	2.26	45.66	0.82	2.15	19.87	38.45	18.58	Н
846.50	-23.14	2.26	45.56	0.82	2.15	18.83	38.45	19.62	Н

# LTE Band 5\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
829.00	-22.66	2.13	45.74	0.90	2.15	19.70	38.45	18.75	Н
836.50	-22.36	2.26	45.66	0.82	2.15	19.71	38.45	18.74	Н
844.00	-23.05	2.26	45.59	0.82	2.15	18.95	38.45	19.50	H





#### LTE Band 5\_1.4MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
824.70	-23.80	2.26	45.79	0.95	2.15	18.53	38.45	19.92	Н
836.50	-23.48	2.26	45.66	0.82	2.15	18.59	38.45	19.86	Н
848.30	-24.28	2.27	45.55	0.80	2.15	17.65	38.45	20.80	Н

# LTE Band 5\_3MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
825.50	-23.85	2.26	45.79	0.94	2.15	18.47	38.45	19.98	Н
836.50	-23.54	2.26	45.66	0.82	2.15	18.53	38.45	19.92	Н
847.50	-24.27	2.27	45.56	0.81	2.15	17.68	38.45	20.77	Н

# LTE Band 5\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
826.50	-23.80	2.25	45.77	0.93	2.15	18.50	38.45	19.95	Н
836.50	-23.53	2.26	45.66	0.82	2.15	18.54	38.45	19.91	Н
846.50	-24.28	2.26	45.56	0.82	2.15	17.69	38.45	20.76	Н

# LTE Band 5\_10MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
829.00	-23.87	2.13	45.74	0.90	2.15	18.49	38.45	19.96	Н
836.50	-23.48	2.26	45.66	0.82	2.15	18.59	38.45	19.86	Н
844.00	-24.26	2.26	45.59	0.82	2.15	17.74	38.45	20.71	Н





#### LTE Band 12 - ERP

**Limits:** ≤34.77dBm (3W)

# LTE Band 12\_1.4MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
699.70	-22.89	1.90	44.66	0.77	2.15	18.49	34.77	16.28	Н
707.50	-22.97	1.91	44.94	0.62	2.15	18.53	34.77	16.24	V
715.30	-23.07	1.92	45.26	0.50	2.15	18.62	34.77	16.15	V

# LTE Band 12\_3MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
700.50	-22.97	1.90	44.68	0.76	2.15	18.42	34.77	16.35	Н
707.50	-23.16	1.91	44.94	0.62	2.15	18.34	34.77	16.43	Н
714.50	-23.24	1.92	45.26	0.50	2.15	18.45	34.77	16.32	V

#### LTE Band 12\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
701.50	-23.05	1.90	44.81	0.74	2.15	18.45	34.77	16.32	Н
707.50	-23.16	1.91	44.94	0.62	2.15	18.34	34.77	16.43	V
713.50	-23.20	1.92	45.22	0.50	2.15	18.45	34.77	16.32	V

# LTE Band 12\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
704.00	-22.87	1.91	44.93	0.70	2.15	18.70	34.77	16.07	Н
707.50	-23.02	1.91	44.94	0.62	2.15	18.48	34.77	16.29	Н
711.00	-23.13	1.92	45.19	0.53	2.15	18.52	34.77	16.25	V





#### LTE Band 12\_1.4MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
699.70	-23.90	1.90	44.66	0.77	2.15	17.48	34.77	17.29	Н
707.50	-23.92	1.91	44.94	0.62	2.15	17.58	34.77	17.19	V
715.30	-24.15	1.92	45.26	0.50	2.15	17.54	34.77	17.23	V

# LTE Band 12\_3MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
700.50	-23.93	1.90	44.68	0.76	2.15	17.46	34.77	17.31	V
707.50	-24.02	1.91	44.94	0.62	2.15	17.48	34.77	17.29	Н
714.50	-24.26	1.92	45.26	0.50	2.15	17.43	34.77	17.34	V

# LTE Band 12\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
701.50	-23.84	1.90	44.81	0.74	2.15	17.66	34.77	17.11	Н
707.50	-23.98	1.91	44.94	0.62	2.15	17.52	34.77	17.25	Н
713.50	-24.17	1.92	45.22	0.50	2.15	17.48	34.77	17.29	V

#### LTE Band 12\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
704.00	-23.94	1.91	44.93	0.70	2.15	17.63	34.77	17.14	Н
707.50	-23.82	1.91	44.94	0.62	2.15	17.68	34.77	17.09	Н
711.00	-24.09	1.92	45.19	0.53	2.15	17.56	34.77	17.21	V





#### LTE Band 12\_1.4MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
699.70	-24.92	1.90	44.66	0.77	2.15	16.46	34.77	18.31	Н
707.50	-25.03	1.91	44.94	0.62	2.15	16.47	34.77	18.30	Н
715.30	-25.21	1.92	45.26	0.50	2.15	16.48	34.77	18.29	V

# LTE Band 12\_3MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
700.50	-24.90	1.90	44.68	0.76	2.15	16.49	34.77	18.28	Н
707.50	-25.08	1.91	44.94	0.62	2.15	16.42	34.77	18.35	V
714.50	-25.20	1.92	45.26	0.50	2.15	16.49	34.77	18.28	V

# LTE Band 12\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
701.50	-24.92	1.90	44.81	0.74	2.15	16.58	34.77	18.19	Н
707.50	-25.06	1.91	44.94	0.62	2.15	16.44	34.77	18.33	Н
713.50	-25.13	1.92	45.22	0.50	2.15	16.52	34.77	18.25	V

# LTE Band 12\_10MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
704.00	-24.90	1.91	44.93	0.70	2.15	16.67	34.77	18.10	Н
707.50	-25.02	1.91	44.94	0.62	2.15	16.48	34.77	18.29	Н
711.00	-25.12	1.92	45.19	0.53	2.15	16.53	34.77	18.24	V





#### LTE Band 14- ERP

**Limits**: ≤50dBm (100W)

# LTE Band 14\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
790.50	-21.74	2.02	45.71	0.18	2.15	19.98	34.77	14.79	V
793.00	-21.82	2.03	45.72	0.19	2.15	19.91	34.77	14.86	V
795.50	-21.85	2.03	45.74	0.20	2.15	19.91	34.77	14.86	V

#### LTE Band 14\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
793.00	-21.77	2.03	45.72	0.19	2.15	19.96	34.77	14.81	V

#### LTE Band 14\_5MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
790.50	-22.55	2.02	45.71	0.18	2.15	19.17	34.77	15.60	V
793.00	-22.72	2.03	45.72	0.19	2.15	19.01	34.77	15.76	V
795.50	-22.77	2.03	45.74	0.20	2.15	18.99	34.77	15.78	V

#### LTE Band 14\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Aq</sub> (dB)	C (dBi)	Correction	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
Frequency(MHZ)	F Mea (UDIII)	F <sub>cl</sub> (ub)	FAg(UB)	G <sub>a</sub> (dBi)	(dB)	ERF(UBIII)	Limit(dBin)	Margin(db)	Folalization
793.00	-22.68	2.03	45.72	0.19	2.15	19.05	34.77	15.72	V

#### LTE Band 14\_5MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
790.50	-23.60	2.02	45.71	0.18	2.15	18.12	34.77	16.65	Н
793.00	-23.76	2.03	45.72	0.19	2.15	17.97	34.77	16.80	Н
795.50	-23.81	2.03	45.74	0.20	2.15	17.95	34.77	16.82	Н

#### LTE Band 14\_10MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	Correction (dB)	ERP(dBm)	Limit(dBm)	Margin(dB)	Polarization
793.00	-23.72	2.03	45.72	0.19	2.15	18.01	34.77	16.76	Н





#### LTE Band 30- EIRP

**Limits:** ≤43 dBm (20W)

#### LTE Band 30\_5MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	G <sub>a</sub> (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2307.50	-23.57	3.48	44.55	5.52	23.02	43.00	19.98	Н
2310.00	-23.73	3.48	44.55	5.53	22.88	43.00	20.12	Н
2312.50	-23.98	3.48	44.56	5.54	22.63	43.00	20.37	Н

#### LTE Band 30\_10MHz\_QPSK

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization	
2310.00	-23.64	3.48	44.55	5.53	22.97	43.00	20.03	Н	

#### LTE Band 30\_5MHz\_16QAM

	Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
ſ	2307.50	-24.52	3.48	44.55	5.52	22.07	43.00	20.93	Н
ſ	2310.00	-24.71	3.48	44.55	5.53	21.90	43.00	21.10	Н
ſ	2312.50	-24.79	3.48	44.56	5.54	21.82	43.00	21.18	Н

#### LTE Band 30\_10MHz\_16QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2310.00	-24.63	3.48	44.55	5.53	21.98	43.00	21.02	Н

#### LTE Band 30\_5MHz\_64QAM

Ī	Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
Ī	2307.50	-25.90	3.48	44.55	5.52	20.69	43.00	22.31	Н
Ī	2310.00	-26.01	3.48	44.55	5.53	20.60	43.00	22.40	Н
ſ	2312.50	-26.23	3.48	44.56	5.54	20.38	43.00	22.62	Н

#### LTE Band 30\_10MHz\_64QAM

Frequency(MHz)	P <sub>Mea</sub> (dBm)	P <sub>cl</sub> (dB)	P <sub>Ag</sub> (dB)	Ga (dBi)	EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
2310.00	-25.96	3.48	44.55	5.53	20.65	43.00	22.35	Н

Peak EIRP(dBm) =  $P_{Mea}$ (-20.25dBm) -  $G_a$  (-5.04dBi) -  $P_{Ag}$  (-44.14dB) -  $P_{Cl}$  (3.76dB) = 25.17dBm Note: Expanded measurement uncertainty is U = 2.84 dB, k = 2.





#### A.2 EMISSION LIMIT


#### A.2.1 Measurement Method

The measurements procedures in TIA-603E-2016 are used. This measurement is carried out in fully-anechoic chamber FAC-3.


The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier. The resolution bandwidth is set 1MHz. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the LTE Bands 2 4 5 12 14 30.

#### The procedure of radiated spurious emissions is as follows:

1. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector.



- 2. The EUT is then put into continuously transmitting mode at its maximum power level during the test. And the maximum value of the receiver should be recorded as (Pr).
- 3. The EUT shall be replaced by a substitution antenna. The test setup refers to figure below.



In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere





with the radiation pattern of the antenna. A power ( $P_{Mea}$ ) is applied to the input of the substitution antenna. Adjust the level of the signal generator output until the value of the receiver reaches the previously recorded ( $P_r$ ). The power of signal source ( $P_{Mea}$ ) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.

- 4. The Path loss (P<sub>pl</sub>) between the Signal Source with the Substitution Antenna and the Substitution Antenna Gain (G<sub>a</sub>) should be recorded after test.
  - An amplifier should be connected in for the test.
  - The Path loss (Ppl) is the summation of the cable loss and the gain of the amplifier.
  - The measurement results are obtained as described below:
  - Power (EIRP)=P<sub>Mea</sub>+ P<sub>pl</sub> + G<sub>a</sub>
- 5. This value is EIRP since the measurement is calibrated using an antenna of known gain (unit: dBi) and known input power.
- 6. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP = EIRP -2.15dB.

#### A.2.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(m)(4) specifies for mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 27.53(c) states for operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB;(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than 65 +





10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

Part 27.53(a) states for mobile and portable stations operating in the 2305–2315 MHz and 2350–2360 MHz bands: By a factor of not less than: 43 +10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

Part 90.691 states that out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116Log<sub>10</sub>(f/6.1) decibels or 50 + 10 Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

#### A.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the LTE Bands 2 4 5 12 14 30. It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the LTE Bands 2 4 5 12 14 30 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this. The evaluated frequency range is from 30MHz to 26GHz.





### **Spot Check Measurement Results:**

# LTE Band 12, 1.4MHz, QPSK, Channel 23017

Fraguerov/MIJz)	D. (dDm)	Path	Antenna	Correction	Peak	Limit	Margin/dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1400.01	-47.47	3.24	4.98	2.15	-47.88	-13.00	34.88	V
2100.00	-55.53	4.19	4.90	2.15	-56.97	-13.00	43.97	Н
2790.00	-52.52	4.90	6.62	2.15	-52.95	-13.00	39.95	Н
3499.02	-55.73	5.52	8.20	2.15	-55.20	-13.00	42.20	Н
4201.02	-55.50	6.21	9.10	2.15	-54.76	-13.00	41.76	Н
4911.01	-55.25	6.73	9.81	2.15	-54.32	-13.00	41.32	Н

# LTE Band 12, 1.4MHz, QPSK, Channel 23095

Fragueray/MIJz)	D. (dDm)	Path	Antenna	Correction	Peak	Limit	Margin/dD)	Polarization	
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	FUIAITZALIUIT	
1415.01	-58.03	3.25	5.06	2.15	-58.37	-13.00	45.37	V	
2113.00	-54.58	4.20	4.94	2.15	-55.99	-13.00	42.99	Н	
2822.00	-52.20	4.94	6.68	2.15	-52.61	-13.00	39.61	V	
3537.02	-55.87	5.69	8.25	2.15	-55.46	-13.00	42.46	Н	
4233.02	-56.04	6.26	9.13	2.15	-55.32	-13.00	42.32	Н	
4958.01	-55.45	6.68	9.86	2.15	-54.42	-13.00	41.42	Н	

#### LTE Band 12, 1.4MHz, QPSK, Channel 23173

Fragueney/MUz)	D. (dPm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1431.01	-56.65	3.28	5.14	2.15	-56.94	-13.00	43.94	V
2131.00	-55.41	4.22	4.99	2.15	-56.79	-13.00	43.79	Н
2875.00	-51.50	4.97	6.78	2.15	-51.84	-13.00	38.84	V
3586.02	-55.36	6.19	8.32	2.15	-55.38	-13.00	42.38	Н
4305.02	-55.40	6.19	9.21	2.15	-54.53	-13.00	41.53	Н
5003.01	-55.79	6.60	9.90	2.15	-54.64	-13.00	41.64	V





# Reference Measurement Results from basic model:

# LTE Band 2, 1.4MHz, QPSK, Channel 18607

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
3702.02	-49.18	6.42	8.48	-47.12	-13.00	34.12	V
5555.02	-49.13	7.19	10.59	-45.73	-13.00	32.73	Н
7406.01	-53.20	8.13	12.09	-49.24	-13.00	36.24	Н
9262.01	-44.39	9.07	13.26	-40.20	-13.00	27.20	Н
11121.01	-46.56	9.74	13.18	-43.12	-13.00	30.12	Н
12942.01	-48.91	10.49	13.47	-45.93	-13.00	32.93	V

# LTE Band 2, 1.4MHz, QPSK, Channel 18900

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna	Peak	Limit(dBm)	Margin(dB)	Polarization
	, , ,		Gain(dBi)	EIRP(dBm)		9(4.2)	
3760.02	-50.45	6.26	8.56	-48.15	-13.00	35.15	V
5644.02	-46.62	7.27	10.57	-43.32	-13.00	30.32	Η
7524.01	-53.20	8.29	12.22	-49.27	-13.00	36.27	H
9409.01	-45.63	9.08	13.35	-41.36	-13.00	28.36	H
11297.01	-45.64	9.98	13.14	-42.48	-13.00	29.48	Н
13119.01	-48.30	10.85	13.67	-45.48	-13.00	32.48	V

#### LTE Band 2, 1.4MHz, QPSK, Channel 19193

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Peak	Limit(dBm)	Margin(dB)	Polarization	
1 requericy(ivii iz)	F Mea(GDIII)	Loss(dB)	Gain(dBi)	EIRP(dBm)	Limit(dbin)	Margin(db)		
3819.02	-53.14	6.08	8.65	-50.57	-13.00	37.57	V	
5733.02	-43.69	7.29	10.55	-40.43	-13.00	27.43	Н	
7643.01	-52.27	8.17	12.31	-48.13	-13.00	35.13	Н	
9558.01	-45.30	9.33	13.34	-41.29	-13.00	28.29	Н	
11478.01	-47.49	9.87	13.10	-44.26	-13.00	31.26	Н	
13394.01	-47.66	10.57	14.05	-44.18	-13.00	31.18	Н	





#### LTE Band 4, 1.4MHz QPSK, Channel 19957

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
3422.02	-49.57	5.38	8.01	-46.94	-13.00	33.94	Н
5138.02	-50.65	6.86	10.09	-47.42	-13.00	34.42	Н
6847.01	-51.01	7.83	11.42	-47.42	-13.00	34.42	V
8558.01	-49.16	8.57	13.01	-44.72	-13.00	31.72	Н
10303.01	-51.39	9.65	13.02	-48.02	-13.00	35.02	Н
12017.01	-49.09	10.10	13.01	-46.18	-13.00	33.18	Н

#### LTE Band 4, 1.4MHz, QPSK, Channel 20175

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
		` '	` ,	, ,			
3465.02	-49.05	5.46	8.12	-46.39	-13.00	33.39	V
5203.02	-42.15	6.96	10.18	-38.93	-13.00	25.93	Н
6935.01	-50.25	7.80	11.52	-46.53	-13.00	33.53	V
8667.01	-44.10	8.40	13.03	-39.47	-13.00	26.47	Н
10406.01	-49.07	9.79	13.06	-45.80	-13.00	32.80	V
12143.01	-48.50	10.22	13.06	-45.66	-13.00	32.66	Н

#### LTE Band 4, 1.4MHz, QPSK, Channel 20393

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path	Antenna	Peak	Limit(dBm)	Margin(dB)	Polarization	
Frequency(winz)	P Mea (UDIII)	Loss(dB)	Gain(dBi)	EIRP(dBm)	Lillil(GBIII)	Margin(ub)		
3509.02	-50.13	5.54	8.21	-47.46	-13.00	34.46	Н	
5266.02	-39.47	6.99	10.27	-36.19	-13.00	23.19	V	
7022.01	-51.58	8.27	11.63	-48.22	-13.00	35.22	V	
8776.01	-40.21	8.59	13.06	-35.74	-13.00	22.74	Н	
10539.01	-48.65	9.51	13.11	-45.05	-13.00	32.05	Н	
12241.01	-48.77	10.03	13.10	-45.70	-13.00	32.70	Н	





#### LTE Band 5, 1.4MHz, QPSK, Channel 20407

Fragueney/MHz)	D. (dPm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1660.01	-55.96	3.57	5.21	2.15	-56.47	-13.00	43.47	V
2463.00	-53.59	4.59	5.99	2.15	-54.34	-13.00	41.34	Н
3299.02	-54.84	5.29	7.72	2.15	-54.56	-13.00	41.56	V
4138.02	-55.77	6.07	9.04	2.15	-54.95	-13.00	41.95	V
4937.01	-55.38	6.71	9.84	2.15	-54.40	-13.00	41.40	V
5776.01	-54.41	7.23	10.54	2.15	-53.25	-13.00	40.25	Н

#### LTE Band 5, 1.4MHz, QPSK, Channel 20525

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
		` '	` '	` '	, ,	, ,		
1661.01	-59.26	3.57	5.21	2.15	-59.77	-13.00	46.77	Н
2515.00	-53.46	4.64	6.13	2.15	-54.12	-13.00	41.12	Н
3348.02	-52.17	5.32	7.84	2.15	-51.80	-13.00	38.80	Н
4172.02	-54.88	6.14	9.07	2.15	-54.10	-13.00	41.10	V
5020.01	-54.71	6.57	9.93	2.15	-53.50	-13.00	40.50	Н
5859.01	-53.70	7.26	10.53	2.15	-52.58	-13.00	39.58	Н

# LTE Band 5, 1.4MHz, QPSK, Channel 20643

Fragueney/MHz)	D. (dPm)	Path	Antenna	Correction	Peak	Limit	Margin(dB)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	ivialyili(ub)	Polarization
1697.01	-49.74	3.60	5.15	2.15	-50.34	-13.00	37.34	Н
2543.00	-52.27	4.66	6.18	2.15	-52.90	-13.00	39.90	Н
3381.02	-55.02	5.35	7.91	2.15	-54.61	-13.00	41.61	V
4232.02	-55.85	6.26	9.13	2.15	-55.13	-13.00	42.13	V
5089.01	-55.15	6.74	10.02	2.15	-54.02	-13.00	41.02	Н
5946.01	-53.48	7.47	10.51	2.15	-52.59	-13.00	39.59	Н





#### LTE Band 12, 1.4MHz, QPSK, Channel 23017

Fraguency/MHz)	D. (dPm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1400.01	-52.23	3.24	4.98	2.15	-52.64	-13.00	39.64	Н
2099.00	-54.22	4.19	4.90	2.15	-55.66	-13.00	42.66	Н
2795.00	-52.27	4.91	6.63	2.15	-52.70	-13.00	39.70	Н
3484.02	-55.16	5.49	8.16	2.15	-54.64	-13.00	41.64	Н
4192.02	-55.21	6.19	9.09	2.15	-54.46	-13.00	41.46	V
4904.01	-55.24	6.73	9.80	2.15	-54.32	-13.00	41.32	Н

#### LTE Band 12, 1.4MHz, QPSK, Channel 23095

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1415.01	-55.36	3.25	5.06	2.15	-55.70	-13.00	42.70	V
2123.00	-39.85	4.21	4.97	2.15	-41.24	-13.00	28.24	V
2834.00	-51.98	4.95	6.70	2.15	-52.38	-13.00	39.38	Н
3531.02	-55.13	5.63	8.24	2.15	-54.67	-13.00	41.67	V
4250.02	-55.72	6.24	9.15	2.15	-54.96	-13.00	41.96	V
4947.01	-55.16	6.69	9.85	2.15	-54.15	-13.00	41.15	V

# LTE Band 12, 1.4MHz, QPSK, Channel 23173

Fragueney/MHz)	D. (dPm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1431.01	-57.06	3.28	5.14	2.15	-57.35	-13.00	44.35	V
2146.00	-53.55	4.24	5.04	2.15	-54.90	-13.00	41.90	Н
2875.00	-51.56	4.97	6.78	2.15	-51.90	-13.00	38.90	V
3590.02	-55.12	6.24	8.33	2.15	-55.18	-13.00	42.18	V
4289.02	-54.47	6.20	9.19	2.15	-53.63	-13.00	40.63	Н
5018.01	-55.58	6.57	9.93	2.15	-54.37	-13.00	41.37	V





#### LTE Band 14, 5 MHz, QPSK, Channel 23305

Eroguanov/MHz)	D. (dDm)	Path	Antenna	Correction	Peak	Limit	Margin(dD)	Polarization
Frequency(MHz)	P <sub>Mea</sub> (dBm)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	Margin(dB)	Polarization
1587.01	-60.85	3.50	5.34	2.15	-61.16	-13.00	48.16	V
2384.00	-53.89	4.50	5.75	2.15	-54.79	-13.00	41.79	Н
3151.02	-53.82	5.37	7.36	2.15	-53.98	-13.00	40.98	Н
3961.02	-55.87	6.10	8.85	2.15	-55.27	-13.00	42.27	Н
4741.02	-54.24	6.55	9.64	2.15	-53.30	-13.00	40.30	Н
5520.01	-55.19	7.14	10.60	2.15	-53.88	-13.00	40.88	Н

# LTE Band 14, 5 MHz, QPSK, Channel 23330

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Correction (dB)	Peak ERP(dBm)	Limit (dBm)	Margin(dB)	Polarization
1587.01	-60.47	3.50	5.34	2.15	-60.78	-13.00	47.78	Н
2383.00	-53.78	4.50	5.75	2.15	-54.68	-13.00	41.68	V
3173.02	-54.38	5.34	7.42	2.15	-54.45	-13.00	41.45	Н
3958.02	-55.23	6.10	8.84	2.15	-54.64	-13.00	41.64	Н
4751.01	-53.50	6.57	9.65	2.15	-52.57	-13.00	39.57	Н
5562.01	-54.61	7.19	10.59	2.15	-53.36	-13.00	40.36	Н

# LTE Band 14, 5 MHz, QPSK, Channel 23355

Fragueney/MHz)	Frequency(MHz) P <sub>Mea</sub> (dBm)		Antenna	Correction	Peak	Limit	Margin(dB)	Polarization
Frequency(winz)	PMea(UDIII)	Loss(dB)	Gain(dBi)	(dB)	ERP(dBm)	(dBm)	ivialyili(ub)	Polarization
1591.01	-60.38	3.51	5.34	2.15	-60.70	-13.00	47.70	V
2389.00	-53.15	4.50	5.77	2.15	-54.03	-13.00	41.03	V
3170.02	-53.65	5.34	7.41	2.15	-53.73	-13.00	40.73	Н
3966.02	-55.30	6.09	8.85	2.15	-54.69	-13.00	41.69	Н
4776.01	-55.35	6.62	9.68	2.15	-54.44	-13.00	41.44	V
5558.01	-55.01	7.19	10.59	2.15	-53.76	-13.00	40.76	V





#### LTE Band 30, 5 MHz, QPSK, Channel 27685

Frequency(MHz)	P <sub>Mea</sub> (dBm)	Path Loss(dB)	Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
4617.02	-55.86	6.45	9.52	-52.79	-13.00	39.79	V
6923.01	-54.69	7.72	11.51	-50.90	-13.00	37.90	Н
9237.01	-49.22	9.01	13.24	-44.99	-13.00	31.99	Н
11554.01	-48.97	9.81	13.09	-45.69	-13.00	32.69	Н
13856.01	-47.41	10.72	14.41	-43.72	-13.00	30.72	Н
16165.00	-45.14	11.77	13.67	-43.24	-13.00	30.24	V

#### LTE Band 30, 5 MHz, QPSK, Channel 27710

Frequency(MHz)	ency(MHz) P <sub>Mea</sub> (dBm)		Antenna Gain(dBi)	Peak EIRP(dBm)	Limit(dBm)	Margin(dB)	Polarization
		Loss(dB)	Gain(dbi)	EIRP(abiii)			
4626.02	-55.60	6.44	9.53	-52.51	-13.00	39.51	Н
6934.01	-54.05	7.79	11.52	-50.32	-13.00	37.32	Н
9245.01	-50.89	9.03	13.25	-46.67	-13.00	33.67	V
11565.01	-49.52	9.80	13.09	-46.23	-13.00	33.23	Н
13858.01	-47.85	10.72	14.41	-44.16	-13.00	31.16	V
16175.00	-45.16	11.76	13.66	-43.26	-13.00	30.26	Н

#### LTE Band 30, 5 MHz, QPSK, Channel 27735

Frequency(MHz) P <sub>Mea</sub> (dBi	Du (dRm)	Path	Antenna	Peak	Limit(dBm)	Margin(dB)	Polarization	
	F Mea(UDIII)	Loss(dB)	Gain(dBi)	EIRP(dBm)		Margin(db)	Folalization	
4638.02	-56.04	6.45	9.54	-52.95	-13.00	39.95	V	
6938.01	-55.03	7.82	11.53	-51.32	-13.00	38.32	V	
9262.01	-51.28	9.07	13.26	-47.09	-13.00	34.09	Н	
11572.01	-49.61	9.80	13.09	-46.32	-13.00	33.32	V	
13861.01	-48.17	10.73	14.42	-44.48	-13.00	31.48	V	
16182.00	-45.56	11.75	13.66	-43.65	-13.00	30.65	V	

Note: The maximum value of expanded measurement uncertainty for this test item is U = 5.16 dB, k = 2.





#### A.3 FREQUENCY STABILITY

#### A.3.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMW500 DIGITAL RADIO COMMUNICATION TESTER.

- 1. Measure the carrier frequency at room temperature.
- Subject the EUT to overnight soak at -10°C.
   With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on middle channel for LTE band 2 4 5 12 14 30, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 4. Repeat the above measurements at 10°C increments from -10°C to +50°C. Allow at least 1.5
- 5. Reursætsæælcæriærefræturen og pat wæredterfærættaækiwighmærsirreh væltæge. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments re-measuring carrier frequency at each voltage. Pause at nominal voltage for 1.5 hours unpowered, to allow any self-heating to stabilize, before continuing.
- Subject the EUT to overnight soak at +50°C.
   With the EUT, powered via nominal voltage, connected to the CMW500 and in a simulated call on the centre channel, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
- 8. Repeat the above measurements at 10 °Cincrements from -10°C to +50°C. Allow at least 1.5
- hours at each temperature, unpowered, before making measurements.

  9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.4VDC, with a nominal voltage of 3.85VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress.





#### A.3.2 Measurement results

# LTE Band 2, 1.4MHz bandwidth (worst case of all bandwidths)

Frequency Error vs Voltage

Voltage	Free	quency error (F	Hz)	Frequency error (ppm)			
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
3.5	-19.45	-43.23	-14.30	0.0103	0.0230	0.008	
3.85	-19.17	-38.88	-16.80	0.0102	0.0207	0.009	
4.4	-17.90	-37.54	-20.20	0.0095	0.0200	0.011	

#### **Frequency Error vs Temperature**

Temperature	Free	quency error (ł	Hz)	Frequency error (ppm)			
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
50	-18.98	-40.77	-17.30	0.0101	0.0217	0.009	
40	-15.52	-40.78	-16.60	0.0083	0.0217	0.009	
30	-18.05	50.37	-18.10	0.0096	0.0268	0.010	
20	-15.56	-40.33	-11.30	0.0083	0.0215	0.006	
10	-19.83	-44.19	-15.10	0.0105	0.0235	0.008	
0	-20.28	-40.14	-10.60	0.0108	0.0214	0.006	
-10	-14.95	-43.23	-24.30	0.0080	0.0230	0.013	

# LTE Band 4, 1.4MHz bandwidth (worst case of all bandwidths)

**Frequency Error vs Voltage** 

Voltage	F	requency error	(Hz)	Frequency error (ppm)			
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
3.5	-22.19	-27.08	-15.20	0.0128	0.0156	0.009	
3.85	-19.68	-43.44	-27.80	0.0114	0.0251	0.016	
4.4	-22.73	-37.81	-22.70	0.0131	0.0218	0.013	

### **Frequency Error vs Temperature**

Temperature	Freq	uency error (H	z)	Frequency error (ppm)			
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
50	-23.90	-37.47	-14.10	0.0138	0.0216	0.008	
40	-22.57	-30.61	-21.70	0.0130	0.0177	0.013	
30	-25.32	-35.05	-16.60	0.0146	0.0202	0.010	
20	-31.27	34.06	-14.30	0.0180	0.0197	0.008	
10	-27.79	-40.56	-15.90	0.0160	0.0234	0.009	
0	-24.93	-37.51	-18.40	0.0144	0.0217	0.011	
-10	-23.69	-38.37	-17.50	0.0137	0.0221	0.010	





# LTE Band 5, 1.4MHz bandwidth (worst case of all bandwidths) Frequency Error vs Voltage

Voltage	Fred	quency error (	Hz)	Frequency error (ppm)			
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
3.5	-15.89	-35.65	-10.80	0.0190	0.0426	0.013	
3.85	-9.04	-36.68	-7.50	0.0108	0.0438	0.009	
4.4	-16.01	-33.82	-11.30	0.0191	0.0404	0.014	

#### **Frequency Error vs Temperature**

Temperature	Fre	quency error (	Hz)	Frequency error (ppm)			
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
50	-13.25	-35.65	-8.20	0.0158	0.0426	0.010	
40	-12.10	-30.77	-14.10	0.0145	0.0368	0.017	
30	-11.52	-30.47	-12.80	0.0138	0.0364	0.015	
20	-11.20	-27.05	-8.70	0.0134	0.0323	0.010	
10	-14.10	-36.98	-10.20	0.0169	0.0442	0.012	
0	-10.53	-35.72	-9.90	0.0126	0.0427	0.012	
-10	-12.86	-34.85	-7.80	0.0154	0.0417	0.009	

# LTE Band 12, 5MHz bandwidth (worst case of all bandwidths)

#### Frequency Error vs Voltage

Voltage	Fred	quency error (I	Hz)	Frequency error (ppm)			
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
3.5	-13.36	-25.99	-11.40	0.0189	0.0367	0.016	
3.85	-15.76	-27.52	-9.60	0.0223	0.0389	0.014	
4.4	-13.66	-26.56	-8.20	0.0193	0.0375	0.012	

#### **Frequency Error vs Temperature**

Temperature	Frequency error (Hz)			Frequency error (ppm)		
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
50	-19.77	-23.35	-5.80	0.0279	0.0330	0.008
40	-14.96	-24.35	-7.80	0.0211	0.0344	0.011
30	-18.07	-26.59	-9.70	0.0255	0.0376	0.014
20	-15.05	-21.94	-10.90	0.0213	0.0310	0.015
10	-13.35	-24.81	-10.10	0.0189	0.0351	0.014
0	-12.12	-24.83	-8.30	0.0171	0.0351	0.012
-10	-11.93	-23.50	-5.90	0.0169	0.0332	0.008





# LTE Band 14, 5MHz bandwidth (worst case of all bandwidths) Frequency Error vs Voltage

Voltage	Frequency error (Hz)		Frequency error (ppm)			
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
3.5	-12.79	-24.98	-10.3	0.0161	0.0315	-0.0130
3.85	-11.77	-25.65	-9.9	0.0148	0.0323	-0.0125
4.4	-12.55	-19.40	-5.8	0.0158	0.0245	-0.0073

#### **Frequency Error vs Temperature**

Temperature	Frequency error (Hz)			Frequency error (ppm)		
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
50	-12.32	-23.69	-8.3	0.0155	0.0299	-0.0105
40	-13.78	-17.80	-9.7	0.0174	0.0224	-0.0122
30	-15.54	-15.61	-2.5	0.0196	0.0197	-0.0032
20	-16.89	-22.40	-7.4	0.0213	0.0282	-0.0093
10	-10.96	-26.04	-8.9	0.0138	0.0328	-0.0112
0	-15.68	-25.18	-12	0.0198	0.0318	-0.0151
-10	-11.54	-22.02	-7.6	0.0146	0.0278	-0.0096

# LTE Band 30, 5MHz bandwidth (worst case of all bandwidths)

#### Frequency Error vs Voltage

Voltage	Frequency error (Hz)			Freq	Frequency error (ppm)		
(V)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM	
3.5	-26.66	-37.34	-19.3	0.0115	0.0162	-0.0084	
3.85	-27.28	-42.20	-14.6	0.0118	0.0183	-0.0063	
4.4	-28.98	-31.40	-23.3	0.0125	0.0136	-0.0101	

# Frequency Error vs Temperature

Temperature	Frequency error (Hz)			Frequency error (ppm)		
(℃)	QPSK	16QAM	64QAM	QPSK	16QAM	64QAM
50	-31.79	-24.40	-22.9	0.0138	0.0106	-0.0099
40	-22.09	-36.19	-13.7	0.0096	0.0157	-0.0059
30	-30.60	-29.90	-17.2	0.0132	0.0129	-0.0074
20	-31.39	-33.87	-14.8	0.0136	0.0147	-0.0064
10	-25.11	-34.79	-33.6	0.0109	0.0151	-0.0145
0	-23.86	-34.79	-24.1	0.0103	0.0151	-0.0104
-10	21.72	-34.10	-23.6	0.0094	0.0148	-0.0102





#### A.4 OCCUPIED BANDWIDTH

#### A.4.1 Occupied Bandwidth Results

Occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the mid frequency. The table below lists the measured 99% BW. Spectrum analyzer plots are included on the following pages.

The measurement method is from ANSI C63.26:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts.
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set  $\geq$  3 × RBW.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
- d) Set the detection mode to peak, and the trace mode to max-hold.






#### LTE band 2, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
1880.0	QPSK	16QAM	64QAM	
	1089.74	1089.74	1089.74	

#### LTE band 2, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:29:05

#### LTE band 2, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:30:29





#### LTE band 2, 1.4MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:46:33






#### LTE band 2, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
1880.0	QPSK	16QAM	64QAM	
	2692.31	2692.31	2692.31	

#### LTE band 2, 3MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:32:43

# LTE band 2, 3MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:34:07





#### LTE band 2, 3MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:47:34






#### LTE band 2, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
1880.0	QPSK	16QAM	64QAM	
	4519.23	4519.23	4519.23	

#### LTE band 2, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:36:20

#### LTE band 2, 5MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:37:45





#### LTE band 2, 5MHz Bandwidth,64QAM (99% BW)



Date: 16.APR.2019 09:48:33






# LTE band 2, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
1880.0	QPSK	16QAM	64QAM	
	9038.46	9038.46	9038.46	

#### LTE band 2, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:39:58

# LTE band 2, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:41:23





# LTE band 2, 10MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:49:32






#### LTE band 2, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
1880.0	QPSK	16QAM	64QAM	
	13557.69	13557.69	13557.69	

#### LTE band 2, 15MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:43:37

#### LTE band 2, 15MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:45:01





# LTE band 2, 15MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:50:35






# LTE band 2, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
1880.0	QPSK	16QAM	64QAM	
	17980.77	17980.77	17980.77	

#### LTE band 2, 20MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:47:15

# LTE band 2, 20MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:48:39





#### LTE band 2, 20MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:51:32






#### LTE band 4, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)			
1732.5	QPSK	16QAM	64QAM	
	1097.76	1097.76	1089.74	

#### LTE band 4, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:51:33

# LTE band 4, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:52:57





# LTE band 4, 1.4MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:56:11






#### LTE band 4, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
4722.5	QPSK	16QAM	64QAM
1732.5	2692.31	2692.31	2692.31

### LTE band 4, 3MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:54:23

# LTE band 4, 3MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:55:48





# LTE band 4, 3MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:57:16






# LTE band 4, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
4700 5	QPSK	16QAM	64QAM
1732.5	4543.27	4519.23	4495.19

### LTE band 4, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 18:57:13

# LTE band 4, 5MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 18:58:38





# LTE band 4, 5MHz Bandwidth,64QAM (99% BW)



Date: 16.APR.2019 09:58:34






# LTE band 4, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
4700 5	QPSK	16QAM	64QAM
1732.5	8990.38	8990.38	9038.46

### LTE band 4, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:00:04

# LTE band 4, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:01:28





# LTE band 4, 10MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:59:51






# LTE band 4, 15MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
4722.5	QPSK	16QAM	64QAM
1732.5	13485.58	13557.69	13557.69

### LTE band 4, 15MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:02:54

# LTE band 4, 15MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:04:19





# LTE band 4, 15MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 10:01:20






# LTE band 4, 20MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
4700 5	QPSK	16QAM	64QAM
1732.5	17980.77	17980.77	17980.77

### LTE band 4, 20MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:06:33

# LTE band 4, 20MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:07:58





# LTE band 4, 20MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 10:02:27






#### LTE band 5, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
926 5	QPSK	16QAM	64QAM
836.5	1097.76	1097.76	1089.74

### LTE band 5, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:10:12

### LTE band 5, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:11:37





# LTE band 5, 1.4MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:37:13






#### LTE band 5, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
020.5	QPSK	16QAM	64QAM
836.5	2692.31	2692.31	2692.31

### LTE band 5, 3MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:13:51

#### LTE band 5, 3MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:15:15





# LTE band 5, 3MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:39:21






#### LTE band 5, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
000 5	QPSK	16QAM	64QAM
836.5	4519.23	4519.23	4519.23

### LTE band 5, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:17:29

#### LTE band 5, 5MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:18:54





# LTE band 5, 5MHz Bandwidth,64QAM (99% BW)



Date: 16.APR.2019 09:40:24






# LTE band 5, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
000 5	QPSK	16QAM	64QAM
836.5	8990.38	8990.38	8990.38

### LTE band 5, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:21:07

#### LTE band 5, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:22:32





# LTE band 5, 10MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 09:41:27






#### LTE band 12, 1.4MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
707.5	QPSK	16QAM	64QAM
707.5	1097.76	1097.76	1089.74

### LTE band 12, 1.4MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:24:46

# LTE band 12, 1.4MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:26:11





# LTE band 12, 1.4MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 10:07:28






#### LTE band 12, 3MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
707.5	QPSK	16QAM	64QAM
707.5	2692.31	2692.31	2692.31

### LTE band 12, 3MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:28:25

# LTE band 12, 3MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:29:49





# LTE band 12, 3MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 10:11:12






#### LTE band 12, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
707.5	QPSK	16QAM	64QAM
707.5	4543.27	4519.23	4495.19

### LTE band 12, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:32:03

#### LTE band 12, 5MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:33:28





# LTE band 12, 5MHz Bandwidth,64QAM (99% BW)



Date: 16.APR.2019 10:13:03






#### LTE band 12, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
707.5	QPSK	16QAM	64QAM
	9038.46	9038.46	9038.46

### LTE band 12, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:35:41

### LTE band 12, 10MHz Bandwidth, 16QAM (99% BW)




Date: 15.APR.2019 19:37:06





# LTE band 12, 10MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 10:14:25






#### LTE band 14, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
793.0	QPSK	16QAM	64QAM
	4519.23	4519.23	4519.23

### LTE band 14, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:39:21

### LTE band 14, 5MHz Bandwidth,16QAM (99% BW)




Date: 15.APR.2019 19:40:46





# LTE band 14, 5MHz Bandwidth,64QAM (99% BW)



Date: 16.APR.2019 10:18:04






#### LTE band 14, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
793.0	QPSK	16QAM	64QAM
	9038.46	9038.46	8990.38

### LTE band 14, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:43:00

# LTE band 14, 10MHz Bandwidth,16QAM (99% BW)




Date: 15.APR.2019 19:44:24





# LTE band 14, 10MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 10:19:49






#### LTE band 30, 5MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
2310.0	QPSK	16QAM	64QAM
	4519.23	4519.23	4519.23

### LTE band 30, 5MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:46:40

# LTE band 30, 5MHz Bandwidth,16QAM (99% BW)




Date: 15.APR.2019 19:48:04





# LTE band 30, 5MHz Bandwidth,64QAM (99% BW)



Date: 16.APR.2019 10:25:26






#### LTE band 30, 10MHz (99%)


Frequency(MHz)	Occupied Bandwidth (99%)( kHz)		
2310.0	QPSK	16QAM	64QAM
	8990.38	8990.38	8990.38

### LTE band 30, 10MHz Bandwidth, QPSK (99% BW)



Date: 15.APR.2019 19:50:18

# LTE band 30, 10MHz Bandwidth,16QAM (99% BW)




Date: 15.APR.2019 19:51:43





# LTE band 30, 10MHz Bandwidth, 64QAM (99% BW)



Date: 16.APR.2019 10:26:48





#### A.5 EMISSION BANDWIDTH

#### A.5.1Emission Bandwidth Results

The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages. The measurement method is from ANSI C63.26:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts.
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set ≥ 3 × RBW.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation.
- d) Set the detection mode to peak, and the trace mode to max-hold.






#### LTE band 2, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1880.0	QPSK	16QAM	64QAM
	1306.09	1290.06	1290.06

#### LTE band 2, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 19:53:43

### LTE band 2, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 19:55:08





### LTE band 2, 1.4MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:46:54






### LTE band 2, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1880.0	QPSK	16QAM	64QAM
1860.0	2884.62	2900.64	2900.64

#### LTE band 2, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 19:57:22

### LTE band 2, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 19:58:47





# LTE band 2, 3MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:47:53






#### LTE band 2, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1880.0	QPSK 16QA	16QAM	64QAM
1660.0	5072.12	5120.19	5096.15

### LTE band 2, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:01:01

### LTE band 2, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:02:26





### LTE band 2, 5MHz Bandwidth,64QAM (-26dBc BW)



Date: 16.APR.2019 09:48:52






### LTE band 2, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1880.0	QPSK	16QAM	64QAM
1660.0	10000.00	10048.08	9903.85

### LTE band 2, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:04:40

### LTE band 2, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:06:05





# LTE band 2, 10MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:49:50






#### LTE band 2, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1880.0	QPSK 16QAM	16QAM	64QAM
1860.0	15216.35	15072.12	15072.12

### LTE band 2, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:08:19

### LTE band 2, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:09:44





# LTE band 2, 15MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:50:53






### LTE band 2, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1880.0	QPSK 16QAM	16QAM	64QAM
1660.0	19423.08	19615.38	19519.23

### LTE band 2, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:11:59

### LTE band 2, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:13:24





# LTE band 2, 20MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:51:51






### LTE band 4, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1732.5	QPSK 16QAM	64QAM	
1732.3	1282.05	1306.09	1306.09

### LTE band 4, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:15:39

### LTE band 4, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:17:04





# LTE band 4, 1.4MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:56:32






#### LTE band 4, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1732.5	QPSK 16QAM	64QAM	
1732.3	2900.64	2900.64	2900.64

### LTE band 4, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:18:31

### LTE band 4, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:19:56





# LTE band 4, 3MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:57:34






#### LTE band 4, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1732.5	QPSK 16QAM	64QAM	
1732.3	5120.19	5096.15	5144.23

### LTE band 4, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:21:22

# LTE band 4, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:22:47





# LTE band 4, 5MHz Bandwidth,64QAM (-26dBc BW)



Date: 16.APR.2019 09:58:55






### LTE band 4, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1732.5	QPSK 16QAM	64QAM	
1732.3	10096.15	10000.00	9855.77

### LTE band 4, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:25:01

### LTE band 4, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:26:26





# LTE band 4, 10MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 10:00:12






### LTE band 4, 15MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
4722 F	QPSK	16QAM	64QAM
1732.5	15072.12	15072.12	15144.23

### LTE band 4, 15MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:28:40

### LTE band 4, 15MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:30:05





# LTE band 4, 15MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 10:01:39






### LTE band 4, 20MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
1732.5	QPSK 16QAM		64QAM
1732.3	19807.69	19615.38	19615.38

### LTE band 4, 20MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:31:32

### LTE band 4, 20MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:32:57





# LTE band 4, 20MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 10:02:45






### LTE band 5, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
926 5	QPSK	16QAM	64QAM
836.5	1290.06	1306.09	1266.03

### LTE band 5, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:35:13

# LTE band 5, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:36:38





# LTE band 5, 1.4MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:38:20






#### LTE band 5, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
836.5	QPSK	16QAM	64QAM
	2884.62	2884.62	2884.62

### LTE band 5, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:38:52

### LTE band 5, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:40:17





# LTE band 5, 3MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:39:41






#### LTE band 5, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
836.5	QPSK	16QAM	64QAM
	5144.23	5072.12	5000.00

### LTE band 5, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:42:31

### LTE band 5, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:43:57





# LTE band 5, 5MHz Bandwidth,64QAM (-26dBc BW)



Date: 16.APR.2019 09:40:43






#### LTE band 5, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
836.5	QPSK	16QAM	64QAM
	10096.15	10048.08	9855.77

### LTE band 5, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:46:11

### LTE band 5, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:47:36





# LTE band 5, 10MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 09:41:47






#### LTE band 12, 1.4MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
707.5	QPSK	16QAM	64QAM
	1298.08	1298.08	1282.05

### LTE band 12, 1.4MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:49:51

### LTE band 12, 1.4MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:51:16





# LTE band 12, 1.4MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 10:07:50






#### LTE band 12, 3MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
707.5	QPSK	16QAM	64QAM
	2900.64	2900.64	2884.62

### LTE band 12, 3MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:53:31

### LTE band 12, 3MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:54:56





# LTE band 12, 3MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 10:12:23






#### LTE band 12, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
707.5	QPSK	16QAM	64QAM
	5192.31	5144.23	4975.96

### LTE band 12, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 20:57:10

### LTE band 12, 5MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 20:58:35





# LTE band 12, 5MHz Bandwidth,64QAM (-26dBc BW)



Date: 16.APR.2019 10:13:41






#### LTE band 12, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
707 5	QPSK	16QAM	64QAM
707.5	10000.00	10144.23	9855.77

# LTE band 12, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 21:00:49

# LTE band 12, 10MHz Bandwidth, 16QAM (-26dBc BW)




Date: 15.APR.2019 21:02:14





# LTE band 12, 10MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 10:14:48






#### LTE band 14, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
702.0	QPSK	16QAM	64QAM
793.0	5144.23	5120.19	5048.08

# LTE band 14, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 21:04:30

# LTE band 14, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 15.APR.2019 21:05:55





# LTE band 14, 5MHz Bandwidth,64QAM (-26dBc BW)



Date: 16.APR.2019 10:18:52






#### LTE band 14, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
702.0	QPSK	16QAM	64QAM
793.0	10048.08	10000.00	9855.77

# LTE band 14, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 21:08:09

# LTE band 14, 10MHz Bandwidth,16QAM (-26dBc BW)




Date: 15.APR.2019 21:09:34





# LTE band 14, 10MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 10:20:09






#### LTE band 30, 5MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
2310.0	QPSK	16QAM	64QAM
2310.0	5168.27	5048.08	5000.00

# LTE band 30, 5MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 21:11:50

# LTE band 30, 5MHz Bandwidth,16QAM (-26dBc BW)




Date: 15.APR.2019 21:13:15





# LTE band 30, 5MHz Bandwidth,64QAM (-26dBc BW)



Date: 16.APR.2019 10:25:49






# LTE band 30, 10MHz (-26dBc)


Frequency(MHz)	Occupied Bandwidth (-26dBc)( kHz)		
2310.0	QPSK	16QAM	64QAM
2310.0	10048.08	10048.08	9855.77

# LTE band 30, 10MHz Bandwidth, QPSK (-26dBc BW)



Date: 15.APR.2019 21:15:30

# LTE band 30, 10MHz Bandwidth,16QAM (-26dBc BW)




Date: 15.APR.2019 21:16:55





# LTE band 30, 10MHz Bandwidth, 64QAM (-26dBc BW)



Date: 16.APR.2019 10:27:14





# A.6 BAND EDGE COMPLIANCE

#### A.6.1 Measurement limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to KDB 971168, a relaxation of the reference bandwidth is often provided for measurements within a specified frequency range at the edge of the authorized frequency block/band. This is often implemented by permitting the use of a narrower RBW (typically limited to a minimum RBW of 1% of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(a) states for mobile and portable stations operating in the 2305–2315 MHz and 2350–2360 MHz bands: By a factor of not less than: 43 +10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.


Part 90.691 states that out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116Log<sub>10</sub>(f/6.1) decibels or 50 + 10 Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.






# A.6.2 Measurement result Only worst case result is given below LTE band 2

OBW: 1RB-low\_offset



Date: 24.APR.2019 13:39:37

# LOW BAND EDGE BLOCK-1RB-low\_offset




Date: 24.APR.2019 13:39:53






# OBW: 1RB-high\_offset



Date: 24.APR.2019 13:42:28

# HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 24.APR.2019 13:42:44






#### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 24.APR.2019 13:40:29

# HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 24.APR.2019 13:43:20






# LTE band 4

# OBW: 1RB-low\_offset



Date: 24.APR.2019 13:45:25

# LOW BAND EDGE BLOCK-1RB-low\_offset




Date: 24.APR.2019 13:45:40






# OBW: 1RB-high\_offset



Date: 24.APR.2019 14:00:58

# HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 24.APR.2019 14:01:13






#### LOW BAND EDGE BLOCK-20MHz-100%RB



Date: 24.APR.2019 13:46:59

# HIGH BAND EDGE BLOCK-20MHz-100%RB




Date: 24.APR.2019 14:02:33






#### LTE band 5

# OBW: 1RB-low\_offset



Date: 24.APR.2019 14:04:43

# LOW BAND EDGE BLOCK-1RB-low\_offset




Date: 24.APR.2019 14:04:59






# OBW: 1RB-high\_offset



Date: 24.APR.2019 14:07:34

# HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 24.APR.2019 14:07:50






#### LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 24.APR.2019 14:05:35

# HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 24.APR.2019 14:08:26






# LTE band 12

# OBW: 1RB-low\_offset



Date: 24.APR.2019 14:14:48

# LOW BAND EDGE BLOCK-1RB-low\_offset




Date: 24.APR.2019 14:15:03






# OBW: 1RB-high\_offset



Date: 24.APR.2019 14:18:21

# HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 24.APR.2019 14:18:37






#### LOW BAND EDGE BLOCK-10MHz-100%RB



Date: 24.APR.2019 14:16:22

# HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 24.APR.2019 14:19:13






LTE band 14
OBW: 1RB-low\_offset



Date: 24.APR.2019 14:32:52

# LOW BAND EDGE BLOCK-1RB-low\_offset




Date: 24.APR.2019 14:34:31





# LOW Emission Mask -1RB-low\_offset




Date: 24.APR.2019 14:35:04






# OBW: 1RB-high\_offset



Date: 24.APR.2019 14:46:32

# HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 24.APR.2019 14:47:09





# HIGH Emission Mask -1RB-high\_offset




Date: 24.APR.2019 14:47:31






#### LOW Emission Mask -10MHz-100%RB



Date: 24.APR.2019 14:44:00

#### LOW BAND EDGE BLOCK-10MHz-100%RB




Date: 24.APR.2019 14:44:33






#### HIGH Emission Mask -10MHz-100%RB



Date: 24.APR.2019 14:50:27

#### HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 24.APR.2019 14:50:48






#### LTE band 30

# OBW: 1RB-low\_offset



Date: 24.APR.2019 14:22:43


# LOW BAND EDGE BLOCK-1RB-low\_offset




Date: 24.APR.2019 14:23:03







Date: 24.APR.2019 14:23:28




Date: 24.APR.2019 14:23:40





# OBW: 1RB-high\_offset




Date: 24.APR.2019 14:26:55






# HIGH BAND EDGE BLOCK-1RB-high\_offset




Date: 24.APR.2019 14:27:16




Date: 24.APR.2019 14:27:48







Date: 26.APR.2019 11:31:59




Date: 24.APR.2019 14:28:09






# LOW BAND EDGE BLOCK-10MHz-100%RB




Date: 26.APR.2019 14:16:29



Date: 26.APR.2019 14:22:25








Date: 26.APR.2019 14:22:36






#### HIGH BAND EDGE BLOCK-10MHz-100%RB




Date: 26.APR.2019 11:30:35



Date: 26.APR.2019 11:31:47







Date: 26.APR.2019 11:31:59





# A.7 CONDUCTED SPURIOUS EMISSION

#### A.7.1 Measurement Method

The following steps outline the procedure used to measure the conducted emissions from the EUT.

- 1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the mobile station equipment tested, this equates to a frequency range of 13 MHz to 9 GHz, data taken from 10 MHz to 25 GHz.
- 2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.
- 3. The number of sweep points of spectrum analyzer is set to 30001 which is greater than span/RBW.

#### A. 7.2 Measurement Limit

Part 22.917, Part 24.238 and Part 27.53(h) specify that the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

The specification that emissions shall be attenuated below the transmitter power (P) by at least 43 + 10 log (P) dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.

Part 27.53(a) states for mobile and portable stations operating in the 2305–2315 MHz and 2350–2360 MHz bands: By a factor of not less than: 43 +10 log (P) dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than 55 + 10 log (P) dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than 61 + 10 log (P) dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than 67 + 10 log (P) dB on all frequencies between 2328 and 2337MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2300 and 2305 MHz, 55 + 10 log (P) dB on all frequencies between 2292 and 2296 MHz, 67 + 10 log (P) dB on all frequencies between 2288 and 2292 MHz, and 70 + 10 log (P) dB below 2288 MHz; By a factor of not less than 43 + 10 log (P) dB on all frequencies between 2360 and 2365 MHz, and not less than 70 + 10 log (P) dB above 2365 MHz.

Part 90.691 states that out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116Log<sub>10</sub>(f/6.1) decibels or 50 + 10 Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed






from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz. For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log<sub>10</sub>(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.






# A. 7.2 Measurement result Only worst case result is given below

# LTE band 2: 30MHz - 19.15GHz



Date: 24.APR.2019 14:54:50

# LTE band 4: 30MHz - 17.8GHz




Date: 24.APR.2019 14:57:22






# LTE band 5: 30MHz - 8.49GHz



Date: 24.APR.2019 14:59:26

# LTE band 12: 30MHz - 7.46GHz




Date: 24.APR.2019 15:01:06






# LTE band 14: 30MHz - 7.98GHz



Date: 24.APR.2019 15:03:31

# LTE band 30: 30MHz - 23.15GHz



Date: 24.APR.2019 15:43:23





# A.8 PEAK-TO-AVERAGE POWER RATIO

The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13 dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

- a)Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- b) Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- c) Set the number of counts to a value that stabilizes the measured CCDF curve;
- d) Set the measurement interval to 1 ms
- e)Record the maximum PAPR level associated with a probability of 0.1%

#### A.8.1 Measurement limit

not exceed 13 dB

#### A.8.2 Measurement results

#### LTE band 2, 20MHz

Frequency(MHz)	PAPR(dB)		
1960.0	QPSK	16QAM	64QAM
1860.0	6.79	7.34	8.62

#### LTE band 4, 20MHz

Frequency(MHz)	PAPR(dB)		
1745 0	QPSK	16QAM	64QAM
1745.0	6.60	7.21	8.49

#### LTE band 12,10MHz

Frequency(MHz)	PAPR(dB)		
707.5	QPSK	16QAM	64QAM
	5.54	6.19	8.33

#### LTE band 30,10MHz

Frequency(MHz)	PAPR(dB)		
2240.0	QPSK	16QAM	64QAM
2310.0	5.54	6.31	8.59





# **ANNEX B: Accreditation Certificate**

United States Department of Commerce National Institute of Standards and Technology



# Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 600118-0

#### Telecommunication Technology Labs, CAICT

Beijing China

is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:

#### **Electromagnetic Compatibility & Telecommunications**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.

This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).

2019-09-26 through 2020-09-30

Effective Dates



For the National Voluntary Laboratory Accreditation Program

\*\*\*END OF REPORT\*\*\*