



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM161201122603
Page: 1 of 69

TEST REPORT

Application No.: SZEM1612011226CR
Applicant: TEAC Corporation
Address of Applicant: 1-47 Ochiai, Tama-shi, Tokyo, Japan
Manufacturer: TEAC Corporation
Address of Manufacturer: 1-47 Ochiai, Tama-shi, Tokyo, Japan
Factory: DONGGUAN TEAC ELECTRONICS CO., LTD.
Address of Factory: Shang-sha, Chang-An District, Dong Guan , Guang Dong, China
Equipment Under Test (EUT):
EUT Name: USB DAC/Integrated Amplifier
Model No.: AI-503
Trade mark: TEAC
IC: 1559C-AI503
Standards: RSS 247
RSS Gen Issue 4
Date of Receipt: 2017-03-01
Date of Test: 2017-03-03 to 2017-04-19
Date of Issue: 2017-05-03

Test Result :	Pass*
----------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.





Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2017-05-03		Original

Authorized for issue by:				
Tested By				2017-05-03
		Bill Chen /Project Engineer		Date
Checked By				2017-05-03
		Eric Fu /Reviewer		Date



2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	RSS 247	N/A	N/A	Pass
N/A: Not applicable				

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Disturbance at AC Power Line (150kHz-30MHz)	RSS 247	ANSI C63.10 (2013) Section 6.2	RSS-Gen Section 8.8	Pass
Conducted Peak Output Power	RSS 247	ANSI C63.10 (2013) Section 11.9.1	RSS-247 Section 5.4(2)	Pass
Minimum 6dB Bandwidth	RSS 247	ANSI C63.10 (2013) Section 11.8.1	RSS-247 Section 5.2(1)	Pass
Power Spectrum Density	RSS 247	ANSI C63.10 (2013) Section 11.10.2	RSS-247 Section 6.2.1(1)&6.2.2(1)&6.2.3(1)&6.2.4(1)	Pass
Conducted Spurious Emissions	RSS 247	ANSI C63.10 (2013) Section 7.8.6	RSS-247 Section 5.5	Pass
Radiated Spurious Emissions	RSS 247	ANSI C63.10 (2013) Section 6.4&6.5&6.6	RSS-Gen Section 8.8	Pass
Radiated Emissions which fall in the restricted bands	RSS 247	ANSI C63.10 (2013) Section 6.4&6.5&6.6	RSS-Gen Section 8.8	Pass
Conducted Band Edges Measurement	RSS 247	ANSI C63.10 (2013) Section 7.8.8	RSS-247 Section 5.5	Pass
20dB Bandwidth	RSS 247	ANSI C63.10 (2013) Section 6.9	RSS-Gen Section 6.6	Pass

N/A: Not applicable



3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	6
4.1 DETAILS OF E.U.T.	6
4.2 DESCRIPTION OF SUPPORT UNITS	8
4.3 MEASUREMENT UNCERTAINTY.....	8
4.4 TEST LOCATION.....	9
4.5 TEST FACILITY	9
4.6 DEVIATION FROM STANDARDS	9
4.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	9
5 EQUIPMENT LIST.....	10
6 RADIO SPECTRUM TECHNICAL REQUIREMENT.....	13
6.1 ANTENNA REQUIREMENT.....	13
6.1.1 Test Requirement:	13
6.1.2 Conclusion	13
7 RADIO SPECTRUM MATTER TEST RESULTS.....	14
7.1 CONDUCTED DISTURBANCE AT AC POWER LINE(150kHz-30MHz).....	14
7.1.1 E.U.T. Operation	15
7.1.2 Test Setup Diagram	15
7.1.3 Measurement Data.....	15
7.2 CONDUCTED PEAK OUTPUT POWER.....	18
7.2.1 E.U.T. Operation	19
7.2.2 Test Setup Diagram	19
7.2.3 Measurement Data.....	19
7.3 MINIMUM 6dB BANDWIDTH	20
7.3.1 E.U.T. Operation	20
7.3.2 Test Setup Diagram	20
7.3.3 Measurement Data.....	20
7.4 POWER SPECTRUM DENSITY.....	21
7.4.1 E.U.T. Operation	21
7.4.2 Test Setup Diagram	21
7.4.3 Measurement Data.....	21
7.5 CONDUCTED SPURIOUS EMISSIONS.....	22
7.5.1 E.U.T. Operation	23
7.5.2 Test Setup Diagram	23
7.5.3 Measurement Data.....	23
7.6 RADIATED SPURIOUS EMISSIONS.....	24
7.6.1 E.U.T. Operation	25
7.6.2 Test Setup Diagram	25
7.6.3 Measurement Data.....	26
7.7 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	32
7.7.1 E.U.T. Operation	33
7.7.2 Test Setup Diagram	33
7.7.3 Measurement Data.....	33



7.8	CONDUCTED BAND EDGES MEASUREMENT	38
7.8.1	<i>E.U.T. Operation</i>	39
7.8.2	<i>Test Setup Diagram</i>	39
7.8.3	<i>Measurement Data</i>	39
7.9	20dB BANDWIDTH	40
7.9.1	<i>E.U.T. Operation</i>	40
7.9.2	<i>Test Setup Diagram</i>	40
7.9.3	<i>Measurement Data</i>	40
8	PHOTOGRAPHS	41
8.1	CONDUCTED DISTURBANCE AT AC POWER LINE(150kHz-30MHz) TEST SETUP	41
8.2	RADIATED SPURIOUS EMISSIONS TEST SETUP	42
8.3	EUT CONSTRUCTIONAL DETAILS	43
9	APPENDIX	44
9.1	APPENDIX RSS247	44-69



4 General Information

4.1 Details of E.U.T.

Frequency Range:	2402MHz to 2480MHz
Bluetooth Version:	V4.0 dual mode
	This test report is for BLE mode.
Modulation Type:	GFSK
Number of Channels:	40
Sample Type:	Fixed production
Antenna Type:	PCB Pattern Antenna
Antenna Gain:	-3dBi
Power supply:	AC 120V 60Hz
	DC 3V (1.5V*2 Size "AAA" batteries) for remote control
Rated power	38W
Cable:	AC cable:200cm Unshielded
Internal source	240MHz

4.2 Test Environment

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel (CH0)	2402MHz
The middle channel (CH19)	2440MHz
The highest channel (CH39)	2480MHz



4.3 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Laptop	Lenovo	T430u
Test board	Supply to SGS	FT232

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10-8
2	Duty cycle	0.37%
3	Occupied Bandwidth	3%
4	RF conducted power	0.75dB
5	RF power density	2.84dB
6	Conducted Spurious emissions	0.75dB
7	RF Radiated power	4.5dB (below 1GHz)
8		4.8dB (above 1GHz)
9	Radiated Spurious emission test	4.5dB (30MHz-1GHz)
		4.8dB (1GHz-18GHz)
	Temperature test	1 °C
10	Humidity test	3%
11	Supply voltages	1.5%
12	Time	3%



4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



5 Equipment List

Conducted Disturbance at AC Power Line(150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2016-05-13	2017-05-13
LISN	Rohde & Schwarz	ENV216	SEM007-01	2016-10-09	2017-10-09
LISN	ETS-LINDGREN	3816/2	SEM007-02	2017-04-14	2018-04-14
8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2016-09-28	2017-09-28
4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2016-09-28	2017-09-28
2 Line ISN	Fischer Custom	FCC-TLISN-T2-02	EMC0122	2016-09-28	2017-09-28

Radiated Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEM001-03	2016-05-13	2017-05-13
EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESCI	SEM004-01	2017-04-14	2018-04-14
Trilog-Broadband Antenna (30M-1GHz)	Schwarzbeck	VULB9168	SEM003-17	2017-01-26	2018-01-26
Pre-amplifier	Sonoma Instrument Co	310N	SEM005-03	2016-07-06	2017-07-06
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2015-08-14	2018-08-14



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM161201122603

Page: 11 of 69

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Date (yyyy-mm-dd)	Cal. Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2016-05-13	2017-05-13
2	EXA Spectrum Analyzer	Agilent Technologies Inc	N9010A	SEM004-09	2016-07-19	2017-07-19
3	BiConiLog Antenna (26-3000MHz)	ETS-Lindgren	3142C	SEM003-02	2014-11-15	2017-11-15
4	Amplifier (0.1-1300MHz)	HP	8447D	SEM005-02	2016-10-09	2017-10-09
5	Horn Antenna (1-18GHz)	Rohde & Schwarz	HF907	SEM003-07	2015-06-14	2018-06-14
6	Horn Antenna (18-26GHz)	ETS-Lindgren	3160	SEM003-12	2014-11-24	2017-11-24
7	Horn Antenna(26GHz-40GHz)	A.H.Systems, inc.	SAS-573	SEM003-13	2015-02-12	2018-02-12
8	Low Noise Amplifier	Black Diamond Series	BDLNA-0118-352810	SEM005-05	2016-10-09	2017-10-09
9	Band filter	Amindeon	Asi 3314	SEM023-01	N/A	N/A

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM161201122603

Page: 12 of 69

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DC Power Supply	ZhaoXin	RXN-305D	SEM011-02	2016-10-09	2017-10-09
Spectrum Analyzer	Rohde & Schwarz	FSP	SEM004-06	2016-10-09	2017-10-09
Power Meter	Rohde & Schwarz	NRVS	SEM014-02	2016-10-09	2017-10-09

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2016-10-12	2017-10-12
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2016-10-12	2017-10-12
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2016-05-18	2017-05-18

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

RSS 247


6.1.2 Conclusion

Standard Requirement:

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level. When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -3dBi.





7 Radio Spectrum Matter Test Results

7.1 Conducted Disturbance at AC Power Line(150kHz-30MHz)

Test Requirement RSS-Gen Section 8.8
Test Method: ANSI C63.10 (2013) Section 6.2
Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		


7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1020 mbar

Test mode e:TX mode:Keep the EUT in transmitting mode


7.1.2 Test Setup Diagram



7.1.3 Measurement Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


Mode:e; Line:Live Line



Site : Shielding Room
Condition : CE LINE
Job No. : 11226CR
Test Mode : e

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15160	0.02	9.64	10.31	19.97	55.91	-35.94	AVERAGE
2	0.15160	0.02	9.64	26.28	35.94	65.91	-29.97	QP
3 @	0.28000	0.02	9.64	38.40	48.06	50.82	-2.76	Average
4	0.28000	0.02	9.64	38.60	48.26	60.82	-12.56	QP
5	0.46861	0.02	9.64	22.30	31.96	56.54	-24.58	QP
6	0.46861	0.02	9.64	8.34	18.00	46.54	-28.54	AVERAGE
7	0.65430	0.02	9.65	6.90	16.58	46.00	-29.42	AVERAGE
8	0.65430	0.02	9.65	17.72	27.39	56.00	-28.61	QP
9	1.519	0.03	9.66	9.49	19.18	56.00	-36.82	QP
10	1.519	0.03	9.66	-0.39	9.30	46.00	-36.70	AVERAGE
11	18.232	0.17	10.10	7.15	17.42	50.00	-32.58	AVERAGE
12	18.232	0.17	10.10	19.74	30.01	60.00	-29.99	QP

Mode:e; Line:Neutral Line



Site : Shielding Room
Condition : CE NEUTRAL
Job No. : 11226CR
Test Mode : e

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.15900	0.02	9.64	21.85	31.50	65.52	-34.01	QP
2	0.15900	0.02	9.64	10.60	20.25	55.52	-35.26	AVERAGE
3	0.18639	0.02	9.63	11.84	21.49	54.20	-32.71	AVERAGE
4	0.18639	0.02	9.63	22.74	32.39	64.20	-31.81	QP
5	0.28000	0.02	9.63	41.00	50.65	60.82	-10.17	QP
6 @	0.28000	0.02	9.63	38.50	48.15	50.82	-2.67	Average
7	0.46861	0.02	9.63	21.15	30.80	56.54	-25.74	QP
8	0.46861	0.02	9.63	10.39	20.04	46.54	-26.50	AVERAGE
9	1.527	0.03	9.65	-4.31	5.37	46.00	-40.63	AVERAGE
10	1.527	0.03	9.65	6.90	16.58	56.00	-39.42	QP
11	18.328	0.17	10.13	7.38	17.68	50.00	-32.32	AVERAGE
12	18.328	0.17	10.13	18.50	28.79	60.00	-31.21	QP



7.2 Conducted Peak Output Power

Test Requirement RSS-247 Section 5.4(2)
Test Method: ANSI C63.10 (2013) Section 11.9.1
Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation


7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1020 mbar

Test mode e:TX mode:Keep the EUT in transmitting mode

7.2.2 Test Setup Diagram



7.2.3 Measurement Data

The detailed test data see: Appendix RSS247

7.3 Minimum 6dB Bandwidth


Test Requirement	RSS-247 Section 5.2(1)
Test Method:	ANSI C63.10 (2013) Section 11.8.1
Limit:	≥500 kHz

7.3.1 E.U.T. Operation

Operating Environment:

Temperature:	25 °C	Humidity:	55 % RH	Atmospheric Pressure:	1020 mbar
Test mode	e:TX mode:Keep the EUT in transmitting mode				

7.3.2 Test Setup Diagram



7.3.3 Measurement Data

The detailed test data see: Appendix RSS247


7.4 Power Spectrum Density

Test Requirement	RSS-247 Section 6.2.1(1)&6.2.2(1)&6.2.3(1)&6.2.4(1)
Test Method:	ANSI C63.10 (2013) Section 11.10.2
Limit:	≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.4.1 E.U.T. Operation

Operating Environment:			
Temperature:	25 °C	Humidity:	55 % RH
		Atmospheric Pressure:	1020 mbar
Test mode	e:TX mode:Keep the EUT in transmitting mode		

7.4.2 Test Setup Diagram



7.4.3 Measurement Data

The detailed test data see: Appendix RSS247



7.5 Conducted Spurious Emissions

Test Requirement RSS-247 Section 5.5

Test Method: ANSI C63.10 (2013) Section 7.8.6

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1020 mbar

Test mode e:TX mode:Keep the EUT in transmitting mode

7.5.2 Test Setup Diagram



7.5.3 Measurement Data

The detailed test data see: Appendix RSS247



7.6 Radiated Spurious Emissions

Test Requirement RSS-Gen Section 8.8
Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6
Measurement Distance: 10 meter semi-anechoic chamber
3 meter fully-anechoic chamber
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz and 110-490kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.		


7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C Humidity: 56 % RH Atmospheric Pressure: 1015 mbar

Test mode e:TX mode:Keep the EUT in transmitting mode

7.6.2 Test Setup Diagram





7.6.3 Measurement Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.



Below 1G:

The test was performed at a 10m test site. According to below formulate and the test data at 10m test distance,

$$L_3 / L_{10} = D_{10} / D_3$$

Note:

L_3 : Level @ 3m distance. Unit: uV/m;


L_{10} : Level @ 10m distance. Unit: uV/m;

D_3 : 3m distance. Unit: m

D_{10} : 10m distance. Unit: m

The level at 3m test distance is below:

Frequency (MHz)	Level @ 10m (dBuV/m)	Level @ 10m (uV/m)	Level @ 3m (uV/m)	Level @ 3m (dBuV/m)	Limit @ 3m (dBuV/m)	Margin (dB)	Ant. Polarization
30.85	17.87	7.83	26.08	28.33	40.00	-11.67	V
46.83	16.29	6.52	21.75	26.75	40.00	-13.25	V
60.28	15.34	5.85	19.49	25.80	40.00	-14.20	V
338.40	22.20	12.88	42.94	32.66	46.00	-13.34	V
636.13	23.92	15.70	52.35	34.38	46.00	-11.62	V
909.67	26.13	20.25	67.51	36.59	46.00	-9.41	V
38.75	13.93	4.97	16.57	24.39	40.00	-15.61	H
54.45	13.51	4.74	15.79	23.97	40.00	-16.03	H
156.46	15.75	6.13	20.44	26.21	43.50	-17.29	H
338.40	19.71	9.67	32.24	30.17	46.00	-15.83	H
638.37	23.94	15.74	52.47	34.40	46.00	-11.60	H
807.43	26.73	21.70	72.34	37.19	46.00	-8.81	H




Condition: 10m HORIZONTAL

Job No. : 11226CR

Test Mode: e

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	38.75	6.78	13.16	32.98	26.97	13.93	29.50	-15.57
2	54.45	6.99	12.42	32.98	27.08	13.51	29.50	-15.99
3	156.46	7.48	13.40	32.74	27.61	15.75	33.00	-17.25
4	338.40	8.19	13.63	32.60	30.49	19.71	35.60	-15.89
5	638.37	9.00	19.39	32.60	28.15	23.94	35.60	-11.66
6 pp	807.43	9.30	21.28	32.59	28.74	26.73	35.60	-8.87



Condition: 10m VERTICAL

Job No. : 11226CR

Test Mode: e

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.85	6.70	12.50	32.97	31.64	17.87	29.50	-11.63
2	46.83	6.84	12.85	33.00	29.60	16.29	29.50	-13.21
3	60.28	7.00	11.94	32.95	29.35	15.34	29.50	-14.16
4	338.40	8.19	13.63	32.60	32.98	22.20	35.60	-13.40
5	636.13	8.99	19.36	32.60	28.17	23.92	35.60	-11.68
6 pp	909.67	9.50	22.35	32.50	26.78	26.13	35.60	-9.47



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM161201122603

Page: 30 of 69

Above:

Mode:e; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:Low

Freq (MHz)	Antenna_Factor (dB/m)	Cable_Loss (dB)	Preamplifier_Gain (dB)	Read_Level (dBuV)	Level (dBuV/m)	Limit_Line (dBuV/m)	Over_Limit (dB)
3732.570	32.87	6.49	37.97	45.26	48.02	74	-25.98
4804.000	34.16	7.73	38.40	45.97	50.17	74	-23.83
6087.002	34.77	8.81	38.21	44.77	51.41	74	-22.59
7206.000	36.42	9.65	37.11	40.93	53.42	74	-20.58
9608.000	37.52	11.06	35.10	37.38	53.46	74	-20.54
12261.500	38.76	12.79	36.23	34.38	52.85	74	-21.15

Mode:e; Polarization:Vertical; Modulation Type:GFSK; ; Channel:Low

Freq (MHz)	Antenna_Factor (dB/m)	Cable_Loss (dB)	Preamplifier_Gain (dB)	Read_Level (dBuV)	Level (dBuV/m)	Limit_Line (dBuV/m)	Over_Limit (dB)
3842.163	33.18	6.58	37.98	45.13	48.15	74	-25.85
4804.000	34.16	7.73	38.40	45.85	50.05	74	-23.95
6256.664	34.91	8.91	38.04	44.47	51.70	74	-22.3
7206.000	36.42	9.65	37.11	41.15	53.64	74	-20.36
9608.000	37.52	11.06	35.1	37.32	53.40	74	-20.6
12279.260	38.77	12.82	36.27	34.47	52.9	74	-21.1

Mode:e; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:middle

Freq (MHz)	Antenna_Factor (dB/m)	Cable_Loss (dB)	Preamplifier_Gain (dB)	Read_Level (dBuV)	Level (dBuV/m)	Limit_Line (dBuV/m)	Over_Limit (dB)
3842.163	33.18	6.58	38.63	44.63	47.00	74	-27
4880.000	34.29	7.83	39.06	45.24	48.99	74	-25.01
6320.356	34.96	8.95	38.80	44.98	51.60	74	-22.4
7320.000	36.37	9.73	38.07	42.09	53.53	74	-20.47
9760.000	37.55	11.21	36.92	38.58	53.14	74	-20.86
12261.500	38.76	12.79	38.57	36.99	53.12	74	-20.88

Mode:e; Polarization:Vertical; Modulation Type:GFSK; ; Channel:middle

Freq (MHz)	Antenna_Factor (dB/m)	Cable_Loss (dB)	Preamplifier_Gain (dB)	Read_Level (dBuV)	Level (dBuV/m)	Limit_Line (dBuV/m)	Over_Limit (dB)
3853.298	33.21	6.59	38.64	45.20	47.59	74	-26.41
4880.000	34.29	7.83	39.06	45.57	49.32	74	-24.68
6016.949	34.71	8.76	38.99	44.58	50.25	74	-23.75
7320.000	36.37	9.73	38.07	41.78	53.22	74	-20.78
9760.000	37.55	11.21	36.92	38.74	53.30	74	-20.7
12422.220	38.85	13.03	38.73	37.59	53.51	74	-20.49



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM161201122603

Page: 31 of 69

Mode:e; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:High

Freq (MHz)	Antenna_Factor (dB/m)	Cable_Loss (dB)	Preamp_Gain (dB)	Read_Level (dBuV)	Level (dBuV/m)	Limit_Line (dBuV/m)	Over_Limit (dB)
3886.896	33.30	6.61	38.65	44.54	46.99	74	-27.01
4960.000	34.43	7.95	39.09	45.20	49.18	74	-24.82
5999.562	34.7	8.75	39.00	45.41	51.04	74	-22.96
7440.000	36.32	9.81	37.94	41.86	53.35	74	-20.65
9920.000	37.58	11.36	36.84	38.87	53.82	74	-20.18
12512.420	38.90	13.15	38.82	37.60	53.39	74	-20.61

Mode:e; Polarization:Vertical; Modulation Type:GFSK; ; Channel:High

Freq (MHz)	Antenna_Factor (dB/m)	Cable_Loss (dB)	Preamp_Gain (dB)	Read_Level (dBuV)	Level (dBuV/m)	Limit_Line (dBuV/m)	Over_Limit (dB)
3797.945	33.06	6.54	38.61	44.86	47.14	74	-26.86
4960.000	34.43	7.95	39.09	44.33	48.31	74	-25.69
6292.980	34.94	8.93	38.81	45.31	51.86	74	-22.14
7440.000	36.32	9.81	37.94	41.52	53.01	74	-20.99
9920.000	37.58	11.36	36.84	38.80	53.75	74	-20.25
12261.500	38.76	12.79	38.57	36.95	53.08	74	-20.92

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

2) Scan from 9kHz to 25GHz, the disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.



7.7 Radiated Emissions which fall in the restricted bands

Test Requirement RSS-Gen Section 8.8
Test Method: ANSI C63.10 (2013) Section 6.4&6.5&6.6
Measurement Distance: 3m
Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C Humidity: 56 % RH Atmospheric Pressure: 1015 mbar

Test mode e:TX mode:Keep the EUT in transmitting mode

7.7.2 Test Setup Diagram




7.7.3 Measurement Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel,the middle channel,the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.



Mode:e; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:Low




Condition: 3m Horizontal
Job No: : 11226CR
Mode: : 2402 Band edge
: BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	29.08	37.96	46.40	42.86	74.00	-31.14
2 pp	2402.288	5.35	29.11	37.96	98.69	95.19	74.00	21.19



Mode:e; Polarization:Vertical; Modulation Type:GFSK; ; Channel:Low



Condition: 3m Vertical


Job No: : 11226CR

Mode: : 2402 Band edge

: BLE

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.000	5.34	29.08	37.96	47.19	43.65	74.00	-30.35
2 pp	2402.288	5.35	29.11	37.96	104.11	100.61	74.00	26.61

Mode:e; Polarization:Horizontal; Modulation Type:GFSK; ; Channel:High



Condition: 3m Horizontal

Job No: : 11226CR


Mode: : 2480 Band edge

: BLE

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2479.731	5.41	29.34	37.95	98.24	95.04	74.00	21.04
2	2483.500	5.41	29.35	37.95	53.83	50.64	74.00	-23.36



Mode:e; Polarization:Vertical; Modulation Type:GFSK; ; Channel:High



Condition: 3m Vertical

Job No: : 11226CR

Mode: : 2480 Band edge

: BLE

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2479.756	5.41	29.34	37.95	103.30	100.10	74.00	26.10
2	2483.500	5.41	29.35	37.95	56.86	53.67	74.00	-20.33



7.8 Conducted Band Edges Measurement

Test Requirement RSS-247 Section 5.5

Test Method: ANSI C63.10 (2013) Section 7.8.8

Limit: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.


7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1020 mbar

Test mode e:TX mode:Keep the EUT in transmitting mode

7.8.2 Test Setup Diagram



7.8.3 Measurement Data

The detailed test data see: Appendix RSS247

7.9 20dB Bandwidth

Test Requirement RSS-Gen Section 6.6

Test Method: ANSI C63.10 (2013) Section 6.9


7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 55 % RH Atmospheric Pressure: 1020 mbar

Test mode e:TX mode:Keep the EUT in transmitting mode

7.9.2 Test Setup Diagram



7.9.3 Measurement Data



The detailed test data see: Appendix RSS247

8 Photographs

8.1 Conducted Disturbance at AC Power Line(150kHz-30MHz) Test Setup



8.2 Radiated Spurious Emissions Test Setup





8.3 EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1612011226CR.





9 Appendix


9.1 Appendix RSS247

1.6dB Bandwidth

Test Mode	TestChannel	EBW[MHz]	Limit	Verdict
BLE	2402	0.702	≥ 0.5	PASS
BLE	2440	0.711	≥ 0.5	PASS
BLE	2480	0.702	≥ 0.5	PASS












2.Occupied Bandwidth

Test Mode	Test Channel	OBW[MHz]	Limit[MHz]	Verdict
BLE	2402	1.032	---	PASS
BLE	2440	1.038	---	PASS
BLE	2480	1.035	---	PASS












3.Maximum peak conducted output power

Test Mode	Test Channel	Power[dBm]	Limit[dBm]	Verdict
BLE	2402	4.2	<30	PASS
BLE	2440	5.82	<30	PASS
BLE	2480	4.36	<30	PASS












4.Maximum Peak power spectral density

Test Mode	Test Channel	PSD[dBm/MHz]	Limit[dBm/MHz]	Verdict
BLE	2402	-12.05	<8.00	PASS
BLE	2440	-10.24	<8.00	PASS
BLE	2480	-9.27	<8.00	PASS











5. Band-edge for RF Conducted Emissions

Test Mode	Test Channel	Carrier Power[dBm]	Max. Spurious Level [dBm]	Limit [dBm]	Verdict
BLE	2402	3.830	-65.648	<-16.17	PASS
BLE	2480	6.280	-45.958	<-13.72	PASS






Band-edge for RF Conducted Emissions_BLE_2480_Hopping Off






6.RF Conducted Spurious Emissions


Test Mode	Test Channel	StartFre [MHz]	StopFre [MHz]	RBW [kHz]	VBW [kHz]	Pref[dBm]	Max. Level [dBm]	Limit [dBm]	Verdict
BLE	2402	30	10000	1000	3000	3.87	-44.530	<-16.13	PASS
BLE	2402	10000	25000	1000	3000	3.87	-64.910	<-16.13	PASS
BLE	2440	30	10000	1000	3000	5.44	-41.910	<-14.56	PASS
BLE	2440	10000	25000	1000	3000	5.44	-64.880	<-14.56	PASS
BLE	2480	30	10000	1000	3000	6.4	-39.280	<-13.6	PASS
BLE	2480	10000	25000	1000	3000	6.4	-64.090	<-13.6	PASS








RF Conducted Spurious Emissions_BLE_2440






CSE_1




CSE_2






RF Conducted Spurious Emissions_BLE_2480





CSE_1



CSE_2

