

MPE CALCULATION
TrueLink 12LB FCC ID: XGS-RL76052
BT FCC ID: XGS-UNNB30
Cellular FCC ID: XPY1EHM44NN

RF Exposure Requirements: 47 CFR §1.1307(b)
RF Radiation Exposure Limits: 47 CFR §1.1310
RF Radiation Exposure Guidelines: FCC OST/OET Bulletin Number 65

Limits for General Population/Uncontrolled Exposure in the band of: 300 – 1500 MHz
Power Density Limit: $f/1500 \text{ mW} / \text{cm}^2$
Limits for General Population/Uncontrolled Exposure in the band of: 1500 – 100,000 MHz
Power Density Limit: $1 \text{ mW} / \text{cm}^2$

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

EUT: ORBCOMM Inc.

Model No.: TripLINK 12LB

Type	CH Freq (MHz)	Conducted Power (dBm)	Antenna Gain (dBi)	Tune-Up Tolerance	Tolerance Max Power (dBm)	Measurement Distance (cm)	Calculated MPE (mW/cm ²)	MPE Limit (mW/cm ²)	Pass/Fail
Lora	914.2	13.72	0.5	±1dB	14.72	30	0.003	0.60	Pass
GSM	848.8	32.78	3.3	±1dB	33.78	30	0.45	0.56	Pass
BT	2402	7.9	3.0	±1dB	8.9	30	0.001	1	Pass

Total = $0.003/0.6 + 0.45/0.56 + 0.001/1 = 0.809 < 1$

The Above Result had shown that the Device complied with MPE requirement.

Completed By: Deon Dai

SIEMIC, Inc

775 Montague Expressway, Milpitas, CA 95035

Phone: (408) 526-1188

Date: May 30, 2019

