#01_LTE Band 4_20M_QPSK_1_0_Bottom Face_0mm_Ch20175

Communication System: LTE ; Frequency: 1732.5 MHz;Duty Cycle: 1:1
Medium: HSL_1750_191122 Medium parameters used: f = 1733 MHz; σ = 1.355 S/m; ε_r = 41.045; ρ = 1000 kg/m^3
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3931; ConvF(8.66, 8.66, 8.66) @ 1732.5 MHz; Calibrated: 2019/9/26
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1131
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (71x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.58 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 22.02 V/m; Power Drift = -0.07 dB
Peak SAR (extrapolated) = 1.96 W/kg
SAR(1 g) = 0.951 W/kg; SAR(10 g) = 0.475 W/kg
Maximum value of SAR (measured) = 1.55 W/kg



0 dB = 1.58 W/kg = 1.99 dBW/kg

#02_LTE Band 7_20M_QPSK_50_0_Bottom Face_0mm_Ch20850

Communication System: LTE ; Frequency: 2510 MHz;Duty Cycle: 1:1
Medium: HSL_2600_191219 Medium parameters used: f = 2510 MHz; σ = 1.836 S/m; ε_r = 38.692; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：22.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3728; ConvF(6.94, 6.94, 6.94) @ 2510 MHz; Calibrated: 2019/1/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1131
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (91x51x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.56 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 18.14 V/m; Power Drift = -0.15 dB
Peak SAR (extrapolated) = 2.23 W/kg
SAR(1 g) = 0.958 W/kg; SAR(10 g) = 0.394 W/kg
Maximum value of SAR (measured) = 1.72 W/kg



0 dB = 1.56 W/kg = 1.93 dBW/kg

#03_LTE Band 12_10M_QPSK_1_0_Edge 1_0mm_Ch23095

Communication System: LTE; Frequency: 707.5 MHz;Duty Cycle: 1:1
Medium: HSL_750_191123 Medium parameters used: f = 707.5 MHz; σ = 0.849 S/m; ε_r = 43.065; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3931; ConvF(9.99, 9.99, 9.99) @ 707.5 MHz; Calibrated: 2019/9/26
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1131
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (41x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.505 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 16.33 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 0.692 W/kg
SAR(1 g) = 0.303 W/kg; SAR(10 g) = 0.146 W/kg
Maximum value of SAR (measured) = 0.552 W/kg



0 dB = 0.505 W/kg = -2.97 dBW/kg

#04_LTE Band 13_10M_QPSK_1_0_Edge 1_0mm_Ch23230

Communication System: LTE; Frequency: 782 MHz;Duty Cycle: 1:1
Medium: HSL_750_191123 Medium parameters used: f = 782 MHz; σ = 0.919 S/m; ε_r = 42.065; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3931; ConvF(9.99, 9.99, 9.99) @ 782 MHz; Calibrated: 2019/9/26
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1131
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (41x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.508 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 25.56 V/m; Power Drift = -0.08 dB
Peak SAR (extrapolated) = 0.655 W/kg
SAR(1 g) = 0.296 W/kg; SAR(10 g) = 0.153 W/kg
Maximum value of SAR (measured) = 0.517 W/kg



0 dB = 0.508 W/kg = -2.94 dBW/kg

#05_LTE Band 25_20M_QPSK_1_0_Bottom Face_0mm_Ch26340

Communication System: LTE; Frequency: 1880 MHz;Duty Cycle: 1:1
Medium: HSL_1900_191122 Medium parameters used: f = 1880 MHz; σ = 1.43 S/m; ε_r = 39.837; ρ = 1000 kg/m^3
Ambient Temperature：23.6 ℃; Liquid Temperature：22.6 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3931; ConvF(8.32, 8.32, 8.32) @ 1880 MHz; Calibrated: 2019/9/26
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1131
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (71x41x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.49 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 24.44 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 1.82 W/kg
SAR(1 g) = 0.871 W/kg; SAR(10 g) = 0.399 W/kg
Maximum value of SAR (measured) = 1.49 W/kg



0 dB = 1.49 W/kg = 1.73 dBW/kg

#06_LTE Band 26_15M_QPSK_1_0_Edge 1_0mm_Ch26865

Communication System: LTE; Frequency: 831.5 MHz;Duty Cycle: 1:1
Medium: HSL_850_191123 Medium parameters used: f = 831.5 MHz; σ = 0.87 S/m; ε_r = 43.232; ρ = 1000 kg/m^3
Ambient Temperature：23.2 ℃; Liquid Temperature：22.2 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3931; ConvF(9.8, 9.8, 9.8) @ 831.5 MHz; Calibrated: 2019/9/26
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1131
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (41x91x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 0.868 W/kg

Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 18.89 V/m; Power Drift = 0.06 dB
Peak SAR (extrapolated) = 1.19 W/kg
SAR(1 g) = 0.488 W/kg; SAR(10 g) = 0.243 W/kg
Maximum value of SAR (measured) = 0.921 W/kg



0 dB = 0.868 W/kg = -0.61 dBW/kg

#07_LTE Band 30_10M_QPSK_1_0_Bottom Face_0mm_Ch27710

Communication System: LTE ; Frequency: 2310 MHz;Duty Cycle: 1:1
Medium: HSL_2300_200110 Medium parameters used: f = 2310 MHz; σ = 1.631 S/m; ε_r = 39.557; ρ = 1000 kg/m^3
Ambient Temperature：23.8 ℃; Liquid Temperature：22.8 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3931; ConvF(7.83, 7.83, 7.83) @ 2310 MHz; Calibrated: 2019/9/26
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1131
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (91x61x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.53 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 12.95 V/m; Power Drift = 0.05 dB
Peak SAR (extrapolated) = 2.24 W/kg
SAR(1 g) = 0.964 W/kg; SAR(10 g) = 0.427 W/kg
Maximum value of SAR (measured) = 1.60 W/kg



0 dB = 1.53 W/kg = 1.85 dBW/kg

#08_LTE Band 41_20M_QPSK_50_0_Bottom Face_0mm_Ch39750

Communication System: LTE ; Frequency: 2506 MHz;Duty Cycle: 1:1.59
Medium: HSL_2600_191219 Medium parameters used : f = 2506 MHz; σ = 1.832 S/m; ε_r = 38.704; ρ = 1000 kg/m^3
Ambient Temperature：23.5 ℃; Liquid Temperature：22.5 ℃

DASY5 Configuration:
- Probe: EX3DV4 - SN3728; ConvF(6.94, 6.94, 6.94) @ 2506 MHz; Calibrated: 2019/1/15
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn778; Calibrated: 2019/5/21
- Phantom: ELI v5.0; Type: QDOVA002AA; Serial: 1131
- Measurement SW: DASY52, Version 52.10 (2);SEMCAD X Version 14.6.12 (7470)

Area Scan (91x51x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 1.27 W/kg

Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 15.92 V/m; Power Drift = -0.06 dB
Peak SAR (extrapolated) = 2.25 W/kg
SAR(1 g) = 0.960 W/kg; SAR(10 g) = 0.390 W/kg
Maximum value of SAR (measured) = 1.77 W/kg



0 dB = 1.27 W/kg = 1.04 dBW/kg