



FCC RADIO EXPOSURE TEST REPORT

FCC ID : XIA-NWL224
Equipment : Vodafone MachineLink 4G Lite
Brand Name : Vodafone,
 NetComm Wireless
Model Name : NWL-224
Applicant : NetComm Wireless Limited
18-20 Orion Road Lane Cove NSW 2066 Australia
Manufacturer : NetComm Wireless Limited
18-20 Orion Road Lane Cove NSW 2066 Australia
Standard : 47 CFR Part 2.1091

The product was received on Sep. 20, 2018, and testing was started from Oct. 03, 2018 and completed on Oct. 22, 2018. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.


Approved by: Cliff Chang

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 EUT General Information	5
1.2 Table for Multiple List	5
1.3 Testing Location	6
2 RF Exposure Limit Introduction.....	7
3 Radio Frequency Radiation Exposure Evaluation.....	8
3.1 Power Density Calculation	8
Photographs of EUT v01	



History of this test report

[illegible]



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3	-	Exposure evaluation	PASS	-

Reviewed by: Sam Chen

Report Producer: Cindy Peng




1 General Description

1.1 EUT General Information

RF General Information				
Evaluation Mode	Bandwidth (MHz)	TX Frequency (MHz)	RX Frequency (MHz)	Modulation Type
LTE Band 2	1.4	1850.7 ~ 1909.3	1930.7 ~ 1989.3	QPSK / 16QAM
	3	1851.5 ~ 1908.5	1931.5 ~ 1988.5	
	5	1852.5 ~ 1907.5	1932.5 ~ 1987.5	
	10	1855.0 ~ 1905.0	1935.0 ~ 1985.0	
	15	1857.5 ~ 1902.5	1937.5 ~ 1982.5	
	20	1860.0 ~ 1900.0	1940.0 ~ 1980.0	
LTE Band 4	1.4	1710.7 ~ 1754.3	2110.7 ~ 2154.3	
	3	1711.5 ~ 1753.5	2111.5 ~ 2153.5	
	5	1712.5 ~ 1752.5	2112.5 ~ 2152.5	
	10	1715.0 ~ 1750.0	2115.0 ~ 2150.0	
	15	1717.5 ~ 1747.5	2117.5 ~ 2147.5	
	20	1720.0 ~ 1745.0	2120.0 ~ 2145.0	
LTE Band 12	1.4	699.7 ~ 715.3	729.7 ~ 745.3	
	3	700.5 ~ 714.5	730.5 ~ 744.5	
	5	701.5 ~ 713.5	731.5 ~ 743.5	
	10	704.0 ~ 711.0	734.0 ~ 741.0	

1.2 Table for Multiple List

The brand names in the following table are all refer to the identical product.

Brand Name	Description
Vodafone	All the models are identical, the difference model for difference brand served as marketing strategy.
 NetCommWireless	



1.3 Testing Location

Testing Location		
<input type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-327-0973
<input checked="" type="checkbox"/>	JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

Test site Designation No. TW0006 with FCC.

Test site registered number IC 4086D with Industry Canada.



2 RF Exposure Limit Introduction

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



3 Radio Frequency Radiation Exposure Evaluation

3.1 Power Density Calculation

Mode	DG (dBi)	Power (dBm)	EIRP (dBm)	Tolerance (dB)	Tune-up EIRP (dBm)	Tune-up EIRP (W)	Distance (cm)	S (mW/cm ²)	S Limit (mW/cm ²)
Band 2_LTE_10MHz_Nss1,(QPSK)	3.42	22.46	25.88	0.50	26.38	0.43451	20	0.08644	1.00000
Band 4_LTE_20MHz_Nss1,(QPSK)	3.28	24.03	27.31	0.50	27.81	0.60395	20	0.12015	1.00000
Band 12_LTE_5MHz_Nss1,(QPSK)	4.71	23.21	27.92	0.50	28.42	0.69502	20	0.13827	0.46647

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band.

Conclusion:

According to 47 CFR Part 2.1091, the RF exposure analysis concludes that the RF Exposure is compliant.

—————THE END—————