



## MEASUREMENT REPORT

### FCC PART 15.247 Bluetooth

**FCC ID:** XJ4KB6226

**APPLICANT:** HUIZHOU CHINFAI ELECTRONIC CO., LTD

**Application Type:** Certification

**Product:** Bluetooth Keyboard

**Model No.:** KB-6226

**FCC Classification:** FCC Part 15 Spread Spectrum Transmitter(DSS)

**FCC Rule Part(s):** Part 15 Subpart C (15.247)

**Test Procedure(s):** ANSI C63.10-2009, DA 00-705

**Test Date:** December 20 ~ 25, 2013

Reviewed By :

( Engineer: Sunny Sun )

Approved By :

( Manager: Robin Wu )

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2009 and DA 00-705. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

# CONTENTS

Description	Page
<b>Revision History.....</b>	<b>5</b>
<b>§2.1033 General Information.....</b>	<b>6</b>
<b>1. INTRODUCTION .....</b>	<b>7</b>
1.1. Scope .....	7
1.2. MRT Test Location .....	7
<b>2. PRODUCT INFORMATION .....</b>	<b>8</b>
2.1. Equipment Description.....	8
2.2. Frequency / Channel Opreation.....	9
2.3. Pseudorandom Frequency Hopping Sequence.....	10
2.4. Device Capabilities .....	10
2.5. Test Configuration .....	10
2.6. Description of Support Units .....	10
2.7. Test Software .....	11
2.8. EMI Suppression Device(s)/Modifications.....	11
2.9. Labeling Requirements.....	11
<b>3. DESCRIPTION OF TEST .....</b>	<b>12</b>
3.1. Evaluation Procedure .....	12
3.2. AC Line Conducted Emissions .....	12
3.3. Radiated Emissions .....	13
<b>4. ANTENNA REQUIREMENTS.....</b>	<b>14</b>
<b>5. TEST EQUIPMENT CALIBRATION DATA .....</b>	<b>15</b>
<b>6. MEASUREMENT UNCERTAINTY.....</b>	<b>16</b>
<b>7. TEST RESULT .....</b>	<b>17</b>
7.1. Summary .....	17
7.2. 20dB Bandwidth Measurement.....	19
7.2.1. Test Limit .....	19
7.2.2. Test Procedure used.....	19
7.2.3. Test Setting.....	19
7.2.4. Test Setup.....	19
7.2.5. Test Result.....	20
7.3. Output Power Measurement.....	23
7.3.1. Test Limit .....	23

7.3.2.	Test Procedure Used .....	23
7.3.3.	Test Setting.....	23
7.3.4.	Test Setup.....	23
7.3.5.	Test Result.....	24
7.4.	Carrier Frequency Separation Measurement .....	27
7.4.1.	Test Limit .....	27
7.4.2.	Test Procedure Used .....	27
7.4.3.	Test Setting.....	27
7.4.4.	Test Setup.....	27
7.4.5.	Test Result.....	28
7.5.	Number of Hopping Channels Measurement .....	31
7.5.1.	Test Limit .....	31
7.5.2.	Test Procedure Used .....	31
7.5.3.	Test Setting.....	31
7.5.4.	Test Setup.....	31
7.5.5.	Test Result.....	32
7.6.	Time of Occupancy Measurement .....	35
7.6.1.	Test Limit .....	35
7.6.2.	Test Procedure Used .....	35
7.6.3.	Test Setting.....	35
7.6.4.	Test Setup.....	36
7.6.5.	Test Result.....	37
7.7.	Band-edge Compliance Measurement.....	39
7.7.1.	Test Limit .....	39
7.7.2.	Test Procedure Used .....	39
7.7.3.	Test Setting.....	39
7.7.4.	Test Setup.....	40
7.7.5.	Test Result.....	41
7.8.	Conducted Spurious Emissions Measurement.....	43
7.8.1.	Test Limit .....	43
7.8.2.	Test Procedure Used .....	43
7.8.3.	Test Setting.....	43
7.8.4.	Test Setup.....	44
7.8.5.	Test Result.....	45
7.9.	Radiated Spurious Emission Measurement .....	48
7.9.1.	Test Limit .....	48
7.9.2.	Test Procedure Used .....	48
7.9.3.	Test Setting.....	48

7.9.4.	Test Setup.....	49
7.9.5.	Test Result.....	51
7.10.	Radiated Restricted Band Edge Measurement .....	58
7.10.1.	Test Result.....	58
7.11.	AC Conducted Emissions Measurement.....	66
7.11.1.	Test Limit .....	66
7.11.2.	Test Setup.....	66
7.11.3.	Test Result.....	67
<b>8.</b>	<b>CONCLUSION.....</b>	<b>69</b>

## Revision History

Report No.	Version	Description	Issue Date
1312RSU00705	Rev. 01	Initial report	2013-12-26
1312RSU00705	Rev. 02	Added the description of Bluetooth characteristic	2013-12-31

## §2.1033 General Information

<b>Applicant:</b>	HUIZHOU CHINFAI ELECTRONIC CO., LTD
<b>Applicant Address:</b>	YINGFENG INDUSTRIAL PARK, SANHE ECONOMIC DEVELOPMENT ZONE, HUIYANG DISTRICT, HUIZHOU, CHINA
<b>Manufacturer:</b>	HUIZHOU CHINFAI ELECTRONIC CO., LTD
<b>Manufacturer Address:</b>	YINGFENG INDUSTRIAL PARK, SANHE ECONOMIC DEVELOPMENT ZONE, HUIYANG DISTRICT, HUIZHOU, CHINA
<b>Test Site:</b>	MRT Technology (Suzhou) Co., Ltd
<b>Test Site Address:</b>	D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
<b>MRT Registration No.:</b>	809388
<b>FCC Rule Part(s):</b>	Part 15.247
<b>Model Name:</b>	KB-6226
<b>FCC ID:</b>	XJ4KB6226
<b>Test Device Serial No.:</b>	N/A <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
<b>FCC Classification:</b>	FCC Part 15 Spread Spectrum Transmitter (DSS)
<b>Method/System:</b>	Frequency Hopping Spread Spectrum (FHSS)
<b>Date(s) of Test:</b>	December 20 ~ 25, 2013
<b>Test Report S/N:</b>	1312RSU00705

# 1. INTRODUCTION

## 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taihu Lake. These measurement tests were conducted at the MRT Technology (Suzhou) Co., Ltd. Facility located at D8 Building, Youxin Industrial Park, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2009 on September 30, 2013.



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name	Bluetooth Keyboard
Model No.	KB-6226
Frequency Range	2402~2480MHz
Maximum Output Power	2.405dBm
Type of Modulation	1Mbps(GFSK), 2Mbps(Pi/4 DQPSK), 3Mbps (8DPSK)
Antenna Type	Internal
Peak Antenna Gain	-1.2dBi

The Equipment Under Test (EUT) is the **Bluetooth Keyboard FCC ID: XJ4KB6226**. The test data contained in this report pertains only to the emissions due to the EUT's Bluetooth transmitter.

- 15.247(g): In accordance with the Bluetooth Industry Standard, the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) system.
- 15.247(h): In accordance with the Bluetooth Industry Standard, the system does not coordinate its channels selection/ hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.
- 15.247(h): The EUT employs Adaptive Frequency Hopping (AFH) which identifies sources of interference namely devices operating in 802.11 WLAN and excludes them from the list of available channels. The process of re-mapping reduces the number of test channels from 79 channels to a minimum number of 20 channels.




## 2.2. Frequency / Channel Opreation

Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2403 MHz	02	2404 MHz
03	2405 MHz	04	2406 MHz	05	2407 MHz
06	2408 MHz	07	2409 MHz	08	2410 MHz
09	2411 MHz	10	2412 MHz	11	2413 MHz
12	2414 MHz	13	2415 MHz	14	2416 MHz
15	2417 MHz	16	2418 MHz	17	2419 MHz
18	2420 MHz	19	2421 MHz	20	2422 MHz
21	2423 MHz	22	2424 MHz	23	2425 MHz
24	2426 MHz	25	2427 MHz	26	2428 MHz
27	2429 MHz	28	2430 MHz	29	2431 MHz
30	2432 MHz	31	2433 MHz	32	2434 MHz
33	2435 MHz	34	2436 MHz	35	2437 MHz
36	2438 MHz	37	2439 MHz	38	2440 MHz
39	2441 MHz	40	2442 MHz	41	2443 MHz
42	2444 MHz	43	2445 MHz	44	2446 MHz
45	2447 MHz	46	2448 MHz	47	2449 MHz
48	2450 MHz	49	2451 MHz	50	2452 MHz
51	2453 MHz	52	2454 MHz	53	2455 MHz
54	2456 MHz	55	2457 MHz	56	2458 MHz
57	2459 MHz	58	2460 MHz	59	2461 MHz
60	2462 MHz	61	2463 MHz	62	2464 MHz
63	2465 MHz	64	2466 MHz	65	2467 MHz
66	2468 MHz	67	2469 MHz	68	2470 MHz
69	2471 MHz	70	2472 MHz	71	2473 MHz
72	2474 MHz	73	2475 MHz	74	2476 MHz
75	2477 MHz	76	2478 MHz	77	2479 MHz
78	2480 MHz	N/A	N/A	N/A	N/A

### 2.3. Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### 2.4. Device Capabilities

This device contains the following capabilities:

Bluetooth V3.0 + HS

### 2.5. Test Configuration

The Bluetooth Keyboard FCC ID: XJ4KB6226 was tested per the guidance of ANSI C63.10-2009 and DA 00-705. ANSI C63.10-2009 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

### 2.6. Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Adapter	Supply by MRT	HSU50600F

## **2.7. Test Software**

The test utility software used during testing was pressed the key with EUT.

## **2.8. EMI Suppression Device(s)/Modifications**

No EMI suppression device(s) were added and/or no modifications were made during testing.

## **2.9. Labeling Requirements**

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase.

However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5).

Please see attachment for FCC ID label and label location.

### 3. DESCRIPTION OF TEST

#### 3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009), and the “Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems” (DA 00-705) were used in the measurement of the **Bluetooth Keyboard FCC ID: XJ4KB6226**.

**Deviation from measurement procedure.....None**

#### 3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 8'x4'x4' shielded enclosure. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.11.

### **3.3. Radiated Emissions**

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. According to 3dB Beamwidth of horn antenna, the horn antenna should be always directed to the EUT when rising height.

## 4. ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna of the Bluetooth Keyboard is **permanently attached**.
- There are no provisions for connection to an external antenna.

### Conclusion:

The **Bluetooth Keyboard FCC ID: XJ4KB6226** unit complies with the requirement of §15.203.

## 5. TEST EQUIPMENT CALIBRATION DATA

### AC Conducted Emissions

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
EMI Test Receiver	R&S	ESR7	101209	1 year	2014/11/08
Two-Line V-Network	R&S	ENV216	101683	1 year	2014/11/08
Two-Line V-Network	R&S	ENV216	101684	1 year	2014/11/08
Temperature/ Meter Humidity	Anymetre	TH101B	SR2-01	1 year	2014/11/15

### Radiated Emission

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cal. Date
Spectrum Analyzer	Agilent	E4447A	MY45300136	1 year	2014/11/08
Preamplifier	MRT	AP01G18	1310002	1 year	2014/10/07
Preamplifier	MRT	AP18G40	1310003	1 year	2014/10/07
Loop Antenna	Schwarzbeck	FMZB1519	1519-041	1 year	2014/11/24
TRILOG Antenna	Schwarzbeck	VULB9162	9162-047	1 year	2014/11/24
Broad-Band Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1167	1 year	2014/11/24
Broadband Horn Antenna	Schwarzbeck	BBHA9170	9170-549	1 year	2014/12/11
Temperature/Humidity Meter	Anymetre	TH101B	AC1-01	1 year	2014/11/15

### Conducted Test Equipments

Instrument	Manufacturer	Type No.	Serial No.	Cali. Interval	Cali. Due Date
Spectrum Analyzer	Agilent	N9010A	MY5144016A	1 year	2014/12/14
Power Sensor	Agilent	U2021XA	MY52450003	1 year	2014/12/14
Temperature/Humidity Meter	Anymetre	TH101B	TR3-01	1 year	2014/11/15

## 6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

AC Conducted Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 150kHz~30MHz: $\pm 3.46\text{dB}$
Radiated Emission Measurement
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_c(y)$ ): 9kHz ~ 1GHz: $\pm 4.2\text{dB}$ 1GHz ~ 40GHz: $\pm 4.8\text{dB}$



## 7. TEST RESULT

### 7.1. Summary

**Company Name:** HUIZHOU CHINFAI ELECTRONIC CO., LTD  
**FCC ID:** XJ4KB6226  
**Method/System:** Frequency Hopping Spread Spectrum (FHSS)  
**Number of Channels:** 79

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(1)(iii)	20dB Bandwidth	< 1 MHz only if using less than 15 non-overlapping channels	Conducted	PASS	Section 7.2
15.247(b)(1)	Peak Transmitter Output Power	<1 Watt if > 75 non-overlapping channels used		PASS	Section 7.3
15.247(a)(1)	Channel Separation	> 2/3 of 20 dB BW for systems with Output Power < 125mW		PASS	Section 7.4
15.247(a)(1)(iii)	Number of Channels	> 15 Channels		PASS	Section 7.5
15.247(a)(1)(iii)	Time of Occupancy	< 0.4 sec in 31.6 sec period		PASS	Section 7.6
15.247(d)	Band Edge / out-of-Band Emissions	Conducted $\geq$ 20dBc		PASS	Section 7.7, Section 7.8
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	RADIATED	PASS	Section 7.9, Section 7.10
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits	Line Conducted	Pass	Section 7.11

#### Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.

- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

## 7.2. 20dB Bandwidth Measurement

### 7.2.1. Test Limit

The maximum permissible 20dB bandwidth is 1 MHz, unless more than 15 non-overlapping channels are employed


### 7.2.2. Test Procedure used

ANSI C63.10: 2009 – Section 6.9.1

### 7.2.3. Test Setting


1. Set RBW  $\geq 1\%$  of the 20dB bandwidth
2. VBW  $\geq 3 \times$  RBW
3. Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace to stabilize
8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

### 7.2.4. Test Setup



## 7.2.5. Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	20dB Bandwidth (KHz)	Result
DH5	1	00	2402	931.4	Pass
DH5	1	39	2441	929.6	Pass
DH5	1	78	2480	932.6	Pass
2DH5	2	00	2402	1278.0	Pass
2DH5	2	39	2441	1276.0	Pass
2DH5	2	78	2480	1277.0	Pass
3DH5	3	00	2402	1277.0	Pass
3DH5	3	39	2441	1277.0	Pass
3DH5	3	78	2480	1278.0	Pass



## 2DH5 20dB Bandwidth

### Channel 00 (2402MHz)



### Channel 39 (2441MHz)



### Channel 78 (2480MHz)



### 3DH5 20dB Bandwidth

#### Channel 00 (2402MHz)



#### Channel 39 (2441MHz)



#### Channel 78 (2480MHz)



### 7.3. Output Power Measurement

#### 7.3.1. Test Limit

The maximum out power permissible output power is 0.125 Watt.


#### 7.3.2. Test Procedure Used

ANSI C63.10: 2009 – Section 6.10.1

#### 7.3.3. Test Setting


1. Set RBW  $\geq$  the 20 dB bandwidth of the emission being measured.
2. VBW  $\geq 3 \times$  RBW
3. Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace to stabilize, Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (don't forget added the external attenuation and cable loss)

#### 7.3.4. Test Setup



### 7.3.5. Test Result

Test Mode	Frequency (MHz)	Data Rate (Mbps)	Channel No.	Peak Power	
				(dBm)	(mw)
DH5	2402	1.0	00	0.279	1.066
DH5	2441	1.0	39	1.490	1.409
DH5	2480	1.0	78	2.054	1.605
2DH5	2402	2.0	00	0.700	1.175
2DH5	2441	2.0	39	1.864	1.536
2DH5	2480	2.0	78	2.405	1.740
3DH5	2402	3.0	00	0.686	1.171
3DH5	2441	3.0	39	1.824	1.522
3DH5	2480	3.0	78	2.341	1.714






### Channel 78 (2480MHz)



### 2DH5 Output Power

### Channel 00 (2402MHz)



### Channel 39 (2441MHz)



### Channel 78 (2480MHz)




### 3DH5 Output Power


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



## 7.4. Carrier Frequency Separation Measurement

### 7.4.1. Test Limit

The minimum permissible channel separation for this system is 2/3 the value of the 20dB BW.


### 7.4.2. Test Procedure Used

ANSI C63.10: 2009 – Section 7.7.2

### 7.4.3. Test Setting


1. Span = wide enough to capture the peaks of two adjacent channels.
2. RBW  $\geq 1$  % of the span
3. VBW  $\geq$  RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

### 7.4.4. Test Setup




### 7.4.5. Test Result

Test Mode	Frequency (MHz)	Data Rate (Mbps)	Channel No.	Limit	Result
DH5	2402	1.0	00	0.621	Pass
DH5	2441	1.0	39	0.620	Pass
DH5	2480	1.0	78	0.622	Pass
2DH5	2402	2.0	00	0.852	Pass
2DH5	2441	2.0	39	0.851	Pass
2DH5	2480	2.0	78	0.851	Pass
3DH5	2402	3.0	00	0.851	Pass
3DH5	2441	3.0	39	0.851	Pass
3DH5	2480	3.0	78	0.852	Pass




### Channel 78 (2480MHz)




### 2DH5 Carrier Frequency Separation

### Channel 00 (2402MHz)



### Channel 39 (2441MHz)



### Channel 78 (2480MHz)




### 3DH5 Carrier Frequency Separation


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



## **7.5. Number of Hopping Channels Measurement**

### **7.5.1. Test Limit**

This frequency hopping system must employ a minimum of 15 hopping channels.


### **7.5.2. Test Procedure Used**

ANSI C63.10: 2009 – Section 7.7.3

### **7.5.3. Test Settling**

1. Span = the frequency band of operation.
2. RBW  $\geq$  1 % of the span
3. VBW  $\geq$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

### **7.5.4. Test Setup**







### 7.5.5. Test Result

Test Mode	Frequency (MHz)	Data Rate (Mbps)	Channel No.	Limit (Hopping Channels)	Result
DH5	2402~2480	1.0	79	$\geq 15$	Pass
2DH5	2402~2480	2.0	79	$\geq 15$	Pass
3DH5	2402~2480	3.0	79	$\geq 15$	Pass

#### DH5 Number of Hopping Channels



2402 ~ 2421MHz

2422 ~ 2441MHz



2442 ~ 2461MHz


2462 ~ 2480MHz






## 2DH5 Number of Hopping Channels


2402 ~ 2421MHz




2422 ~ 2441MHz



2442 ~ 2461MHz




2462 ~ 2480MHz




### 3DH5 Number of Hopping Channels


2402 ~ 2421MHz




2422 ~ 2441MHz



2442 ~ 2461MHz



2462 ~ 2480MHz



## **7.6. Time of Occupancy Measurement**

### **7.6.1. Test Limit**

The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

### **7.6.2. Test Procedure Used**

ANSI C63.10: 2009 – Section 7.7.4


### **7.6.3. Test Settling**

1. Span = zero span, centered on a hopping channel.
2. RBW = 1MHz
3. VBW  $\geq$  RBW
4. Sweep time = as necessary to capture the entire dwell time per hopping channel
5. Detector = Peak
6. Trace mode = max hold

If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (data rate, modulation format, etc.), repeat this test for each variation.


An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.

#### 7.6.4. Test Setup




### 7.6.5. Test Result

Test Mode	Frequency (MHz)	Data Rate (Mbps)	Channel No.	Time of Occupancy (ms)	Limit (ms)	Result
3DH1	2441	1.0	39	124.80	< 400	Pass
3DH3	2441	2.0	39	262.40	< 400	Pass
3DH5	2441	3.0	39	323.68	< 400	Pass




Note: Test Time Period:  $0.4 \times 79 = 31.6$  sec, Hopping Times Within 1 sec:  $40/50 \text{ msec} = 800$  hops/sec.

The Maximum Occupancy Time within 31.6 sec:  $[(0.390 \text{ ms} \times 800) / 79] \times 31.6 = 124.80 \text{ msec}$ .



Note: Test Time Period:  $0.4 \times 79 = 31.6$ sec, Hopping Times Within 1sec:  $20/50$ msec=400hops/sec.

The Maximum Occupancy Time within 31.6sec:  $[(1.64\text{ms} \times 400)/79] \times 31.6 = 262.40$  msec.



Note: Test Time Period:  $0.4 \times 79 = 31.6$ sec, Hopping Times Within 1sec:  $14/50$ msec=280 hops/sec.

The Maximum Occupancy Time within 31.6sec:  $[(2.890\text{ms} \times 280)/79] \times 31.6 = 323.68$ msec.

## **7.7. Band-edge Compliance Measurement**

### **7.7.1. Test Limit**

The maximum permissible emission level is 20 dBc. Any emission lying outside of the emission bandwidth and in a restricted band is subject to a field strength limit specified in Section 15.209 of the Title 47 CFR.


### **7.7.2. Test Procedure Used**

ANSI C63.10: 2009 – Section 7.7.9

### **7.7.3. Test Setting**

1. Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
2. RBW  $\geq$  1% of spectrum analyzer display span
3. VBW  $\geq$  RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.

**7.7.4. Test Setup**



### 7.7.5. Test Result


Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Limit (MHz)	Result
DH5	1	00	2402	20dBc	Pass
DH5	1	78	2480	20dBc	Pass
2DH5	2	00	2402	20dBc	Pass
2DH5	2	78	2480	20dBc	Pass
3DH5	3	00	2402	20dBc	Pass
3DH5	3	78	2480	20dBc	Pass

#### DH5 Band-edge Compliance

Channel 00 (2402MHz)



Channel 78 (2480MHz)



#### 2DH5 Band-edge Compliance

Channel 00 (2402MHz)



Channel 78 (2480MHz)



### 3DH5 Band-edge Compliance

Channel 00 (2402MHz)




Channel 78 (2480MHz)




### DH5 Band-edge Compliance within Hopping Mode

Channel 00 (2402MHz)



Channel 78 (2480MHz)



## **7.8. Conducted Spurious Emissions Measurement**

### **7.8.1. Test Limit**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### **7.8.2. Test Procedure Used**


ANSI C63.10: 2009 – Section 7.7.10

### **7.8.3. Test Setting**

1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10<sup>th</sup> harmonic. Typically, several plots are required to cover this entire span.
2. RBW = 100 KHz
3. VBW  $\geq$  RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

#### 7.8.4. Test Setup




### 7.8.5. Test Result

Test Mode	Data Rate (Mbps)	Channel No.	Frequency (MHz)	Limit (MHz)	Result
DH5	1	00	2402	20dBc	Pass
DH5	1	39	2441	20dBc	Pass
DH5	1	78	2480	20dBc	Pass
2DH5	2	00	2402	20dBc	Pass
2DH5	2	39	2441	20dBc	Pass
2DH5	2	78	2480	20dBc	Pass
3DH5	3	00	2402	20dBc	Pass
3DH5	3	39	2441	20dBc	Pass
3DH5	3	78	2480	20dBc	Pass

### DH5 Conducted Spurious Emissions


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)




## 2DH5 Conducted Spurious Emissions


Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




### 3DH5 Conducted Spurious Emissions


Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)





## 7.9. Radiated Spurious Emission Measurement

### 7.9.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [V/m]	Measured Distance [Meters]
0.009 – 0.490	2400/F (kHz)	300
0.490 – 1.705	24000/F (kHz)	30
1.705 - 30	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

### 7.9.2. Test Procedure Used

ANSI C63.10-2009 – Section 7.10.1 & Section 7.10.2

### 7.9.3. Test Setting

#### Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize




### Average Field Strength Measurements


1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be  $> 2 \times \text{span}/\text{RBW}$ )
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

#### **7.9.4. Test Setup**


##### 9kHz ~ 30MHz Test Setup:



##### 30MHz ~ 1GHz Test Setup:



### Above 1GHz Test Setup:



### 7.9.5. Test Result


Test Mode:	3DH5	Test Site:	AC1
Test Channel:	39	Test Engineer:	Roy Cheng
Remark:	1. Average measurement was not performed if peak level lower than average limit. 3. <b>The worst case of Radiated Spurious Emission</b>		

Mark	Frequency (MHz)	Reading Level (dBμV/m)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3700.00	34.22	4.02	38.24	74.0	-35.76	Peak	Horizontal
	4884.50	43.35	6.65	50.00	74.0	-24.00	Peak	Horizontal
*	7324.00	39.96	14.02	53.98	73.7	-19.72	Peak	Horizontal
*	9764.00	37.35	16.25	53.60	73.7	-20.10	Peak	Horizontal
	3700.00	39.83	4.02	43.85	74.0	-30.15	Peak	Vertical
	4884.50	47.30	6.65	53.95	74.0	-20.05	Peak	Vertical
*	7323.00	38.64	14.01	52.65	73.7	-21.05	Peak	Vertical
*	9764.00	36.36	16.25	52.61	73.7	-21.09	Peak	Vertical

Note: "\*" is not in restricted band, its limit is 20dBc of the fundamental emission level (93.7dBμV/m).


### The worst case of Radiated Emission 9KHz ~ 1GHz and 18GHz ~ 25GHz:

Engineer: Roy Cheng	
Site: AC1	Time: 2013/11/03 - 17:45
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: VULB9162_0.03-8GHz	Polarity: Horizontal
EUT: Bluetooth Keyboard	Power: By Battery
<b>Worst Case Mode : DH5 Channel 2402MHz</b>	




No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		530.520	32.717	13.989	-13.283	46.000	18.728	PK
2	*	710.940	35.997	14.629	-10.003	46.000	21.368	PK

Engineer: Roy Cheng	
Site: AC1	Time: 2013/11/03 - 17:48
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: VULB9162_0.03-8GHz	Polarity: Vertical
EUT: Bluetooth Keyboard	Power: By Battery
<b>Worst Case Mode : DH5 Channel 2402MHz</b>	




No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		523.730	33.114	14.481	-12.886	46.000	18.633	PK
2	*	728.400	37.156	15.582	-8.844	46.000	21.574	PK

Engineer: Roy Cheng	
Site: AC1	Time: 2013/12/31 - 16:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: FMZB1519_0.009-30MHz	Polarity: Face On
EUT: Bluetooth Keyboard	Power: By Battery
Note: There is the ambient noise within frequency range 9kHz~30MHz.	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			0.049	50.367	29.861	-63.422	113.789	20.505	PK
2		*	0.105	44.143	23.996	-63.029	107.173	20.147	PK

Engineer: Roy Cheng	
Site: AC1	Time: 2013/12/31 - 16:41
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: FMZB1519_0.009-30MHz	Polarity: Face On
EUT: Bluetooth Keyboard	Power: By Battery
Note: There is the ambient noise within frequency range 9kHz~30MHz.	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2.513	30.495	10.336	-39.005	69.500	20.159	PK
2		*	7.041	30.974	10.579	-38.526	69.500	20.395	PK


Engineer: Roy Cheng	
Site: AC1	Time: 2013/12/31 - 15:33
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9170_18-40GHz	Polarity: Horizontal
EUT: Bluetooth Keyboard	Power: By Battery
Note: There is the ambient noise within frequency range 18GHz~25GHz.	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			26767.000	58.270	18.492	-15.730	74.000	39.778	PK
2			26767.000	45.128	5.350	-8.872	54.000	39.778	AV
3			36370.000	63.559	21.622	-10.441	74.000	41.937	PK
4		*	36370.300	47.573	5.636	-6.427	54.000	41.937	AV



Engineer: Roy Cheng	
Site: AC1	Time: 2013/12/31 - 16:44
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9170_18-40GHz	Polarity: Vertical
EUT: Bluetooth Keyboard	Power: By Battery
Note: There is the ambient noise within frequency range 18GHz~25GHz.	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			23203.000	57.745	19.023	-16.255	74.000	38.722	PK
2			23203.300	43.072	4.350	-10.928	54.000	38.722	AV
3			35424.000	63.032	21.445	-10.968	74.000	41.587	PK
4		*	35424.320	47.591	6.004	-6.409	54.000	41.587	AV

## 7.10. Radiated Restricted Band Edge Measurement


### 7.10.1. Test Result

Engineer: Roy	
Site: AC1	Time: 2013/12/23 - 15:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Bluetooth Keyboard	Power: DC 3V
<b>Worst Case Mode:</b> Transmit at Channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2350.232	58.520	27.737	-15.480	74.000	30.783	PK
2			2390.000	55.974	25.290	-18.026	74.000	30.684	PK
3		*	2402.073	89.254	58.593	N/A	N/A	30.661	PK

Engineer: Roy	
Site: AC1	Time: 2013/12/23 - 15:41
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Bluetooth Keyboard	Power: DC 3V
<b>Worst Case Mode:</b> Transmit at Channel 2402MHz by 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2349.997	44.982	14.198	-9.018	54.000	30.784	AV
2			2390.000	43.694	13.010	-10.306	54.000	30.684	AV
3		*	2402.073	88.773	58.112	N/A	N/A	30.661	AV

Engineer: Roy	
Site: AC1	Time: 2013/12/23 - 15:42
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Bluetooth Keyboard	Power: DC 3V
<b>Worst Case Mode:</b> Transmit at Channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2350.091	57.811	27.027	-16.189	74.000	30.784	PK
2			2390.000	56.116	25.432	-17.884	74.000	30.684	PK
3		*	2402.073	93.464	62.803	N/A	N/A	30.661	PK

Engineer: Roy	
Site: AC1	Time: 2013/12/23 - 15:43
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Bluetooth Keyboard	Power: DC 3V
<b>Worst Case Mode:</b> Transmit at Channel 2402MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1			2349.997	46.967	16.183	-7.033	54.000	30.784	AV
2			2390.000	43.633	12.949	-10.367	54.000	30.684	AV
3		*	2402.073	93.285	62.624	N/A	N/A	30.661	AV

Engineer: Roy	
Site: AC1	Time: 2013/12/23 - 15:43
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Bluetooth Keyboard	Power: DC 3V
<b>Worst Case Mode:</b> Transmit at Channel 2480MHz by 3DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2479.969	92.264	61.602	N/A	N/A	30.662	PK
2			2483.500	55.844	25.171	-18.156	74.000	30.673	PK

Engineer: Roy	
Site: AC1	Time: 2013/12/23 - 15:54
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Bluetooth Keyboard	Power: DC 3V
<b>Worst Case Mode:</b> Transmit at Channel 2480MHz by 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	92.053	61.390	N/A	N/A	30.662	AV
2			2483.500	43.498	12.825	-10.502	54.000	30.673	AV


Engineer: Roy	
Site: AC1	Time: 2013/12/23 - 15:54
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Bluetooth Keyboard	Power: DC 3V
<b>Worst Case Mode:</b> Transmit at Channel 2480MHz by 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	93.962	63.299	N/A	N/A	30.662	PK
2			2483.500	55.537	24.864	-18.463	74.000	30.673	PK



Engineer: Roy	
Site: AC1	Time: 2013/12/23 - 15:55
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Bluetooth Keyboard	Power: DC 3V
<b>Worst Case Mode:</b> Transmit at Channel 2480MHz by 3DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor	Type
1		*	2480.046	93.699	63.036	N/A	N/A	30.662	AV
2			2483.500	43.554	12.881	-10.446	54.000	30.673	AV

## 7.11. AC Conducted Emissions Measurement


### 7.11.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 Limits		
Frequency (MHz)	QP (dB $\mu$ V)	Average (dB $\mu$ V)
0.15 - 0.50	66 - 56	56 – 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

### 7.11.2. Test Setup




### 7.11.3. Test Result

Engineer: Roy Cheng	
Site: SR2	Time: 2013/12/31 - 09:56
Limit: FCC_Part15.207_CE_Class B	Margin: 0
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: Bluetooth Keyboard	Power: AC 120V/60Hz
Note: Charging and Communication	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor	Type
1			0.154	37.640	26.900	-28.142	65.781	10.740	QP
2			0.154	31.040	20.300	-24.742	55.781	10.740	AV
3			0.330	29.128	19.100	-30.323	59.451	10.028	QP
4			0.330	21.028	11.000	-28.423	49.451	10.028	AV
5			0.390	35.077	25.000	-22.987	58.064	10.077	QP
6		*	0.390	33.177	23.100	-14.887	48.064	10.077	AV
7			2.374	26.661	16.800	-29.339	56.000	9.861	QP
8			2.374	20.461	10.600	-25.539	46.000	9.861	AV
9			2.818	24.547	14.700	-31.453	56.000	9.847	QP
10			2.818	18.247	8.400	-27.753	46.000	9.847	AV
11			4.514	23.491	13.500	-32.509	56.000	9.992	QP
12			4.514	16.991	7.000	-29.009	46.000	9.992	AV

Engineer: Roy Cheng	
Site: SR2	Time: 2013/12/31 - 10:03
Limit: FCC_Part15.207_CE_Class B	Margin: 0
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: Bluetooth Keyboard	Power: AC 120V/60Hz
Note: Charging and Communication	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor	Type
1			0.158	37.590	27.300	-27.979	65.568	10.290	QP
2			0.158	29.890	19.600	-25.679	55.568	10.290	AV
3			0.338	32.166	22.100	-27.087	59.252	10.066	QP
4			0.338	22.566	12.500	-26.687	49.252	10.066	AV
5			0.390	35.705	25.600	-22.359	58.064	10.105	QP
6		*	0.390	33.505	23.400	-14.559	48.064	10.105	AV
7			2.658	28.156	18.300	-27.844	56.000	9.856	QP
8			2.658	19.956	10.100	-26.044	46.000	9.856	AV
9			4.298	26.687	16.700	-29.313	56.000	9.987	QP
10			4.298	18.487	8.500	-27.513	46.000	9.987	AV
11			16.182	28.621	18.500	-31.379	60.000	10.121	QP
12			16.182	23.021	12.900	-26.979	50.000	10.121	AV

## 8. CONCLUSION

The data collected relate only the item(s) tested and show that the **Bluetooth Keyboard FCC ID: XJ4KB6226** is in compliance with Part 15C of the FCC Rules.