



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page: 1 of 55
Date : Apr. 14, 2009

Product Name: Bluetooth RS-232 Adapter
Model Number: BT-232B
Applicant: Uconnect International Co., Ltd.
13F., No.368, Sec. 1, Fuxing S. Rd., Taipei City 106 ,
Taiwan (R.O.C)
Date of Receipt: Apr. 09, 2009
Finished date of Test: Apr. 14, 2009
Applicable Standards: 47 CFR Part 15, Subpart C
ANSI C63.4:2003

We, **Spectrum Research & Testing Laboratory Inc.**, hereby certify that one sample of the above was tested in our laboratory with positive results according to the above-mentioned standards. The records in the report are an accurate account of the results. Details of the results are given in the subsequent pages of this report.

Checked By :

Kunter Jin

(Kunter Jin)

Date:

Apr. 14, 2009

Approved By :

JH
(Johnson Ho, Director)

Date:

4/14/2009

NVLAP[®]

Lab Code: 200099-0



TEST REPORT

TABLE OF CONTENTS

1. DOCUMENT POLICY AND TEST STATEMENT.....	4
1.1 DOCUMENT POLICY.....	4
1.2 TEST STATEMENT	4
1.3 EUT MODIFICATION.....	4
2. DESCRIPTION OF EUT AND TEST MODE	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 DESCRIPTION OF SUPPORT UNIT.....	5
2.3 DESCRIPTION OF TEST MODE	6
3. DESCRIPTION OF APPLIED STANDARDS.....	6
4. TECHNICAL CHARACTERISTICS TEST	7
4.1 CHANNEL SEPARATION TEST	7
4.1.1 LIMIT	7
4.1.2 TEST EQUIPMENT	7
4.1.3 TEST SET-UP.....	7
4.1.4 TEST PROCEDURE.....	7
4.1.5 EUT OPERATING CONDITION.....	8
4.1.6 TEST RESULT.....	8
4.2 20DB BANDWIDTH	12
4.2.1 LIMIT	12
4.2.2 TEST EQUIPMENT	12
4.2.3 TEST SET-UP.....	12
4.2.4 TEST PROCEDURE.....	12
4.2.5 TEST RESULT.....	13
4.3 QUANTITY OF HOPPING CHANNEL TEST	16
4.3.1 LIMIT	16
4.3.2 TEST EQUIPMENT	16
4.3.3 TEST SET-UP.....	16
4.3.4 TEST PROCEDURE.....	16
4.3.5 EUT OPERATING CONDITION.....	16
4.3.6 TEST RESULT.....	17
4.4 TIME OF OCCUPANCY (DWELL TIME).....	18
4.4.1 LIMIT	18
4.4.2 TEST EQUIPMENT	18
4.4.3 TEST SET-UP.....	18
4.4.4 TEST PROCEDURE.....	18
4.4.5 EUT OPERATING CONDITION.....	18
4.4.6 TEST RESULT.....	19
4.5 PEAK POWER TEST	22
4.5.1 LIMIT	22
4.5.2 TEST EQUIPMENT	22
4.5.3 TEST SET-UP.....	23
4.5.4 TEST PROCEDURE.....	23
4.5.5 EUT OPERATING CONDITION.....	23
4.5.6 TEST RESULT.....	23



TEST REPORT

4.6	BAND EDGE TEST	27
4.6.1	LIMIT	27
4.6.2	TEST EQUIPMENT	28
4.6.3	TEST SET-UP.....	29
4.6.4	TEST PROCEDURE.....	30
4.6.5	EUT OPERATING CONDITION.....	30
4.6.6	TEST RESULT.....	30
4.7	FUNDERMENTAL & SPURIOUS RADIATED EMISSION TEST	33
4.7.1	LIMIT	33
4.7.2	TEST EQUIPMENT	34
4.7.3	TEST SET-UP.....	35
4.7.4	TEST PROCEDURE.....	37
4.7.5	EUT OPERATING CONDITION.....	37
4.7.6	TEST RESULT.....	38
5.	CONDUCTED EMISSION TEST FOR POWER PORT	46
5.1	LIMIT	46
5.2	TEST EQUIPMENT	46
5.3	TEST PROCEDURE.....	47
5.4	TEST SETUP.....	47
5.5	TEST RESULT.....	48
6.	ANTENNA APPLICATION.....	50
6.1	ANTENNA REQUIREMENT	50
6.2	RESULT	50
6.	PHOTOS OF TESTING	51
7.	TERMS OF ABBREVIATION	55

 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:4 of 55 Date : Apr. 14, 2009
---	----------------------	---

1. DOCUMENT POLICY AND TEST STATEMENT

1.1 DOCUMENT POLICY

- The report shall not be reproduced except in full, without the written approval of SRT Lab, Inc.
- The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

1.2 TEST STATEMENT

- The test results in the report apply only to the unit tested by SRT Lab.
- There was no deviation from the requirements of test standards during the test.
- AC power source, 120 VAC/60 Hz, was used during the test.

1.3 EUT MODIFICATION

- No modification in SRT Lab.

 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:5 of 55 Date : Apr. 14, 2009
---	----------------------	---

2. DESCRIPTION OF EUT AND TEST MODE

2.1 GENERAL DESCRIPTION OF EUT

Product	Bluetooth RS-232 Adapter
Model No.	BT-232B
Power Supply	PC USB Port, DC 5.0V~6.0V, 90 mA
Frequency Band	2400-2483.5 MHz
Number of Channel	79
Channel Spacing	1 MHz
Rated RF Output Power	94.3 dBuV/m@2480MHz
Modulation Type	GFSK
Bit Rate of Transmission	3Mbps
Mode of Operation	Duplex.
Antenna Gain	1.2 dBi
Operating Temperature Range	-20°C to +75°C
Channel Bandwidth	1 MHz
Antenna Type	PCB Printing
Duty Cycle	50 %
Carrier Frequency	2402-2480 MHz

NOTE :

For more detailed information, please refer to the EUT's specification or user's manual provided by manufacturer.

2.2 DESCRIPTION OF SUPPORT UNIT

The transmitter part of EUT was tested with a Notebook and configured by the requirement of ANSI C63.4. All interface ports were connected to the appropriate support units via specific cables. The support units and cables are listed below.

No	Device	Brand	Model #	FCC ID/DoC	Cable
1	NoteBook	COMPAQ	1525AP	DOC	power cable 2.0m (unshielding)
2	Dongle	ASUS	WL-BTD202	DOC	NA
3	NoteBook	COMPAQ	HSTNN-Q09C	DOC	Power cable 2.0m(shielding)

NOTE : For the actual test configuration, please refer to the photos of testing.



TEST REPORT

2.3 DESCRIPTION OF TEST MODE

79 channels are provided by EUT. Three channels of lower, medium and higher were chosen for test.

Channel	Frequency (MHz)
00	2402
39	2441
78	2480

NOTE :

1. Below 1 GHz, the channel 0, 39 and 78 were pre-tested in chamber.
2. Above 1 GHz, the channel 0, 39 and 78 were tested individually.

3. DESCRIPTION OF APPLIED STANDARDS

The EUT is a kind of wireless product and to be connected with a PC system for normal use. According to the specifications provided by the applicant, it must comply with the requirements of the following standards:

47 CFR Part 15, Subpart C
ANSI C63.4: 2003

All tests have been performed and recorded as the above standards.

 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:7 of 55 Date : Apr. 14, 2009
---	----------------------	---

4. TECHNICAL CHARACTERISTICS TEST

4.1 CHANNEL SEPARATION TEST

4.1.1 LIMIT

FCC Part15, Subpart C Section 15.247(a)(1). Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Frequency Range (MHz)	Limit(kHz)
902-928	>25kHz
2400-2483.5	>25kHz
5725-5850	>25kHz


4.1.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test :

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-40GHz	ROHDE & SCHWARZ	FSP40/ 100093	SEP. 2009 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.1.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

4.1.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.
 Printed out the test result from the spectrum by hard copy function.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page:8 of 55
Date : Apr. 14, 2009

4.1.5 EUT OPERATING CONDITION

1. Set the EUT under transmission condition continuously at a specific channel frequency.
2. The EUT was set to the highest available power level.

4.1.6 TEST RESULT


Temperature:	25°C	Humidity:	63%RH
Spectrum Detector:	PK	Tested by:	Kunter Jin
Test Result:	PASS	Tested Date:	Apr.11,2009

Channel Number	Channel Frequency (MHz)	Separation Read Value (kHz)	Minimum Limit(20dB Bandwidth) (kHz)
00	2402	976.000	25
39	2441	1004.000	25
78	2480	1000.000	25



TEST REPORT


CH00:





TEST REPORT


CH39:





TEST REPORT

CH78:



 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:12 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.2 20dB Bandwidth

4.2.1 LIMIT

Frequency Range (MHz)	Limit(kHz)				
	Quantity of Hopping Channel	50	25	15	75
902-928		<250	>250	NA	NA
2400-2483.5		NA	NA	>1000	<1000


4.2.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. center
SPECTRUM	9kHz-40GHz	ROHDE & SCHWARZ	FSP40/ 100093	SEP. 2009 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.2.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

4.2.4 TEST PROCEDURE

The EUT was operated in hopping mode or any specific channel.
 Printed out the test result from the spectrum by hard copy function.




4.2.5 TEST RESULT

Temperature:	25°C	Humidity:	63%RH
Spectrum Detector:	PK	Tested by:	Kunter Jin
Test Result:	PASS	Tested Date:	Apr. 11, 2009

Channel Number	Channel Frequency (MHz)	20dB Down Bandwidth (KHz)
0	2402	276
39	2441	280
78	2480	280

CH00:






**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT


Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page:14 of 55
Date : Apr. 14, 2009

CH39:





CH78:



 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:16 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.3 QUANTITY OF HOPPING CHANNEL TEST

4.3.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit (Quantity of Hopping Channel)			
	20dB Bandwidth <250kHz	20dB Bandwidth >250kHz	20dB Bandwidth <1MHz	20dB Bandwidth >1MHz
902-928	50	25	N/A	N/A
2400-2483.5	N/A	N/A	75	15
5725-5850	N/A	N/A	75	N/A


4.3.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/Facilities	Specifications	Manufacturer	Model#/Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-40GHz	ROHDE & SCHWARZ	FSP40/100093	SEP. 2009 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

4.3.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.
 Printed out the test result from the spectrum by hard copy function.

4.3.5 EUT OPERATING CONDITION

1. Set the EUT under frequency hopping transmission condition.
2. The EUT was set to the highest available power level.




TEST REPORT

4.3.6 TEST RESULT

Temperature:	25°C	Humidity:	63%RH
Spectrum Detector:	PK	Tested by:	Kunter Jin
Test Result:	PASS	Tested Date:	Apr.11,2009

Hopping Channel Frequency Range(MHz)	Quantity of Hopping Channel Read Value	Quantity of Hopping Channel Limit
2402~2480	79	75

CH00-CH78



 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:18 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.4 TIME OF OCCUPANCY (Dwell Time)

4.4.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit (ms)		
	20dB Bandwidth <250kHz(50Channel)	20dB Bandwidth >250kHz(25Channel)	20dB Bandwidth <1MHz(75Channel)
902-928	400(20s)	400(10s)	NA
2400-2483.5	NA	NA	400(30s)
5725-5850	NA	NA	400(30s)

NOTE: The “()” is all channel’s average time of occupancy.


4.4.2 TEST EQUIPMENT

The following test equipment was used during the test:

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-40GHz	ROHDE & SCHWARZ	FSP40/ 100093	SEP. 2009 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST SET-UP



The EUT was connected to a spectrum through a 50Ω RF cable.

4.4.4 TEST PROCEDURE

The EUT was operating in hopping mode or could be controlled its channel.
 Printed out the test result from the spectrum by hard copy function.

4.4.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.




TEST REPORT

4.4.6 TEST RESULT

Temperature:	25°C	Humidity:	63%RH
Spectrum Detector:	PK	Tested by:	Kunter Jin
Test Result:	PASS	Tested Date:	Apr.11,2009

Channel Number	Channel Frequency (MHz)	Pulse Time (μs)	Time of Occupancy (Dwell Time) (ms)	Average Time of Occupancy Limit (ms)
0	2402.00	398	125.768	400
39	2441.00	382	120.832	400
78	2480.00	383	121.028	400


CH00:





TEST REPORT


Ch39:





TEST REPORT

CH78:



 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:22 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.5 PEAK POWER TEST

4.5.1 LIMIT

FCC Part15, Subpart C Section 15.247.

Frequency Range (MHz)	Limit(w)				
	Quantity of Hopping Channel	50	25	15	75
902-928		1(30dBm)	0.125(21dBm)	NA	NA
2400-2483.5		NA	NA	0.125(21dBm)	1(30dBm)
5725-5850		NA	NA	NA	1(30dBm)

4.5.2 TEST EQUIPMENT


The following test equipment was used during the test :

Equipment/ Facilities	Specifications	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-40GHz	ROHDE & SCHWARZ	FSP40/ 100093	SEP. 2009 ETC
POWER METER	N/A	BOONTON	4232A/ 29001	MAY 2009 ETC
POWER SENSOR	DC-8GHz 50 Ω	BOONTON	51011EMC/ 31181	JUN. 2009 ETC

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.

 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:23 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.5.3 TEST SET-UP



The EUT was connected to a spectrum through a 50 Ω RF cable.

4.5.4 TEST PROCEDURE

The EUT was operating in hopping mode or could control its channel.
 Printed out the test result from the spectrum by hard copy function.
 Recorded the read value of the power meter.

4.5.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.5.6 TEST RESULT

Temperature:	25°C	Humidity:	63%RH
Spectrum Detector:	PK	Tested by:	Kunter Jin
Test Result:	PASS	Tested Date:	Apr. 11, 2009

Channel Number	Channel Frequency (MHz)	Peak Output Power (dBm)	Peak Power Limit (dBm)
0	2402.0000	-0.33	30
39	2441.0000	-1.59	30
78	2480.0000	-3.49	30




**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page:24 of 55
Date : Apr. 14, 2009


CH00:





TEST REPORT


CH39:





TEST REPORT

CH78:



 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:27 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.6 BAND EDGE TEST

4.6.1 LIMIT

FCC Part15, Subpart C Section 15.249 (c), Emission radiated outside of the specified frequency bands, except for harmonics, shall attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Operating Frequency Range (MHz)	Limit (dBμV/m)	
	Peak	Average
902-928	74	54
2400-2483.5		
5725-5850		

FCC Part15, Subpart C Section 15.247. In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

OPERATING FREQUENCY RANGE (MHz)	SPURIOUS EMISSION FREQUENCY (MHz)	LIMIT	
		Peak power ration to emission(dBc)	Emission level(dBuV/m)
902 - 928	<902	>20	NA
	>928	>20	NA
	960-1240	NA	54
2400 - 2483.5	<2400	>20	NA
	>2483.5-2500	NA	54
5725 - 5850	<5350-5460	NA	54
	<5725	>20	NA
	>5850	>20	NA

 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:28 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.6.2 TEST EQUIPMENT

The following test equipment was used during the test :


Equipment/ Facilities	Specification	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
SPECTRUM	9kHz-40GHz	ROHDE & SCHWARZ	FSP40/ 100093	SEP. 2009 ETC
EMI TEST RECEIVER	9 kHz TO 2750 MHz	ROHDE & SCHWARZ	ESCS30/ 830245/012	OCT. 2009 ETC
SPECTRUM	9KHz-26.5GHz	HP	8953E/ 3710A03220	SEP 2009 ETC
PRE-AMPLIFIER	1GHz-26.5GHz Gain:30dB	HP	8449B/ 3008A01019	NOV. 2009 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3142/ 9701-1124	FEB. 2010 SRT
HORN ANTENNA	1GHz to 18GHz	EMCO	3115/ 9602-4681	DEC. 2009 ETC
OATS	3 - 10 M measurement	SRT	SRT-1	APR. 2010 SRT

NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.




4.6.3 TEST SET-UP

FOR RF CONDUCTED TEST (dBc)



The EUT was connected to the spectrum through a 50Ω RF cable.

FOR RADIATED EMISSION TEST



NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.



4.6.4 TEST PROCEDURE

1. The EUT was operating in hopping mode or could be controlled its channel.
Printed out the test result from the spectrum by hard copy function.
2. The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The measurements were made at an open area test site with 3 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

4.6.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

4.6.6 TEST RESULT

Temperature:	25°C	Humidity:	63%RH
Spectrum Detector:	PK & AV	Tested by:	Kunter Jin
Test Result:	PASS	Tested Date:	Apr. 11, 2009

1. Conducted emission test


Frequency (MHz)	PEAK POWER OUTPUT (dBm)	Emission read Value (dBm)	Result of Band edge (dBc)	Band edge LIMIT (dBc)
<2400	-5.44	-54.36	48.92	>20dBc
>2483.5	-8.81	-53.92	45.11	>20dBc

2. Radiated emission test

Frequency (MHz)	Antenna polarization (H/V)	Reading (dBuV)	Emission (dBuV/m)	Band edge Limit (dBuV)
		Strength	Strength	Strength
<2400	H	37.9	33.7	54.0
<2400	H	36.1	31.9	54.0
>2483.5	V	33.3	29.3	54.0
>2483.5	V	37.9	33.9	54.0




CH00:





Ch78:





TEST REPORT

4.7 FUNDAMENTAL & SPURIOUS RADIATED EMISSION TEST

4.7.1 LIMIT

FCC Part15, Subpart C Section 15.209 limit of radiated emission for frequency below1000MHz. The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Distance (m)	Field Strength (dB μ V/m)
30 - 88	3	40.0
88 - 216	3	43.5
216 - 960	3	46.0
ABOVE 960	3	54.0

- NOTE** : 1. In the emission tables above , the tighter limit applies at the band edges.
2. Distance refers to the distance between measuring instrument , antenna , and the closest point of any part of the device or system.

FCC Part 15, Section15.35(b) limit of radiated emission for frequency above 1000 MHz

Frequency (MHz)	Class A (dBUV/m) (at 3m)		Class B (dBUV/m) (at 3m)	
	Peak	Average	Peak	Average
Above 1000	80.0	60.0	74.0	54.0

 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:34 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.7.2 TEST EQUIPMENT

The following test equipment was used during the radiated emission test :


Equipment/ Facilities	Specification	Manufacturer	Model#/ Serial#	Due Date of Cal. & Cal. Center
EMI TEST RECEIVER	9kHz TO 2.75 GHz	ROHDE & SCHWARZ	ESCS30 / 830245/012	OCT. 2009 ETC
BI-LOG ANTENNA	26 MHz TO 2 GHz	EMCO	3142B / 0005-1534	NOV. 2009 ETC
OATS	3 – 10 M MEASUREMENT	SRT	SRT-1	NOV. 2009 SRT
COAXIAL CABLE	25M	TIMES	J400 / #25M	AUG. 2009 ETC
FILTER	2 LINE, 30A	FIL.COIL	FC-943 / 869	NCR
PRE-AMPLIFIER	1GHz-26.5GHz Gain:30dB	HP	8449B/ 3008A01019	NOV. 2009 ETC
BI-LOG ANTENNA	25 MHz TO 2 GHz	EMCO	3142/ 9701-1124	FEB. 2010 SRT

NOTE:

1. The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.
2. The Open Area Test Site (SRT-1) is registered by FCC with No. 90957 and VCCI with No. R-1081.
3. The Open Area Test Site (SRT-2) is registered by FCC with No. 98458 and VCCI with No. R-1168.




4.7.3 TEST SET-UP



NOTE :

1. The EUT system was put on a wooden table with 0.8m heights above a ground plane.
2. For the actual test configuration, please refer to the photos of testing.

TEST SET- UP (1GHz - 25GHz)



NOTE :

- 1.The EUT system was put on a wooden table with 0.8m heights above a ground plane.
- 2.For the actual test configuration, please refer to the photos of testing.



4.7.4 TEST PROCEDURE

The EUT was tested according to the requirement of ANSI C63.4 and CISPR 22. The measurements were made at an open area test site with 3 meter measurement distance under 1 GHz and with 3m distance above 1GHz. The frequency spectrum measured started from 30 MHz. Under 1 GHz. All readings were quasi-peak values with 120 kHz resolution bandwidth of the test receiver. Above 1 GHz, the measurements were made at an open area test site with 3 meter measurement distance and all readings were peak and average values with 1 MHz resolution bandwidth of the test receiver. The EUT system was operated in all typical methods by users. The cables connected to EUT and support units were moved to find the maximum emission levels for each frequency.

4.7.5 EUT OPERATING CONDITION

Same as section 4.1.5 of this report.

 Spectrum Research & Testing Lab., Inc. No. 101-10, Ling 8, Shan-Tong Li, Chung-Li City, Taoyuan, Taiwan	<h1>TEST REPORT</h1>	Reference No.: A09040901 Report No.: FCC A09040901 FCCID: XJ8-BT-232B Page:38 of 55 Date : Apr. 14, 2009
---	----------------------	--

4.7.6 TEST RESULT

Temperature:	22°C	Humidity:	67 %RH
Frequency Range:	30 – 1000 MHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested Mode:	Standby
Tested By:	Kunter Jin	Tested Date:	Apr. 11, 2009

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
453.8360	2.98	16.89	10.5	30.4	46.0	-15.6	205	2.40
571.0125	3.69	18.71	11.2	33.6	46.0	-12.4	136	2.20
680.3371	4.31	20.80	4.9	30.0	46.0	-16.0	94	2.30
772.4916	4.65	21.34	10.0	36.0	46.0	-10.0	103	1.50
840.3951	4.69	22.52	2.9	30.1	46.0	-15.9	351	1.85
942.2743	4.88	23.07	6.1	34.1	46.0	-11.9	12	1.71

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
453.8360	2.98	16.89	10.5	30.4	46.0	-15.6	51	1.40
571.0125	3.69	18.71	11.2	33.6	46.0	-12.4	226	1.20
680.3371	4.31	20.80	4.9	30.0	46.0	-16.0	155	1.60
772.4916	4.65	21.34	10.0	36.0	46.0	-10.0	38	1.35
840.3951	4.69	22.52	2.9	30.1	46.0	-15.9	349	1.48
942.2743	4.88	23.07	6.1	34.1	46.0	-11.9	135	1.27

NOTE :

1. Measurement uncertainty is +/-3.7dB.
2. "**": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



TEST REPORT

Temperature:	32°C	Humidity:	68 %RH
Frequency Range:	30 – 1000 MHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested Mode:	Link
Tested By:	Kunter Jin	Tested Date:	Apr. 11, 2009

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
39.3494	0.89	9.91	13.9	24.7	40.0	-15.3	355	2.50
136.5575	1.70	11.28	13.6	26.6	43.5	-16.9	27	1.99
680.1953	4.31	20.80	14.8	39.9	46.0	-6.1	342	1.81
772.5725	4.65	21.34	11.1	37.1	46.0	-8.9	5	1.72
840.3153	4.69	22.52	12.8	40.0	46.0	-6.0	338	1.58
973.1430	5.07	22.23	6.9	34.2	54.0	-19.8	348	1.39

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
39.0846	0.89	9.91	11.6	22.4	40.0	-17.6	17	1.79
284.0155	2.64	13.27	11.1	27.0	46.0	-19.0	340	1.62
571.2052	3.69	18.71	16.7	39.1	46.0	-6.9	155	1.58
680.2162	4.31	20.80	11.3	36.4	46.0	-9.6	351	1.42
840.1705	4.69	22.52	10.4	37.6	46.0	-8.4	97	1.33
972.9941	5.07	22.26	7.1	34.4	54.0	-19.6	82	1.25

NOTE :

1. Measurement uncertainty is +/-3.7dB.
2. "": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



TEST REPORT

Temperature:	32°C	Humidity:	68%RH
Frequency Range:	30 – 1000 MHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested Mode:	TX_2402MHz
Tested By:	Kunter Jin	Tested Date:	Apr. 11, 2009

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
453.8360	2.98	16.89	10.5	30.4	46.0	-15.6	86	2.90
571.0125	3.69	18.71	11.2	33.6	46.0	-12.4	148	2.50
680.3371	4.31	20.80	4.9	30.0	46.0	-16.0	25	2.20
772.4916	4.65	21.34	10.0	36.0	46.0	-10.0	99	1.80
840.3951	4.69	22.52	2.9	30.1	46.0	-15.9	279	1.60
942.2743	4.88	23.07	6.1	34.1	46.0	-11.9	234	1.20

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
136.3041	1.70	11.28	20.5	33.5	43.5	-10.0	86	1.50
174.0456	1.82	8.97	13.2	24.0	43.5	-19.5	148	1.61
308.2234	2.49	14.27	7.1	23.9	46.0	-22.1	25	1.38
642.1264	4.61	20.04	6.1	30.8	46.0	-15.2	99	1.45
840.1257	4.69	22.52	2.9	30.1	46.0	-15.9	279	1.25
917.2018	4.77	23.74	6.9	35.4	46.0	-10.6	234	1.18

NOTE :

1. Measurement uncertainty is +/-3.7dB.
2. "": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page:41 of 55
Date : Apr. 14, 2009

Temperature:	32°C	Humidity:	68%RH
Frequency Range:	30 – 1000 MHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested Mode:	TX_2441MHz
Tested By:	Kunter Jin	Tested Date:	Apr. 11, 2009

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
68.5454	1.13	5.58	21.5	28.2	40.0	-11.8	83	4.00
286.0197	2.65	13.37	12.6	28.6	46.0	-17.4	18	3.50
308.5471	2.49	14.27	7.2	24.0	46.0	-22.0	120	3.40
642.0066	4.61	20.04	13.1	37.8	46.0	-8.2	169	2.40
840.1024	4.69	22.52	2.0	29.2	46.0	-16.8	209	1.60
917.2018	4.77	23.74	6.9	35.4	46.0	-10.6	230	1.20

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
136.3041	1.70	11.28	20.5	33.5	43.5	-10.0	101	1.20
174.0456	1.82	8.97	13.2	24.0	43.5	-19.5	162	1.30
308.2234	2.49	14.27	7.1	23.9	46.0	-22.1	219	1.60
642.1264	4.61	20.04	6.1	30.8	46.0	-15.2	331	2.50
840.1257	4.69	22.52	2.9	30.1	46.0	-15.9	171	3.40
917.1118	4.77	23.74	6.9	35.4	46.0	-10.6	33	3.50

NOTE :

1. Measurement uncertainty is +/-3.7dB.
2. "": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



TEST REPORT

Temperature:	32°C	Humidity:	68%RH
Frequency Range:	30 – 1000 MHz	Measured Distance:	3m
Receiver Detector:	Q.P.	Tested Mode:	TX_2480MHz
Tested By:	Kunter Jin	Tested Date:	Apr. 11, 2009

Antenna Polarization: Horizontal

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
68.1540	1.13	5.58	20.5	27.2	40.0	-12.8	82	4.00
286.1197	2.65	13.37	12.2	28.2	46.0	-17.8	108	3.50
308.3371	2.49	14.27	7.9	24.7	46.0	-21.3	20	3.40
642.6565	4.61	20.04	12.0	36.7	46.0	-9.3	69	2.40
840.3951	4.69	22.52	2.5	29.7	46.0	-16.3	239	1.60
917.7522	4.77	23.74	6.4	34.9	46.0	-11.1	233	1.20

Antenna Polarization: Vertical

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Reading Data (dBμV)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	AZ(°)	EL(m)
136.1455	1.70	11.28	21.5	34.5	43.5	-9.0	107	1.20
174.0456	1.82	8.97	15.2	26.0	43.5	-17.5	102	1.30
308.2234	2.49	14.27	7.4	24.2	46.0	-21.8	119	1.60
642.6446	4.61	20.04	6.9	31.6	46.0	-14.4	341	2.50
840.1257	4.69	22.52	2.3	29.5	46.0	-16.5	191	3.40
860.7878	4.58	23.08	8.2	35.9	46.0	-10.1	83	3.50

NOTE :

1. Measurement uncertainty is +/-3.7dB.
2. "**": Measurement does not apply for this frequency.
3. Emission Level = Reading Value + Ant. Factor + Cable Loss.
4. The field strength of other emission frequencies were very low against the limit.



Spectrum Research & Testing Lab., Inc.
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page:43 of 55
Date : Apr. 14, 2009

Temperature:	32 °C	Humidity:	68 %RH
Frequency Range:	1 – 25 GHz	Measured Distance:	3m
Receiver Detector:	PK. or AV.	Tested Mode:	TX-2402MHz
Tested By:	Kunter Jin	Tested Date:	Apr. 11, 2009

Antenna Polarization : Horizontal

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dBμV)		Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2402.00	-32.16	28.00	89.6	86.2	85.4	82.0	114.0	94.0	(F)	(F)	183	1.71
4804.50	-30.47	33.64	52.6	30.9	55.8	34.1	74.0	54.0	-18.2	-19.9	283	1.20
7206.00	-28.90	36.26	49.6	26.8	57.0	34.2	74.0	54.0	-17.0	-19.8	90	1.39
9608.50	-28.55	37.84	40.1	*	49.4	*	74.0	54.0	-24.6	*	*	*
1610.00	-32.89	25.72	31.2	*	24.0	*	74.0	54.0	-50.0	*	351	1.20
1663.00	-32.78	25.92	37.6	*	30.7	*	74.0	54.0	-43.3	*	110	1.15

Antenna Polarization : Vertical

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dBμV)		Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2402.00	-32.16	28.00	89.5	88.6	85.3	84.4	114.0	94.0	(F)	(F)	42	1.01
4804.00	-30.47	33.64	52.3	31.9	55.5	35.1	74.0	54.0	-18.5	-18.9	102	1.36
7206.50	-28.90	36.26	48.9	29.2	56.3	36.5	74.0	54.0	-17.7	-17.5	343	1.57
9608.00	-28.55	37.84	38.8	*	48.1	*	74.0	54.0	-25.9	*	110	1.15
1205.50	-33.86	24.65	31.1	*	21.9	*	74.0	54.0	-52.1	*	211	1.27
1610.50	-32.89	25.72	30.6	*	23.4	*	74.0	54.0	-50.6	*	158	1.00

NOTE :

1. Measurement uncertainty is +/-3.7dB.
2. "*": The Peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Emission Level = Reading Value + Ant. Factor + Correct Factor (incl.:Cable Loss and Pre-Amplifier Gain)
4. The field strength of other emission frequencies were very low against the limit.
5. (F):The field strength of fundamental frequency.



TEST REPORT

Temperature:	32 °C	Humidity:	68 %RH
Frequency Range:	1 – 25 GHz	Measured Distance:	3m
Receiver Detector:	PK. or AV.	Tested Mode:	TX-2441MHz
Tested By:	Kunter Jin	Tested Date:	Apr. 11, 2009

Antenna Polarization : Horizontal

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dBμV)		Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2441.00	-32.23	28.08	83.2	80.2	79.0	76.1	114.0	94.0	(F)	(F)	183	1.31
4882.50	-30.26	33.71	51.6	30.9	55.0	34.3	74.0	54.0	-19.0	-19.7	283	1.36
7323.00	-29.04	36.36	48.6	26.8	55.9	34.1	74.0	54.0	-18.1	-19.9	90	1.49
9764.50	-28.50	37.91	30.3	*	39.7	*	74.0	54.0	-34.3	*	164	1.25
1610.00	-32.89	25.72	31.2	*	24.0	*	74.0	54.0	-50.0	*	72	1.57
1663.00	-32.78	25.92	37.6	*	30.7	*	74.0	54.0	-43.3	*	39	1.37

Antenna Polarization : Vertical

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dBμV)		Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2441.00	-32.23	28.08	83.1	80.6	79.0	76.5	114.0	94.0	(F)	(F)	42	1.54
4882.00	-30.26	33.71	52.1	32.1	55.5	35.5	74.0	54.0	-18.5	-18.5	102	1.66
7323.50	-29.04	36.36	46.9	29.2	54.2	36.5	74.0	54.0	-19.8	-17.5	343	1.37
9764.00	-28.50	37.91	38.4	*	47.8	*	74.0	54.0	-26.2	*	141	1.25
1213.50	-33.83	24.67	31.6	*	22.4	*	74.0	54.0	-51.6	*	309	1.21
1310.00	-33.59	24.88	31.1	*	22.4	*	74.0	54.0	-51.6	*	36	1.31

NOTE :

1. Measurement uncertainty is +/-3.7dB.
2. "**": The Peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Emission Level = Reading Value + Ant. Factor + Correct Factor (incl.:Cable Loss and Pre-Amplifier Gain)
4. The field strength of other emission frequencies were very low against the limit.
5. (F):The field strength of fundamental frequency.



TEST REPORT

Temperature:	32 °C	Humidity:	68 %RH
Frequency Range:	1 – 25 GHz	Measured Distance:	3m
Receiver Detector:	PK. or AV.	Tested Mode:	TX-2480MHz
Tested By:	Kunter Jin	Tested Date:	Apr. 11, 2009

Antenna Polarization : Horizontal

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dBμV)		Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2480.00	-32.19	28.16	98.3	80.3	94.3	76.3	114.0	94.0	(F)	(F)	103	1.31
4960.50	-30.26	33.77	50.6	30.1	54.1	33.6	74.0	54.0	-19.9	-20.4	83	1.26
7440.00	-28.95	36.45	47.6	26.8	55.1	34.3	74.0	54.0	-18.9	-19.7	92	1.42
9920.50	-28.65	37.97	30.6	*	39.9	*	74.0	54.0	-34.1	*	10	1.33
1213.50	-33.83	24.67	31.1	*	21.9	*	74.0	54.0	-52.1	*	201	1.55
1520.00	-31.78	25.38	33.3	*	26.9	*	74.0	54.0	-47.1	*	179	1.61

Antenna Polarization : Vertical

Frequency (MHz)	Correct Factor (dB)	Ant. Factor (dB/m)	Reading Data (dBμV)		Emission Level (dBμV/m)		Limit (dBμV/m)		Margin (dB)		AZ (°)	EL (m)
			PK.	AV.	PK.	AV.	PK.	AV.	PK.	AV.		
2480.00	-32.19	28.16	93.1	80.1	89.1	76.1	114.0	94.0	(F)	(F)	142	1.64
4960.00	-30.26	33.77	52.3	31.0	55.8	34.5	74.0	54.0	-18.2	-19.5	10	1.33
7440.50	-28.95	36.45	46.1	28.2	53.6	35.7	74.0	54.0	-20.4	-18.3	303	1.17
9920.00	-28.65	37.97	38.1	*	47.4	*	74.0	54.0	-26.6	*	103	1.31
1310.00	-33.59	24.88	30.8	*	22.1	*	74.0	54.0	-51.9	*	36	1.31
1610.50	-32.89	25.72	30.9	*	23.7	*	74.0	54.0	-50.3	*	169	1.71

NOTE :

1. Measurement uncertainty is +/-3.7dB.
2. "**": The Peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. Emission Level = Reading Value + Ant. Factor + Correct Factor (incl.:Cable Loss and Pre-Amplifier Gain)
4. The field strength of other emission frequencies were very low against the limit.
5. (F):The field strength of fundamental frequency.



TEST REPORT

5. CONDUCTED EMISSION TEST FOR POWER PORT

5.1 LIMIT

Frequency (MHz)	Class A (dB μ V)		Class B (dB μ V)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

NOTE :

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.2 TEST EQUIPMENT

The following test equipment was used for the test:

EQUIPMENT/ FACILITIES	SPECIFICATIONS	MANUFACTURER	MODEL#/ SERIAL#	DUE DATE OF CAL. & CAL. CENTER
EMI TEST RECEIVER	9 kHz TO 30 MHz	ROHDE & SCHWARZ	ESHS30 / 826003/008	SEP. 2009 ETC
LISN	50 μ H, 50 ohm	FCC	FCC-LISN-50-25-2 / 01017	OCT. 2009 ETC
LISN	50 μ H, 50 ohm	FCC	9252-50-R24-BNC / 951315	JUN. 2009 ETC
50 OHM TERMINATOR	50 ohm	HP	11593A / #2	OCT. 2009 ETC
COAXIAL CABLE	5M	TIMES	EQM-0159 / #5-5m	AUG. 2009 SRT
FILTER	2 LINE, 30A	FIL.COIL	FC-943 / 771	NCR
GROUND PLANE	2.3M (H) x 2.4M (W)	SRT	N/A	NCR
GROUND PLANE	2.4M (H) x 2.4M (W)	SRT	N/A	NCR


NOTE: The calibration interval of the above test equipment is one year and the calibrations are traceable to NML/ROC and NIST/USA.



5.3 TEST PROCEDURE

According to FCC Part15, Subpart C

5.4 TEST SETUP



NOTE:

1. The EUT was put on a wooden table with 0.8m heights above ground plane, and 0.4m away from reference ground plane (> 2mx2m).
2. For the actual test configuration, please refer to the photos of testing.
3. The serial no. of the LISN connected to EUT is 01017.
4. The serial no. of the LISN connected to support units is 01018.



TEST REPORT

5.5 TEST RESULT

Temperature:	23 °C	Humidity:	69 %RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	Link
Receiver Detector:	Q.P. and AV.	Modulation Type:	N/A
Tested By:	Kunter Jin	Tested Channel:	N/A
		Tested Date:	Apr. 11, 2009

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB μ V)		Emission Level (dB μ V)		Limit (dB μ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.156	0.30	47.96	21.17	48.26	21.47	65.66	55.66	-17.40	-34.19
0.552	0.24	21.89	20.34	22.13	20.58	56.00	46.00	-33.87	-25.42
3.378	0.19	25.30	21.60	25.49	21.79	56.00	46.00	-30.51	-24.21
3.705	0.19	21.80	13.25	21.99	13.44	56.00	46.00	-34.01	-32.56
5.000	0.22	22.36	10.29	22.58	10.51	56.00	46.00	-33.42	-35.49
22.524	0.39	10.76	1.52	11.15	1.91	60.00	50.00	-48.85	-48.09

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB μ V)		Emission Level (dB μ V)		Limit (dB μ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.153	0.30	49.46	21.12	49.76	21.42	65.82	55.82	-16.06	-34.40
0.509	0.24	24.48	18.40	24.72	18.64	56.00	46.00	-31.28	-27.36
2.725	0.17	24.58	19.79	24.75	19.96	56.00	46.00	-31.25	-26.04
2.982	0.18	24.24	18.63	24.42	18.81	56.00	46.00	-31.58	-27.19
6.360	0.22	15.44	9.09	15.66	9.31	60.00	50.00	-44.34	-40.69
26.265	0.30	10.68	0.41	10.98	0.71	60.00	50.00	-49.02	-49.29

NOTE :

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies was very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.



TEST REPORT

Temperature:	21 °C	Humidity:	49 %RH
Frequency Range:	0.15 – 30 MHz	Tested Mode:	Standby
Receiver Detector:	Q.P. and AV.	Modulation Type:	N/A
Tested By:	Kunter Jin	Tested Channel:	N/A
		Tested Date:	Apr. 11, 2009

Power Line Measured : Line

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB μ V)		Emission Level (dB μ V)		Limit (dB μ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.152	0.30	49.46	21.12	49.76	21.42	65.82	55.82	-16.06	-34.40
0.508	0.24	24.48	18.40	24.72	18.64	56.00	46.00	-31.28	-27.36
2.724	0.17	24.58	19.79	24.75	19.96	56.00	46.00	-31.25	-26.04
2.981	0.18	24.24	18.63	24.42	18.81	56.00	46.00	-31.58	-27.19
6.359	0.22	15.44	9.09	15.66	9.31	60.00	50.00	-44.34	-40.69
26.264	0.30	10.68	0.41	10.98	0.71	60.00	50.00	-49.02	-49.29

Power Line Measured : Neutral

Freq. (MHz)	Correct. Factor (dB)	Reading Value (dB μ V)		Emission Level (dB μ V)		Limit (dB μ V)		Margin (dB)	
		Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
0.157	0.30	47.96	21.17	48.26	21.47	65.66	55.66	-17.40	-34.19
0.553	0.24	21.89	20.34	22.13	20.58	56.00	46.00	-33.87	-25.42
3.379	0.19	25.30	21.60	25.49	21.79	56.00	46.00	-30.51	-24.21
3.706	0.19	21.80	13.25	21.99	13.44	56.00	46.00	-34.01	-32.56
5.001	0.22	22.36	10.29	22.58	10.51	56.00	46.00	-33.42	-35.49
22.525	0.39	10.76	1.52	11.15	1.91	60.00	50.00	-48.85	-48.09

NOTE :

1. Measurement uncertainty is +/-2dB
2. Emission level = Reading value + Correction factor
3. Correction Factor = Cable loss + Insertion loss of LISN
4. Margin value = Emission level - Limit
5. The emission of other frequencies was very low against the limit.
6. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.



**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page:50 of 55
Date : Apr. 14, 2009

6. Antenna application

6.1 Antenna requirement

The EUT's antenna is met the requirement of FCC part15C section15.203 and 15.204.


6.2 Result

The EUT's antenna used a PCB Printing Antenna on PCB. The antenna's gain is 1.2 dBi and meets the requirement.



6. PHOTOS OF TESTING


- Radiated test (Standby, Tx, below 1GHz)






TEST REPORT

- Radiated test (Tx, above 1GHz)





- Radiated test (Link)





**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page:54 of 55
Date : Apr. 14, 2009

- Conducted test





**Spectrum Research &
Testing Lab., Inc.**
No. 101-10, Ling 8,
Shan-Tong Li, Chung-Li
City, Taoyuan, Taiwan

TEST REPORT

Reference No.: A09040901
Report No.: FCC A09040901
FCCID: XJ8-BT-232B
Page:55 of 55
Date : Apr. 14, 2009

7. TERMS OF ABBREVIATION

AV.	Average detection
AZ(°)	Turn table azimuth
Correct.	Correction
EL(m)	Antenna height (meter)
EUT	Equipment Under Test
Horiz.	Horizontal direction
LISN	Line Impedance Stabilization Network
NSA	Normalized Site Attenuation
Q.P.	Quasi-peak detection
SRT Lab	Spectrum Research & Testing Laboratory, Inc.
Vert.	Vertical direction