

Jointing in the connecting way of right picture

1.Instruction of assembling the controller

will be further (fig.1)
install 6x AA' batteries in the remote controller in right ways, plug adapters, and the
install fine batteries into battery box, Fasten with screw.(fig.2) in the hole of transmitter press lightly and turn clockwise, until the led to the controller well. Extend the antenna, the control distance is

. Install the battery must recognize the battery and battery box is precise plus or minus polarity, can't installation reverse.

Do not mix new and 10d batteries together when in use.

Please don't mix different types of batteries when in use.

5. Power batteries charging instruction

X (2)

sure the electric voltage in your living conditions the adapter, the plug insert correctly battery is overheated when recharge time to long, which can cause the damage, in make the battery failure. Please stop me at none

Il limit, or disturb the flying control. ions, your helicopter may become lost and/or damaged.

Do not fly in electric storms, rain, steet, snow or other adverse weather conditions. Select a large, wide-open, grassy area for fling. Select a large, wide-open area for flying, and make sure that there is no obstructions animals or people nearby.

.Prepare for take off the area to make sure it is clear of people, trees, buildings, high voltage wire, and other n the flat ground, Turn on the stand still for about 3 seconds. at least 2m away from the back of 2 the tail). slow, quick switch

Fig.4

he throids exist, if the helicopter is till revolving in the sky, please according special prompt.

special prompt.

Sow, quick switch pull out inwart?SLOW! in order to go toward, retreat to Sow, toward, retreat toward seawly in keeping with naw recult), be a switch to pull out broard become sawly in keeping with and on other to go forward, retreat speed to become quickly (in keeping with and on other to go forward, retreat speed to become quickly (in keeping with and


Control range. The control range of the RIC helicopter is about 30 meters.

Warring: Do not thy in strong wind, wind rang over power your helicopter and cause it to fly Warring to cold strates, where the helicopter is not drawing, you will not be abile to control it. Phyling time Co. a full divelage, and it also what conditions, the RIC helicopter will fly for Export about 6 terminates.

don't move the rudder slick in flying, the helicopter is still revolving in the sky. u can adjust the rudder the rudder trim.

u can sojust the rudder the rudder trim.

the helicopter is turning to left , please rightward clockwise turn slowly until the topic is still. Ascend 1 1 Right stick (rudder stick) push up



	tion	12. Caution
Fully charge	Helicopter is no fully charged.	enough
Pushing up	Rotor speed is too slow.	Helicopter is
Do not fly in flying contro	It is a windy day.	
Ensure that controller ar	Transmitter s antenna is not screwed in place and/or is not fully extended.	NO control
install new t	Batteries are drained.	doesn't works
Check and by the right	Install the batteries but doesn't follow the right polarity.	The indicator of transmitter
	Cause	Problem
	Trubleshooting guide	11. Trub
rotor	amporature and the second	for a while.
- Contract	Proposition and Control	ompoint.

1 The control distance and shorter when the guality of electicity is no full.
2 The controlled large of the hallocytes is 50m places only if it has operational arraps. If the operational arraps between transmitter and reliciopies as boack 50m, the placing in the propositional arraps between transmitter and reliciopies are shortered and of the controlled and of the contro

consible for the using of the nelocopter. Makes sure that it will not do any uny or damage the property.

Uny of damage the property.

Gligat, assembled and fify the helicopter, you must operate it according to a restruction strictly.

The correct operating and using the product, sesponsible completely for the correct operating and using the product, dealer accept no lisability for damage and loss that due to incorrect using dealer.

orbid operating.

The product control of children and the product control orbid orbi