INTERTEK TESTING SERVICES

Analysis Report

The equipment under test (EUT) is a portable transmitter for a Mini R/C Car In Capsule operating at 49.86MHz. The EUT is powered by two 1.5V AA size batteries. For more detail information pls. refer to the user manual.

Antenna Type: Dedicated antenna
Antenna Gain: 0dBi

The nominal conducted output power specified: -28.0dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -30.15dBm (+/- 3dB)

Modulation Type: Pulse modulation

According to the KDB 447498:

The worst-case peak radiated emission for the EUT is 67.2dBµV/m at 3m in the frequency 49.86MHz
The EIRP = [(FS*D) ^2 / 30] mW= -28.03dBm
The ERP = EIRP – 2.15 = -30.18 dBm
which is within the production variation.

The maximun conducted output power specified is -25.0dBm =0.003mW
The source- based time-averaging conducted output power
= 0.003* Duty Cycle mW< 0.1mW   (Duty Cycle<100%)

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:
= 474 * [1 + log(100/f(MHz)]/2
= 308.6 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

Transmitter Duty Cycle Calculation
The duration of one cycle   = 18.3333 ms
Effective period of the cycle = 507.2µs x 10 + 1.5217ms x 4 = 11.1588 ms
DC = 11.1588 ms / 18.3333 ms = 0.6087 or 60.87 %

FCC ID: XJJCHCC211100049