



# FCC PART 15.247 TEST REPORT

For

# SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD.

NO.1 Shuoying Rd., Hebei Industry Area, Dalang, Longhua Town, Baoan, Shenzhen, China

FCC ID: XJN-PA0906X

Report Type: Original Report		Product Type:  Mobile Internet Devices
Test Engineer:	Ares Liu	Am. lin
Report Number:	R2DG1306	628021-00A
Report Date:	2013-08-0	7
	Ivan Cao	han Can
Reviewed By:	RF Leader	<u>:</u>
Test Laboratory:	No.69 Pulc Tangxia, D Tel: +86-76 Fax: +86-7	Compliance Laboratories Corp. (Dongguan) ongcun, Puxinhu Industrial Zone, Dongguan, Guangdong, China 69-86858888 769-86858891 corp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP\*, or any agency of the Federal Government.

\* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

# **TABLE OF CONTENTS**

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EUT EXERCISE SOFTWARE	
EQUIPMENT MODIFICATIONS	
EXTERNAL CABLE	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT	10
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT Setup.	
EMI TEST RECEIVER SETUP	12
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTYEUT SETUP	
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	10
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS.	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	29
APPLICABLE STANDARD	29
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
Test Data	29

FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS	37
TEST DATA	38
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST EQUIPMENT LIST AND DETAILS	51
TEST DATA	51
FCC §15.247(e) - POWER SPECTRAL DENSITY	56
APPLICABLE STANDARD	56
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	56
Test Data	

#### **GENERAL INFORMATION**

### **Product Description for Equipment under Test (EUT)**

The SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD.'s product, model number: PA0906 (FCC ID: XJN-PA0906X) (the "EUT") in this report was a Mobile Internet Devices, which was measured approximately: 24.0 cm (L) x 14.7 cm (W) x 1.0 cm (H), rated input voltage: DC 3.7 V from lithium battery or DC 5V from adapter.

Report No.: R2DG130628021-00A

Adapter information: TEKA Model: TEKA018-0502500UK

Input: AC 100-240V, 50/60Hz, 0.5A max

Output: DC 5V, 2.5A

#### **Objective**

This report is prepared on behalf of *SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD*. in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communications Commission rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

#### Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: XJN-PA0906X

#### **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FCC Part 15.247 Page 4 of 63

<sup>\*</sup> All measurement and test data in this report was gathered from production sample serial number: 130628021 (Assigned by BACL.Dongguan). The EUT was received on 2013-07-01.

#### **Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Report No.: R2DG130628021-00A

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at <a href="http://ts.nist.gov/standards/scopes/5">http://ts.nist.gov/standards/scopes/5</a> 000690.htm

FCC Part 15.247 Page 5 of 63

#### SYSTEM TEST CONFIGURATION

#### **Description of Test Configuration**

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4G band, 11 channels are provided to testing:

Report No.: R2DG130628021-00A

Channel	Frequency (MHz)	Channel	Frequency (MHz)	
1	2412	7	2442	
2	2417	8	2447	
3	2422	9	2452	
4	2427	10	2457	
5	2432	11	2462	
6	2437	/	/	

For 802.11b, 802.11g, and 802.11n20 modes were tested with Channel 1, 6 and 11. For 802.11n40 mode were tested with Channel 3, 6 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all date rates bandwidths, and modulations.

#### **EUT Exercise Software**

"Cmd.exe" was used in the test, which the commands were provided by the manufacturer.

#### **Equipment Modifications**

No modification was made to the EUT tested.

#### **Support Equipment List and Details**


Manufacturer Description		Model	Serial Number
DELL	DELL Monitor		CN-OPH5NY-74445-16T-290L
Earphone	Earphone SOMIC		N/A
Kinston Micro SD Card		4G	N/A

### **External Cable**

Cable Description	Length (m) From Port		То
Shielded Detachable HDMI Cable	1.5	LCD Monitor	EUT

FCC Part 15.247 Page 6 of 63

# **Block Diagram of Test Setup**



FCC Part 15.247 Page 7 of 63

# **SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
\$15.205, \$15.209, \$15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Report No.: R2DG130628021-00A

FCC Part 15.247 Page 8 of 63

# FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

## **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: R2DG130628021-00A

According to KDB 447498 D01 Mobile Portable RF Exposure V05 Appendix A, SAR can be exempted if the output power is less than the SAR exclusion threshold:

For f=2450MHz, the output power is less 10mW at distance of 5mm.

#### **Measurement Result**

Peak conducted output power= 9.61 dBm Antenna gain =1 dBi SAR exclusion threshold 10 mW (10dBm) > 9.61 dBm

So the SAR evaluation is not necessary.

FCC Part 15.247 Page 9 of 63

# FCC §15.203 - ANTENNA REQUIREMENT

#### **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: R2DG130628021-00A

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

#### **Antenna Connector Construction**

The EUT has an internal antenna, which was permanently attached to the EUT, and the maximum gain is 1dBi, please refer to the internal photos.

**Result:** Compliance.

FCC Part 15.247 Page 10 of 63

#### **Applicable Standard**

FCC§15.207

#### **Measurement Uncertainty**

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: R2DG130628021-00A

If  $U_{\rm lab}$  is less than or equal to  $U_{\rm cispr}$  of Table 1, then:


- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If  $U_{\text{lab}}$  is greater than  $U_{\text{cispr}}$  of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} U_{cispr})$ , exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by  $(U_{\text{lab}} U_{\text{cispr}})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of 
$$U_{\text{cispr}}$$

Measurement	$U_{ m cispr}$	
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB	

#### **EUT Setup**



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 11 of 63

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

### **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

#### **Test Procedure**

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

#### **Corrected Amplitude & Margin Calculation**

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$
$$C_f = A_C + VDF$$

Herein.

V<sub>C</sub>(cord. Reading): corrected voltage amplitude

V<sub>R</sub>: reading voltage amplitude A<sub>c</sub>: attenuation caused by cable loss VDF: voltage division factor of AMN

C<sub>f</sub>: Correction Factor

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit - Corrected Amplitude

FCC Part 15.247 Page 12 of 63

#### **Test Equipment List and Details**

Manufacturer	Manufacturer Description		Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECIEVER	ESCS 30	830245/006	2013-1-10	2014-1-9
R&S	L.I.S.N	ESH3-Z5	843331/015	2012-9-17	2013-9-16
R&S	L.I.S.N	ESH3-Z5	100113	2012-11-29	2013-11-28
BACL	Test Software	BACL-EMC	V1.0-2010	N/A	N/A

Report No.: R2DG130628021-00A

#### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

#### 10.16 dB at 0.170 MHz in the Line conducted mode

#### **Test Data**

#### **Environmental Conditions**

Temperature:	27.6 °C
Relative Humidity:	57 %
ATM Pressure:	100.1 kPa


The testing was performed by Ares Liu on 2013-08-05.

FCC Part 15.247 Page 13 of 63

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

# Test Mode: Transmitting

# 120 V, 60 Hz, Line:



Frequency (MHz)	Cord. Reading (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/AV/QP)
0.170	54.80	0.45	64.96	10.16	QP
0.170	36.31	0.45	54.96	18.65	AV
0.230	43.44	0.40	62.45	19.01	QP
0.230	26.20	0.40	52.45	26.25	AV
0.440	40.86	0.32	57.06	16.20	QP
0.440	22.47	0.32	47.06	24.59	AV
1.200	33.74	0.33	56.00	22.26	QP
1.190	29.42	0.33	46.00	16.58	AV
2.910	32.31	0.39	56.00	23.69	QP
2.880	27.94	0.39	46.00	18.06	AV
4.800	37.66	0.46	56.00	18.34	QP
4.790	33.17	0.46	46.00	12.83	AV

FCC Part 15.247 Page 14 of 63

# 120 V, 60 Hz, Neutral:



Frequency (MHz)	Cord. Reading (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/AV/QP)
0.180	51.39	0.25	64.49	13.10	QP
0.180	33.19	0.25	54.49	21.30	AV
0.220	44.84	0.25	62.82	17.98	QP
0.220	29.58	0.25	52.82	23.24	AV
0.680	33.95	0.22	56.00	22.05	QP
0.680	28.49	0.22	46.00	17.51	AV
2.780	32.94	0.30	56.00	23.06	QP
2.780	28.27	0.30	46.00	17.73	AV
4.160	34.63	0.36	56.00	21.37	QP
4.140	28.83	0.36	46.00	17.17	AV
18.480	38.09	1.37	60.00	21.91	QP
18.610	34.15	1.38	50.00	15.85	AV

FCC Part 15.247 Page 15 of 63

#### **Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

#### **Measurement Uncertainty**

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: R2DG130628021-00A

If  $U_{\text{lab}}$  is less than or equal to  $U_{\text{cispr}}$  of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If  $U_{\text{lab}}$  is greater than  $U_{\text{cispr}}$  of Table 2, then:
- compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} U_{cispr})$ , exceeds the disturbance limit:
- non compliance is deemed to occur if any measured disturbance level, increased by  $(U_{\text{lab}} U_{\text{cispr}})$ , exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

Table 2 – Values of  $U_{\text{cisp}}$ 

Measurement						
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB					
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB					
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB					


#### **EUT Setup**

#### **Below 1GHz:**



FCC Part 15.247 Page 16 of 63

#### **Above 1GHz:**



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

#### **EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 CHz	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	Ave.

#### **Test Procedure**

For the radiated emissions test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 17 of 63

#### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: R2DG130628021-00A

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

# **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCI	100224	2013-5-6	2014-5-5
Sunol Sciences	Antenna	ЈВ3	A060611-1	2012-9-6	2015-9-5
HP	HP AMPLIFIER	8447E	2434A02181	N/A	N/A
R&S	Spectrum analyzer	FSEM 30	849016/001	2012-9-4	2013-9-3
ETS LINDGREN	horn antenna	3115	000 527 35	2012-9-6	2015-9-5
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	N/A	N/A
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

#### **Test Results Summary**

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247</u>, with the worst margin reading of:

**3.27 dB** at **34.85 MHz** in the Vertical polarization for 802.11b Mode

## **Test Data**

#### **Environmental Conditions**

Temperature:	26.7 °C
Relative Humidity:	61 %
ATM Pressure:	99.8 kPa

The testing was performed by Ares Liu on 2013-07-01.

FCC Part 15.247 Page 18 of 63

Mode: Transmitting 802.11b Mode

Company   Comp	802.11b Mode										
Reading (dBμV)	E	Re	eceiver	Rx Ai	ntenna	Cable	Amplifier	Corrected	FCC 1:	5.247	
CMBLY   CMB_WV   CM		Reading	Detector	Polar	Factor		_		Limit	Margin	
2412   69.09   PK	(MHZ)	8	(PK/QP/AV)	(H/V)	(dB)	(dB)	(dB)	(dBµV/m)		(dB)	
2412   69.09   PK											
2412   64.71   AV	2412	69.09	PK					98.69	N/A	N/A	
2412										N/A	
2412   68.79   AV										N/A	
2390	2412		AV	V	25.67		0.00		N/A	N/A	
4824	2390	28.15	PK	V	25.61	3.84	0.00	57.60	74.00	16.40	
A824   37.92   AV   V   30.64   4.73   27.26   46.03   54.00   7.9°	2390	14.31	AV	V	25.61	3.84	0.00	43.76	54.00	10.24	
T236	4824	41.96	PK	V	30.64	4.73	27.26	50.07	74.00	23.93	
T236	4824	37.92	AV	V	30.64	4.73	27.26		54.00	7.97	
9648   33.28   PK   V   36.06   8.70   26.06   51.98   74.00   22.0     9648   19.81   AV   V   36.06   8.70   26.06   38.51   54.00   15.4     3265   34.45   PK   V   28.05   5.07   27.43   26.67   54.00   27.3     34.85   38.9   QP   V   18.46   0.79   21.42   36.73   40.00   3.27	7236	31.14	PK	V	34.17	6.56	26.36	45.51	74.00	28.49	
9648	7236	18.57	AV	V	34.17	6.56	26.36	32.94	54.00	21.06	
3265   34.45   PK   V   28.05   5.07   27.43   40.14   74.00   33.8     3265   20.98   AV   V   28.05   5.07   27.43   26.67   54.00   27.3     34.85   38.9   QP   V   18.46   0.79   21.42   36.73   40.00   3.27	9648	33.28	PK	V	36.06	8.70	26.06	51.98	74.00	22.02	
3265   20.98   AV   V   28.05   5.07   27.43   26.67   54.00   27.3		19.81	AV		36.06	8.70	26.06	38.51	54.00	15.49	
34.85   38.9   QP	3265	34.45	PK		28.05	5.07			74.00	33.86	
Middle Channel: 2437 MHz	3265				28.05	5.07	27.43	26.67	54.00	27.33	
2437         69.25         PK         H         25.74         3.98         0.00         98.97         N/A         N/A           2437         64.6         AV         H         25.74         3.98         0.00         94.32         N/A         N/A           2437         73.3         PK         V         25.74         3.98         0.00         103.02         N/A         N/A           2437         68.85         AV         V         25.74         3.98         0.00         103.02         N/A         N/A           4874         42.02         PK         V         30.77         4.76         27.26         50.29         74.00         23.7           4874         38.05         AV         V         30.77         4.76         27.26         46.32         54.00         7.66           7311         31.19         PK         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         34.35         6.70         26.51         33.23         54.00         20.7           9748         33.26         PK         V         36.30         8.60 <t< td=""><td>34.85</td><td>38.9</td><td>QP</td><td></td><td></td><td></td><td>·</td><td>36.73</td><td>40.00</td><td>3.27*</td></t<>	34.85	38.9	QP				·	36.73	40.00	3.27*	
2437         64.6         AV         H         25.74         3.98         0.00         94.32         N/A         N/A           2437         73.3         PK         V         25.74         3.98         0.00         103.02         N/A         N/A           2437         68.85         AV         V         25.74         3.98         0.00         98.57         N/A         N/A           4874         42.02         PK         V         30.77         4.76         27.26         50.29         74.00         23.7           4874         38.05         AV         V         30.77         4.76         27.26         46.32         54.00         7.68           7311         31.19         PK         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         36.30         8.60         25.68         52.48         74.00         21.5           9748         19.78         AV         V         36.30         8.60							MHz				
2437         73.3         PK         V         25.74         3.98         0.00         103.02         N/A         N/A           2437         68.85         AV         V         25.74         3.98         0.00         98.57         N/A         N/A           4874         42.02         PK         V         30.77         4.76         27.26         50.29         74.00         23.7           4874         38.05         AV         V         30.77         4.76         27.26         46.32         54.00         7.68           7311         31.19         PK         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         34.35         6.70         26.51         33.23         54.00         20.7           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         15.0           1623         34.4         PK         V         23.85         3.18		69.25					0.00			N/A	
2437         68.85         AV         V         25.74         3.98         0.00         98.57         N/A         N/A           4874         42.02         PK         V         30.77         4.76         27.26         50.29         74.00         23.7           4874         38.05         AV         V         30.77         4.76         27.26         46.32         54.00         7.66           7311         31.19         PK         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         34.35         6.70         26.51         33.23         54.00         20.7           9748         33.26         PK         V         36.30         8.60         25.68         52.48         74.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         15.0           1623         34.4         PK         V         23.85         3.18         26.91         34.52         74.00         39.4           1623         20.9         AV         V         23.85         3.18	2437	64.6	AV		25.74			94.32		N/A	
4874         42.02         PK         V         30.77         4.76         27.26         50.29         74.00         23.7           4874         38.05         AV         V         30.77         4.76         27.26         46.32         54.00         7.66           7311         31.19         PK         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         34.35         6.70         26.51         33.23         54.00         20.7           9748         33.26         PK         V         36.30         8.60         25.68         52.48         74.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         52.48         74.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         15.0           1623         34.4         PK         V         23.85         3.18         26.91         34.52         74.00         39.4           1623         34.46         PK         V         28.05         5.07<	2437									N/A	
4874         38.05         AV         V         30.77         4.76         27.26         46.32         54.00         7.66           7311         31.19         PK         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         34.35         6.70         26.51         33.23         54.00         20.7           9748         33.26         PK         V         36.30         8.60         25.68         52.48         74.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         21.5           9748         19.78         AV         V         23.85         3.18         26.91         34.52         74.00         39.4           1623         34.4         PK         V         28.05         5.07<										N/A	
7311         31.19         PK         V         34.35         6.70         26.51         45.73         74.00         28.2           7311         18.69         AV         V         34.35         6.70         26.51         33.23         54.00         20.7           9748         33.26         PK         V         36.30         8.60         25.68         52.48         74.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         21.5           9748         19.78         AV         V         23.85         3.18         26.91         34.52         74.00         39.4           1623         34.4         PK         V         23.85         3.18         26.91         21.02         54.00         32.9           3265         34.46         PK         V         28.05         5.07<										23.71	
7311         18.69         AV         V         34.35         6.70         26.51         33.23         54.00         20.7           9748         33.26         PK         V         36.30         8.60         25.68         52.48         74.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         15.0           1623         34.4         PK         V         23.85         3.18         26.91         34.52         74.00         39.4           1623         20.9         AV         V         23.85         3.18         26.91         21.02         54.00         32.9           3265         34.46         PK         V         28.05         5.07         27.43         40.15         74.00         33.8           3265         21.03         AV         V         28.05         5.07         27.43         40.15         74.00         33.8           34.82         38.7         QP         V         18.48         0.79         21.42         36.55         40.00         3.45           High Channel: 2462 MHz           2462         64.54         <										7.68	
9748         33.26         PK         V         36.30         8.60         25.68         52.48         74.00         21.5           9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         15.0           1623         34.4         PK         V         23.85         3.18         26.91         34.52         74.00         39.4           1623         20.9         AV         V         23.85         3.18         26.91         21.02         54.00         32.9           3265         34.46         PK         V         28.05         5.07         27.43         40.15         74.00         33.8           3265         21.03         AV         V         28.05         5.07         27.43         26.72         54.00         27.2           34.82         38.7         QP         V         18.48         0.79         21.42         36.55         40.00         3.45           High Channel: 2462 MHz           2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         73.25         P										28.27	
9748         19.78         AV         V         36.30         8.60         25.68         39.00         54.00         15.0           1623         34.4         PK         V         23.85         3.18         26.91         34.52         74.00         39.4           1623         20.9         AV         V         23.85         3.18         26.91         21.02         54.00         32.9           3265         34.46         PK         V         28.05         5.07         27.43         40.15         74.00         33.8           3265         21.03         AV         V         28.05         5.07         27.43         26.72         54.00         27.2           34.82         38.7         QP         V         18.48         0.79         21.42         36.55         40.00         3.45           High Channel: 2462 MHz           2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>20.77</td>										20.77	
1623         34.4         PK         V         23.85         3.18         26.91         34.52         74.00         39.4           1623         20.9         AV         V         23.85         3.18         26.91         21.02         54.00         32.9           3265         34.46         PK         V         28.05         5.07         27.43         40.15         74.00         33.8           3265         21.03         AV         V         28.05         5.07         27.43         26.72         54.00         27.2           34.82         38.7         QP         V         18.48         0.79         21.42         36.55         40.00         3.45           High Channel: 2462 MHz           2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK										21.52	
1623         20.9         AV         V         23.85         3.18         26.91         21.02         54.00         32.9           3265         34.46         PK         V         28.05         5.07         27.43         40.15         74.00         33.8           3265         21.03         AV         V         28.05         5.07         27.43         26.72         54.00         27.2           34.82         38.7         QP         V         18.48         0.79         21.42         36.55         40.00         3.45           High Channel: 2462 MHz           2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK         V         25.80         3.93         0.00         102.98         N/A         N/A           2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK										15.00	
3265         34.46         PK         V         28.05         5.07         27.43         40.15         74.00         33.8           3265         21.03         AV         V         28.05         5.07         27.43         26.72         54.00         27.2           34.82         38.7         QP         V         18.48         0.79         21.42         36.55         40.00         3.45           High Channel: 2462 MHz           2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK         V         25.80         3.93         0.00         102.98         N/A         N/A           2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK         V         25.86         3.80         0.00         58.00         74.00         16.0				·						39.48	
3265         21.03         AV         V         28.05         5.07         27.43         26.72         54.00         27.2           34.82         38.7         QP         V         18.48         0.79         21.42         36.55         40.00         3.45           High Channel: 2462 MHz           2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK         V         25.80         3.93         0.00         102.98         N/A         N/A           2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK         V         25.86         3.80         0.00         58.00         74.00         16.0										32.98	
34.82         38.7         QP         V         18.48         0.79         21.42         36.55         40.00         3.45           High Channel: 2462 MHz           2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK         V         25.80         3.93         0.00         102.98         N/A         N/A           2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK         V         25.86         3.80         0.00         58.00         74.00         16.0										33.85	
High Channel: 2462 MHz           2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK         V         25.80         3.93         0.00         102.98         N/A         N/A           2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK         V         25.86         3.80         0.00         58.00         74.00         16.0										27.28	
2462         69.08         PK         H         25.80         3.93         0.00         98.81         N/A         N/A           2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK         V         25.80         3.93         0.00         102.98         N/A         N/A           2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK         V         25.86         3.80         0.00         58.00         74.00         16.0	34.82	38.7	QP					36.55	40.00	3.45*	
2462         64.54         AV         H         25.80         3.93         0.00         94.27         N/A         N/A           2462         73.25         PK         V         25.80         3.93         0.00         102.98         N/A         N/A           2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK         V         25.86         3.80         0.00         58.00         74.00         16.0	2462	60.00	D. 7.	_				00.01	37/4	27/4	
2462         73.25         PK         V         25.80         3.93         0.00         102.98         N/A         N/A           2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK         V         25.86         3.80         0.00         58.00         74.00         16.0							0.00				
2462         68.71         AV         V         25.80         3.93         0.00         98.44         N/A         N/A           2483.5         28.34         PK         V         25.86         3.80         0.00         58.00         74.00         16.0											
2483.5 28.34 PK V 25.86 3.80 0.00 58.00 74.00 16.0											
				V							
										9.51 23.63	
										7.56	
										27.99	
										20.63	
										20.03	
										14.49	
										33.69	
										27.18	
										3.40*	

<sup>\*</sup>Within measurement uncertainty!

FCC Part 15.247 Page 19 of 63

802.11g Mode

Е.	R	eceiver	Rx A	Antenna	Cable	Amplifier	Corrected	FCC 15	5.247
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Low Channel: 2412 MHz									
2412	68.38	PK	Н	25.67	3.93	0.00	97.98	N/A	N/A
2412	57.97	AV	Н	25.67	3.93	0.00	87.57	N/A	N/A
2412	72.74	PK	V	25.67	3.93	0.00	102.34	N/A	N/A
2412	62.24	AV	V	25.67	3.93	0.00	91.84	N/A	N/A
2390	28.23	PK	V	25.61	3.84	0.00	57.68	74.00	16.32
2390	14.29	AV	V	25.61	3.84	0.00	43.74	54.00	10.26
4824	40.96	PK	V	30.64	4.73	27.26	49.07	74.00	24.93
4824	28.13	AV	V	30.64	4.73	27.26	36.24	54.00	17.76
7236	31.42	PK	V	34.17	6.56	26.36	45.79	74.00	28.21
7236	18.35	AV	V	34.17	6.56	26.36	32.72	54.00	21.28
9648	32.87	PK	V	36.06	8.70	26.06	51.57	74.00	22.43
9648	19.78	AV	V	36.06	8.70	26.06	38.48	54.00	15.52
3265	34.05	PK	V	28.05	5.07	27.43	39.74	74.00	34.26
3265	20.39	AV	V	28.05	5.07	27.43	26.08	54.00	27.92
34.85	38.8	QP	V	18.46	0.79	21.42	36.63	40.00	3.37*
			Mid	ldle Channe					
2437	68.35	PK	Н	25.74	3.98	0.00	98.07	N/A	N/A
2437	57.99	AV	Н	25.74	3.98	0.00	87.71	N/A	N/A
2437	72.79	PK	V	25.74	3.98	0.00	102.51	N/A	N/A
2437	62.41	AV	V	25.74	3.98	0.00	92.13	N/A	N/A
4874	41.11	PK	V	30.77	4.76	27.26	49.38	74.00	24.62
4874	28.22	AV	V	30.77	4.76	27.26	36.49	54.00	17.51
7311	31.45	PK	V	34.35	6.70	26.51	45.99	74.00	28.01
7311	18.45	AV	V	34.35	6.70	26.51	32.99	54.00	21.01
9748	32.72	PK	V	36.30	8.60	25.68	51.94	74.00	22.06
9748	19.78	AV	V	36.30	8.60	25.68	39.00	54.00	15.00
1623	34.02	PK	V	23.85	3.18	26.91	34.14	74.00	39.86
1623	20.45	AV	V	23.85	3.18	26.91	20.57	54.00	33.43
3265	33.16	PK	V	28.05	5.07	27.43	38.85	74.00	35.15
3265	20.34	AV	V	28.05	5.07	27.43	26.03	54.00	27.97
34.84	38.9	QP	V	18.46	0.79	21.42	36.73	40.00	3.27*
				gh Channel:					
2462	68.39	PK	Н	25.80	3.93	0.00	98.12	N/A	N/A
2462	57.11	AV	Н	25.80	3.93	0.00	86.84	N/A	N/A
2462	72.85	PK	V	25.80	3.93	0.00	102.58	N/A	N/A
2462	62.43	AV	V	25.80	3.93	0.00	92.16	N/A	N/A
2483.5	27.57	PK	V	25.86	3.80	0.00	57.23	74.00	16.77
2483.5	14.23	AV	V	25.86	3.80	0.00	43.89	54.00	10.11
4924	41.1	PK	V	30.90	4.70	27.27	49.43	74.00	24.57
4924	28.29	AV	V	30.90	4.70	27.27	36.62	54.00	17.38
7386	31.55	PK	V	34.53	6.84	26.66	46.26	74.00	27.74
7386	18.48	AV	V	34.53	6.84	26.66	33.19	54.00	20.81
9848	32.97	PK	V	36.54	8.49	25.49	52.51	74.00	21.49
9848	19.89	AV	V	36.54	8.49	25.49	39.43	54.00	14.57
3265	34.13	PK	V	28.05	5.07	27.43	39.82	74.00	34.18
3265	20.62	AV	V	28.05	5.07	27.43	26.31	54.00	27.69
34.86	38.7	QP	V	18.45	0.79	21.42	36.52	40.00	3.48*

Report No.: R2DG130628021-00A

FCC Part 15.247 Page 20 of 63

<sup>\*</sup>Within measurement uncertainty!

802.11 n20 Mode

Engress	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)
			Lo	w Channe	1: 2412 N	ſНz			
2412	68.11	PK	Н	25.67	3.93	0.00	97.71	N/A	N/A
2412	57.96	AV	Н	25.67	3.93	0.00	87.56	N/A	N/A
2412	72.63	PK	V	25.67	3.93	0.00	102.23	N/A	N/A
2412	62.29	AV	V	25.67	3.93	0.00	91.89	N/A	N/A
2390	28.58	PK	V	25.61	3.84	0.00	58.03	74.00	15.97
2390	14.58	AV	V	25.61	3.84	0.00	44.03	54.00	9.97
4824	41.11	PK	V	30.64	4.73	27.26	49.22	74.00	24.78
4824	28.14	AV	V	30.64	4.73	27.26	36.25	54.00	17.75
7236	31.42	PK	V	34.17	6.56	26.36	45.79	74.00	28.21
7236	18.41	AV	V	34.17	6.56	26.36	32.78	54.00	21.22
9648	32.67	PK	V	36.06	8.70	26.06	51.37	74.00	22.63
9648	19.33	AV	V	36.06	8.70	26.06	38.03	54.00	15.97
3265	33.77	PK	V	28.05	5.07	27.43	39.46	74.00	34.54
3265	20.47	AV	V	28.05	5.07	27.43	26.16	54.00	27.84
34.85	38.9	QP	V	18.46	0.79	21.42	36.73	40.00	3.27*
			Mid	dle Chann	el: 2437	MHz			
2437	68.25	PK	Н	25.74	3.98	0.00	97.97	N/A	N/A
2437	57.9	AV	Н	25.74	3.98	0.00	87.62	N/A	N/A
2437	72.54	PK	V	25.74	3.98	0.00	102.26	N/A	N/A
2437	62.23	AV	V	25.74	3.98	0.00	91.95	N/A	N/A
4874	41.25	PK	V	30.77	4.76	27.26	49.52	74.00	24.48
4874	28.31	AV	V	30.77	4.76	27.26	36.58	54.00	17.42
7311	31.45	PK	V	34.35	6.70	26.51	45.99	74.00	28.01
7311	18.52	AV	V	34.35	6.70	26.51	33.06	54.00	20.94
9748	32.59	PK	V	36.30	8.60	25.68	51.81	74.00	22.19
9748	19.38	AV	V	36.30	8.60	25.68	38.60	54.00	15.40
1623	33.81	PK	V	23.85	3.18	26.91	33.93	74.00	40.07
1623	20.38	AV	V	23.85	3.18	26.91	20.50	54.00	33.50
3265	33.67	PK	V	28.05	5.07	27.43	39.36	74.00	34.64
3265	20.42	AV	V	28.05	5.07	27.43	26.11	54.00	27.89
34.85	38.7	QP	V	18.46	0.79	21.42	36.53	40.00	3.47*
	1	Ī		gh Channe			T -	T	
2462	68.36	PK	H	25.80	3.93	0.00	98.09	N/A	N/A
2462	58.11	AV	Н	25.80	3.93	0.00	87.84	N/A	N/A
2462	72.69	PK	V	25.80	3.93	0.00	102.42	N/A	N/A
2462	62.37	AV	V	25.80	3.93	0.00	92.10	N/A	N/A
2483.5	27.35	PK	V	25.86	3.80	0.00	57.01	74.00	16.99
2483.5	14.15	AV	V	25.86	3.80	0.00	43.81	54.00	10.19
4924	41.2	PK	V	30.90	4.70	27.27	49.53	74.00	24.47
4924	28.16	AV	V	30.90	4.70	27.27	36.49	54.00	17.51
7386	31.51	PK	V	34.53	6.84	26.66	46.22	74.00	27.78
7386	18.56	AV	V	34.53	6.84	26.66	33.27	54.00	20.73
9848	32.77	PK	V	36.54	8.49	25.49	52.31 39.16	74.00	21.69
9848 3265	19.62 33.95	AV PK	V	36.54 28.05	8.49 5.07	25.49 27.43	39.16	54.00 74.00	14.84 34.36
3265	20.6	AV	V	28.05	5.07	27.43	26.29	54.00	27.71
	38.8	QP	V	18.45	0.79	21.42	36.62	40.00	3.38*
34.86	38.8	ΥY	V	16.43	0.79	21.42	30.02	40.00	3.38"

<sup>\*</sup>Within measurement uncertainty!

FCC Part 15.247 Page 21 of 63

802.11 n40 Mode

Enggrana	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1:	5.247	
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)	
	Low Channel: 2422 MHz									
2422	68.35	PK	Н	25.70	3.95	0.00	98.00	N/A	N/A	
2422	58.07	AV	Н	25.70	3.95	0.00	87.72	N/A	N/A	
2422	72.63	PK	V	25.70	3.95	0.00	102.28	N/A	N/A	
2422	62.26	AV	V	25.70	3.95	0.00	91.91	N/A	N/A	
2390	28.42	PK	V	25.61	3.84	0.00	57.87	74.00	16.13	
2390	14.67	AV	V	25.61	3.84	0.00	44.12	54.00	9.88	
4844	41.23	PK	V	30.69	4.78	27.26	49.44	74.00	24.56	
4844	28.17	AV	V	30.69	4.78	27.26	36.38	54.00	17.62	
7266	31.43	PK	V	34.24	6.62	26.42	45.87	74.00	28.13	
7266	18.51	AV	V	34.24	6.62	26.42	32.95	54.00	21.05	
9688	32.84	PK	V	36.15	8.66	25.91	51.74	74.00	22.26	
9688	19.41	AV	V	36.15	8.66	25.91	38.31	54.00	15.69	
3265	34.25	PK	V	28.05	5.07	27.43	39.94	74.00	34.06	
3265	20.46	AV	V	28.05	5.07	27.43	26.15	54.00	27.85	
34.87	38.8	QP	V	18.44	0.79	21.42	36.61	40.00	3.39*	
2	20.0	χ-	Mid	dle Chann			20.01	.0.00	3.57	
2437	68.15	PK	Н	25.74	3.98	0.00	97.87	N/A	N/A	
2437	57.94	AV	Н	25.74	3.98	0.00	87.66	N/A	N/A	
2437	72.5	PK	V	25.74	3.98	0.00	102.22	N/A	N/A	
2437	62.21	AV	V	25.74	3.98	0.00	91.93	N/A	N/A	
4874	41.3	PK	V	30.77	4.76	27.26	49.57	74.00	24.43	
4874	28.19	AV	V	30.77	4.76	27.26	36.46	54.00	17.54	
7311	31.46	PK	V	34.35	6.70	26.51	46.00	74.00	28.00	
7311	18.59	AV	V	34.35	6.70	26.51	33.13	54.00	20.87	
9748	32.96	PK	V	36.30	8.60	25.68	52.18	74.00	21.82	
9748	19.64	AV	V	36.30	8.60	25.68	38.86	54.00	15.14	
1623	33.65	PK	V	23.85	3.18	26.91	33.77	74.00	40.23	
1623	20.42	AV	V	23.85	3.18	26.91	20.54	54.00	33.46	
3265	34.26	PK	V	28.05	5.07	27.43	39.95	74.00	34.05	
3265	21.43	AV	V	28.05	5.07	27.43	27.12	54.00	26.88	
34.88	38.9	QP	V	18.43	0.79	21.42	36.70	40.00	3.30*	
	•	-	Hig	gh Channe	l: 2452 N	ИHz			•	
2452	68.27	PK	Н	25.78	4.00	0.00	98.04	N/A	N/A	
2452	58.08	AV	Н	25.78	4.00	0.00	87.85	N/A	N/A	
2452	72.52	PK	V	25.78	4.00	0.00	102.29	N/A	N/A	
2452	62.29	AV	V	25.78	4.00	0.00	92.06	N/A	N/A	
2483.5	27.66	PK	V	25.86	3.80	0.00	57.32	74.00	16.68	
2483.5	14.47	AV	V	25.86	3.80	0.00	44.13	54.00	9.87	
4904	41.14	PK	V	30.85	4.72	27.27	49.44	74.00	24.56	
4904	28.32	AV	V	30.85	4.72	27.27	36.62	54.00	17.38	
7356	31.48	PK	V	34.45	6.79	26.60	46.12	74.00	27.88	
7356	18.53	AV	V	34.45	6.79	26.60	33.17	54.00	20.83	
9808	33.51	PK	V	36.44	8.53	25.48	53.00	74.00	21.00	
9808	20.45	AV	V	36.44	8.53	25.48	39.94	54.00	14.06	
3265	33.87	PK	V	28.05	5.07	27.43	39.56	74.00	34.44	
3265	20.42	AV	V	28.05	5.07	27.43	26.11	54.00	27.89	
34.84	38.7	QP	V	18.46	0.79	21.42	36.53	40.00	3.47*	


<sup>\*</sup>Within measurement uncertainty!

FCC Part 15.247 Page 22 of 63


#### **Conducted Spurious Emissions at Antenna Port**

Report No.: R2DG130628021-00A

#### 802.11b Low Channel




#### 802.11b Middle Channel




FCC Part 15.247 Page 23 of 63

# 802.11b High Channel

Report No.: R2DG130628021-00A




# 802.11g Low Channel




FCC Part 15.247 Page 24 of 63

## **802.11g Middle Channel**

Report No.: R2DG130628021-00A




#### 802.11g High Channel




FCC Part 15.247 Page 25 of 63

#### 802.11n20 Low Channel

Report No.: R2DG130628021-00A







FCC Part 15.247 Page 26 of 63

#### 802.11n20 High Channel

Report No.: R2DG130628021-00A




#### **802.11n40** Low Channel




FCC Part 15.247 Page 27 of 63

#### 802.11n40 Middle Channel

Report No.: R2DG130628021-00A



#### 802.11n40 High Channel



FCC Part 15.247 Page 28 of 63

# FCC $\S15.247(a)$ (2) – 6 dB EMISSION BANDWIDTH

#### **Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: R2DG130628021-00A

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.



#### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

Temperature:	27.9 °C
Relative Humidity:	69 %
ATM Pressure:	99.8 kPa

The testing was performed by Ares Liu on 2013-07-01.

Test Result: Pass.

Please refer to the following tables and plots.

FCC Part 15.247 Page 29 of 63

Channel	Frequency	6 dB Bandwidth	Limit						
Channel	(MHz)	(MHz)	(kHz)						
	802.11b mode								
Low	2412	10.15	>500						
Middle	2437	10.11	>500						
High	2462	10.15	>500						
	8	02.11g mode							
Low	2412	16.62	>500						
Middle	2437	16.58	>500						
High	2462	16.62	>500						
	80	2.11n20 mode							
Low	2412	17.86	>500						
Middle	2437	17.90	>500						
High	2462	17.90	>500						
	80	2.11n40 mode							
Low	2422	37.72	>500						
Middle	2437	37.80	>500						
High	2452	37.72	>500						


FCC Part 15.247 Page 30 of 63

Report No.: R2DG130628021-00A



1.JUL.2013 11:18:01 Date:

#### **802.11b Middle Channel**




1.JUL.2013 11:21:16 Date:

FCC Part 15.247 Page 31 of 63


# Report No.: R2DG130628021-00A

# 802.11b High Channel



Date: 1.JUL.2013 11:24:01

#### 802.11g Low Channel




Date: 1.JUL.2013 11:34:54

FCC Part 15.247 Page 32 of 63


# 802.11g Middle Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 11:37:31

#### 802.11g High Channel




Date: 1.JUL.2013 11:40:28

FCC Part 15.247 Page 33 of 63


# 802.11n20 Low Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:30:25

#### 802.11n20 Middle Channel




Date: 1.JUL.2013 13:32:03

FCC Part 15.247 Page 34 of 63


#### 002 11 -20 H\*-1 -Cl-----1

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:34:59

#### **802.11n40** Low Channel




Date: 1.JUL.2013 13:40:12

FCC Part 15.247 Page 35 of 63


# 802.11n40 Middle Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:41:58

#### 802.11n40 High Channel



Date: 1.JUL.2013 13:44:30

FCC Part 15.247 Page 36 of 63

# FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER


#### **Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: R2DG130628021-00A

#### **Test Procedure**

- 1. Place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
- 3. Add a correction factor to the display.



- 4. According to KDB 558074 D01 DTS Meas Guidance v02, Section 8.2.1 Option 1:
  - 4.1 Set the analyzer span to a minimum of 1.5 times the EBW.
  - 4.2 Set the RBW = 1 MHz.
  - 4.3 Set the VBW = 3 MHz.
  - 4.4 Ensure that the number of measurement points in the sweep  $\geq 2 \text{ x span/RBW}$
  - 4.5 Sweep time = auto couple.
  - 4.6 Detector = power averaging (RMS) or sample detector when RMS not available.
  - 4.7 Employ trace averaging in power averaging (RMS) mode over a minimum of 100 traces.
  - 4.8 Use the spectrum analyzer's band power measurement function with band limits set equal to the EBW band edges.

Note: EBW means 26dB bandwidth.

### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.247 Page 37 of 63

#### . Test Data

# **Environmental Conditions**

Temperature:	27.9 °C	
Relative Humidity:	69 %	
ATM Pressure:	99.8 kPa	

The testing was performed by Ares Liu on 2013-07-01.

Test Mode: Transmitting


Channel	Frequency	Conducted Output Power	Limit	Result
	(MHz)	(dBm)	(dBm)	
	80	02.11b mode		
Low	2412 MHz	9.27	30	PASS
Middle	2437 MHz	9.38	30	PASS
High	2462 MHz	9.12	30	PASS
	80	02.11g mode		
Low	2412 MHz	9.60	30	PASS
Middle	2437 MHz	9.49	30	PASS
High	2462 MHz	9.26	30	PASS
	802.11n20 mode			
Low	2412 MHz	9.45	30	PASS
Middle	2437 MHz	9.50	30	PASS
High	2462 MHz	9.61	30	PASS
802.11n40 mode				
Low	2422 MHz	9.17	30	PASS
Middle	2437 MHz	9.30	30	PASS
High	2452 MHz	9.58	30	PASS

Report No.: R2DG130628021-00A

Please refer to the following plots


FCC Part 15.247 Page 38 of 63

### 802.11b 26dB, Low Channel



Date: 1.JUL.2013 11:18:12

# 802.11b RF Output Power, Low Channel




Date: 1.JUL.2013 11:18:26

FCC Part 15.247 Page 39 of 63


# 802.11b 26dB, Middle Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 11:21:28


### 802.11b RF Output Power, Middle Channel



Date: 1.JUL.2013 11:21:42


FCC Part 15.247 Page 40 of 63

# 802.11b 26dB, High Channel




Date: 1.JUL.2013 11:24:12

# 802.11b RF Output Power, High Channel




Date: 1.JUL.2013 11:24:26

FCC Part 15.247 Page 41 of 63



Date: 1.JUL.2013 11:35:05

# 802.11g RF Output Power, Low Channel




Date: 1.JUL.2013 11:35:19

FCC Part 15.247 Page 42 of 63


#### 2 11 ~ 2(dD Middle Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 11:37:42

# 802.11g RF Output Power, Middle Channel




Date: 1.JUL.2013 11:37:56

FCC Part 15.247 Page 43 of 63


# 802.11g RF 26dB, High Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 11:40:39

# 802.11g RF Output Power, High Channel




Date: 1.JUL.2013 11:40:53

FCC Part 15.247 Page 44 of 63


# 802.11n20 26dB, Low Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:30:38

# 802.11n20 RF Output Power, Low Channel




Date: 1.JUL.2013 13:30:52

FCC Part 15.247 Page 45 of 63


# 802.11n20 26dB, Middle Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:32:15


## 802.11n20 RF Output Power, Middle Channel



Date: 1.JUL.2013 13:32:29


FCC Part 15.247 Page 46 of 63

# 802.11n20 26dB, High Channel



Date: 1.JUL.2013 13:35:11

# 802.11n20 RF Output Power, High Channel




Date: 1.JUL.2013 13:35:25

FCC Part 15.247 Page 47 of 63


# 802.11n40 26dB, Low Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:40:23

# 802.11n40 RF Output Power, Low Channel




Date: 1.JUL.2013 13:40:37

FCC Part 15.247 Page 48 of 63


# 802.11n40 26dB, Middle Channel

Report No.: R2DG130628021-00A




Date: 1.JUL.2013 13:42:09

### 802.11n40 RF Output Power, Middle Channel




Date: 1.JUL.2013 13:42:23

FCC Part 15.247 Page 49 of 63



#### Date: 1.JUL.2013 13:44:41

# 802.11n40 RF Output Power, High Channel



Date: 1.JUL.2013 13:44:55

FCC Part 15.247 Page 50 of 63

# FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Report No.: R2DG130628021-00A

#### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

## **Test Data**

#### **Environmental Conditions**

Temperature:	27.9 °C
Relative Humidity:	69 %
ATM Pressure:	99.8 kPa

The testing was performed by Ares Liu on 2013-07-01.


**Test Result:** Compliance

Please refer to following table and plots.

FCC Part 15.247 Page 51 of 63


# 802.11b: Band Edge, Left Side

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 11:18:51

### 802.11b: Band Edge, Right Side




Date: 1.JUL.2013 11:24:50

FCC Part 15.247 Page 52 of 63


# 802.11g: Band Edge, Left Side

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 11:35:46

### 802.11g: Band Edge, Right Side




Date: 1.JUL.2013 11:41:20

FCC Part 15.247 Page 53 of 63


## 802.11n20 Band Edge, Left Side

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:31:20

# 802.11n20 Band Edge, Right Side




Date: 1.JUL.2013 13:35:53

FCC Part 15.247 Page 54 of 63


## 802.11n40 Band Edge, Left Side

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:41:15

# 802.11n40 Band Edge, Right Side



Date: 1.JUL.2013 13:45:34

FCC Part 15.247 Page 55 of 63

# FCC §15.247(e) - POWER SPECTRAL DENSITY

#### **Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: R2DG130628021-00A

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. According to KDB 558074 D01 DTS Meas Guidance v02, set the RBW = 3 kHz, VBW = 30 kHz, Set the span to 1.5 times the DTS channel bandwidth.
- 4. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

# **Test Equipment List and Details**

	Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Ī	R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

<sup>\*</sup> Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

Temperature:	27.9 °C	
Relative Humidity:	69 %	
ATM Pressure:	99.8 kPa	

The testing was performed by Ares Liu on 2013-07-01.

FCC Part 15.247 Page 56 of 63

Test Mode: Transmitting

Test Result: Pass


Channel	PSD	Limit	Result		
Channel	(dBm/3kHz)	(dBm/3kHz)	Resuit		
802.11b mode					
Low	-21.53	8	PASS		
Middle	-21.52	8	PASS		
High	-21.76	8	PASS		
	802.11g mod	e			
Low	-21.05	8	PASS		
Middle	-20.70	8	PASS		
High	-21.16 8		PASS		
802.11n20 mode					
Low	-20.95	8	PASS		
Middle	-19.97	8	PASS		
High	-20.56	8	PASS		
802.11n40 mode					
Low	-24.06	8	PASS		
Middle	-22.95	8	PASS		
High	-22.48	8	PASS		

Report No.: R2DG130628021-00A

Please refer to the following plots


FCC Part 15.247 Page 57 of 63

# Power Spectral Density, 802.11b Low Channel



Date: 1.JUL.2013 11:18:33

### Power Spectral Density, 802.11b Middle Channel




Date: 1.JUL.2013 11:21:49

FCC Part 15.247 Page 58 of 63


# Power Spectral Density, 802.11b High Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 11:24:33


# Power Spectral Density, 802.11g Low Channel



Date: 1.JUL.2013 11:35:29


FCC Part 15.247 Page 59 of 63

# Power Spectral Density, 802.11g Middle Channel



Date: 1.JUL.2013 11:38:06


# Power Spectral Density, 802.11g High Channel



Date: 1.JUL.2013 11:41:03


FCC Part 15.247 Page 60 of 63

# Power Spectral Density, 802.11n20 Low Channel



Date: 1.JUL.2013 13:31:02

# Power Spectral Density, 802.11n20 Middle Channel




Date: 1.JUL.2013 13:32:39

FCC Part 15.247 Page 61 of 63


# Power Spectral Density, 802.11n20 High Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:35:35

## Power Spectral Density, 802.11n40 Low Channel




Date: 1.JUL.2013 13:40:58

FCC Part 15.247 Page 62 of 63


# Power Spectral Density, 802.11n40 Middle Channel

Report No.: R2DG130628021-00A



Date: 1.JUL.2013 13:42:44

## Power Spectral Density, 802.11n40 High Channel



Date: 1.JUL.2013 13:45:16

\*\*\*\*\* END OF REPORT \*\*\*\*\*

FCC Part 15.247 Page 63 of 63