

FCC PART 15.247

TEST REPORT

For

SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD.

NO.1 Shuoying Rd., Hebei Industry Area, Dalang, Longhua Town, Baoan,Shenzhen,China.

FCC ID: XJN-PA0942X

Report Type: Original Report	Product Type: Mobile Internet Devices
Test Engineer:	Ares Liu <i>Ares Liu</i>
Report Number:	R2DG130809021-00B
Report Date:	2013-09-22 Ivan Cao
Reviewed By:	RF Leader <i>Ivan Cao</i>
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP.....	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	16
APPLICABLE STANDARD	16
MEASUREMENT UNCERTAINTY.....	16
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS.....	18
CORRECTED AMPLITUDE & MARGIN CALCULATION	18
TEST RESULTS SUMMARY	18
TEST DATA	18
FCC §15.247(a) (1) - CHANNEL SEPARATION TEST	27
APPLICABLE STANDARD	27
TEST EQUIPMENT LIST AND DETAILS.....	27
TEST PROCEDURE	27
TEST DATA	27
FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING.....	33

APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST	39
APPLICABLE STANDARD	39
TEST PROCEDURE	39
TEST EQUIPMENT LIST AND DETAILS.....	39
TEST DATA	39
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	43
APPLICABLE STANDARD	43
TEST PROCEDURE	43
TEST EQUIPMENT LIST AND DETAILS.....	43
TEST DATA	43
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	59
APPLICABLE STANDARD	59
TEST PROCEDURE	59
TEST EQUIPMENT LIST AND DETAILS.....	59
TEST DATA	59
FCC §15.247(d) - BAND EDGES TESTING	65
APPLICABLE STANDARD	65
TEST PROCEDURE	65
TEST EQUIPMENT LIST AND DETAILS.....	65
TEST DATA	65

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD.*'s product, model number: *PA0942 (FCC ID: XJN-PA0942X)* (the "EUT") in this report was a *Mobile Internet Devices*, which was measured approximately: 24.0cm (L) x 18.8 cm (W) x 1.0 cm (H), rated input voltage: DC 3.7 V from lithium battery or DC 5V from adapter.

Adapter information: Flypower
Model: PS14K0502000U5
Input: AC 100-240V, 50/60Hz, 0.35A
Output: DC 5V, 2000mA

** All measurement and test data in this report was gathered from production sample serial number: 130809021 (Assigned by BACL.Dongguan). The EUT was received on 2013-08-12.*

Objective

This report is prepared on behalf of *SHUOYING INDUSTRIAL(SHENZHEN)CO.,LTD.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission rules.

The tests were performed in order to determine the Bluetooth of EUT compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: *XJN-PA0942X*
FCC Part 15C DTS submissions with FCC ID: *XJN-PA0942X* for Wifi.
FCC Part 15C DTS submissions with FCC ID: *XJN-PA0942X* for Bluetooth LE mode.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at <http://ts.nist.gov/standards/scopes/5000690.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer.

EUT Exercise Software

The software “cmd” was used.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
DELL	LCD Monitor	U3011t	CN-OPH5NY-74445-16T-290L
Kinston	Micro SD Card	4G	N/A

External I/O Cable

Cable Description	Length (m)	From	To
Shielded Detachable HDMI Cable	1.5	HDMI Port of Monitor	EUT
Shielded Detachable USB Cable	0.7	Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance
§15.247 (a)(1)	20 dB Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band Edges	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure V05 Appendix A, SAR can be exempted if the output power is less than the SAR exclusion threshold:

For $f=2450\text{MHz}$, the output power is less 10mW at distance of 5mm.

Measurement Result

Peak conducted output power= 1.45 dBm

Antenna gain = 2 dBi

SAR exclusion threshold 10 mW (10dBm) > 1.45dBm

So the SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has an internal antenna, which was permanently attached to the EUT, and the maximum gain is 2dBi, please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2003 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,

V_C : corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECIEVER	ESCS 30	830245/006	2013-1-10	2014-1-9
R&S	L.I.S.N	ESH3-Z5	843331/015	2012-9-17	2013-9-16
R&S	L.I.S.N	ESH3-Z5	100113	2012-11-29	2013-11-28
BACL	Test Software	BACL-EMC	V1.0-2010	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

20.31 dB at 0.190 MHz in the Line conducted mode


Test Data**Environmental Conditions**

Temperature:	27.4 °C
Relative Humidity:	65 %
ATM Pressure:	99.6 kPa


The testing was performed by Ares Liu on 2013-09-09.

Test Mode: Transmitting

120 V, 60 Hz, Line:



Frequency (MHz)	Cord. Reading (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/AV/QP)
0.190	43.73	0.44	64.04	20.31	QP
0.190	30.11	0.44	54.04	23.93	AV
0.340	35.00	0.33	59.20	24.20	QP
0.340	19.39	0.33	49.20	29.81	AV
0.660	31.82	0.31	56.00	24.18	QP
0.660	25.58	0.31	46.00	20.42	AV
0.940	27.90	0.32	56.00	28.10	QP
0.940	21.30	0.32	46.00	24.70	AV
1.580	27.45	0.34	56.00	28.55	QP
1.570	20.73	0.34	46.00	25.27	AV
2.370	27.29	0.37	56.00	28.71	QP
2.370	20.57	0.37	46.00	25.43	AV

120 V, 60 Hz, Neutral:

Frequency (MHz)	Cord. Reading (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/AV/QP)
0.180	41.92	0.25	64.49	22.57	QP
0.180	33.42	0.25	54.49	21.07	AV
0.250	36.82	0.24	61.76	24.94	QP
0.250	23.81	0.24	51.76	27.95	AV
0.540	29.84	0.21	56.00	26.16	QP
0.540	19.12	0.21	46.00	26.88	AV
0.920	29.16	0.23	56.00	26.84	QP
0.920	23.26	0.23	46.00	22.74	AV
1.530	30.09	0.25	56.00	25.91	QP
1.530	23.30	0.25	46.00	22.70	AV
2.320	27.56	0.28	56.00	28.44	QP
2.320	20.46	0.28	46.00	25.54	AV

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 1 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

During the radiated emissions, the EUT was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet. #

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz - 1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCI	100224	2013-5-6	2014-5-5
Sunol Sciences	Antenna	JB3	A060611-1	2012-9-6	2015-9-5
HP	HP AMPLIFIER	8447E	2434A02181	N/A	N/A
R&S	Spectrum analyzer	FSEM 30	849016/001	2013-9-4	2014-9-3
ETS LINDGREN	horn antenna	3115	000 527 35	2012-9-6	2015-9-5
Mini-Circuit	Amplifier	ZVA-213-S+	54201245	N/A	N/A
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, and section 15.205, 15.209 and 15.247, with the worst margin reading of:

4.64 dB at 40.67 MHz in the **Vertical** polarization of BDR Mode (GFSK)

Test Data**Environmental Conditions**

Temperature:	27.6° C
Relative Humidity:	66 %
ATM Pressure:	99.1 kPa

The testing was performed by Ares Liu on 2013-09-22.

Mode: Transmitting

BDR Mode (GFSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	48.76	AV	H	25.65	3.90	0.00	78.31	N/A	N/A
2402	60.44	PK	H	25.65	3.90	0.00	89.99	N/A	N/A
2402	45.63	AV	V	25.65	3.90	0.00	75.18	N/A	N/A
2402	51.46	PK	V	25.65	3.90	0.00	81.01	N/A	N/A
2390	31.61	PK	H	25.61	3.84	0.00	61.06	74.00	12.94
2390	15.82	AV	H	25.61	3.84	0.00	45.27	54.00	8.73
4804	45.23	PK	H	30.59	4.67	27.26	53.23	74.00	20.77
4804	26.84	AV	H	30.59	4.67	27.26	34.84	54.00	19.16
7206	33.31	PK	H	34.09	6.50	26.30	47.60	74.00	26.40
7206	19.21	AV	H	34.09	6.50	26.30	33.50	54.00	20.50
9608	32.41	PK	V	35.96	8.75	26.22	50.90	74.00	23.10
9608	18.45	AV	V	35.96	8.75	26.22	36.94	54.00	17.06
1678.34	33.35	PK	V	23.96	3.18	26.94	33.55	74.00	40.45
1678.34	18.62	AV	V	23.96	3.18	26.94	18.82	54.00	35.18
40.67	42.00	QP	V	13.95	0.83	21.42	35.36	40.00	4.64*
Middle Channel: 2441(MHz)									
2441	48.17	AV	H	25.75	3.99	0.00	77.91	N/A	N/A
2441	59.65	PK	H	25.75	3.99	0.00	89.39	N/A	N/A
2441	44.72	AV	V	25.75	3.99	0.00	74.45	N/A	N/A
2441	50.54	PK	V	25.75	3.99	0.00	80.27	N/A	N/A
4882	46.60	PK	H	30.79	4.75	27.26	54.88	74.00	19.12
4882	26.34	AV	H	30.79	4.75	27.26	34.62	54.00	19.38
7323	33.89	PK	H	34.38	6.72	26.53	48.46	74.00	25.54
7323	20.83	AV	H	34.38	6.72	26.53	35.40	54.00	18.60
9764	33.35	PK	V	36.33	8.58	25.62	52.64	74.00	21.36
9764	19.34	AV	V	36.33	8.58	25.62	38.63	54.00	15.37
1123.26	32.32	PK	V	22.62	2.36	27.22	30.08	74.00	43.92
1123.26	18.94	AV	V	22.62	2.36	27.22	16.70	54.00	37.30
1613.25	33.57	PK	V	23.83	3.18	26.90	33.68	74.00	40.32
1613.25	19.62	AV	V	23.83	3.18	26.90	19.73	54.00	34.27
40.13	41.60	QP	V	14.34	0.83	21.42	35.35	40.00	4.65*
High Channel: 2480(MHz)									
2480	48.28	AV	H	25.85	3.82	0.00	77.94	N/A	N/A
2480	58.65	PK	H	25.85	3.82	0.00	88.31	N/A	N/A
2480	45.06	AV	V	25.85	3.82	0.00	74.73	N/A	N/A
2480	49.68	PK	V	25.85	3.82	0.00	79.35	N/A	N/A
2483.5	31.21	PK	H	25.86	3.80	0.00	60.87	74.00	13.13
2483.5	17.01	AV	H	25.86	3.80	0.00	46.67	54.00	7.33
4960	45.28	PK	H	31.00	4.70	27.27	53.71	74.00	20.29
4960	25.48	AV	H	31.00	4.70	27.27	33.91	54.00	20.09
7440	33.63	PK	H	34.66	6.95	26.56	48.68	74.00	25.32
7440	19.49	AV	H	34.66	6.95	26.56	34.54	54.00	19.46
9920	32.79	PK	V	36.71	8.41	25.50	52.41	74.00	21.59
9920	18.39	AV	V	36.71	8.41	25.50	38.01	54.00	15.99
1653.22	33.67	PK	V	23.91	3.17	26.93	33.82	74.00	40.18
1653.22	18.33	AV	V	23.91	3.17	26.93	18.48	54.00	35.52
40.57	41.10	QP	V	14.02	0.83	21.42	34.53	40.00	5.47

*Within measurement uncertainty!

EDR Mode ($\pi/4$ -DQPSK):


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	48.49	AV	H	25.65	3.90	0.00	78.04	N/A	N/A
2402	60.82	PK	H	25.65	3.90	0.00	90.37	N/A	N/A
2402	45.39	AV	V	25.65	3.90	0.00	74.94	N/A	N/A
2402	51.02	PK	V	25.65	3.90	0.00	80.57	N/A	N/A
2390	31.65	PK	H	25.61	3.84	0.00	61.10	74.00	12.90
2390	15.64	AV	H	25.61	3.84	0.00	45.09	54.00	8.91
4804	45.28	PK	H	30.59	4.67	27.26	53.28	74.00	20.72
4804	25.71	AV	H	30.59	4.67	27.26	33.71	54.00	20.29
7206	33.14	PK	H	34.09	6.50	26.30	47.43	74.00	26.57
7206	19.10	AV	H	34.09	6.50	26.30	33.39	54.00	20.61
9608	32.57	PK	V	35.96	8.75	26.22	51.06	74.00	22.94
9608	18.42	AV	V	35.96	8.75	26.22	36.91	54.00	17.09
1678.34	34.15	PK	V	23.96	3.18	26.94	34.35	74.00	39.65
1678.34	18.52	AV	V	23.96	3.18	26.94	18.72	54.00	35.28
40.67	41.30	QP	V	13.95	0.83	21.42	34.66	40.00	5.34
Middle Channel: 2441(MHz)									
2441	48.53	AV	H	25.75	3.99	0.00	78.27	N/A	N/A
2441	60.22	PK	H	25.75	3.99	0.00	89.96	N/A	N/A
2441	44.79	AV	V	25.75	3.99	0.00	74.52	N/A	N/A
2441	51.56	PK	V	25.75	3.99	0.00	81.30	N/A	N/A
4882	45.95	PK	H	30.79	4.75	27.26	54.23	74.00	19.77
4882	27.15	AV	H	30.79	4.75	27.26	35.43	54.00	18.57
7323	33.52	PK	H	34.38	6.72	26.53	48.09	74.00	25.91
7323	21.25	AV	H	34.38	6.72	26.53	35.82	54.00	18.18
9764	32.91	PK	V	36.33	8.58	25.62	52.20	74.00	21.80
9764	18.89	AV	V	36.33	8.58	25.62	38.18	54.00	15.82
1123.26	33.86	PK	V	22.62	2.36	27.22	31.62	74.00	42.38
1123.26	19.14	AV	V	22.62	2.36	27.22	16.90	54.00	37.10
1613.25	33.54	PK	V	23.83	3.18	26.90	33.65	74.00	40.35
1613.25	18.65	AV	V	23.83	3.18	26.90	18.76	54.00	35.24
40.13	41.50	QP	V	14.34	0.83	21.42	35.25	40.00	4.75*
High Channel: 2480(MHz)									
2480	48.45	AV	H	25.85	3.82	0.00	78.12	N/A	N/A
2480	58.98	PK	H	25.85	3.82	0.00	88.65	N/A	N/A
2480	45.05	AV	V	25.85	3.82	0.00	74.72	N/A	N/A
2480	50.48	PK	V	25.85	3.82	0.00	80.15	N/A	N/A
2483.5	31.25	PK	H	25.86	3.80	0.00	60.91	74.00	13.09
2483.5	16.96	AV	H	25.86	3.80	0.00	46.62	54.00	7.38
4960	46.04	PK	H	31.00	4.70	27.27	54.47	74.00	19.53
4960	25.71	AV	H	31.00	4.70	27.27	34.14	54.00	19.86
7440	33.20	PK	H	34.66	6.95	26.56	48.25	74.00	25.75
7440	19.02	AV	H	34.66	6.95	26.56	34.07	54.00	19.93
9920	33.58	PK	V	36.71	8.41	25.50	53.20	74.00	20.80
9920	17.76	AV	V	36.71	8.41	25.50	37.38	54.00	16.62
1653.22	33.41	PK	V	23.91	3.17	26.93	33.56	74.00	40.44
1653.22	18.41	AV	V	23.91	3.17	26.93	18.56	54.00	35.44
40.57	40.90	QP	V	14.02	0.83	21.42	34.33	40.00	5.67

*Within measurement uncertainty!


EDR Mode (8-DPSK):

Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
(MHz)	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)				Limit (dBμV/m)	Margin (dB)
Low Channel: 2402(MHz)									
2402	48.24	AV	H	25.65	3.90	0.00	77.79	N/A	N/A
2402	59.72	PK	H	25.65	3.90	0.00	89.27	N/A	N/A
2402	44.41	AV	V	25.65	3.90	0.00	73.96	N/A	N/A
2402	50.66	PK	V	25.65	3.90	0.00	80.21	N/A	N/A
2390	31.65	PK	H	25.61	3.84	0.00	61.10	74.00	12.90
2390	16.02	AV	H	25.61	3.84	0.00	45.47	54.00	8.53
4804	45.13	PK	H	30.59	4.67	27.26	53.13	74.00	20.87
4804	26.79	AV	H	30.59	4.67	27.26	34.79	54.00	19.21
7206	33.72	PK	H	34.09	6.50	26.30	48.01	74.00	25.99
7206	19.40	AV	H	34.09	6.50	26.30	33.69	54.00	20.31
9608	33.57	PK	V	35.96	8.75	26.22	52.06	74.00	21.94
9608	18.30	AV	V	35.96	8.75	26.22	36.79	54.00	17.21
1678.34	33.74	PK	V	23.96	3.18	26.94	33.94	74.00	40.06
1678.34	18.36	AV	V	23.96	3.18	26.94	18.56	54.00	35.44
40.67	41.80	QP	V	13.95	0.83	21.42	35.16	40.00	4.84*
Middle Channel: 2441(MHz)									
2441	47.93	AV	H	25.75	3.99	0.00	77.66	N/A	N/A
2441	58.78	PK	H	25.75	3.99	0.00	88.51	N/A	N/A
2441	44.24	AV	V	25.75	3.99	0.00	73.97	N/A	N/A
2441	50.52	PK	V	25.75	3.99	0.00	80.26	N/A	N/A
4882	45.85	PK	H	30.79	4.75	27.26	54.13	74.00	19.87
4882	26.20	AV	H	30.79	4.75	27.26	34.48	54.00	19.52
7323	33.41	PK	H	34.38	6.72	26.53	47.98	74.00	26.02
7323	20.62	AV	H	34.38	6.72	26.53	35.19	54.00	18.81
9764	33.64	PK	V	36.33	8.58	25.62	52.93	74.00	21.07
9764	18.74	AV	V	36.33	8.58	25.62	38.03	54.00	15.97
1123.26	33.51	PK	V	22.62	2.36	27.22	31.27	74.00	42.73
1123.26	18.62	AV	V	22.62	2.36	27.22	16.38	54.00	37.62
1613.25	32.50	PK	V	23.83	3.18	26.90	32.61	74.00	41.39
1613.25	18.50	AV	V	23.83	3.18	26.90	18.61	54.00	35.39
40.13	41.60	QP	V	14.34	0.83	21.42	35.35	40.00	4.65*
High Channel: 2480(MHz)									
2480	48.12	AV	H	25.85	3.82	0.00	77.78	N/A	N/A
2480	58.41	PK	H	25.85	3.82	0.00	88.08	N/A	N/A
2480	44.46	AV	V	25.85	3.82	0.00	74.13	N/A	N/A
2480	49.54	PK	V	25.85	3.82	0.00	79.21	N/A	N/A
2483.5	31.58	PK	H	25.86	3.80	0.00	61.24	74.00	12.76
2483.5	16.35	AV	H	25.86	3.80	0.00	46.01	54.00	7.99
4960	44.90	PK	H	31.00	4.70	27.27	53.33	74.00	20.67
4960	25.46	AV	H	31.00	4.70	27.27	33.89	54.00	20.11
7440	33.58	PK	H	34.66	6.95	26.56	48.63	74.00	25.37
7440	19.19	AV	H	34.66	6.95	26.56	34.24	54.00	19.76
9920	32.75	PK	V	36.71	8.41	25.50	52.37	74.00	21.63
9920	18.40	AV	V	36.71	8.41	25.50	38.02	54.00	15.98
1653.22	33.37	PK	V	23.91	3.17	26.93	33.52	74.00	40.48
1653.22	18.43	AV	V	23.91	3.17	26.93	18.58	54.00	35.42
40.57	41.30	QP	V	14.02	0.83	21.42	34.73	40.00	5.27


*Within measurement uncertainty!

Conducted Spurious Emissions at Antenna Port*BDR Mode (GFSK):***Low Channel**


Date: 22.SEP.2013 16:01:24

Middle Channel

Date: 22.SEP.2013 16:02:42


High Channel

Date: 22.SEP.2013 16:04:41

*EDR Mode ($\pi/4$ -DQPSK):***Low Channel**


Date: 22.SEP.2013 16:07:48

Middle Channel



Date: 22.SEP.2013 16:06:46


High Channel



Date: 22.SEP.2013 16:06:11


EDR Mode (8-DPSK):

Low Channel




Date: 22.SEP.2013 16:09:09

Middle Channel



Date: 22.SEP.2013 16:10:23

High Channel



Date: 22.SEP.2013 16:11:19

FCC §15.247(a) (1) - CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.50 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

1. Set the EUT in transmitting mode, spectrum Bandwidth was set at 100 kHz, maxhold the channel.
2. Set the adjacent channel of the EUT maxhold another trace
3. Measure the channel separation.

Test Data**Environmental Conditions**

Temperature:	27.5 °C
Relative Humidity:	56 %
ATM Pressure:	99.1 kPa

* The testing was performed by Ares Liu on 2013-09-22

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR Mode (GFSK)	Low	2402	1.000	0.627	Pass
	Adjacent	2403			
	Middle	2441	1.012	0.627	Pass
	Adjacent	2442			
	High	2480	1.000	0.627	Pass
	Adjacent	2479			
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.004	0.813	Pass
	Adjacent	2403			
	Middle	2441	1.004	0.813	Pass
	Adjacent	2442			
	High	2480	1.000	0.813	Pass
	Adjacent	2479			
EDR Mode (8-DPSK):	Low	2402	1.000	0.808	Pass
	Adjacent	2403			
	Middle	2441	1.008	0.808	Pass
	Adjacent	2442			
	High	2480	1.004	0.808	Pass
	Adjacent	2479			


BDR Mode (GFSK):

Low Channel




Date: 22.SEP.2013 10:43:48

Middle Channel



Date: 22.SEP.2013 10:44:36


High Channel



Date: 22.SEP.2013 10:46:12


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 22.SEP.2013 13:58:12


Middle Channel



Date: 22.SEP.2013 13:58:43


High Channel

Date: 22.SEP.2013 13:59:14

*EDR Mode (8-DPSK):***Low Channel**


Date: 22.SEP.2013 14:10:25

Middle Channel



Date: 22.SEP.2013 14:10:54

High Channel



Date: 22.SEP.2013 14:11:21

FCC §15.247(a) (1) – 20 dB BANDWIDTH TESTING**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.5 °C
Relative Humidity:	56 %
ATM Pressure:	99.1 kPa

* The testing was performed by Ares Liu on 2013-09-22

Test Result: Compliance.


Please refer to following tables and plots

Mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
BDR Mode (GFSK)	Low	2402	0.920
	Middle	2441	0.940
	High	2480	0.936
EDR Mode ($\pi/4$ -DQPSK):	Low	2402	1.196
	Middle	2441	1.224
	High	2480	1.220
EDR Mode (8-DPSK):	Low	2402	1.340
	Middle	2441	1.336
	High	2480	1.340

BDR Mode (GFSK):




Middle Channel



Date: 22.SEP.2013 11:42:28


High Channel



Date: 22.SEP.2013 11:41:27


EDR Mode ($\pi/4$ -DQPSK):

Low Channel




Date: 22.SEP.2013 13:39:29

Middle Channel



Date: 22.SEP.2013 11:57:38


High Channel



Date: 22.SEP.2013 11:53:44


EDR Mode (8-DPSK):

Low Channel




Date: 22.SEP.2013 14:08:56

Middle Channel



Date: 22.SEP.2013 14:08:04

High Channel



Date: 22.SEP.2013 14:07:09

FCC §15.247(a) (1) (iii) - QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the Max-Hold function record the Quantity of the channel.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.5 °C
Relative Humidity:	56 %
ATM Pressure:	99.1 kPa

* The testing was performed by Ares Liu on 2013-09-22

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15


Number of Hopping Channels



Date: 22.SEP.2013 11:35:09

EDR Mode ($\pi/4$ -DQPSK):


Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



Date: 22.SEP.2013 13:49:15

EDR Mode (8-DPSK):

Frequency Range (MHz)	Number of Hopping Channel	Limit
2400-2483.5	79	≥ 15



Date: 22.SEP.2013 14:20:06

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT was worked in channel hopping; Spectrum SPAN was set as 0. Sweep was set as $0.4 \times \text{channel no. (s)}$, the quantity of pulse was get from single sweep. In addition, the time of single pulses was tested.

Dwell Time = time slot length * hop rate / number of hopping channels * 31.6s
Hop rate = 1600/s

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.5 °C
Relative Humidity:	56 %
ATM Pressure:	99.1 kPa

* The testing was performed by Ares Liu on 2013-09-22

Test Result: Compliance.


Please refer to following tables and plots

Test Mode: Transmitting

BDR Mode (GFSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.450	0.144	0.4	Pass
	Middle	0.450	0.144	0.4	Pass
	High	0.450	0.144	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
DH3	Low	1.710	0.274	0.4	Pass
	Middle	1.710	0.274	0.4	Pass
	High	1.710	0.274	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
DH5	Low	2.980	0.318	0.4	Pass
	Middle	2.980	0.318	0.4	Pass
	High	2.980	0.318	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

DH1: Low Channel




Date: 22.SEP.2013 10:52:57

DH1: Middle Channel




Date: 22.SEP.2013 10:53:38

DH1: High Channel




Date: 22.SEP.2013 10:53:59

DH3: Low Channel




Date: 22.SEP.2013 11:29:56

DH3: Middle Channel




Date: 22.SEP.2013 11:29:46

DH3: High Channel




Date: 22.SEP.2013 11:29:39

DH5: Low Channel




Date: 22.SEP.2013 11:30:31

DH5: Middle Channel



Date: 22.SEP.2013 11:30:40

DH5: High Channel




Date: 22.SEP.2013 11:30:55

EDR Mode ($\pi/4$ -DQPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
DH1	Low	0.460	0.147	0.4	Pass
	Middle	0.460	0.147	0.4	Pass
	High	0.460	0.147	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
DH3	Low	1.350	0.216	0.4	Pass
	Middle	1.340	0.214	0.4	Pass
	High	1.340	0.214	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
DH5	Low	2.970	0.317	0.4	Pass
	Middle	2.970	0.317	0.4	Pass
	High	2.970	0.317	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

DH1: Low Channel




Date: 22.SEP.2013 13:50:15

DH1: Middle Channel




Date: 22.SEP.2013 13:51:15

DH1: High Channel




Date: 22.SEP.2013 13:52:25

DH3: Low Channel




Date: 22.SEP.2013 13:53:54

DH3: Middle Channel




Date: 22.SEP.2013 13:53:32

DH3: High Channel




Date: 22.SEP.2013 13:53:16

DH5: Low Channel




Date: 22.SEP.2013 13:54:24

DH5: Middle Channel



Date: 22.SEP.2013 13:54:39

DH5: High Channel




Date: 22.SEP.2013 13:54:53

EDR Mode (8-DPSK):


Mode	Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
<i>DH1</i>	Low	0.452	0.145	0.4	Pass
	Middle	0.452	0.145	0.4	Pass
	High	0.452	0.145	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/2/79) \times 31.6 s				
<i>DH3</i>	Low	1.702	0.272	0.4	Pass
	Middle	1.702	0.272	0.4	Pass
	High	1.702	0.272	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/4/79) \times 31.6 s				
<i>DH5</i>	Low	2.972	0.317	0.4	Pass
	Middle	2.972	0.317	0.4	Pass
	High	2.972	0.317	0.4	Pass
	Note: Dwell time=Pulse time (ms) \times (1600/6/79) \times 31.6 s				

DH1: Low Channel




Date: 22.SEP.2013 14:42:16

DH1: Middle Channel




Date: 22.SEP.2013 14:42:31

DH1: High Channel




Date: 22.SEP.2013 14:42:46

DH3: Low Channel




Date: 22.SEP.2013 14:43:39

DH3: Middle Channel




Date: 22.SEP.2013 14:43:32

DH3: High Channel




Date: 22.SEP.2013 14:43:22

DH5: Low Channel




Date: 22.SEP.2013 14:44:58

DH5: Middle Channel



Date: 22.SEP.2013 14:45:08

DH5: High Channel



Date: 22.SEP.2013 14:45:19

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI test receiver.
3. Add a correction factor to the display.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	27.5 °C
Relative Humidity:	56 %
ATM Pressure:	99.1 kPa

* The testing was performed by Ares Liu on 2013-09-22


Test Result: Compliance.

Test Mode: Transmitting

Mode	Channel	Frequency (MHz)	Output power (dBm)	Limit (dBm)
BDR Mode (GFSK)	Low	2402	0.78	30
	Middle	2441	1.21	30
	High	2480	1.21	30
EDR Mode ($\pi/4$ -DQPSK)	Low	2402	-1.87	30
	Middle	2441	1.45	30
	High	2480	1.42	30
EDR Mode (8-DPSK)	Low	2402	-0.47	30
	Middle	2441	0.20	30
	High	2480	0.26	30


Note: The data above was tested in conducted mode.

BDR Mode (GFSK):




Date: 22.SEP.2013 10:34:59

Output Power, Middle



Date: 22.SEP.2013 11:38:26


Output Power, High



Date: 22.SEP.2013 11:40:09


EDR Mode ($\pi/4$ -DQPSK):

Output Power, Low




Date: 22.SEP.2013 13:38:14

Output Power, Middle



Date: 22.SEP.2013 11:56:48


Output Power, High



Date: 22.SEP.2013 11:52:50


EDR Mode (8-DPSK):

Output Power, Low




Date: 22.SEP.2013 14:03:05

Output Power, Middle



Date: 22.SEP.2013 14:02:05

Output Power, High



Date: 22.SEP.2013 14:01:13

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data


Environmental Conditions

Temperature:	27.5 °C
Relative Humidity:	56 %
ATM Pressure:	99.1 kPa

* The testing was performed by Ares Liu on 2013-09-22

Test Result: Compliance*BDR Mode (GFSK):***Band Edge, Left Side**


Date: 22.SEP.2013 10:42:08

Band Edge, Right Side

Date: 22.SEP.2013 11:44:23


EDR Mode ($\pi/4$ -DQPSK):

Band Edge, Left Side



Date: 22.SEP.2013 13:40:43


Band Edge, Right Side



Date: 22.SEP.2013 11:55:26


EDR Mode (8-DPSK):

Band Edge, Left Side



Date: 22.SEP.2013 14:04:45

Band Edge, Right Side



Date: 22.SEP.2013 14:05:55

***** END OF REPORT *****