



FCC PART 15.247 TEST REPORT

For

SHUOYING INDUSTRIAL (SHENZHEN) CO., LTD.

NO.1 Shuoying Rd., Hebei Industry Area, Dalang, Longhua Town, Baoan, Shenzhen, China

FCC ID: XJN-PM0783X

Report Type: **Product Type:** Mobile Internet Devices Original Report Allen Rious Test Engineer: Allen Qiao **Report Number:** R2DG131127001-00B **Report Date:** 2014-01-13 Ivan Cao RF Leader **Reviewed By: Test Laboratory:** Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★" (Rev.2). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	
External I/O Cable	
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUP	
EMI TEST RECEIVER SETUP TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS.	
TEST RESULTS SUMMARY	13
TEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	16
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT SETUP	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS.	
TEST RESULTS SUMMARY	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	30
APPLICABLE STANDARD	
TEST PROCEDURE TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	
• (/(/	

APPLICABLE STANDARD	38
TEST PROCEDURE	38
TEST EQUIPMENT LIST AND DETAILS.	
TEST DATA	
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	52
APPLICABLE STANDARD	52
Test Procedure	52
TEST EQUIPMENT LIST AND DETAILS.	52
Test Data	52
FCC §15.247(e) - POWER SPECTRAL DENSITY	57
APPLICABLE STANDARD	57
Test Procedure	57
TEST EQUIPMENT LIST AND DETAILS.	57
TEST DATA	57

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The SHUOYING INDUSTRIAL (SHENZHEN) CO., LTD.'s product, model number: PM0783 (FCC ID: XJN-PM0783X) (the "EUT") in this report was a Mobile Internet Devices, which was measured approximately: 18.6cm (L) x 11.6 cm (W) x 0.9 cm (H), rated input voltage: DC 3.7 V from lithium battery or DC 5V from adapter.

Report No.: R2DG131127001-00B

Adapter information: SPPS Model: SA/12PA/05FUS050200 Input: AC 100-240V, 50/60Hz, 0.5A

Output: DC 5.0V, 2A

Objective

This report is prepared on behalf of *SHUOYING INDUSTRIAL (SHENZHEN) CO., LTD.* in accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: *XJN-PM0783X* FCC Part15C DSS submissions with FCC ID: *XJN-PM0783X for Bluetooth BDR, EDR mode*. FCC Part15C DTS submissions with FCC ID: *XJN-PM0783X for Bluetooth LE mode*. FCC Part 22H & 24E PCB submissions with FCC ID: *XJN-PM0783X*.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2003, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

FCC Part 15.247 Page 4 of 64

^{*} All measurement and test data in this report was gathered from production sample serial number: 131127001 (Assigned by BACL.Dongguan). The EUT was received on 2013-11-18.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Report No.: R2DG131127001-00B

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Dongguan) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 500069-0).



The current scope of accreditations can be found at http://ts.nist.gov/standards/scopes/5 000690.htm

FCC Part 15.247 Page 5 of 64

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode, which was provided by manufacturer. For 2.4G band, 11 channels are provided to testing:

Report No.: R2DG131127001-00B

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b and 802.11g modes were tested with Channel 1, 6 and 11.

For 802.11n40 mode were tested with Channel 3, 6 and 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all date rates bandwidths, and modulations.

EUT Exercise Software

The engineering mode was a build in software entered with engineering code, which was provided by manufacturer, and the test configured as following table:

Test Mode	Test Software Version	engineering mode				
	Test Frequency	2412MHz	2412MHz 2437MHz			
802.11b	Data Rate	1 Mbps	1Mbps	1Mbps		
002.110	Power Level Setting	12.5	12.5	12		
	Test Frequency	2412MHz	2437MHz	2462MHz		
802.11g	Data Rate	6Mbps	6Mbps	6Mbps		
002.11g	Power Level Setting	11.5	11.5	11		
	Test Frequency	2412MHz	2437MHz	2462MHz		
802.11n20	Data Rate	MCS0	MCS0	MCS0		
002.111120	Power Level Setting	10.5	10.5	10.5		
	Test Frequency	2422MHz	2437MHz	2452MHz		
802.11n40	Data Rate	MCS0	MCS0	MCS0		
002.111140	Power Level Setting	12.5	12.5	12.5		

FCC Part 15.247 Page 6 of 64

Equipment Modifications

No modification was made to the EUT.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
SAMSUNG	LCD Monitor	S22C330H	ZXDCHTHD10149991K
SAMSUNG	TF Card	4G	N/A
N/A	Earphone	N/A	N/A

Report No.: R2DG131127001-00B

External I/O Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
HDMI Cable	yes	no	0.5	HDMI Port of Monitor	EUT
USB Cable	yes	yes	0.6	Adapter	EUT
Earphone Cable	no	no	1.2	EUT	Earphone

Block Diagram of Test Setup



FCC Part 15.247 Page 7 of 64

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF EXPOSURE	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
\$15.205, \$15.209, \$15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Report No.: R2DG131127001-00B

FCC Part 15.247 Page 8 of 64

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

Report No.: R2DG131127001-00B

According to KDB 447498 D01 Mobile Portable RF Exposure V05 Appendix A, SAR can be exempted if the average output power is less than the SAR exclusion threshold:

For f=2450MHz, the output power is less 10mW at distance of 5mm.

Measurement Result

Average conducted output power= 9.57 dBm SAR exclusion threshold 10 mW (10dBm) > 9.57dBm

So the stand-alone SAR evaluation is not necessary. The simultaneous transmission SAR please refer to the SAR report: R1DG131127001-20.

FCC Part 15.247 Page 9 of 64

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

Report No.: R2DG131127001-00B

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has an internal antenna, which was permanently attached to the EUT, and the maximum gain is 2.0dBi, please refer to the internal photos.

Result: Compliance.

FCC Part 15.247 Page 10 of 64

FCC §15.207 (a) - AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: R2DG131127001-00B

If $U_{\rm lab}$ is less than or equal to $U_{\rm cispr}$ of Table 1, then:


- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of
$$U_{\text{cispr}}$$

Measurement	$U_{ m cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15.247 Page 11 of 64

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$
$$C_f = A_C + VDF$$

Herein.

V_C (cord. Reading): corrected voltage amplitude

V_R: reading voltage amplitude A_c: attenuation caused by cable loss VDF: voltage division factor of AMN

C_f: Correction Factor

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15.247 Page 12 of 64

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCS 30	830245/006	2013-11-20	2014-11-19
R&S	Two-line V-network	ENV216	3560.6550.12	2013-2-18	2014-2-17
R&S	L.I.S.N	ESH3-Z5	100113	N/A	N/A
BACL	Test Software	BACL-EMC	V1.0-2010	N/A	N/A

Report No.: R2DG131127001-00B

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.207</u>, with the worst margin reading of:

4.83 dB at 1.335 MHz in the Neutral conducted mode

Test Data

Environmental Conditions

Temperature:	20.1 °C
Relative Humidity:	51 %
ATM Pressure:	101.1 kPa


The testing was performed by Allen Qiao on 2013-12-16.

FCC Part 15.247 Page 13 of 64

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Mode: Transmitting


120 V, 60 Hz, Line:



Frequency (MHz)	Cord. Reading (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/AV/QP)
0.200	50.79	9.71	63.16	12.37	QP
0.200	45.45	9.71	53.16	7.71	AV
0.270	42.87	9.70	61.12	18.25	QP
0.270	37.88	9.70	51.12	13.24	AV
1.310	45.08	9.68	56.00	10.92	QP
1.310	39.03	9.68	46.00	6.97	AV
1.380	43.11	9.68	56.00	12.89	QP
1.380	37.84	9.68	46.00	8.16	AV
1.650	43.25	9.68	56.00	12.75	QP
1.650	33.26	9.68	46.00	12.74	AV
30.000	40.21	9.78	60.00	19.79	QP
30.000	34.94	9.78	50.00	15.06	AV

FCC Part 15.247 Page 14 of 64

120 V, 60 Hz, Neutral:



Frequency (MHz)	Cord. Reading (dBµV)	Correction Factor (dB)	Limit (dBµV)	Margin (dB)	Detector (PK/AV/QP)
0.195	47.86	9.70	63.82	15.96	QP
0.195	35.73	9.70	53.82	18.09	AV
0.225	51.00	9.68	62.63	11.63	QP
0.225	47.22	9.68	52.63	5.41	AV
1.025	38.49	9.69	56.00	17.51	QP
1.025	33.05	9.69	46.00	12.95	AV
1.335	48.32	9.69	56.00	7.68	QP
1.335	41.17	9.69	46.00	4.83	AV
1.625	44.81	9.68	56.00	11.19	QP
1.625	36.36	9.68	46.00	9.64	AV
30.000	41.01	9.93	60.00	18.99	QP
30.000	36.05	9.93	50.00	13.95	AV

FCC Part 15.247 Page 15 of 64

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: R2DG131127001-00B

If U_{lab} is less than or equal to U_{cispr} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 2, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit:
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:


30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB

Table 2 – Values of U_{cispr}

Measurement						
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB					
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB					
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB					


EUT Setup

Below 1GHz:



FCC Part 15.247 Page 16 of 64

Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2003. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30MHz – 1000 MHz	120 kHz	300 kHz	120kHz	QP
Above 1 CHa	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

FCC Part 15.247 Page 17 of 64

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Report No.: R2DG131127001-00B

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI TEST RECEIVER	ESCI	100224	2013-5-6	2014-5-5
Sunol Sciences	Antenna	JB3	A060611-1	2011-9-6	2014-9-5
HP	AMPLIFIER	8447E	2434A02181	N/A	N/A
R&S	Spectrum analyzer	FSEM	DE31388	2013-5-7	2014-5-6
ETS LINDGREN	horn antenna	3115	000 527 35	2012-9-6	2015-9-5
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	N/A	N/A
R&S	Spectrum Analyzer	FSP 38	100478	2013-6-16	2014-6-15
Ducommun Technolagies	horn antenna	ARH-4223-02	1007726-01 1304	2013-6-16	2014-6-15
Quinstar	Amplifier	QLW- 18405536-JO	15964001001	N/A	N/A

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247</u>, with the worst margin reading of:

3.17 dB at 178.92 MHz in the Horizontal polarization for 802.11n40 Mode

FCC Part 15.247 Page 18 of 64

Test Data

Environmental Conditions

Temperature:	17.5~24.4 °C
Relative Humidity:	48~57 %
ATM Pressure:	100.9~102.1 kPa

The testing was performed by Allen Qiao from 2013-11-18 to 2014-01-13.

Report No.: R2DG131127001-00B

FCC Part 15.247 Page 19 of 64

Mode: Transmitting

802.11	802.11b Mode									
-	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1:	5.247	
Frequency	Reading	Detector	Polar	Factor	loss	Gain	Amplitude	Limit	Margin	
(MHz)	(dBµV)	(PK/QP/AV)	(H/V)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
Low Channel: 2412 MHz										
2412	67.28	PK	Н	25.67	4.42	0.00	97.37	N/A	N/A	
2412	62.12	AV	Н	25.67	4.42	0.00	92.21	N/A	N/A	
2412	63.75	PK	V	25.67	4.42	0.00	93.84	N/A	N/A	
2412	58.56	AV	V	25.67	4.42	0.00	88.65	N/A	N/A	
2390	29.24	PK	H	25.61	4.39	0.00	59.24	74.00	14.76	
2390	14.06	AV	Н	25.61	4.39	0.00	44.06	54.00	9.94	
4824	36.04	PK	Н	30.64	6.03	27.26	45.45	74.00	28.55	
4824	30.5	AV	Н	30.64	6.03	27.26	39.91	54.00	14.09	
7236	32.71	PK	Н	34.17	7.47	26.36	47.99	74.00	26.01	
7236	18.18	AV	Н	34.17	7.47	26.36	33.46	54.00	20.54	
9648	33.08	PK	V	36.06	8.81	26.06	51.89	74.00	22.11	
9648	18.19	AV	V	36.06	8.81	26.06	37.00	54.00	17.00	
3220.44	32.74	PK	V	27.91	6.49	27.48	39.66	74.00	34.34	
3220.44	18.66	AV	V	27.91	6.49	27.48	25.58	54.00	28.42	
178.41	48.2	OP	Н	11.38	1.61	21.45	39.74	43.50	3.76*	
170.71	70.2	Q1		dle Chann			37.14	75.50	3.70	
2437	67.13	PK	Н	25.74	4.41	0.00	97.27	N/A	N/A	
2437	61.93	AV	Н	25.74	4.41	0.00	92.07	N/A	N/A	
2437	62.4	PK	V	25.74	4.41	0.00	92.54	N/A	N/A	
2437	57.44	AV	V	25.74	4.41	0.00	87.58	N/A	N/A	
4874	36.12	PK	H	30.77	6.09	27.26	45.72	74.00	28.28	
4874	30.58	AV	Н	30.77	6.09	27.26	40.18	54.00	13.82	
7311	32.18	PK	H	34.35	7.51	26.51	47.53	74.00	26.47	
7311	18.05	AV	H	34.35	7.51	26.51	33.40	54.00	20.60	
9748	32.23	PK	V	36.30	8.83	25.68	51.68	74.00	22.32	
9748	18.29	AV	V	36.30	8.83	25.68	37.74	54.00	16.26	
1623.58	32.55	PK	V	23.85	3.31	26.91	32.80	74.00	41.20	
1623.58	18.43	AV	V	23.85	3.31	26.91	18.68	54.00	35.32	
3220.59	32.46	PK	V	27.91	6.48	27.48	39.37	74.00	34.63	
3220.59	18.32	AV	V	27.91	6.48	27.48	25.23	54.00	28.77	
178.55	48	QP	H	11.37	1.61	21.45	39.53	43.50	3.97*	
176.33	40	Qr		gh Channe			39.33	43.30	3.91	
2462	66.6	PK	H	25.80	4.43	0.00	96.83	N/A	N/A	
2462	61.31	AV	Н	25.80	4.43	0.00	91.54	N/A	N/A	
2462	61.11	PK	V	25.80	4.43	0.00	91.34	N/A	N/A	
2462	55.93	AV	V	25.80	4.43	0.00	86.16	N/A	N/A	
2483.5	27.66	PK	Н	25.86	4.49	0.00	58.01	74.00	15.99	
2483.5	13.54	AV	Н	25.86	4.49	0.00	43.89	54.00	10.11	
4924	38.92	PK	Н	30.90	5.97	27.27	48.52	74.00	25.48	
4924	33.23	AV	Н	30.90	5.97	27.27	42.83	54.00	11.17	
7386	32.66	PK	Н	34.53	7.55	26.66	48.08	74.00	25.92	
7386	18.23	AV	Н	34.53	7.55	26.66	33.65	54.00	20.35	
9848	32.51	PK	V	36.54	8.85	25.49	52.41	74.00	21.59	
9848	18.31	AV	V	36.54	8.85	25.49	38.21	54.00	15.79	
3220.63	32.44	PK	V	27.91	6.48	27.48	39.35	74.00	34.65	
3220.63	18.73	AV	V	27.91	6.48	27.48	25.64	54.00	28.36	
178.92	47.9	QP	H	11.37	1.61	21.45	39.43	43.50	4.07*	
1,0.72				/	1.01		57.15			

 $[*]Within\ measurement\ uncertainty!$

FCC Part 15.247 Page 20 of 64

802 11g Mode

802.11g N	802.11g Mode										
_	R	eceiver	Rx A	Antenna	Cable	Amplifier	Corrected	FCC 1	5.247		
Frequency	Reading	Detector	Polar	Factor	loss	Gain	Amplitude	Limit	Margin		
(MHz)	(dBµV)	(PK/QP/AV)	(H/V)	(dB)	(dB)	(dB)	(dBµV/m)	(dBµV/m)	(dB)		
Low Channel: 2412 MHz											
2412	69.36	PK	Н	25.67	4.42	0.00	99.45	N/A	N/A		
2412	54.7	AV	Н	25.67	4.42	0.00	84.79	N/A N/A	N/A		
2412	63.79	PK	V	25.67	4.42	0.00	93.88	N/A	N/A		
2412	50.11	AV	V	25.67	4.42	0.00	80.20	N/A N/A	N/A		
2390	27.87	PK	H	25.61	4.39	0.00	57.87	74.00	16.13		
2390	14.49	AV	Н	25.61	4.39	0.00	44.49	54.00	9.51		
4824	37.35	PK	Н	30.64	6.03	27.26	46.76	74.00	27.24		
4824	21.21	AV	Н	30.64	6.03	27.26	30.62	54.00	23.38		
7236	32.19	PK	Н	34.17	7.47	26.36	47.47	74.00	26.53		
7236	18.12	AV	Н	34.17	7.47	26.36	33.40	54.00	20.60		
9648	32.12	PK	V	36.06	8.81	26.06	50.93	74.00	23.07		
9648	18.21	AV	V	36.06	8.81	26.06	37.02	54.00	16.98		
3220.44	32.47	PK	V	27.91	6.49	27.48	39.39	74.00	34.61		
3220.44	18.76	AV	V	27.91	6.49	27.48	25.68	54.00	28.32		
178.41	48.4	QP	Н	11.38	1.61	21.45	39.94	43.50	3.56*		
			M	iddle Chann	el: 2437 l	МНz					
2437	68.77	PK	Н	25.74	4.41	0.00	98.91	N/A	N/A		
2437	54.34	AV	Н	25.74	4.41	0.00	84.48	N/A	N/A		
2437	62.49	PK	V	25.74	4.41	0.00	92.63	N/A	N/A		
2437	48.47	AV	V	25.74	4.41	0.00	78.61	N/A	N/A		
4874	37.65	PK	Н	30.77	6.09	27.26	47.25	74.00	26.75		
4874	21.34	AV	H	30.77	6.09	27.26	30.94	54.00	23.06		
7311	32.29	PK	Н	34.35	7.51	26.51	47.64	74.00	26.36		
7311 9748	18.17 32.2	AV PK	H V	34.35	7.51	26.51 25.68	33.52 51.65	54.00	20.48		
9748	18.23	AV	V	36.30 36.30	8.83 8.83	25.68	37.68	74.00 54.00	16.32		
1623.58	32.69	PK	V	23.85	3.31	26.91	32.94	74.00	41.06		
1623.58	18.51	AV	V	23.85	3.31	26.91	18.76	54.00	35.24		
3220.59	32.56	PK	V	27.91	6.48	27.48	39.47	74.00	34.53		
3220.59	18.47	AV	V	27.91	6.48	27.48	25.38	54.00	28.62		
178.55	48.1	QP	H	11.37	1.61	21.45	39.63	43.50	3.87*		
				ligh Channe			-				
2462	68.46	PK	Н	25.80	4.43	0.00	98.69	N/A	N/A		
2462	54.28	AV	Н	25.80	4.43	0.00	84.51	N/A	N/A		
2462	61	PK	V	25.80	4.43	0.00	91.23	N/A	N/A		
2462	47.07	AV	V	25.80	4.43	0.00	77.30	N/A	N/A		
2483.5	29.75	PK	Н	25.86	4.49	0.00	60.10	74.00	13.90		
2483.5	14.47	AV	Н	25.86	4.49	0.00	44.82	54.00	9.18		
4924	38.89	PK	H	30.90	5.97	27.27	48.49	74.00	25.51		
4924	22.77	AV	H	30.90	5.97	27.27	32.37	54.00	21.63		
7386	32.23	PK	Н	34.53	7.55	26.66	47.65	74.00	26.35		
7386	18.06	AV	H	34.53	7.55	26.66 25.49	33.48	54.00	20.52		
9848 9848	32.35 18.11	PK AV	V	36.54 36.54	8.85 8.85	25.49	52.25 38.01	74.00 54.00	21.75 15.99		
3220.63	32.52	PK	V	27.91	6.48	27.48	39.43	74.00	34.57		
3220.63	18.81	AV	V	27.91	6.48	27.48	25.72	54.00	28.28		
178.92	47.8	QP	H	11.37	1.61	21.45	39.33	43.50	4.17*		
170.72	17.0	Υ1		11.01	1.01	21.10	27.22	15.50	1.1/		

FCC Part 15.247 Page 21 of 64

^{*}Within measurement uncertainty!

802.11 n20 Mode

E	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	5.247	
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBμV/m)	Limit (dBµV/m)	Margin (dB)	
Low Channel: 2412 MHz										
2412	68.34	PK	Н	25.67	4.42	0.00	98.43	N/A	N/A	
2412	52.36	AV	Н	25.67	4.42	0.00	82.45	N/A	N/A	
2412	62.51	PK	V	25.67	4.42	0.00	92.60	N/A	N/A	
2412	49.43	AV	V	25.67	4.42	0.00	79.52	N/A	N/A	
2390	29.68	PK	Н	25.61	4.39	0.00	59.68	74.00	14.32	
2390	14.35	AV	Н	25.61	4.39	0.00	44.35	54.00	9.65	
4824	35.37	PK	Н	30.64	6.03	27.26	44.78	74.00	29.22	
4824	19.86	AV	Н	30.64	6.03	27.26	29.27	54.00	24.73	
7236	32.69	PK	Н	34.17	7.47	26.36	47.97	74.00	26.03	
7236	18.06	AV	Н	34.17	7.47	26.36	33.34	54.00	20.66	
9648	33.26	PK	V	36.06	8.81	26.06	52.07	74.00	21.93	
9648	18.25	AV	V	36.06	8.81	26.06	37.06	54.00	16.94	
3220.44	32.98	PK	V	27.91	6.49	27.48	39.90	74.00	34.10	
3220.44	18.85	AV	V	27.91	6.49	27.48	25.77	54.00	28.23	
178.41	47.9	QP	Н	11.38	1.61	21.45	39.44	43.50	4.06*	
			Mi	ddle Chan	nel: 2437	MHz				
2437	68.37	PK	Н	25.74	4.41	0.00	98.51	N/A	N/A	
2437	52.38	AV	Н	25.74	4.41	0.00	82.52	N/A	N/A	
2437	62.15	PK	V	25.74	4.41	0.00	92.29	N/A	N/A	
2437	49.36	AV	V	25.74	4.41	0.00	79.50	N/A	N/A	
4874	39.38	PK	Н	30.77	6.09	27.26	48.98	74.00	25.02	
4874	21.76	AV	Н	30.77	6.09	27.26	31.36	54.00	22.64	
7311	35.16	PK	Н	34.35	7.51	26.51	50.51	74.00	23.49	
7311	19.51	AV	Н	34.35	7.51	26.51	34.86	54.00	19.14	
9748	33.14	PK	V	36.30	8.83	25.68	52.59	74.00	21.41	
9748	18.19	AV	V	36.30	8.83	25.68	37.64	54.00	16.36	
1623.58	33.22	PK	V	23.85	3.31	26.91	33.47	74.00	40.53	
1623.58	18.42	AV	V	23.85	3.31	26.91	18.67	54.00	35.33	
3220.59	32.75	PK	V	27.91	6.48	27.48	39.66	74.00	34.34	
3220.59	19.32	AV	V	27.91	6.48	27.48	26.23	54.00	27.77	
178.55	48.1	QP	Н	11.37	1.61	21.45	39.63	43.50	3.87*	
				igh Chann						
2462	67.95	PK	Н	25.80	4.43	0.00	98.18	N/A	N/A	
2462	52.6	AV	Н	25.80	4.43	0.00	82.83	N/A	N/A	
2462	62.63	PK	V	25.80	4.43	0.00	92.86	N/A	N/A	
2462	49.65	AV	V	25.80	4.43	0.00	79.88	N/A	N/A	
2483.5	29.6	PK	H	25.86	4.49	0.00	59.95	74.00	14.05	
2483.5	14.42	AV	H	25.86	4.49	0.00	44.77	54.00	9.23	
4924	35.59	PK	H	30.90	5.97	27.27	45.19	74.00	28.81	
4924	19.76	AV	H	30.90	5.97	27.27	29.36	54.00	24.64	
7386	33.01	PK	H	34.53	7.55	26.66	48.43	74.00	25.57	
7386	17.89	AV	Н	34.53	7.55	26.66	33.31	54.00	20.69	
9848	33.14	PK	V	36.54	8.85	25.49	53.04	74.00	20.96	
9848	17.95	AV	V	36.54	8.85	25.49	37.85	54.00	16.15	
3220.63 3220.63	32.76	PK AV	V	27.91	6.48	27.48	39.67	74.00 54.00	34.33 28.59	
	18.5			27.91	6.48	27.48	25.41			
178.92	47.6	QP	Н	11.37	1.61	21.45	39.13	43.50	4.37*	

FCC Part 15.247 Page 22 of 64

^{*}Within measurement uncertainty!

802.11 n40 Mode

E	Re	eceiver	Rx A	ntenna	Cable	Amplifier	Corrected	FCC 1	15.247		
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB/m)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)		
Low Channel: 2422 MHz											
2422	68.51	PK	Н	25.70	4.41	0.00	98.62	N/A	N/A		
2422	53.68	AV	Н	25.70	4.41	0.00	83.79	N/A	N/A		
2422	63.77	PK	V	25.70	4.41	0.00	93.88	N/A	N/A		
2422	50.51	AV	V	25.70	4.41	0.00	80.62	N/A	N/A		
2390	28.33	PK	Н	25.61	4.39	0.00	58.33	74.00	15.67		
2390	14.11	AV	Н	25.61	4.39	0.00	44.11	54.00	9.89		
4844	37.65	PK	Н	30.69	6.08	27.26	47.16	74.00	26.84		
4844	20.85	AV	Н	30.69	6.08	27.26	30.36	54.00	23.64		
7266	32.08	PK	Н	34.24	7.48	26.42	47.38	74.00	26.62		
7266	17.78	AV	Н	34.24	7.48	26.42	33.08	54.00	20.92		
9688	32.43	PK	V	36.15	8.82	25.91	51.49	74.00	22.51		
9688	18.07	AV	V	36.15	8.82	25.91	37.13	54.00	16.87		
3220.44	32.37	PK	V	27.91	6.49	27.48	39.29	74.00	34.71		
3220.44	18.47	AV	V	27.91	6.49	27.48	25.39	54.00	28.61		
178.41	48.3	QP	Н	11.38	1.61	21.45	39.84	43.50	3.66*		
	•		Mi	ddle Chan							
2437	68.31	PK	Н	25.74	4.41	0.00	98.45	N/A	N/A		
2437	53.63	AV	Н	25.74	4.41	0.00	83.77	N/A	N/A		
2437	63.85	PK	V	25.74	4.41	0.00	93.99	N/A	N/A		
2437	50.55	AV	V	25.74	4.41	0.00	80.69	N/A	N/A		
4874	38.11	PK	Н	30.77	6.09	27.26	47.71	74.00	26.29		
4874	21.11	AV	Н	30.77	6.09	27.26	30.71	54.00	23.29		
7311	37.19	PK	Н	34.35	7.51	26.51	52.54	74.00	21.46		
7311	21.01	AV	Н	34.35	7.51	26.51	36.36	54.00	17.64		
9748	32.06	PK	V	36.30	8.83	25.68	51.51	74.00	22.49		
9748	18.51	AV	V	36.30	8.83	25.68	37.96	54.00	16.04		
1623.58	32.59	PK	V	23.85	3.31	26.91	32.84	74.00	41.16		
1623.58	17.92	AV	V	23.85	3.31	26.91	18.17	54.00	35.83		
3220.59	32.12	PK	V	27.91	6.48	27.48	39.03	74.00	34.97		
3220.59	18.59	AV	V	27.91	6.48	27.48	25.50	54.00	28.50		
178.55	48.5	QP	Н	11.37	1.61	21.45	40.03	43.50	3.47*		
			Н	igh Chann	el: 2452	MHz					
2452	69.03	PK	Н	25.78	4.41	0.00	99.21	N/A	N/A		
2452	54.19	AV	Н	25.78	4.41	0.00	84.37	N/A	N/A		
2452	63.8	PK	V	25.78	4.41	0.00	93.98	N/A	N/A		
2452	50.6	AV	V	25.78	4.41	0.00	80.78	N/A	N/A		
2483.5	28.02	PK	Н	25.86	4.49	0.00	58.37	74.00	15.63		
2483.5	14.17	AV	Н	25.86	4.49	0.00	44.52	54.00	9.48		
4904	37.16	PK	Н	30.85	6.06	27.27	46.80	74.00	27.20		
4904	20.88	AV	Н	30.85	6.06	27.27	30.52	54.00	23.48		
7356	31.97	PK	H	34.45	7.53	26.60	47.35	74.00	26.65		
7356	18.2	AV	Н	34.45	7.53	26.60	33.58	54.00	20.42		
9808	32.1	PK	V	36.44	8.84	25.48	51.90	74.00	22.10		
9808	18.06	AV	V	36.44	8.84	25.48	37.86	54.00	16.14		
3220.63	32.87	PK	V	27.91	6.48	27.48	39.78	74.00	34.22		
3220.63	19.07	AV	V	27.91	6.48	27.48	25.98	54.00	28.02		
178.92	48.8	QP	Н	11.37	1.61	21.45	40.33	43.50	3.17*		


FCC Part 15.247 Page 23 of 64

^{*}Within measurement uncertainty!

Conducted Spurious Emissions at Antenna Port


Report No.: R2DG131127001-00B

802.11b Low Channel



Date: 18.NOV.2013 17:59:28

802.11b Middle Channel




Date: 18.NOV.2013 18:00:06

FCC Part 15.247 Page 24 of 64


802.11b High Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 18:00:48

802.11g Low Channel




Date: 18.NOV.2013 17:50:24

FCC Part 15.247 Page 25 of 64


802.11g Middle Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:51:03

802.11g High Channel




Date: 18.NOV.2013 17:52:28

FCC Part 15.247 Page 26 of 64


802.11n20 Low Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 14:56:14

802.11n20 Middle Channel




Date: 13.JAN.2014 14:59:29

FCC Part 15.247 Page 27 of 64


802.11n20 High Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:01:10

802.11n40 Low Channel




Date: 13.JAN.2014 15:05:23

FCC Part 15.247 Page 28 of 64


802.11n40 Middle Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:07:17

802.11n40 High Channel



Date: 13.JAN.2014 15:08:48

FCC Part 15.247 Page 29 of 64

FCC $\S15.247(a)$ (2) – 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Report No.: R2DG131127001-00B

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	18.7~26.4 °C
Relative Humidity:	30~51 %
ATM Pressure:	100.9~102.1 kPa

The testing was performed by Allen Qiao from 2013-11-18 to 2014-01-13.

Test Result: Pass.

Please refer to the following tables and plots.


FCC Part 15.247 Page 30 of 64

Test Mode	Channel	Frequency	6 dB Bandwidth	Limit
1 est Mode	Chamie	(MHz)	(MHz)	(kHz)
	Low	2412	10.14	>500
802.11b	Middle	2437	9.64	>500
	High	2462	9.59	>500
	Low	2412	16.43	>500
802.11g	Middle	2437	16.48	>500
	High	2462	16.48	>500
	Low	2412	17.73	>500
802.11n20	Middle	2437	17.68	>500
	High	2462	17.73	>500
	Low	2422	36.46	>500
802.11n40	Middle	2437	35.26	>500
	High	2452	35.26	>500

FCC Part 15.247 Page 31 of 64


802.11b Low Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:03:52

802.11b Middle Channel




Date: 18.NOV.2013 17:05:12

FCC Part 15.247 Page 32 of 64


802.11b High Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:07:38

802.11g Low Channel




Date: 18.NOV.2013 17:23:18

FCC Part 15.247 Page 33 of 64


802.11g Middle Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:24:39

802.11g High Channel




Date: 18.NOV.2013 17:26:01

FCC Part 15.247 Page 34 of 64


802.11n20 Low Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 14:55:15

802.11n20 Middle Channel




Date: 13.JAN.2014 14:58:39

FCC Part 15.247 Page 35 of 64


802.11n20 High Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:00:12

802.11n40 Low Channel




Date: 13.JAN.2014 15:03:26

FCC Part 15.247 Page 36 of 64


802.11n40 Middle Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:06:07

802.11n40 High Channel



Date: 13.JAN.2014 15:07:48

FCC Part 15.247 Page 37 of 64

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Report No.: R2DG131127001-00B

Test Procedure

- 1. According to KDB 558074 D01 DTS Meas Guidance v03r01, place the EUT on a bench and set it in transmitting mode.
- 2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to a spectrum Analyzer.
- 3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

FCC Part 15.247 Page 38 of 64

. Test Data

Environmental Conditions

Temperature:	18.7~26.4 °C	
Relative Humidity:	30~51 %	
ATM Pressure:	100.9~102.1 kPa	

 $The \ testing \ was \ performed \ by \ Allen \ Qiao \ from \ 2013-11-18 \ to \ 2014-01-13.$

Test Mode: Transmitting

Test Mode	Channel	Frequency Conducted Output Power		Limit	Result	
		(MHz)	(dBm)	(dBm)		
	Low	2412	9.28	30	PASS	
802.11b	Middle	2437	9.57	30	PASS	
	High	2462	9.55	30	PASS	
	Low	2412	9.23	30	PASS	
802.11g	Middle	2437	9.34	30	PASS	
	High	2462	9.14	30	PASS	
	Low	2412	9.18	30	PASS	
802.11n20	Middle	2437	8.97	30	PASS	
	High	2462	9.28	30	PASS	
802.11n40	Low	2422	9.18	30	PASS	
	Middle	2437	9.09	30	PASS	
	High	2452	9.12	30	PASS	


Report No.: R2DG131127001-00B

Please refer to the following plots

FCC Part 15.247 Page 39 of 64


802.11b 20dB OBW, Low Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:04:06

802.11b RF Output Power, Low Channel




Date: 18.NOV.2013 17:04:16

FCC Part 15.247 Page 40 of 64


802.11b 20dB OBW, Middle Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:05:26

802.11b RF Output Power, Middle Channel




Date: 18.NOV.2013 17:05:36

FCC Part 15.247 Page 41 of 64


802.11b 20dB OBW, High Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:07:52

802.11b RF Output Power, High Channel




Date: 18.NOV.2013 17:08:03

FCC Part 15.247 Page 42 of 64


802.11g 20dB OBW, Low Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:23:32

802.11g RF Output Power, Low Channel




Date: 18.NOV.2013 17:33:41

FCC Part 15.247 Page 43 of 64


802.11g 20dB OBW, Middle Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:24:53

802.11g RF Output Power, Middle Channel




Date: 18.NOV.2013 17:25:11

FCC Part 15.247 Page 44 of 64


802.11g RF 20dB OBW, High Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:26:15

802.11g RF Output Power, High Channel




Date: 18.NOV.2013 17:26:31

FCC Part 15.247 Page 45 of 64


802.11n20 20dB OBW, Low Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 14:55:28

802.11n20 RF Output Power, Low Channel




Date: 13.JAN.2014 14:55:48

FCC Part 15.247 Page 46 of 64


802.11n20 20dB OBW, Middle Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 14:58:53

802.11n20 RF Output Power, Middle Channel




Date: 13.JAN.2014 14:59:03

FCC Part 15.247 Page 47 of 64


802.11n20 RF 20dB OBW, High Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:00:26

802.11n20 RF Output Power, High Channel




Date: 13.JAN.2014 15:15:58

FCC Part 15.247 Page 48 of 64

802.11n40 20dB OBW, Low Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:03:39

802.11n40 RF Output Power, Low Channel




Date: 13.JAN.2014 15:04:44

FCC Part 15.247 Page 49 of 64

802.11n40 20dB OBW, Middle Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:06:21

802.11n40 RF Output Power, Middle Channel




Date: 13.JAN.2014 15:06:38

FCC Part 15.247 Page 50 of 64


802.11n40 RF 20dB OBW, High Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:08:02

802.11n40 RF Output Power, High Channel



Date: 13.JAN.2014 15:11:38

FCC Part 15.247 Page 51 of 64

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Report No.: R2DG131127001-00B

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	18.7~26.4 °C	
Relative Humidity:	30~51 %	
ATM Pressure:	100.9~102.1 kPa	

The testing was performed by Allen Qiao from 2013-11-18 to 2014-01-13.


Test Result: Compliance

Please refer to following table and plots.

FCC Part 15.247 Page 52 of 64


802.11b: Band Edge, Left Side

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:04:37

802.11b: Band Edge, Right Side




Date: 18.NOV.2013 17:08:24

FCC Part 15.247 Page 53 of 64


802.11g: Band Edge, Left Side

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:24:09

802.11g: Band Edge, Right Side




Date: 18.NOV.2013 17:26:56

FCC Part 15.247 Page 54 of 64


802.11n20 Band Edge, Left Side

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 14:56:26

802.11n20 Band Edge, Right Side




Date: 13.JAN.2014 15:01:22

FCC Part 15.247 Page 55 of 64


802.11n40 Band Edge, Left Side

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:05:35

802.11n40 Band Edge, Right Side



Date: 13.JAN.2014 15:09:00

FCC Part 15.247 Page 56 of 64

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Report No.: R2DG131127001-00B

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS bandwidth.
- 4. Use the peak marker function to determine the maximum amplitude level.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum analyzer	FSP 38	100478	2013-6-16	2014-6-15

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	18.7~26.4 °C	
Relative Humidity:	30~51 %	
ATM Pressure:	100.9~102.1 kPa	

The testing was performed by Allen Qiao from 2013-11-18 to 2014-01-13.

FCC Part 15.247 Page 57 of 64

Test Mode: Transmitting

Test Result: Pass

Total Mode	Channal	PSD	Limit	D 14
Test Mode	Channel	(dBm/3kHz)	(dBm/3kHz)	Result
	Low	-16.91	8	PASS
802.11b	Middle	-16.37	8	PASS
	High	-16.79	8	PASS
802.11g	Low	-20.36	8	PASS
	Middle	-20.33	8	PASS
	High	-20.06	8	PASS
802.11n20	Low	-21.19	8	PASS
	Middle	-20.50	8	PASS
	High	-21.08	8	PASS
802.11n40	Low	-20.52	8	PASS
	Middle	-20.01	8	PASS
	High	-20.51	8	PASS


Report No.: R2DG131127001-00B

Please refer to the following plots

FCC Part 15.247 Page 58 of 64


Power Spectral Density, 802.11b Low Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:04:25

Power Spectral Density, 802.11b Middle Channel




Date: 18.NOV.2013 17:05:45

FCC Part 15.247 Page 59 of 64


Power Spectral Density, 802.11b High Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:08:12

Power Spectral Density, 802.11g Low Channel




Date: 18.NOV.2013 17:36:00

FCC Part 15.247 Page 60 of 64


Power Spectral Density, 802.11g Middle Channel

Report No.: R2DG131127001-00B



Date: 18.NOV.2013 17:25:24

Power Spectral Density, 802.11g High Channel




Date: 18.NOV.2013 17:26:44

FCC Part 15.247 Page 61 of 64


Power Spectral Density, 802.11n20 Low Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 14:56:02

Power Spectral Density, 802.11n20 Middle Channel




Date: 13.JAN.2014 14:59:17

FCC Part 15.247 Page 62 of 64


Power Spectral Density, 802.11n20 High Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:17:11

Power Spectral Density, 802.11n40 Low Channel




Date: 13.JAN.2014 15:05:10

FCC Part 15.247 Page 63 of 64


Power Spectral Density, 802.11n40 Middle Channel

Report No.: R2DG131127001-00B



Date: 13.JAN.2014 15:07:04

Power Spectral Density, 802.11n40 High Channel



Date: 13.JAN.2014 15:12:56

***** END OF REPORT *****

FCC Part 15.247 Page 64 of 64