

# FCC TEST REPORT

FCC 47 CFR Part 15C  
Industry Canada RSS-210

Digital transmission systems operating within the 902 – 928MHz band

Report Reference No. .... : G0M-1110-1448-TFC247D-V01

Testing Laboratory ..... : Eurofins Product Service GmbH

Address ..... : Storkower Str. 38c  
15526 Reichenwalde  
Germany

Accreditation ..... : FCC Filed Test Laboratory, Reg.-No.: 96970  
A2LA Accredited Testing Laboratory, Certificate No.: 1983.01



Applicant's name ..... : Steute Schaltgeräte GmbH & Co KG

Address ..... : Brückenstr. 91  
32584 Löhne  
GERMANY

## Test specification:

Standard..... : 47 CFR Part 15C  
RSS-210, Issue 8, 2010-12  
RSS-Gen, Issue 3, 2010-12  
ANSI C63.4:2009

## Equipment under test (EUT):

Product description Transceiver Module

Model No. RFRX SW 915-4W

Hardware version E194K02\_02

Firmware / Software version V2.1

FCC-ID: XK5-RFRXSW915 IC: 5158A-RFRXSW915

Test result Passed

Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany

**Possible test case verdicts:**

- neither assessed nor tested ..... : N/N
- required by standard but not appl. to test object ..... : N/A
- required by standard but not tested ..... : N/T
- not required by standard for the test object ..... : N/R
- test object does meet the requirement ..... : P (Pass)
- test object does not meet the requirement ..... : F (Fail)

**Testing:**

Date of receipt of test item ..... : 2011-11-02

Date (s) of performance of tests ..... : 2011-11-02 - 2011-11-03

Compiled by ..... : Christian Weber

Tested by (+ signature) ..... : Wilfried Treffke

Approved by (+ signature) ..... : Jens Zimmermann

Date of issue ..... : 2012-04-20

Total number of pages ..... : 49


**General remarks:**

**The test results presented in this report relate only to the object tested.**

**The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.**

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

**Additional comments:**



## REPORT INDEX

<b>1</b>	<b>EQUIPMENT (TEST ITEM) DESCRIPTION:</b>	<b>4</b>
1.1	Equipment photos	5
1.2	Supporting Equipment Used During Testing:	7
1.3	Test Modes:	8
1.4	Test Equipment Used During Testing	9
1.5	Sample emission level calculation	10
<b>2</b>	<b>RESULT SUMMARY</b>	<b>11</b>
<b>3</b>	<b>TEST CONDITIONS AND RESULTS</b>	<b>12</b>
3.1	Test Conditions and Results – Occupied Bandwidth	12
3.2	Test Conditions and Results – 6dB Bandwidth	14
3.3	Test Conditions and Results – Maximum peak conducted power	16
3.4	Test Conditions and Results – Power spectral density	17
3.5	Test Conditions and Results – AC power line conducted emissions	18
3.6	Test Conditions and Results – Band edge compliance	21
3.7	Test Conditions and Results – Conducted spurious emissions	24
3.8	Test Conditions and Results – Transmitter radiated emissions	27
3.9	Test Conditions and Results – Receiver radiated emissions	30
ANNEX A	Transmitter radiated spurious emissions	32
ANNEX B	Receiver radiated spurious emissions	43

## 1 Equipment (Test item) Description:


Description	Transceiver Module	
Model	RFRX SW 915-4W	
Serial number	None	
Hardware version	E194K02_02	
Software / Firmware version	V2.1	
FCC-ID	XK5-RFRXSW915	
IC	5158A-RFRXSW915	
Equipment type	Radio module	
Radio type	Transceiver	
Radio technology	custom	
Operating frequency range	915MHz	
Assigned frequency band	902 - 928MHz	
Number of channels	1	
Main test frequencies	$F_{MID}$	915MHz
Spreading	None	
Modulations	FSK	
Number of channels	1 Channel	
Channel spacing	None	
Number of antennas	1	
Antenna	Type	external dedicated
	Model	FME-f magent foot antenna, MC0114037
	Manufacturer	MC Technologies GmbH
	Gain	+5.0dBi
Manufacturer	IK ELEKTRONIK GmbH Friedrichsgrüner Straße 11-13 08269 Hammerbrücke GERMANY	
Power supply	$V_{NOM}$	3.3VDC
	$V_{MIN}$	2.80VDC
	$V_{MIN}$	3.80VDC
AC/DC-Adaptor	Model	N/A
	Vendor	N/A
	Input	N/A
	Output	N/A

## 1.1 Equipment photos






**EUT WITH SHIELDING**



**EUT WITHOUT SHIELDING**



## 1.2 Supporting Equipment Used During Testing:

Product Type*	Device	Manufacturer	Model No.	Comments
AE	Multi-Mode PSU	Thurlby-Thandar Instruments Ltd.	EX752M	
<p><b>*Note:</b> Use the following abbreviations:</p> <p>AE : Auxiliary/Associated Equipment, or</p> <p>SIM : Simulator (Not Subjected to Test)</p> <p>CABL : Connecting cables</p>				

### 1.3 Test Modes:

Mode #	Description	
Single	General conditions:	EUT powered by laboratory power supply
	Radio conditions:	Mode = standalone transmit Spreading = None Modulation = FSK Duty cycle = 10% Power level = Maximum
Receive	General conditions:	EUT powered by laboratory power supply
	Radio conditions:	Mode = standalone receive Spreading = None Modulation = FSK
AC-Powerline	General conditions:	EUT powered by laboratory power supply
	Radio conditions:	Mode = standalone transmit Spreading = None Modulation = FSK Duty cycle = 10% Power level = Maximum



#### 1.4 Test Equipment Used During Testing

Occupied Bandwidth					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	Inv. No. 0496	Aug 10	Aug 12

6dB Bandwidth					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	Inv. No. 0496	Aug 10	Aug 12

Maximum peak conducted power					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	Inv. No. 0496	Aug 10	Aug 12

Power spectral density					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	Inv. No. 0496	Aug 10	Aug 12

Band edge compliance					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	Inv. No. 0496	Aug 10	Aug 12

Conducted spurious emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Spectrum Analyzer	R&S	FSP 30	Inv. No. 0496	Aug 10	Aug 12

Radiated spurious emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
Semi-anechoic chamber	Frankonia	AC 5	Inv. No. 0583		
Spectrum Analyzer	R&S	FSIQ26	Inv. No. 0413	Apr. 11	Apr. 12
Biconical Antenna	R&S	HK 116	Inv. No. 0012	Jan 10	Jan 13
LPD Antenna	R&S	HL 223	Inv. No. 0295	Feb 11	Feb 13
LPD Antenna	R&S	HL 025	Inv. No. 0512	Feb 10	Feb 13

AC powerline conducted emissions					
Description	Manufacturer	Model	Identifier	Cal. Date	Cal. Due
AMN	R&S	ESH2-Z5	Inv. No. 0288	Sep 10	Sep 12
AMN	R&S	ESH3-Z5	Inv. No. 0040	Nov 10	Nov 12
EMI Test Receiver	R&S	ESCS 30	Inv. No. 0474	Jun 11	Jun 12

Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany

## 1.5 Sample emission level calculation

The following is a description of terms and a sample calculation, as appears in the radiated emissions data table. The numbers used in the calculation are for example only. There is no direct correlation to the specific data taken for the product described in this document:

Reading:

This is the reading obtained on the spectrum analyzer in dB $\mu$ V. Any external preamplifiers used are taken into account through internal analyzer settings.

A.F.:

This is the antenna factor for the receiving antenna. It is a conversion factor, which converts electric fields strengths to voltages, which can be measured directly on the spectrum analyzer. It is treated as a loss in dB. Cable losses have been included with the A.F. to simplify the calculations. The antenna factor is used in calculations as follows:

$$\text{Reading on Analyzer (dB}\mu\text{V)} + \text{A.F. (dB)} = \text{Net field strength (dB}\mu\text{V/m)}$$

Net:

This is the net field strength measurement (as shown above).

Limit:

This is the FCC Class B radiated emission limit (in units of dB $\mu$ V/m). The FCC limits are given in units of  $\mu$ V/m. The following formula is used to convert the units of  $\mu$ V/m to dB $\mu$ V/m:

$$\text{Limit (dB}\mu\text{V/m)} = 20 \cdot \log (\mu\text{V/m})$$

Margin:

This is the margin of compliance below the FCC limit. The units are given in dB. A negative margin indicates the emission was below the limit. A positive margin indicates that the emission exceeds the limit.

Example only:

$$\begin{array}{rclcl} \text{Reading} & + & \text{AF} & = & \text{Net Reading} & : & \text{Net reading - FCC limit} & = & \text{Margin} \\ 21.5 \text{ dB}\mu\text{V} & + & 26 \text{ dB} & = & 47.5 \text{ dB}\mu\text{V/m} & : & 47.5 \text{ dB}\mu\text{V/m} - 57.0 \text{ dB}\mu\text{V/m} & = & -9.5 \text{ dB} \end{array}$$

## 2 Result Summary

FCC 47 CFR Part 15C, IC RSS-210				
Product Specific Standard Section	Requirement – Test	Reference Method	Result	Remarks
RSS-Gen 4.6.1	Occupied Bandwidth	RSS-Gen 4.6.1	N/A	Informational only
FCC § 15.247(a)(2) IC RSS-210 § A8.2	6dB Bandwidth	KDB Publication No. 558074	PASS	
FCC § 15.247(b)(3) IC RSS-210 § A8.4	Maximum peak conducted power	KDB Publication No. 558074	PASS	
FCC § 15.247(e) IC RSS-210 § A8.2	Power spectral density	KDB Publication No. 558074	PASS	
47 CFR 15.207 RSS-Gen 7.2.4	AC power line conducted emissions	KDB Publication No. 558074 / ANSI C63.4	PASS	
FCC § 15.247(d) IC RSS-210 § A8.5	Band edge compliance	KDB Publication No. 558074	PASS	
FCC § 15.247(d) IC RSS-210 § A8.5	Conducted spurious emissions	KDB Publication No. 558074	PASS	
FCC § 15.247(d) FCC § 15.209 IC RSS-210 A8.5 IC RSS-Gen 4.9 IC RSS-Gen 7.2.5	Transmitter radiated spurious emissions	KDB Publication No. 558074 / ANSI C 63.4	PASS	
IC RSS-Gen 4.10 IC RSS-Gen 6.1	Receiver radiated spurious emissions	ANSI C 63.4	PASS	
<b>Remarks:</b> Testing has been performed with the strongest antenna listed above (antenna 3).				

### 3 Test Conditions and Results

#### 3.1 Test Conditions and Results – Occupied Bandwidth

Occupied Bandwidth acc. IC RSS-Gen			Verdict: PASS
Test according to measurement reference		Reference Method	
		RSS-Gen 4.6.1	
Test frequency range		Tested frequencies	
		F <sub>MID</sub>	
EUT test mode		Single	
Limits			
None (Informational only)			
Test setup			
<div><div>Spectrum Analyzer</div><div>EUT</div></div>			
Test procedure			
<div>1. EUT set to test mode (Communication tester is used if needed)</div> <div>2. Span set to at least twice the emission spectrum</div> <div>3. Resolution bandwidth set to 1% of span</div> <div>4. Occupied Bandwidth (99%) measurement with spectrum analyzer built in measurement function</div>			
Test results			
Channel	Frequency [MHz]	Occupied Bandwidth [kHz]	
F <sub>MID</sub>	915	546.796	
Comments:			


# Occupied Bandwidth - F<sub>MID</sub>

## RSS Gen Occupied Bandwidth

EUT	Transceiver Module
Model	RFRX SW915-4W
Approval Holder	Steute Schaltgeräte GmbH / Ord.: G0M-1110-1448
Temperature / Voltage	25°C, V <sub>nom</sub>
Test Site / Operator	Eurofins Product Service GmbH, Mr. Treffke
Test Specification	4.4.1 Occupied Bandwidth
Comment 1	Channel.: 915 MHz
Comment 2	A spectrum analyzer with an integrated 99% power bandwidth function is used
Comment 3	pass



\* RBW 30 kHz      Marker 1 [T1]  
 \* VBW 100 kHz      7.49 dBm  
 Ref 30 dBm      Att 50 dB      SWT 5 ms      914.796000000 MHz



Comment: Occupied bandwidth: 546 KHz  
 Date: 3.NOV.2011 13:30:49

Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

### 3.2 Test Conditions and Results – 6dB Bandwidth

20dB Bandwidth acc. FCC 15.247 / IC RSS-210				Verdict: PASS
EUT requirement rule parts and clause		Reference		
		FCC 15.247(a)(2) / IC RSS-210 A8.2		
Test according to measurement reference		Reference Method		
		FCC KDB Publication No. 558074		
Test frequency range		Tested frequencies		
		F <sub>MID</sub>		
EUT test mode		Single		
Limits				
≥ 500kHz				
Test setup				
<div><div>Spectrum Analyzer</div><div>EUT</div></div>				
Test procedure				
<div>1. EUT set to test mode (Communication tester is used if needed)</div> <div>2. Span set to at least twice the emission spectrum</div> <div>3. Detector set to peak and max hold</div> <div>4. Envelope peak value of emission spectrum is selected</div> <div>5. Marker on envelope of spectrum is set to level of -6dB to the left of the peak</div> <div>6. Marker on envelope of spectrum is set to level of -6dB to the right of the peak</div> <div>7. 6dB Bandwidth is determined by marker frequency separation</div>				
Test results				
Channel	Frequency [MHz]	6dB Bandwidth [kHz]	Limit [kHz]	Result
F <sub>MID</sub>	915	549.600	≥ 500	PASS
Comments:				




**6dB Bandwidth - F<sub>MID</sub>**
**FCC part 15.247 (a)(2)  
Minimum 6 dB Bandwidth**

EUT	Transceiver Module
Model	RFRX SW915-4W
Approval Holder	Steute Schaltgeräte GmbH / Ord.: G0M-1110-1448
Temperature / Voltage	25°C, V <sub>nom</sub>
Test Site / Operator	Eurofins Product Service GmbH, Mr. Treffke
Test Specification	FCC part 15.247 (a)(2)
Comment 1	Minimum 6 dB Bandwidth
Comment 2	Channel : 915 MHz
Comment 3	pass



\*RBW 100 kHz Delta 1 [T1]  
 \*VBW 300 kHz -0.46 dB  
 Ref 20 dBm Att 50 dB SWT 2.5 ms 549.600000000 kHz



Comment: 6 dB bandwidth: 549.6 KHz > 500 KHz; verdict: PASS  
 Date: 3.NOV.2011 13:14:52

**Test Report No.: G0M-1110-1448-TFC247D-V01**

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

### 3.3 Test Conditions and Results – Maximum peak conducted power

Maximum peak conducted power acc. FCC 15.247 / IC RSS-210						Verdict: PASS	
EUT requirement rule parts and clause			Reference				
			FCC 15.247(b)(3) / IC RSS-210 A8.4				
Test according to measurement reference			Reference Method				
			FCC KDB Publication No. 558074				
Test frequency range			Tested frequencies				
			F <sub>MID</sub>				
EUT test mode			Single				
Measurement mode			Peak				
Maximum antenna gain			5dBi ⇒ Limit correction = 0dB				
Limits							
1W (30dBm)							
The conducted output power limit specified above is based on the use of antennas with directional gains that do not exceed 6dBi. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in the table, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.							
Test setup							
<div><div>Spectrum Analyzer</div><div>EUT</div></div>							
Test procedure							
<div>1. EUT set to test mode (Communication tester is used if needed)</div> <div>2. Center frequency set to test channel center frequency</div> <div>3. Span is set to be larger than the 6dB bandwidth and RBW is set to be at least the 6dB bandwidth</div> <div>4. Peak output power is determined from the maximum of the emission envelope</div>							
Test results							
Channel	Frequency [MHz]	Voltage	Peak power [dbm]	Peak power [W]	Limit [dBm]	Margin [dB]	Result
F <sub>MID</sub>	915	3.3VDC	8.07	0.006	30	-21.93	PASS
F <sub>MID</sub>	915	2.80VDC	8.08	0.006	30	-21.92	PASS
F <sub>MID</sub>	915	3.80VDC	8.07	0.006	30	-21.93	PASS
Comments:							

### 3.4 Test Conditions and Results – Power spectral density

Power spectral density acc. FCC 15.247 / IC RSS-210						Verdict: PASS	
EUT requirement rule parts and clause			Reference				
			FCC 15.247(e) / IC RSS-210 A8.2				
Test according to measurement reference			Reference Method				
			FCC KDB Publication No. 558074				
Test frequency range			Tested frequencies				
			F <sub>MID</sub>				
EUT test mode			Single				
Measurement mode			Peak				
Limits							
8dBm/3kHz							
Test setup							
<div><div>Spectrum Analyzer</div><div>EUT</div></div>							
Test procedure							
1. EUT set to test mode (Communication tester is used if needed) 2. Center frequency set to test channel center frequency 3. Span is set large enough to capture maximum emissions in passband, RBW is set to 3kHz 4. Peak power density is determined from peak emission of envelope							
Test results							
Channel	Frequency [MHz]	Voltage	Peak frequency [MHz]	Peak power density [dBm]	Limit [dBm/3kHz]	Margin [dB]	Result
F <sub>MID</sub>	915	3.3VDC	915.132	4.4	8.0	-03.60	PASS
Comments:							

### 3.5 Test Conditions and Results – AC power line conducted emissions

Power line conducted emissions acc. FCC 47 CFR 15.207 / IC RSS-Gen				Verdict: PASS	
Test according referenced standards		Reference Method			
		ANSI C63.4			
Fully configured sample scanned over the following frequency range		Frequency range			
		0.15MHz to 30MHz			
Points of Application		Application Interface			
AC Mains		LISN			
EUT test mode		AC-Powerline			
Limits and results					
Frequency [MHz]	Quasi-Peak [dBµV]	Result	Average [dBµV]	Result	
0.15 to 5	66 to 56*	PASS	56 to 46*	PASS	
0.5 to 5	56	PASS	46	PASS	
5 to 30	60	PASS	50	PASS	
Comments:					
* Limit decreases linearly with the logarithm of the frequency.					


### Conducted Emissions

#### EMI voltage test in the ac-mains according to FCC 15B

Order number: G0M-1110-1448

Manufacturer: Steute Schaltgeräte GmbH & Co. KG  
 EUT Name: Tranceiver Module RFRX SW915-4W  
 Model: version E194K02\_02  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pflug  
 Test Conditions: Tnom: 23°C, Unom: 120 VAC power supply output +5 VDC  
 LISN: ESH2-Z5 N  
 Mode: 1  
 Test Date: 03.11.2011  
 Note:

Index 3



Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany


## Conducted Emissions

### EMI voltage test in the ac-mains according to FCC 15B

Order number: G0M-1110-1448

Manufacturer: Steute Schaltgeräte GmbH & Co. KG  
 EUT Name: Tranceiver Module RFRX SW915-4W  
 Model: version E194K02\_02  
 Test Site: Eurofins Product Service GmbH  
 Operator: Mr. Pflug  
 Test Conditions: Tnom: 23°C, Unom: 120 VAC power supply output +5 VDC  
 LISN: ESH2-Z5 L  
 Mode: 2  
 Test Date: 03.11.2011  
 Note:

Index 4



Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany



### 3.6 Test Conditions and Results – Band edge compliance


Band-edge compliance acc. FCC 15.247 / IC RSS-210					Verdict: PASS	
EUT requirement rule parts and clause		Reference				
		FCC 15.247(d) / IC RSS-210 A8.5				
Test according to measurement reference		Reference Method				
		FCC KDB Publication No. 558074				
Test frequency range		Tested frequencies				
		F <sub>MID</sub>				
EUT test mode		Single				
Limits						
Limit			Condition			
≤ -20dB/100kHz			Peak power measurement detector = Peak			
≤ -30dB/100kHz			Peak power measurement detector = RMS			
Test setup						
<div><div>Spectrum Analyzer</div><div>EUT</div></div>						
Test procedure						
1. EUT set to test mode (Communication tester is used if needed) 2. Span set around lower band edge and detector is set to peak and max hold 3. Resolution bandwidth is set to 100kHz 4. Markers are set to peak emission levels within frequency band and outside frequency band 5. Band edge attenuation is determined from level difference						
Test results						
Channel	Frequency [MHz]	Mode	Level [dBc]	Limit [dBc]	Margin [dB]	Result
F <sub>MID</sub>	915	Single	-57.10	-20	-37.10	PASS
F <sub>MID</sub>	915	Single	-58.33	-20	-38.33	PASS
Comments:						

**Band-edge compliance – F<sub>MID</sub> single – Lower Edge**
**FCC part 15.247**
**Band-edge compliance of RF conducted emissions**

EUT	Transceiver Module
Model	RFRX SW915-4W
Approval Holder	Steute Schaltgeräte GmbH / Ord.: G0M-1110-1448
Temperature / Voltage	25°C, V <sub>nom</sub>
Test Site / Operator	Eurofins Product Service GmbH, Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 915 MHz
Comment 3	pass



\*RBW 100 kHz Delta 1 [T1]  
 \*VBW 100 kHz -57.10 dB  
 Ref 10 dBm Att 40 dB SWT 5 ms -12.780000000 MHz



Date: 3.NOV.2011 13:39:07

Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

Band-edge compliance – F<sub>MID</sub> single – Upper Edge


FCC part 15.247

Band-edge compliance of RF conducted emissions

EUT	Transceiver Module
Model	RFRX SW915-4W
Approval Holder	Steute Schaltgeräte GmbH / Ord.: G0M-1110-1448
Temperature / Voltage	25°C, V <sub>nom</sub>
Test Site / Operator	Eurofins Product Service GmbH, Mr. Treffke
Test Specification	FCC part 15 section 247(c)
Comment 1	Band-edge compliance
Comment 2	Channel.: 915 MHz
Comment 3	pass



\*RBW 100 kHz Delta 1 [T1]  
 \*VBW 100 kHz -58.33 dB  
 Ref 10 dBm Att 40 dB SWT 5 ms 12.780000000 MHz



Date: 3.NOV.2011 13:44:11

Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

### 3.7 Test Conditions and Results – Conducted spurious emissions


Conducted spurious emissions acc. FCC 15.247 / IC RSS-210						Verdict: PASS	
EUT requirement rule parts and clause			Reference				
			FCC 15.247(d) / IC RSS-210 A8.5				
Test according to measurement reference			Reference Method				
			FCC KDB Publication No. 558074				
Test frequency range			Tested frequencies				
			10MHz – 10 <sup>th</sup> Harmonic				
EUT test mode			Single				
Limits							
Limit				Condition			
≤ -20dB/100kHz				Peak power measurement detector = Peak			
≤ -30dB/100kHz				Peak power measurement detector = RMS			
Test setup							
<div><div>Spectrum Analyzer</div><div>EUT</div></div>							
Test procedure							
<div>1. EUT set to test mode (Communication tester is used if needed)</div> <div>2. Span it set according to measurement range</div> <div>3. Resolution bandwidth is set to 100kHz and detector to peak and max hold</div> <div>4. Markers are set to peak emission levels within frequency band</div> <div>5. Emission level is determined by second marker on emission peak</div> <div>6. Attenuation is determined from level difference</div>							
Test results							
Channel	Frequency [MHz]	Emission [MHz]	Emission Level [dbm]	Peak power [dBm]	Limit [dBm]	Margin [dB]	Result
F <sub>MID</sub>	902.4	3660	-48.29	7.39	-12.61	-35.68	PASS
Comments:							

**Conducted spurious emissions – F<sub>MID</sub>**
**FCC part 15.247 (d)  
Spurious Emissions**

EUT	Transceiver Module
Model	RFRX SW915-4W
Approval Holder	Steute Schaltgeräte GmbH / Ord.: G0M-1110-1448
Temperature / Voltage	25°C, V <sub>nom</sub>
Test Site / Operator	Eurofins Product Service GmbH, Mr. Treffke
Test Specification	FCC part 15.247 (d)
Comment 1	Spurious Emissions conducted
Comment 2	Channel : 915 MHz
Comment 3	pass



\*RBW 100 kHz    Marker 1 [T1]  
 \*VBW 300 kHz    7.39 dBm  
 \*SWT 5 s    912.980000000 MHz



Date: 3.NOV.2011 13:20:43

Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany

**Conducted spurious emissions – F<sub>MID</sub>**
**FCC part 15.247 (d)  
Spurious Emissions**

EUT	Transceiver Module
Model	RFRX SW915-4W
Approval Holder	Steute Schaltgeräte GmbH / Ord.: G0M-1110-1448
Temperature / Voltage	25°C, V <sub>nom</sub>
Test Site / Operator	Eurofins Product Service GmbH, Mr. Treffke
Test Specification	FCC part 15.247 (d)
Comment 1	Spurious Emissions conducted
Comment 2	Channel : 915 MHz
Comment 3	pass



\*RBW 100 kHz    Marker 1 [T1]  
 \*VBW 300 kHz    -48.29 dBm  
 \*SWT 5 s    3.660000000 GHz


Ref 9.5 dBm

\*Att 30 dB

\*SWT 5 s

3.660000000 GHz

1 PR  
VIEW



Start 3 GHz

1 GHz/

Stop 13 GHz


Date: 3.NOV.2011 13:25:01

Test Report No.: G0M-1110-1448-TFC247D-V01

Eurofins Product Service GmbH  
 Storkower Str. 38c, D-15526 Reichenwalde, Germany



### 3.8 Test Conditions and Results – Transmitter radiated emissions


Transmitter radiated emissions acc. FCC 47 CFR 15.247 / IC RSS-210				Verdict: PASS
Test according referenced standards	Reference Method			
	FCC 15.247(d) / IC RSS-210 A8.5			
Test according to measurement reference	Reference Method			
	FCC KDB Publication No. 558074 / ANSI C63.4			
Test frequency range	Tested frequencies			
	30MHz – 10 <sup>th</sup> Harmonic			
EUT test mode	Single			
Limits				
Frequency range [MHz]	Detector	Limit [µV/m]	Limit [dBµV/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
<p>Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).</p> <p>When average radiated emission measurements are specified, including average emission measurements below 1000 MHz, there also is a limit on the peak level of the radio frequency emissions. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.</p>				
Test setup				
				

Test Report No.: G0M-1110-1448-TFC247D-V01


Eurofins Product Service GmbH  
Storkower Str. 38c, D-15526 Reichenwalde, Germany

Test procedure								
<ol style="list-style-type: none"> <li>1. EUT set to test mode (Communication tester is used if needed)</li> <li>2. Span it set according to measurement range</li> <li>3. Resolution bandwidth below 1GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1MHz with peak/average detector is used above 1GHz</li> <li>4. Markers are set to peak emission levels within restricted bands</li> </ol>								
Test results – Internal Antenna								
Channel	Frequency [MHz]	Emission [MHz]	Level [db $\mu$ V/m]	Detector	Pol.	Limit [db $\mu$ V/m]	Limit distance [m]*	Margin [dB]
F <sub>MID</sub>	915	3663	52.7	pk	ver	74.00	3	-21.30
Comments: * Physical distance between EUT and measurement antenna.								

Test setup



### 3.9 Test Conditions and Results – Receiver radiated emissions

Receiver radiated emissions acc. IC RSS-210				Verdict: PASS
Test according referenced standards	Reference Method			
	IC RSS-210 A8.5			
Test according to measurement reference	Reference Method			
	ANSI C63.4			
Test frequency range	Tested frequencies			
	30MHz – 3 <sup>th</sup> Harmonic			
EUT test mode	Receive			
Limits				
Frequency range [MHz]	Detector	Limit [μV/m]	Limit [dBμV/m]	Limit Distance [m]
30 – 88	Quasi-Peak	100	40	3
88 – 216	Quasi-Peak	150	43.5	3
216 – 960	Quasi-Peak	200	46	3
960 – 1000	Quasi-Peak	500	54	3
> 1000	Average	500	54	3
Test setup				
				

Test procedure							
<ol style="list-style-type: none"> <li>1. EUT set to receive mode (Communication tester is used if needed)</li> <li>2. Span it set according to measurement range</li> <li>3. Resolution bandwidth below 1GHz is set according to CISPR 16 with peak/quasi-peak detector and RBW of 1MHz with peak/average detector is used above 1GHz</li> <li>4. Markers are set to peak emission levels</li> </ol>							
Test results							
Channel	Frequency [MHz]	Emission [MHz]	Emission Level [dB $\mu$ V/m]	Emission Level [ $\mu$ V/m]	Det.	Limit [ $\mu$ V/m]	Margin [ $\mu$ V/m]
F <sub>MID</sub>	915MHz	814	27.49	23.686	pk	200.00	-176.31
Comments: * Physical distance between EUT and measurement antenna.							


**ANNEX A Transmitter radiated spurious emissions**



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HK 116  
Comment 2: Freq: 188.758MHz, Emax: 33.95dBµV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HK 116  
Comment 2: Freq: 191.824MHz, Emax: 33.47dBµV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.  
Comment 2: Freq: 813.371MHz, Emax: 25.35dBµV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247  
Comment 1: Dist.: 3m, Ant.: HL 223, amplif.  
Comment 2: Freq: 813.371MHz, Emax: 29.39dBµV/m, RBW: 100kHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.  
Comment 2: Freq: 3.663GHz, Emax: 45.12dBµV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: BBHA9120D, amplif.  
Comment 2: Freq: 3.663GHz, Emax: 52.67dBµV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.  
Comment 2: Freq: 7.976GHz, Emax: 39.26dBµV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.  
Comment 2: Freq: 6.405GHz, Emax: 49.54dBµV/m, RBW: 1MHz






## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C


Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.  
Comment 2: Freq: 11.800GHz, Emax: 43.51dBµV/m, RBW: 1MHz



## Spurious emissions Field Strength

### FCC RULES PART 15, SUBPART C

Approval Holder: Steute Schaltgeräte GmbH / GOM-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Tx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: according to §15.247, peak detector  
Comment 1: Dist.: 3m, Ant.: BBHA9120D, ampl.+HP.  
Comment 2: Freq: 10.725GHz, Emax: 43.54dBµV/m, RBW: 1MHz




**ANNEX B Receiver radiated spurious emissions**

## Field Strength under normal conditions

### Standards Industry Canada, RSS-GEN


Approval Holder: Steute Schaltgeräte GmbH / G0M-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Rx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: Freq. / CH: 915  
Comment 1: Dist.: 3m, Ant.: HK 116  
Comment 2: Freq:188.417MHz Emax:33.74dBuV/m RBW: 100 kHz



## Field Strength under normal conditions

### Standards Industry Canada, RSS-GEN


Approval Holder: Steute Schaltgeräte GmbH / G0M-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Rx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: Freq. / CH: 915  
Comment 1: Dist.: 3m, Ant.: HK 116  
Comment 2: Freq:198.978MHz Emax:33.17dBµV/m RBW: 100 kHz



## Field Strength under normal conditions

### Standards Industry Canada, RSS-GEN


Approval Holder: Steute Schaltgeräte GmbH / G0M-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Rx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: Freq. / CH: 915  
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.  
Comment 2: Freq: 814.028MHz Emax: 27.49dBµV/m RBW: 100 kHz



## Field Strength under normal conditions

### Standards Industry Canada, RSS-GEN


Approval Holder: Steute Schaltgeräte GmbH / G0M-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Rx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: Freq. / CH: 915  
Comment 1: Dist.: 3m, Ant.: HL 223, ampl.  
Comment 2: Freq: 814.028MHz Emax: 25.86dBuV/m RBW: 100 kHz



## Field Strength under normal conditions

### Standards Industry Canada, RSS-GEN

Approval Holder: Steute Schaltgeräte GmbH / G0M-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Rx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: Freq. / CH: 915  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.  
Comment 2: Freq: 3.988GHz Emax: 43.05dBµV/m RBW: 1 MHz





## Field Strength under normal conditions

### Standards Industry Canada, RSS-GEN

Approval Holder: Steute Schaltgeräte GmbH / G0M-1110-1448  
EUT: SRD-Transceiver Modul  
Model: RFRX SW915-4W(ext. ant. MC0114037) / setup: Rx, 915.0 MHz  
Test Site / Operator: Eurofins Product Service GmbH / Mr. Treffke  
Test Condition: Tnom.: 24°C / Vnom: 3.3 VDC  
Test Specification: Freq. / CH: 915  
Comment 1: Dist.: 3m, Ant.: HL025, ampl.  
Comment 2: Freq: 3.964GHz Emax: 43.22dBµV/m RBW: 1 MHz

