RF Exposure Evaluation declaration

Product Name	802.11b/g/n WLAN USB Dongle
Model No.	RE150U-DT, JW301UE, WUA-0614, MT4206, WUA-0624
FCC ID	XKRRE15U-DT

Applicant	BaudTec Corporation
Address	12F, No.181, Sec.1, Tatung Rd., Hsi-Chih City ,Taipei County, 221, Taiwan. R.O.C.

Date of Receipt	June 09, 2009
Date of Declaration	July 13, 2009
Report No.	096144R-RFUSP37V02

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1.   RF Exposure Evaluation

1.1.   Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm^2)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $Pd = (Pout*G)/(4*pi*r^2)$

Where

Pd = power density in mW/cm^2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm^2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2.   Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18℃ and 78％ RH.

1.3. Test Result of RF Exposure Evaluation

Product   :   802.11b/g/n WLAN USB Dongle

Test Item   :   RF Exposure Evaluation

Test Site   :   No.3 OATS

Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 5.0 dBi in logarithm scale.

802.11b

Output Power Into Antenna & RF Exposure Evaluation Distance (5.0 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)
1	2412.00	34.9945	0.022016
6	2437.00	32.8095	0.020641
11	2462.00	34.9945	0.022016

802.11g

Output Power Into Antenna & RF Exposure Evaluation Distance (5.0 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)
1	2412.00	106.1696	0.066793
6	2437.00	106.4143	0.066947
11	2462.00	100.9253	0.063494

The distance r (4[th] column) calculated from the Fries transmission formula is far shorter than 20 cm separation requirement.

802.11n-20M

Output Power Into Antenna & RF Exposure Evaluation Distance (5.0 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)
1	2412.00	100.9253	0.063494
6	2437.00	105.1962	0.066181
11	2462.00	101.1579	0.063640

802.11n-40M

Output Power Into Antenna & RF Exposure Evaluation Distance (5.0 dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm2)
1	2422.00	108.6426	0.068349
4	2437.00	103.9920	0.065423
7	2452.00	99.7700	0.062767

The distance r (4[th] column) calculated from the Fries transmission formula is far shorter than 20 cm separation requirement.