

# FCC Radio Test Report

## FCC ID: XMF-MID8011

### Original Grant

**Report No.** : TB-FCC171372  
**Applicant** : Lightcomm Technology Co., Ltd.

#### Equipment Under Test (EUT)

**EUT Name** : 8"Tablet  
**Model No.** : 100003561  
**Series Model No.** : MID8011  
**Brand Name** : onn  
**Receipt Date** : 2019-12-30  
**Test Date** : 2020-01-02 to 2020-01-14  
**Issue Date** : 2020-01-14  
**Standards** : FCC Part 15, Subpart E 15.407  
**Test Method** : ANSI C63.10: 2013  
**Conclusions** : PASS

In the configuration tested, the EUT complied with the standards specified above,  
The EUT technically complies with the FCC and IC requirements

**Test/Witness Engineer** : 

Jack Deng

**Test/Witness Engineer** : 

Ivan Su

**Approved& Authorized** : 

Ray Lai



This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

TB-RF-074-1.0

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT.....</b>	<b>5</b>
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test) .....	5
1.3 Block Diagram Showing the Configuration of System Tested.....	7
1.4 Description of Support Units .....	7
1.5 Description of Test Mode.....	8
1.6 Description of Test Software Setting .....	10
1.7 Measurement Uncertainty .....	12
1.8 Test Facility.....	12
<b>2. TEST SUMMARY .....</b>	<b>13</b>
<b>3. TEST SOFTWARE.....</b>	<b>13</b>
<b>4. TEST EQUIPMENT.....</b>	<b>14</b>
<b>5. CONDUCTED EMISSION TEST .....</b>	<b>15</b>
5.1 Test Standard and Limit.....	15
5.2 Test Setup.....	15
5.3 Test Procedure.....	16
5.4 Deviation From Test Standard.....	16
5.5 EUT Operating Mode .....	16
5.6 Test Data.....	16
<b>6. RADIATED EMISSION TEST .....</b>	<b>17</b>
6.1 Test Standard and Limit.....	17
6.2 Test Setup.....	18
6.3 Test Procedure.....	19
6.4 Deviation From Test Standard.....	20
6.5 EUT Operating Condition .....	20
6.6 Test Data.....	20
<b>7. BAND EDGE EMISSIONS .....</b>	<b>21</b>
7.1 Test Standard and Limit.....	21
7.2 Test Setup.....	21
7.3 Test Procedure.....	22
7.4 Deviation From Test Standard.....	22
7.5 EUT Operating Condition .....	22
7.6 Test Data.....	22
<b>8. BANDWIDTH TEST.....</b>	<b>23</b>
8.1 Test Standard and Limit.....	23
8.2 Test Setup.....	23
8.3 Test Procedure.....	23
8.4 Deviation From Test Standard.....	24

---

8.5 EUT Operating Condition .....	24
8.6 Test Data.....	24
<b>9. OUTPUT POWER TEST.....</b>	<b>25</b>
9.1 Test Standard and Limit.....	25
9.2 Test Setup.....	25
9.3 Test Procedure.....	25
9.4 Deviation From Test Standard.....	25
9.5 EUT Operating Condition .....	25
9.6 Test Date.....	25
<b>10. POWER SPECTRAL DENSITY TEST .....</b>	<b>26</b>
10.1 Test Standard and Limit .....	26
9.2 Test Setup.....	26
10.3 Test Procedure.....	26
10.4 Deviation From Test Standard.....	27
10.5 EUT Operating Condition .....	27
10.6 Test Data.....	27
<b>11. FREQUENCY STABILITY MEASUREMENT .....</b>	<b>28</b>
11.1 Test Standard and Limit .....	28
11.2 Test Setup.....	28
11.3 Test Procedure.....	28
11.4 Deviation From Test Standard.....	28
11.5 EUT Operating Condition .....	29
11.6 Test Data.....	29
<b>12. ANTENNA REQUIREMENT.....</b>	<b>30</b>
12.1 Standard Requirement.....	30
12.2 Antenna Connected Construction.....	30
12.3 Deviation From Test Standard.....	30
12.4 Result.....	30
<b>ATTACHMENT A-- CONDUCTED EMISSION TEST DATA.....</b>	<b>31</b>
<b>ATTACHMENT B-- RADIATED EMISSION TEST DATA .....</b>	<b>33</b>
<b>ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT AND BAND-EDGE TEST DATA .....</b>	<b>155</b>
<b>ATTACHMENT D--BANDWIDTH TEST DATA.....</b>	<b>245</b>
<b>ATTACHMENT E--AVG OUTPUT POWER TEST DATA .....</b>	<b>302</b>
<b>ATTACHMENT F-- POWER SPECTRAL DENSITY TEST DATA.....</b>	<b>320</b>
<b>ATTACHMENT G---FREQUENCY STABILITY MEASUREMENT DATA.....</b>	<b>353</b>

## Revision History

## 1. General Information about EUT

### 1.1 Client Information

<b>Applicant</b>	:	Lightcomm Technology Co., Ltd.
<b>Address</b>	:	UNIT 1306 13/F ARION COMMERCIAL CENTRE, 2-12 QUEEN'S ROAD WEST, SHEUNG WAN HK
<b>Manufacturer</b>	:	Huizhou Hengdu Electronics Co., Ltd.
<b>Address</b>	:	No.8 Huitai Road, Huinan High-tech Industrial Park, Huiao Avenue, Huizhou, Guangdong, China

### 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	8"Tablet	
<b>Models No.</b>	:	100003561, MID8011	
<b>Model Difference</b>	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is model name for commercial purpose.	
<b>Product Description</b>	:	Operation Frequency: U-NII-1: 5180MHz~5240MHz, U-NII-2A: 5260MHz~5320MHz U-NII-2C: 5500MHz~5720MHz, U-NII-3: 5745MHz~5825MHz	
		Antenna Gain:	2.92dBi FPC Antenna provided by the applicant.
		Modulation Type:	802.11a: OFDM (QPSK, BPSK, 16QAM) 802.11n: OFDM (QPSK, BPSK, 16QAM, 64QAM) 802.11ac: OFDM (QPSK, BPSK, 16QAM, 64QAM, 256QAM)
		Bit Rate of Transmitter:	802.11a: 6/9/12/18/24/36/48/54 Mbps 802.11n: up to 150Mbps 802.11ac: at most 433.3 Mbps
		Power Rating: Input: AC 100-240V, 50/60Hz, 0.35A Output: DC 5V 2A DC 3.8V by 4500mAh Li-ion battery	
<b>Software Version</b>	:	QP1A.190711.020 release-keys	
<b>Hardware Version</b>	:	MID8011MQ_MT8768_LPDDR4_DSP_MB-VER1.1	
<b>Remark</b>	:	The adapter and antenna gain provided by the applicant, the verified for the RF conduction test provided by TOBY test lab.	

#### Note:


- (1) This Test Report is FCC Part 15, Subpart E(15.407) for 802.11a/n/ac, the test procedure follows the KDB 789033 D02 General U-NII Test Procedures New Rules v02r01. More detailed features description, please refer to the manufacturer's specifications or the User's Manual.

## (2) Channel List:


<b>Frequency Band</b>	<b>Channel No.</b>	<b>Frequency</b>	<b>Channel No.</b>	<b>Frequency</b>
5180~5240MHz <b>(U-NII-1)</b>	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz		
For 20 MHz Bandwidth, use channel 36, 40, 44, 48. For 40 MHz Bandwidth, use channel 38, 46.				
For 80 MHz Bandwidth, use channel 42.				
<b>Frequency Band</b>	<b>Channel No.</b>	<b>Frequency</b>	<b>Channel No.</b>	<b>Frequency</b>
5260~5320 MHz <b>(U-NII-2A)</b>	52	5260 MHz	60	5300 MHz
	54	5270 MHz	62	5310MHz
	56	5280MHz	64	5320 MHz
	58	5290MHz		
For 20 MHz Bandwidth, use channel 52, 56, 60, 64. For 40 MHz Bandwidth, use channel 54, 62.				
For 80 MHz Bandwidth, use channel 58.				
<b>Frequency Band</b>	<b>Channel No.</b>	<b>Frequency</b>	<b>Channel No.</b>	<b>Frequency</b>
5500~5720 MHz <b>(U-NII-2C)</b>	100	5500 MHz	124	5620 MHz
	102	5510 MHz	126	5630 MHz
	104	5520 MHz	128	5640 MHz
	106	5530 MHz	132	5660 MHz
	108	5540 MHz	134	5670 MHz
	110	5550 MHz	136	5680 MHz
	112	5560 MHz	138	5690 MHz
	116	5580 MHz	140	5700 MHz
	118	5590 MHz	142	5710 MHz
	120	5600 MHz	144	5720 MHz
	122	5610 MHz		
For 20 MHz Bandwidth, use channel 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144				
For 40 MHz Bandwidth, use channel 102, 110, 118, 126, 134, 142				
For 80 MHz Bandwidth, use channel 106, 122, 138.				
<b>Frequency Band</b>	<b>Channel No.</b>	<b>Frequency</b>	<b>Channel No.</b>	<b>Frequency</b>
5745~5825MHz <b>(U-NII-3)</b>	149	5745 MHz	157	5785 MHz
	151	5755 MHz	159	5795 MHz
	153	5765 MHz	161	5805 MHz
	155	5775 MHz	165	5825 MHz
For 20 MHz Bandwidth, use channel 149, 153, 157, 161, 165. For 40 MHz Bandwidth, use channel 151, 159.				
For 80 MHz Bandwidth, use channel 155.				

### 1.3 Block Diagram Showing the Configuration of System Tested

#### Charging + TX Mode



#### TX Mode



### 1.4 Description of Support Units

The EUT has been test as an independent unit.

## 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

<b>For Conducted Test</b>		
<b>Final Test Mode</b>	<b>Description</b>	
Mode 1	Charging + TX a Mode(5180MHz)	
<b>For Radiated Test Below 1GHz</b>		
<b>Final Test Mode</b>	<b>Description</b>	
Mode 2	Charging + TX a Mode(5180MHz)	
<b>For Radiated Test Above 1GHz</b>		
<b>Test Band</b>	<b>Final Test Mode</b>	<b>Description</b>
U-NII-1	Mode 3	TX Mode 802.11a Mode Channel 36/40/48
	Mode 4	TX Mode 802.11n(HT20) Mode Channel 36/40/48
	Mode 5	TX Mode 802.11ac(VHT20) Mode Channel 36/40/48
	Mode 6	TX Mode 802.11n(HT40) Mode Channel 38/46
	Mode 7	TX Mode 802.11ac(VHT40) Mode Channel 38/46
	Mode 8	TX Mode 802.11ac(VHT80) Mode Channel 42
U-NII-2A	Mode 9	TX Mode 802.11a Mode Channel 52/56/64
	Mode 10	TX Mode 802.11n(HT20) Mode Channel 52/56/64
	Mode 11	TX Mode 802.11ac(VHT20) Mode Channel 52/56/64
	Mode 12	TX Mode 802.11n(HT40) Mode Channel 54/62
	Mode 13	TX Mode 802.11ac(VHT40) Mode Channel 54/62
	Mode 14	TX Mode 802.11ac(VHT80) Mode Channel 58
U-NII-2C	Mode 15	TX Mode 802.11a Mode Channel 100/120/144
	Mode 16	TX Mode 802.11n(HT20) Mode Channel 100/120/144
	Mode 17	TX Mode 802.11ac(VHT20) Mode Channel 100/120/144
	Mode 18	TX Mode 802.11n(HT40) Mode Channel 102/118/142
	Mode 19	TX Mode 802.11ac(VHT40) Mode Channel 102/118/142
	Mode 20	TX Mode 802.11ac(VHT80) Mode Channel 106/122/138
U-NII-3	Mode 21	TX Mode 802.11a Mode Channel 149/157/165
	Mode 22	TX Mode 802.11n(HT20) Mode Channel 149/157/165
	Mode 23	TX Mode 802.11ac(VHT20) Mode Channel 149/157/165
	Mode 24	TX Mode 802.11n(HT40) Mode Channel 151/159
	Mode 25	TX Mode 802.11ac(VHT40) Mode Channel 151/159
	Mode 26	TX Mode 802.11ac(VHT80) Mode Channel 155

### Note:

- (1) For all test, we have verified the construction and function in typical operation. And all the

test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.

According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:

802.11a Mode: OFDM (6 Mbps)

802.11n (HT20) Mode: MCS 0

802.11n (HT40) Mode: MCS 0

802.11a(VHT20) Mode: MCS 0

802.11a(VHT40) Mode: MCS 0

802.11a(VHT80) Mode: MCS 0

- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a portable unit; it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel& Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of WLAN.

Test Software: LaunchEngmode		
Test Mode: Continuously transmitting		
U-NII-1		
Mode	Frequency (MHz)	Parameters
802.11a	5180	13
	5200	13
	5240	13
802.11n(HT20)	5180	13
	5200	13
	5240	13
802.11ac(VHT20)	5180	13
	5200	13
	5240	13
802.11n(HT40)	5190	13
	5230	13
802.11ac(VHT40)	5190	13
	5230	13
802.11ac(VHT80)	5210	13
U-NII-2A		
Mode	Frequency (MHz)	Parameters
802.11a	5260	13
	5280	13
	5320	13
802.11n(HT20)	5260	13
	5280	13
	5320	13
802.11ac(HT20)	5260	13
	5280	13
	5320	13
802.11n(HT40)	5270	13
	5310	13
802.11ac(VHT40)	5270	13
	5310	13
802.11ac(VHT80)	5290	13

U-NII-2C		
Mode	Frequency (MHz)	Parameters
802.11a	5500	13
	5600	13
	5720	13
802.11n(HT20)	5500	13
	5600	13
	5720	13
802.11ac(HT20)	5500	13
	5600	13
	5720	13
802.11n(HT40)	5510	13
	5590	13
	5710	13
802.11ac(VHT40)	5510	13
	5590	13
	5710	13
802.11ac(VHT80)	5530	13
	5610	13
	5690	13
U-NII-3		
Mode	Frequency (MHz)	Parameters
802.11a	5745	13
	5785	13
	5825	13
802.11n(HT20)	5745	13
	5785	13
	5825	13
802.11ac(HT20)	5745	13
	5785	13
	5825	13
802.11n(HT40)	5755	13
	5795	13
802.11ac(VHT40)	5755	13
	5795	13
802.11ac(VHT80)	5775	13

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz 150kHz to 30MHz	$\pm 3.50$ dB $\pm 3.10$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.50$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB

## 1.8 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at: 1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.

At the time of testing, the following bodies accredited the Laboratory:

### CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351.

### IC Registration No.: (11950A-1)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

## 2. Test Summary

FCC Part 15 Subpart E(15.407)			
Standard Section	Test Item	Judgment	Remark
FCC			
15.203	Antenna Requirement	PASS	N/A
15.207	Conducted Emission	PASS	N/A
15.407(b)	Band Edge Emissions	PASS	N/A
15.407(a)	26dB Bandwidth&99% Bandwidth	PASS	N/A
15.407(e)	6dB Bandwidth( <b>only for UNII-3</b> )	PASS	N/A
15.407(a)	AVG Output Power	PASS	N/A
15.407(a)	Power Spectral Density	PASS	N/A
15.407(b)	Transmitter Radiated Spurious Emission	PASS	N/A
15.407(a)	Peak Excursion	PASS	N/A
15.407(g)	Frequency Stability	PASS	N/A

**Note:** "/" for no requirement for this test item.  
N/A is an abbreviation for Not Applicable.

## 3. Test Software

Test Item	Test Software	Manufacturer	Version No.
Conducted Emission	EZ-EMC	EZ	CDI-03A2
Radiation Emission	EZ-EMC	EZ	FA-03A2RE
RF Conducted Measurement	MTS-8310	MWRFTest	V2.0.0.0

## 4. Test Equipment

<b>Conducted Emission Test</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Last Cal.</b>	<b>Cal. Due Date</b>
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul. 13, 2019	Jul. 12, 2020
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul. 13, 2019	Jul. 12, 2020
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul. 13, 2019	Jul. 12, 2020
LISN	Rohde & Schwarz	ENV216	101131	Jul. 13, 2019	Jul. 12, 2020
<b>Radiation Emission Test</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Last Cal.</b>	<b>Cal. Due Date</b>
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 13, 2019	Jul. 12, 2020
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul. 13, 2019	Jul. 12, 2020
Spectrum Analyzer	Rohde & Schwarz	FSV40-N	102197	Jan. 31, 2019	Jan. 30, 2020
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Jan. 27, 2019	Jan. 26, 2020
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.03, 2019	Mar. 02, 2020
Horn Antenna	ETS-LINDGREN	BBHA 9170	BBHA9170582	Aug.07, 2019	Aug. 06, 2020
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 13, 2019	Jul. 12, 2020
Pre-amplifier	Sonoma	310N	185903	Mar.04, 2019	Mar. 03, 2020
Pre-amplifier	HP	8449B	3008A00849	Mar.03, 2019	Mar. 02, 2020
Pre-amplifier	SKET	LNPA_1840G-50	SK201904032	Jul. 27, 2019	Jul. 26, 2020
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.03, 2019	Mar. 02, 2020
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
<b>Antenna Conducted Emission</b>					
<b>Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Last Cal.</b>	<b>Cal. Due Date</b>
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul. 13, 2019	Jul. 12, 2020
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul. 13, 2019	Jul. 12, 2020
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Sep. 16, 2019	Sep. 15, 2020
Vector Signal Generator	Agilent	N5182A	MY50141294	Sep. 16, 2019	Sep. 15, 2020
Analog Signal Generator	Agilent	N5181A	MY50141953	Sep. 16, 2019	Sep. 15, 2020
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Sep. 16, 2019	Sep. 15, 2020
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Sep. 16, 2019	Sep. 15, 2020

## 5. Conducted Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.207

#### 5.1.2 Test Limit


Conducted Emission Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Notes:

- (1) \*Decreasing linearly with logarithm of the frequency.
- (2) The lower limit shall apply at the transition frequencies.
- (3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 5.2 Test Setup



### 5.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9kHz, and the test frequency band is from 0.15MHz to 30MHz.

### 5.4 Deviation From Test Standard

No deviation

### 5.5 EUT Operating Mode

Please refer to the description of test mode.

### 5.6 Test Data

Please refer to the Attachment A.

## 6. Radiated Emission Test

### 6.1 Test Standard and Limit

#### 6.1.1 Test Standard

FCC Part 15.209

#### 6.1.2 Test Limit

**Radiated Emission Limits (9kHz~1000MHz)**

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

**Radiated Emission Limit (Above 1000MHz)**

Frequency (MHz)	Distance of 3m (dBuV/m)	
	Peak	Average
Above 1000	74	54

**Note:**

- (1) The tighter limit applies at the band edges.
- (2) Emission Level(dBuV/m)=20log Emission Level(uV/m)

Limits of unwanted emission out of the restricted bands

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.3
5250~5350	-27	68.3
5470~5725	-27	68.3
5725~5825	-27(Note 2)	68.3
	10(Note 2)	105.3
	15.6(Note 2)	110.9
	27(Note 2)	122.3


## NOTE:

1, The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:


$$E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where } P \text{ is the eirp (Watts)}$$

2, According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.


## 6.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

### 6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz. The EUT was placed on a rotating 0.8m high above the ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical Antenna Or set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

## 6.4 Deviation From Test Standard

No deviation

## 6.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 6.6 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

## 7. Band Edge Emissions

### 7.1 Test Standard and Limit

#### 7.1.1 Test Standard

FCC Part 15.407(b)

#### 7.1.2 Test Limit

Limits of unwanted emission out of the restricted bands

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.3
5250~5350	-27	68.3
5470~5725	-27	68.3
5725~5825	-27(Note 2)	68.3
	10(Note 2)	105.3
	15.6(Note 2)	110.9
	27(Note 2)	122.3


NOTE:

1, The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where } P \text{ is the eirp (Watts)}$$

2, According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz. The EUT was placed on a rotating 0.8m high above the ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical Antenna Ore set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Below 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

### 7.4 Deviation From Test Standard

No deviation

### 7.5 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

### 7.6 Test Data

Please refer to the Attachment C.

## 8. Bandwidth Test

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

FCC Part 15.407

#### 8.1.2 Test Limit

FCC Part 15 Subpart C(15.407)/RSS-210		
Test Item	Limit	Frequency Range (MHz)
26 Bandwidth	N/A	5150~5250
		5250~5350
		5500~5700
6 dB Bandwidth	>500kHz	5725~5850

### 8.2 Test Setup



### 8.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The setting of the spectrum analyser as below:

26dB Bandwidth Test	
Spectrum Parameters	Setting
Attenuation	Auto
Span	>26 dB Bandwidth
RBW	Approximately 1% of the emission bandwidth
VBW	VBW>RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6dB Bandwidth Test	
Spectrum Parameters	Setting
Attenuation	Auto
Span	>6 dB Bandwidth
RBW	100 kHz
VBW	VBW>=3*RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto
99% Occupied Bandwidth Test	
Spectrum Parameters	Setting
Attenuation	Auto
RBW	1% to 5% of the OBW
VBW	≥ 3RBW
Detector	Peak
Trace	Max Hold

#### 8.4 Deviation From Test Standard

No deviation

#### 8.5 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

#### 8.6 Test Data

Please refer to the Attachment D.

## 9. Output Power Test

### 9.1 Test Standard and Limit


#### 9.1.1 Test Standard

FCC Part 15.407 (a)

#### 9.1.2 Test Limit

FCC Part 15 Subpart E(15.407)/RSS-210		
Test Item	Limit	Frequency Range(MHz)
Conducted Output Power	Fixed: 1 Watt (30dBm) Mobile and Portable: 250mW (24dBm)	5150~5250
	250mW (24dBm)	5250~5350
	250mW (24dBm)	5500~5700
	1 Watt (30dBm)	5725~5850

### 9.2 Test Setup



### 9.3 Test Procedure

The measurement is according to section 3 of KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

The EUT was connected to RF power meter via a broadband power sensor as show the block above.

### 9.4 Deviation From Test Standard

No deviation

### 9.5 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 9.6 Test Date

Please refer to the Attachment E.

## 10. Power Spectral Density Test

### 10.1 Test Standard and Limit


#### 10.1.1 Test Standard

FCC Part 15.407 (a)

#### 10.1.2 Test Limit

FCC Part 15 Subpart E(15.407)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	Other than Mobile and Portable : 17dBm/MHz Mobile and Portable : 11dBm/MHz	5150~5250
	11dBm/MHz	5250~5350
	11dBm/MHz	5500~5700
	30dBm/500kHz	5725~5850

### 9.2 Test Setup



### 10.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement is according to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser centre frequency to transmitting frequency.
- (3) Set the span to encompass the entire emissions bandwidth (EBW)(alternatively, the entire 99% OBW) of the signal.
- (4) Set the RBW to: 1 MHz
- (5) Set the VBW to: 3 MHz
- (6) Detector: RMS
- (7) Trace: Max Hold
- (7) Sweep time: auto
- (8) Trace average at least 100 traces in power averaging.

- (9) User the peak marker function to determine the maximum amplitude level within the RBW.  
Apply correction to the result if different RBW is used.

#### 10.4 Deviation From Test Standard

No deviation

#### 10.5 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

#### 10.6 Test Data

Please refer to the Attachment F.

## 11. Frequency Stability Measurement

### 11.1 Test Standard and Limit


#### 11.1.1 Test Standard

FCC Part 15.407

#### 11.1.2 Test Limit

FCC Part 15 Subpart C(15.407)		
Test Item	Limit	Frequency Range(MHz)
Peak Excursion Measurement	Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual	5150~5250
		5250~5350
		5500~5700
		5725~5850

### 11.2 Test Setup



### 11.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser centre frequency to transmitting frequency.
- (3) Set the span to encompass the entire emissions bandwidth (EBW) of the signal.
- (4) Set the RBW to: 10 kHz, VBW=10 kHz with peak detector and maxhold settings.
- (5) The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.
- (6) Extreme temperature is 0°C~50°C

### 11.4 Deviation From Test Standard

No deviation

## 11.5 EUT Operating Condition

The EUT was set to continuously transmitting in continuously un-modulation transmitting mode.

## 11.6 Test Data

Please refer to the Attachment G.

## 12. Antenna Requirement

### 12.1 Standard Requirement

#### 12.1.1 Standard

FCC Part 15.203

#### 12.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 12.2 Antenna Connected Construction

The gains of the antenna used for transmitting is 2.92 dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.

### 12.3 Deviation From Test Standard

No deviation


### 12.4 Result

The EUT antennas are FPC Antenna. It complies with the standard requirement.

Antenna Type
<input type="checkbox"/> Permanent attached antenna
<input checked="" type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

## Attachment A-- Conducted Emission Test Data

Remark: All channels have been tested and Shows only the worst channels.



<b>Temperature:</b>	24.8 °C	<b>Relative Humidity:</b>	42%																																																																																																																													
<b>Test Voltage:</b>	AC 120V/60 Hz																																																																																																																															
<b>Terminal:</b>	Neutral																																																																																																																															
<b>Test Mode:</b>	TX 802.11a Mode CH36																																																																																																																															
<b>Remark:</b>	Only worse case is reported																																																																																																																															
<table border="1"> <thead> <tr> <th>No.</th> <th>Mk.</th> <th>Freq.</th> <th>Reading Level</th> <th>Correct Factor</th> <th>Measurement</th> <th>Limit</th> <th>Over</th> </tr> <tr> <th></th> <th></th> <th>MHz</th> <th>dBuV/m</th> <th>dB</th> <th>dBuV/m</th> <th>dBuV/m</th> <th>dB</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td>1</td> <td></td> <td>0.2860</td> <td>29.86</td> <td>9.70</td> <td>39.56</td> <td>60.64</td> <td>-21.08</td> <td>QP</td> </tr> <tr> <td>2</td> <td></td> <td>0.2860</td> <td>23.58</td> <td>9.70</td> <td>33.28</td> <td>50.64</td> <td>-17.36</td> <td>AVG</td> </tr> <tr> <td>3</td> <td></td> <td>0.6060</td> <td>33.20</td> <td>9.79</td> <td>42.99</td> <td>56.00</td> <td>-13.01</td> <td>QP</td> </tr> <tr> <td>4</td> <td>*</td> <td>0.6060</td> <td>31.28</td> <td>9.79</td> <td>41.07</td> <td>46.00</td> <td>-4.93</td> <td>AVG</td> </tr> <tr> <td>5</td> <td></td> <td>0.6900</td> <td>29.29</td> <td>9.75</td> <td>39.04</td> <td>56.00</td> <td>-16.96</td> <td>QP</td> </tr> <tr> <td>6</td> <td></td> <td>0.6900</td> <td>27.49</td> <td>9.75</td> <td>37.24</td> <td>46.00</td> <td>-8.76</td> <td>AVG</td> </tr> <tr> <td>7</td> <td></td> <td>1.2140</td> <td>27.95</td> <td>9.63</td> <td>37.58</td> <td>56.00</td> <td>-18.42</td> <td>QP</td> </tr> <tr> <td>8</td> <td></td> <td>1.2140</td> <td>24.76</td> <td>9.63</td> <td>34.39</td> <td>46.00</td> <td>-11.61</td> <td>AVG</td> </tr> <tr> <td>9</td> <td></td> <td>2.7220</td> <td>26.91</td> <td>9.85</td> <td>36.76</td> <td>56.00</td> <td>-19.24</td> <td>QP</td> </tr> <tr> <td>10</td> <td></td> <td>2.7220</td> <td>20.69</td> <td>9.85</td> <td>30.54</td> <td>46.00</td> <td>-15.46</td> <td>AVG</td> </tr> <tr> <td>11</td> <td></td> <td>14.5580</td> <td>22.21</td> <td>9.86</td> <td>32.07</td> <td>60.00</td> <td>-27.93</td> <td>QP</td> </tr> <tr> <td>12</td> <td></td> <td>14.5580</td> <td>9.25</td> <td>9.86</td> <td>19.11</td> <td>50.00</td> <td>-30.89</td> <td>AVG</td> </tr> </tbody> </table>				No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over			MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	1		0.2860	29.86	9.70	39.56	60.64	-21.08	QP	2		0.2860	23.58	9.70	33.28	50.64	-17.36	AVG	3		0.6060	33.20	9.79	42.99	56.00	-13.01	QP	4	*	0.6060	31.28	9.79	41.07	46.00	-4.93	AVG	5		0.6900	29.29	9.75	39.04	56.00	-16.96	QP	6		0.6900	27.49	9.75	37.24	46.00	-8.76	AVG	7		1.2140	27.95	9.63	37.58	56.00	-18.42	QP	8		1.2140	24.76	9.63	34.39	46.00	-11.61	AVG	9		2.7220	26.91	9.85	36.76	56.00	-19.24	QP	10		2.7220	20.69	9.85	30.54	46.00	-15.46	AVG	11		14.5580	22.21	9.86	32.07	60.00	-27.93	QP	12		14.5580	9.25	9.86	19.11	50.00	-30.89	AVG
No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over																																																																																																																									
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector																																																																																																																								
1		0.2860	29.86	9.70	39.56	60.64	-21.08	QP																																																																																																																								
2		0.2860	23.58	9.70	33.28	50.64	-17.36	AVG																																																																																																																								
3		0.6060	33.20	9.79	42.99	56.00	-13.01	QP																																																																																																																								
4	*	0.6060	31.28	9.79	41.07	46.00	-4.93	AVG																																																																																																																								
5		0.6900	29.29	9.75	39.04	56.00	-16.96	QP																																																																																																																								
6		0.6900	27.49	9.75	37.24	46.00	-8.76	AVG																																																																																																																								
7		1.2140	27.95	9.63	37.58	56.00	-18.42	QP																																																																																																																								
8		1.2140	24.76	9.63	34.39	46.00	-11.61	AVG																																																																																																																								
9		2.7220	26.91	9.85	36.76	56.00	-19.24	QP																																																																																																																								
10		2.7220	20.69	9.85	30.54	46.00	-15.46	AVG																																																																																																																								
11		14.5580	22.21	9.86	32.07	60.00	-27.93	QP																																																																																																																								
12		14.5580	9.25	9.86	19.11	50.00	-30.89	AVG																																																																																																																								
*:Maximum data    x:Over limit    !:over margin																																																																																																																																
<b>Emission Level= Read Level+ Correct Factor</b>																																																																																																																																


## Attachment B-- Radiated Emission Test Data

### 9 KHz~30 MHz


From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

### 30MHz~1GHz



<b>Temperature:</b>	24.6 °C	<b>Relative Humidity:</b>	43%
<b>Test Voltage:</b>	AC 120V/60Hz		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11a Mode 5180MHz (U-NII-1)		
<b>Remark:</b>	Only worse case is reported.		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1		31.9542	40.77	-14.48	26.29	40.00	-13.71	QP
2		48.6719	55.08	-22.90	32.18	40.00	-7.82	QP
3	*	78.9651	55.16	-22.66	32.50	40.00	-7.50	QP
4		143.3257	53.05	-22.14	30.91	43.50	-12.59	QP
5		184.4898	48.85	-19.97	28.88	43.50	-14.62	QP
6		535.7073	38.53	-9.26	29.27	46.00	-16.73	QP

\*:Maximum data    x:Over limit    !:over margin

Emission Level= Read Level+ Correct Factor

**5180MHz-5240MHz(U-NII-1)**

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	TX 802.11a Mode 5180MHz (U-NII-1)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit. Only worse case is reported.								
<hr/>									
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over Detector		
1	*	10360.16	23.37	20.50	43.87	54.00	-10.13	AVG	
		10360.25	32.85	20.50	53.35	68.30	-14.95	peak	
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	TX 802.11a Mode 5180MHz (U-NII-1)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit. Only worse case is reported.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		10360.15	32.74	20.50	53.24	68.30	-15.06 peak		
2	*	10360.15	24.21	20.50	44.71	54.00	-9.29 AVG		
<b>Emission Level= Read Level+ Correct Factor</b>									

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11a Mode 5200MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1	*	10399.20	23.86	20.56	44.42	54.00	-9.58 AVG
2		10400.30	33.86	20.56	54.42	68.30	-13.88 peak
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11a Mode 5200MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB	Detector
1		10400.20	34.12	20.56	54.68	68.30	-13.62 peak
2	*	10400.20	23.15	20.56	43.71	54.00	-10.29 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11a Mode 5240MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1	*	10480.20	22.68	20.68	43.36	54.00	-10.64 AVG
2		10480.30	32.87	20.68	53.55	68.30	-14.75 peak
Emission Level= Read Level+ Correct Factor							

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11a Mode 5240MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10480.30	33.17	20.68	53.85	68.30	-14.45	peak
2	*	10480.30	23.47	20.68	44.15	54.00	-9.85	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10360.20	30.58	20.50	51.08	68.30	-17.22 peak
2	*	10360.50	23.74	20.50	44.24	54.00	-9.76 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		10359.20	31.25	20.50	51.75	68.30	-16.55 peak
2	*	10359.40	21.58	20.50	42.08	54.00	-11.92 AVG
Emission Level= Read Level+ Correct Factor							

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11n(HT20) Mode 5200MHz (U-NII-1)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10400.28	20.85	20.56	41.41	54.00	-12.59 AVG
2	*	10400.30	30.56	20.56	51.12	68.30	-17.18 peak
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5200MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB	Detector
1		10400.10	31.05	20.56	51.61	68.30	-16.69 peak
2	*	10400.20	20.38	20.56	40.94	54.00	-13.06 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT20) Mode 5240MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	10479.50	30.74	20.68	51.42	68.30	-16.88	peak
2		10479.80	20.24	20.68	40.92	54.00	-13.08	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5240MHz (U-NII-1)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10479.70	29.75	20.68	50.43	68.30	-17.87	peak
2	*	10479.70	19.68	20.68	40.36	54.00	-13.64	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10360.40	28.69	20.50	49.19	68.30	-19.11 peak
2	*	10360.40	18.69	20.50	39.19	54.00	-14.81 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	10360.50	19.24	20.50	39.74	54.00	-14.26
2		10360.60	30.57	20.50	51.07	68.30	-17.23
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%						
<b>Test Voltage:</b>	DC 3.8V									
<b>Ant. Pol.</b>	Horizontal									
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5200MHz (U-NII-1)									
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.									
<hr/>										
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB			
1		10400.60	31.25	20.56	51.81	68.30	-16.49			
2	*	10400.80	20.17	20.56	40.73	54.00	-13.27			
							Detector			
							peak			
							AVG			
<hr/>										
<b>Emission Level= Read Level+ Correct Factor</b>										

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%		
<b>Test Voltage:</b>	DC 3.8V					
<b>Ant. Pol.</b>	Vertical					
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5200MHz (U-NII-1)					
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.					
No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1	10400.70	30.57	20.56	51.13	68.30	-17.17 peak
2 *	10400.70	20.25	20.56	40.81	54.00	-13.19 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	DC 3.8V										
<b>Ant. Pol.</b>	Horizontal										
<b>Test Mode:</b>	TX 802.11 ac(VHT20) Mode 5240MHz (U-NII-1)										
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.										
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over				
		MHz	dBuV	dB	dBuV/m	dB	Detector				
1		10480.30	31.24	20.68	51.92	68.30	-16.38 peak				
2	*	10480.30	21.87	20.68	42.55	54.00	-11.45 AVG				
<b>Emission Level= Read Level+ Correct Factor</b>											

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT20) Mode 5240MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	10480.36	20.68	20.68	41.36	54.00	-12.64	AVG
2		10480.40	30.24	20.68	50.92	68.30	-17.38	peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5190MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10380.50	28.65	20.53	49.18	68.30	-19.12 peak
2	*	10380.50	19.58	20.53	40.11	54.00	-13.89 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5190MHz (U-NII-1)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10380.50	28.74	20.53	49.27	68.30	-19.03	peak
2	*	10380.50	18.64	20.53	39.17	54.00	-14.83	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		10460.25	28.56	20.65	49.21	68.30	-19.09 peak		
2	*	10460.25	18.96	20.65	39.61	54.00	-14.39 AVG		
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10460.45	18.21	20.65	38.86	54.00	-15.14	AVG
2	*	10460.75	27.99	20.65	48.64	68.30	-19.66	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB	Detector
1		10380.62	28.66	20.53	49.19	68.30	-19.11 peak
2	*	10380.62	19.52	20.53	40.05	54.00	-13.95 AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10380.52	18.59	20.53	39.12	54.00	-14.88	AVG
2	*	10380.72	28.66	20.53	49.19	68.30	-19.11	peak

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
1	*	10460.52	30.56	20.65	51.21	68.30	-17.09 peak
2		10460.85	19.85	20.65	40.50	54.00	-13.50 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10460.60	27.65	20.65	48.30	68.30	-20.00 peak
2	*	10460.60	18.22	20.65	38.87	54.00	-15.13 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10420.80	28.32	20.59	48.91	68.30	-19.39	peak
2	*	10420.80	19.32	20.59	39.91	54.00	-14.09	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10420.90	29.85	20.59	50.44	68.30	-17.86 peak
2	*	10420.90	19.77	20.59	40.36	54.00	-13.64 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

**5260MHz-5320MHz(U-NII-2A)**

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	TX 802.11a Mode 5260MHz (U-NII-2A)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit. Only worse case is reported.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		10520.80	31.25	20.73	51.98	68.30	-16.32 peak		
2	*	10520.80	22.58	20.73	43.31	54.00	-10.69 AVG		
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11a Mode 5260MHz (U-NII-2A)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit. Only worse case is reported.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10520.80	30.88	20.73	51.61	68.30	-16.69 peak
2	*	10520.80	21.85	20.73	42.58	54.00	-11.42 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V							
<b>Ant. Pol.</b>	Horizontal							
<b>Test Mode:</b>	TX 802.11a Mode 5280MHz (U-NII-2A)							
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.							
<hr/>								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	10560.70	21.74	20.78	42.52	54.00	-11.48	AVG
2		10560.80	30.57	20.78	51.35	68.30	-16.95	peak
<hr/>								
<b>Emission Level= Read Level+ Correct Factor</b>								

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11a Mode 5280MHz (U-NII-2A)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB	Detector
1		10560.50	31.56	20.78	52.34	68.30	-15.96 peak
2	*	10560.60	21.98	20.78	42.76	54.00	-11.24 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11a Mode 5320MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10640.80	31.64	20.88	52.52	68.30	-15.78 peak
2	*	10640.80	22.85	20.88	43.73	54.00	-10.27 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11a Mode 5320MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10640.70	32.58	20.88	53.46	68.30	-14.84 peak
2	*	10640.90	23.24	20.88	44.12	54.00	-9.88 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5260MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10520.50	30.42	20.73	51.15	68.30	-17.15 peak
2	*	10520.50	22.55	20.73	43.28	54.00	-10.72 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5260MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10520.40	29.68	20.73	50.41	68.30	-17.89 peak
2	*	10520.40	19.52	20.73	40.25	54.00	-13.75 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5280MHz (U-NII-2A)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		10560.80	28.67	20.78	49.45	68.30	-18.85 peak		
2	*	10560.80	18.68	20.78	39.46	54.00	-14.54 AVG		
<b>Emission Level= Read Level+ Correct Factor</b>									

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5280MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10560.90	27.63	20.78	48.41	68.30	-19.89 peak
2	*	10560.90	18.25	20.78	39.03	54.00	-14.97 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10640.40	29.57	20.88	50.45	68.30	-17.85	peak
2	*	10640.40	19.25	20.88	40.13	54.00	-13.87	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10640.60	28.97	20.88	49.85	68.30	-18.45	peak
2	*	10640.60	18.69	20.88	39.57	54.00	-14.43	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz (U-NII-2A)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB	Detector
1		10520.80	29.35	20.73	50.08	68.30	-18.22 peak
2	*	10520.80	19.52	20.73	40.25	54.00	-13.75 AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz (U-NII-2A)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		10520.70	28.89	20.73	49.62	68.30	-18.68 peak
2	*	10520.70	18.64	20.73	39.37	54.00	-14.63 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5280MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10560.80	29.28	20.78	50.06	68.30	-18.24 peak
2	*	10560.80	19.25	20.78	40.03	54.00	-13.97 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5280MHz (U-NII-2A)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		10560.70	28.36	20.78	49.14	68.30	-19.16	peak
2	*	10560.70	18.69	20.78	39.47	54.00	-14.53	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11 ac(VHT20) Mode 5320MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB/m	dBuV/m	dB	Detector
1		10480.246	32.46	20.68	53.14	68.30	-15.16 peak
2	*	10480.392	25.19	20.68	45.87	54.00	-8.13 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5320MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB	Detector
1	*	10640.50	18.97	20.88	39.85	54.00	-14.15 AVG
2		10640.70	28.69	20.88	49.57	68.30	-18.73 peak
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5270MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10540.60	27.85	20.75	48.60	68.30	-19.70 peak
2	*	10540.60	17.68	20.75	38.43	54.00	-15.57 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5270MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10540.80	29.35	20.75	50.10	68.30	-18.20 peak
2	*	10540.80	18.23	20.75	38.98	54.00	-15.02 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%							
<b>Test Voltage:</b>	DC 3.8V										
<b>Ant. Pol.</b>	Horizontal										
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5310MHz (U-NII-2A)										
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.										
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector				
1		10620.80	28.33	20.86	49.19	68.30	-19.11 peak				
2	*	10620.80	16.99	20.86	37.85	54.00	-16.15 AVG				
<b>Emission Level= Read Level+ Correct Factor</b>											

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT40) Mode 5310MHz (U-NII-2A)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10620.70	28.67	20.86	49.53	68.30	-18.77 peak
2	*	10620.70	17.06	20.86	37.92	54.00	-16.08 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5270MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10540.80	27.98	20.75	48.73	68.30	-19.57 peak
2	*	10540.80	18.52	20.75	39.27	54.00	-14.73 AVG
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5270MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10540.74	27.96	20.75	48.71	68.30	-19.59 peak
2	*	10540.74	17.65	20.75	38.40	54.00	-15.60 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5310MHz (U-NII-2A)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		10620.45	28.36	20.86	49.22	68.30	-19.08 peak		
2	*	10620.45	18.29	20.86	39.15	54.00	-14.85 AVG		
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5310MHz (U-NII-2A)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		10620.58	28.67	20.86	49.53	68.30	-18.77 peak		
2	*	10620.65	19.22	20.86	40.08	54.00	-13.92 AVG		
Emission Level= Read Level+ Correct Factor									

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5290MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10580.85	27.69	20.80	48.49	68.30	-19.81 peak
2	*	10580.85	18.58	20.80	39.38	54.00	-14.62 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5290MHz (U-NII-2A)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10580.45	28.94	20.80	49.74	68.30	-18.56 peak
2	*	10580.45	17.97	20.80	38.77	54.00	-15.23 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

**5500MHz-5720MHz(U-NII-2C)**

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11a Mode 5500MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11000.60	27.69	21.33	49.02	68.30	-19.28 peak
2	*	11000.60	18.67	21.33	40.00	54.00	-14.00 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11a Mode 5500MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		10999.56	28.67	21.33	50.00	68.30	-18.30 peak
2	*	10999.56	19.52	21.33	40.85	54.00	-13.15 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11a Mode 5600MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11200.50	27.68	21.52	49.20	68.30	-19.10 peak
2	*	11200.50	18.36	21.52	39.88	54.00	-14.12 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11a Mode 5600MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB	Detector
1		11200.76	29.35	21.52	50.87	68.30	-17.43 peak
2	*	11200.84	18.69	21.52	40.21	54.00	-13.79 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11a Mode 5700MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		11400.56	28.78	21.76	50.54	68.30	-17.76
2	*	11400.56	19.24	21.76	41.00	54.00	-13.00
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11a Mode 5700MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11400.58	28.69	21.76	50.45	68.30	-17.85 peak
2	*	11400.58	18.36	21.76	40.12	54.00	-13.88 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5500MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		11000.58	29.24	21.33	50.57	68.30	-17.73 peak
2	*	11000.58	19.57	21.33	40.90	54.00	-13.10 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V							
<b>Ant. Pol.</b>	Vertical							
<b>Test Mode:</b>	TX 802.11 n(HT20) Mode 5500MHz (U-NII-2C)							
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.							
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over Detector	
1	*	11000.62	28.67	21.33	50.00	68.30	-18.30	peak
2		11000.85	18.74	21.33	40.07	54.00	-13.93	AVG
							Emission Level= Read Level+ Correct Factor	

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5600MHz (U-NII-2C)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11200.76	29.24	21.52	50.76	68.30	-17.54	peak
2	*	11200.76	18.75	21.52	40.27	54.00	-13.73	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5600MHz (U-NII-2C)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	11200.64	19.25	21.52	40.77	54.00	-13.23		
2		11200.84	27.96	21.52	49.48	68.30	-18.82		
							Detector		
							AVG		
							peak		
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Horizontal						
Test Mode:	TX 802.11n(HT20) Mode 5700MHz (U-NII-2C)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		11400.52	28.49	21.72	50.21	68.30	-18.09
2	*	11400.52	19.25	21.72	40.97	54.00	-13.03
		-	-	-	-	-	AVG
Emission Level= Read Level+ Correct Factor							

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11n(HT20) Mode 5700MHz (U-NII-2C)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11400.43	30.24	21.72	51.96	68.30	-16.34 peak
2	*	11400.43	19.74	21.72	41.46	54.00	-12.54 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5500MHz (U-NII-2C)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		11000.48	29.35	21.33	50.68	68.30	-17.62		
2	*	11000.48	19.24	21.33	40.57	54.00	-13.43		
							AVG		
Emission Level= Read Level+ Correct Factor									

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11 ac(VHT20) Mode 5500MHz (U-NII-2C)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11000.24	28.69	21.33	50.02	68.30	-18.28 peak
2	*	11000.24	18.35	21.33	39.68	54.00	-14.32 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11 ac(VHT20) Mode 5600MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over Detector
1		11200.57	29.56	21.52	51.08	68.30	-17.22
2	*	11200.84	20.17	21.52	41.69	54.00	-12.31
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11 ac(VHT20) Mode 5600MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11200.69	29.35	21.52	50.87	68.30	-17.43 peak
2	*	11200.69	19.38	21.52	40.90	54.00	-13.10 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	TX 802.11 ac(VHT20) Mode 5700MHz (U-NII-2C)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		11400.68	28.73	21.76	50.49	68.30	-17.81 peak		
2	*	11400.68	19.35	21.76	41.11	54.00	-12.89 AVG		
<b>Emission Level= Read Level+ Correct Factor</b>									

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11 ac(VHT20) Mode 5700MHz (U-NII-2C)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11400.75	29.71	21.76	51.47	68.30	-16.83 peak
2	*	11400.86	18.89	21.76	40.65	54.00	-13.35 AVG
Emission Level= Read Level+ Correct Factor							

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11n(HT40) Mode 5510MHz (U-NII-2C)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB		
1		11020.52	29.38	21.35	50.73	68.30	-17.57	peak
2	*	11020.52	20.14	21.35	41.49	54.00	-12.51	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5510MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	11020.34	19.86	21.35	41.21	54.00	-12.79
2		11020.58	28.37	21.35	49.72	68.30	-18.58
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5590MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11180.56	29.35	21.51	50.86	68.30	-17.44 peak
2	*	11180.56	19.33	21.51	40.84	54.00	-13.16 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V							
<b>Ant. Pol.</b>	Vertical							
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5590MHz (U-NII-2C)							
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.							
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over Detector	
1		11180.57	29.57	21.51	51.08	68.30	-17.22 peak	
2	*	11180.57	19.66	21.51	41.17	54.00	-12.83 AVG	
							Emission Level= Read Level+ Correct Factor	

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5670MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11340.58	30.25	21.73	51.98	68.30	-16.32 peak
2	*	11340.58	20.47	21.73	42.20	54.00	-11.80 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5670MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11340.65	29.37	21.73	51.10	68.30	-17.20 peak
2	*	11340.65	19.38	21.73	41.11	54.00	-12.89 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5510MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11020.58	30.68	21.35	52.03	68.30	-16.27 peak
2	*	11020.64	19.68	21.35	41.03	54.00	-12.97 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5510MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11020.76	29.15	21.35	50.50	68.30	-17.80 peak
2	*	11020.85	20.11	21.35	41.46	54.00	-12.54 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5590MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		11180.58	28.33	21.51	49.84	68.30	-18.46
2	*	11180.58	19.23	21.51	40.74	54.00	-13.26
		^	^				AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5590MHz (U-NII-2C)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		11180.77	29.35	21.51	50.86	68.30	-17.44 peak		
2	*	11180.77	19.55	21.51	41.06	54.00	-12.94 AVG		
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5670MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11340.55	30.25	21.73	51.98	68.30	-16.32 peak
2	*	11340.55	20.15	21.73	41.88	54.00	-12.12 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11ac(VHT40) Mode 5670MHz (U-NII-2C)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11340.64	29.35	21.73	51.08	68.30	-17.22 peak
2	*	11340.64	19.35	21.73	41.08	54.00	-12.92 AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5530MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		11060.52	29.68	21.39	51.07	68.30	-17.23
2	*	11060.52	19.60	21.39	40.99	54.00	-13.01
							Detector
							peak
							AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5530MHz (U-NII-2C)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1	*	11060.85	29.35	21.39	50.74	68.30	-17.56 peak		
2	*	11060.85	20.15	21.39	41.54	54.00	-12.46 AVG		
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5610MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11220.55	28.69	21.54	50.23	68.30	-18.07 peak
2	*	11220.55	19.25	21.54	40.79	54.00	-13.21 AVG
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5610MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1	*	11220.47	29.42	21.54	50.96	68.30	-17.34 peak
2	*	11220.47	18.30	21.54	39.84	54.00	-14.16 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5690MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11380.52	28.22	21.70	49.92	68.30	-18.38 peak
2	*	11380.52	19.25	21.70	40.95	54.00	-13.05 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT80) Mode 5690MHz (U-NII-2C)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11380.43	18.35	21.70	40.05	54.00	-13.95 AVG
2	*	11380.47	28.36	21.70	50.06	68.30	-18.24 peak
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

**5745MHz-5825MHz(U-NII-3)**

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Horizontal								
<b>Test Mode:</b>	TX 802.11a Mode 5745MHz (U-NII-3)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		11490.20	28.96	21.81	50.77	68.30	-17.53		
2	*	11490.20	19.35	21.81	41.16	54.00	-12.84		
							Detector		
							AVG		

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	TX 802.11a Mode 5745MHz (U-NII-3)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		11490.58	28.97	21.81	50.78	68.30	-17.52 peak		
2	*	11490.58	18.96	21.81	40.77	54.00	-13.23 AVG		
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11a Mode 5785MHz (U-NII-3)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1	*	11490.57	19.45	21.81	41.26	54.00	-12.74	AVG
2		11490.58	29.64	21.81	51.45	68.30	-16.85	peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11a Mode 5785MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11490.60	29.41	21.81	51.22	68.30	-17.08 peak
2	*	11490.60	18.59	21.81	40.40	54.00	-13.60 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11a Mode 5825MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11650.42	28.69	21.96	50.65	68.30	-17.65 peak
2	*	11650.42	19.24	21.96	41.20	54.00	-12.80 AVG
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11a Mode 5825MHz (U-NII-3)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1	*	11650.38	19.28	21.96	41.24	54.00	-12.76 AVG
2		11650.45	28.69	21.96	50.65	68.30	-17.65 peak
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5745MHz (U-NII-3)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11490.58	29.35	21.81	51.16	68.30	-17.14	peak
2	*	11490.58	19.35	21.81	41.16	54.00	-12.84	AVG

Emission Level= Read Level+ Correct Factor

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Vertical		
Test Mode:	TX 802.11n(HT20) Mode 5745MHz (U-NII-3)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	
			Level	Factor	ment			
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11490.28	28.47	21.81	50.28	68.30	-18.02	peak
2	*	11490.28	18.36	21.81	40.17	54.00	-13.83	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5785MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11570.05	27.69	21.88	49.57	68.30	-18.73 peak
2	*	11570.05	18.62	21.88	40.50	54.00	-13.50 AVG
Emission Level= Read Level+ Correct Factor							

Temperature:	25 °C	Relative Humidity:	55%				
Test Voltage:	DC 3.8V						
Ant. Pol.	Vertical						
Test Mode:	TX 802.11n(HT20) Mode 5785MHz (U-NII-3)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		11570.85	28.74	21.88	50.62	68.30	-17.68
2	*	11570.85	19.25	21.88	41.13	54.00	-12.87
							Detector
							AVG
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5825MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB
1		11650.25	29.35	21.96	51.31	68.30	-16.99
2	*	11650.25	20.58	21.96	42.54	54.00	-11.46
							peak
							AVG
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT20) Mode 5825MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11650.26	30.52	21.96	52.48	68.30	-15.82 peak
2	*	11650.26	21.27	21.96	43.23	54.00	-10.77 AVG
Emission Level= Read Level+ Correct Factor							

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	DC 3.8V		
Ant. Pol.	Horizontal		
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3)		
Remark:	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over
			Level	Factor	ment		
1		11490.25	29.68	21.81	51.49	68.30	-16.81 peak
2	*	11490.25	19.25	21.81	41.06	54.00	-12.94 AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over Detector		
1		11490.68	29.67	21.81	51.48	68.30	-16.82	peak	
2	*	11490.68	19.58	21.81	41.39	54.00	-12.61	AVG	
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11570.68	29.52	21.88	51.40	68.30	-16.90	peak
2	*	11570.68	19.25	21.88	41.13	54.00	-12.87	AVG

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C		<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.8V								
<b>Ant. Pol.</b>	Vertical								
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3)								
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.								
<hr/>									
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector		
1		11570.56	29.34	21.88	51.22	68.30	-17.08 peak		
2	*	11570.56	18.69	21.88	40.57	54.00	-13.43 AVG		
<hr/>									
<b>Emission Level= Read Level+ Correct Factor</b>									

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over Detector
1		11650.25	30.24	21.96	52.20	68.30	-16.10
2	*	11650.25	19.32	21.96	41.28	54.00	-12.72
Emission Level= Read Level+ Correct Factor							AVG

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/> <hr/> <hr/> <hr/> <hr/> <hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1	*	11650.25	19.24	21.96	41.20	54.00	-12.80 AVG
2		11650.45	30.87	21.96	52.83	68.30	-15.47 peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11510.56	29.52	21.82	51.34	68.30	-16.96 peak
2	*	11510.56	18.63	21.82	40.45	54.00	-13.55 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dB	Detector
1		11510.72	28.49	21.82	50.31	68.30	-17.99 peak
2	*	11510.72	19.32	21.82	41.14	54.00	-12.86 AVG
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5795MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1		11590.50	27.69	21.90	49.59	68.30	-18.71 peak
2	*	11590.50	18.02	21.90	39.92	54.00	-14.08 AVG
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	TX 802.11n(HT40) Mode 5795MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB Detector
1	*	11590.60	17.99	21.90	39.89	54.00	-14.11 AVG
2		11590.70	28.34	21.90	50.24	68.30	-18.06 peak
<b>Emission Level= Read Level+ Correct Factor</b>							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.8V						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3)						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB	Over Detector
1	*	11510.54	18.63	21.82	40.45	54.00	-13.55
2		11510.70	29.35	21.82	51.17	68.30	-17.13
Emission Level= Read Level+ Correct Factor							

<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.8V		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3)		
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		11510.36	29.24	21.82	51.06	68.30	-17.24	peak
2	*	11510.36	19.52	21.82	41.34	54.00	-12.66	AVG

Emission Level= Read Level+ Correct Factor