



TEST REPORT

Report No.: HK12071469-1

IntelliTouch

Application
For
Certification
(Original Grant)
(FCC ID: XMQEOS-P500)

Transceiver

Prepared and Checked by:

Approved by:

Signed On File
Wong Cheuk Ho, Herbert
Engineer

Chan Chi Hung, Terry
Assistant Supervisor
Date: September 04, 2012

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

INTERTEK TESTING SERVICES

GENERAL INFORMATION

IntelliTouch

BRAND NAME: IntelliTouch, MODEL: EOSP-500

FCC ID: XMQEOS-P500

Grantee:	IntelliTouch
Grantee Address:	6370 Nancy Ridge Dr., Stc. 105, San Diego, CA 92121, United States.
Contact Person:	Jeff O'Shea
Tel:	858-457-3300
Fax:	858-457-3311
e-mail:	N/A
Manufacturer:	Victory Telecom (Huizhou) Ltd
Manufacturer Address:	Building A, No 18, ShuiYuan Industrial District, RuHu Town, Hui Zhou City 516021, GuangDong Province, P.R. China.
Brand Name:	IntelliTouch
Model:	EOSP-500
Type of EUT:	Transceiver
Description of EUT:	Dual Zone Streaming Music Player
Serial Number:	N/A
FCC ID:	XMQEOS-P500
Date of Sample Submitted:	July 31, 2012
Date of Test:	August 24, 2012
Report No.:	HK12071469-1
Report Date:	September 04, 2012
Environmental Conditions:	Temperature: +10 to 40°C Humidity: 10 to 90%

INTERTEK TESTING SERVICES

SUMMARY OF TEST RESULT

IntelliTouch

BRAND NAME: IntelliTouch, MODEL: EOSP-500

FCC ID: XMQEOS-P500

TEST SPECIFICATION	REFERENCE	RESULTS
Maximum Peak Output Power	15.247(b), (c) / RSS-210 A8.4	N/A
Hopping Channel Carrier Frequencies Separation	15.247(e) / RSS-210 A8.1	N/A
20dB Bandwidth of the Hopping Channel	15.247(a) / RSS-210 A8.1	N/A
Number of Hopping Frequencies	15.247(e) / RSS-210 A8.1	N/A
Average Time of Occupancy of Hopping Frequency	15.247(e) / RSS-210 A8.1	N/A
Antenna Conducted Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
Radiated Spurious Emissions	15.247(d) / RSS-210 A8.5	N/A
RF Exposure Compliance	15.247(i) / RSS-Gen 5.6	N/A
Transmitter Power Line Conducted Emissions	15.207 / RSS-Gen 7.2.4	Pass
Transmitter Field Strength	15.227 / RSS-310 3.8	N/A
Transmitter Field Strength	15.229 / RSS-210 A2.7	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(a) / RSS-210 A1.1.1	N/A
Transmitter Field Strength, Bandwidth and Timing Requirement	15.231(e) / RSS-210 A1.1.5	N/A
Transmitter Field Strength and Bandwidth Requirement	15.239 / RSS-210 A2.8	N/A
Transmitter Field Strength and Bandwidth Requirement	15.249 / RSS-210 A2.9	Pass
Transmitter Field Strength and Bandwidth Requirement	15.235 / RSS-310 3.9	N/A
Receiver / Digital Device Radiated Emissions	15.109 / RSS-210 2.5	N/A
Digital Device Conducted Emissions	15.107 / ICES-003	N/A

- Note: 1. The EUT uses a permanently attached antenna which, in accordance to section 15.203, is considered sufficient to comply with the provisions of this section.
2. Pursuant to FCC part 15 Section 15.215(c), the 20 dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered.

INTERTEK TESTING SERVICES

Table of Contents

1.0	<u>General Description</u>	1
1.1	Product Description	1
1.2	Related Submittal(s) Grants	1
1.3	Test Methodology	1
1.4	Test Facility	1
2.0	<u>System Test Configuration</u>	2
2.1	Justification	2
2.2	EUT Exercising Software	2
2.3	Special Accessories	2
2.4	Equipment Modification	2
2.5	Measurement Uncertainty	2
2.6	Support Equipment List and Description	2
3.0	<u>Emission Results</u>	3
3.1	Field Strength Calculation	3
3.2	Radiated Emission Configuration Photograph	4
3.3	Radiated Emission Data	4
3.4	Conducted Emission Configuration Photograph	4
3.5	Conducted Emission Data	4
4.0	<u>Equipment Photographs</u>	11
5.0	<u>Product Labelling</u>	11
6.0	<u>Technical Specifications</u>	11
7.0	<u>Instruction Manual</u>	11
8.0	<u>Miscellaneous Information</u>	12
8.1	Measured Bandwidth	12
8.2	Discussion of Pulse Desensitization	15
8.3	Calculation of Average Factor	15
8.4	Emissions Test Procedures	15
9.0	<u>Confidentiality Request</u>	16
10.0	<u>Equipment List</u>	17

INTERTEK TESTING SERVICES

1.0 General Description

1.1 Product Description

The Equipment Under Test (EUT) is a Dual Zone Streaming Music Player with 2.4GHz transceiver module. After the pairing procedure (pressing the link buttons of both the EUT and its corresponding transceiver), the EUT can transmit audio signal to the corresponding transceiver via the 2.4GHz modules. The EUT accepts audio signal sources from Internet Radio (via Ethernet LAN), USB flash, SD Card and analog inputs only.

The EUT has built-in power amplifier and monitor loudspeaker. It is powered by an AC/DC adaptor with 9VDC 1.5A output. The AC/DC adaptor can accept universal input (100-240VAC).

The 2.4GHz transceiver module has two external antennas with unique antenna connector and operates in three channels (2412MHz, 2438MHz and 2464MHz, 26MHz channel spacing). The modulation scheme is QPSK (DSSS). Either one antenna is emitting in normal operation. RF output power is fixed at +12dBm.

Antenna Type : External antenna (with unique antenna connector)

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

1.2 Related Submittal(s) Grants

The Certification procedure of transceivers (with FCC ID: XMQEOS-P610 and XMQEOS-P622) for this transceiver (with FCC ID: XMQEOS-P500) is being processed as the same time of this application.

1.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2009). All radiated measurements were performed in an Open Area Test Site. Preliminary scans were performed in the Open Area Test Site only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the “**Justification Section**” of this Application.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been placed on file with the FCC.

INTERTEK TESTING SERVICES

2.0 **System Test Configuration**

2.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.4 (2009).

The device was powered by 120VAC.

For maximizing emissions, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data reported in Exhibit 3.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the wooden turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

2.2 EUT Exercising Software

There was no special software to exercise the device. Once the unit is powered up, it transmits the RF signal continuously.

2.3 Special Accessories

There are no special accessories necessary for compliance of this product.

2.4 Equipment Modification

Any modifications installed previous to testing by IntelliTouch will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Intertek Testing Services Hong Kong Ltd.

2.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

2.6 Support Equipment List and Description

1. SD Card (Provided by Intertek)
2. USB Flash (Provided by Intertek)
3. LAN Router (Provided by Intertek)
4. 2 x LAN cable with length of 1 meter long (Provided by Intertek)
5. 2 x 1 meter long audio cable with 47k ohm resistive terminator. (Provided by Intertek)

INTERTEK TESTING SERVICES

3.0 Emission Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

3.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any), Average Factor (optional) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG - AV$$

where

- FS = Field Strength in dB μ V/m
- RA = Receiver Amplitude (including preamplifier) in dB μ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- AV = Average Factor in dB

In the following table(s), the reading shown on the data table reflects the preamplifier gain. An example for the calculations in the following table is as follows:

$$FS = RR + LF$$

where

- FS = Field Strength in dB μ V/m
- RR = RA - AG - AV in dB μ V
- LF = CF + AF in dB

Assume a receiver reading of 52.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB are added. The amplifier gain of 29 dB and average factor of 5 dB are subtracted, giving a field strength of 27 dB μ V/m. This value in dB μ V/m was converted to its corresponding level in μ V/m.

$$RA = 52.0 \text{ dB}\mu\text{V/m}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$AV = 5.0 \text{ dB}$$

$$FS = RR + LF$$

$$FS = 18 + 9 = 27 \text{ dB}\mu\text{V/m}$$

$$RR = 18.0 \text{ dB}\mu\text{V}$$

$$LF = 9.0 \text{ dB}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(27 \text{ dB}\mu\text{V/m})/20] = 22.4 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

3.2 Radiated Emission Configuration Photograph

The worst case in radiated emission was found at 2412.000 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

3.3 Radiated Emission Data

The data on the following page lists the significant emission frequencies, the limit and the margin of compliance. Numbers with a minus sign are below the limit.

Judgment: Passed by 0.2 dB

3.4 Conducted Emission Configuration Photograph

For electronic filing, the worst case line-conducted configuration photographs are saved with filename: conducted photo.pdf.

3.5 Conducted Emission Data

For electronic filing, the graph and data table of conducted emission is saved with filename: conducted.pdf.

Judgment: Pass by more than 20 dB

INTERTEK TESTING SERVICES

Applicant: IntelliTouch

Date of Test: August 24, 2012

Model: EOSP-500

Worst-Case Operating Mode: Transmitting (Antenna 1)

Table 1

Radiated Emissions
Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2412.000	97.4	33	29.4	93.8	94.0	-0.2
V	4824.000	41.7	33	34.9	43.6	54.0	-10.4
V	7236.000	35.1	33	37.9	40.0	54.0	-14.0
V	9648.000	30.7	33	40.4	38.1	54.0	-15.9
V	12060.000	30.1	33	40.5	37.6	54.0	-16.4
V	14472.000	30.0	33	40.0	37.0	54.0	-17.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2412.000	114.2	33	29.4	110.6	114.0	-3.4
V	4824.000	59.7	33	34.9	61.6	74.0	-12.4
V	7236.000	55.9	33	37.9	60.8	74.0	-13.2
V	9648.000	41.2	33	40.4	48.6	74.0	-25.4
V	12060.000	42.6	33	40.5	50.1	74.0	-23.9
V	14472.000	44.1	33	40.0	51.1	74.0	-22.9

NOTES: 1. Average Detector and Peak Detector are used for emission measurement.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: IntelliTouch

Date of Test: August 24, 2012

Model: EOSP-500

Worst-Case Operating Mode: Transmitting (Antenna 1)

Table 2

Radiated Emissions
Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2438.000	96.6	33	29.4	93.0	94.0	-1.0
V	4876.000	41.9	33	34.9	43.8	54.0	-10.2
V	7314.000	35.7	33	37.9	40.6	54.0	-13.4
V	9752.000	31.6	33	40.4	39.0	54.0	-15.0
V	12190.000	30.2	33	40.5	37.7	54.0	-16.3
V	14628.000	32.1	33	38.4	37.5	54.0	-16.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2438.000	114.4	33	29.4	110.8	114.0	-3.2
V	4876.000	58.9	33	34.9	60.8	74.0	-13.2
V	7314.000	56.7	33	37.9	61.6	74.0	-12.4
V	9752.000	41.4	33	40.4	48.8	74.0	-25.2
V	12190.000	42.7	33	40.5	50.2	74.0	-23.8
V	14628.000	46.2	33	38.4	51.6	74.0	-22.4

NOTES: 1. Average Detector and Peak Detector are used for emission measurement.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: IntelliTouch

Date of Test: August 24, 2012

Model: EOSP-500

Worst-Case Operating Mode: Transmitting (Antenna 1)

Table 3

Radiated Emissions
Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2464.000	96.6	33	29.4	93.0	94.0	-1.0
V	4928.000	41.7	33	34.9	43.6	54.0	-10.4
V	7392.000	35.6	33	37.9	40.5	54.0	-13.5
V	9856.000	31.2	33	40.4	38.6	54.0	-15.4
V	12320.000	30.1	33	40.5	37.6	54.0	-16.4
V	14784.000	32.0	33	38.4	37.4	54.0	-16.6

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2464.000	114.6	33	29.4	111.0	114.0	-3.0
V	4928.000	59.0	33	34.9	60.9	74.0	-13.1
V	7392.000	56.6	33	37.9	61.5	74.0	-12.5
V	9856.000	41.2	33	40.4	48.6	74.0	-25.4
V	12320.000	42.9	33	40.5	50.4	74.0	-23.6
V	14784.000	46.1	33	38.4	51.5	74.0	-22.5

NOTES: 1. Average Detector and Peak Detector are used for emission measurement.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: IntelliTouch

Date of Test: August 24, 2012

Model: EOSP-500

Worst-Case Operating Mode: Transmitting (Antenna 2)

Table 4

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Lowest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2412.000	96.7	33	29.4	93.1	94.0	-0.9
V	4824.000	43.9	33	34.9	45.8	54.0	-8.2
V	7236.000	37.2	33	37.9	42.1	54.0	-11.9
V	9648.000	32.6	33	40.4	40.0	54.0	-14.0
V	12060.000	29.5	33	40.5	37.0	54.0	-17.0
V	14472.000	29.0	33	40.0	36.0	54.0	-18.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2412.000	114.7	33	29.4	111.1	114.0	-2.9
V	4824.000	61.7	33	34.9	63.6	74.0	-10.4
V	7236.000	61.5	33	37.9	66.4	74.0	-7.6
V	9648.000	50.6	33	40.4	58.0	74.0	-16.0
V	12060.000	42.6	33	40.5	50.1	74.0	-23.9
V	14472.000	44.6	33	40.0	51.6	74.0	-22.4

- NOTES: 1. Average Detector and Peak Detector are used for emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative sign in the column shows value below limit.
4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: IntelliTouch

Date of Test: August 24, 2012

Model: EOSP-500

Worst-Case Operating Mode: Transmitting (Antenna 2)

Table 5

Radiated Emissions
Pursuant to FCC Part 15 Section 15.249 Requirement

Middle Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2438.000	96.4	33	29.4	92.8	94.0	-1.2
V	4876.000	43.7	33	34.9	45.6	54.0	-8.4
V	7314.000	37.5	33	37.9	42.4	54.0	-11.6
V	9752.000	32.1	33	40.4	39.5	54.0	-14.5
V	12190.000	29.6	33	40.5	37.1	54.0	-16.9
V	14628.000	31.1	33	38.4	36.5	54.0	-17.5

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2438.000	114.6	33	29.4	111.0	114.0	-3.0
V	4876.000	60.2	33	34.9	62.1	74.0	-11.9
V	7314.000	58.7	33	37.9	63.6	74.0	-10.4
V	9752.000	50.6	33	40.4	58.0	74.0	-16.0
V	12190.000	42.9	33	40.5	50.4	74.0	-23.6
V	14628.000	45.7	33	38.4	51.1	74.0	-22.9

NOTES: 1. Average Detector and Peak Detector are used for emission measurement.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

Applicant: IntelliTouch

Date of Test: August 24, 2012

Model: EOSP-500

Worst-Case Operating Mode: Transmitting (Antenna 2)

Table 6

Radiated Emissions Pursuant to FCC Part 15 Section 15.249 Requirement

Highest Channel

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Average (dBμV/m)	Average Limit at 3m (dBμV/m)	Margin (dB)
V	2464.000	97.2	33	29.4	93.6	94.0	-0.4
V	4928.000	43.2	33	34.9	45.1	54.0	-8.9
V	7392.000	37.7	33	37.9	42.6	54.0	-11.4
V	9856.000	32.4	33	40.4	39.8	54.0	-14.2
V	12320.000	29.9	33	40.5	37.4	54.0	-16.6
V	14784.000	30.6	33	38.4	36.0	54.0	-18.0

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Peak Limit at 3m (dBμV/m)	Margin (dB)
V	2464.000	114.2	33	29.4	110.6	114.0	-3.4
V	4928.000	63.5	33	34.9	65.4	74.0	-8.6
V	7392.000	58.1	33	37.9	63.0	74.0	-11.0
V	9856.000	49.1	33	40.4	56.5	74.0	-17.5
V	12320.000	43.1	33	40.5	50.6	74.0	-23.4
V	14784.000	46.2	33	38.4	51.6	74.0	-22.4

NOTES: 1. Average Detector and Peak Detector are used for emission measurement.

2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distances were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.

3. Negative sign in the column shows value below limit.

4. Horn antenna is used for the emission over 1000MHz.

INTERTEK TESTING SERVICES

4.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.pdf and internal photos.pdf.

5.0 **Product Labelling**

For electronics filing, the FCC ID label artwork and the label location are saved with filename: label.pdf.

6.0 **Technical Specifications**

For electronic filing, the block diagram and schematic of the tested EUT are saved with filename: block.pdf and circuit.pdf respectively.

7.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

INTERTEK TESTING SERVICES

8.0 **Miscellaneous Information**

The miscellaneous information includes details of the test procedure and measured bandwidth.

8.1 Measured Bandwidth

From the following plots, they show that the fundamental emissions are confined in the specified band (2400MHz to 2483.5MHz). In case of the fundamental emissions are within two standard bandwidths from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2009) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50dB below the level of the fundamental or to the general radiated emissions limits in Section 15.209, whichever is the lesser attenuation, which meet the requirement of part 15.249(d).

INTERTEK TESTING SERVICES

Peak Measurement (Antenna 1)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

=110.6 dB μ V/m - 44.4 dB

=66.2 dB μ V/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

=93.8 dB μ V/m - 44.4 dB

=49.4 dB μ V/m

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

=111.0 dB μ V/m - 50.3 dB

=58.0 dB μ V/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

=93.0 dB μ V/m - 53.0 dB

=40.0 dB μ V/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74 dB μ V/m (Peak Limit) and 54 dB μ V/m (Average Limit).

INTERTEK TESTING SERVICES

Peak Measurement (Antenna 2)

Bandedge compliance is determined by applying marker-delta method, i.e. (Bandedge Plot).

Lower bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

=111.1 dB μ V/m - 42.9 dB

=68.2 dB μ V/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

=93.1 dB μ V/m - 42.9 dB

=50.2 dB μ V/m

Upper bandedge

Peak Resultant field strength = Fundamental emissions (peak value) – delta from the plot

=110.6 dB μ V/m - 53.7 dB

=56.9 dB μ V/m

Average Resultant field strength = Fundamental emissions (average value) – delta from the plot

=93.6 dB μ V/m - 53.7 dB

=39.9 dB μ V/m

The resultant field strength meets the general radiated emission limit in section 15.209, which does not exceed 74 dB μ V/m (Peak Limit) and 54 dB μ V/m (Average Limit).

INTERTEK TESTING SERVICES

8.2 Discussion Pulse Desensitivity

Pulse desensitivity is not applicable for this device. Since the transmitter transmits the RF signal continuously.

8.3 Calculation of Average Factor

The average factor is not applicable for this device as the transmitted signal is a continuously signal.

8.4 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services Hong Kong Ltd. in the measurements of transmitter operating under the Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.4 (2009). A typical or an unmodulated CW signal at the operating frequency of the EUT has been supplied to the EUT for all measurements. Such a signal is supplied by a signal generator and an antenna in close proximity to the EUT. The signal level is sufficient to stabilize the local oscillator of the EUT.

The transmitting equipment under test (EUT) is placed on a wooden turntable which is four feet in diameter and approximately one meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axis to obtain maximum emission levels. The antenna height and polarization are also varied during the testing to search for maximum signal levels. The height of the antenna is varied from one to four meters.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in Exhibit 8.3.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or 40 GHz, whichever is lower. For line conducted emissions, the range scanned is 150 kHz to 30 MHz.

INTERTEK TESTING SERVICES

8.4 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements were made as described in ANSI C63.4 (2009).

The IF bandwidth used for measurement of radiated signal strength was 100 kHz or greater when frequency is below 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report (See Exhibit 8.1). Above 1000 MHz, a resolution bandwidth of 1 MHz is used.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the forbidden bands and above 1 GHz, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, unless otherwise reported. Measurements taken at a closer distance are so marked.

9.0 **Confidentiality Request**

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.

INTERTEK TESTING SERVICES

10.0 Equipment List

1) Radiated Emissions Test

Equipment	EMI Test Receiver	Biconical Antenna	Log Periodic Antenna
Registration No.	EW-2500	EW-2512	EW-0446
Manufacturer	R&S	EMCO	EMCO
Model No.	ESCI	3104C	3146
Calibration Date	Feb. 24, 2012	Nov. 15, 2011	Oct. 31, 2011
Calibration Due Date	Feb. 24, 2013	May 15, 2013	Apr. 30, 2013

Equipment	Spectrum Analyzer	Double Ridged Guide Antenna
Registration No.	EW-1792	EW-1133
Manufacturer	R&S	EMCO
Model No.	FSP40	3115
Calibration Date	Sep. 28, 2011	Mar. 02, 2011
Calibration Due Date	Sep. 28, 2012	Sep. 02, 2012

2) Conducted Emissions Test

Equipment	EMI Test Receiver	LISN
Registration No.	EW-2500	EW-2041
Manufacturer	R&S	KYORITSU
Model No.	ESCI	KNW-403D
Calibration Date	Feb. 24, 2012	Jan. 05, 2012
Calibration Due Date	Feb. 24, 2013	Dec. 31, 2012

3) Bandedge Measurement

Equipment	Spectrum Analyzer
Registration No.	EW-1792
Manufacturer	R&S
Model No.	FSP40
Calibration Date	Sep. 28, 2011
Calibration Due Date	Sep. 28, 2012