



RF TEST REPORT

Applicant Quectel Wireless Solutions Co., Ltd
FCC ID XMR201909EG95NAX
Product LTE Module
Brand Quectel
Model EG95-NAX
Report No. R1907A0407-R6V1
Issue Date November 29, 2019

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR47 Part 27C (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report	4
1.2	Testing Location	4
2	General Description of Equipment under Test.....	5
3	Applied Standards	6
4	Test Configuration	7
5	Test Case Results	9
5.1	RF Power Output	9
5.2	Effective Isotropic Radiated Power	16
5.3	Occupied Bandwidth	22
5.4	Band Edge Compliance	39
5.5	Peak-to-Average Power Ratio (PAPR)	61
5.6	Frequency Stability.....	65
5.7	Spurious Emissions at Antenna Terminals	70
5.8	Radiates Spurious Emission	89
6	Main Test Instruments	106



Summary of Measurement Results

Number	Test Case	Clause in FCC rules	Verdict
1	RF power output	2.1046	PASS
2	Effective Isotropic Radiated power	27.50(d)(4)/27.50(b)(10)/27.50(c)(10)	PASS
3	Occupied Bandwidth	2.1049	PASS
4	Band Edge Compliance	27.53(h)/27.53(g)/27.53(f) /27.53(c)	PASS
5	Peak-to-Average Power Ratio	27.50(d)/KDB971168 D01(5.7)	PASS
6	Frequency Stability	2.1055 / 27.54	PASS
7	Spurious Emissions at Antenna Terminals	2.1051/27.53(h)/27.53(g)/27.53(f)	PASS
8	Radiates Spurious Emission	2.1051/27.53(h) /27.53(g) /27.53(f)	PASS

Date of Testing: May 25, 2018 ~ June 27, 2018 and November 28, 2019

Note: PASS: The EUT complies with the essential requirements in the standard.
FAIL: The EUT does not comply with the essential requirements in the standard.

EG95-NAX (Report No.: R1907A0407-R6) is a variant of the EG95-NA (Report No.: R1805A0249-R3). Test values duplicated from Original for variant. There is no test for variant in this report.



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com



2 General Description of Equipment under Test

Client Information

Applicant	Quectel Wireless Solutions Co., Ltd
Applicant address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
Manufacturer	Quectel Wireless Solutions Co., Ltd
Manufacturer address	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

General information

EUT Description			
Model	EG95-NAX		
IMEI	865026040005000		
Hardware Version	R1.0		
Software Version	EG95NAXGAR07A01M1G		
Power Supply	External Power Supply		
Antenna Type	The EUT don't have standard Antenna, The Antenna used for testing in this report is the after-market accessory (Dipole Antenna)		
Test Mode(s)	WCDMA Band IV; LTE Band 4; LTE Band 12, LTE Band 13;		
Test Modulation	(WCDMA)QPSK; (LTE)QPSK 16QAM;		
HSDPA UE Category	24		
HSUPA UE Category	6		
DC-HSDPA UE Category	24		
LTE Category	4		
Maximum E.I.R.P./ E.R.P.	WCDMA Band IV:	25.63dBm	
	LTE Band 4:	25.14dBm	
	LTE Band 12:	19.7dBm	
	LTE Band 13:	22.41Bm	
Rated Power Supply Voltage:	3.8V		
Extreme Voltage	Minimum: 3.3V Maximum: 4.3V		
Extreme Temperature	Lowest: -40°C Highest: +85°C		
Operating Frequency Range(s)	Mode	Tx (MHz)	Rx (MHz)
	WCDMA Band IV	1710 ~ 1755	2110 ~ 2155
	LTE Band 4	1710 ~ 1755	2110 ~ 2155
	LTE Band 12	699 ~ 716	729 ~ 746
	LTE Band 13	777 ~ 787	746 ~ 756
Note: 1. The information of the EUT is declared by the manufacturer.			



3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

FCC CFR47 Part 2 (2017)

FCC CFR47 Part 27C (2017)

ANSI/TIA-603-E (2016)

KDB 971168 D01 Power Meas License Digital Systems v03r01



4 Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (Z axis, horizontal position) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in WCDMA/LTE is set based on the maximum RF Output Power.

The following testing in different Bandwidth is set to detailin the following table:

Test modes are chosen to be reported as the worst case configuration below for WCDMA Band IV:

	Test items	Modes/Modulation
		WCDMA Band IV
Conducted Test cases	RF power output	RMC HSDPA/HSUPA DC-HSDPA
	Occupied Bandwidth	RMC
	Band Edge Compliance	RMC
	Peak-to-Average Power Ratio	RMC
	Frequency Stability	RMC
	Spurious Emissions at Antenna Terminals	RMC
Radiated Test cases	Effective Isotropic Radiated power	RMC
	Radiates Spurious Emission	RMC



Test modes are chosen to be reported as the worst case configuration below for LTE Band 4/12/13:

Test items	Modes	Bandwidth (MHz)						Modulation		RB			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	50%	100%	L	M	H
RF power output	LTE 4	O	O	O	O	O	O	O	O	O	O	O	O	O	O
	LTE 12	O	O	O	O	-	-	O	O	O	O	O	O	O	O
	LTE 13	-	-	O	O	-	-	O	O	O	O	O	O	O	O
Effective Isotropic Radiated power	LTE 4	O	O	O	O	O	O	O	O	O	O	O	O	O	O
	LTE 12	O	O	O	O	-	-	O	O	O	O	O	O	O	O
	LTE 13	-	-	O	O	-	-	O	O	O	O	O	O	O	O
Occupied Bandwidth	LTE 4	O	O	O	O	O	O	O	O	-	-	O	O	O	O
	LTE 12	O	O	O	O	-	-	O	O	-	-	O	O	O	O
	LTE 13	-	-	O	O	-	-	O	O	-	-	O	O	O	O
Band Edge Compliance	LTE 4	O	O	O	O	O	O	O	O	O	-	O	O	-	O
	LTE 12	O	O	O	O	-	-	O	O	O	-	O	O	-	O
	LTE 13	-	-	O	O	-	-	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	LTE 4	O	O	O	O	O	O	O	O	-	-	O	O	O	O
	LTE 12	O	O	O	O	-	-	O	O	-	-	O	O	O	O
	LTE 13	-	-	O	O	-	-	O	O	-	-	O	O	O	O
Frequency Stability	LTE 4	O	O	O	O	O	O	O	O	-	-	O	O	-	O
	LTE 12	O	O	O	O	-	-	O	O	-	-	O	O	-	O
	LTE 13	-	-	O	O	-	-	O	O	-	-	O	O	-	O
Spurious Emissions at Antenna Terminals	LTE 4	O	O	O	O	O	O	O	-	O	-	-	O	O	O
	LTE 12	O	O	O	O	-	-	O	-	O	-	-	O	O	O
	LTE 13	-	-	O	O	-	-	O	-	O	-	-	O	O	O
Radiates Spurious Emission	LTE 4	O	-	O	-	-	O	O	-	O	-	-	O	O	O
	LTE 12	O	-	O	O	-	-	O	-	O	-	-	O	O	O
	LTE 13	-	-	O	O	-	-	O	-	O	-	-	O	O	O
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.														

5 Test Case Results

5.1 RF Power Output


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

Limits

No specific RF power output requirements in part 2.1046.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U=0.4$ dB.



Test Results

WCDMA Band IV		AV Conducted Power(dBm)		
		Channel 1312	Channel 1413	Channel 1513
		1712.4 (MHz)	1732.6 (MHz)	1752.6(MHz)
RMC	12.2k	23.56	23.56	23.50
	64k	23.42	23.50	23.37
	144k	23.41	23.40	23.36
	384k	23.40	23.39	23.35
HSDPA	Sub - Test 1	22.76	22.81	22.71
	Sub - Test 2	22.86	22.77	22.73
	Sub - Test 3	22.85	22.77	22.72
	Sub - Test 4	22.85	22.78	22.68
HSUPA	Sub - Test 1	23.20	23.11	23.07
	Sub - Test 2	23.24	23.21	23.16
	Sub - Test 3	23.24	23.20	23.16
	Sub - Test 4	22.78	22.73	22.78
	Sub - Test 5	22.86	22.69	22.67
DC-HSDPA	Sub - Test 1	23.43	23.43	23.37
	Sub - Test 2	23.41	23.42	23.36
	Sub - Test 3	22.90	22.91	22.85
	Sub - Test 4	22.89	22.90	22.84



LTE Band 4				AV Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				19957/1710.7	20175/1732.5	20393/1754.3
1.4MHz	QPSK	1	0	23.76	24.02	23.83
		1	2	23.56	23.92	23.99
		1	5	24.00	23.83	23.91
		3	0	23.82	23.68	23.89
		3	2	23.74	23.83	23.69
		3	3	23.89	23.86	23.75
		6	0	22.70	22.91	22.91
	16QAM	1	0	23.56	22.91	23.49
		1	2	23.60	22.88	23.32
		1	5	23.78	22.87	23.56
		3	0	22.60	22.68	22.92
		3	2	22.65	22.78	22.92
		3	3	22.71	22.89	22.83
		6	0	21.86	21.88	21.97
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				19965/1711.5	20175/1732.5	20385/1753.5
3MHz	QPSK	1	0	23.78	24.06	23.86
		1	7	23.59	23.97	24.03
		1	14	24.03	23.88	23.95
		8	0	22.92	22.80	23.02
		8	4	22.86	22.93	22.81
		8	7	22.99	22.97	22.85
		15	0	22.73	22.95	22.94
	16QAM	1	0	23.59	22.93	23.52
		1	7	23.63	22.93	23.36
		1	14	23.80	22.91	23.59
		8	0	21.71	21.81	22.04
		8	4	21.76	21.91	22.04
		8	7	21.81	22.01	21.96
		15	0	21.89	21.92	22.00
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				19975/1712.5	20175/1732.5	20375/1752.5
5MHz	QPSK	1	0	23.75	24.04	23.82
		1	13	23.57	23.93	24.00
		1	24	24.00	23.83	23.91
		12	0	22.89	22.75	22.98
		12	6	22.84	22.89	22.76
		12	13	22.97	22.95	22.81
		25	0	22.71	22.94	22.92



	16QAM	1	0	23.56	22.89	23.49
		1	13	23.60	22.91	23.33
		1	24	23.77	22.89	23.55
		12	0	21.69	21.77	22.01
		12	6	21.73	21.86	22.00
		12	13	21.78	21.96	21.92
		25	0	21.87	21.88	21.95
		Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)
10MHz						20000/1715
QPSK	1	0	23.77	24.05	23.85	
	1	25	23.60	23.98	24.04	
	1	49	24.02	23.87	23.94	
	25	0	22.92	22.80	23.02	
	25	13	22.87	22.94	22.80	
	25	25	22.99	22.99	22.86	
	50	0	22.79	22.96	22.96	
16QAM	1	0	23.58	22.92	23.51	
	1	25	23.63	22.95	23.36	
	1	49	23.80	22.91	23.58	
	25	0	21.72	21.82	22.05	
	25	13	21.75	21.90	22.03	
	25	25	21.81	22.01	21.96	
	50	0	21.90	21.93	21.99	
	Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)	
					15MHz	
QPSK	1	0	23.76	24.01	23.83	
	1	38	23.58	23.97	24.01	
	1	74	23.99	23.82	23.90	
	36	0	22.90	22.76	22.99	
	36	18	22.84	22.89	22.76	
	36	39	22.96	22.96	22.82	
	75	0	22.77	22.92	22.91	
16QAM	1	0	23.53	22.90	23.49	
	1	38	23.61	22.92	23.34	
	1	74	23.77	22.87	23.55	
	36	0	21.69	21.80	22.02	
	36	18	21.72	21.85	21.99	
	36	39	21.79	21.97	21.93	
	75	0	21.87	21.88	21.95	
	Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)	
					20MHz	
QPSK	1	0	23.73	23.97	23.80	
	1	50	23.57	23.93	23.99	



		1	99	23.97	23.81	23.87
		50	0	22.87	22.71	22.95
		50	25	22.82	22.85	22.73
		50	50	22.93	22.91	22.78
		100	0	22.74	22.87	22.87
	16QAM	1	0	23.51	22.86	23.44
		1	50	23.57	22.90	23.30
		1	99	23.75	22.84	23.53
		50	0	21.66	21.76	21.99
		50	25	21.69	21.83	21.96
		50	50	21.76	21.92	21.89
		100	0	21.85	21.84	21.92

LTE Band 12				AV Conducted Power(dBm)		
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				23017/699.7	23095/707.5	23173/715.3
1.4MHz	QPSK	1	0	23.32	23.88	23.58
		1	2	23.55	23.70	23.50
		1	5	23.52	23.31	23.50
		3	0	23.62	23.54	23.59
		3	2	23.81	23.61	23.51
		3	3	23.57	23.51	23.66
		6	0	22.54	22.53	22.65
	16QAM	1	0	22.53	22.31	23.13
		1	2	23.19	22.33	23.60
		1	5	22.70	22.19	22.81
		3	0	22.53	22.59	22.69
		3	2	22.70	22.57	22.78
		3	3	22.57	22.51	22.80
		6	0	21.44	21.60	21.69
3MHz	QPSK	RB size	RB offset	Channel/Frequency (MHz)		
				23025/700.5	23095/707.5	23165/714.5
		1	0	23.33	23.91	23.60
		1	7	23.59	23.76	23.55
		1	14	23.54	23.35	23.53
		8	0	22.72	22.66	22.72
		8	4	22.94	22.72	22.62
	16QAM	8	7	22.67	22.64	22.77
		15	0	22.63	22.58	22.70
		1	0	22.55	22.32	23.15



		1	14	22.72	22.23	22.83
		8	0	21.65	21.73	21.82
		8	4	21.80	21.69	21.89
		8	7	21.67	21.63	21.93
		15	0	21.48	21.65	21.71
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)		
				23035/701.5	23095/707.5	23155/713.5
5MHz	QPSK	1	0	23.32	23.87	23.58
		1	13	23.57	23.75	23.52
		1	24	23.51	23.30	23.49
		12	0	22.70	22.62	22.69
		12	6	22.91	22.67	22.58
		12	13	22.64	22.61	22.73
		25	0	22.61	22.54	22.65
	16QAM	1	0	22.50	22.30	23.13
		1	13	23.20	22.37	23.62
		1	24	22.69	22.19	22.80
		12	0	21.62	21.71	21.79
		12	6	21.77	21.64	21.85
		12	13	21.65	21.59	21.90
		25	0	21.45	21.60	21.67
10MHz	QPSK	RB size	RB offset	Channel/Frequency (MHz)		
				23060/704	23095/707.5	23130/711
		1	0	23.29	23.83	23.55
		1	25	23.56	23.71	23.50
		1	49	23.49	23.29	23.46
		25	0	22.67	22.57	22.65
		25	13	22.89	22.63	22.55
	16QAM	25	25	22.61	22.56	22.69
		50	0	22.58	22.49	22.61
		1	0	22.48	22.26	23.08
		1	25	23.16	22.35	23.58
		1	49	22.67	22.16	22.78
		25	0	21.59	21.67	21.76
		25	13	21.74	21.62	21.82
		25	25	21.62	21.54	21.86
		50	0	21.43	21.56	21.64



LTE Band 13				Conducted Power(dBm)								
Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)								
				23205/779.5	23230/782	23255/784.5						
5MHz	QPSK	1	0	23.56	23.41	23.36						
		1	13	23.31	23.60	23.58						
		1	24	23.33	21.39	23.46						
		12	0	22.58	22.49	22.43						
		12	6	22.50	22.67	22.65						
		12	13	22.49	22.60	22.54						
		25	0	22.56	22.69	22.59						
	16QAM	1	0	23.06	22.13	22.39						
		1	13	22.75	22.11	22.39						
		1	24	22.79	21.97	22.27						
		12	0	21.35	21.40	21.55						
		12	6	21.55	21.63	21.41						
		12	13	21.36	21.44	21.33						
		25	0	21.64	21.81	21.69						
10MHz	QPSK	Bandwidth	Modulation	RB size	RB offset	Channel/Frequency (MHz)						
						/	23230/782	/				
						/	23.61	/				
						/	23.78	/				
						/	23.44	/				
						/	22.56	/				
						/	22.52	/				
	16QAM					/	22.63	/				
						/	22.69	/				
						/	22.82	/				
						/	23.21	/				
						/	22.87	/				
						/	21.54	/				
						/	21.50	/				



5.2 Effective Isotropic Radiated Power

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.8 and ANSI/TIA-603-E (2016).
 - a) Connect the equipment as illustrated. Mount the equipment with the manufacturer specified antenna in a vertical orientation on a manufacturer specified mounting surface located on a non-conducting rotating platform of a RF anechoic chamber (preferred) or a standard radiation site.
 - b) Key the transmitter, then rotate the EUT 360° azimuthally and record spectrum analyzer power level (LVL) measurements at angular increments that are sufficiently small to permit resolution of all peaks. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading at each angular increment. (Note: several batteries may be needed to offset the effect of battery voltage droop, which should not exceed 5% of the manufactured specified battery voltage during transmission).
 - c) Replace the transmitter under test with a vertically polarized half-wave dipole (or an antenna whose gain is known relative to an ideal half-wave dipole). The center of the antenna should be at the same location as the center of the antenna under test.
 - d) Connect the antenna to a signal generator with a known output power and record the path loss (in dB) as LOSS. If a standard radiation test site is used, raise and lower the test antenna to obtain a maximum reading.
$$\text{LOSS} = \text{Generator Output Power (dBm)} - \text{Analyzer reading (dBm)}$$
 - e) Determine the effective radiated output power at each angular position from the readings in steps b) and d) using the following equation:
$$\text{ERP (dBm)} = \text{LVL (dBm)} + \text{LOSS (dB)}$$
 - f) The maximum ERP is the maximum value determined in the preceding step.
 - g) When calculating ERP, in addition to knowing the antenna radiation and matching characteristics, it is necessary to know the loss values of all elements (e.g.transmission line attenuation, mismatches, filters, combiners) interposed between the point where transmitter output power is measured, and the point where power is applied to the antenna. ERP can then be calculated as follows:
$$\text{ERP (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBd)}$$
where: dBd refers to gain relative to an ideal dipole.
$$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15 (\text{dB})$$

The RB allocation refers to section 5.1, using the maximum output power configuration.

Test setup



Note: Area side:2.4mX3.6m

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the worst case was recorded.



Limits

Rule Part 27.50(b) (10) specifies that “Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP”

Rule Part 27.50(c) (10) specifies that “Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP”

Rule Part 27.50(d) (4) specifies that “Fixed, mobile and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP”

Part 27.50(b)(10)Limit	$\leq 3 \text{ W}$ (34.77 dBm)
Part 27.50(c)(10)Limit	$\leq 3 \text{ W}$ (34.77 dBm)
Part 27.50(d)(4)Limit	$\leq 1 \text{ W}$ (30 dBm)

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 1.19 \text{ dB}$

**Test Results**

The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.

Mode	Channel	Frequency (MHz)	Polarization	EIRP (dBm)	Limit (dBm)	Conclusion
WCDMA Band IV	Low	1712.4	Horizontal	25.49	30	Pass
	Mid	1732.6	Horizontal	25.50	30	Pass
	High	1752.6	Horizontal	25.63	30	Pass

LTE Band 4						
Bandwidth	Channel	Frequency (MHz)	Polarization	EIRP (dBm)	Limit (dBm)	Conclusion
1.4 MHz (QPSK)	Low	1710.7	Horizontal	25.13	30	Pass
	Mid	1732.5	Horizontal	24.25	30	Pass
	High	1754.3	Horizontal	24.33	30	Pass
3 MHz (QPSK)	Low	1711.5	Horizontal	24.95	30	Pass
	Mid	1732.5	Horizontal	24.33	30	Pass
	High	1753.5	Horizontal	24.43	30	Pass
5 MHz (QPSK)	Low	1712.5	Horizontal	25.06	30	Pass
	Mid	1732.5	Horizontal	24.44	30	Pass
	High	1752.5	Horizontal	24.67	30	Pass
10 MHz (QPSK)	Low	1715	Horizontal	24.88	30	Pass
	Mid	1732.5	Horizontal	24.43	30	Pass
	High	1750	Horizontal	24.20	30	Pass
15 MHz (QPSK)	Low	1717.5	Horizontal	25.14	30	Pass
	Mid	1732.5	Horizontal	24.43	30	Pass
	High	1747.5	Horizontal	24.60	30	Pass
20 MHz (QPSK)	Low	1720	Horizontal	24.90	30	Pass
	Mid	1732.5	Horizontal	24.47	30	Pass
	High	1745	Horizontal	24.41	30	Pass
1.4 MHz (16QAM)	Low	1710.7	Horizontal	24.89	30	Pass
	Mid	1732.5	Horizontal	24.01	30	Pass
	High	1754.3	Horizontal	24.03	30	Pass
3 MHz (16QAM)	Low	1711.5	Horizontal	24.76	30	Pass
	Mid	1732.5	Horizontal	24.13	30	Pass
	High	1753.5	Horizontal	24.02	30	Pass
5 MHz (16QAM)	Low	1712.5	Horizontal	24.78	30	Pass
	Mid	1732.5	Horizontal	24.03	30	Pass
	High	1752.5	Horizontal	24.13	30	Pass
10 MHz (16QAM)	Low	1715	Horizontal	24.66	30	Pass
	Mid	1732.5	Horizontal	24.21	30	Pass
	High	1750	Horizontal	24.00	30	Pass



15 MHz (16QAM)	Low	1717.5	Horizontal	24.86	30	Pass
	Mid	1732.5	Horizontal	24.21	30	Pass
	High	1747.5	Horizontal	24.30	30	Pass
20 MHz (16QAM)	Low	1720	Horizontal	24.57	30	Pass
	Mid	1732.5	Horizontal	24.04	30	Pass
	High	1745	Horizontal	24.01	30	Pass

LTE Band 12						
Bandwidth	Channel	Frequency (MHz)	Polarization	ERP (dBm)	Limit (dBm)	Conclusion
1.4 MHz (QPSK)	Low	699.7	Horizontal	19.20	34.77	Pass
	Mid	707.5	Horizontal	19.49	34.77	Pass
	High	715.3	Horizontal	19.70	34.77	Pass
3 MHz (QPSK)	Low	700.5	Horizontal	19.29	34.77	Pass
	Mid	707.5	Horizontal	19.57	34.77	Pass
	High	714.5	Horizontal	19.55	34.77	Pass
5 MHz (QPSK)	Low	701.5	Horizontal	19.31	34.77	Pass
	Mid	707.5	Horizontal	19.57	34.77	Pass
	High	713.5	Horizontal	19.41	34.77	Pass
10 MHz (QPSK)	Low	704	Horizontal	19.16	34.77	Pass
	Mid	707.5	Horizontal	19.44	34.77	Pass
	High	711	Horizontal	19.51	34.77	Pass
1.4 MHz (16QAM)	Low	699.7	Horizontal	18.63	34.77	Pass
	Mid	707.5	Horizontal	18.84	34.77	Pass
	High	715.3	Horizontal	19.06	34.77	Pass
3 MHz (16QAM)	Low	700.5	Horizontal	18.72	34.77	Pass
	Mid	707.5	Horizontal	18.98	34.77	Pass
	High	714.5	Horizontal	18.96	34.77	Pass
5 MHz (16QAM)	Low	701.5	Horizontal	18.82	34.77	Pass
	Mid	707.5	Horizontal	18.87	34.77	Pass
	High	713.5	Horizontal	18.52	34.77	Pass
10 MHz (16QAM)	Low	704	Horizontal	18.59	34.77	Pass
	Mid	707.5	Horizontal	18.81	34.77	Pass
	High	711	Horizontal	18.88	34.77	Pass



LTE Band 13						
Bandwidth	Channel	Frequency (MHz)	Polarization	ERP (dBm)	Limit (dBm)	Conclusion
5MHz (QPSK)	Low	779.5	Horizontal	22.17	34.77	Pass
	Mid	782	Horizontal	21.87	34.77	Pass
	High	784.5	Horizontal	21.96	34.77	Pass
10MHz (QPSK)	Mid	782	Horizontal	22.41	34.77	Pass
5MHz (16QAM)	Low	779.5	Horizontal	21.82	34.77	Pass
	Mid	782	Horizontal	21.61	34.77	Pass
	High	784.5	Horizontal	21.73	34.77	Pass
10MHz (16QAM)	Mid	782	Horizontal	21.87	34.77	Pass

5.3 Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 51 kHz, VBW is set to 160 kHz for WCDMA Band IV.

RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 4/12 (1.4MHz).

RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 4/12 (3MHz).


RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 4/12/13 (5MHz).

RBW is set to 300 kHz, VBW is set to 1MHz for LTE Band 4/12/13 (10MHz).

RBW is set to 300 kHz, VBW is set to 1MHz for LTE Band 4 (15MHz/20MHz).

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U=624\text{Hz}$.



Test Result

Mode	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
WCDMA Band IV (RMC)	1312	1712.4	4.1071	4.678
	1413	1732.6	4.1193	4.679
	1513	1752.6	4.1284	4.703

LTE Band 4						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	19957	1710.7	1.1274	1.337
			20175	1732.5	1.1077	1.315
			20393	1754.3	1.1108	1.335
		3	19965	1711.5	2.7345	3.04
			20175	1732.5	2.7353	3.064
			20385	1753.5	2.7424	3.034
		5	19975	1712.5	4.5308	5.03
			20175	1732.5	4.514	4.976
			20375	1752.5	4.5177	5.022
		10	20000	1715	9.0214	10.04
			20175	1732.5	9.0081	10.02
			20350	1750	9.0092	10.08
		15	20025	1717.5	13.474	14.7
			20175	1732.5	13.438	14.56
			20325	1747.5	13.431	14.61
		20	20050	1720	17.896	19.21
			20175	1732.5	17.911	19.04
			20300	1745	17.861	19.36
16QAM	1.4	19957	1710.7	1.1224	1.35	
		20175	1732.5	1.1055	1.309	
		20393	1754.3	1.1183	1.342	
	3	19965	1711.5	2.7288	3.066	
		20175	1732.5	2.744	3.05	
		20385	1753.5	2.7395	3.045	
	5	19975	1712.5	4.5457	5.016	
		20175	1732.5	4.5193	5.001	
		20375	1752.5	4.5362	5.011	
	10	20000	1715	9.0281	9.965	
		20175	1732.5	9.0551	9.913	




			20350	1750	9.0086	9.943	
15		20025	1717.5	13.428	14.69		
		20175	1732.5	13.467	14.65		
		20325	1747.5	13.447	14.66		
	20	20050	1720	17.865	19.04		
20		20175	1732.5	17.91	19.22		
		20300	1745	17.873	19.48		

LTE Band 12						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	23017	699.7	1.1165	1.315
			23095	707.5	1.1136	1.335
			23173	715.3	1.1154	1.319
		3	23025	700.5	2.7422	3.059
			23095	707.5	2.7444	3.052
			23165	714.5	2.7392	3.072
		5	23035	701.5	4.5137	5.013
			23095	707.5	4.516	4.972
			23155	713.5	4.5174	5.013
	16QAM	10	23060	704	9.0155	10.1
			23095	707.5	9.0102	10.03
			23130	711	9.0204	9.967
		1.4	23017	699.7	1.1057	1.305
			23095	707.5	1.1087	1.343
			23173	715.3	1.1209	1.328
		3	23025	700.5	2.7444	3.083
			23095	707.5	2.7409	3.038
			23165	714.5	2.7411	3.053
		5	23035	701.5	4.5136	4.969
			23095	707.5	4.5062	4.964
			23155	713.5	4.5132	5.003
		10	23060	704	9.0129	10.01
			23095	707.5	8.9972	10.06
			23130	711	9.0348	10.03




LTE Band 13						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	5	23205	779.5	4.4928	4.95
			23230	782	4.533	5.062
			23255	784.5	4.5082	4.948
		10	23230	782	9.035	10.05
	16QAM	5	23205	779.5	4.5002	4.973
			23230	782	4.5258	5.029
			23255	784.5	4.5057	4.978
		10	23230	782	9.0513	10.08







LTE Band 4 QPSK 1.4MHz CH-Low




LTE Band 4 QPSK 3MHz CH-Low




LTE Band 4 QPSK 1.4MHz CH-Middle




LTE Band 4 QPSK 3MHz CH-Middle





LTE Band 4 QPSK 1.4MHz CH-High



LTE Band 4 QPSK 3MHz CH-High











LTE Band 4 16QAM 1.4MHz CH-Low




LTE Band 4 16QAM 3MHz CH-Low




LTE Band 4 16QAM 1.4MHz CH-Middle




LTE Band 4 16QAM 3MHz CH-Middle




LTE Band 4 16QAM 1.4MHz CH-High




LTE Band 4 16QAM 3MHz CH-High









LTE Band 4 16QAM 15MHz CH-Low




LTE Band 4 16QAM 20MHz CH-Low




LTE Band 4 16QAM 15MHz CH-Middle




LTE Band 4 16QAM 20MHz CH-Middle




LTE Band 4 16QAM 15MHz CH-High



LTE Band 4 16QAM 20MHz CH-High










LTE Band 12 16QAM 1.4MHz CH-Low




LTE Band 12 16QAM 3MHz CH-Low




LTE Band 12 16QAM 1.4MHz CH-Middle




LTE Band 12 16QAM 3MHz CH-Middle



LTE Band 12 16QAM 1.4MHz CH-High




LTE Band 12 16QAM 3MHz CH-High







LTE Band 12 16QAM 5MHz CH-Low




LTE Band 12 16QAM 10MHz CH-Low




LTE Band 12 16QAM 5MHz CH-Middle




LTE Band 12 16QAM 10MHz CH-Middle



LTE Band 12 16QAM 5MHz CH-High




LTE Band 12 16QAM 10MHz CH-High







LTE Band 13 QPSK 5MHz CH-Low




LTE Band 13 16QAM 5MHz CH-Low




LTE Band 13 QPSK 5MHz CH-Middle




LTE Band 13 16QAM 5MHz CH-Middle




LTE Band 13 QPSK 5MHz CH-High



LTE Band 13 16QAM 5MHz CH-High





5.4 Band Edge Compliance

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured.

The testing follows KDB 971168 D01 v03r01 Section 6.0

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.

2. The band edges of low and high channels for the highest RF powers were measured.

3. RBW is set to 51 kHz, VBW is set to 160 kHz for WCDMA Band IV.

RBW is set to 30 kHz, VBW is set to 100 kHz for LTE Band 4 (1.4MHz/3MHz).

RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 4 (5MHz).

RBW is set to 100 kHz, VBW is set to 300kHz for LTE Band 4 (10MHz).

RBW is set to 150 kHz, VBW is set to 510 kHz for LTE Band 4(15MHz).

RBW is set to 200 kHz, VBW is set to 620 kHz for LTE Band 4(20MHz)

RBW is set to 100 kHz, VBW is set to 300kHz for LTE Band 12(1.4MHz/3MHz/5MHz/10MHz).


on spectrum analyzer.

4. Set spectrum analyzer with RMS detector.

5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

6. Checked that all the results comply with the emission limit line.

Test Setup



Limits

Rule Part 27.53(h) specifies that "for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be



attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB"

Part 27.53(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Rule Part 27.53(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Part 27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684\text{dB}$.



Test Result

All the test traces in the plots shows the test results clearly.






LTE Band 4 QPSK 1.4MHz CH-Low, 1 RB




LTE Band 4 QPSK 1.4MHz CH-High, 1 RB




LTE Band 4 QPSK 1.4MHz CH-Low, 100%RB




LTE Band 4 QPSK 1.4MHz CH-High, 100%RB



LTE Band 4 QPSK 3MHz CH-Low, 1 RB



LTE Band 4 QPSK 3MHz CH-High, 1 RB






LTE Band 4 QPSK 3MHz CH-Low, 100%RB



LTE Band 4 QPSK 3MHz CH-High, 100%RB



LTE Band 4 QPSK 5MHz CH-Low, 1 RB



LTE Band 4 QPSK 5MHz CH-High, 1 RB



LTE Band 4 QPSK 5MHz CH-Low, 100%RB



LTE Band 4 QPSK 5MHz CH-High, 100%RB






LTE Band 4 QPSK 10MHz CH-Low, 1 RB



LTE Band 4 QPSK 10MHz CH-High, 1 RB




LTE Band 4 QPSK 10MHz CH-Low, 100%RB




LTE Band 4 QPSK 10MHz CH-High, 100%RB



LTE Band 4 QPSK 15MHz CH-Low, 1 RB



LTE Band 4 QPSK 15MHz CH-High, 1 RB






LTE Band 4 QPSK 15MHz CH-Low, 100%RB




LTE Band 4 QPSK 15MHz CH-High, 100%RB




LTE Band 4 QPSK 20MHz CH-Low, 1 RB



LTE Band 4 QPSK 20MHz CH-High, 1 RB



LTE Band 4 QPSK 20MHz CH-Low, 100%RB




LTE Band 4 QPSK 20MHz CH-High, 100%RB






LTE Band 4 16QAM 1.4MHz CH-Low, 1 RB




LTE Band 4 16QAM 1.4MHz CH-High, 1 RB




LTE Band 4 16QAM 1.4MHz CH-Low, 100%RB



LTE Band 4 16QAM 1.4MHz CH-High, 100%RB



LTE Band 4 16QAM 3MHz CH-Low, 1 RB




LTE Band 4 16QAM 3MHz CH-High, 1 RB






LTE Band 4 16QAM 3MHz CH-Low, 100%RB




LTE Band 4 16QAM 3MHz CH-High, 100%RB



LTE Band 4 16QAM 5MHz CH-Low, 1 RB



LTE Band 4 16QAM 5MHz CH-High, 1 RB



LTE Band 4 16QAM 5MHz CH-Low, 100%RB




LTE Band 4 16QAM 5MHz CH-High, 100%RB







LTE Band 4 16QAM 10MHz CH-Low, 1 RB



LTE Band 4 16QAM 10MHz CH-High, 1 RB




LTE Band 4 16QAM 10MHz CH-Low, 100%RB




LTE Band 4 16QAM 10MHz CH-High, 100%RB



LTE Band 4 16QAM 15MHz CH-Low, 1 RB




LTE Band 4 16QAM 15MHz CH-High, 1 RB






LTE Band 4 16QAM 15MHz CH-Low, 100%RB




LTE Band 4 16QAM 15MHz CH-High, 100%RB




LTE Band 4 16QAM 20MHz CH-Low, 1 RB



LTE Band 4 16QAM 20MHz CH-High, 1 RB



LTE Band 4 16QAM 20MHz CH-Low, 100%RB



LTE Band 4 16QAM 20MHz CH-High, 100%RB





LTE Band 12 QPSK 1.4MHz CH-Low, 1 RB



LTE Band 12 QPSK 1.4MHz CH-High, 1 RB



LTE Band 12 QPSK 1.4MHz CH-Low, 100%RB



LTE Band 12 QPSK 1.4MHz CH-High, 100%RB






LTE Band 12 QPSK 3MHz CH-Low, 1 RB



LTE Band 12 QPSK 3MHz CH-High, 1 RB



LTE Band 12 QPSK 3MHz CH-Low, 100%RB




LTE Band 12 QPSK 3MHz CH-High, 100%RB






LTE Band 12 QPSK 5MHz CH-Low, 1 RB



LTE Band 12 QPSK 5MHz CH-High, 1 RB



LTE Band 12 QPSK 5MHz CH-Low, 100%RB



LTE Band 12 QPSK 5MHz CH-High, 100%RB






LTE Band 12 QPSK 10MHz CH-Low, 1 RB



LTE Band 12 QPSK 10MHz CH-High, 1 RB



LTE Band 12 QPSK 10MHz CH-Low, 100%RB



LTE Band 12 QPSK 10MHz CH-High, 100%RB






LTE Band 12 16QAM 1.4MHz CH-Low, 1 RB




LTE Band 12 16QAM 1.4MHz CH-High, 1 RB



LTE Band 12 16QAM 1.4MHz CH-Low, 100%RB




LTE Band 12 16QAM 1.4MHz CH-High, 100%RB







LTE Band 12 16QAM 3MHz CH-Low, 1 RB



LTE Band 12 16QAM 3MHz CH-High, 1 RB




LTE Band 12 16QAM 3MHz CH-Low, 100%RB




LTE Band 12 16QAM 3MHz CH-High, 100%RB



LTE Band 12 16QAM 5MHz CH-Low, 1 RB




LTE Band 12 16QAM 5MHz CH-High, 1 RB






LTE Band 12 16QAM 5MHz CH-Low, 100%RB




LTE Band 12 16QAM 5MHz CH-High, 100%RB




LTE Band 12 16QAM 10MHz CH-Low, 1 RB



LTE Band 12 16QAM 10MHz CH-High, 1 RB



LTE Band 12 16QAM 10MHz CH-Low, 100%RB




LTE Band 12 16QAM 10MHz CH-High, 100%RB






LTE Band 13 QPSK 5MHz CH-Low, 1 RB




Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	775	-53.77	-36
2	775	776.9	100	776.9	-22.02	-13
3	776.9	777	30	776.998	-17.76	-13
5	787	787.1	30	787.0682	-53.94	-13
6	787.1	793	100	792.8171	-48.91	-13
7	793	805	6.8	793.492	-41.07	-36

LTE Band 13 QPSK 5MHz CH-High, 1 RB




Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	775.468	-60.99	-36
2	775	776.9	100	775.5301	-48.89	-13
3	776.9	777	30	776.9738	-54.26	-13
5	787	787.1	30	787.0053	-17.96	-13
6	787.1	793	100	787.1059	-22.59	-13
7	793	805	6.8	795.3218	-58.56	-36

LTE Band 13 QPSK 5MHz CH-Low, 100%RB



Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	774.988	-43.68	-36
2	775	776.9	100	776.9962	-23.75	-13
3	776.9	777	30	776.9969	-24.51	-13
5	787	787.1	30	787.0453	-42.04	-13
6	787.1	793	100	787.2593	-37.31	-13
7	793	805	6.8	793.072	-56.53	-36


LTE Band 13 QPSK 5MHz CH-High, 100%RB



Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	774.784	-50.1	-36
2	775	776.9	100	776.7404	-35.54	-13
3	776.9	777	30	776.9656	-40.70	-13
5	787	787.1	30	787.0014	-24.48	-13
6	787.1	793	100	787.1059	-23.79	-13
7	793	805	6.8	793.208	-49.36	-36




LTE Band 13 QPSK 10MHz CH-Low, 1 RB




Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	774.976	-53.98	-35
2	775	778.9	100	776.8896	-31.41	-13
3	778.9	777	30	776.9944	-30.8	-13
5	787	787.1	30	787.0235	-49.49	-13
6	787.1	793	100	787.1059	-44.99	-13
7	793	805	6.8	795.232	-48.14	-35

LTE Band 13 QPSK 10MHz CH-Low, 100%RB



Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	774.916	-42.99	-35
2	775	778.9	100	776.8791	-25.89	-13
3	778.9	777	30	776.9851	-29.94	-13
5	787	787.1	30	787.0283	-29.13	-13
6	787.1	793	100	787.1177	-26.22	-13
7	793	805	6.8	795.144	-44.94	-35


LTE Band 13 QPSK 10MHz CH-Middle, 1 RB



Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	773.164	-57.28	-35
2	775	778.9	100	776.8582	-46.92	-13
3	778.9	777	30	776.9995	-49.68	-13
5	787	787.1	30	787.0015	-30.6	-13
6	787.1	793	100	787.1118	-28.39	-13
7	793	805	6.8	795.232	-47.32	-35




LTE Band 13 16QAM 5MHz CH-Low, 1 RB




Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	774.968	-54.29	-35
2	775	776.9	100	776.9	-22.13	-13
3	776.9	777	30	776.9966	-18.3	-13
5	787	787.1	30	787.0038	-54.17	-13
6	787.1	793	100	787.5396	-48.36	-13
7	793	805	6.8	794.2986	-41.1	-35

LTE Band 13 16QAM 5MHz CH-High, 1 RB




Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	772.584	-41.12	-35
2	775	776.9	100	776.4136	-48.8	-13
3	776.9	777	30	776.9003	-54.25	-13
5	787	787.1	30	787.0001	-18.41	-13
6	787.1	793	100	787.1059	-23.37	-13
7	793	805	6.8	795.3208	-57.48	-35

LTE Band 13 16QAM 5MHz CH-Low, 100%RB



Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	775	-44.29	-35
2	775	776.9	100	776.8943	-24.45	-13
3	776.9	777	30	776.996	-24.94	-13
5	787	787.1	30	787.0193	-42.87	-13
6	787.1	793	100	787.4068	-38.34	-13
7	793	805	6.8	793.456	-57.67	-35

LTE Band 13 16QAM 5MHz CH-High, 100%RB



Range	Start (MHz)	Stop (MHz)	RBW (MHz)	Spur Freq (MHz)	Spur Level (dBm)	Limit (dBm)
1	763	775	6.8	774.544	-51.05	-35
2	775	776.9	100	776.7955	-36.4	-13
3	776.9	777	30	776.9568	-41.65	-13
5	787	787.1	30	787.0004	-25.01	-13
6	787.1	793	100	787.1059	-26.32	-13
7	793	805	6.8	793.18	-51.62	-35

