FCC 47 CFR MPE REPORT

Zylux Acoustic Corporation

Big Blue 200

Model Number: AR108A4BKA

FCC ID: XN6-AR108A4BKA

Prepared for: Zylux Acoustic Corporation

3F, 22, Lane 35, Jihu Road Taipei Neihu Technology

Park, 114 Taipei Taiwan

Prepared By: EST Technology Co., Ltd.

San Tun Management Zone, Houjie District,

Dongguan, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1703035 Date of Test: March 04 ~ 23, 2017 Date of Report: March 23, 2017



Maximum Permissible Exposure

1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a) Limits for Occupational / Controlled Exposure

			1	
Frequency	Electric Field	Magnetic	Power	Averaging
Range (MHz)	Strength E)	Field Strength	Density (S)	Times E
	(V/m)	(H) (A/m)	(mW/cm2)	2, H 2 or
				S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b). Limits for General Population / Uncontrolled Exposure

Frequency	Electric Field	Magnetic	Power	Averaging
Range (MHz)	Strength E)	Field Strength	Density (S)	Times E
	(V/m)	(H) (A/m)	(mW/cm2)	2 , H 2 or
				S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2. MPE Calculation Method

E (V/m) = (30*P*G) 0.5/d Power Density: Pd (W/m2) = E2/377

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

Pd = (30*P*G) / (377*d2)

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



3、Calculated Result and Limit

3.1 Antenna 1

					Ante	nna gain		Limited	
Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	(dBi)	(Linear)	Power Density (S) (mW /cm2)	of Power Density (S) (mW /cm2)	Test Result
	2402	5.40	3.467	5±2	3.24	2.109	0.00210	1	Compiles
GFSK	2441	5.70	3.715	5±2	3.24	2.109	0.00210	1	Compiles
	2480	5.60	3.631	5±2	3.24	2.109	0.00210	1	Compiles
	2402	9.00	7.943	9±2	3.24	2.109	0.00528	1	Compiles
8-DPSK	2441	8.90	7.762	8±2	3.24	2.109	0.00419	1	Compiles
	2480	8.70	7.413	8±2	3.24	2.109	0.00419	1	Compiles
	2402	2.81	1.910	2 ± 2	3.24	2.109	0.00105	1	Compiles
BLE	2440	2.57	1.807	2 ± 2	3.24	2.109	0.00105	1	Compiles
	2480	2.42	1.746	2±2	3.24	2.109	0.00105	1	Compiles
IDDD	2412	10.35	10.839	10 ± 2	3.24	2.109	0.00665	1	Compiles
IEEE	2437	10.43	11.041	10±2	3.24	2.109	0.00665	1	Compiles
802.11b	2462	10.05	10.116	10±2	3.24	2.109	0.00665	1	Compiles
IEEE	2412	8.54	7.145	8±2	3.24	2.109	0.00419	1	Compiles
IEEE	2437	8.04	6.368	8±2	3.24	2.109	0.00419	1	Compiles
802.11g	2462	8.13	6.501	8±2	3.24	2.109	0.00419	1	Compiles
IEEE	2412	7.69	5.875	7±2	3.24	2.109	0.00333	1	Compiles
802.11n	2437	7.08	5.105	7±2	3.24	2.109	0.00333	1	Compiles
HT20	2462	7.72	5.916	7±2	3.24	2.109	0.00333	1	Compiles



					Ante	nna gain		Limited	
		Peak	Peak	Torgot			Power	of	
Mode	Frequency	output	output	Target power			Density (S)	Power Density	Test
Mode	(MHz)	power	power	(dBm)	(dBi)	(Linear)	(mW	(S)	Result
		(dBm)	(mW)	(dDin)			/cm2)	(mW	
							/CIII2)	/cm2)	
	5180	13.70	23.442	13±2	3.12	2.051	0.01290	1	Compiles
	5200	13.90	24.547	13±2	3.12	2.051	0.01290	1	Compiles
	5240	13.80	23.988	13±2	3.12	2.051	0.01290	1	Compiles
	5260	14.20	26.303	14 ± 2	3.12	2.051	0.01625	1	Compiles
	5300	14.20	26.303	14±2	3.12	2.051	0.01625	1	Compiles
IEEE	5320	14.50	28.184	14 ± 2	3.12	2.051	0.01625	1	Compiles
802.11a	5500	14.80	30.200	14 ± 2	3.12	2.051	0.01625	1	Compiles
	5580	14.70	29.512	14 ± 2	3.12	2.051	0.01625	1	Compiles
	5700	14.80	30.200	14 ± 2	3.12	2.051	0.01625	1	Compiles
	5745	15.10	32.359	15±2	3.12	2.051	0.02045	1	Compiles
	5785	15.50	35.481	15±2	3.12	2.051	0.02045	1	Compiles
	5825	15.30	33.884	15 ± 2	3.12	2.051	0.02045	1	Compiles
	5180	13.60	22.909	13 ± 2	3.12	2.051	0.01290	1	Compiles
	5200	13.60	22.909	13 ± 2	3.12	2.051	0.01290	1	Compiles
	5240	13.90	24.547	13 ± 2	3.12	2.051	0.01290	1	Compiles
	5260	14.30	26.915	14 ± 2	3.12	2.051	0.01625	1	Compiles
IEEE	5300	14.60	28.840	14 ± 2	3.12	2.051	0.01625	1	Compiles
IEEE 802.11n	5320	14.60	28.840	14 ± 2	3.12	2.051	0.01625	1	Compiles
HT20	5500	14.90	30.903	14 ± 2	3.12	2.051	0.01625	1	Compiles
11120	5580	14.50	28.184	14±2	3.12	2.051	0.01625	1	Compiles
	5700	14.80	30.200	14±2	3.12	2.051	0.01625	1	Compiles
	5745	15.00	31.623	15±2	3.12	2.051	0.02045	1	Compiles
	5785	15.10	32.359	15±2	3.12	2.051	0.02045	1	Compiles
	5825	15.60	36.308	14±2	3.12	2.051	0.02045	1	Compiles

					Ante	nna gain		Limited	
		D 1	D 1				Power	of	
		Peak	Peak	Target			Density	Power	
Mode	Frequency	output	output	power	(15.)	(7.	(S)	Density	Test
	(MHz)	power	power	(dBm)	(dBi)	(Linear)	(mW	(S)	Result
		(dBm)	(mW)				/cm2)	(mW	
								/cm2)	
	5180	13.50	22.387	13±2	3.12	2.051	0.01290	1	Compiles
	5200	13.60	22.909	13±2	3.12	2.051	0.01290	1	Compiles
	5240	14.00	25.119	14±2	3.12	2.051	0.01625	1	Compiles
	5260	14.00	25.119	14±2	3.12	2.051	0.01625	1	Compiles
IEEE	5300	14.50	28.184	14±2	3.12	2.051	0.01625	1	Compiles
802.11ac	5320	14.40	27.542	14±2	3.12	2.051	0.01625	1	Compiles
20	5500	14.90	30.903	14±2	3.12	2.051	0.01625	1	Compiles
20	5580	14.40	27.542	14 ± 2	3.12	2.051	0.01625	1	Compiles
	5700	14.60	28.840	14 ± 2	3.12	2.051	0.01625	1	Compiles
	5745	15.00	31.623	15 ± 2	3.12	2.051	0.02045	1	Compiles
	5785	15.30	33.884	15 ± 2	3.12	2.051	0.02045	1	Compiles
	5825	15.40	34.674	15 ± 2	3.12	2.051	0.02045	1	Compiles
	5190	9.70	9.333	9±2	3.12	2.051	0.00514	1	Compiles
	5230	10.00	10.000	10 ± 2	3.12	2.051	0.00647	1	Compiles
	5270	11.40	13.804	11±2	3.12	2.051	0.00814	1	Compiles
IEEE	5310	11.30	13.490	11 ± 2	3.12	2.051	0.00814	1	Compiles
802.11n	5510	12.80	19.055	12±2	3.12	2.051	0.01025	1	Compiles
HT40	5550	12.90	19.498	12 ± 2	3.12	2.051	0.01025	1	Compiles
	5670	12.70	18.621	12±2	3.12	2.051	0.01025	1	Compiles
	5755	15.50	35.481	15 ± 2	3.12	2.051	0.02045	1	Compiles
	5795	15.50	35.481	15±2	3.12	2.051	0.02045	1	Compiles
	5190	9.70	9.333	9±2	3.12	2.051	0.00514	1	Compiles
	5230	9.70	9.333	9±2	3.12	2.051	0.00514	1	Compiles
	5270	11.00	12.589	11±2	3.12	2.051	0.00814	1	Compiles
IEEE	5310	10.80	12.023	10±2	3.12	2.051	0.00647	1	Compiles
802.11ac	5510	12.70	18.621	12±2	3.12	2.051	0.01025	1	Compiles
40	5550	12.70	18.621	12±2	3.12	2.051	0.01025	1	Compiles
	5670	12.80	19.055	12±2	3.12	2.051	0.01025	1	Compiles
	5755	15.40	34.674	15±2	3.12	2.051	0.02045	1	Compiles
	5795	15.40	34.674	15±2	3.12	2.051	0.02045	1	Compiles



					Ante	nna gain		Limited	
Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	(dBi)	(Linear)	Power Density (S) (mW /cm2)	of Power Density (S) (mW /cm2)	Test Result
IEEE	5210	6.30	4.266	6±2	3.12	2.051	0.00257	1	Compiles
802.11ac	5290	7.00	5.012	7 ± 2	3.12	2.051	0.00324	1	Compiles
802.11ac	5530	10.60	11.482	10 ± 2	3.12	2.051	0.00647	1	Compiles
00	5775	11.10	12.882	11±2	3.12	2.051	0.00814	1	Compiles



3.2 Antenna 2

	111a Z				1		l .	1	
					Ante	nna gain		Limited	
	Frequency	Peak	Peak	Target			Power Density	of Power	T
Mode		output	output	power	(15.1)		(S)	Density	Test
	(MHz)	power	power	(dBm)	(dBi)	(Linear)	(mW	(S)	Result
		(dBm)	(mW)				/cm2)	(mW	
								/cm2)	
	2402	5.90	3.890	5±2	3.24	2.109	0.00210	1	Compiles
GFSK	2441	5.80	3.802	5±2	3.24	2.109	0.00210	1	Compiles
	2480	5.50	3.548	5 ± 2	3.24	2.109	0.00210	1	Compiles
	2402	9.00	7.943	9±2	3.24	2.109	0.00528	1	Compiles
8-DPSK	2441	8.90	7.762	8 ± 2	3.24	2.109	0.00419	1	Compiles
	2480	8.70	7.413	8 ± 2	3.24	2.109	0.00419	1	Compiles
	2402	2.05	1.603	2 ± 2	3.24	2.109	0.00105	1	Compiles
BLE	2440	2.39	1.734	2 ± 2	3.24	2.109	0.00105	1	Compiles
	2480	2.21	1.663	2 ± 2	3.24	2.109	0.00105	1	Compiles
IEEE	2412	10.51	11.246	10 ± 2	3.24	2.109	0.00665	1	Compiles
802.11b	2442	10.55	11.350	10 ± 2	3.24	2.109	0.00665	1	Compiles
802.110	2472	10.92	12.359	10 ± 2	3.24	2.109	0.00665	1	Compiles
IEEE	2412	8.45	6.998	8±2	3.24	2.109	0.00419	1	Compiles
802.11g	2442	8.14	6.516	8±2	3.24	2.109	0.00419	1	Compiles
602.11g	2472	8.86	7.691	8±2	3.24	2.109	0.00419	1	Compiles
IEEE	2412	7.14	5.176	7±2	3.24	2.109	0.00333	1	Compiles
802.11n	2442	7.93	6.209	7±2	3.24	2.109	0.00333	1	Compiles
HT20	2472	7.57	5.715	7±2	3.24	2.109	0.00333	1	Compiles



					Ante	nna gain		Limited	
Mode	Frequency (MHz)	Peak output	Peak output	Target power			Power Density (S)	of Power Density	Test
Wode		power (dBm)	power (mW)	(dBm)	(dBi)	(Linear)	(mW /cm2)	(S) (mW /cm2)	Result
	5180	14.10	25.704	14±2	3.12	2.051	0.01625	1	Compiles
	5200	13.90	24.547	13±2	3.12	2.051	0.01290	1	Compiles
	5240	13.90	24.547	13±2	3.12	2.051	0.01290	1	Compiles
	5260	14.20	26.303	14±2	3.12	2.051	0.01290	1	Compiles
	5300	14.70	29.512	14±2	3.12	2.051	0.01625	1	Compiles
IEEE	5320	14.80	30.200	14±2	3.12	2.051	0.01625	1	Compiles
802.11a	5500	14.90	30.903	14±2	3.12	2.051	0.01625	1	Compiles
	5580	14.50	28.184	14±2	3.12	2.051	0.01625	1	Compiles
	5700	14.50	28.184	14±2	3.12	2.051	0.01625	1	Compiles
	5745	15.00	31.623	15 ± 2	3.12	2.051	0.02045	1	Compiles
	5785	15.10	32.359	15 ± 2	3.12	2.051	0.02045	1	Compiles
	5825	14.80	30.200	14 ± 2	3.12	2.051	0.01625	1	Compiles
	5180	13.70	23.442	13 ± 2	3.12	2.051	0.01290	1	Compiles
	5200	14.00	25.119	14±2	3.12	2.051	0.01625	1	Compiles
	5240	14.10	25.704	14±2	3.12	2.051	0.01625	1	Compiles
	5260	14.20	26.303	14 ± 2	3.12	2.051	0.01625	1	Compiles
IDDD	5300	14.30	26.915	14 ± 2	3.12	2.051	0.01625	1	Compiles
IEEE 802.11n	5320	14.70	29.512	14 ± 2	3.12	2.051	0.01625	1	Compiles
HT20	5500	15.00	31.623	15 ± 2	3.12	2.051	0.02045	1	Compiles
11120	5580	14.30	26.915	14±2	3.12	2.051	0.01625	1	Compiles
	5700	14.10	25.704	14±2	3.12	2.051	0.01625	1	Compiles
	5745	14.50	28.184	14±2	3.12	2.051	0.01625	1	Compiles
	5785	14.70	29.512	14±2	3.12	2.051	0.01625	1	Compiles
	5825	14.90	30.903	14±2	3.12	2.051	0.01625	1	Compiles

					Antei	nna gain		Limited	
					7 HICH	Ina gam	Power	of	
		Peak	Peak	Target			Density	Power	
Mode	Frequency	output	output	power			(S)	Density	Test
	(MHz)	power	power	(dBm)	(dBi)	(Linear)	(mW	(S)	Result
		(dBm)	(mW)				/cm2)	(mW	
							, (1112)	/cm2)	
	5180	13.90	24.547	13±2	3.12	2.051	0.01290	1	Compiles
	5200	13.80	23.988	13±2	3.12	2.051	0.01290	1	Compiles
	5240	13.90	24.547	13±2	3.12	2.051	0.01290	1	Compiles
	5260	14.00	25.119	14±2	3.12	2.051	0.01625	1	Compiles
	5300	14.40	27.542	14±2	3.12	2.051	0.01625	1	Compiles
IEEE	5320	14.80	30.200	14±2	3.12	2.051	0.01625	1	Compiles
802.11ac	5500	14.50	28.184	14±2	3.12	2.051	0.01625	1	Compiles
20	5580	14.10	25.704	14±2	3.12	2.051	0.01625	1	Compiles
	5700	13.90	24.547	13±2	3.12	2.051	0.01290	1	Compiles
	5745	14.60	28.840	14±2	3.12	2.051	0.01625	1	Compiles
	5785	14.60	28.840	14±2	3.12	2.051	0.01625	1	Compiles
	5825	14.80	30.200	14±2	3.12	2.051	0.01625	1	Compiles
	5190	7.80	6.026	7±2	3.12	2.051	0.00324	1	Compiles
	5230	8.00	6.310	8±2	3.12	2.051	0.00408	1	Compiles
	5270	10.10	10.233	10±2	3.12	2.051	0.00647	1	Compiles
IEEE	5310	10.50	11.220	10±2	3.12	2.051	0.00647	1	Compiles
802.11n	5510	12.60	18.197	12±2	3.12	2.051	0.01025	1	Compiles
HT40	5550	12.40	17.378	12±2	3.12	2.051	0.01025	1	Compiles
	5670	12.40	17.378	12±2	3.12	2.051	0.01025	1	Compiles
	5755	15.00	31.623	15±2	3.12	2.051	0.02045	1	Compiles
	5795	14.90	30.903	14±2	3.12	2.051	0.01625	1	Compiles
	5190	7.90	6.166	7±2	3.12	2.051	0.00324	1	Compiles
	5230	7.80	6.026	7±2	3.12	2.051	0.00324	1	Compiles
	5270	9.90	9.772	9±2	3.12	2.051	0.00514	1	Compiles
IEEE	5310	10.10	10.233	10±2	3.12	2.051	0.00647	1	Compiles
802.11ac	5510	12.50	17.783	12±2	3.12	2.051	0.01025	1	Compiles
40	5550	12.10	16.218	12±2	3.12	2.051	0.01025	1	Compiles
	5670	12.30	16.982	12±2	3.12	2.051	0.01025	1	Compiles
	5755	12.40	17.378	12±2	3.12	2.051	0.01025	1	Compiles
	5795	14.70	29.512	14±2	3.12	2.051	0.01625	1	Compiles



					Ante	nna gain		Limited	
Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	(dBi)	(Linear)	Power Density (S) (mW /cm2)	of Power Density (S) (mW /cm2)	Test Result
IEEE	5210	5.60	3.631	5±2	3.12	2.051	0.00205	1	Compiles
802.11ac	5290	7.10	5.129	7 ± 2	3.12	2.051	0.00324	1	Compiles
802.11ac 80	5530	10.20	10.471	10±2	3.12	2.051	0.00647	1	Compiles
00	5775	10.40	10.965	10±2	3.12	2.051	0.00647	1	Compiles

3.3 Note:

- A、 2.4 and 5GHz bands are share an antenna, Cann't both the 2.4 and 5 GHz bands operate simultaneously;
 - $B_{\, {}^{\circ}}$ Antenna 1 and 2 cann't both operate simultaneously $_{\circ}$