# **FCC 47 CFR MPE REPORT**

**Zylux Acoustic Corporation** 

Big Blue 100

Model Number: AD107A4BKA

FCC ID: XN6-AD107A4BKA

Prepared for: Zylux Acoustic Corporation

3F, 22, Lane 35, Jihu Road Taipei Neihu Technology

Park, 114 Taipei Taiwan

Prepared By: EST Technology Co., Ltd.

San Tun Management Zone, Houjie District,

Dongguan, China

Tel: 86-769-83081888-808

Report Number: ESTE-R1702011

Date of Test : January 04 ~ February 06, 2017

Date of Report: February 07, 2017

# **Maximum Permissible Exposure**

# 1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

### (a) Limits for Occupational / Controlled Exposure

Frequency	Electric Field	Magnetic	Power	Averaging
Range (MHz)	Strength E)	Field Strength	Density (S)	Times   E
	(V/m)	(H) (A/m)	(mW/cm2)	2 ,   H   2 or
				S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

# (b). Limits for General Population / Uncontrolled Exposure

Frequency	Electric Field	Magnetic	Power	Averaging
Range (MHz)	Strength E)	Field Strength	Density (S)	Times   E
	(V/m)	(H) (A/m)	(mW/cm2)	2 ,   H   2 or
				S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

#### 2. MPE Calculation Method

E (V/m) = (30\*P\*G) 0.5/d Power Density: Pd (W/m2) = E2/377

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

Pd = (30\*P\*G) / (377\*d2)

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained



## 3. Calculated Result and Limit

## 3.1 Antenna 1

					Antei	nna gain		Limited	
Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	(dBi)	(Linear)	Power Density (S) (mW /cm2)	of Power Density (S) (mW /cm2)	Test Result
	2402	0.81	1.205	$0\pm 2$	3.24	2.109	0.00066	1	Compiles
GFSK	2441	0.34	1.081	0±2	3.24	2.109	0.00066	1	Compiles
	2480	-0.20	0.955	-1±2	3.24	2.109	0.00053	1	Compiles
	2402	1.26	1.337	$1\pm2$	3.24	2.109	0.00084	1	Compiles
8-DPSK	2441	0.84	1.213	$0\pm2$	3.24	2.109	0.00066	1	Compiles
	2480	0.36	1.086	$0\pm2$	3.24	2.109	0.00066	1	Compiles
	2402	1.14	1.300	$1\pm2$	3.24	2.109	0.00084	1	Compiles
BLE	2440	0.56	1.138	0±2	3.24	2.109	0.00066	1	Compiles
	2480	0.25	1.059	$0\pm 2$	3.24	2.109	0.00066	1	Compiles
IEEE	2412	13.10	20.417	$13\pm 2$	3.24	2.109	0.01327	1	Compiles
802.11b	2437	13.70	23.442	$13\pm 2$	3.24	2.109	0.01327	1	Compiles
802.110	2462	13.57	22.751	13±2	3.24	2.109	0.01327	1	Compiles
IEEE	2412	10.57	11.403	10±2	3.24	2.109	0.00665	1	Compiles
	2437	10.13	10.304	$10\pm 2$	3.24	2.109	0.00665	1	Compiles
802.11g	2462	10.36	10.864	10±2	3.24	2.109	0.00665	1	Compiles
IEEE	2412	9.11	8.1470	9±2	3.24	2.109	0.00528	1	Compiles
802.11n	2437	9.68	9.290	9±2	3.24	2.109	0.00528	1	Compiles
HT20	2462	9.29	8.492	9±2	3.24	2.109	0.00528	1	Compiles



					Ante	nna gain		Limited	
Mode	Frequency (MHz)	Peak output power	Peak output power	Target power (dBm)	(dBi)	(Linear)	Power Density (S) (mW	of Power Density (S)	Test Result
		(dBm) (mW)				/cm2)	(mW /cm2)		
	5180	14.43	27.733	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5200	14.42	27.669	14±2	3.12	2.051	0.01625	1	Compiles
	5240	14.01	25.177	14±2	3.12	2.051	0.01625	1	Compiles
	5260	14.17	26.122	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5300	13.70	23.442	$13\pm 2$	3.12	2.051	0.01290	1	Compiles
IEEE	5320	13.72	23.550	$13\pm 2$	3.12	2.051	0.01290	1	Compiles
802.11a	5500	14.71	29.580	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5580	14.75	29.854	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5700	14.57	28.642	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5745	15.02	31.769	$15\pm2$	3.12	2.051	0.02045	1	Compiles
	5785	15.08	32.211	$15 \pm 2$	3.12	2.051	0.02045	1	Compiles
	5825	15.07	32.137	$15 \pm 2$	3.12	2.051	0.02045	1	Compiles
	5180	14.54	28.445	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5200	14.09	25.645	14±2	3.12	2.051	0.01625	1	Compiles
	5240	14.28	26.792	14±2	3.12	2.051	0.01625	1	Compiles
	5260	14.10	25.704	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
IEEE	5300	13.36	21.677	$13 \pm 2$	3.12	2.051	0.01290	1	Compiles
IEEE 802.11n	5320	13.72	23.550	$13 \pm 2$	3.12	2.051	0.01290	1	Compiles
HT20	5500	14.68	29.377	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
11120	5580	14.60	28.840	14±2	3.12	2.051	0.01625	1	Compiles
	5700	14.57	28.642	14±2	3.12	2.051	0.01625	1	Compiles
	5745	14.60	28.840	14±2	3.12	2.051	0.01625	1	Compiles
	5785	15.09	32.285	15±2	3.12	2.051	0.02045	1	Compiles
	5825	14.95	31.261	14±2	3.12	2.051	0.01625	1	Compiles

					Antei	nna gain		Limited	
					7 HICH	Ina gam	Power	of	
		Peak	Peak	Target			Density	Power	
Mode	Frequency (MHz)	output power	output power	power			(S)	Density	Test
1,1000				(dBm)	(dBi)	(Linear)	(mW	(S)	Result
		(dBm)	(mW)	( ==== )			/cm2)	(mW	
							, (1112)	/cm2)	
	5180	14.03	25.293	14±2	3.12	2.051	0.01625	1	Compiles
	5200	14.08	25.586	14±2	3.12	2.051	0.01625	1	Compiles
	5240	13.60	22.909	13±2	3.12	2.051	0.01290	1	Compiles
	5260	13.89	24.491	13±2	3.12	2.051	0.01290	1	Compiles
	5300	13.77	23.823	13±2	3.12	2.051	0.01290	1	Compiles
IEEE	5320	13.65	23.174	13±2	3.12	2.051	0.01290	1	Compiles
802.11ac	5500	14.36	27.290	14±2	3.12	2.051	0.01625	1	Compiles
20	5580	13.65	23.174	13±2	3.12	2.051	0.01290	1	Compiles
	5700	14.68	29.377	14±2	3.12	2.051	0.01625	1	Compiles
	5745	14.71	29.580	14±2	3.12	2.051	0.01625	1	Compiles
	5785	15.03	31.842	15±2	3.12	2.051	0.02045	1	Compiles
	5825	14.93	31.117	14±2	3.12	2.051	0.01625	1	Compiles
	5190	10.23	10.544	10±2	3.12	2.051	0.00647	1	Compiles
	5230	10.00	10.000	10±2	3.12	2.051	0.00647	1	Compiles
	5270	11.40	13.804	11±2	3.12	2.051	0.00814	1	Compiles
IEEE	5310	11.41	13.836	11±2	3.12	2.051	0.00814	1	Compiles
802.11n	5510	11.30	13.490	11±2	3.12	2.051	0.00814	1	Compiles
HT40	5550	11.46	13.996	11±2	3.12	2.051	0.00814	1	Compiles
	5670	11.30	13.490	11±2	3.12	2.051	0.00814	1	Compiles
	5755	15.22	33.266	15±2	3.12	2.051	0.02045	1	Compiles
	5795	14.99	31.550	14±2	3.12	2.051	0.01625	1	Compiles
	5190	12.02	15.922	12±2	3.12	2.051	0.01025	1	Compiles
	5230	11.82	15.205	11±2	3.12	2.051	0.00814	1	Compiles
	5270	11.77	15.031	11±2	3.12	2.051	0.00814	1	Compiles
IEEE	5310	11.29	13.459	11±2	3.12	2.051	0.00814	1	Compiles
802.11ac	5510	11.28	13.428	11±2	3.12	2.051	0.00814	1	Compiles
40	5550	11.63	14.555	11±2	3.12	2.051	0.00814	1	Compiles
	5670	11.28	13.428	11±2	3.12	2.051	0.00814	1	Compiles
	5755	15.14	32.659	15±2	3.12	2.051	0.02045	1	Compiles
	5795	14.94	31.189	14±2	3.12	2.051	0.01625	1	Compiles



					Ante	nna gain		Limited	
Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	(dBi)	(Linear)	Power Density (S) (mW /cm2)	of Power Density (S) (mW	Test Result
	5210	0.60	7.244	0   2	2.12	2.051	0.00400	/cm2)	C 11
IEEE	5210	8.60	7.244	8±2	3.12	2.051	0.00408	1	Compiles
802.11ac	5290	8.52	7.112	$8\pm2$	3.12	2.051	0.00408	1	Compiles
80	5530	10.34	10.814	$10\pm 2$	3.12	2.051	0.00647	1	Compiles
80	5775	10.51	11.246	10±2	3.12	2.051	0.00647	1	Compiles

### 3.2 Antenna 2

					Antei	nna gain		Limited	
Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	(dBi)	(Linear)	Power Density (S) (mW /cm2)	of Power Density (S) (mW /cm2)	Test Result
	2402	1.20	1.318	1±2	3.24	2.109	0.00084	1	Compiles
GFSK	2441	0.71	1.178	$0\pm2$	3.24	2.109	0.00066	1	Compiles
	2480	0.17	1.040	$0\pm 2$	3.24	2.109	0.00066	1	Compiles
	2402	1.91	1.552	$1\pm2$	3.24	2.109	0.00084	1	Compiles
8-DPSK	2441	1.51	1.416	$1\pm2$	3.24	2.109	0.00084	1	Compiles
	2480	0.94	1.242	0±2	3.24	2.109	0.00066	1	Compiles
	2402	1.17	1.309	1±2	3.24	2.109	0.00084	1	Compiles
BLE	2440	0.25	1.059	$0\pm2$	3.24	2.109	0.00066	1	Compiles
	2480	0.06	1.014	$0\pm2$	3.24	2.109	0.00066	1	Compiles
IEEE	2412	13.37	21.727	$13\pm 2$	3.24	2.109	0.01327	1	Compiles
802.11b	2442	13.71	23.496	$13\pm 2$	3.24	2.109	0.01327	1	Compiles
802.110	2472	13.34	21.577	$13\pm 2$	3.24	2.109	0.01327	1	Compiles
IEEE	2412	10.85	12.162	$10\pm 2$	3.24	2.109	0.00665	1	Compiles
802.11g	2442	10.44	11.066	10±2	3.24	2.109	0.00665	1	Compiles
302.11g	2472	10.73	11.830	10±2	3.24	2.109	0.00665	1	Compiles
IEEE	2412	9.21	8.337	9±2	3.24	2.109	0.00528	1	Compiles
802.11n	2442	9.62	9.162	9±2	3.24	2.109	0.00528	1	Compiles
HT20	2472	9.14	8.204	9±2	3.24	2.109	0.00528	1	Compiles

					Ante	nna gain		Limited	
		Peak	Peak				Power	of	
Mode	Frequency	output	output	Target			Density	Power	Test
	(MHz)	power	power	power	(dBi)	(Linear)	(S)	Density	Result
	(11112)	(dBm)	(mW)	(dBm)	(uDi)	(Ellicar)	(mW	(S)	resur
		(GDIII)	(111 // )				/cm2)	(mW	
								/cm2)	
	5180	14.36	27.290	14±2	3.12	2.051	0.01625	1	Compiles
	5200	14.37	27.353	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5240	14.34	27.164	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5260	13.97	24.946	$13\pm 2$	3.12	2.051	0.01290	1	Compiles
	5300	14.10	25.704	$14\pm 2$	3.12	2.051	0.01625	1	Compiles
IEEE	5320	13.55	22.646	$13\pm 2$	3.12	2.051	0.01290	1	Compiles
802.11a	5500	14.41	27.606	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5580	14.34	27.164	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5700	14.23	26.485	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5745	14.32	27.040	$14\pm2$	3.12	2.051	0.01625	1	Compiles
	5785	14.19	26.242	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5825	14.14	25.942	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5180	14.41	27.606	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5200	14.40	27.542	$14 \pm 2$	3.12	2.051	0.01625	1	Compiles
	5240	13.86	24.322	13±2	3.12	2.051	0.01290	1	Compiles
	5260	13.93	24.717	$13\pm 2$	3.12	2.051	0.01290	1	Compiles
IEEE	5300	13.58	22.803	13±2	3.12	2.051	0.01290	1	Compiles
IEEE	5320	14.08	25.586	14±2	3.12	2.051	0.01625	1	Compiles
802.11n	5500	14.35	27.227	14±2	3.12	2.051	0.01625	1	Compiles
HT20	5580	14.43	27.733	14±2	3.12	2.051	0.01625	1	Compiles
	5700	14.04	25.351	14±2	3.12	2.051	0.01625	1	Compiles
	5745	14.55	28.510	14±2	3.12	2.051	0.01625	1	Compiles
	5785	14.14	25.942	14±2	3.12	2.051	0.01625	1	Compiles
	5825	14.11	25.763	14±2	3.12	2.051	0.01625	1	Compiles

					Antei	nna gain		Limited	
					1 111001	and guin	Power	of	
		Peak	Peak	Target			Density	Power	
Mode	Frequency	output	output	power			(S)	Density	Test
	(MHz)	power	power (mW)	(dBm)	(dBi)	(Linear)	(mW	(S)	Result
		(dBm)					/cm2)	(mW	
							, , , , , ,	/cm2)	
	5180	14.50	28.184	14±2	3.12	2.051	0.01625	1	Compiles
	5200	13.93	24.717	13±2	3.12	2.051	0.01290	1	Compiles
	5240	14.08	25.586	14±2	3.12	2.051	0.01625	1	Compiles
	5260	13.91	24.604	13±2	3.12	2.051	0.01290	1	Compiles
IEEE	5300	13.53	22.542	13±2	3.12	2.051	0.01290	1	Compiles
IEEE	5320	13.52	22.491	13±2	3.12	2.051	0.01290	1	Compiles
802.11ac	5500	14.28	26.792	14±2	3.12	2.051	0.01625	1	Compiles
20	5580	14.36	27.290	14±2	3.12	2.051	0.01625	1	Compiles
	5700	14.04	25.351	14±2	3.12	2.051	0.01625	1	Compiles
	5745	14.27	26.730	14±2	3.12	2.051	0.01625	1	Compiles
	5785	14.11	25.763	14±2	3.12	2.051	0.01625	1	Compiles
	5825	13.85	24.266	13±2	3.12	2.051	0.01290	1	Compiles
	5190	11.39	13.772	11±2	3.12	2.051	0.00814	1	Compiles
	5230	11.08	12.823	11±2	3.12	2.051	0.00814	1	Compiles
	5270	14.47	27.990	14±2	3.12	2.051	0.01625	1	Compiles
IEEE	5310	10.49	11.194	10±2	3.12	2.051	0.00647	1	Compiles
802.11n	5510	12.51	17.824	12±2	3.12	2.051	0.01025	1	Compiles
HT40	5550	12.62	18.281	12±2	3.12	2.051	0.01025	1	Compiles
	5670	12.24	16.749	12±2	3.12	2.051	0.01025	1	Compiles
	5755	14.55	28.510	14±2	3.12	2.051	0.01625	1	Compiles
	5795	14.29	26.853	14±2	3.12	2.051	0.01625	1	Compiles
	5190	10.15	10.351	10±2	3.12	2.051	0.00647	1	Compiles
	5230	9.63	9.183	9±2	3.12	2.051	0.00514	1	Compiles
	5270	9.59	9.099	9±2	3.12	2.051	0.00514	1	Compiles
IEEE	5310	9.15	8.222	9±2	3.12	2.051	0.00514	1	Compiles
802.11ac	5510	12.57	18.072	12±2	3.12	2.051	0.01025	1	Compiles
40	5550	12.30	16.982	12±2	3.12	2.051	0.01025	1	Compiles
	5670	12.17	16.482	12±2	3.12	2.051	0.01025	1	Compiles
	5755	14.07	25.527	14±2	3.12	2.051	0.01625	1	Compiles
	5795	13.94	24.774	13±2	3.12	2.051	0.01290	1	Compiles



					Ante	nna gain		Limited	
Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	(dBi)	(Linear)	Power Density (S) (mW /cm2)	of Power Density (S) (mW /cm2)	Test Result
IEEE	5210	6.61	4.581	6±2	3.12	2.051	0.00257	1	Compiles
802.11ac	5290	6.30	4.266	6±2	3.12	2.051	0.00257	1	Compiles
802.11ac	5530	10.30	10.715	$10\pm 2$	3.12	2.051	0.00647	1	Compiles
60	5775	9.62	9.162	9±2	3.12	2.051	0.00324	1	Compiles

### 3.3 Note:

- A、 2.4 and 5GHz bands are share an antenna, Cann't both the 2.4 and 5 GHz bands operate simultaneously;
  - $B_{\, {}^{\circ}}$  Antenna 1 and 2 cann't both operate simultaneously  $_{\circ}$