



# **RADIO TEST REPORT**

## **FCC ID: XN6-SS2521C6**

## **IC: 8819A-SS2521C6**

**Product :** 25"2.1 Sound Stand

**Trade Name :** VIZIO

**Model Name :** SS2521-C6

**Serial Model :** N/A

**Report No. :** NTEK-2015NT0104125F2

### **Prepared for**

Zylux Acoustic Corporation  
3F,22,Lane 35,Jihu Road,Taipei Neihu Technology Park,114 Taipei  
Taiwan-R.O.C

### **Prepared by**

Shenzhen NTEK Testing Technology Co., Ltd.  
1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street  
Bao'an District, Shenzhen P.R. China  
Tel.: +86-0755-61156588 Fax.: +86-0755-61156599  
Website: www.ntek.org.cn

## TEST RESULT CERTIFICATION

**Applicant's name** ..... Zylux Acoustic Corporation

**Address** ..... 3F,22,Lane 35,Jihu Road,Taipei NeiHu Technology Park,  
114 Taipei Taiwan-R.O.C

**Manufacture's Name**... Zhao Yang Electronic(Shenzhen)Co., Ltd.

**Address** ..... Sec.A, 4F, Building 1&2, De Yong Jia Ind. Park, GuangQiao Rd. Yu Lv  
Com., GongMing St. 518100 Guang Ming New Distr., Shenzhen, China

### Product description

**Product name** ..... 25"2.1 Sound Stand

**Model and/or type** ..... SS2521-C6  
**reference** .....

**Serial Model** ..... N/A

**Standards** ..... FCC Part15.247:01 Oct. 2014  
IC RSS-210,Issue 8, December 2010

**Test procedure**..... ANSI C63.4-2003  
RSS-Gen ISSUE 4 November 2014 and KDB 558074:June 5, 2014,

This device described above has been tested by NTEK, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements/ the Industry Canada requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK, this document may be altered or revised by NTEK, personal only, and shall be noted in the revision of the document.


**Date of Test** .....

**Date (s) of performance of tests** ..... 04 Jan. 2015 ~21 Jan. 2015

**Date of Issue**..... 21 Jan. 2015


**Test Result**..... **Pass**

Testing Engineer :



Denny Huang

Technical Manager :



(Brown Lu)

Authorized Signatory :



(Bill Yao)

## Table of Contents

	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>5</b>
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
<b>2 . GENERAL INFORMATION</b>	<b>7</b>
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
<b>3 . EMC EMISSION TEST</b>	<b>13</b>
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 RADIATED EMISSION LIMITS	19
3.2.2 TEST PROCEDURE	20
3.2.3 DEVIATION FROM TEST STANDARD	20
3.2.4 TEST SETUP	21
3.2.5 EUT OPERATING CONDITIONS	22
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	23
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	24
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	28
<b>4 . POWER SPECTRAL DENSITY TEST</b>	<b>30</b>
4.1 APPLIED PROCEDURES / LIMIT	30
4.1.1 TEST PROCEDURE	30
4.1.2 DEVIATION FROM STANDARD	30
4.1.3 TEST SETUP	30
4.1.4 EUT OPERATION CONDITIONS	30
4.1.5 TEST RESULTS	31
<b>5 . BANDWIDTH TEST</b>	<b>33</b>
5.1 APPLIED PROCEDURES / LIMIT	33
5.1.1 TEST PROCEDURE	33

<b>Table of Contents</b>	<b>Page</b>
5.1.2 EUT OPERATION CONDITIONS	33
5.1.3 TEST RESULTS	34
<b>6 . MAX CONDUCTED OUTPUT POWER TEST</b>	<b>36</b>
6.1 APPLIED PROCEDURES / LIMIT	36
6.1.1 TEST PROCEDURE	36
6.1.2 DEVIATION FROM STANDARD	36
6.1.3 TEST SETUP	36
6.1.4 EUT OPERATION CONDITIONS	36
6.1.5 TEST RESULTS	37
<b>7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>38</b>
7.1 DEVIATION FROM STANDARD	38
7.2 TEST SETUP	38
7.3 EUT OPERATION CONDITIONS	38
7.4 TEST RESULTS	39
<b>8 . ANTENNA REQUIREMENT</b>	<b>41</b>
8.1 STANDARD REQUIREMENT	41
8.2 EUT ANTENNA	41
<b>9 . EUT TEST PHOTO</b>	<b>42</b>
<b>APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C/ RSS-210 & RSS-Gen Rules			
Standard Section	Test Item	Judgment	Remark
15.207/ RSS-Gen §7.2.4	Conducted Emission	PASS	
15.247 (a)(2)/ RSS-Gen§4.6.1&RSS-210§A8.2 (a)	99% Occupied Bandwidth & 6dB Bandwidth	PASS	
15.247 (b)/ RSS-210 §A8.4 (4)	Peak Output Power	PASS	
15.247 (c)/ RSS-210 §2.2, §A8.5	Radiated Spurious Emission	PASS	
15.247 (d)/ RSS-210 §A8.2 (b)	Power Spectral Density	PASS	
15.205/ RSS-210 §2.2, §A8.5	Band Edge Emission	PASS	
15.203/ RSS-Gen §7.1.2	Antenna Requirement	PASS	

### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

## 1.1 TEST FACILITY

NTEK Testing Technology Co., Ltd

Add.:1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China.

FCC Registration No.:238937; IC Registration No.:9270A-1

CNAS Registration No.:L5516

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	25"2.1 Sound Stand	
Trade Name	VIZIO	
Model Name	SS2521-C6	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a 25"2.1 Sound Stand	
	Operation Frequency:	2402~2480MHz
	Modulation Type:	GFSK
	Number Of Channel	40CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	1.0dbi
Channel List	Please refer to the Note 2.	
Ratings	AC 120V,60Hz	
Adapter	Adapter 1: main test    Adapter 2: Deputy test	
Battery	N/A	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel	Frequency (MHz)
00	2402
01	2404
.....	.....
.....	.....
.....	...
.....	.....
38	2478
39	2480

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	PCB Antenna	N/A	1.0	BT Antenna



## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Keeping TX mode


For Conducted Emission	
Final Test Mode	Description
Mode 4	Keeping TX mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH19
Mode 3	CH39
Mode 4	Keeping TX mode

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported

### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



## 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	25"2.1 Sound Stand	VIZIO	SS2521-C6	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

## 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2014.07.06	2015.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2014.06.07	2015.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2014.07.06	2015.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2014.06.07	2015.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2014.06.07	2015.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2014.07.06	2015.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2014.12.22	2015.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2014.06.08	2015.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2014.07.06	2015.07.05	1 year

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2014.06.06	2015.06.05	1 year
2	LISN	R&S	ENV216	101313	2014.08.24	2015.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2014.06.07	2015.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2014.06.07	2015.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2014.06.08	2015.06.07	1 year

1	Attenuation	MCE	24-10-34	BN9258	2014.06.08	2015.06.07	1 year
---	-------------	-----	----------	--------	------------	------------	--------

### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC/ RSS-210
0.50 -5.0	73.00	60.00	56.00	46.00	FCC/ RSS-210
5.0 -30.0	73.00	60.00	60.00	50.00	FCC/ RSS-210

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

### 3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



**Note: 1.**Support units were connected to second LISN.

**2.**Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


### 3.1.6 TEST RESULTS

EUT :	25"2.1 Sound Stand	Model Name. :	SS2521-C6
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz- Adapter 1	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1700	34.84	9.58	44.42	64.96	-20.54	QP
0.1700	17.43	9.58	27.01	54.96	-27.95	AVG
0.4020	32.63	9.18	41.81	57.81	-16.00	QP
0.4020	25.61	9.18	34.79	47.81	-13.02	AVG
0.8100	29.18	9.59	38.77	56.00	-17.23	QP
0.8100	21.25	9.59	30.84	46.00	-15.16	AVG
1.2177	23.08	9.58	32.66	56.00	-23.34	QP
1.2177	13.97	9.58	23.55	46.00	-22.45	AVG
3.2099	21.61	9.60	31.21	56.00	-24.79	QP
3.2099	13.19	9.60	22.79	46.00	-23.21	AVG
23.6297	34.21	9.86	44.07	60.00	-15.93	QP
23.6297	30.22	9.86	40.08	50.00	-9.92	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	25"2.1 Sound Stand	Model Name. :	SS2521-C6
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz- Adapter 1	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1940	32.39	9.49	41.88	63.86	-21.98	QP
0.1940	16.13	9.49	25.62	53.86	-28.24	AVG
0.4020	32.47	9.45	41.92	57.81	-15.89	QP
0.4020	25.83	9.45	35.28	47.81	-12.53	AVG
0.4858	31.29	9.47	40.76	56.24	-15.48	QP
0.4858	22.35	9.47	31.82	46.24	-14.42	AVG
0.8100	29.29	9.45	38.74	56.00	-17.26	QP
0.8100	20.05	9.45	29.50	46.00	-16.50	AVG
15.2299	29.07	9.71	38.78	60.00	-21.22	QP
15.2299	24.57	9.71	34.28	50.00	-15.72	AVG
27.6497	30.25	9.91	40.16	60.00	-19.84	QP
27.6497	25.21	9.91	35.12	50.00	-14.88	AVG

Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.






EUT :	25"2.1 Sound Stand	Model Name. :	SS2521-C6
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC 120V/60Hz- Adapter 2	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	39.84	9.63	49.47	65.56	-16.09	QP
0.1580	24.77	9.63	34.40	55.56	-21.16	AVG
0.3860	30.23	9.23	39.46	58.15	-18.69	QP
0.3860	23.73	9.23	32.96	48.15	-15.19	AVG
0.4420	28.72	9.33	38.05	57.02	-18.97	QP
0.4420	24.40	9.33	33.73	47.02	-13.29	AVG
0.8338	27.42	9.59	37.01	56.00	-18.99	QP
0.8338	19.73	9.59	29.32	46.00	-16.68	AVG
4.0979	19.55	9.62	29.17	56.00	-26.83	QP
4.0979	14.06	9.62	23.68	46.00	-22.32	AVG
25.0899	26.62	9.84	36.46	60.00	-23.54	QP
25.0899	20.73	9.84	30.57	50.00	-19.43	AVG

Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.




EUT :	25"2.1 Sound Stand	Model Name. :	SS2521-C6
Temperature :	26 °C	Relative Humidity :	56%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC 120V/60Hz- Adapter 2	Test Mode :	Mode 4

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV)	Limits (dBμV)	Margin (dB)	Remark
0.1580	41.95	9.63	51.58	65.56	-13.98	QP
0.1580	24.78	9.63	34.41	55.56	-21.15	AVG
0.4020	31.29	9.18	40.47	57.81	-17.34	QP
0.4020	24.17	9.18	33.35	47.81	-14.46	AVG
0.8218	27.17	9.59	36.76	56.00	-19.24	QP
0.8218	18.77	9.59	28.36	46.00	-17.64	AVG
4.0979	21.15	9.62	30.77	56.00	-25.23	QP
4.0979	17.05	9.62	26.67	46.00	-19.33	AVG
8.1937	24.14	9.66	33.80	60.00	-26.20	QP
8.1937	20.97	9.66	30.63	50.00	-19.37	AVG
25.6060	25.93	9.85	35.78	60.00	-24.22	QP
25.6060	18.85	9.85	28.70	50.00	-21.30	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a)/ RSS-210 §2.2& A8.5, then the 15.209(a)/ RSS-210 & A8.5 limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	(dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C/ RSS-Gen.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic

The frequency spectrum from 30 MHz to 25 GHz was investigated.

All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=1MHz VBW=3MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector.

### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested  
and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


#### (A) Radiated Emission Test-Up Frequency Below 30MHz



#### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	25"2.1 Sound Stand	Model Name. :	SS2521-C6
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	N/A
--	--	--	--	N/A

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


### 3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	25"2.1 Sound Stand	Model Name :	SS2521-C6
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz- Adapter 1
Test Mode :	TX		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	32.7486	11.59	17.92	29.51	40.00	-10.49	QP
V	60.9176	17.93	7.63	25.56	40.00	-14.44	QP
V	109.0286	15.03	9.86	24.89	43.50	-18.61	QP
V	125.4457	16.26	11.98	28.24	43.50	-15.26	QP
V	178.7584	13.59	10.61	24.20	43.50	-19.30	QP
V	229.2931	13.31	12.76	26.07	46.00	-19.93	QP

#### Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit






Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	84.4054	24.09	6.75	30.84	40.00	-9.16	QP
H	131.7574	17.18	11.81	28.99	43.50	-14.51	QP
H	149.4857	19.05	10.46	29.51	43.50	-13.99	QP
H	178.1327	23.91	10.61	34.52	43.50	-8.98	QP
H	246.8149	19.80	13.56	33.36	46.00	-12.64	QP
H	345.5952	17.41	16.06	33.47	46.00	-12.53	QP

**Remark:**

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit




EUT :	25"2.1 Sound Stand	Model Name :	SS2521-C6
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz- Adapter 2
Test Mode :	TX		

Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
V	38.8878	16.78	14.25	31.03	40.00	-8.97	QP
V	46.0162	23.50	11.67	35.17	40.00	-4.83	QP
V	96.7749	17.00	8.64	25.64	43.50	-17.86	QP
V	160.9088	21.64	10.48	32.12	43.50	-11.38	QP
V	279.0436	11.81	13.92	25.73	46.00	-20.27	QP
V	346.8091	9.81	16.10	25.91	46.00	-20.09	QP

**Remark:**


Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Polar (H/V)	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark
	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
H	46.9948	18.36	11.43	29.79	40.00	-10.21	QP
H	84.4054	24.27	6.75	31.02	40.00	-8.98	QP
H	149.4857	21.64	10.46	32.10	43.50	-11.40	QP
H	178.1327	23.06	10.61	33.67	43.50	-9.83	QP
H	250.3012	20.68	13.59	34.27	46.00	-11.73	QP
H	349.2500	17.34	16.21	33.55	46.00	-12.45	QP

**Remark:**

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



### 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

EUT :	25"2.1 Sound Stand	Model Name :	SS2521-C6
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz- Adapter 1
Test Mode :	TX		

Frequency (MHz)	Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Polar (H/V)
Low Channel (2402 MHz)-Above 1G							
4804.236	58.92	-3.64	55.28	74	-18.72	Pk	Vertical
4804.236	41.26	-3.64	37.62	54	-16.38	AV	Vertical
7206.147	59.07	-0.95	58.12	74	-15.88	Pk	Vertical
7206.147	37.22	-0.95	36.27	54	-17.73	AV	Vertical
4804.066	59.31	-3.64	55.67	74	-18.33	Pk	Horizontal
4804.066	42.16	-3.64	38.52	54	-15.48	AV	Horizontal
7206.236	57.27	-0.95	56.32	74	-17.68	Pk	Horizontal
7206.236	37.09	-0.95	36.14	54	-17.86	AV	Horizontal
Mid Channel (2440 MHz)-Above 1G							
4880.208	58.77	-3.68	55.09	74	-18.91	Pk	Vertical
4880.208	40.84	-3.68	37.16	54	-16.84	AV	Vertical
7320.139	58.16	-0.82	57.34	74	-16.66	Pk	Vertical
7320.139	39.32	-0.82	38.5	54	-15.5	AV	Vertical
4880.147	60.67	-3.68	56.99	74	-17.01	Pk	Horizontal
4880.147	43.87	-3.68	40.19	54	-13.81	AV	Horizontal
7320.152	58.16	-0.82	57.34	74	-16.66	Pk	Horizontal
7320.152	38.27	-0.82	37.45	54	-16.55	AV	Horizontal
High Channel (2480MHz)- Above 1G							
4960.088	58.09	-3.59	54.5	74	-19.5	Pk	Vertical
4960.088	40.94	-3.59	37.35	54	-16.65	AV	Vertical
7440.203	56.56	-0.68	55.88	74	-18.12	Pk	Vertical
7440.203	40.82	-0.68	40.14	54	-13.86	AV	Vertical
4960.142	57.92	-3.59	54.33	74	-19.67	Pk	Horizontal
4960.142	41.14	-3.59	37.55	54	-16.45	AV	Horizontal
7440.326	59.45	-0.68	58.77	74	-15.23	Pk	Horizontal
7440.326	38.29	-0.68	37.61	54	-16.39	AV	Horizontal

EUT :	25"2.1 Sound Stand	Model Name :	SS2521-C6
Temperature :	20 °C	Relative Humidity :	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz- Adapter 2
Test Mode :	TX		

Frequency (MHz)	Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Remark	Polar (H/V)
Low Channel (2402 MHz)-Above 1G							
4804.145	58.39	-3.64	54.75	74	-19.25	Pk	Vertical
4804.145	40.73	-3.64	37.09	54	-16.91	AV	Vertical
7206.206	58.54	-0.95	57.59	74	-16.41	Pk	Vertical
7206.206	36.69	-0.95	35.74	54	-18.26	AV	Vertical
4804.148	59.13	-3.64	55.49	74	-18.51	Pk	Horizontal
4804.148	41.63	-3.64	37.99	54	-16.01	AV	Horizontal
7206.362	56.74	-0.95	55.79	74	-18.21	Pk	Horizontal
7206.362	36.56	-0.95	35.61	54	-18.39	AV	Horizontal
Mid Channel (2440 MHz)-Above 1G							
4880.142	58.24	-3.68	54.56	74	-19.44	Pk	Vertical
4880.142	40.28	-3.68	36.6	54	-17.4	AV	Vertical
7320.305	57.63	-0.82	56.81	74	-17.19	Pk	Vertical
7320.305	38.49	-0.82	37.67	54	-16.33	AV	Vertical
4880.216	60.14	-3.68	56.46	74	-17.54	Pk	Horizontal
4880.216	43.28	-3.68	39.6	54	-14.4	AV	Horizontal
7320.201	57.61	-0.82	56.79	74	-17.21	Pk	Horizontal
7320.201	37.74	-0.82	36.92	54	-17.08	AV	Horizontal
High Channel (2480MHz)- Above 1G							
4960.139	57.56	-3.59	53.97	74	-20.03	Pk	Vertical
4960.139	40.41	-3.59	36.82	54	-17.18	AV	Vertical
7440.216	56.03	-0.68	55.35	74	-18.65	Pk	Vertical
7440.216	40.29	-0.68	39.61	54	-14.39	AV	Vertical
4960.321	57.39	-3.59	53.8	74	-20.2	Pk	Horizontal
4960.321	40.59	-3.59	37	54	-17	AV	Horizontal
7440.062	58.92	-0.68	58.24	74	-15.76	Pk	Horizontal
7440.062	37.76	-0.68	37.08	54	-16.92	AV	Horizontal

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Reading + Factor

Margin = Emission Level- Limit

## 4. POWER SPECTRAL DENSITY TEST

### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247/ RSS-210§A8. 2 (b)	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


#### 4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW  $\geq 3$  kHz.
4. Set the VBW  $\geq 3 \times$  RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP




#### 4.1.4 EUT OPERATION CONDITIONS



The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 4.1.5 TEST RESULTS

EUT :	25"2.1 Sound Stand	Model Name :	SS2521-C6
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode /CH00, CH19, CH39		

Frequency	Power Density (dBm)	Limit (dBm)	Result
2402 MHz	-17.87	8	PASS
2440 MHz	-17.46	8	PASS
2480 MHz	-17.60	8	PASS







## 5. BANDWIDTH TEST


### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)/ RSS-Gen§4.6 .1&RSS-210§ A8.2 (a)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

#### 5.1.1 TEST PROCEDURE

According to KDB 558074 D01 DTS Meas Guidance v03r01

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.




#### 5.1.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


### 5.1.3 TEST RESULTS

EUT :	25"2.1 Sound Stand	Model Name :	SS2521-C6
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode /CH00, CH19, CH39		


Channel	Frequency (MHz)	6dB bandwidth (kHz)	99% Bandwidth (MHz)	Limit (kHz)	Result
Low	2402	693.491	1.033	500	Pass
Middle	2440	704.679	1.036	500	Pass
High	2480	699.161	1.037	500	Pass



TX CH 19



TX CH 39



## 6. MAX CONDUCTED OUTPUT POWER TEST

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)/ RSS-210 §A8.4 (4)	Max Conducted output power	1 watt or 30dBm	2400-2483.5	PASS

#### 6.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### 6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

### 6.1.5 TEST RESULTS

EUT :	25"2.1 Sound Stand	Model Name :	SS2521-C6
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode		

Test Channe	Frequency	Maximum Conducted Output Power	LIMIT
	(MHz)	(dBm)	dBm
CH01	2402	-2.66	30
CH19	2440	-2.75	30
CH39	2480	-2.71	30

## 7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

### APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


### TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

### 7.1 DEVIATION FROM STANDARD

No deviation.

### 7.2 TEST SETUP



### 7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 7.4 TEST RESULTS

EUT :	25"2.1 Sound Stand	Model Name :	SS2521-C6
Temperature :	25 °C	Relative Humidity :	56%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz


Frequency Band	Delta Peak to band emission (dBc)	> Limit (dBc)	Result
Left-band	57.46	30	Pass
Right-band	62.62	30	Pass

Radiated band edge:


Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Remark	Comment
2390	59.82	-13.06	46.76	74	-27.24	peak	Vertical
2390	59.56	-13.06	46.5	74	-27.50	peak	Horizontal
2483.5	60.79	-12.78	48.01	74	-25.99	peak	Vertical
2483.5	60.8	-12.78	48.02	74	-25.98	peak	Horizontal

Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average not record.

### Band Edge, Left Side



### Band Edge, Right Side





## **8. ANTENNA REQUIREMENT**

### **8.1 STANDARD REQUIREMENT**


15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### **8.2 EUT ANTENNA**

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

## 9. EUT TEST PHOTO

### Radiated Measurement Photos



**Conducted Measurement Photos**