

FCC Test Report

FCC ID : XNAWPM05

Equipment : BPM Connect

Model No. : WPM05

Brand Name : Withings

Applicant : Withings SA

Address : 2 rue Maurice Hartmann

92130 Issy-Les-Moulineaux

France

Standard : 47 CFR FCC Part 15.247

Received Date : Apr. 18, 2019

Tested Date : May 07 ~ May 13, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen Assistant Manager Gary Chang / Manager

Testing Laboratory

Page: 1 of 60

Report No.: FR941802AD Report Version: Rev. 02



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	8
1.3	Test Setup Chart	8
1.4	The Equipment List	g
1.5	Test Standards	1C
1.6	Deviation from Test Standard and Measurement Procedure	1C
1.7	Measurement Uncertainty	10
2	TEST CONFIGURATION	11
2.1	Testing Condition	11
2.2	The Worst Test Modes and Channel Details	11
3	TRANSMITTER TEST RESULTS	12
3.1	Conducted Emissions	12
3.2	Unwanted Emissions into Restricted Frequency Bands	15
3.3	Unwanted Emissions into Non-Restricted Frequency Bands	34
3.4	Conducted Output Power	39
3.5	Number of Hopping Frequency	42
3.6	20dB and Occupied Bandwidth	45
3.7	Channel Separation	50
3.8	Number of Dwell Time	55
4	TEST LABORATORY INFORMATION	60



Release Record

Report No.	Version	Description	Issued Date
FR941802AD	Rev. 01	Initial issue	May 27, 2019
FR941802AD	Rev. 02	Added ANSI C63.4-2014 on P10.	Jun. 06, 2019

Report No.: FR941802AD Page: 3 of 60



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.183MHz 51.98 (Margin -12.35dB) - QP	Pass
15.247(d)	Radiated Emissions	[dBuV/m at 3m]: 46.49MHz	Pass
15.209	Radiated Emissions	32.34 (Margin -7.66dB) - PK	Fa55
15.247(d)	Band Edge	Meet the requirement of limit	Pass
15.247(b)(1)	Conducted Output Power	Power [dBm]: 9.98	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Meet the requirement of limit	Pass
15.247(a)(1)	Hopping Channel Separation	Meet the requirement of limit	Pass
15.247(a)(1)(iii)	Dwell Time	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Page: 4 of 60

Report No.: FR941802AD

Report Version: Rev. 02



1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information							
Frequency Range (MHz)	Data Rate						
2400-2483.5	BR	2402-2480	0-78 [79]	1 Mbps			
2400-2483.5	EDR	2402-2480	0-78 [79]	2 Mbps			
2400-2483.5	EDR	2402-2480	0-78 [79]	3 Mbps			

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.

Note 2: Bluetooth BR uses a GFSK.

Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.

1.1.2 Antenna Details

Ant. No.	Brand	Model	Туре	Connector	Gain (dBi)
1	BROADCOM	BCM9Fractal	PCB	NA	2.8

1.1.3 EUT Operational Condition

Power Supply Type	3.7Vdc from battery Brand: CEL Model: 652265-1000mAh 5Vdc from host
-------------------	---

1.1.4 Accessories

N/A

Report No.: FR941802AD Page: 5 of 60

Report Version: Rev. 02



1.1.5 Channel List

	Frequency	band (MHz)			2400~2	2483.5	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

Page : 6 of 60



1.1.6 Test Tool and Duty Cycle

Test Tool	tera term, V4.101			
Modulation Mode	Duty Cycle (%)	Duty Factor (dB)		
DH5	77.99%	1.08		
3DH5	78.29%	1.06		

1.1.7 Power Index of Test Tool

Modulation Mode		Test Frequency (MHz)	
Modulation Mode	2402	2441	2480
GFSK/1Mbps	Default	Default	Default
π/4-DQPSK /2Mbps	Default	Default	Default
8DPSK/3Mbps	Default	Default	Default


Report No.: FR941802AD Page: 7 of 60




1.2 Local Support Equipment List

	Support Equipment List						
No. Equipment Brand Model FCC ID Remarks							
1	Notebook	DELL	Latitude E6440	JPXMD12			

1.3 Test Setup Chart



Note: The support notebook is connected to fixture by console cable and is disconnected from EUT and removed from test table after sending command to link EUT to CBT.



Report No.: FR941802AD Page: 8 of 60

Report Version: Rev. 02



1.4 The Equipment List

Test Item	Conducted Emission	Conducted Emission					
Test Site	Conduction room 1 / (Conduction room 1 / (CO01-WS)					
Instrument	Manufacturer Model No. Serial No. Calibration Date Calibration Until						
Receiver	R&S	ESR3	101657	Jan. 08, 2019	Jan. 07, 2020		
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 05, 2018	Nov. 04, 2019		
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 23, 2018	Oct. 23, 2019		
Measurement Software AUDIX e3 6.120210k NA NA NA							
Note: Calibration Interval of instruments listed above is one year.							

Test Item	Radiated Emission	Radiated Emission					
Test Site	966 chamber1 / (03Cl	H01-WS)					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019		
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 18, 2018	Jul. 17, 2019		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019		
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019		
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019		
Preamplifier	EMC	EMC02325	980225	Jul. 20, 2018	Jul. 19, 2019		
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019		
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019		
RF Cable	EMC	EMC104-SM-SM-80 00	181106	Oct. 08, 2018	Oct. 07, 2019		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 08, 2018	Oct. 07, 2019		
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 08, 2018	Oct. 07, 2019		
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 08, 2018	Oct. 07, 2019		
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 08, 2018	Oct. 07, 2019		
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 08, 2018	Oct. 07, 2019		
Measurement Software SENSE-15247_DTS V5.10 NA NA NA							
Note: Calibration Inter	val of instruments liste	d above is one year.					

Page: 9 of 60

Report No.: FR941802AD

Report Version: Rev. 02



Test Item	RF Conducted									
Test Site	(TH01-WS)									
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until					
Spectrum Analyzer	R&S	FSV40	101063	Apr. 17, 2019	Apr. 16, 2020					
Power Meter	Anritsu	ML2495A	1241002	Oct. 09, 2018	Oct. 08, 2019					
Power Sensor	Anritsu	MA2411B	1207366	Oct. 09, 2018	Oct. 08, 2019					
Bluetooth Tester	R&S	CBT	100959	Sep. 24, 2018	Sep. 23, 2019					
DC POWER SOURCE	GW INSTEK	GPC-6030D	EM892433	Oct. 25, 2018	Oct. 24, 2019					
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA					
Note: Calibration Interval of instruments listed above is one year.										

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

ANSI C63.4-2014

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty							
Parameters	Uncertainty						
Bandwidth	±34.130 Hz						
Conducted power	±0.808 dB						
Power density	±0.583 dB						
Conducted emission	±2.715 dB						
AC conducted emission	±2.92 dB						
Radiated emission ≤ 1GHz	±3.41 dB						
Radiated emission > 1GHz	±4.59 dB						

Page: 10 of 60

Report No.: FR941802AD

Report Version: Rev. 02



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	24°C / 62%	Alex Tsai
Radiated Emissions	03CH01-WS	22°C / 62%	Akun Chung
RF Conducted	TH01-WS	20°C / 66%	Aska Huang

FCC Designation No.: TW2732FCC site registration No.: 181692

➤ ISED#: 10807A

> CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Test Configuration
Conducted Emissions	GFSK	2480	1Mbps	2
Radiated Emissions ≤ 1GHz	GFSK	2480	1Mbps	1, 2
Radiated Emissions > 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	1
Conducted Output Power	GFSK л/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	1
Number of Hopping Channels	GFSK л/4 DQPSK 8DPSK	2402~2480 2402~2480 2402~2480	1Mbps 2Mbps 3Mbps	1
Hopping Channel Separation 20dB and Occupied bandwidth	GFSK л/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	1
Dwell Time	GFSK л/4 DQPSK 8DPSK	2441 2441 2441	1Mbps 2Mbps 3Mbps	1

NOTE:

- 1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.
- 2. Test configurations are listed as below:
 - 1) Test Configuration 1: Battery mode
 - 2) Test Configuration 2: Charger mode

Report No.: FR941802AD Page: 11 of 60

Report Version: Rev. 02



3 Transmitter Test Results

3.1 Conducted Emissions


3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit							
Frequency Emission (MHz) Quasi-Peak Average							
0.15-0.5	66 - 56 *	56 - 46 *					
0.5-5	56	46					
5-30	60	50					
Note 1: * Decreases with the logarithm of the frequency.							

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V/60Hz

3.1.3 Test Setup



Note: 1. Support units were connected to second LISN.


Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR941802AD Page: 12 of 60

Report Version: Rev. 02




Test Result of Conducted Emissions 3.1.4



Report Version: Rev. 02

Report No.: FR941802AD Page: 13 of 60





2: Over Limit (dB) = Level (dBuV) - Limit Line (dBuV).

Report Version: Rev. 02

Report No.: FR941802AD Page: 14 of 60



3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit								
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)					
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300					
0.490~1.705	24000/F(kHz)	33.8 - 23	30					
1.705~30.0	30	29	30					
30~88	100	40	3					
88~216	150	43.5	3					
216~960	200	46	3					
Above 960	500	54	3					

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit Note 2:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

Report No.: FR941802AD Report Version: Rev. 02



3.2.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. Radiated emission above 1GHz / Peak value RBW=1MHz, VBW=3MHz and Peak detector

Radiated emission above 1GHz / Average value for harmonics
The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:

Page: 16 of 60


3. $20\log \text{ (Duty cycle)} = 20\log \frac{1\text{s} / 1600 * 5}{100 \text{ ms}} = -30.1 \text{dB}$

4. Radiated emission above 1GHz / Average value for other emissions RBW=1MHz, VBW=1/T and Peak detector

Report No.: FR941802AD Report Version: Rev. 02




3.2.3 Test Setup





Test Configuration 1: Battery mode

3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Page: 18 of 60

Report No.: FR941802AD

Report Version: Rev. 02



Modulation		GFSK			-	Test Freq. (MHz)			2480	
Polarization			Vertical							
90 Le	vel (dBu	V/m)								
80										
00										
70										
60										
									FCC CL	ASS-B
50										
40			_							
12	3 5									
30	4 [6	3								
20										
40										
10										
0 <mark>LL</mark>	100.	20	0. 30	0. 40	00. 50	0. 600	0. 700.	800.	900.	1000
					Freque	ncy (MHz)				
	Fi	req. E	mission	Limit	Margin	SA	Factor	Remark	ANT	Turn
			level			reading	Ţ.		Hig	h Table
	I	MHz	dBuV/m	dBuV/r	n dB	dBuV	dB		cm	deg
1		32.91	30.06	40.00	-9.94	38.82	-8.76	Peak		
2		46.49	32.34	40.00		40.12	-7.78	Peak		
3		52.31	30.47	40.00		38.36	-7.89	Peak		
4		62.98	26.95		-13.05	36.15	-9.20	Peak		
5	10	01.78	29.67		-13.83	42.27	-12.60	Peak		
6	13	29.91	26.02	43.50	-17.48	35.62	-9.60	Peak		

*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.


Report No.: FR941802AD

Page: 19 of 60

Report Version: Rev. 02



3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report Version: Rev. 02

Report No.: FR941802AD Page: 20 of 60



Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq.	Emission level dBuV/m	Limit dBuV/m	Ü	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	20 F1	<u></u> -	15 40		2.07	A	201	177
1	2390.00	38.51	54.00	-15.49	41.58	-3.07	Average	301	177
2	2390.00	49.26	74.00	-24.74	52.33	-3.07	Peak	301	177
3	4804.00	26.07	54.00	-27.93	22.57	3.50	Average	152	256
4	4804.00	56.17	74.00	-17.83	52.67	3.50	Peak	152	256
5	12010.00	25.55	54.00	-28.45	12.29	13.26	Average	100	24
6	12010.00	55.65	74.00	-18.35	42.39	13.26	Peak	100	24

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report Version: Rev. 02

Report No.: FR941802AD Page: 21 of 60



Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal		
oo Level (dBu	V/m)		



	Freq. [Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.51	54.00	-15.49	41.58	-3.07	Average	100	125
2	2390.00	49.32	74.00	-24.68	52.39	-3.07	Peak	100	125
3	2483.50	38.63	54.00	-15.37	41.85	-3.22	Average	100	125
4	2483.50	49.25	74.00	-24.75	52.47	-3.22	Peak	100	125
5	4882.00	26.20	54.00	-27.80	22.59	3.61	Average	100	198
6	4882.00	56.30	74.00	-17.70	52.69	3.61	Peak	100	198
7	7323.00	23.85	54.00	-30.15	15.06	8.79	Average	100	197
8	7323.00	53.95	74.00	-20.05	45.16	8.79	Peak	100	197

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report Version: Rev. 02

Report No.: FR941802AD Page: 22 of 60



Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical		
90 Level (dBu\	//m)		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.51	54.00	-15.49	41.58	-3.07	Average	301	178
2	2390.00	49.10	74.00	-24.90	52.17	-3.07	Peak	301	178
3	2483.50	38.36	54.00	-15.64	41.58	-3.22	Average	301	178
4	2483.50	49.16	74.00	-24.84	52.38	-3.22	Peak	301	178
5	4882.00	25.78	54.00	-28.22	22.17	3.61	Average	100	96
6	4882.00	55.88	74.00	-18.12	52.27	3.61	Peak	100	96
7	7323.00	23.75	54.00	-30.25	14.96	8.79	Average	154	251
8	7323.00	53.85	74.00	-20.15	45.06	8.79	Peak	154	251

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

The previous version of the test report has been cancelled and replaced by new version.

Report No.: FR941802AD Report Version: Rev. 02

Page: 23 of 60



Modulation	GFSK		Test Freq. (MH	z)	2480	
Polarization	Horizontal			•		
oo Level (dE	Qu\//m\					
90	Juvilly					
80						
70					FCC CLAS	S-B
70						
60	4			ECC	CLASS-B (A	VC)
50 2	6			rcc	CLASS-D (A	vo)
50						
40 1						
30						
20						
10						
01000	4000. 6000. 80		0. 14000. 16000. 1 ency (MHz)	8000. 20000.	22000.	25000
	Frea Emission	Limit Margir		r Remark	ANT	Turn
	level	LIMIC HUISI	reading	i iteliai k		Table
	MHz dBuV/m	dBuV/m dB	dBuV dB		cm	deg
_				_		
	483.50 38.59		41.81 -3.2	_		121
	483.50 49.35		52.57 -3.2		100	121
	960.00 25.65 960.00 55.75	54.00 -28.35			100 100	185 185

8.54

8.54

Average

Peak

100

100

190

190

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR941802AD Page: 24 of 60


7440.00 23.00 54.00 -31.00 14.46 7440.00 53.10 74.00 -20.90 44.56

Report Version: Rev. 02

5



Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	J	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2/83 50	38.63	54 00	15 37	41.85	-3.22	Average	308	176
_						-3.22	Average		
2	2483.50	50.24	74.00	-23.76	53.46	-3.22	Peak	308	176
3	4960.00	26.42	54.00	-27.58	22.56	3.86	Average	100	97
4	4960.00	56.52	74.00	-17.48	52.66	3.86	Peak	100	97
5	7440.00	23.32	54.00	-30.68	14.78	8.54	Average	153	244
6	7440.00	53.42	74.00	-20.58	44.88	8.54	Peak	153	244


*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR941802AD Report Version: Rev. 02



Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK 3.2.6



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report Version: Rev. 02

Report No.: FR941802AD Page: 26 of 60



Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Ū	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	30 F1	<u></u> .	15 40	41 50		A	200	102
1	2390.00	38.51	54.00	-15.49	41.58	-3.07	Average	299	182
2	2390.00	49.62	74.00	-24.38	52.69	-3.07	Peak	299	182
3	4804.00	21.55	54.00	-32.45	18.05	3.50	Average	100	102
4	4804.00	51.65	74.00	-22.35	48.15	3.50	Peak	100	102
5	12010.00	24.75	54.00	-29.25	11.49	13.26	Average	100	33
6	12010.00	54.85	74.00	-19.15	41.59	13.26	Peak	100	33

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR941802AD

Report Version: Rev. 02



Modulation			8D	PSK				Test	Freq	ı. (MHz)		244	11	
Polarization			Но	rizon	al			•						
			•											
	90 ^L	evel (dBuV/m)											
	80													
	-											FC	C CLAS	S-B
	70													
	60			_							EC	C CL A	SS-B (A	MGY
	50	24		6	-8						10	CCLA	133-D (A	VO)
	40													
	30													
	20													
	10													
	01	000	4000.	6000	. 80	000. 100		00. 140 uency (N		6000. 180	00. 20000	. 220	000.	25000
			F	F		122.				C+	Damanl		ANT	Turn
			rreq.		sion vel	Limit	marg		A ding	Factor	Remark		ANT High	Table
			MHz			dBuV/ı	n dB	dB	_	dB			CM	deg
												_		
1 2			2390.0		.46	54.00 74.00	-15.54		.53 .39	-3.07	Averag	ge	323	84 84
3			2390.0 2483.5						.39	-3.07 -3.22	Peak Averag	76	323 323	84 84
4						74.00			.57	-3.22	Peak	,-	323	84

3.61

3.61

8.79

8.79

Average

Average

Peak

Peak

100

100

100

100

189

189

192

192

Page: 28 of 60

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor, cable loss and amplifier gain

4882.00 23.08 54.00 -30.92 19.47 4882.00 53.18 74.00 -20.82 49.57

7323.00 21.38 54.00 -32.62 12.59

7323.00 51.48 74.00 -22.52 42.69

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR941802AD

5

6


7

8

Report Version: Rev. 02



Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical		



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	38.45	54.00	-15.55	41.52	-3.07	Average	317	186
2	2390.00	49.58	74.00	-24.42	52.65	-3.07	Peak	317	186
3	2483.50	38.58	54.00	-15.42	41.80	-3.22	Average	317	186
4	2483.50	49.17	74.00	-24.83	52.39	-3.22	Peak	317	186
5	4882.00	21.36	54.00	-32.64	17.75	3.61	Average	100	105
6	4882.00	51.46	74.00	-22.54	47.85	3.61	Peak	100	105
7	7323.00	21.16	54.00	-32.84	12.37	8.79	Average	100	256
8	7323.00	51.26	74.00	-22.74	42.47	8.79	Peak	100	256

*Factor includes antenna factor, cable loss and amplifier gain

The previous version of the test report has been cancelled and replaced by new version.

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR941802AD Report Version: Rev. 02



Modulation			80	PSI	<				Test	Freq	ą. (MHz	<u>z</u>)		248	0	
Polarization			Но	rizo	ntal											
		evel ((dBuV/m)													
	90		dDa villi)													
	80															
	70					+-						+		FC	C CLAS	<u>S-B</u>
	70															
	60			_	_								FCC	CLA	SS-B (A	VG)
	50	- 1	2	4	6								100	02.1	J J J (N	
	40															
	30													_		
	20			3	5											
	20															
	10															
	0	1000	4000.	60	00. 8	000.	1000	0. 1200	D. 14 (000. 1	6000. 1	8000.	20000.	2200	00.	25000
								Frequ	ency (MHz)						
			Freq.				nit	Margi		Α	Factor	r R	Remark		ANT	Turn
					level					ding					High	Tabl
			MHz	di	BuV/m	dBi	uV/m	dВ	dE	uV	dB				CM	deg
1			2483.5	0 -	38.36	54	.00	-15.64	41	.58	-3.22	2 4	verage		312	85
2			2483.5		50.98			-23.02		.20	-3.22		eak		312	85
3			4960.0		22.58			-31.42		.72	3.86		verage	2	100	186
4			4960.0	_						.82	3.86		eak		100	186
5 6			7440.0							.47 .57	8.54 8.54		lverage Peak	2	100 100	193 193

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report Version: Rev. 02

Report No.: FR941802AD Page: 30 of 60



Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



		Emission level		Ü	SA reading		Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2483.50	38.63	54.00	-15.37	41.85	-3.22	Average	313	181
2	2483.50	50.95	74.00	-23.05	54.17	-3.22	Peak	313	181
3	4960.00	21.93	54.00	-32.07	18.07	3.86	Average	100	95
4	4960.00	52.03	74.00	-21.97	48.17	3.86	Peak	100	95
5	7440.00	21.32	54.00	-32.68	12.78	8.54	Average	144	259
6	7440.00	51.42	74.00	-22.58	42.88	8.54	Peak	144	259

*Factor includes antenna factor, cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report Version: Rev. 02



Test Configuration 2: Charger mode

3.2.7 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Page: 32 of 60

Report No.: FR941802AD

Report Version: Rev. 02



Modulation Polarization		GFS	GFSK				Test Freq. (MHz)				2480		
			Vertical										
	90 L	_evel (d	BuV/m)										
	90												
	80												
	70												
	70												
	60										FCC	CLAS	S B
	50										100	CLAS	3-0
	30					+							
	40						6						_
	30	12		3 4	5								
	20												
	10												
	0	30 10	0. 200	0. 30	0. 4	00.		00. 60	0. 700.	800.	9(00.	1000
								ency (MHz)					_
			Freq. E	mission level	Limit	Ma	rgin	SA reading	Factor	Remark		ANT High	Turn Table
			MHz	dBuV/m	dBuV/	m d	R	dBuV	dB			ingii	deg
			11112	abav/ III	ubu*/			abav	ub				ucg
1	L	-	32.91	29.20	40.00	-10	.80	37.96	-8.76	Peak			
2	<u>)</u>		46.49	28.73	40.00			36.51	-7.78	Peak			
3			232.73	28.49				38.59		Peak			
4			298.69	30.31				38.14	-7.83	Peak			
9)		374.35	29.46	46.00	-16	.54	35.15	-5.69	Peak			

-3.93

Peak

Page: 33 of 60

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

449.04 35.53 46.00 -10.47 39.46

Report No.: FR941802AD

Report Version: Rev. 02



3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures


Reference level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Use the peak marker function to determine the maximum PSD level

Emission level measurement

- 1. Set RBW=100kHz, VBW = 300kHz, Detector = Peak, Sweep time = Auto
- 2. Trace = max hold, Allow Trace to fully stabilize
- 3. Scan Frequency range is up to 25GHz
- 4. Use the peak marker function to determine the maximum amplitude level


3.3.3 Test Setup



Report No.: FR941802AD Page: 34 of 60




3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands




Report No.: FR941802AD Report Version: Rev. 02






Report No.: FR941802AD Report Version: Rev. 02









Report No.: FR941802AD Page: 38 of 60

Report Version: Rev. 02



3.4 Conducted Output Power

3.4.1 Limit of Conducted Output Power

1 Watt For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
0.125 Watt For all other frequency hopping systems in the 2400–2483.5 MHz band.
0.125 Watt For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

- A wideband power meter is used for power measurement. Bandwidth of power senor and meter is 50MHz
- 2 If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup



Report No.: FR941802AD Page: 39 of 60

Report Version: Rev. 02



3.4.4 Test Result of Conducted Output Power

Summary of Peak Conducted Output Power

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	9.98	0.00995
BT-EDR(2Mbps)	8.45	0.00700
BT-EDR(3Mbps)	8.72	0.00745

Result

Mode	Result	Gain	Power	Power Limit
		(dBi)	(dBm)	(dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	2.80	9.95	21.00
2441MHz	Pass	2.80	9.67	21.00
2480MHz	Pass	2.80	9.98	21.00
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	2.80	7.20	21.00
2441MHz	Pass	2.80	7.89	21.00
2480MHz	Pass	2.80	8.45	21.00
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	2.80	7.52	21.00
2441MHz	Pass	2.80	8.14	21.00
2480MHz	Pass	2.80	8.72	21.00

Report No.: FR941802AD

Report Version: Rev. 02



Summary of Conducted (Average) Output Power

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	9.91	0.00979
BT-EDR(2Mbps)	5.86	0.00385
BT-EDR(3Mbps)	5.90	0.00389

Result

Mode	Result	Gain	Power	Power Limit
		(dBi)	(dBm)	(dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	2.80	9.86	-
2441MHz	Pass	2.80	9.60	-
2480MHz	Pass	2.80	9.91	-
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	2.80	4.53	-
2441MHz	Pass	2.80	5.22	-
2480MHz	Pass	2.80	5.86	-
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	2.80	4.54	-
2441MHz	Pass	2.80	5.23	-
2480MHz	Pass	2.80	5.90	-

Note: Average power is for reference only.

Report No.: FR941802AD Report Version: Rev. 02



3.5 Number of Hopping Frequency


3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.5.2 Test Procedures

- 1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
- 2 Allow trace to stabilize.

3.5.3 Test Setup



Report No.: FR941802AD Page: 42 of 60



3.5.4 Test Result of Number of Hopping Frequency

Summary

Mode	Max-Hop No	
2.4-2.4835GHz	-	
BT-BR(1Mbps)	79	
BT-EDR(2Mbps)	79	
BT-EDR(3Mbps)	79	


Result

Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(2Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(3Mbps)	-	-	-
2441MHz	Pass	79	15

Report No.: FR941802AD Page: 43 of 60

Report Version: Rev. 02







3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures


20dB Bandwidth

- Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Peak, Trace max hold
- 2 Allow trace to stabilize
- 3 Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

- Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Sample, Trace max hold
- 2 Allow trace to stabilize
- 3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup



Report No.: FR941802AD Page: 45 of 60



3.6.3 Test result of 20dB and Occupied Bandwidth

Summary

Mode	Max-N dB	Max-OBW	ITU-Code	Min-N dB	Min-OBW
	(Hz)	(Hz)		(Hz)	(Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-BR(1Mbps)	923.913k	897.25k	897KF1D	920.29k	893.632k
BT-EDR(2Mbps)	1.351M	1.226M	1M23G1D	1.348M	1.212M
BT-EDR(3Mbps)	1.366M	1.219M	1M22G1D	1.333M	1.216M

Max-N dB = Maximum 20dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth; **Min-N dB** = Minimum 20dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result


Mode	Result	Limit	Port 1-N dB	Port 1-OBW
		(Hz)	(Hz)	(Hz)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	Inf	920.29k	893.632k
2441MHz	Pass	Inf	920.29k	893.632k
2480MHz	Pass	Inf	923.913k	897.25k
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.351M	1.223M
2441MHz	Pass	Inf	1.348M	1.212M
2480MHz	Pass	Inf	1.348M	1.226M
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.366M	1.216M
2441MHz	Pass	Inf	1.341M	1.216M
2480MHz	Pass	Inf	1.333M	1.219M

Port X-N dB = Port X 20dB down bandwidth; Port X-OBW = Port X 99% occupied bandwidth;


Report Version: Rev. 02

Report No.: FR941802AD Page: 46 of 60
















3.7 Channel Separation

3.7.1 Limit of Channel Separation


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum
of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures

- 1. Set RBW=30kHz, VBW=100kHz,Sweep time = Auto, Detector=Peak Trace max hold
- 2 Allow trace to stabilize
- 3 Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup



Report No.: FR941802AD

Page: 50 of 60



3.7.4 Test result of Channel Separation

Summary


Mode	Max-Space	Min-Space
	(Hz)	(Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1.16087M	934.782609k
BT-EDR(2Mbps)	1.034783M	1M
BT-EDR(3Mbps)	1M	986.956522k

Result

Mode	Result	FI	Fh	Ch.Space	Limit
		(Hz)	(Hz)	(Hz)	(Hz)
BT-BR(1Mbps)	-	-	-	-	-
2402MHz	Pass	2.40203G	2.40303G	1M	612.91314k
2441MHz	Pass	2.440961G	2.442122G	1.16087M	612.91314k
2480MHz	Pass	2.479026G	2.479961G	934.782609k	615.326058k
BT-EDR(2Mbps)	-	-	-	-	-
2402MHz	Pass	2.401965G	2.402965G	1M	899.766k
2441MHz	Pass	2.440961G	2.441965G	1.004348M	897.768k
2480MHz	Pass	2.478926G	2.479961G	1.034783M	897.768k
BT-EDR(3Mbps)	-	-	-	-	-
2402MHz	Pass	2.401965G	2.402965G	1M	909.756k
2441MHz	Pass	2.440961G	2.441961G	1M	893.106k
2480MHz	Pass	2.478961G	2.479948G	986.956522k	887.778k

Report Version: Rev. 02






Report No.: FR941802AD Page: 52 of 60

Report Version: Rev. 02






Report No.: FR941802AD Page: 53 of 60

Report Version: Rev. 02





Report No.: FR941802AD

Page: 54 of 60

Report Version: Rev. 02



3.8 Number of Dwell Time

3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures

- 1. Set RBW=300kHz,VBW=1MHz,Sweep time = 10 ms, Detector=Peak, Span=0Hz,Trace max hold
- 2 Enable gating and trigger function of spectrum analyzer to measure burst on time.
- The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots. Non AFH mode

The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds. DH1 Packet permit maximum 1600 / 79 / 2 = 10.12 hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds. AFH mode

The hopping rate is 800 hops/second so the maximum dwell time is 1/800 seconds. DH1 Packet permit maximum 800/20/2 = 20 hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $20 \times 8 = 160$ within 8 seconds.

4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots. Non AFH mode

The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds. DH3 Packet permit maximum 1600 / 79 / 4 = 5.06 hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160 \text{ within } 31.6 \text{ seconds}$. AFH mode

The hopping rate is 800hops/second so the maximum dwell time is 3/800 seconds. DH3 Packet permit maximum 800 / 20 / 4 = 10 hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10 \times 8 = 80$ within 8 seconds.

The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots.


Non AFH mode

The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum 1600/79/6 = 3.37 hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds

AFH mode

The hopping rate is 800 hops/second so the maximum dwell time is 5/800 seconds. DH5 Packet permit maximum 800/20 / 6 = 6.667 hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $6.667 \times 8 = 53.33$ within 8 seconds

3.8.3 Test Setup



Report No.: FR941802AD Page: 55 of 60

Report Version: Rev. 02



3.8.4 Test Result of Dwell Time

Summary

Mode	Max-Dwell			
	(s)			
2.4-2.4835GHz	-			
BT-BR(1Mbps)	310.530435m_DH5			
BT-EDR(2Mbps)	310.530435m_DH5			
BT-EDR(3Mbps)	310.530435m_DH5			

Result/ Non AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (s)
2441MHz	Pass	31.6	310.530435m_DH5	400m	2.913043m
2441MHz	Pass	31.6	266.666667m_DH3	400m	1.666667m
2441MHz	Pass	31.6	129.855072m_DH1	400m	405.797101ι
BT-EDR(2Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	310.530435m_DH5	400m	2.913043m
2441MHz	Pass	31.6	266.666667m_DH3	400m	1.666667m
2441MHz	Pass	31.6	129.855072m_DH1	400m	405.797101
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	310.530435m_DH5	400m	2.913043m
2441MHz	Pass	31.6	264.347826m_DH3	400m	1.652174m
2441MHz	Pass	31.6	129.855072m_DH1	400m	405.797101u


Result/ AFH mode

Mode	Result	Period	Dwell	Limit	Tx On
		(s)	(s)	(s)	(s)
BT-BR(1Mbps)	-	-	-	-	-
2441MHz	Pass	8	155.3526m_DH5	400m	2.913043m
2441MHz	Pass	8	133.3334m_DH3	400m	1.666667m
2441MHz	Pass	8	64.92754m_DH1	400m	405.797101u
BT-EDR(2Mbps)	-	-	-	-	-
2441MHz	Pass	8	155.3526m_DH5	400m	2.913043m
2441MHz	Pass	8	133.3334m_DH3	400m	1.666667m
2441MHz	Pass	8	64.92754m_DH1	400m	405.797101u
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz	Pass	8	155.3526m_DH5	400m	2.913043m
2441MHz	Pass	8	132.1739m_DH3	400m	1.652174m
2441MHz	Pass	8	64.92754m_DH1	400m	405.797101u


Report Version: Rev. 02

Report No.: FR941802AD Page: 56 of 60
















4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Page: 60 of 60

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FR941802AD

Report Version: Rev. 02