

# **FCC Test Report**

FCC ID : XNAWSM02

Equipment : Nokia Sleep

Model No. : WSM02

Brand Name : NOKIA

Applicant : NOKIA TECHNOLOGIES (France)

Address : 2 rue Maurice Hartmann

92130 Issy-Les-Moulineaux

**France** 

Standard : 47 CFR FCC Part 15.247

Received Date : Sep. 28, 2017

Tested Date : Oct. 24 ~ Nov. 10, 2017

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Chen Assistant Manager Gary Chang / Manager

Testing Laboratory 2732

Report No.: FR792802AE Page: 1 of 32



# **Table of Contents**

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	Test Equipment List and Calibration Data	8
1.5	Test Standards	9
1.6	Measurement Uncertainty	9
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	Conducted Emissions	11
3.2	6dB and Occupied Bandwidth	14
3.3	RF Output Power	16
3.4	Power Spectral Density	18
3.5	Emissions in Restricted Frequency Bands	
3.6	Emissions in non-restricted Frequency Bands	30
4	TEST LABORATORY INFORMATION	32



# **Release Record**

Report No.	Version	Description	Issued Date
FR792802AE	Rev. 01	Initial issue	Jan. 31, 2018

Report No.: FR792802AE Page: 3 of 32



# **Summary of Test Results**

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.476MHz 34.92(Margin -11.49dB) - AV	Pass
15.247(d)	Radiated Emissions	[dBuV/m at 3m]: 7320.00MHz	Pass
15.209	Radiated Emissions	51.68 (Margin -2.32dB) - AV	Pa55
15.247(b)(3)	Maximum Output Power	Power [dBm]: 4.82	Pass
15.247(a)(2)	6dB Bandwidth	Meet the requirement of limit	Pass
15.247(e)	Power Spectral Density	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Report No.: FR792802AE Page: 4 of 32



# 1 General Description

# 1.1 Information

## 1.1.1 Specification of the Equipment under Test (EUT)

RF General Information								
Frequency Range (MHz) Bluetooth Ch. Freq. (MHz) Channel Number Data Rate								
2400-2483.5	V4.1 LE	2402-2480	0-39 [40]	1 Mbps				
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.								

### 1.1.2 Antenna Details

Ant. No.	Brand	Model	Туре	Connector	Gain (dBi)	Remarks
1	Broadcom	BCM9Fractal	PCB	N/A	2.8	

## 1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	5Vdc from AC adapter
-------------------	----------------------

## 1.1.4 Accessories

	Accessories					
No.	Equipment	Description				
1	AC adapter	Brand: ABP Model: SWA06B-050-1000U Power Rating: I/P: 100-240Vac, 50-60Hz, 0.3A O/P: 5Vdc, 1000mA				

Report No.: FR792802AE Page: 5 of 32



## 1.1.5 Channel List

	Frequency	band (MHz)		2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
37	2402	9	2422	18	2442	28	2462
0	2404	10	2424	19	2444	29	2464
1	2406	38	2426	20	2446	30	2466
2	2408	11	2428	21	2448	31	2468
3	2410	12	2430	22	2450	32	2470
4	2412	13	2432	23	2452	33	2472
5	2414	14	2434	24	2454	34	2474
6	2416	15	2436	25	2456	35	2476
7	2418	16	2438	26	2458	36	2478
8	2420	17	2440	27	2460	39	2480

# 1.1.6 Test Tool and Duty Cycle

Test tool	Tera Term, ver. 4.94
Duty cycle of test signal (%)	63.89%
Duty Factor (dB)	1.95

# 1.1.7 Power Setting

Madulation Mada	Test Frequency (MHz)				
Modulation Mode	2402	2440	2480		
GFSK/1Mbps	Default	Default	Default		


Report No.: FR792802AE Page: 6 of 32



# 1.2 Local Support Equipment List

	Support Equipment List							
No.	No. Equipment Brand Model FCC ID Signal cable / Length (m)							
1	Notebook	DELL	Latitude E6430	Doc				

# 1.3 Test Setup Chart



Note: The notebook is disconnected from EUT and removed from test table when EUT is set to transmit continuously.

Report No.: FR792802AE Page: 7 of 32



# 1.4 Test Equipment List and Calibration Data

Test Item	Conducted Emission	Conducted Emission						
Test Site	Conduction room 1 /	Conduction room 1 / (CO01-WS)						
Tested Date	Nov. 01, 2017	Nov. 01, 2017						
Instrument	Manufacturer Model No. Serial No. Calibration Date Calibration Until							
Receiver	R&S ESR3 101657 Dec. 21, 2016 Dec. 20, 201							
LISN	SCHWARZBECK         Schwarzbeck 8127         8127-667         Nov. 08, 2016         Nov.							
RF Cable-CON	EMC EMCCFD300-BM-BM-6000 50821 Dec. 20, 2016 Dec. 19, 2017							
Measurement Software	AUDIX e3 6.120210k NA NA							
	Software AODIX e3 6.120210K NA							

Test Item	Radiated Emission	Radiated Emission						
Test Site	966 chamber 3 / (03C	966 chamber 3 / (03CH03-WS)						
Tested Date	Oct. 24 ~ Oct. 25, 2017							
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	ROHDE&SCHWAR Z	FSV40	101486	Nov. 15, 2016	Nov. 14, 2017			
Receiver	Agilent	N9038A	MY53290044	Sep. 26, 2017	Sep. 25, 2018			
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 28, 2017	Apr. 27, 2018			
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Feb. 09, 2017	Feb. 08, 2018			
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170508	Dec. 29, 2016	Dec. 28, 2017			
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 10, 2016	Nov. 09, 2017			
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Dec. 09, 2016	Dec. 08, 2017			
Preamplifier	EMC	EMC02325	980187	Sep. 04, 2017	Sep. 03, 2018			
Preamplifier	Agilent	83017A	MY53270014	Aug. 21, 2017	Aug. 20, 2018			
Preamplifier	EMC	EMC184045B	980192	Aug. 22, 2017	Aug. 21, 2018			
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/4	Feb. 04, 2017	Feb. 03, 2018			
RF cable-8M	HUBER+SUHNER	SUCOFLEX104	MY22600/4	Feb. 04, 2017	Feb. 03, 2018			
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Feb. 04, 2017	Feb. 03, 2018			
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Feb. 04, 2017	Feb. 03, 2018			
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Feb. 04, 2017	Feb. 03, 2018			
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104	Feb. 04, 2017	Feb. 03, 2018			
Measurement Software								
Note: Calibration Inter	rval of instruments liste	d above is one year.						

Report No.: FR792802AE Page: 8 of 32



Test Item	RF Conducted	RF Conducted						
Test Site	(TH01-WS)	(TH01-WS)						
Tested Date	Nov. 10, 2017							
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until			
Spectrum Analyzer	R&S	FSV40	101063	Mar. 15, 2017	Mar. 14, 2018			
Power Meter	Anritsu	ML2495A	1241002	Oct. 16, 2017	Oct. 15, 2018			
Power Sensor	Anritsu	MA2411B	1207366	Oct. 16, 2017	Oct. 15, 2018			
AC POWER SOURCE	G.W .	APS-9102	EL920581	Jun. 03, 2017	Jun. 02, 2018			
Measurement Software	Sporton Sporton_1 1.3.30 NA NA							
Note: Calibration Inter	rval of instruments liste	d above is one year.		•				

## 1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247 ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v04

# 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty				
Parameters	Uncertainty			
Bandwidth	±34.134 Hz			
Conducted power	±0.808 dB			
Power density	±0.463 dB			
Conducted emission	±2.670 dB			
AC conducted emission	±2.90 dB			
Radiated emission ≤ 1GHz	±3.66 dB			
Radiated emission > 1GHz	±5.37 dB			

Report No.: FR792802AE Page: 9 of 32



# 2 Test Configuration

# 2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	23°C / 59%	Alex Tsai
Radiated Emissions	03CH03-WS	24-25°C / 64-66%	Aska Huang
RF Conducted	TH01-WS	22°C / 63%	Brad Wu

FCC Designation No.: TW0009
 FCC site registration No.: 207696
 IC site registration No.: 10807C-1

## 2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions Radiated Emissions ≤ 1GHz	BT LE	2440	1Mbps	
Maximum Output Power 6dB bandwidth Power spectral density Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1Mbps	

### NOTE:

Report No.: FR792802AE Page: 10 of 32

<sup>1.</sup> The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Y-plane** results were found as the worst case and were shown in this report.



## 3 Transmitter Test Results

### 3.1 Conducted Emissions

#### 3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit					
Frequency Emission (MHz) Quasi-Peak Average					
0.15-0.5	66 - 56 *	56 - 46 *			
0.5-5	56	46			
5-30 60 50					
Note 1: * Decreases with the logarithm of the frequency.					

#### 3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50  $\Omega$  LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V/60Hz

#### 3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR792802AE Page: 11 of 32




#### **Test Result of Conducted Emissions** 3.1.4



Report No.: FR792802AE Page: 12 of 32





Report No.: FR792802AE Page: 13 of 32



## 3.2 6dB and Occupied Bandwidth

#### 3.2.1 Limit of 6dB Bandwidth

The minimum 6dB bandwidth shall be at least 500 kHz.

#### 3.2.2 Test Procedures


#### 6dB Bandwidth

- 1. Set resolution bandwidth (RBW) = 100 kHz, Video bandwidth = 300 kHz.
- 2. Detector = Peak, Trace mode = max hold.
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

## **Occupied Bandwidth**

- Set resolution bandwidth (RBW) = 30 kHz, Video bandwidth = 100 kHz.
- 2. Detector = Sample, Trace mode = max hold.
- 3 Sweep = auto couple, Allow the trace to stabilize.
- 4. Use the OBW measurement function of spectrum analyzer to measure the occupied bandwidth.

### 3.2.3 Test Setup




Report No.: FR792802AE Page: 14 of 32



## 3.2.4 Test Result of 6dB and Occupied Bandwidth

Mode	Freq. (MHz)	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit of 6dB Bandwidth (kHz)
BT LE	2402	0.717	1.05	500
BT LE	2440	0.713	1.05	500
BT LE	2480	0.717	1.05	500



Report No.: FR792802AE Page: 15 of 32



## 3.3 RF Output Power

### 3.3.1 Limit of RF Output Power

Con	duct	ed power shall not exceed 1Watt.
$\boxtimes$	Ante	enna gain <= 6dBi, no any corresponding reduction is in output power limit.
	Ante	enna gain > 6dBi
		Non Fixed, point to point operations.  The conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dB
		Fixed, point to point operations Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point Operations, maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
		Systems operating in the 5725–5850 MHz band that are used exclusively for fixed, point-to-point operations ,no any corresponding reduction is in transmitter peak output power

#### 3.3.2 Test Procedures

Maximum Peak Conducted Output Power

#### □ Spectrum analyzer

- 1. Set RBW = 1MHz, VBW = 3MHz, Detector = Peak.
- 2. Sweep time = auto, Trace mode = max hold, Allow trace to fully stabilize.
- 3. Use the spectrum analyzer channel power measurement function with the band limits set equal to the DTS bandwidth edges.

#### Nower meter

- A broadband Peak RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.
- Maximum Conducted Average Output Power (For reference only)

#### Nower meter

 A broadband Average RF power meter is used for output power measurement. The video bandwidth of power meter is greater than DTS bandwidth of EUT. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power.

### 3.3.3 Test Setup



Report No.: FR792802AE Page: 16 of 32



# 3.3.4 Test Result of Maximum Output Power

		Peak Power			Antenna	EIRP	EIRP
Mode	Freq. (MHz)	Power (mW)	Power (dBm)	Limit (dBm)	gain (dBi)	(dBm)	Limit (dBm)
BT LE	2402	2.978516	4.74	30	2.8	7.54	36
BT LE	2440	3.033891	4.82	30	2.8	7.62	36
BT LE	2480	2.673006	4.27	30	2.8	7.07	36

Mode	Freq. (MHz)	AV Power (mW)	AV Power (dBm)	Limit (dBm)
BT LE	2402	2.877398	4.59	
BT LE	2440	2.917427	4.65	
BT LE	2480	2.58226	4.12	

Note: Average power is for reference only

Report No.: FR792802AE Page: 17 of 32



## 3.4 Power Spectral Density


### 3.4.1 Limit of Power Spectral Density

Power spectral density shall not be greater than 8 dBm in any 3 kHz band.

#### 3.4.2 Test Procedures

- Maximum peak conducted output power was used to demonstrate compliance to the fundamental output power limit.
  - Set the RBW = 3kHz, VBW = 10kHz.
  - 2. Detector = Peak, Sweep time = auto couple.
  - 3. Trace mode = max hold, allow trace to fully stabilize.
  - 4. Use the peak marker function to determine the maximum amplitude level.
- Maximum (average) conducted output power was used to demonstrate compliance to the fundamental output power limit.
  - 1. Set the RBW = 100kHz, VBW = 300 kHz.
  - 2. Detector = RMS, Sweep time = auto couple.
  - 3. Set the sweep time to: ≥ 10 x (number of measurement points in sweep) x (maximum data rate per stream).
  - 4. Perform the measurement over a single sweep.
  - 5. Use the peak marker function to determine the maximum amplitude level.

## 3.4.3 Test Setup




Report No.: FR792802AE Page: 18 of 32



## 3.4.4 Test Result of Power Spectral Density

Mode	Freq. (MHz)	Total Power Spectral Density (dBm/3kHz)	Limit (dBm/3kHz)
BT LE	2402	-9.87	8
BT LE	2440	-9.95	8
BT LE	2480	-10.45	8



Report No.: FR792802AE Page: 19 of 32



## 3.5 Emissions in Restricted Frequency Bands

### 3.5.1 Limit of Emissions in Restricted Frequency Bands

Restricted Band Emissions Limit						
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)			
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300			
0.490~1.705	24000/F(kHz)	33.8 - 23	30			
1.705~30.0	30	29	30			
30~88	100	40	3			
88~216	150	43.5	3			
216~960	200	46	3			
Above 960	500	54	3			

#### Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2**:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

#### 3.5.2 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- 2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


#### Note:

- 1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
- 2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
- RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

Report No.: FR792802AE Page: 20 of 32




## 3.5.3 Test Setup



Report No.: FR792802AE Page: 21 of 32



## 3.5.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR792802AE Page: 22 of 32



Modulation	ılation			GFSK			Test Freq. (MHz)			2440	
Polarization			Verti	cal		*					
			•								
	90 <sup>L(</sup>	evel (d	IBuV/m)								
	80										
	70										
	60										
	00									FCC CLAS	S-B
	50										_
	40			_							<u></u>
	_	.							5		
	30-		2	3	4						
	20			Ť							
	10										
	03	0 10	0. 20	0. 30	0. 40		00. 600	0. 700.	800.	900.	1000
							ency (MHz)				_
			Freq. t	mission: level	Limit	Margir	n SA reading	Factor	Remark	ANT High	Turn Table
			MHz	dBuV/m	dBuV/r	n dB	dBuV	dB		cm	deg
1				27.49		-12.51	36.04	-8.55	Peak		
2			192.96	22.28		-21.22	33.13	-10.85	Peak		
3			242.43			-24.53	31.02	-9.55	Peak		
4			345.25	24.35			31.20	-6.85	Peak		
5			794.36			-13.26	30.63	2.11	Peak		
6			955.38	38.29	46.00	-7.71	33.61	4.68	Peak		


\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report No.: FR792802AE Page: 23 of 32



## 3.5.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR792802AE Page: 24 of 32



Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	40.50	54.00	-13.50	42.47	-1.97	Average	100	110
2	2390.00	52.28	74.00	-21.72	54.25	-1.97	Peak	100	110
3	4804.00	47.43	54.00	-6.57	42.81	4.62	Average	224	333
4	4804.00	53.71	74.00	-20.29	49.09	4.62	Peak	224	333
5	12010.00	43.19	54.00	-10.81	29.28	13.91	Average	100	164
6	12010.00	54.55	74.00	-19.45	40.64	13.91	Peak	100	164

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR792802AE Page: 25 of 32






\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR792802AE Page: 26 of 32



Modulation	GFSK	Test Freq. (MHz)	2440
Polarization	Vertical		



	Freq.   MHz	Emission level dBuV/m	Limit dBuV/m		SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
		abav,	ubuv,	u.	abar	u.		C	acg
1	2390.00	40.73	54.00	-13.27	42.70	-1.97	Average	100	127
2	2390.00	52.62	74.00	-21.38	54.59	-1.97	Peak	100	127
3	2483.50	41.18	54.00	-12.82	42.80	-1.62	Average	100	127
4	2483.50	53.11	74.00	-20.89	54.73	-1.62	Peak	100	127
5	4880.00	48.11	54.00	-5.89	43.33	4.78	Average	230	338
6	4880.00	54.08	74.00	-19.92	49.30	4.78	Peak	230	338
7	7320.00	51.68	54.00	-2.32	42.34	9.34	Average	200	250
8	7320.00	59.90	74.00	-14.10	50.56	9.34	Peak	200	250

\*Factor includes antenna factor, cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR792802AE Page: 27 of 32



Modulation			GFSK			-	Test Freq. (MHz)			2480	
Polarization			Hori	zontal		1					
		evel	(dBuV/m)								
	90		(ubuviiii)								
	80									F00 01 4 0	
	70									FCC CLAS	S-B
	70										
	60	-	2 4	6					FCC	CLASS-B (A	WG)
	50		4						100	CLASS-D (A	<del>, , , , , , , , , , , , , , , , , , , </del>
			1								
	40										
	30	_									
	20										
	20										
	10										
	0		4000	2000			44000 4	2000 400		2222	05000
		1000	4000.	6000. 80	00. 100		. 14000. 1 ncy (MHz)	6000. 180	00. 20000.	22000.	25000
			Freq. E	mission	Limit	Margin	SA	Factor	Remark	ANT	Turn
				level			reading			High	Table
			MHz	dBuV/m	dBuV/ı	n dB	dBuV	dB		cm	deg
1	L		2483.50	40.05	54.00	-13.95	41.67	-1.62	Average	100	63
2			2483.50				55.18	-1.62	Peak	100	63
3	3		4960.00	46.06	54.00	-7.94	41.13	4.93	Average	220	305

47.62

37.38

4.93

9.68

9.68

Peak

Peak

Average

220

100

100

305

63

63

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

4960.00 52.55 74.00 -21.45

7440.00 47.06 54.00 -6.94

7440.00 56.56 74.00 -17.44 46.88

\*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Report No.: FR792802AE Page: 28 of 32

Report Version: Rev. 01

5



Modulation	GFSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2483.50	43.80	54.00	-10.20	45.42	-1.62	Average	100	89
2	2483.50	64.76	74.00	-9.24	66.38	-1.62	Peak	100	89
3	4960.00	48.88	54.00	-5.12	43.95	4.93	Average	222	339
4	4960.00	54.95	74.00	-19.05	50.02	4.93	Peak	222	339
5	7440.00	51.52	54.00	-2.48	41.84	9.68	Average	203	255
6	7440.00	59.67	74.00	-14.33	49.99	9.68	Peak	203	255

\*Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR792802AE Page: 29 of 32



# 3.6 Emissions in non-restricted Frequency Bands

## 3.6.1 Emissions in non-restricted frequency bands limit

The peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

#### 3.6.2 Test Procedures


#### Reference Level Measurement

- 1. Set the RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Set Sweep time = auto couple, Trace mode = max hold.
- 3. Allow trace to fully stabilize.
- 4. Use the peak marker function to determine the maximum amplitude level.

#### **Unwanted Emissions Level Measurement**

- 1. Set RBW = 100 kHz, VBW = 300 kHz, Detector = peak.
- 2. Trace Mode = max hold, Sweep = auto couple.
- 3. Allow the trace to stabilize.
- 4. Use peak marker function to determine maximum amplitude of all unwanted emissions within any 100 kHz bandwidth.


#### 3.6.3 Test Setup



Report No.: FR792802AE Page: 30 of 32



## 3.6.4 Test Result of Emissions in non-restricted Frequency Bands



Report No.: FR792802AE Report Version: Rev. 01



# 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <a href="http://www.icertifi.com.tw">http://www.icertifi.com.tw</a>.

#### Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

#### Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

#### Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC\_Service@icertifi.com.tw

==END==

Report No.: FR792802AE Page: 32 of 32