

FCC RADIO TEST REPORT

Applicant's company	Joymax Electronics Co., Ltd.
Applicant Address	No. 5, Dong Yuan Rd. 2, Jhongli Industrial Park, Jhongli City, Tao Yuan 32063 Taiwan, R.O.C.
FCC ID	XNNMD120FC
Manufacturer's company	Joymax Electronics Co., Ltd.
Manufacturer Address	No. 5, Dong Yuan Rd. 2, Jhongli Industrial Park, Jhongli City, Tao Yuan 32063 Taiwan, R.O.C.

Product Name	2.4GHz ZigBee Wireless Module
Brand Name	Joymax
Model No.	MD-120FC
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2405~ 2475MHz
Received Date	Dec. 17, 2012
Final Test Date	Jun. 04, 2013
Submission Type	Original Equipment



Statement

Test result included is only for the IEEE 802.15.4 ZigBee part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009, 47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03 and KDB 662911 D01 v01r02.**

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	3
3.4. Table for Carrier Frequencies	3
3.5. Table for Test Modes	4
3.6. Table for Testing Locations.....	4
3.7. Table for Supporting Units	5
3.8. Table for Parameters of Test Software Setting	5
3.9. EUT Operation during Test	5
3.10. Duty Cycle.....	6
3.11. Test Configurations	7
4. TEST RESULT	9
4.1. AC Power Line Conducted Emissions Measurement.....	9
4.2. Maximum Conducted Output Power Measurement.....	13
4.3. Power Spectral Density Measurement	15
4.4. 6dB Spectrum Bandwidth Measurement	20
4.5. Radiated Emissions Measurement	24
4.6. Emissions Measurement	39
4.7. Antenna Requirements	52
5. LIST OF MEASURING EQUIPMENTS	53
6. TEST LOCATION.....	55
APPENDIX A. TEST PHOTOS	A1 ~ A9
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B5


History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR2D1701	Rev. 01	Initial issue of report	Jun. 24, 2013

1. CERTIFICATE OF COMPLIANCE

Product Name : 2.4GHz ZigBee Wireless Module
Brand Name : Joymax
Model No. : MD-120FC
Applicant : Joymax Electronics Co., Ltd.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Dec. 17, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	4.87dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	12.77 dB
4.3	15.247(e)	Power Spectral Density	Complies	3.97 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	1.56 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.33 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	From host system
Modulation	DSSS (O-QPSK)
Data Rate (Mbps)	DSSS (250kbps)
Frequency Range	2405~ 2475MHz
Channel Number	15
Channel Band Width (99%)	2.44 MHz
Maximum Conducted Output Power	17.23 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Ant. Gain (dBi)	Cable Loss	Total Gain (dBi)
1	JOYMAX	IWX-152RSXXX-999	Swivel Antenna	Reversed-SMA	4	1.6	2.4
2	JOYMAX	IFF-BS01IPXX-753	PIFA Antenna	I-PEX	3	0.3	2.7
3	JOYMAX	IPF-003XMPXX-500	Patch Antenna	I-PEX	3	0.45	2.55

3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2405 ~ 2475MHz	11	2405 MHz	19	2445 MHz
	12	2410 MHz	20	2450 MHz
	13	2415 MHz	21	2455 MHz
	14	2420 MHz	22	2460 MHz
	15	2425 MHz	23	2465 MHz
	16	2430 MHz	24	2470 MHz
	17	2435 MHz	25	2475 MHz
	18	2440 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	-	-	-
Maximum Conducted Output Power	TX Mode	250 kbps	11/18/25	1, 2, 3
Power Spectral Density 6dB Spectrum Bandwidth	TX Mode	250 kbps	11/18/25	1, 2, 3
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-
Radiated Emissions 1GHz~10 th Harmonic	TX Mode	250 kbps	11/18/25	1, 2, 3
Band Edge Emissions	TX Mode	250 kbps	11/25	1, 2, 3

The following test modes were performed for all tests:

For Conducted Emission test and For Radiated Emission test (30MHz~1GHz):

EUT has three types of antenna. Only the highest gain antenna was selected from each different types of antenna to test and record in the report.

Mode 1. Ant. 2

For Radiated Emission test (Above 1GHz):

Mode 1. Ant. 1

Mode 2. Ant. 2

Mode 3. Ant. 3

All test results were recorded in the report.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

< AC Power Line Conduction Emissions and Radiation Emissions(30MHz -1GHz) >

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	QDS-BRCM1049LE
Notebook	DELL	D420	E2KWM3945ABG
Mouse	Logitech	M-U0026	DoC
Earphone	E-BOOKI	E-EPC040	N/A
Zigbee RX	N/A	N/A	N/A
Fixture	Joymax	210206001	N/A

< Radiation Emissions(Above 1GHz) >

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	QDS-BRCM1049LE
Fixture	Joymax	210206001	N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.15.4 ZigBee (Ant .1)

Test Software Version	HyperTerminal		
Frequency	2405 MHz	2440 MHz	2475 MHz
IEEE 802.15.4 ZigBee	3	3	3

Power Parameters of IEEE 802.15.4 ZigBee (Ant .2)

Test Software Version	HyperTerminal		
Frequency	2405 MHz	2440 MHz	2475 MHz
IEEE 802.15.4 ZigBee	3	2	3


Power Parameters of IEEE 802.15.4 ZigBee (Ant .3)

Test Software Version	HyperTerminal		
Frequency	2405 MHz	2440 MHz	2475 MHz
IEEE 802.15.4 ZigBee	3	3	3

3.9. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


3.10. Duty Cycle



Date: 4.JUN.2013 10:52:36


3.11. Test Configurations

3.11.1. AC Power Line Conduction Emissions and Radiation Emissions(30MHz -1 GHz) Test Configuration



Item	Connection	Shield	Length
1	Power Cable	No	1.0m
2	Ant Cable	Yes	0.2m
3	USB Cable	Yes	1.7m
4	Power Cable	No	2.6m
5	Audio cable	Yes	1.1m
6	USB Cable	No	1.8m
7	USB Cable	Yes	1.7m
8	Power Cable	No	1.0m

3.11.2. Radiation Emissions (Above 1GHz) Test Configuration



Item	Connection	Shield	Length(m)
1	Power Cable	No	1.0m
2	Ant Cable	Yes	0.2m
3	USB Cable	Yes	1.7m
4	Power Cable	No	2.6m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For a Low-power Radio-frequency Device which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	48%
Test Engineer	Hank Yang	Phase	Line
Configuration	Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.30834	27.53	-22.49	50.02	27.18	0.15	0.20	LINE	AVERAGE
2	0.30834	32.49	-27.53	60.02	32.14	0.15	0.20	LINE	QP
3 β	0.69110	47.56	-8.44	56.00	47.20	0.16	0.20	LINE	QP
4 β	0.69110	41.13	-4.87	46.00	40.77	0.16	0.20	LINE	AVERAGE
5	0.91843	29.32	-16.68	46.00	28.96	0.17	0.19	LINE	AVERAGE
6	0.91843	34.47	-21.53	56.00	34.11	0.17	0.19	LINE	QP
7	1.374	22.15	-23.85	46.00	21.76	0.18	0.21	LINE	AVERAGE
8	1.374	31.71	-24.29	56.00	31.32	0.18	0.21	LINE	QP
9	2.946	32.90	-23.10	56.00	32.45	0.20	0.25	LINE	QP
10	2.946	27.93	-18.07	46.00	27.48	0.20	0.25	LINE	AVERAGE
11	3.759	30.91	-25.09	56.00	30.40	0.22	0.29	LINE	QP
12	3.759	25.99	-20.01	46.00	25.48	0.22	0.29	LINE	AVERAGE

Temperature	24°C	Humidity	48%
Test Engineer	Hank Yang	Phase	Neutral
Configuration	Mode 1		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.30998	26.60	-33.37	59.97	26.32	0.08	0.20	NEUTRAL	QP
2	0.30998	18.61	-31.36	49.97	18.33	0.08	0.20	NEUTRAL	AVERAGE
3	0.69357	41.25	-14.76	56.00	40.96	0.09	0.20	NEUTRAL	QP
4	0.69357	32.16	-13.85	46.00	31.87	0.09	0.20	NEUTRAL	AVERAGE
5	1.388	14.23	-31.77	46.00	13.92	0.10	0.21	NEUTRAL	AVERAGE
6	1.388	25.58	-30.42	56.00	25.27	0.10	0.21	NEUTRAL	QP
7	2.055	22.12	-33.88	56.00	21.78	0.11	0.23	NEUTRAL	QP
8	2.055	10.49	-35.51	46.00	10.15	0.11	0.23	NEUTRAL	AVERAGE
9	2.854	24.72	-31.28	56.00	24.35	0.12	0.25	NEUTRAL	QP
10	2.854	15.35	-30.65	46.00	14.98	0.12	0.25	NEUTRAL	AVERAGE
11	7.290	11.77	-38.23	50.00	11.28	0.19	0.30	NEUTRAL	AVERAGE
12	7.290	19.64	-40.36	60.00	19.15	0.19	0.30	NEUTRAL	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	802.15.4 Zigbee
Test Date	Jun. 04, 2013		

Configuration IEEE 802.15.4 Zigbee (Ant .1)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
11	2405 MHz	17.23	30.00	Complies
18	2440 MHz	16.53	30.00	Complies
25	2475 MHz	15.84	30.00	Complies

Configuration IEEE 802.15.4 Zigbee (Ant .2)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
11	2405 MHz	17.23	30.00	Complies
18	2440 MHz	5.29	30.00	Complies
25	2475 MHz	15.84	30.00	Complies

Configuration IEEE 802.15.4 Zigbee (Ant .3)

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
11	2405 MHz	17.23	30.00	Complies
18	2440 MHz	16.53	30.00	Complies
25	2475 MHz	15.84	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	5-30 % greater than the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03 section 10.2 Method PKPSD (peak PSD) & KDB 662911 D01 v01r02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add $10 \log(\text{NANT})$ dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	802.15.4 Zigbee

Configuration IEEE 802.15.4 Zigbee (Ant .1)

Frequency	Power Density (dBm/3kHz)	Single Port Limit (dBm/3kHz)	Result
2405 MHz	4.03	8.00	Complies
2440 MHz	2.63	8.00	Complies
2475 MHz	1.93	8.00	Complies

Configuration IEEE 802.15.4 Zigbee (Ant .2)

Frequency	Power Density (dBm/3kHz)	Single Port Limit (dBm/3kHz)	Result
2405 MHz	4.03	8.00	Complies
2440 MHz	-7.83	8.00	Complies
2475 MHz	1.93	8.00	Complies


Configuration IEEE 802.15.4 Zigbee (Ant .3)

Frequency	Power Density (dBm/3kHz)	Single Port Limit (dBm/3kHz)	Result
2405 MHz	4.03	8.00	Complies
2440 MHz	2.63	8.00	Complies
2475 MHz	1.93	8.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

Power Density Plot on Configuration 802.15.4 Zigbee / Ant.1 / 2405 MHz




Date: 4.JUN.2013 11:57:06

Power Density Plot on Configuration 802.15.4 Zigbee / Ant.2 / 2405 MHz



Date: 4.JUN.2013 11:57:06

Power Density Plot on Configuration 802.15.4 Zigbee / Ant.3 / 2405 MHz



Date: 4.JUN.2013 11:57:06

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v01r02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	62%
Test Engineer	Serway Li	Configurations	802.15.4 Zigbee

Configuration 802.15.4 Zigbee (Ant. 1)

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
11	2405 MHz	1.58	2.32	500.00	Complies
18	2440 MHz	1.62	2.38	500.00	Complies
25	2475 MHz	1.81	2.44	500.00	Complies

Configuration 802.15.4 Zigbee (Ant. 2)

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
11	2405 MHz	1.58	2.32	500.00	Complies
18	2440 MHz	1.61	2.38	500.00	Complies
25	2475 MHz	1.81	2.44	500.00	Complies


Configuration 802.15.4 Zigbee (Ant. 3)

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
11	2405 MHz	1.58	2.32	500.00	Complies
18	2440 MHz	1.62	2.38	500.00	Complies
25	2475 MHz	1.81	2.44	500.00	Complies

Note: All the test values were listed in the report.


For plots, only the channel with maximum results was shown.

6 dB Bandwidth Plot on Configuration 802.15.4 Zigbee / Ant. 1 / 2405 MHz




Date: 4.JUN.2013 10:37:02

6 dB Bandwidth Plot on Configuration 802.15.4 Zigbee / Ant. 2 / 2405 MHz



Date: 4.JUN.2013 10:37:02

6 dB Bandwidth Plot on Configuration 802.15.4 Zigbee / Ant. 3 / 2405 MHz



Date: 4.JUN.2013 10:37:02

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 1GHz



For radiated emissions above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	Normal Link
Test Date	May 17, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	Mode 1

Horizontal



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	30.00	32.17	40.00	-7.83	40.60	0.61	18.76	27.80	QP	100	187 VERTICAL
2	95.96	29.83	43.50	-13.67	46.07	1.19	10.19	27.62	Peak	400	0 VERTICAL
3	144.46	35.11	43.50	-8.39	48.95	1.42	12.12	27.38	Peak	400	0 VERTICAL
4	165.80	31.48	43.50	-12.02	44.83	1.45	12.47	27.27	Peak	400	0 VERTICAL
5	540.22	36.35	46.00	-9.65	43.61	2.76	18.08	28.10	Peak	400	0 VERTICAL
6	564.47	37.51	46.00	-8.49	44.46	2.79	18.36	28.10	Peak	400	0 VERTICAL
7	688.63	33.56	46.00	-12.44	39.45	3.07	19.05	28.01	Peak	400	0 VERTICAL

Vertical



	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg
1	30.00	35.27	40.00	-4.73	43.70	0.61	18.76	27.80	Peak	100	0 HORIZONTAL
2	143.49	31.82	43.50	-11.68	45.61	1.42	12.17	27.38	Peak	100	0 HORIZONTAL
3	336.52	34.47	46.00	-11.53	45.18	2.08	14.36	27.15	Peak	100	0 HORIZONTAL
4	589.69	36.93	46.00	-9.07	43.58	2.80	18.65	28.10	Peak	100	0 HORIZONTAL
5	600.36	37.27	46.00	-8.73	43.79	2.81	18.77	28.10	Peak	100	0 HORIZONTAL
6	635.28	36.66	46.00	-9.34	42.90	2.94	18.88	28.06	Peak	100	0 HORIZONTAL
7	648.86	35.16	46.00	-10.84	41.29	2.99	18.93	28.05	Peak	100	0 HORIZONTAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 11 / Ant. 1
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4810.91	45.55	54.00	-8.45	41.54	5.85	33.36	35.20	Average	126	11	HORIZONTAL
2	4810.96	55.52	74.00	-18.48	51.51	5.85	33.36	35.20	Peak	126	11	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4808.93	59.43	74.00	-14.57	55.42	5.85	33.36	35.20	Peak	128	326	VERTICAL
2	4808.98	49.79	54.00	-4.21	45.78	5.85	33.36	35.20	Average	128	326	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 18 / Ant. 1
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4878.90	55.80	74.00	-18.20	51.60	5.92	33.48	35.20	Peak	121	234	HORIZONTAL
2	4878.95	46.11	54.00	-7.89	41.91	5.92	33.48	35.20	Average	121	234	HORIZONTAL
3	7318.49	51.13	74.00	-22.87	42.91	7.14	36.51	35.43	Peak	100	213	HORIZONTAL
4	7318.54	38.63	54.00	-15.37	30.41	7.14	36.51	35.43	Average	100	213	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4878.92	57.04	74.00	-16.96	52.84	5.92	33.48	35.20	Peak	124	338	VERTICAL
2	4878.98	47.73	54.00	-6.27	43.53	5.92	33.48	35.20	Average	124	338	VERTICAL
3	7318.30	53.87	74.00	-20.13	45.65	7.14	36.51	35.43	Peak	100	210	VERTICAL
4	7318.55	42.35	54.00	-11.65	34.13	7.14	36.51	35.43	Average	100	210	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 25 / Ant. 1
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4948.96	45.62	54.00	-8.38	41.23	5.98	33.61	35.20	Average	142	223	HORIZONTAL
2	4948.97	55.16	74.00	-18.84	50.77	5.98	33.61	35.20	Peak	142	223	HORIZONTAL
3	7423.39	38.31	54.00	-15.69	29.92	7.19	36.67	35.47	Average	170	215	HORIZONTAL
4	7426.62	50.70	74.00	-23.30	42.31	7.19	36.67	35.47	Peak	170	215	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4948.90	57.32	74.00	-16.68	52.93	5.98	33.61	35.20	Peak	126	116	VERTICAL
2	4948.95	48.25	54.00	-5.75	43.86	5.98	33.61	35.20	Average	126	116	VERTICAL
3	7423.31	42.30	54.00	-11.70	33.91	7.19	36.67	35.47	Average	108	215	VERTICAL
4	7423.57	53.72	74.00	-20.28	45.33	7.19	36.67	35.47	Peak	108	215	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 11 / Ant. 2
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4809.04	49.80	54.00	-4.20	45.79	5.85	33.36	35.20	Average	100	360	HORIZONTAL
2	4809.04	59.20	74.00	-14.80	55.19	5.85	33.36	35.20	Peak	100	360	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4808.92	52.44	54.00	-1.56	48.43	5.85	33.36	35.20	Average	128	279	VERTICAL
2	4808.96	62.83	74.00	-11.17	58.82	5.85	33.36	35.20	Peak	128	279	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 18 / Ant. 2
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4878.76	55.49	74.00	-18.51	51.29	5.92	33.48	35.20	Peak	100	354	HORIZONTAL
2	4879.00	45.55	54.00	-8.45	41.35	5.92	33.48	35.20	Average	100	354	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4878.88	55.42	74.00	-18.58	51.22	5.92	33.48	35.20	Peak	100	278	VERTICAL
2	4879.04	45.79	54.00	-8.21	41.59	5.92	33.48	35.20	Average	100	278	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 25 / Ant. 2
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4950.01	33.23	54.00	-20.77	28.84	5.98	33.61	35.20	Average	100	82	HORIZONTAL
2	4950.01	44.88	74.00	-29.12	40.49	5.98	33.61	35.20	Peak	100	82	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4950.01	28.71	54.00	-25.29	25.26	5.66	32.99	35.20	Average	100	34	VERTICAL
2	4950.01	43.40	74.00	-30.60	39.95	5.66	32.99	35.20	Peak	100	34	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 11 / Ant. 3
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4808.94	55.51	74.00	-18.49	51.50	5.85	33.36	35.20	Peak	129	128 HORIZONTAL
2	4808.97	45.01	54.00	-8.99	41.00	5.85	33.36	35.20	Average	129	128 HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4808.86	57.41	74.00	-16.59	53.40	5.85	33.36	35.20	Peak	100	257 VERTICAL
2	4810.87	47.98	54.00	-6.02	43.97	5.85	33.36	35.20	Average	100	257 VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 18 / Ant. 3
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4878.98	54.68	74.00	-19.32	50.48	5.92	33.48	35.20	Peak	100	125	HORIZONTAL
2	4878.99	44.62	54.00	-9.38	40.42	5.92	33.48	35.20	Average	100	125	HORIZONTAL
3	7318.27	52.45	74.00	-21.55	44.23	7.14	36.51	35.43	Peak	100	212	HORIZONTAL
4	7321.45	39.49	54.00	-14.51	31.27	7.14	36.51	35.43	Average	100	212	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp		A/Pos	T/Pos	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	Pol/Phase
1	4878.98	47.92	54.00	-6.08	43.72	5.92	33.48	35.20	Average	111	255	VERTICAL
2	4880.95	57.23	74.00	-16.77	53.03	5.92	33.48	35.20	Peak	111	255	VERTICAL
3	7318.52	43.51	54.00	-10.49	35.29	7.14	36.51	35.43	Average	100	176	VERTICAL
4	7321.41	54.59	74.00	-19.41	46.37	7.14	36.51	35.43	Peak	100	176	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 25 / Ant. 3
Test Date	May 17, 2013		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	4950.96	43.86	54.00	-10.14	39.47	5.98	33.61	35.20	Average	100	132	HORIZONTAL
2	4951.07	53.81	74.00	-20.19	49.42	5.98	33.61	35.20	Peak	100	132	HORIZONTAL
3	7423.00	51.45	74.00	-22.55	43.06	7.19	36.67	35.47	Peak	103	208	HORIZONTAL
4	7423.17	38.76	54.00	-15.24	30.37	7.19	36.67	35.47	Average	103	208	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	4950.83	56.53	74.00	-17.47	52.14	5.98	33.61	35.20	Peak	100	210	VERTICAL
2	4950.95	47.06	54.00	-6.94	42.67	5.98	33.61	35.20	Average	100	210	VERTICAL
3	7423.21	42.55	54.00	-11.45	34.16	7.19	36.67	35.47	Average	100	176	VERTICAL
4	7423.38	53.84	74.00	-20.16	45.45	7.19	36.67	35.47	Peak	100	176	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

For Radiated band edges Measurement:

- The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around band edges.

For Conducted Out of Band Emission Measurement:

- Test was performed in accordance with KDB 558074 D01 v03 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
- The conducted emission test is performed on each TX port of operating mode without summing or adding $10\log(N)$ since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

For Radiated band edges Measurement:

This test setup layout is the same as that shown in section 4.5.4.

For Conducted Out of Band Emission Measurement:

This test setup layout is the same as that shown in section 4.4.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	23°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 11, 18, 25 / Ant. 1
Test Date	May 17, 2013		

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2373.00	50.38	54.00	-3.62	18.29	4.08	28.01	0.00	Average	100	278 VERTICAL
2	2373.60	59.13	74.00	-14.87	27.04	4.08	28.01	0.00	Peak	100	278 VERTICAL
3	2404.60	116.18			83.98	4.11	28.09	0.00	Peak	100	278 VERTICAL
4	2405.00	111.94			79.74	4.11	28.09	0.00	Average	100	278 VERTICAL

Item 3, 4 are the fundamental frequency at 2405 MHz.

Channel 18

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2343.60	56.83	74.00	-17.17	24.84	4.06	27.93	0.00	Peak	100	148 VERTICAL
2	2344.00	45.61	54.00	-8.39	13.62	4.06	27.93	0.00	Average	100	148 VERTICAL
3	2440.00	111.59			79.28	4.13	28.18	0.00	Average	100	148 VERTICAL
4	2440.40	116.21			83.90	4.13	28.18	0.00	Peak	100	148 VERTICAL
5	2483.50	44.97	54.00	-9.03	12.55	4.16	28.26	0.00	Average	100	148 VERTICAL
6	2483.50	52.41	74.00	-21.59	19.99	4.16	28.26	0.00	Peak	100	148 VERTICAL

Item 3, 4 are the fundamental frequency at 2440 MHz.

Channel 25

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2474.60	114.97			82.55	4.16	28.26	0.00	Peak	100	150 VERTICAL
2	2475.00	110.04			77.62	4.16	28.26	0.00	Average	100	150 VERTICAL
3	2483.50	51.30	54.00	-2.70	18.88	4.16	28.26	0.00	Average	100	150 VERTICAL
4	2483.50	61.93	74.00	-12.07	29.51	4.16	28.26	0.00	Peak	100	150 VERTICAL

Item 1, 2 are the fundamental frequency at 2475 MHz.

Temperature	23°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 11, 18, 25 / Ant. 2
Test Date	May 17, 2013		

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2373.20	53.67	54.00	-0.33	21.58	4.08	28.01	0.00	Average	108	325 VERTICAL
2	2373.60	61.22	74.00	-12.78	29.13	4.08	28.01	0.00	Peak	108	325 VERTICAL
3	2405.00	115.27			83.07	4.11	28.09	0.00	Average	108	325 VERTICAL
4	2405.40	117.55			85.35	4.11	28.09	0.00	Peak	108	325 VERTICAL

Item 3, 4 are the fundamental frequency at 2405 MHz.

Channel 18

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2390.00	44.69	54.00	-9.31	12.55	4.09	28.05	0.00	Average	100	355 VERTICAL
2	2390.00	55.17	74.00	-18.83	23.03	4.09	28.05	0.00	Peak	100	355 VERTICAL
3	2440.00	96.67			64.36	4.13	28.18	0.00	Average	100	355 VERTICAL
4	2440.40	100.65			68.34	4.13	28.18	0.00	Peak	100	355 VERTICAL
5	2483.50	45.27	54.00	-8.73	12.85	4.16	28.26	0.00	Average	100	355 VERTICAL
6	2483.50	54.47	74.00	-19.53	22.05	4.16	28.26	0.00	Peak	100	355 VERTICAL

Item 3, 4 are the fundamental frequency at 2440 MHz.

Channel 25

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamplifier Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2475.00	109.68			77.26	4.16	28.26	0.00	Average	100	300 VERTICAL
2	2475.60	114.18			81.76	4.16	28.26	0.00	Peak	100	300 VERTICAL
3	2483.50	49.75	54.00	-4.25	17.33	4.16	28.26	0.00	Average	100	300 VERTICAL
4	2483.50	62.23	74.00	-11.77	29.81	4.16	28.26	0.00	Peak	100	300 VERTICAL

Item 1, 2 are the fundamental frequency at 2475 MHz.

Temperature	23°C	Humidity	58%
Test Engineer	Benson Peng	Configurations	802.15.4 Zigbee CH 11, 18, 25 / Ant. 3
Test Date	May 17, 2013		

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2372.40	60.13	74.00	-13.87	28.04	4.08	28.01	0.00	Peak	100	194 VERTICAL
2	2372.80	53.37	54.00	-0.63	21.28	4.08	28.01	0.00	Average	100	194 VERTICAL
3	2404.40	117.57			85.37	4.11	28.09	0.00	Peak	100	194 VERTICAL
4	2405.00	113.51			81.31	4.11	28.09	0.00	Average	100	194 VERTICAL

Item 3, 4 are the fundamental frequency at 2405 MHz.

Channel 18

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2343.60	55.87	74.00	-18.13	23.88	4.06	27.93	0.00	Peak	100	195 VERTICAL
2	2344.00	45.64	54.00	-8.36	13.65	4.06	27.93	0.00	Average	100	195 VERTICAL
3	2439.60	115.47			83.16	4.13	28.18	0.00	Peak	100	195 VERTICAL
4	2440.00	110.92			78.61	4.13	28.18	0.00	Average	100	195 VERTICAL
5	2483.50	45.02	54.00	-8.98	12.60	4.16	28.26	0.00	Average	100	195 VERTICAL
6	2483.50	55.94	74.00	-18.06	23.52	4.16	28.26	0.00	Peak	100	195 VERTICAL

Item 3, 4 are the fundamental frequency at 2440 MHz.


Channel 25

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	2474.43	113.54			81.12	4.16	28.26	0.00	Peak	100	331 VERTICAL
2	2475.00	109.22			76.80	4.16	28.26	0.00	Average	100	331 VERTICAL
3	2483.50	51.54	54.00	-2.46	19.12	4.16	28.26	0.00	Average	100	331 VERTICAL
4	2483.50	62.09	74.00	-11.91	29.67	4.16	28.26	0.00	Peak	100	331 VERTICAL

Item 1, 2 are the fundamental frequency at 2475 MHz.


For Emission not in Restricted Band

Plot on Configuration 802.15.4 Zigbee / Ant .1 / Reference Level




Date: 18.MAY.2013 01:03:59

Plot on Configuration 802.15.4 Zigbee / Ant .1 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 18.MAY.2013 01:04:55

Plot on Configuration 802.15.4 Zigbee / Ant .1 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 18.MAY.2013 01:05:24

Plot on Configuration 802.15.4 Zigbee / Ant .1 / CH 25 / 30MHz~2400MHz (down 30dBc)




Date: 18.MAY.2013 01:07:47

Plot on Configuration 802.15.4 Zigbee / Ant .1 / CH 25 / 2500MHz~26500MHz (down 30dBc)




Date: 18.MAY.2013 01:07:27

Plot on Configuration 802.15.4 Zigbee / Ant .2 / Reference Level




Date: 31.MAY.2013 18:49:34

Plot on Configuration 802.15.4 Zigbee / Ant .2 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 31.MAY.2013 18:50:31

Plot on Configuration 802.15.4 Zigbee / Ant .2 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 31.MAY.2013 18:51:44

Plot on Configuration 802.15.4 Zigbee / Ant .2 / CH 25 / 30MHz~2400MHz (down 30dBc)




Date: 31.MAY.2013 18:52:58

Plot on Configuration 802.15.4 Zigbee / Ant .2 / CH 25 / 2500MHz~26500MHz (down 30dBc)




Date: 31.MAY.2013 18:53:48

Plot on Configuration 802.15.4 Zigbee / Ant .3 / Reference Level




Date: 18.MAY.2013 01:16:34

Plot on Configuration 802.15.4 Zigbee / Ant .3 / CH 11 / 30MHz~2400MHz (down 30dBc)




Date: 18.MAY.2013 01:17:04

Plot on Configuration 802.15.4 Zigbee / Ant .3 / CH 11 / 2500MHz~26500MHz (down 30dBc)




Date: 18.MAY.2013 01:17:29

Plot on Configuration 802.15.4 Zigbee / Ant .3 / CH 25 / 30MHz~2400MHz (down 30dBc)



Date: 18.MAY.2013 01:18:51

Plot on Configuration 802.15.4 Zigbee / Ant .3 / CH 25 / 2500MHz~26500MHz (down 30dBc)



Date: 18.MAY.2013 01:18:32

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 04, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Apr. 15, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz - 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

*Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085