RADIO FREQUENCY EXPOSURE

LIMIT

According to §15.247(i) and §15.407(f), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b) of this chapter.

EUT Specification

EUT	AC750W
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.15GHz ~ 5.25GHz ☐ WLAN: 5.25GHz ~ 5.35GHz ☐ WLAN: 5.47GHz ~ 5.725GHz ☒ WLAN: 5.725GHz ~ 5.85GHz ☐ Others
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm^2) ☒ General Population/Uncontrolled exposure (S=1mW/cm^2)

Antenna diversity	☐ Single antenna
	☒ Multiple antennas
	   ☐ Tx diversity
	   ☐ Rx diversity
	   ☒ Tx/Rx diversity

Max. output power	2.412-2.462GHz IEEE 802.11b mode: 23.45 dBm IEEE 802.11g mode: 23.24 dBm draft 802.11n Standard-20 MHz Channel mode: 22.39 dBm draft 802.11n Wide-40 MHz Channel mode: 22.01 dBm 5.725-5.85GHz: 802.11a mode: 21.13 dBm 802.11an 20MHz mode: 20.31 dBm 802.11an 40MHz mode: 20.41 dBm
Antenna gain (Max)	Dipole antennas for 2.4GHz Gain 7.0 dBi and Dipole antennas for 5 GHz Gain 7.0 dBi
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A

Remark:

1. *The maximum output power is* <u>*23.45dBm (221.31mW) at 2412MHz (with 5.012 numeric antenna gain.); 21.13dBm (129.72mW) at 5785MHz (with 5.012 numeric antenna gain.)*</u>
2. *DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.*
3. *For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm2 even if the calculation indicates that the power density would be larger.*
4. *All two antennas are completely uncorrelated with each other.*

TEST RESULTS

No non-compliance noted.

Calculation

Given $E = \dfrac{\sqrt{30 \times P \times G}}{d}$ & $S = \dfrac{E^2}{3770}$

Where *E = Field strength in Volts / meter*
P = Power in Watts
G = Numeric antenna gain
d = Distance in meters
S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and

d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \textbf{\textit{Equation 1}}$$

Where *d = Distance in cm*
P = Power in mW
G = Numeric antenna gain
S = Power density in mW / cm²

Maximum Permissible Exposure

Substituting the MPE safe distance using d = 20 cm into Equation 1:

Yields

$$S = 0.000199 \times P \times G$$

Where *P = Power in mW*
G = Numeric antenna gain
S = Power density in mW / cm²

Modulation Mode	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm2)	Limit (mW/cm2)
802.11b	2412-2462	23.45	7.0	20	0.2207	1
802.11g		23.24	7.0	20	0.2103	1
802.11 n(20MHz)		22.39	7.0	20	0.1729	1
802.11 n(40MHz)		22.01	7.0	20	0.1584	1
802.11a	5725-5850	21.13	7.0	20	0.1294	1
802.11 an(20MHz)		20.31	7.0	20	0.1071	1
802.11 an(40MHz)		20.41	7.0	20	0.1096	1

Note:
Both of the WLAN 2.4G&5.0G can transmit simultaneously, the formula of calculated the MPE is:
CPD1 / LPD1 + CPD2 / LPD2 + ……etc. < 1
CPD = Calculation power density
LPD = Limit of power density

WLAN 2.4G+ WLAN 5G=0.2207+0.1294=0.3501

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.)