



MPE Report

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance

FCC Part 2 §2.1091

1. Evaluation method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

2. Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

3. Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density



P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the maximum gain of the used antenna is 5.0dBi for 2.4GWLAN and 5GWLAN, the RF power density can be obtained.

4. Estimation Result

4.1 Conducted Power Results

2.4GHz WIFI

Antenna	Mode	Frequency(MHz)	Average Conducted Output Power (dBm)
Antenna 1	IEEE 802.11b	2412	21.56
		2437	20.94
		2462	20.14
Antenna 2		2412	19.92
		2437	19.24
		2462	18.60
Antenna 1	IEEE 802.11g	2412	16.54
		2437	15.95
		2462	15.69
Antenna 2		2412	19.43
		2437	18.67
		2462	18.02
Antenna 1	IEEE 802.11n HT20	2412	16.88
		2437	16.19
		2462	15.39
Antenna 2		2412	15.25
		2437	14.47
		2462	13.92
Antenna 1	IEEE 802.11n HT40	2422	16.09
		2437	15.65
		2452	15.22
Antenna 2		2422	14.48
		2437	14.02
		2452	15.39

**Compliance Certification Services (Shenzhen) Inc.**

Report No: C160415Z12-RP1_MPE

FCC ID: XPF-REG10-UTT

Date of Issue: May 31, 2016

5GHz WIFI

Antenna	Mode	Frequency(MHz)	Average Conducted Output Power (dBm)
Antenna 3	IEEE 802.11a	5745	17.26
		5785	16.94
		5825	16.58
Antenna 4		5745	15.55
		5785	13.98
		5825	13.41
Antenna 3	IEEE 802.11n HT20	5745	16.09
		5785	16.87
		5825	16.41
Antenna 4		5745	14.37
		5785	13.80
		5825	13.31
Antenna 3	IEEE 802.11n HT40	5755	17.15
		5795	16.82
Antenna 4		5755	14.26
		5795	13.71
Antenna 3	IEEE 802.11ac 80	5775	17.20
Antenna 4		5775	14.37

4.2 Manufacturing tolerance**2.4GHz WIFI**

IEEE 802.11 b (Average)						
Frequency (MHz)	Antenna 1			Antenna 2		
	2412	2437	2462	2412	2437	2462
Target (dBm)	21.0	20.0	20.0	19.0	19.0	18.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0

IEEE 802.11 g (Average)						
Frequency (MHz)	Antenna 1			Antenna 2		
	2412	2437	2462	2412	2437	2462
Target (dBm)	16.0	15.0	15.0	19.0	18.0	18.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0

IEEE 802.11 n HT 20 (Average)						
Frequency (MHz)	Antenna 1			Antenna 2		
	2412	2437	2462	2412	2437	2462
Target (dBm)	16.0	16.0	15.0	15.0	14.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0



IEEE 802.11 n HT 40 (Average)						
Frequency (MHz)	Antenna 1			Antenna 2		
	2412	2437	2462	2412	2437	2462
Target (dBm)	16.0	15.0	15.0	14.0	14.0	14.0
Tolerance \pm (dB)	1.0	1.0	1.0	1.0	1.0	1.0

5GHz WIFI

IEEE 802.11 a (Average)						
Frequency (MHz)	Antenna 3			Antenna 4		
	5745	5785	5825	5745	5785	5825
Target (dBm)	17.0	16.0	16.0	15.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0	1.0	1.0	1.0

IEEE 802.11n HT20 (Average)						
Frequency (MHz)	Antenna 3			Antenna 4		
	5745	5785	5825	5745	5785	5825
Target (dBm)	16.0	16.0	16.0	14.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0	1.0	1.0	1.0

IEEE 802.11n HT40 (Average)						
Frequency (MHz)	Antenna 3			Antenna 4		
	5755	---	5795	5755	---	5795
Target (dBm)	17.0		16.0	14.0		13.0
Tolerance \pm (dB)	1.0	1.0	1.0	1.0	1.0	1.0

IEEE 802.11ac 80 (Average)						
Frequency (MHz)	Antenna 3			Antenna 4		
	5775	---	---	5775	---	---
Target (dBm)	17.0			14.0		
Tolerance \pm (dB)	1.0	1.0	1.0	1.0	1.0	1.0

4.3 Measurement Results

**4.3.1 Standalone MPE****2.4GWLAN****Antenna 1**

Mode	Output power (Including tune-up tolerance)		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 b	22.00	158.4893	5.0	3.1623	100%	0.0998	1.000
IEEE 802.11 g	17.00	50.1187	5.0	3.1623	100%	0.0315	1.000
IEEE 802.11 n HT20	17.00	50.1187	5.0	3.1623	100%	0.0315	1.000
IEEE 802.11 n HT40	17.00	50.1187	5.0	3.1623	100%	0.0315	1.000

Antenna 2

Mode	Output power (Including tune-up tolerance)		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 b	20.00	100.0000	5.0	3.1623	100%	0.0629	1.000
IEEE 802.11 g	20.00	100.0000	5.0	3.1623	100%	0.0629	1.000
IEEE 802.11 n HT20	16.00	39.8107	5.0	3.1623	100%	0.0251	1.000
IEEE 802.11 n HT40	16.00	39.8107	5.0	3.1623	100%	0.0251	1.000

5GWLAN**Antenna 3**

Mode	Output power (Including tune-up tolerance)		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 a	18.00	63.0957	5.0	3.1623	100%	0.0397	1.000
IEEE 802.11 n HT20	17.00	50.1187	5.0	3.1623	100%	0.0315	1.000
IEEE 802.11 n HT40	18.00	63.0957	5.0	3.1623	100%	0.0397	1.000
IEEE 802.11 ac 80	18.00	63.0957	5.0	3.1623	100%	0.0397	1.000

Antenna 4

Mode	Output power (Including tune-up tolerance)		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 a	16.00	39.8107	5.0	3.1623	100%	0.0251	1.000
IEEE 802.11 n HT20	15.00	31.6228	5.0	3.1623	100%	0.0199	1.000
IEEE 802.11 n HT40	15.00	31.6228	5.0	3.1623	100%	0.0199	1.000
IEEE 802.11 ac 80	15.00	31.6228	5.0	3.1623	100%	0.0199	1.000

**4.3.2 Simultaneous transmission MPE**

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

\sum of MPE ratios ≤ 1.0

Antenna 1 and Antenna 2 for 2.4GWLAN

Mode	MPE _{Antenna 1} (mW/cm ²)	MPE _{Antenna 2} (mW/cm ²)	\sum MPE ratios	Limit	Results
IEEE 802.11b	0.0998	0.0629	N/A	1.000	Pass
IEEE 802.11g	0.0315	0.0629	N/A	1.000	Pass
IEEE 802.11n HT20	0.0315	0.0251	0.0566	1.000	Pass
IEEE 802.11n HT40	0.0315	0.0251	0.0566	1.000	Pass

Antenna 3 and Antenna 4 for 5GWLAN

Mode	MPE _{Antenna 3} (mW/cm ²)	MPE _{Antenna 4} (mW/cm ²)	\sum MPE ratios	Limit	Results
IEEE 802.11n HT20	0.0315	0.0199	0.0514	1.000	Pass
IEEE 802.11n HT40	0.0397	0.0199	0.0596	1.000	Pass
IEEE 802.11a	0.0397	0.0251	N/A	1.000	Pass
IEEE 802.11ac 80	0.0397	0.0199	0.0596	1.000	Pass

Maximum Simultaneous transmission MPE Ratio for 2.4GWLAN and 5GWLAN

Maximum MPE ratio _{2.4GWLAN}	Maximum MPE ratio _{5GWLAN}	\sum MPE ratios	Limit	Results
0.0998	0.0596	0.1594	1.000	Pass

Note: The estimation distance is 20cm

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.