

**InterLab®**

## RF Exposure and Maximum ERP/EIRP Assessment

For

**LARA-R203 LTE Single Mode**

**FCC ID: XPY1DIQN3NN**

**IC: 8595A-1DIQN3NN**

**Assessment Reference:** MDE\_UBLOX\_1712\_MPEa\_rev1

**Test Laboratory:**

7layers GmbH  
Borsigstrasse 11  
40880 Ratingen  
Germany



Deutsche  
Akkreditierungsstelle  
D-PL-12140-01-00

**Note:**

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the test laboratory.

**7layers GmbH**

Borsigstraße 11  
40880 Ratingen, Germany  
T +49 (0) 2102 749 0  
F +49 (0) 2102 749 350

Geschäftsführer/  
Managing Directors:  
Frank Spiller  
Bernhard Retka  
Alexandre Norré-Oudard

Registergericht/registered:  
Düsseldorf HRB 75554  
USt-Id.-Nr./VAT-No. DE203159652  
Steuer-Nr./TAX-No. 147/5869/0385

a Bureau Veritas  
Group Company  
[www.7layers.com](http://www.7layers.com)

## Table of Contents

<b>0</b>	<b>Summary</b>	<b>3</b>
0.1	Technical Report Summary	3
<b>1</b>	<b>Administrative Data</b>	<b>4</b>
1.1	Testing Laboratory	4
1.2	Project Data	4
1.3	Applicant Data	4
1.4	Manufacturer Data	4
<b>2</b>	<b>Test object Data</b>	<b>5</b>
2.1	General EUT Description	5
2.2	EUT Main components	5
2.3	Ancillary Equipment	5
2.4	Auxiliary Equipment	5
<b>3</b>	<b>Evaluation Results</b>	<b>6</b>
3.1	Maximum ERP / EIRP	6
3.2	RF Exposure Evaluation for Module	7
3.3	RF Exposure Evaluation for multiple transmitters in co-location	9
3.4	Co-Location Considerations	9
3.5	Assumptions	9

## 0 Summary

### 0.1 Technical Report Summary

#### Type of Report

RF Exposure and Maximum ERP/EIRP Assessment for a LTE radio module. Including RF Exposure for use with co-located radios on generic host device.

#### Applicable FCC and ISSED Rules

##### For RF Exposure:

OET Bulletin 65 Edition 97-01 August 1997

FCC 47 CFR §1.1307

FCC 47 CFR §1.1310

RSS-102 Issue 5 – March 2015

##### For Maximum ERP/EIRP:

FCC 47 CFR §22.913

IC SRSP-503 Issue 7, September 2008

FCC 47 CFR §24.232

IC SRSP-510 Issue 5, February 2009

FCC 47 CFR §27.50(d)

RSS-139, Issue 2 / SRSP-513

Report version control			
Version	Release date	Changes	Version validity
001	03.06.2017	Initial version	Not valid
Rev1	28.07.2017	MPE calculation updated	Valid

Reviewer:



Responsible  
for Report:



## 1 Administrative Data

### 1.1 Testing Laboratory

Company Name: 7Layers GmbH

Address Borsigstr. 11  
40880 Ratingen  
Germany

This facility has been fully described in a report submitted to the FCC and accepted under the registration number 96716.

The test facility is also accredited by the following accreditation organisation:  
Laboratory accreditation no.: DAkkS D-PL-12140-01-01

Responsible for Accreditation Scope: Dipl.-Ing. Bernhard Retka  
Dipl.-Ing. Robert Machulec  
Dipl.-Ing. Andreas Petz  
Dipl.-Ing. Marco Kullik

Report Template Version: 2016-08-30

### 1.2 Project Data

Responsible for assessment and report: Mr. Andreas Tübel

Date of Report: 2017-07-28

### 1.3 Applicant Data

Company Name: u-blox AG

Address: Zürcherstrasse 68,  
CH-8800 Thalwil  
Switzerland

Contact Person: Giulio Comar

### 1.4 Manufacturer Data

Company Name: please see applicant data

Address:

Contact Person:

## 2 Test object Data

### 2.1 General EUT Description

<b>Equipment under Test</b>	LTE Single Mode
<b>Type Designation:</b>	LARA-R203
<b>Kind of Device:</b>	LTE Single Mode
<b>LTE CAT</b>	1
<b>FCC ID:</b>	XPY1DIQN3NN
<b>IC Number:</b>	8595A-1DIQN3NN

#### General product description:

The EUT is Cellular radio module supporting LTE

### 2.2 EUT Main components

#### Type, S/N, Short Descriptions etc. used in this Test Report

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status
EUT A (Code: DE1015055ia04)	LTE Module	LARA-R203	356935080016147	2730A2	30.34
Remark: EUT A is equipped with a temporary antenna connector. The Module is not sold with a predefined antenna.					

NOTE: The short description is used to simplify the identification of the EUT in this test report.

### 2.3 Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	HW Status	SW Status	Serial no.	FCC ID
AE 1	AC/DC converter	UUX324-1215	-	-	G05-0122268	-
AE 2	Evaluation test board	EVb-WL3	NO_EVk_CS_191A00	-	-	-

### 2.4 Auxiliary Equipment

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial no.	HW Status	SW Status	FCC ID
N/A						-

### 3 Evaluation Results

#### 3.1 Maximum ERP / EIRP

Standard	Frequency Band
FCC 47 CFR §22.913 IC RSS-132, Issue 3	(FDD5 WCDMA/HSUPA/HSDPA/LTE)
FCC 47 CFR §24.232 IC RSS-133 Issue 6	(FDD2 WCDMA/HSUPA/HSDPA/LTE)
FCC 47 CFR §27.50(d) RSS-139, Issue 2 / SRSP-513	(FDD4,12 LTE)

##### 3.1.1 Test Limits

For the 850MHz band, FCC §22.913 states that the maximum ERP of this device shall not exceed 7 Watts. IC SRSP-503 Issue 7, states that this device shall not exceed a maximum EIRP of 11.5 Watts  
For the purposes of this test report, the 7 Watt ERP limit stipulated in FCC §22.913 has been converted to an equivalent EIRP value of 11.5 Watts.

For all other limits, refer to the values stipulated in the corresponding tables.

##### 3.1.2 Test Protocol

Band	Mode	Duty Cycle (%)	Frequency (MHz)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Freq of highest power (MHz)	FCC / IC EIRP limit (mW)	Maximum antenna gain to meet EIRP Limit (dBi)
eFDD 2	LTE	100.0%	1850-1910	22.49	177.4189481	1850.00	2000	10.5
eFDD 4	LTE	100.0%	1710-1755	22.93	196.33603	1710.00	1000	7.1
eFDD12	LTE	100.0%	699.7-715.5	22.37	172.58379	699.00	4921	14.6

##### 3.1.3 Conclusion

All gains in (dBi)	Band	Max gain to be used to comply with EIRP Limits	Max gain to be used to comply with FCC MPE Limits	Max gain to be used to comply with IC MPE Limits	Maximum gain to be compliant with all limits
	eFDD 2	10.5	13.0	9.5	9.5
	eFDD 4	7.1	13.0	9.3	7.1
	eFDD 12	14.6	9.7	6.6	6.6

## 3.2 RF Exposure Evaluation for Module

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310
RSS-102 Issue 5 – March 2015

### 3.2.1 Test limits

As specified in Table 1B of 47 CFR 1.1310 – Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure.

Frequency range (MHz)	Power density (mW/cm <sup>2</sup> )
300 – 1,500	f/1500
1,500 – 100,000	1.0

Limits specified per RSS-102, Issue 5.

Frequency range (MHz)	Power density (W/m <sup>2</sup> )	Power density (mW/cm <sup>2</sup> )
300 – 6000	$0.02619 f^{0.6834}$	$mW/cm^2 = W/m^2 * 0.1$

Equation OET bulletin 65, page 18, edition 97-01: 
$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

Where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna

**MPE Calculation using antenna gain which meets MPE and EIRP Limits for RSS-102, Annex A \*\*Informational only\*\***

Band	Mode	Frequency (MHz)	Maximum Conducted output power (dBm)	Max Cond output power (mW)	FCC MPE Limit (mW/cm <sup>2</sup> )	IC MPE Limit (mW/cm <sup>2</sup> )	Separation distance (cm)	MPE using gain for overall compliance
eFDD 2	LTE	1850.0	24	251.19	1.0000	0.4476	20	0.447617269
eFDD 4	LTE	1710.0	24	251.19	1.0000	0.4242	20	0.254525038
eFDD12	LTE	699.0	24	251.19	0.4660	0.2302	20	0.230163989

### 3.2.2 Test Protocol

Maximum antenna gain to comply with MPE limits for FCC									
Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Equivalent conducted output power (mW)	MPE Limit (mW/cm <sup>2</sup> )	Maximum antenna gain to meet MPE Limit (dBi)	Separation distance (cm)
eFDD 2	LTE	100.0%	1850.0	24	251.19	251.19	1.0000	<b>13.0</b>	20
eFDD 4	LTE	100.0%	1710.0	24	251.19	251.19	1.0000	<b>13.0</b>	20
eFDD12	LTE	100.0%	699.0	24	251.19	251.19	0.4660	<b>9.7</b>	20

\* Conducted output power values bases on "Tune-up" information provided by manufacturer.

Maximum antenna gain to comply with MPE limits for Industry Canada									
Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Maximum Conducted output power (mW)	Equivalent conducted output power (mW)	MPE Limit (mW/cm <sup>2</sup> )	Maximum antenna gain to meet MPE Limit (dBi)	Separation distance (cm)
eFDD 2	LTE	100.0%	1850.0	24.0	251.19	251.19	0.4476	<b>9.5</b>	20
eFDD 4	LTE	100.0%	1710.0	24.0	251.19	251.19	0.4242	<b>9.3</b>	20
eFDD12	LTE	100.0%	699.0	24.0	251.19	251.19	0.2302	<b>6.6</b>	20

\* Conducted output power values bases on "Tune-up" information provided by manufacturer.

### 3.2.3 Conclusion

Band	Max gain for FCC MPE Limits	Max gain for Industry Canada MPE Limits	Maximum gain to be compliant with all limits
eFDD 2	13.0	9.5	<b>9.5</b>
eFDD 4	13.0	9.3	<b>9.3</b>
eFDD12	9.7	6.6	<b>6.6</b>



### 3.3 RF Exposure Evaluation for multiple transmitters in co-location

Standards
OET Bulletin 65 Edition 97-01 August 1997
FCC 47 CFR §1.1307
FCC 47 CFR §1.1310
RSS-102 Issue 5 – March 2015

### 3.4 Co-Location Considerations

The calculation below is used to consider situations in which simultaneous exposure to fields of different frequencies occur. The calculation is performed by the sum of each relative exposure for each equipment according to the following criteria.

$$\sum_{i=1}^N \frac{S_{eqi}}{S_{Lim i}} = \frac{S_{eq1}}{S_{Lim1}} + \frac{S_{eq2}}{S_{Lim2}} + \dots + \frac{S_{eqN}}{S_{LimN}} \leq 1$$

Where:

$S_{eq}$  is the power density of the electromagnetic field at a given distance by a specific transmitter and a defined frequency.

$S_{lin}$  is the MPE limit for the frequency being evaluated.

### 3.5 Assumptions

1. Primary transmitter does not support power reduction for multiple time slots on the uplink.
2. Antenna separation from module to human body is  $\geq 20$ cm.
3. Separation distance between co-located transmitting antennas is 0cm.
4. Hypothetical Bluetooth radio is assumed to have an output power of 9.5dBm and an antenna gain of 4dBi.
5. Hypothetical WLAN radio is assumed to have an output power of 19dBm and an antenna gain of 5dBi.

#### 3.5.1 Test Protocol

The below table is to determine the MPE values using the maximum gain values obtained in section 3.3.4 of this document.

##### OP mode-1 – FOR FCC ONLY

Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Equivalent conducted output power (mW)	MPE Limit (mW/cm <sup>2</sup> )	MPE Value using Max gain	Separation distance (cm)	Verdict
eFDD 2	LTE	100.0%	1850.0	24	251.19	1.0000	<b>0.5607</b>	20	Pass
eFDD 4	LTE	100.0%	1710.0	24	251.19	1.0000	<b>0.2563</b>	20	Pass
eFDD12	LTE	100.0%	699.0	24	251.19	0.466	<b>0.4352</b>	20	Pass

\* Conducted output power values bases on "Tune-up" information provided by manufacturer.

##### OP mode-1 – FOR Industry Canada ONLY

Band	Mode	Duty Cycle	Frequency (MHZ)	Maximum Conducted output power (dBm)	Equivalent conducted output power (mW)	MPE Limit (mW/cm <sup>2</sup> )	MPE Value using Max gain	Separation distance (cm)	Verdict
eFDD 2	LTE	100.0%	1850.0	24	251.19	0.4476	<b>0.3969</b>	20	PASS
eFDD 4	LTE	100.0%	1710.0	24	251.19	0.4242	<b>0.3791</b>	20	PASS
eFDD12	LTE	100.0%	699.0	24	251.19	0.2302	<b>0.2036</b>	20	PASS

MPE Values for the generic Bluetooth and WLAN radios operating alone. These values are used to calculate the relative exposure for simultaneous transmission with the primary transmitter.

MPE Calculation for Single Transmitter installed in Generic host for FCC								
Radio type	Duty Cycle	ERP (mW)	ERP Equivalent (mW)	MPE Limit (mW/cm <sup>2</sup> )	Maximum antenna gain	Power density	Separation distance (cm)	Verdict
Bluetooth	64%	8.91	3.72	1.0000	4.0	<b>0.0019</b>	20	Pass
WLAN	100%	79.43	79.43	1.0000	5.0	<b>0.0500</b>	20	Pass

MPE Calculation for Single Transmitter installed in Generic host for Industry Canada								
Radio type	Duty Cycle	ERP (mW)	ERP Equivalent (mW)	MPE Limit (mW/cm <sup>2</sup> )	Maximum antenna gain	Power density	Separation distance (cm)	Verdict
Bluetooth	64%	8.91	3.72	0.54	4.00	<b>0.0019</b>	20.00	Pass
WLAN	100%	79.43	79.43	0.54	5.00	<b>0.0500</b>	20.00	Pass

Below are the relative exposure values for the primary, secondary and combined primary + secondary transmitters for both FCC and Industry Canada limits.

#### OP mode-1

Relative exposure for Primary Transmitter for FCC							
OP-Mode	Mode	Output power	Frequency (MHZ)	$S_{eq}$ (mW/cm <sup>2</sup> )	$S_{lin}$ (mW/cm <sup>2</sup> )	$S_{eq}$ ----- $S_{lin}$	Verdict
eFDD 2	LTE	<b>251.1886</b>	1850.0	<b>0.5607</b>	1.0000	0.5606999	Pass
eFDD 4	LTE	<b>251.1886</b>	1710.0	<b>0.2563</b>	1.0000	0.2562893	Pass
eFDD12	LTE	<b>251.1886</b>	699.0	<b>0.4352</b>	0.4660	0.9339951	Pass

Relative exposure for Primary Transmitter for Industry Canada							
OP-Mode	Mode	Output power	Frequency (MHZ)	$S_{eq}$ (mW/cm <sup>2</sup> )	$S_{lin}$ (mW/cm <sup>2</sup> )	$S_{eq}$ ----- $S_{lin}$	Verdict
eFDD 2	LTE	<b>251.1886</b>	1850.0	<b>0.3969</b>	0.4476	0.8867677	Pass
eFDD 4	LTE	<b>251.1886</b>	1710.0	<b>0.3791</b>	0.4242	0.8936459	Pass
eFDD12	LTE	<b>251.1886</b>	699.0	<b>0.2036</b>	0.2302	0.8844623	Pass

Relative exposure for Secondary transmitter for FCC				
Transmitter	Output power	$S_{eq}$ (mW/cm <sup>2</sup> )	$S_{lin}$ (mW/cm <sup>2</sup> )	$S_{eq}$ ----- $S_{lin}$
Bluetooth	3.72	<b>0.0019</b>	1.0000	0.0019
WLAN	79.43	<b>0.0500</b>	1.0000	0.0500

Relative exposure for Secondary transmitter for Industry Canada				
Transmitter	Output power	$S_{eq}$ (mW/cm <sup>2</sup> )	$S_{lin}$ (mW/cm <sup>2</sup> )	$S_{eq}$ ----- $S_{lin}$
Bluetooth	3.72	<b>0.0019</b>	0.5410	0.003431873
WLAN	79.43	<b>0.0500</b>	0.5410	0.092370053

**Simultaneous exposure of Primary and Secondary transmitter  
installed in generic host device for FCC**

Primary Band	Primary Mode	Transmitter	Frequency (MHZ)	Maximum Seq / Slin	Maximum Spri/Slim_pri + Ssec / Slin_Sec	Compliance Maximum (Spri/Slim_pri) + (Ssec / Slin_Sec) < 1
eFDD 2	LTE	Bluetooth	2441	0.0019	0.6125	Compliant
		WLAN	2412	0.0500		
		LARA-R203	1850.0	0.5607		
eFDD 4	LTE	Bluetooth	2441	0.0019	0.3081	Compliant
		WLAN	2412	0.0500		
		LARA-R203	1710.0	0.2563		
eFDD12	LTE	Bluetooth	2441	0.0019	0.9858	Compliant
		WLAN	2412	0.0500		
		LARA-R203	699.0	0.9340		

**Simultaneous exposure of Primary and Secondary transmitter  
installed in generic host device for Industry Canada**

Primary Band	Primary Mode	Transmitter	Frequency (MHZ)	Maximum Seq / Slin	Maximum Spri/Slim_pri + Ssec / Slin_Sec	Compliance Maximum (Spri/Slim_pri) + (Ssec / Slin_Sec) < 1
eFDD 2	LTE	Bluetooth	2441	0.0034	0.9826	Compliant
		WLAN	2412	0.0924		
		LARA-R203	1850.0	0.8868		
eFDD 4	LTE	Bluetooth	2441	0.0034	0.9894	Compliant
		WLAN	2412	0.0924		
		LARA-r203	1710.0	0.8936		
eFDD12	LTE	Bluetooth	2441	0.0034	0.9803	Compliant
		WLAN	2412	0.0924		
		LARA-R203	699.0	0.8845		

**When operating the primary transmitter simultaneously with a generic Bluetooth and WLAN radio, the following antenna gains can be used with the module LARA-R203 while still complying with the exposure limits.**

Band	dBi (For FCC)	dBi (For Industry Canada)
eFDD 2	10.5	9.0
eFDD 4	7.1	8.8
eFDD 12	9.4	6.1