





### ISO/IEC17025 Accredited Lab.

Report No: FCC1109134-01 File reference No: 2011-12-29

Applicant: Guangzhou Sunday Electronics Co., Ltd.

Product: Wireless Keyboard with Touchpad

Model No: S-KW252TG

Brand Name: SUNDAY

Test Standards: FCC Part 15 Subpart C, Paragraph 15.249

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4&FCC Part 15 Subpart C, Paragraph 15.249 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: Dec 29, 2011

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

# SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

East 5/Block 4, Anhua Industrial Zone, No.8, Tairan Rd. CheGongMiao, FuTian District, Shenzhen, CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1109134-01 Page 2 of 35

Date: 2011-12-29



# **Special Statement:**

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

#### **CNAS-LAB Code: L2292**

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

# FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

# IC- Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.



Report No: 1109134-01

Date: 2011-12-29



# Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	4
1.5	Test Duration.	4
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment.	5
3.0	Technical Details	6
3.1	Summary of Test Results	6
3.2	Test Standards	6
4.0	EUT Modification.	6
5.0	Power Line Conducted Emission Test.	7
5.1	Schematics of the Test.	7
5.2	Test Method and Test Procedure.	7
5.3	Configuration of the EUT	7
5.4	EUT Operating Condition.	8
5.5	Conducted Emission Limit.	8
5.6	Test Result.	9
6.0	Radiated Emission test	9
6.1	Test Method and Test Procedure.	9
6.2	Configuration of the EUT	9
6.3	EUT Operation Condition.	9
6.4	Radiated Emission Limit	10
6.5	Test Result.	11
7.0	Band Edge	19
7.1	Test Method and Test Procedure.	19
7.2	Radiated Test Setup.	19
7.3	Configuration of the EUT.	19
7.4	EUT Operating Condition.	19
7.5	Band Edge Limit.	19
7.6	Band Edge Test Result.	20
8.0	Antenna Requirement.	24
9.0	20dB bandwidth measurement.	25
10.0	FCC ID Label	28
11.0	Photo of Test Setup and EUT View	20

Date: 2011-12-29



#### 1.0 General Details

#### 1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-01

For 3m & 10 m OATS

#### 1.2 Applicant Details

Applicant: Guangzhou Sunday Electronics Co., Ltd.

Address: NO.236-238, Minsheng Road, Lanhe Town, Panyu District, Guangzhou, China

Telephone: 020-8492 8933/8492 8938

Fax: 020-8492 8823

# 1.3 Description of EUT

Product: Wireless Keyboard with Touchpad

Manufacturer: Guangzhou Sunday Electronics Co., Ltd.

Brand Name: SUNDAY
Model Number: S-KW252TG

Additional Model Name S-KW1xxxx,S-KW6xxxx (the "x" means one discretionary character of A/a -

 $\mathbb{Z}/\mathbb{Z}$  or one Arabic number of 0-9)

Additional Trade Name N/A

Rating: DC3.0V, 2 pcs AA batteries

Modulation Type: GFSK

Operation Frequency 2402-2480MHz

Antenna Designation Printed antenna, which is built-in, designed as an indispensable part of the EUT.

PCB printed antenna with Gain 2.0dBi

#### 1.4 Submitted Sample

1 Sample

#### 1.5 Test Duration

2011-12-08 to 2011-12-27

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1109134-01 Page 5 of 35

1.6 Test Uncertainty Conducted Emissions Uncertainty =3.6dB

Date: 2011-12-29

Radiated Emissions Uncertainty =4.7dB

Terry Tang 1.7 Test Engineer

The sample tested by

Print Name: Terry Tang

2.0		Test Equi	pments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2011-04-26	2012-04-25
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2011-04-26	2012-04-25
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2011-04-26	2012-04-25
Ultra Broadband ANT	Schwarebeck	VULB9163	9163/340	2011-04-26	2012-04-25
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2011-04-26	2012-04-25
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2011-04-26	2012-04-25
Power meter	Anritsu	ML2487A	6K00003613	2011-04-26	2012-04-25
Power sensor	Anritsu	MA2491A	32263	2011-04-26	2012-04-25
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2011-04-26	2012-04-25
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2011-04-26	2012-04-25
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2011-04-26	2012-04-25

Page 6 of 35

Report No: 1109134-01

Date: 2011-12-29



#### 3.0 Technical Details

## 3.1 Summary of test results

The EUT has been tested according to the following specifications:

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.207	Conducted Emission Test	N/A	Complies
FCC Part 15 Subpart C Paragraph 15.249(a) & 15.249(b) Limit	Field Strength of Fundamental	PASS	Complies
FCC Part 15, Paragraph 15.209	Radiated Emission Test	PASS	Complies
FCC Part 15 Subpart C Paragraph 15.249(d) Limit	Band Edge Test	PASS	Complies

#### 3.2 Test Standards

FCC Part 15 Subpart C, Paragraph 15.249

### 4.0 EUT Modification


No modification by Shenzhen Timeway Technology Consulting Co.,Ltd

Report No: 1109134-01 Date: 2011-12-29



#### 5. Power Line Conducted Emission Test

#### 5.1 Schematics of the test




**EUT: Equipment Under Test** 

#### 5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

#### Block diagram of Test setup



# 5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

One channels are provided to the EUT

#### A. EUT

Device	Manufacturer	Model	FCC ID
Wireless keyboard	Guangzhou Sunday Electronics Co., Ltd.	S-KW252TG	XQLS-KW252TG
with Touchpad			

#### B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1109134-01 Page 8 of 35

Date: 2011-12-29



# C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

#### 5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207

Eraguanay (MHz)	Class A Lir	nits (dB µ V)	Class B Limits (dB µ V)		
Frequency(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
$5.00 \sim 30.00$	73.0	60.0	60.0	50.0	

Notes:

- 1. \*Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

#### 5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

# Due to DC operation, this test item not applicable

Report No: 1109134-01 Page 9 of 35


Date: 2011-12-29



#### **6** Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 1 GHz was investigated. All readings from 30 MHz to 1 GHz are quasi-peak values with a resolution bandwidth of 120 kHz. All readings are above 1 GHz, peak values with a resolution bandwidth of 1 MHz. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) The antenna polarization: Vertical polarization and Horizontal polarization.

# **Block diagram of Test setup**



- 6.2 Configuration of The EUT

  Same as section 5.3 of this report
- 6.3 EUT Operating Condition
  Same as section 5.4 of this report.

Report No: 1109134-01 Page 10 of 35

Date: 2011-12-29



#### 6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

#### A FCC Part 15 Subpart C Paragraph 15.249(a) Limit

Fundamental Frequency	Field Strength of Fundamental (3m)			Field S	trength of Harmo	onics (3m)
(MHz)	mV/m	dBuV/m		uV/m	dBu	V/m
2400-2483.5	50	94 (Average)	114 (Peak)	500	54 (Average)	74 (Peak)

Note:

- 1. RF Field Strength  $(dBuV) = 20 \log RF \text{ Voltage } (uV)$
- 2.Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
- 3. The emission limit in this paragraph is based on measurement instrumentation employing an average detector.

### B. Frequencies in restricted band are complied to limit on Paragraph 15.209.

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the tighter limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. New batteries were installed in the equipment under test for radiated emission testing.
- 5. All scanning using PK detector. And the final emission level was get using QP detector for frequency range from 30-1000MHz.As to 1G-25G, the final emission level got using PK and AV detector.
- 6. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No: 1109134-01 Page 11 of 35

Date: 2011-12-29



#### 6.5 Test result

#### **Fundamental & Harmonics Radiated Emission Data** $\mathbf{A}$

Product:	Wireless Keyboard with Touchpad	Test Mode:	Low Channel- keep transmitting
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	3.0VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2402	89.3 (PK)	Н	114/94	-4.7
2402	87.6 (PK)	V	114/94	-6.4
4804		H/V	74/54	
7206		H/V	74/54	
9608		H/V	74/54	
12010		H/V	74/54	
14412		H/V	74/54	
16814		H/V	74/54	
19216		H/V	74/54	
21618		H/V	74/54	
24020		H/V	74/54	

Report No: 1109134-01 Page 12 of 35



Product:	Wireless Keyboard with Touchpad	Test Mode:	Middle Channel- keep transmitting
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	3.0VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2448	89.1(PK)	Н	114/94	-4.9
2448	87.4(PK)	V	114/94	-6.6
4896		Н	74/54	
7344		V	74/54	
9792		H/V	74/54	
12240		H/V	74/54	
14688		H/V	74/54	
17136		H/V	74/54	
19584		H/V	74/54	
22032		H/V	74/54	
24480		H/V	74/54	

Report No: 1109134-01 Page 13 of 35

Date: 2011-12-29



Product:	Wireless Keyboard with Touchpad	Test Mode:	High Channel- keep transmitting
Test Item:	Fundamental Radiated Emission Data	Temperature:	25℃
Test Voltage:	3.0VDC	Humidity:	56%
Test Result:	Pass		

Frequency	Emission PK/AV	Horiz /	Limits PK/AV	Margin
(MHz)	(dBuV/m)	Vert	(dBuV/m)	(dB)
2480	89.6(PK)	Н	114/94	-4.4
2480	87.6(PK)	V	114/94	-6.4
4960		H/V	74/54	
7440		H/V	74/54	
9920		H/V	74/54	
12400		H/V	74/54	
14880		H/V	74/54	
17360		H/V	74/54	
19840		H/V	74/54	
22320		H/V	74/54	
24800		H/V	74/54	

Note: (1) PK= Peak, AV= Average

- (2) Emission Level = Reading Level + Antenna Factor + Cable Loss.
- (3)Margin=Emission-Limits
- (4)According to section 15.35(b), the peak limit is 20dB higher than the average limit
- (5) The measured PK value less than the AV limit.


Report No: 1109134-01

Date: 2011-12-29




Please refer to the following test plots for details:

#### Low Channel: Horizontal



#### **Low Channel: Vertical**



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Page 15 of 35

Report No: 1109134-01


Date: 2011-12-29



### **Middle Channel: Horizontal**



#### Middle Channel: Vertical




Report No: 1109134-01


Date: 2011-12-29



### **High Channel: Horizontal**



#### **High Channel: Vertical**



Note: for the radiated emissions from 18-25GHz, it was the floor noise.

Report No: 1109134-01 Page 17 of 35

Date: 2011-12-29



# B. General Radiated Emission Data Radiated Emission In Horizontal (30MHz----1000MHz)


EUT set Condition: Keep Tx transmitting

Mode: Low Channel

**Results:** Pass

681.2

Please refer to following diagram for individual



28.0

Н

46.0

Report No: 1109134-01 Page 18 of 35

Date: 2011-12-29




## Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Tx transmitting

Mode: Low Channel

**Results:** Pass

Please refer to following diagram for individual



Report No: 1109134-01

Date: 2011-12-29




# 7. Band Edge

#### 7.1 Test Method and test Procedure:

- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) Set Spectrum as RBW=VBW=1MHz and Peak detector used
- (3) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (4) The antenna polarization: Vertical polarization and Horizontal polarization.

#### 7. 2 Radiated Test Setup



For the actual test configuration, please refer to the related items – Photos of Testing

## 7.3 Configuration of The EUT

Same as section 5.3 of this report

#### 7.4 EUT Operating Condition

Same as section 5.4 of this report.

#### 7.5 Band Edge Limit

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Remark: low, mid and high channel all have been tested; only worse case is reported.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1109134-01 Page 20 of 35


Date: 2011-12-29



#### 7.6 Test Result

Product:	Wireless Keybo	ard with Touchpad	Test Mode:	Low Channel- keep transmitting
Mode	Keeping	Γransmitting	Test Voltage	DC3V
Temperature	24 0	leg. C,	Humidity	56% RH
Test Result:	F	ass	Detector	PK
2400MHz	PK (dBμV/m)	60.36	Limit	$74(dB\mu V/m)$
2400MITZ	$AV(dB\mu V/m)$	44.32	Lillit	54(dBμV/m)
2390MHz	PK (dBμV/m) 31.99		Limit	74(dBμV/m)
	AV(dBμV/m)			54(dBμV/m)

#### Horizontal



Page 21 of 35


Report No: 1109134-01

Date: 2011-12-29



Product:	Wireless Keybo	ard with Touchpad	Test Mode:	High Channel- keep transmitting
Mode	Keeping	Fransmitting	Test Voltage	DC3V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400MHz	PK (dBμV/m)	57.86	Limit	74(dBμV/m)
2400MHZ	$AV(dB\mu V/m)$	41.45	Limit	54(dBμV/m)
2390MHz	PK (dBμV/m) 32.12		Limit	74(dBμV/m)
	AV(dBμV/m)			54(dBμV/m)

#### Vertical




Report No: 1109134-01 Page 22 of 35

Date: 2011-12-29



Product:	Wireless Keybo	ard with Touchpad	Test Mode:	High Channel- keep transmitting
Mode	Keeping	Γransmitting	Test Voltage	DC3V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2492 5MHz	PK (dBμV/m)	42.98	I imit	74(dBμV/m)
2483.5MHz	AV(dBμV/m)		Limit	54(dBμV/m)

#### Horizontal




Report No: 1109134-01 Page 23 of 35

Date: 2011-12-29



Product:	Wireless Keybo	ard with Touchpad	Test Mode:	High Channel- keep transmitting
Mode	Keeping	Fransmitting	Test Voltage	DC3V
Temperature	24 0	leg. C,	Humidity	56% RH
Test Result:	Pass		Detector	PK
2492 5MH-	PK (dBμV/m)	41.56	T ::4	$74(dB\mu V/m)$
2483.5MHz	$AV(dB\mu V/m)$		Limit	54(dBμV/m)

### Vertical



Report No: 1109134-01 Page 24 of 35

Date: 2011-12-29



# 8.0 Antenna Requirement

## **Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

This product has a PCB permanent antenna, fulfill the requirement of this section.

Test Result: Pass

Page 25 of 35

Report No: 1109134-01



Mode		Wireless Keyboard with Touchpad				Test Mode:		Low Channel- keep transmittin			
		K	Leeping T	ransmittii	ng	Test V	oltage	DC3.0V			
Tempera	ture	24 deg. C, Pass				Humic	Humidity		56%	RH	
Test Res	ult:					De	etector		P	K	
0dB Band	lwidth		1.164	4MHz					-	=	
<b>%</b>	MARKER	1				*RBW 1	.00 kHz	Marker	1 [T1 ]		
<b>*</b> **		22 GHz					.00 kHz			38 dBm	
R	lef -20	dBm		Att 1	0 dB	*SWT 1	.00 ms	2	.4019220	000 GHz	
	-20							ndB [T		00 dB	
									.164000		-
-	-30							Temp 1	[T1 nd]		A
1 PK					1			_		34 dBm	
VIEW	-40				<u> </u>				.401292		
	10					$\cap$		Temp 2	[Tl ndi	98 dBm	
				/	1	\		2	-59. .402456		
-	-50							2	. 1021300	700 GIIZ	
			TA	AMOUNT.			T2				
	-60						W. Way				
	-70							V <sub>V</sub>			
_	-80	اماليان مه دراه	M M					James	<b>\</b>		3DB
ų l		Unitropolitical	•						Monday	Mynulyhu	
	-90										
	-100										
-110	-110										
Ļ	-120										
C	Center	2.402 G	Hz		300	kHz/			Spa	n 3 MHz	

Page 26 of 35

Report No: 1109134-01



Produ	ict:	Wireles	Wireless Keyboard with Touchpad			Test	Test Mode:		Middle Channel- keep transmitting		
Mod	de	I.	Keeping T	ranemitti	na	Test V	oltage			nitting 3.0V	
		Г			ng					S RH	
	Temperature 24 deg. C, Test Result: Pass				Humic	-					
						De	etector			K	
20dB Bar	ndwidth		1.188	BMHz						· <b>-</b>	
<b>8</b>	2.447 Ref -20	904 GHz		Att 1	.0 dB		100 kHz 100 kHz 100 ms		1 [T1 ] -36	.09 dBm	
	-20							ndB [T	1] 20	.00 dB	1
									.188000		<b>7</b>
	30				1			Temp 1	<u>[T1 nd]</u> -55	3] .71 dBm	A
1 PK								2	-55 .447328		
VIEW	40				/ * `			Temp 2			
				ر ا	/					.88 dBm	
	50			~~~~				2	.448516	000 GHz	
	60		7				T2				
			\ \frac{1}{2}					ή,			
	70	N. Alexandria	W					h	mn,		3DB
	11.0 -80	HANGURA MANAGAN							W.		JDB
	100										
	110										
	-120										ļ
	Center	2.448 G	Hz		300	kHz/			Spa	n 3 MHz	

Page 27 of 35

Report No: 1109134-01



Product:	Wireless Keybo	oard with Touchpad	Test Mode:	High Channel- keep transmittin		
Mode	Keeping	Transmitting	Test Voltage	DC3.0V		
Temperature	24	deg. C,	Humidity	56% RH		
Test Result:	-	Pass	Detector	PK		
OdB Bandwidth	1.1	76MHz				
MARKER 2.479 Ref -20	898 GHz	Att 10 dB	*RBW 100 kHz *VBW 100 kHz *SWT 100 ms	Marker 1 [T1 ] -34.82 dBm 2.479898000 GHz		
-20 30		1		ndB [T1] 20.00 dB BW 1.176000000 MHz Temp 1 [T1 ndB] -54.30 dBm	А	
40 50	Т	M. M	T2	2.479322000 GHz Temp 2 [T1 nd8] -54.90 dBm 2.480498000 GHz		
60	7		122			
70	Jank with the wilder			Who was a second	3DB	
1 Mu W				White way		
100						
110 120						
Center	2.48 GHz	300	kHz/	Span 3 MHz		

Report No: 1109134-01 Page 28 of 35

Date: 2011-12-29




#### 10.0 FCC ID Label

# FCC ID: XQLS-KW252TG

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

#### **Mark Location:**



Report No: 1109134-01 Date: 2011-12-29



#### 11.0 Photo of testing

#### 11.1 Conducted test View--

N/A

#### 11.2 Radiated emission test view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 30 of 35

Report No: 1109134-01

Date: 2011-12-29



# Photographs - EUT

# Outside View-Keyboard Part





Page 31 of 35

Report No: 1109134-01



Outside View—Keyboard Part





Page 32 of 35

Report No: 1109134-01



Outside View—Keyboard Part







Report No: 1109134-01 Page 33 of 35



Interior View—Keyboard Part





Page 34 of 35

Date: 2011-12-29

Report No: 1109134-01



Interior View—Keyboard Part






Page 35 of 35


Report No: 1109134-01

Date: 2011-12-29



Interior View—Keyboard Part





-- End of the report--

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.